

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

BOOK 4324

Book C

FIELD NOTES

of the

Dependent Resurvey of the

First Standard Parallel North,

Through Range 11 West, and a Portion of

Range 10 West,

and

the Survey of the

East Boundary and Subdivisional Lines of

Township 5 North, Range 11 West.

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

G. Marvin Litz, Junior Cadastral Engineer,
and

Bert E. Wakeman, Senior Engineering Aid,

General Land Office.

Under special instructions dated October 29, 1941, which provided for the surveys included under Group No. 234, bearing the approval of the Commissioner of the General Land Office under date of November 7, 1941, and assignment instructions dated December 22, 1941 and January 16, 1942.

Survey commenced March 9, 1942.

Survey completed May 2, 1942.

4324

1A

BOOK 4824

INDEX DIAGRAM.

Township 5 North, Range 11 West.

6	57 5	46 4	38 3	31 2	23 1	15
56	56	45	38	30	22	
7	55 8	44 9	37 10	30 11	22 12	15
55	54	44	36	29	21	
18	53 17	43 16	35 15	28 14	20 13	14
52	52	42	35	27	20	
19	51 20	41 21	34 22	26 23	19 24	13
50	49	41	33	26	18	
20	49 29	40 28	33 27	25 26	17 25	12
48	47	39	32	24	16	
21	48 32	40 33	32 34	25 35	17 36	12 31
1	3	4	5	8	9	11

T. 5 N., R. 11 W.

Chains

The resurvey and surveys herein described were executed with Buff solar transit No. 16730 and Gurley solar transit No. 371535.

For description of instruments and equipment used, see the field notes of T. 6 N., R. 11 W., surveyed under this group.

March 8, 1942, in camp in the NW. $\frac{1}{4}$ of sec. 26, T. 6 N., R. 11 W., on the meridian described in the field notes of T. 6 N., R. 11 W., between the hours of 7:30 to 10:30 a.m. and 1:30 to 5 p.m., we make the proper settings on the arcs of the solar attachments and ascertain that the resulting orientation of each instrument, when compared with the meridian established by Polaris observation, has a maximum error of less than 1' 30".

The instruments were tested at frequent intervals and maintained in satisfactory adjustment throughout the survey.

Resurvey of the 1st Stan. Par. N., Thru R. 11 W.

Reestablishment of the survey executed by J.F. Hesse, Deputy Surveyor, in 1908.

Preliminary to the resurvey, the lines of the original survey are retraced and diligent search is made for all original corners. Identified corners of the original survey are restored in their original positions as angle points. New standard $\frac{1}{4}$ sec. and sec. corners are then established on line at 40.00 and 80.00 chs. counting measurement from the east. The retracement data are thoroughly verified and only the true line notes are given herein.

The standard cor. of Ts. 5 N., Rs. 11 and 12 W. is a granite stone, 8x6 ins., 6 ins. above ground, mkd. SC 5N and 6 grooves on N., 11W and 6 grooves on E., 6 grooves on S., and 12W and 6 grooves on W. faces, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

At point for cor.,

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with the old cor. stone buried alongside, for the standard cor. of Ts. 5 N., Rs. 11 and 12 W., with brass cap mkd.

S	C
T5N	
R12W	R11W
S 36	S 31
1942	

rebuild a mound
of stone, 3 ft. base, 2 ft. high, N. of cor.

Thence,

S. 89° 15' E., on a true line, along the S. bdy. of sec. 31.
Over rolling desert land.

- 5.00 Wash, 4 ft. deep, 20 lks. wide, course SW.
- 11.20 Dim desert road, bears N. and S.
- 28.98 The $\frac{1}{4}$ sec. cor. of sec. 1, T. 4 N., R. 12 W.; an iron post 1 in. diam., in a mound of stone, 4 ft. base, 2 ft. high, to top, with brass cap mkd.

$\frac{1}{4}$	S 1
1923	

Resurvey of the 1st Stan. Par. N., Thru R. 11 W.

Chains	
31.30	Wash, 3 ft. deep, 10 lks. wide, course SW.
38.93	<p>At this point, which is 40.00 chs. in departure from the SE. cor. of sec. 31, hereinafter described,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	$\begin{array}{r} \text{SC} \\ \frac{1}{4} \text{ S } 31 \\ \hline 1942 \end{array}$
	<p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
40.00	<p>The standard $\frac{1}{4}$ sec. cor., which is a granite stone, 12x10 ins., 4 ins. above ground, mkd. SC$\frac{1}{4}$ on N. face, with a mound of stone, 3 ft. base, 1$\frac{1}{2}$ ft. high, N. of cor.</p>
	<p>As this cor. no longer serves as the standard $\frac{1}{4}$ sec. cor.,</p> <p>At point for cor.</p>
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, for angle point, with brass cap mkd.</p>
	$\begin{array}{r} \text{AP} \\ \text{T5N R11W} \\ \text{S } 31 \\ \hline 1942 \end{array}$
	<p style="text-align: right;">rebuild mound</p> <p>of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p>Thence,</p> <p>S. 89° 46' E., on a true line, along S. bdy. of sec. 31, with continued measurement.</p>
50.40	Wash, 4 ft. deep, 40 lks. wide, course S.
69.11	<p>The closing cor. of Ts. 4 N., Rs. 11 and 12 W., which is an iron post, 3 ins. diam., in a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, to top, with brass cap mkd.</p>
	$\begin{array}{r} \text{T5N} \\ \text{R12W R11W} \\ \text{S } 36 \text{S } 31 \\ \hline \text{C } \text{C} \\ \text{S } 1 \text{S } 6 \\ \text{R12W } \text{R11W} \\ \text{T4N} \\ 1914 \end{array}$
	<p>Cor. stands under a 4 strand barbed wire fence, bears N.& S.</p>
78.93	<p>Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to rock, and in a mound of stone, 4 ft. base, to top, for standard cor. of secs. 31 and 32, with brass cap mkd.</p>
	$\begin{array}{r} \text{S C} \\ \text{T5N R11W} \\ \text{S } 31 \text{S } 32 \\ \hline 1942 \end{array}$
	<p>Land, rolling desert.</p> <p>Soil, sandy and gravelly, 3rd rate.</p> <p>Timber, paloverde, ironwood and mesquite.</p> <p>Undergrowth, creosote brush and cacti.</p>

Resurvey of the 1st. Stan. Par. N., thru R. 11 W.

Chains.

Thence,

S.89°46'E., on a true line, on the S. bdy. sec. 32.

Over nearly level desert land.

0.81 The standard cor. of secs. 31 and 32, which is a granite stone, 10x6 ins., 4 ins. above ground, mkd. SC on N., 5 grooves on E., and 1 groove on W. faces, with a mound of stone, 3 ft. base, 1½ ft. high N. of cor.

As this cor. no longer serves as the standard cor. of secs. 31 and 32,

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground, with the old cor. stone buried alongside, and in a mound of stone, 2 ft. base to top, for angle point, with brass cap mkd.

AP
T5N R11W
S 32
1942

Thence,

S.89°46'E., on a true line, on the S. bdy. of sec. 32 with continued measurement.

22.70 Desert road, bears N. and S.

27.90 Wash, 5 ft. deep, 30 lks. wide, course S.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard ¼ sec. cor., with brass cap mkd.

S C
¼ S 32
1942

raise a mound
of stone, 3 ft. high, 3 ft. base, N. of cor.

40.58 The standard ¼ sec. cor., which is a stone, 8x6 ins., 4 ins., above ground, mkd. SC ¼ on N. face, with a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

As this cor. no longer serves as the standard ¼ sec. cor.,

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old cor. stone buried alongside, for angle point, with brass cap mkd.

A P
T5N R11W
S 32
1942

rebuild mound
of stone, 3 ft. base, 2 ft. high, N. of cor.

Thence,

S.89°50'E., on a true line, on S. bdy. sec. 32, with continued measurement.

Over rolling desert land.

Resurvey of the 1st. Stan. Par. N., Thru R. 11 W.

Chains	
57.00	Dim desert road, bears SW. and NE.
63.30	Dim desert road, bears N. and S.
68.14	The closing cor. of secs. 5 and 6, T. 4 N., which is an iron post, 2 ins. diam., in a mound of stone, 3 ft. base, 1 ft. high, to top, with brass cap mkd.
	T5N R11W <u>S32 S33</u> C C S 6 S 5 1914
77.41	House, in sec. 29, bears N. 14°53'W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to rock, and in a mound of stone, 4 ft. base to top, for standard cor. of secs. 32 and 33, with brass cap mkd.
	S C T5N R11W <u>S 32 S 33</u> 1942
	Land, nearly level desert. Soil, sandy and gravelly, 3rd. rate... Timber, paloverde and ironwood. Undergrowth, creosote brush and cacti.
	Thence, S.89°50' E., on a true line, on S. bdy. sec. 33 Over nearly level desert land.
0.49	The standard cor. of secs. 32 and 33, which is a quartz stone, 6x4 ins., 4 ins. above ground, mkd. SC on N., 4 grooves on E., and 2 grooves on W. faces, with a scattered mound of stone N. of cor. longer AS this cor. no/serves as the standard cor. of secs. 32 and 33., At point for cor., Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to rock, with the old cor. stone buried alongside, and in a mound of stone, 5 ft. base to top, for angle point, with brass cap mkd.
	A P T5N R11W <u>S 33</u> 1942
	Thence, S.89°46' E., on a true line, on S. bdy. sec. 33, with continued measurement.
10.90	Dim desert road, bears NE. and SW.
18.90	Wash, 4 ft. deep, 1 ch. wide, course SW.
30.50	Dim desert road, bears NE. and SW.

Resurvey of the 1st. Stan. Par. N., thru R. 11 W.

Chains.	
39.50	Dim desert road, bears NW. and SE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S C $\frac{1}{4}$ S 33 1942
	raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
40.32	The standard $\frac{1}{4}$ sec. cor., which is a granite stone, 8x6 ins., 4 ins. above ground, mkd. SC $\frac{1}{4}$ on N. face, with a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
	As this cor. no longer serves as the standard $\frac{1}{4}$ sec. cor.,
	At point for cor.,
	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the old cor. stone buried alongside, for angle point, with brass cap mkd.
	A P T5N R11W S 33 1942
	Thence,
	S. 89° 52' E., on a true line, on S. bdy. of sec. 33, with continued measurement.
45.30	Wash, 4ft. deep, 50 lks. wide, course SW.
58.80	Wash, .10ft. deep, 15 lks. wide, course SW.
60.30	Old road, bears N. and S.
68.06	The closing cor. of secs. 4 and 5, T. 4 N., which is an iron post, 2 ins. diam., in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.
	T5N R11W S33 S34 C C S 5 S 4 1914
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base to top, for standard cor. of secs. 33 and 34, with brass cap mkd.
	S C T5N R11W S 33 S 34 1942
	Land, nearly level. Soil, sandy and gravelly, 3rd. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush and cacti.
	Thence,
	S. 89° 52' E., on a true line, on the S. bdy. sec. 34.
	Over nearly level desert land.

Resurvey of the 1st. Stan. Par. N., Thru R.11W.

Chains

0.16

The standard cor. of secs. 33 and 34, which is a granite stone, 10x6 ins., 4 ins. above ground, mkd. SC. on N., and 3 grooves on E. and W. faces, with a mound of stone, 2ft. base, 1½ft. high N. of cor.

As this cor. no longer serves as the standard cor. of secs. 33 and 34,

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old cor. stone buried alongside, for angle point, with brass cap mkd.

A P
T5N R11W
S 34
1942

from which

Original bearing tree:

A paloverde, partly dead, 12 ins. diam., bears N. 63½° E., 208 lks. dist. Old blaze open, no scribe marks visible.

Rebuild mound of stone, 2½ ft. base, 1½ft. high N. of cor.

Thence,

S. 89° 44' E., on a true line, on S. bdy. sec. 34, with continued measurement.

1.15 Wash, 10 lks. wide, course S.

32.05 Wash, 5 ft. deep, 20 lks. wide, course SW.

39.79 The standard ¼ sec. cor., which is a granite stone, 12x8 ins. 6 ins. above ground, mkd. SC¼ on N. face, with a mound of stone, 2 ft. base, 1½ ft. high, N. of cor..

As this cor. no longer serves as the standard ¼ sec. cor.,

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, with the old cor. stone buried alongside, and in a small mound of stone, for angle point, with brass cap mkd.

A P
T5N R11W
S 34
1942

from which

Original bearing trees:

An ironwood, 6 ins. diam., bears N. 86½° E., 137 lks. dist., mkd. ¼ SC BT

No evidence remains of the NW. bearing tree.

Thence,

S. 89° 52' E., on a true line, on S. bdy. sec. 34, with continued measurement.

Resurvey of the 1st. Stan. Par. N., Thru R. 11 W.

Chains. 40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground and in a mound of stone, 3 ft. base, to top, for standard. 4 sec. cor., with brass cap mkd.</p> <p style="text-align: center;">SC $\frac{1}{4}$ S 34 1942</p>
46.90	Wash, 10.ft. deep 40 lks. wide, course SW.
51.10	Same wash, course W., in bend.
68.16	<p>The closing cor. of secs. 3 and 4, T. 4 N., which is an iron post, 2 ins. diam., 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T5N R11W S34 S35 C C S 4 S 3 1914</p> <p style="text-align: right;">from which</p> <p>Original bearing trees: A paloverde 10 ins. diam., bears S.3½°W., 229 lks. dist. mkd. CC.T4N R11W S4 BT. An ironwood, 10 ins. diam., bears S.61½°E., 137 lks. dist., mkd. CC T4N R11W S3BT.</p>
79.92	<p>The standard cor. of secs. 34 and 35, which is a granite stone, 8x6 ins., 4 ins. above ground, mkd. SC on N., 4 grooves on W. and 2 grooves on E. faces, with a mound of stone, 2½ft. base, 1½ ft. high, N. of cor.</p> <p>As this cor. no longer serves as the standard cor. of secs. 34 and 35,</p> <p>At point for cor.,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the old cor. stone buried alongside, for angle point, with brass cap mkd.</p> <p style="text-align: center;">A P T5N R11W S 34 1942</p> <p style="text-align: right;">rebuild mound of</p> <p>stone, 2½ ft. base, 1½ ft. high, N. of cor.</p> <p>Thence,</p> <p>S. 89° 45' E., on a true line, on S. bdy. sec. 34, with continued measurement.</p>
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for standard cor. of secs. 34 and 35, with brass cap mkd.</p> <p style="text-align: center;">S C T5N R11W S 34 S 35 1942</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 2½ ft. base, 1½ ft. high, N. of cor.</p> <p>Land, nearly level. Soil, sandy and gravelly, 3rd rate. Timber, paloverde and ironwood. Undergrowth, creosote brush and cacti.</p>

Resurvey of the 1st. Stan. 4ar. N., Thru R. 11W.

Chains.	Thence, S. 89° 45' E., on true line, on S. bdy. sec. 35. Over rolling desert land.
15.70	Wash, 8ft. deep, 50 lks. wide, course S.
21.00	Wash, .5 ft. deep, 1 ch. wide, course S.
36.30	Wash, 60 lks. wide, course S.
38.50	Wash, .40 lks. wide, course S.; asc. 25 ft. over W. slope.
39.69	The standard $\frac{1}{4}$ sec. cor., which is a granite stone, 12x6 ins., 6 ins. above ground, mkd. SC. $\frac{1}{4}$ on N. face, with a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor. As this cor. no longer serves as the standard $\frac{1}{4}$ sec. cor., At point for cor., Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with the old cor. stone, buried alongside, and in a mound of stone, 4 ft. base, to top, for angle point, with brass cap mkd. A P T5N R11W S 35 1942
	Thence, N. 89° 24' E., on a true line, on S. bdy. sec. 35, with continued measurement. Over mountainous land, asc. 60 ft. over rocky W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bed rock, and in a mound of stone, 4 ft. base, to top, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd. S C $\frac{1}{4}$ S 35 1942
42.50	Short spur, slopes NW.; desc. 65ft. over NE. slope.
47.15	Wash, 3 ft. deep, 10 lks. wide, course NW.; asc. 115 ft. over W. slope.
58.85	Short spur, slopes N.; asc. along N. slope 140 ft.
67.92	The closing cor. of secs. 2 and 3, T.4 N., which is an iron post, 2 ins. diam., 10 ins. above ground, with brass cap mkd. T5N R11W S35 S36 C C S 3 S 2 1914
	with a mound of stone, 3ft. base, 2ft. high, S. of cor.
75.25	Saddle in spur, slopes SW.; asc. 30 ft. over rocky S. slope.

Resurvey of the 1st.. Stan.. Par. N., Thru R. 11 W.

Chains.

- 79.53 The standard cor. of secs. 35 and 36, which is a granite stone, 10x6 ins., 4 ins. above ground, mkd. SC on N., 1 groove on E., and 5 grooves on W. faces, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.
- As this cor. no longer serves as the standard cor. of secs. 35 and 36,
- At point for cor.,
- Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. to bedrock, with the old cor. stone, buried alongside, and in a mound of stone, 3ft. base to top, for angle point, with brass cap mkd.
- A P
T5N R11W
S 35
S 2
T4N R 11W
1942
- Cor. stands on a short rocky point, slopes S.
- Thence,
- N. 89° 45' E., on a true line, on S. bdy. sec. 35., with continued measurement.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the the ground over a cross (x) mkd. on bed rock, and in a mound of stone, 4 ft. base to top, for standard cor. of secs. 35 and 36, with brass cap mkd.
- SC
T5NR11W
S 35 | S 36
S 2
1942
- Land, mountainous.
Soil, rocky, 4th. rate.
Timber, paloverde and ironwood.
Undergrowth, creosote brush, and cacti.
-
- Thence,
- N. 89° 45' E., on a true line, on S. bdy. sec. 36.
- Over rough mountainous land, desc. along broken S. slope 270 ft.
- 15.25 Short wash, 8 ft. deep, 10 lks. wide, course S.; asc. 20 ft. along rocky S. slope.
- 25.60 Top of ascent, desc. 90 ft. over SE. slope.
- 31.25 Wash, 10 ft. deep, 30 lks. wide, course SW. 3 chs. thence S.; asc. steep NW. slope 160 ft.
- 39.70 The standard $\frac{1}{4}$ sec. cor. which is a stone, 6x6ins., 12 ins. above ground, mkd. SC $\frac{1}{4}$ on N. face, with a mound of stone, 3ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
- As this cor. no longer serves as the standard $\frac{1}{4}$ sec. cor.,

Resurvey of the 1st. Stan. Par. N., Thru R.11W.

Chains.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground over a cross (+) mkd. on bedrock, with the old cor. stone buried alongside, and in a mound of stone, 4 ft. base to top, for angle point, with brass cap mkd.

A P
S 36
1942.

Cor. stands in small side hill drain, course NW.

Thence,

N. 89° 58' E., on a true line, on S. bdy. of sec. 36, with continued measurment.

Asc. 80 ft. over steep broken NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top, for standard 4 sec. cor., with brass cap mkd.

S C
1/4 S 36
1942

43.40 Spur, slopes S.; desc. along rocky NE. slope 290ft.

63.10 Wash, 8 ft. deep, 30 lks. wide, course SE.

64.70 Enter same wash, course E.

67.93 The true point for closing cor. of secs. 1 and 2, T.4 N. The witness cor. for same bears S.0° 01' E., 67 lks. dist.; an iron post, 2 ins. diam., 10 ins. above ground, with brass cap mkd.

T5N
R11W R10W
S 36 | S 31
WC | CC
S 2 | S 1
1914

with a mound of stone, 2ft. high, 3ft. base, S. of cor.

70.30 Leave wash, course SE.

79.22 The standard cor. of Ts. 5 N., Rs. 10 and 11 W., which is a granite stone, 12x10ins., 10 ins. above ground, mkd. SC 5N and 6 grooves on N., 10W and 6 grooves on E., and 11W and 6 grooves on W. faces, with a mound of stone, 3ft. base, 1 ft. high, N. of Cor.

As this cor. no longer serves as the standard cor. of Ts. 5 N., Rs. 10. and 11 W.,

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to rock, with the old cor. stone buried alongside, and in a mound of stone, 5 ft. base, to top, for angle point, with brass cap mkd.

A P
T5N R11W
S 36
1942

Resurvey of the 1st. Stan. Par. N., Thru R. 11 W.

Chains.

Thence,

S. 89° 58' E., on true line, on S. bdy. sec. 36, with continued measurement.

79.72

Set an iron post, 3 ft. long, 3 ins. diam., 14 ins. in the ground, and in a mound of stone, 4 ft. base, to top, for witness standard cor. of Tps. 5 N., Rs. 10 and 11 W., with brass cap mkd.

T5N
R11W R10W
S | C
S 36 | S 31
1942 W C

80.00

The true point for standard cor. of Tps. 5 N., Rs. 10 and 11 W., a point due S. from the cor. of Tps. 5 and 6 N., Rs. 10 and 11 W., falls in a wash, 10 lks. wide, course S.; a place unsuitable for a permanent cor.

Land, mountainous.
Soil, gravelly and rocky, 4th. rate.
Timber, paloverde and ironwood.
Undergrowth, creosote brush, ocotilla and cacti.

Resurvey of the 1st. Stan. Par. N., thru a portion of R. 10 W.

Thence, S. 89° 58' E., on true line, on S. bdy. sec. 31.

Over mountainous land.

4.20

Foot of ascent; asc. 110 ft. over W. slope.

10.40

spur, slopes S.; desc. 100 ft. over E. slope.

15.00

Mine dump, bears N., approximately 12 chs. dist.

16.00

Foot of descent, thence over level desert land.

32.60

Wash, 6 ft. deep, 20 lks. wide, course SW.

37.65

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.

S C
 $\frac{1}{4}$ S 31
1942

raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

39.66

The standard $\frac{1}{4}$ sec. cor., which is a granite stone, 4x6 ins. 8 ins. above ground, mkd. SC $\frac{1}{4}$ on N. face, with a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

As this cor. no longer serves as the standard $\frac{1}{4}$ sec. cor.,

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old cor. stone buried alongside, for angle point, with brass cap mkd.

A P
T5N R10W
S 31
1942

E. Bdy. T. 5 N., R. 11 W.

...

Chains

Land, level desert and mountainous.
Soil, rocky and gravelly, 3rd and 4th. rates.
Timber, paloverde and ironwood.
Undergrowth, creosote brush, ocotilla and cacti.

E. Bdy. T. 5 N., R. 11 W.

From the true point for standard cor. of Tps. 5 N., Rs. 10 and 11 W., (for witness cor. see south. bdy. sec. 36, R. 11 W.)

North, bet. secs. 31 and 36.


Over mountainous land; asc. 390ft. over rocky S. slope.

20.00 Spur, slopes SE.; desc. NE. slope 90 ft.

23.15 Wash, near head, 3 ft. deep, 10 lks. wide, course SE.; asc. 245 ft. over SE. slope.

35.30 Spur, slopes E.; desc. 180 ft. over rocky N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, over a cross (+) mkd. on bedrock, and in a mound of stone, 4 ft. base, to top, for 1/4 sec. cor., with brass cap mkd.




Desc. 90 ft. over NE. slope.

48.70 Wash, near head, 10 ft. deep, 30 lks. wide, course NE.; asc. 310 ft. over rough SE. slope.

65.30 Spur, slopes NE.; desc. steep N. slope 274 ft.

78.10 Wash, 10 ft. deep, 20 lks. wide, course E.; asc. 25 ft. over S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.



Land, mountainous.
Soil, rocky, 4th. rate.
Timber, paloverde and ironwood.
Undergrowth, creosote brush, ocotilla and cacti.

Thence,

North, bet. secs. 25 and 30.

Over rough mountainous land.

4.50 Toe of spur, slopes E.

E. bdy. T. 5 N., R. 11 W.

Chains	
11.00	Wash, near head, 6 ft. deep, 20 lks. wide, course SE.; asc. 590ft. over steep broken S. slope.
26.00	Spur, slopes SE.; desc. 35 ft. over N. slope.
30.00	Wash, near head, 2 ft. deep, 10 lks. wide, course SE.; asc. 100 ft. over S. slope.
34.40	Short spur, slopes E.; desc. 60 ft. along rolling E. slope
39.60	Small wash, course SE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3ft. base, to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	$\frac{1}{4}$ S 25 S 30 1942
40.70	Spur, slopes SE.; desc. steep NE. slope 250 ft.
51.60	Wash, 4ft. deep, 20 lks. wide, course E.; asc. 179 ft. over steep SE. slope.
59.25	Short spur, slopes SE.; thence along E. slope, desc. 25ft.
61.50	Ridge, bears SW. and NE.; desc 195 ft. along NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for cor. of secs. 19, 24, 25 and 30, with brass cap mkd.
	T5N R11W R10W S 24 S 19 S 25 S 30 1942.
	Land, rough mountain. Soil, rocky, 4th. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush and cacti.
	Thence, North, bet. secs. 19 and 24. Over rolling mountain land, desc. 80 ft. over NW. slope.
14.40	Wash, 6 ft. deep, 30 lks. wide, course SW.; asc. 80ft. along E. slope.
18.80	Old road, bears SW. and NE. about 10 chs. to end.
24.30	Mine tunnel, bears N. 79 $\frac{3}{4}$ ° E.
28.71	Mine tunnel, same, bears S. 74 $\frac{3}{4}$ ° E., and a second mine tunnel, bears S. 52 $\frac{1}{4}$ ° E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 24 S 19 1942

14.

E. Bdy. of T. 5 N., R. 11 W.

Chains.	
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Asc. 70 ft. along E. slope of spur.
41.60	Wash, near head, 3 ft. deep, 10 lks. wide, course SE.; asc. 470 ft. over rocky SE. slope.
48.57	The second mine tunnel, bears S. 21 $\frac{3}{4}$ ° E.
57.40	Spur, slopes W.; desc. 200ft. over broken NW. slope.
79.70	Wash, 3 ft. deep, 20 lks. wide, course SW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for cor. of secs. 13, 18, 19 and 24, with brass cap mkd.
	T5N R11W R10 W S 13 S 18 S 24 S 19 1942.
	Land, rolling and mountainous. Soil, rocky, 4th. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush and cacti.
	Thence, North, bet. secs. 13 and 18. Over rough mountainous land; asc. 330ft. over SE. slope.
9.00	Spur, slopes SW.; desc. steep rocky NW. slope, 260ft.
28.20	Wash, near head, 6 ft. deep, 20 lks. wide, course W.; asc. 375 ft. over SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	↑ S 13 S 18 1942
	Asc. 140 ft. over SW. slope.
47.80	Ridge, bears NW. and SE., desc. 130 ft.
54.50	Same ridge, bears NE. and SW.; thence along W. slope.
60.70	Same ridge, bears NW. and SE.; desc. N. slope, 150 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for cor. of secs. 7, 12, 13 and 18, with brass cap mkd.
	T5N R11W R10W S 12 S 7 S 13 S 18 1942

E. Bdy. T. 5 N., R. 11 W.

Chains.	<p>Land, rough, mountainous. Soil, rocky, 4th. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush, mescale and cacti.</p> <hr/> <p>Thence, North, bet. secs. 7 and 12. Over rough mountainous land; desc. 30 ft. over N. slope.</p> <p>1.50 Wash, near head, 3ft. deep, 20 lks. wide, course NE.; asc. 120 ft. over rocky S. slope.</p> <p>6.30 Spur, slopes, E.; desc. NE. slope, 60 ft.</p> <p>20.30 Wash, 3 ft. deep, 20 lks. wide, course E.; asc. S. slope 200ft.</p> <p>25.30 Spur, slopes E.; desc. 115 ft. along broken E. slope of ridge.</p> <p>39.20 Head of small wash, course E.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \uparrow \\ S\ 12\ \ S\ 7 \\ \hline 1942 \end{array}$ </div> <p>Asc. 690 ft. along E. slope of ridge.</p> <p>75.30 Ridge, bears S. 30° W. and N. 30° E. Thence along W. slope of same.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T5N \\ R11W\ R10W \\ S\ 1\ \ S\ 6 \\ \hline S\ 12\ \ S\ 7 \\ \hline 1942 \end{array}$ </div> <p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rough, mountainous. Soil, 4th. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush, mescale and cacti.</p> <hr/> <p>Thence, North, bet. secs. 1 and 6. Over mountainous land. Desc. 30 ft. along NW. slope.</p> <p>3.00 Wash, at head, 10 lks. wide, course SW.; asc. 220 ft.</p> <p>11.00 Wash, near head, 4 ft. deep, 10 lks. wide, course SW.; asc. 200ft. over rolling SW. slope.</p>
---------	---

E. Bdy. T. 5 N., R. 11 W.

Chains.	
17.70	Spur, slopes W., thence over NW. slope.
21.80	Wash, near head, 4 ft. deep, 20 lks. wide, course SW.; asc. 580 ft. over steep S. slope.
38.25	Spur, slopes SW.; desc. 15 ft. along steep, rocky NW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to rock, and in a mound of stone, 4 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S. 1 S 6 1942.
	Desc. 125 ft. over rocky NW. slope.
47.85	Head of rocky wash, 6 ft. deep, 20 lks. wide, course SW.; asc. 150 ft. over rocky S. slope.
51.80	Spur slopes W.; desc. 70 ft. over NW. slope.
58.00	Rocky wash, 4 ft. deep, 20 lks. wide, course SW.; asc. 390 ft. over steep broken SW. slope.
61.80	Old mine shaft, bears W. about 4 chs. dist.
69.60	Head of wash, 4 ft. deep, 10 lks. wide, course SW.; asc. 500 ft. over broken SW. slope.
82.36	The cor. of Ts. 5 and 6 N., Rs. 10 and 11 W.; described in the field notes of the completion of the E. Bdy. of T. 6 N., R. 11 W., resurveyed under this group.
	Land, mountainous. Soil, rocky, 4th. rate. Timber, paloverde and ironwood. Undergrowth, mesquite, cacti and oakbrush.
Subdivision of T. 5 N., R. 11 W.	
	From the cor. of secs. 25, 30, 31 and 36, on E. bdy. of Tp. West, on true line, on sectional correction line, bet. secs. 25 and 36.
	Over rolling mountain land.
4.70	Wash, 10ft. deep; 20 lks. wide, course SE. 2 chs. thence E.; asc. 350 ft. along N. slope.
39.97	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, and in a mound of stone, 6 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 25 S 36 1942
	Asc. 90 ft. over NE. slope.
43.20	Spur, slopes N. 10° E., 5 chs. to saddle. Thence along N. slope of spur, slopes W., near top.
50.30	Same spur, slopes NW.; desc. 315 ft. over SE. slope.

Subdivision of T. 5 N., R. 11 W.

Chains	
65.90	Wash, 10 lks. wide, course S.; asc. 135 ft. along S. slope.
79.94	At this point, which is N.0°01'W., 80.20 chs. dist., from the standard cor. of secs. 35 and 36,
	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.
	T5NR11W S 26 S 25 S 35 S 36 1942
	Land, mountainous. Soil, rocky, 4th. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
	From the standard cor. of secs. 35 and 36, on S. bdy. of Tp. N. 0°01'W., on a true line, bet. secs. 35 and 36.
	Over rough mountainous land, asc. 150 ft.
6.60	Spur, slopes SW.; desc. 335 ft. along NW. slope.
31.50	Junction of washes, 20 lks. wide, from S.10°W. and SE.
40.20	Set an iron post, 3 ft. long, .1 in. diam., 18 ins. in the ground, and in a mound of stone, 2 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	↑ S 35 S 36 1942
43.60	Wash, 4 ft. deep, 10 lks. wide, course SW. asc. 120 ft. over S. slope.
48.75	Spur, slopes W.; desc. 60 ft. over N. slope.
54.15	Wash, 10 lks. wide, course W.; asc. 155 ft. over S. slope.
61.90	Spur, slopes W.; desc. 160 ft. over N. slope.
69.90	Wash, 5 ft. deep, 20 lks. wide, course W.; asc. 180 ft. over S. slope.
80.20	The cor. of secs. 25, 26, 35 and 36.
	Land, mountainous. Soil, rocky, 4th. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
	N.0°01'W., bet. secs. 25 and 26.
	Asc. 130 ft. over S. slope.
3.30	Spur, slopes NW.; desc. 340 ft. over NW. slope.
6.50	Spur, slopes NW., continue descent along NE. slope.

Subdivisions of T. 5 N., R. 11 W.

Chains.	
22.90	Wash, 8 ft. deep, 20 lks. wide, course W.; asc. 175 ft. over SW. slope.
33.17	Spur, slopes W.; desc. 160 ft. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \uparrow \\ S\ 26 \mid S\ 25 \\ \hline 1942 \end{array}$
	Desc. 60 ft. over N. slope.
43.59	Wash, 8 ft. deep, 50 lks. wide, course SW.; asc. 40 ft. over SW. slope.
52.80	Road, bears E. and W. Asc. 185 ft. along W. slope,
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.
	$\begin{array}{c} T5NR11W \\ \hline S\ 23 \mid S\ 24 \\ \hline S\ 26 \mid S\ 25 \\ \hline 1942 \end{array}$
	Land, mountainous. Soil, 4th. rate. Timber, paloverde and ironwood and mesquite. Undergrowth, creosote brush, ocotillo and cacti.
	East, on a random line, bet. secs. 24 and 25.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.04	A point, 5 lks. N. of the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.
	Thence, N. 89° 58' W., on a true line, bet. secs. 24 and 25. Over rolling desert land; desc. 150 ft. over NW. slope.
19.50	Wash, 30 lks. wide, 10 ft. deep, course SW.
22.60	Old road bears NE. and SW.
31.40	Mine shaft, bears South.
37.07	NE. cor. of house, bears S. 4.07 chs. dist.; a second mine shaft, 6x6 ft. 20 ft. deep, bears S. 10° E., approximately 60 lks. dist. from the house.
40.02	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, and in a mound of stone, 5 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} S\ 24 \\ \hline \frac{1}{4} S\ 25 \\ \hline 1942 \end{array}$

Subdivision of T. 5 N., R. 11 W.

Chains.	
40.50	Wash, 3 ft. deep, 20 lks. wide, course S. 80° W.
54.30	Wash, 6 ft. deep, 50 lks. wide, course S.; asc. 220 ft. over E. slope.
74.20	Spur, slopes S.; mine shaft, bears S. 76° 37' E. Desc. 190 ft over W. slope.
80.04	The cor. of secs. 23, 24, 25 and 26.
<p>Land, mountainous and rolling. Soil, gravelly and rocky, 3rd and 4th. rate. Timber, paloverde and ironwood and mesquite. Undergrowth, creosote brush, ocotillo, and cacti.</p>	
<p>N. 0° 01' W., bet. secs. 23 and 24.</p>	
<p>Over mountainous land, asc. 185 ft. over SW. slope.</p>	
7.30	Spur, slopes SE.; desc. 195 ft. over NE. slope.
7.40	Mine, bears N. 27° W.
20.68	Wash, 6 ft. deep, 10 lks. wide, course E.; asc. rolling E. slope, 20 ft.
39.80	Wash, 10 lks. wide, course SE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for 1/4 sec. cor., with brass cap mkd.
<p style="text-align: center;"> ↑ S 23 S 24 ↓ 1942 </p>	
<p>From cor., mine bears S. 35° W.</p>	
<p>Asc. 465 ft. over SE. slope.</p>	
41.90	Low spur, slopes SE., continue ascent.
57.60	Spur, slopes SW.; thence along steep W. slope.
62.05	Spur, slopes NW.; desc. 300 ft. over NE. slope.
72.80	Head of wash, course NW.; asc. 20 ft. along W. slope.
79.00	Low saddle, bears SE. and NW.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd..
<p style="text-align: center;"> T5NR11W S 14 S 13 S 23 S 24 1942 </p>	
<p style="text-align: right;">raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.</p>	
<p>Land, mountainous. Soil, rocky, 4th. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.</p>	

Subdivision of T. 5 N., R. 11 W.



Chains.	S. 89° 58' E., on random line, bet. secs. 13 and 24.
40.00	Set temp. ¼ sec. cor.
80.10	A point 18 lks. S. of the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.
	Thence,
	S. 89° 54' W., on a true line, bet. secs. 13 and 24.
	Over rough mountain land; asc. 30 ft. over broken SE. slope.
8.15	Rocky spur, slopes SW.; desc. 320 ft. over rough W. slope.
19.15	Wash, 20 ft. deep, 30 lks. wide, course SW.; asc. 405 ft. over broken SE. slope.
40.05	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} \text{S } 13 \\ \text{S } 24 \\ 1942 \end{array}$
	Cor. stands on rocky spur, slopes S.
	Desc. 230 ft. over W. slope.
52.70	Wash, 10 lks. wide, course S. Thence along SE. slope.
59.20	Spur, slopes S. 30° E.; desc. 130 ft. along SW. slope.
75.15	Wash, 4 ft. deep, 50 lks. wide, course S.; asc. 80 ft. over NE. slope.
80.10	The cor. of secs. 13, 14, 23 and 24.
	Land, rocky, 4th. rate. Soil, mountain. Timber, paloverde, ironwood and mesquite. Undergrowth, catclaw, creosote brush, ocotillo and cacti.
	N. 0° 01' W., bet. secs. 13 and 14.
	Over rough mountainous land, desc. 35 ft. over NE. slope.
3.80	Small wash, course SE.; asc. 430 ft. over SE. slope.
32.00	Spur, slopes SW.; asc. 130 ft. along top of same.
35.00	Leave spur, asc. 90 ft. along rocky W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\begin{array}{c} \uparrow \\ \text{S } 14 \mid \text{S } 13 \\ \downarrow \\ 1942 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Cor. stands on rocky spur, slopes W.

Subdivision of T. 5 N., R. 11 W.

Chains.	
	Thence along broken NW. slope.
49.99	Wash at head, 10 lks. wide, course SW.; asc. 430 ft. over broken S. slope.
67.50	Spur, slopes SW.; desc. 160 ft. over rocky, broken, NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top, for cor. of secs. 11, 12, 13 and 14, with brass cap mkd.
	T5NR11W S 11 S 12 S 14 S 13 1942
	Land, mountainous. Soil, rocky, 4th. rate. Timber, paloverde; Undergrowth, creosote brush and cacti.
	N. 89° 54' E., on random line, bet. secs. 12. and 13.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	A point 18 lks. N. of the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.
	Thence,
	N. 89° 58' W., on true line, bet. secs. 12 and 13.
	Over rough mountain land.
6.00	Wash, 10 lks. wide, course N. 80° E.; asc. 280 ft. over SE. slope.
12.30	Ridge, bears N. 10° W. and S. 10° E.; desc. 30 ft. over W. slope
15.75	Wash, near head, 10 lks. wide, course S.; asc. E. slope 65 ft.
21.20	Spur, slopes S.; desc. broken, rocky, NW. slope, 390 ft.
38.60	Wash, 3 ft. deep, 50 lks. wide, course S.; asc. broken NE. slope 55 ft. Wash has pools of water.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S 12}{S 13}$ 1942
	Asc. 180 ft. over broken NE. slope.
45.40	Spur, slopes SE.; asc. 100 ft. over broken S. slope.
61.85	Junction of washes from NW. and SW., course SE.; asc. 345 ft. over rocky E. slope.
72.40	Long spur, bears SW. and N. 10° E.; desc. 285 ft. over broken rocky, NW. slope.

300K

Subdivision of T. 5 N., R. 11 W.

Chains.	
80.00	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rough, mountainous. Soil, 4th. rate. Timber paloverde; undergrowth, catclaw, creosote brush.</p>
	<p>N. 0° 01' W.; bet. secs. 11 and 12.</p> <p>Over very rough, broken mountain land; desc. NW. slope 140 ft.</p>
8.20	<p>Wash, at head, course W.; asc. 315 ft. over rough, broken, SW. slope.</p>
21.35	<p>Rocky spur, slopes W.; desc. 245 ft. over NW. slope.</p>
28.25	<p>Wash, 4 ft. deep, 20 lks. wide; course W.; asc. 264 ft. over broken SW. slope.</p>
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground; and in a mound of stone, 5 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	<p style="text-align: center;">  </p>
	<p>Asc. 310 ft. along rocky SW. slope.</p>
56.00	<p>Spur, slopes W., desc. 50 ft. over NW. slope.</p>
62.85	<p>Wash, 20 lks. wide, course SW.; asc. 300 ft. over S. slope.</p>
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.</p>
	<p style="text-align: center;">  </p>
	<p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rough, mountainous. Soil, 4th. rate. Timber; paloverde; undergrowth, catclaw, cacti.</p>
	<p>S. 89° 58' E., on random line, bet. secs. 1 and 12.</p>
40.00	<p>Set temp. $\frac{1}{4}$ sec. cor.</p>
80.00	<p>A point, 8 lks. S. of the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>Thence,</p>
	<p>S. 89° 59' W., on true line, bet. secs. 1 and 12.</p>
	<p>Over rolling mountain land. Desc. 150 ft. over W. slope.</p>
15.35	<p>Wash, 6 ft. deep, 20 lks. wide; course S.; asc. 110 ft. over E. slope.</p>
21.65	<p>Spur, slopes S.; desc. 220 ft. over W. slope.</p>

Subdivision of T. 5 N., R. 11 W.

Chains	
30.40	Wash, 6 ft. deep, 30 lks. wide, course SW.; well in wash bears SW., 1 ch. dist.; arrastre, bears S., 1.50 chs. dist. Asc. 200 ft. over E. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4} \begin{array}{c} S 1 \\ S 12 \\ 1942 \end{array}$
40.50	Spur, slopes S.; desc. 120 ft. over W. slope.
44.85	Wash, 4 ft. deep, 20 lks. wide, course S., from junction of washes, 1 ch. N., from NE. and NW.; asc. 400 ft. over NE. slope.
63.20	Spur, slopes S.; desc. 95 ft. over W. slope.
70.90	Wash, at head, 10 lks. wide, course SW.; asc. 140 ft. over E. slope.
80.00	The cor. of secs. 1, 2, 11 and 12. Land, rolling mountains. Soil, 3rd and 4th rate. Timber, paloverde. Undergrowth, catclaw, oakbrush, cacti.
	N. 0° 01' W., on random line, bet. secs. 1 and 2.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
82.45	A point 12 lks. E. of the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp.; described in the field notes of the S. bdy. T. 6 N., R. 11 W., surveyed under this group. Thence, S. 0° 06' E., on true line, bet. secs. 1 and 2. Over rough broken NE. slope, asc. 220 ft.
5.55	Rocky spur, slopes NW.; desc. 425 ft. over steep rocky, W. slope.
32.45	Head of wash, course NW.; asc. 60 ft. over NW. slope.
35.65	Divide, bears NE. and W.; desc. 95 ft. over S. slope.
40.35	Wash, at head, course SE.; asc. 20 ft. along NE. slope.
42.45	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd. $S 2 \begin{array}{c} \\ S 1 \\ 1942 \end{array}$ <p style="text-align: right;">raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> Asc. 20 ft. along NE. slope.
46.00	Top of ascent, desc. 130 ft. over SW. slope.
53.65	Wash, 4 ft. deep, 20 lks. wide; course SW.; asc. 195 ft. along NW. slope.

Subdivision of T. 5 N., R. 11 W.

Chains.

73.25 Spur, slopes S. from NE.; desc. 25 ft. along top of spur.

81.55 Leave top of spur, slopes S. 20° W.; desc. 15 ft.

82.45 The cor. of secs. 1, 2, 11 and 12.

Land, N. $\frac{1}{2}$ rough broken mountain, S. $\frac{1}{2}$ rolling mountain.

Soil, rocky, 4th. rate.

Timber, paloverde.

Undergrowth, catclaw, oakbrush, mescale, sangre de cristo.

From the cor. of secs. 25, 26, 35 and 36,

West, on true line, on sectional correction line, bet. secs. 26 and 35.

Over mountainous land, asc. 25 ft. along rolling S. slope.

2.10 Spur, slopes S.; desc. 35 ft.

7.00 Wash, 5 lks. wide, course SW.; asc. 160 ft.

17.80 Spur, slopes SW.; desc. 210 ft. over NW. slope

27.60 Wash, 8 ft. deep, 10 lks. wide, course S.; asc. 35 ft.

31.60 Spur, slopes S.; thence along S. slope.

34.70 Spur, slopes SW.; desc. 60 ft. along NW. slope of spur.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 26
4 S 35
1942

Desc. 100 ft. along N. slope.

49.87 Wash, 50 lks. wide, course S.; thence over level land.

55.00 Wash, 10 ft. deep, 50 lks. wide, course SE.

59.60 Road, bears NE. and SW.

68.70 Road, bears N. and S.

75.50 Low spur, slopes SW.

80.00 At this point, which is N. 0° 01' W., 80.54 chs. dist., from the standard cor. of secs. 34 and 35,

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, and in a mound of stone to top, for cor. of secs. 26, 27, 34, and 35, with brass cap mkd.

T5NR11W	
S 27	S 26
S 34	S 35
1942	

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. raise a mound

Land, rolling and level.

Soil, 3rd and 4th. rate,

Timber, paloverde, ironwood, mesquite; undergrowth, creosote brush and cacti, ocotillo.

Subdivision of T. 5 N., R. 11 W.

Chains.


From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp.

N. 0° 01' W., on a true line, bet. secs. 34 and 35

Over rolling desert land thru scattered paloverde and ironwood.

28.00 Wash, 15 lks. wide, course SW.

40.54 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, and in a small mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

An iron wood, 4 ins. diam., bears S.48 $\frac{1}{2}$ °E., 62 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

An ironwood, 4 ins. diam., bears N.82 $\frac{3}{4}$ °W., 73 lks. dist., mkd. BT.

56.75 Old road, bears N.70°E and S.70°W.

61.00 Wash, 15 lks. wide, course S. 70°W.

80.54 The cor. of secs. 26, 27, 34 and 35.


Land, level and rolling desert.
Soil, sandy and gravelly, 3 rd rate.
Timber, paloverde and ironwood.
Undergrowth, creosote brush and cacti, and ocotillo.

N. 0° 01' W., bet. secs. 26 and 27.

Over rolling desert land

24.10 Wash, 15 lks. wide, course S.70°W. Enter rolling hills. Asc. 90 ft. over W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with a stone, 10x6x4 ins., mkd. with a cross (+) deposited at the base, and in a mound of stone, 3 $\frac{1}{2}$ ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



Desc. 40 ft. over W. slope.

47.60 Wash, course S. 35°W. Asc. 140 ft. over SE. slope.

56.50 Spur, slopes S.40°W.; asc. 190 ft. along broken W. slope.

73.20 Spur, slopes SW. from a spur, slopes S.15°E. Thence along W. slope of spur near top.

Subdivision of T. 5 N., R. 11 W.

Chains.	
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, with a stone, 10x8x7 ins., mkd. with a cross (+) deposited at the base, and in a mound of stone, 5 ft. base to top, for cor. of secs. 22,23,26 and 27, with brass cap mkd.</p> <p style="text-align: center;">T5NR11W S 22 S 23 S 27 S 26 1942</p> <p>Land, rolling desert. Soil, 3rd and 4th. rates. Timber, paloverde and ironwood. Undergrowth, creosote brush and cacti.</p>
East, on a random line, bet. secs. 23 and 26.	
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.98	A point 22 lks. S. of the cor. of secs. 23,24,25 and 26.
	Thence,
	S. 89° 51' W., on true line, bet. secs. 23 and 26.
2.70	Wash, 5 lks. wide, course S. 10°W.; asc. 60 ft. over E. slope.
5.50	Low spur, slopes S.15°W.; desc. 20 ft.
8.10	Wash, course S.15°W.; asc. 180 ft. over SE. slope.
21.85	Spur, slopes S.70°W.; asc. 20 ft. along N. slope.
26.30	Same spur, slopes N.60°W.; desc. 130 ft. over SW. slope.
33.50	Change to W. slope desc. 40 ft.
39.99	<p>Set an iron post, 3 ft. long, 1 ins. diam., 18 ins. in the ground, with a white quartz stone, 4x4x3 ins., mkd. with a cross (+) deposited at the base, and in a mound of stone 3 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$ 1942</p>
	Desc. 60 ft. over W. slope.
48.40	Wash, 50 lks. wide, course S.20°W.
55.70	Road, N.25°E. and S.15°W.
59.20	Road, bears NE. and S.30°W.
64.90	Wash, course S.10°E.; asc. 115 ft. over SE. slope.
79.98	The cor. of secs. 22,23,26 and 27.
	<p>Land, rolling hills. Soil, 3rd and 4th rate. Timber, paloverde, ironwood and mesquite. Undergrowth, catclaw, creosote brush, ocotillo and cacti.</p>

Subdivision of T. 5 N., R. 11 W.

Chains.	<p>N.0° 01' W., bet. secs. 22 and 23.</p> <p>Over rolling mountain land; asc. 20 ft. over SE. slope.</p> <p>1.40 Spur, slopes S.10°W.; desc. 182 ft. over NW. slope.</p> <p>13.10 Wash, drains W.; asc. 295 ft. over SW. slope.</p> <p>32.20 Spur, slopes S.60°W.; desc. 120ft. over NW. slope.</p> <p>38.30 Wash, course W.</p> <p>40.00 True point for cor. falls in a wash, course W., a place unsuitable for a permanent cor.</p> <p>40.40 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, with a stone, 10x6x5 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 4 ft. base to top, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> \uparrow <table style="margin: auto;"> <tr><td>S 22</td><td> </td><td>S 23</td></tr> <tr><td>W</td><td> </td><td>C</td></tr> <tr><td colspan="3">1942</td></tr> </table> </div> <p>Asc. 110 ft. over SW. slope.</p> <p>48.85 Spur, slopes S.30°E. thence along E. slope.</p> <p>76.40 Wash, course S.20°E.; asc. 35 ft..</p> <p>79.40 Spur, slopes SE.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="3">T5NR11W</td></tr> <tr><td>S 15</td><td> </td><td>S 14</td></tr> <tr><td>S 22</td><td> </td><td>S 23</td></tr> <tr><td colspan="3">1942</td></tr> </table> <p style="text-align: right;">from which</p> <p>An ironwood, 4 ins. diam., bears S.60°E., 76 lks. dist. mkd. BT.</p> <p>An ironwood, 4 ins. diam., bears S.48$\frac{1}{4}$°W., 130 lks. dist., mkd. BT.</p> <p>Raise a mound of stone W. of cor.</p> <p>Land, mountainous.</p> <p>Soil, 4th. rate.</p> <p>Timber, paloverde and ironwood.</p> <p>Undergrowth, creosote brush, ocotillo and cacti.</p> </div>	S 22		S 23	W		C	1942			T5NR11W			S 15		S 14	S 22		S 23	1942		
S 22		S 23																				
W		C																				
1942																						
T5NR11W																						
S 15		S 14																				
S 22		S 23																				
1942																						
	<p>N. 89° 51' E., on random line, bet. secs. 14 and 23:</p> <p>40.00 Set temp. $\frac{1}{4}$ sec. cor.</p> <p>80.00 A point 5 lks. N. of the cor. of secs. 13, 14, 23 and 24.</p>																					

Subdivision of T. 5 N., R. 11 W.

Chains.	
	Thence,
	S. 89° 53' W., on true line, bet. secs. 14 and 23.
	Over mountainous desert land.
0.50	Spur, slopes SE.; desc. 140 ft. over SW. slope.
10.20	Wash, in curve, from SE. to S. 60° W.
17.60	Road, bears N. and S. 10° W.
20.50	Wash, 60 lks. wide, course S.; asc. 115 ft. over E. slope.
28.20	Low spur, slopes S.; desc. 55 ft. over SW. slope.
35.00	Wash, course S. 10° E.; asc. 110 ft. over E. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with pieces of broken glass deposited at the base, and in a mound of stone, 6 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S \ 14}{S \ 23}$ 1942
40.70	Spur, slopes S. 10° E.; desc. 160 ft. over SW. slope.
49.70	Wash, course S. 10° E.; Asc. 190 ft. over E. slope.
59.90	Spur, slopes S.; desc. 205 ft. over SW. slope.
76.80	Wash, 50 lks. wide, course S. 10° E.; asc. E. slope 50 ft.
80.00	The cor. of secs. 14, 15, 22 and 23.
	Land, mountainous.
	Soil, 4th. rate.
	Timber, paloverde, ironwood, mesquite.
	Undergrowth, creosote brush, catclaw, ocotillo and cacti.
	N. 0° 01' W., bet. secs. 14 and 15.
	Over mountainous land, desc. 40 ft. over NE. slope.
5.75	Wash, 40 lks. wide, course S. 20° E.; asc. 430 ft. over broken SW. slope.
21.80	Spur, slopes W.; desc. 60 ft. over NW. slope.
27.20	Wash, course W.; asc. 60 ft. over broken W. slope.
36.30	Spur, slopes W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \uparrow \\ S \ 15 \ S \ 14 \\ 1942 \end{array}$
	raise a mound
	of stone, 3 ft. base, 2 ft. high, W. of cor.
	Asc. 90 ft. over W. slope.
52.70	Spur, slopes S. 10° E.; desc. 90 ft. along E. slope.

Subdivision of T. 5 N., R. 11 W.

Chains.

- 61.10 Wash, course S.80°E.; asc. 345 ft. over SE. slope.
- 73.00 Same spur, slopes S.15°W.; asc. 160 ft. over W. slope.
- 79.00 Same spur, slopes S. 10°E.; thence along E. slope.
- 79.25 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, with a stone, 12x8x6 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 3ft. base, to top, for witness cor. of secs. 10,11,14 and 15, with brass cap mkd.
- W C
T5N R11W
S 10 | S 11
S 15 | S 14
1942
- 80.00 Mark a cross (+) on sloping bedrock for cor. of secs. 10,11,14 and 15. This point is unsuitable for a permanent monument.
- Land, mountainous..
Soil, 4th. rate.
Timber, paloverde; undergrowth, creosote brush and cacti.
-
- N. 89° 53' E., on random line, bet. secs. 11 and 14.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.92 A point 11 lks. N. of the cor. of secs. 11,12,13 and 14.
Thence,
S. 89° 58' W., on true line, bet. secs. 11 and 14.
Over mountainous land, desc. 665 ft. over broken NW. slope.
- 31.30 Wash, 20 lks. wide, course S.30°W.; asc. 80 ft. over S. slope.
- 39.96 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$ $\frac{S 11}{S 14}$
1942
- raise a mound
- of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
- 42.20 Wash, course S.; asc. 365 ft. over E. slope.
- 59.00 Spur, slopes S.; desc. 255 ft. over rocky SW. slope.
- 68.80 Wash, course S. from NW.; asc. 370 ft. over E. slope.
- 79.92 The true point for cor. of secs. 10,11,14 and 15. For witness cor. set see line bet. secs. 14 and 15.
Land, mountainous.
Soil; 4th. rate.
Timber, paloverde and ironwood.
Undergrowth, creosote brush, ocotillo and cacti.

Subdivision of T. 5 N., R. 11 W.

Chains.	<p>From true point for cor. of secs. 10, 11, 14 and 15. N. 0° 01' W., bet. secs. 10 and 11. Over mountainous land, along E. slope.</p> <p>22.30 Wash, course S.20°E.; asc. 510 ft. over broken SW. slope.</p> <p>37.70 Spur, slopes SE.; thence over NE. slope.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \\ S\ 10\ \ S\ 11 \\ \\ 1942 \end{array}$ </div> <p>of stone, 3 ft. base, 2 ft. high, W. of cor. raise a mound T</p> <p>Desc. 80 ft. over NE. slope.</p> <p>45.30 Wash, course SE.; asc. 655 ft. over SW. slope.</p> <p>65.70 Spur, slopes SE.; desc. 40 ft. along rolling E. slope.</p> <p>75.60 Divide, bears S. 80°W. and N.60°E.; desc. 90 ft. over NW. slope.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground, with a stone, 6x6x3 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 3½ ft. base to top, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T5NR11W \\ S\ 3\ \ S\ 2 \\ \hline S\ 10\ \ S\ 11 \\ 1942 \end{array}$ </div> <p>Land, mountainous. Soil, 4th. rate. Timber, paloverde; undergrowth, oakbrush and cacti.</p>
	<p>N. 89° 58' E., on random, bet. secs. 2 and 11.</p> <p>40.00 Set temp. $\frac{1}{4}$ sec. cor.</p> <p>80.06 A point, 2 lks. S. of the cor. of secs. 1, 2, 11 and 12. Thence, S. 89° 57' W., on true line, bet. secs. 2 and 11. Over mountainous land.</p> <p>0:35 Spur, slopes S.5°W.; desc. 430 ft. over W. slope.</p> <p>13:55 Wash, course S.30°W.; asc. 140 ft. over SE. slope.</p> <p>21.20 Spur, slopes S.10°W.; desc. 170 ft. over NW. slope.</p> <p>25.30 Wash, course SW. 10 chs. then S.; asc. 260 ft. over SE. slope.</p> <p>35.70 Small spur, slopes SE.; desc. 50 ft. over S. slope.</p>

Subdivision of T. 5 N., R. 11 W.

4024

Chains.	
40.03	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, with a stone, 9x7x3 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 6 ft. base to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S 2}{S 11}$ 1942
	Desc. 90ft. over S. slope.
51.90	Wash, course SE.; asc. 200 ft. over E. slope.
61.00	Spur, slopes SE.; asc. 20 ft. over S. slope.
67.50	Wash, at head, course SE. ; asc. 125 ft. over rolling top of mountain.
78.25	Ridge, bears S.30°W. and N.60°E.; desc. 60 ft. over W. slope.
80.06	The cor. of secs. 2,3,10 and 11.
	Land, mountainous. Soil, 4th. rate. Timber palo verde. Undergrowth, oakbrush and cacti.
	N. 0° 07' W., on random line, bet. secs. 2 and 3.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
82.62	A point 7 lks. E. of the cor. of secs. 2,3,34 and 35, on the N. bdy. of the Tp., described in the field notes of the S. bdy. T.6 N., R.11 W.; surveyed under this group. Thence,
	S. 0° 10' E., on true line, bet. secs. 2 and 3.
	over mountainous land, asc. 110 ft. over rocky, broken, NW. slope.
4.50	Spur, slopes W.; desc. 300 ft. over broken SW. slope.
19.00	Wash, course NW.; asc. 700 ft. over broken NE. slope.
42.00	Spur, slopes NW.
42.62	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, with a stone, 10x7x2 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$S 3 \left S 2 \right.$ 1942
	Desc. 285 ft. over SW. slope.
54.65	Wash, course N.70°W.; asc. 140 ft. over broken NE. slope.
58.55	Spur, slopes NW., 6 chs. to toe. Asc. 50 ft. along W. slope.
67.55	Wash, course N.30°W.; asc. 360 ft. over NE. slope.

Subdivision of T. 5 N., R. 11 W.

Chains.

74.95 Spur, slopes NW.; asc. 60 ft. over NW. slope.

82.62 The cor. of secs. 2, 3, 10 and 11.


Land, mountainous.
Soil, rocky, 4th. rate.
Timber, paloverde. Undergrowth, creosote brush, oak brush, ocotillo and cacti.

From the cor. of secs. 26, 27, 34 and 35,

W., on true line, on sectional correction line, bet. secs. 27 and 34.

Over rolling desert land, thru scattered timber.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.




raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

68.40 Wash, 20 ft. deep, 50 lks. wide, course SW.

79.96 At this point, which is N. 0° 02' W., 80.28 chs. dist., from the standard cor. of secs. 33 and 34 on S. bdy. of the Tp.,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling desert.
Soil, sandy and gravelly, 3rd rate.
Timber, paloverde and ironwood.
Undergrowth, creosote brush, ocotillo and cacti.

From the standard cor. of secs. 33 and 34, S. bdy. of Tp.,

N. 0° 02' W., on true line, bet. secs. 33 and 34.


Over rolling desert land, thru scattered timber.

11.40 Road, bears N. 70° E. and S. 70° W.

20.40 Wash, 20 ft. deep, 30 lks. wide, course S. 60° W.

38.00 Wash, 15 lks. wide, course SW.

40.28 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



Subdivision of T. 5 N., R. 11 W.

Chains.	raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
59.90	Wash, 16 ft. deep, 30 lks. wide, course S.70°W.
80.28	The cor. of secs. 27, 28, 33 and 34. Land, rolling desert. Soil 3rd. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
	N. 0° 02' W., bet. secs. 27 and 28. Over rolling desert land.
3.70	Wash, 15 lks. wide, course W. from NE.
34.50	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness ¼ sec. cor., with brass cap mkd. WTC S 28 S 27 1942
	raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
35.90	Center of wash, in curve, 20 ft. deep, 20 lks. wide, course SW. from N.
40.00	True point for ¼ sec. cor. falls in wash, a place unsuitable for a permanent cor..
45.00	Leave wash, course S. from NE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for cor. of secs. 21, 22, 27 and 28, with brass cap mkd. T5NR11W S 21 S 22 S 28 S 27 1942
	raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor. Land, rolling desert. Soil, 3rd rate, sandy and gravelly. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
	East, on random line, bet. secs. 22 and 27.
40.00	Set temp. ¼ sec. cor..
80.08	Intersect the cor. of secs. 22, 23, 26 and 27. Thence, West, on true line, bet. secs. 22 and 27. Over rolling desert land.
0.40	Spur, slopes S.10°W.; desc. 245 ft. over NW. slope.

Subdivision of T. 5 N., R. 11 W.

Chains.	
14.50	Wash, 25 lks. wide, course S. 30° W.; thence over level land
40.04	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{S \ 22}{S \ 27}$ 1942 raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.
42.50	Wash, 30 lks. wide, course S.
60.80	Wash, 40 lks. wide, course S.
80.08	The cor. of secs. 21, 22, 27 and 28. Land, rolling desert. Soil, gravelly, sandy, 3rd. rate. Timber, creosote brush, ocotillo and cacti.
N. 0° 02' W., bet. secs. 21 and 22. Over rolling mountain land, asc. 70 ft.	
7.40	Low flat spur, slopes S. 30° E., 2 chs. to toe; asc. 100 ft. along top of same.
28.20	Leave spur, slopes S. from N. 20° E., thence over W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd. $S \ 21 \ \ S \ 22$ 1942 raise a mound of stone, 2½ ft. base, 1½ ft. high W. of cor.
44.70	Wash, 10 lks. wide, course SW.; asc. 140 ft. over S. slope.
51.00	Spur, slopes S. 20° E. from N. 30° E.; asc. 240 ft. along broken W. slope.
72.90	Same spur, slopes S. 5° E.; asc. along E. slope, 25 ft.
79.60	Side hill drain, course S. 60° E.; asc. 15 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, with a stone, 9x6x5, mkd. with a cross (+), deposited at the base, and in a mound of stone, 5 ft. base, to top, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd. T5NR11W $\frac{S \ 16 \ \ S \ 15}{S \ 21 \ \ S \ 22}$ 1942 Land, rolling mountain. Soil, sandy, gravelly and rocky, 3rd and 4th. rates. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.

Subdivision of T. 5 N., R. 11 W.

Chains.

- East, on random line, bet. secs. 15 and 22.
- 40.00 Set temp. $\frac{1}{4}$ sec, cor.
- 80.14 A point 5 lks. S. of the cor. of secs. 14, 15, 22 and 23.
Thence,
S. $89^{\circ} 58'$ W., on true line, bet. secs. 15 and 22.
Over mountainous land.
- 0.50 Spur, slopes SE.; desc. 20 ft. along S. slope.
- 6.20 Wash, course S. 60° E.; asc. 280 ft. over E. slope.
- 22.20 Spur, slopes NE.; thence along N. slope.
- 29.90 Spur, slopes S. 20° E.; desc. 200 ft. over broken SW. slope.
- 37.15 Wash, course SW.; asc. 70 ft. along SE. slope.
- 40.07 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$$\frac{1}{4} \frac{S 15}{S 22}$$

1942

raise a mound
of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
Asc. 45 ft. over S. slope.

- 44.70 Spur, slopes SW.; desc. 260 ft. over W. slope.
- 58.20 Wash, ~~50 lks.~~ widey course S.; asc. E. slope, 40 ft.
- 62.70 Wash, course SE.; asc. 190 ft. over NE. slope.
- 71.20 Spur, slopes SE.; asc. 35 ft. over S. slope.
- 80.14 The cor. of secs. 15, 16, 21 and 22.

Land, mountainous.
Soil, third and fourth rates.
Timber, paloverde. Undergrowth, creosote brush, cacti.

- N. $0^{\circ} 02'$ W., bet. secs. 15 and 16.
Over mountainous land, asc. 280 ft. over S. slope.
- 5.80 Spur, slopes S. 60° E.; thence along E. slope.
- 10.70 Spur, slopes E.; desc. 160 ft. over N. slope.
- 16.80 Wash, course N. 80° E.; asc. 245 ft. over SE. slope.
- 26.10 Spur, slopes S. 80° E.; asc. 25 ft. over E. slope.
- 30.95 Wash, course SE.; asc. 310 ft. over S. slope.
- 36.30 Spur, slopes S. 80° E.; desc. 100 ft. over broken E. slope.

Subdivision of T. 5 N., R. 11 W.

Chains.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, with a stone, 16x12x8 ins., mkd. with a cross (+) deposited at the base, and in a mound of stone, 4 ft. base to top, for 1/4 sec. cor., with brass cap mkd.

S 16 | S 15

1942

Desc. 50 ft. over broken E. slope.

48.20 Wash, course SE.; asc. 520 ft. over SW. slope.

65.00 Spur, slopes S. 60° E.; desc. 85 ft. over NE. slope.

70.30 Wash, course S. 80° E.; asc. 120 ft. SW. slope.

74.80 Spur, slopes S. 20° E., desc. 25 ft. over broken E. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, with a stone, 12x5x3 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 3 ft. base to top, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

T5NR11W
S 9 | S 10
S 16 | S 15
1942

Land, mountainous.
Soil, 4 th. rate.
Timber paloverde. Undergrowth, creosote brush, catclaw, and cacti.

N. 89° 58' E. on random line bet. secs. 10 and 15.

40.00 Set temp. 1/4 sec. cor.

80.20 A point 10 lks. N. of true point; for cor. of secs. 10, 11, 14 and 15. For witness cor. set see line bet. secs. 14 and 15.

Thence,

N. 89° 58' W., on true line, bet. secs. 10 and 15.

Over mountainous land, asc. 30 ft. over E. slope.

0.90 Spur, slopes SE.; desc. 355 ft. over SW. slope.

15.90 Spur, slopes SW., continue descent.

23.60 Wash, course S.; thence along S. slope.

32.30 Wash, 20 lks. wide, course S.

40.20 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, with a stone, 12x6x4 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 3 ft. base to top, for 1/4 sec. cor., with brass cap mkd.

S 10 | S 15

1942

-Subdivision of T. 5 N., R. 11 W.

K 4224

Chains.	Asc. 60 ft. over S. slope
46.00	Spur, slopes S.; desc. 40 ft.
48.50	Wash, 6 ft. deep, 30 lks. wide, course SE. 2chs. dist. then S.60°E.; asc. 410 ft. over SE. slope.
59.00	High spur, slopes S.20°E.; S. side of butte on top spur; desc. 45 ft.
65.90	Hillside drain, course N.55°E.; asc. 365 ft. over SE.slope.
80.20	The cor. of secs. 9,10,15 and 16.
	Land, mountainous. Soil, 3rd and 4th. rate. Timber paloverde; undergrowth, oakbrush, creosote brush, catclaw and cacti.
	N. 0° 02' W., bet. secs. 9. and 10.
	Over mountainous land, desc. 80 ft. over broken E.slope.
13.50	Wash, course E.; asc. 190 ft. over SE. slope.
21.30	Divide, bears S.75°W. and NE.; desc. 290 ft. over rocky, broken, NW. slope.
37.50	Spur, slopes N.60°W.; desc. 100ft. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap, mkd.
	$\begin{array}{c} \uparrow \\ S\ 9\ \ S\ 10 \\ \downarrow \\ 1942 \end{array}$
	of stone, 3 ft. base, 2½ ft. high, W. of cor. raise a mound
	Desc. 50 ft. over N. slope
41.30	Wash, course N.60°W.; desc. 30 ft. over broken W. slope.
52.00	Spur, slopes N.80°W.; desc. 260 ft. over NE. slope;
59.90	Wash, course W.; asc. 70 ft. over SW. slope.
76.20	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. of secs. 3,4,9 and 10, with brass cap mkd.
	$\begin{array}{c} W\ C \\ T5NR11W. \\ S\ 4\ \ S\ 3 \\ S\ 9\ \ S\ 10. \\ \downarrow \\ 1942 \end{array}$
	of stone, 3 ft. base, 2 ft. high, W. of cor. raise a mound
77.20	Wash, course SW.; asc. 100 ft. over broken ledge rock sloping S.
80.00	True point for cor. falls on face of broken cliffs, a place unsuitable for a permanent cor.
	Land, mountainous. Soil, 4th. rate, rocky. Timber, paloverde; undergrowth, oak brush, cacti.

Subdivision of T. 5 N., R. 11 W.

Chains	S. 89° 58' E., on random line, bet. secs. 3 and 10.
40.00	Set temp. 1/4 sec. cor.
79.88	A point, 19 lks. S. of the cor. of secs. 2, 3, 10 and 11. Thence, S. 89° 54' W., on true line, bet. secs. 3 and 10. Over mountainous land; desc. 240 ft. over NW. slope.
6.60	Ravine, drains N. 20° W.; desc. 190 ft. over broken N. slope.
14.50	Wash, course N.; asc. 170 ft. over N. slope.
25.00	Top of ascent; desc. 165 ft.
28.80	Wash, course N.; asc. 170 ft. over NE. slope.
38.51	Spur, slopes N.; desc. 60 ft. over NW. slope.
39.94	Mark a cross (*), on sloping ledge, for 1/4 sec. cor., a place unsuitable for setting a permanent monument.
40.34	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness 1/4 sec. cor., with brass cap mkd. $\frac{S \ 3}{S \ 10 \ W \ C}$ 1942 raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Desc. 114 ft. over NW. slope.
43.75	Spur, slopes N. 60° W.; desc. 795 ft. over broken SW. slope.
71.00	Wash, course N. 80° W.; desc. 70 ft. over broken NW. slope.
77.00	Same wash, course SW.; asc. 50 ft. over broken S. slope.
79.88	The true point for cor. of secs. 3, 4, 9 and 10. For witness cor. set, see line bet. secs. 9 and 10. Land, mountainous. Soil, 4th rate. Timber, paloverde; undergrowth, oakbrush, cacti.
	From true point for cor. of secs. 3, 4, 9 and 10, N. 0° 11' W., on random line, bet. secs. 3 and 4.
40.00	Set temp. 1/4 sec. cor.
82.56	A point 14 lks. E. of the cor. of secs. 3, 4, 33 and 34, on N. bdy. of the Tp.; described in the field notes of the S. bdy. of T. 6 N., R. 11 W., surveyed under this group. Thence, S. 0° 17' E., on true line, bet. secs. 3 and 4. Over mountainous land, asc. 18 ft.

Subdivision of T. 5 N., R. 11 W.

Chains.	
1.30	Spur, slopes NW. desc. 140 ft. over SW. slope.
15.40	Wash, 30 lks. wide, course N.35°W.; asc. 225 ft. over gentle NW. slope.
39.90	Wash, course NW.; asc. 35 ft. over NE. slope.
42.56	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \uparrow \\ S\ 4\ S\ 3 \\ 1942 \end{array}$
	of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. raise a mound
	Asc. 215 ft. over NE. slope.
54.00	Wash, course N.30°E.; asc. 240 ft. over NW. slope.
63.50	Spur, slopes N.20°E.; asc. 285 ft. over NE. slope.
72.60	Spur, slopes N.60°W.; desc. 370 ft. over broken S. slope.
82.56	True point for cor. of secs. 3, 4, 9 and 10.
	Land, mountainous. Soil, 3rd and 4th rates. Timber palo verde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
<hr/>	
	From the cor. of secs. 27, 28, 33 and 34,
	West, on true line, on sectional correction line, bet. secs. 28 and 33.
	Over nearly level desert land, thru scattered timber.
5.80	Wash, 10 ft. deep, 20 lks. wide, course SW.
37.70	Wash, 5 ft. deep, 30 lks. wide, course S.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to rock, and in a mound of stone, 5 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \uparrow \\ S\ 28 \\ S\ 33 \\ 1942 \end{array}$
45.60	Road, bears SW. and NE.
64.10	Road, bears SW. and NE.
80.00	At this point, which is N. 0° 02' W., 80.09 obs. dist. from the standard cor. of secs. 32 and 33, on S. bdy. of Tp.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.
	$\begin{array}{c} T5NR11W \\ S\ 29\ S\ 28 \\ S\ 32\ S\ 33 \\ 1942 \end{array}$

Subdivision of T. 5 N., R. 11 W.

Chains

Land, nearly level.
Soil, 3rd rate, sandy and gravelly.
Timber, palo verde and ironwood.
Undergrowth, creosote brush, ocotillo and cacti.


From the standard cor. of secs. 32 and 33, S. bdy. of Tp.

N. 0° 02' W., on true line, bet. secs. 32 and 33.

Over nearly level desert land, thru scattered timber.

14.10 Road, bears N. 20° E. and SW.

40.09 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



1942

raise a mound of stone, 3 ft. base, .2 ft. high, W. of cor.

69.90 Wash, 25 lks. wide, course SW. from N. 10° E.

73.30 Same wash, 15 ft. deep, course S. 10° E., from N. 30° W.

80.09 The cor. of secs. 28, 29, 32 and 33.

Land, nearly level.
Soil, sandy and gravelly, 3rd. rate.
Timber, palo verde and ironwood.
Undergrowth, creosote brush, ocotillo and cacti.

N. 10° 02' W., on true line bet. secs. 28 and 29.


Over nearly level desert land thru scattered timber.

3.70 Wash, 30 lks. wide, course S. 30° W.

7.90 Wash, 10 lks. wide, course S. 30° W., from NE.

11.80 Same wash, course SE.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, and in a mound of stone to top, for 1/4 sec. cor., with brass cap mkd.



1942

raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, with a stone, 5x5x2 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 3 1/2 ft. base, to top, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.



Subdivision of T. 5 N., R. 11 W.

Chains.	Land, nearly level. Soil, sandy and gravelly, 3rd. rate. Timber, palo verde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
	East, on random line, bet. secs. 21 and 28.
40.00	Set temp. $\frac{1}{4}$ sec. cor..
80.12	A point, $\frac{5}{8}$ lks. N. of the cor. of secs. 21, 22, 27 and 28. Thence, N. $89^{\circ} 58'$ W., on true line, bet. secs. 21 and 28. Over rolling desert land, asc. 35 ft.
8.00	Low spur, slopes S.; desc. 45 ft.
11.20	Wash, course S. 10° W.
26.70	Desert road, bears S. 25° W and N. 25° E.
40.06	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \text{S } 21 \\ \hline \text{S } 20 \\ 1942 \end{array}$
	raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high N. of cor.
59.00	Wash, 50 lks. wide, course S. 10° E.
69.00	Road to Silver Queen mine, bears N. and S.
75.50	Wash, 20 lks. wide, course S. 20° E.
80.12	The cor. of secs. 20, 21, 28 and 29. Land, rolling desert. Soil, 3rd rate, gravelly. Timber, palo verde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
	N. $0^{\circ} 02'$ W., bet. secs. 20 and 21. Over nearly level desert land, thru scattered timber.
12.70	Wash, 20 lks. wide, course S. 60° E.
18.90	Enter mountains, bear SW. and E.; asc. 350 ft. over SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to rock, with a stone, $8 \times 5 \times 4$ ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 4 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \uparrow \\ \text{S } 20 \quad \text{S } 21 \\ \hline 1942 \end{array}$
	Asc. 30 ft. over SE. slope.

.142.

Subdivision of T. 5 N., R. 11 W.

Chains	
41.12	Spur, slopes S.60°E.; desc. 245 ft. over broken NE.slope.
55.40	Wash, 20 ft. deep, 50 lks. wide, course SE: from N., at junction with wash from NW.; asc. 53 ft. along E. side of wash.
62.50	Mouth of ravine from E.; leave wash course S. from N.30°W. Asc. 300ft. over broken S. slope.
75.00	Short spur, slopes W.; asc. 50 ft. over broken SW.slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, with a stone, 6x4x3 ins., mkd. with a cross (+), deposited at the base and in a mound of stone, 5ft. base, to top, for cor. of secs. 16,17,20 and 21, with brass cap mkd.
	T5NR11W S 17 S 16 S 20 S 21 .1942.
	Land, mountainous. Soil, gravelly and rocky, 3rd and 4th. rates. Timber, palo verde and ironwood. Undergrowth, creosote brush, ocotilla and cacti.
	S. 89° 58' E., on random line, bet. secs. 16 and 21.
40.00	Set temp. ¼ sec. cor.
80.18	A point 5 lks. N. of the cor. of secs. 15,16,21 and 22. Thence, N. 89° 56' W., on true line, bet. secs. 16 and 21. Over mountainous land, thru scattered timber.
1.00	Wash, course SE.; asc. 100 ft. over SE. slope.
4.20	Spur, slopes S.30°E.; desc. 235 ft. over SW. slope.
32.90	Wash, S.20°E. 2 chs. thence course SE.; asc. 225 ft. over broken E. slope.
34.80	Trail, bears S.10°E. and N.
40.09	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap. mkd.
	¼ S 16 S 21 1942
	of stone, 3 ft. base, 2 ft. high, N. of cor. raise a mound
	From ¼ sec. cor., a prospect tunnel, bears S., 1.50 chs. dist.
	Asc. 275 ft. over E. slope.
44.34	NE. end sheet iron cabin, bears S.16½°E.

Subdivision of T. 5 N., R. 11 W.

Chains.	
45.30	Spur, slopes SE.; thence along broken S. slope.
61.20	Wash, course S.10°E.; asc. 90 ft. over E. slope.
65.13	Spur, slopes S.; U.S.L.M. No. 3554 A & B, bears N.53°00'W., 11.44 chs. dist.; an iron pipe, 1½ in. diam., 3 ft. above and firmly set in a mound of stone, mkd. USLM No 3554 A & B. The NE. end of sheet iron cabin, bears S.39½°E.
67.40	Hillside canyon, 100 ft. deep, 1 ch. wide, drains S.30°W.; desc. 195 ft.
80.18	The cor. of secs. 16,17,20 and 21. Land, mountainous. Soil, rocky, 4th. rate. Timber, palo verde and ironwood. Undergrowth, catclaw, creosote brush, ocotillo and cacti.
	N. 0° 02' W., bet. secs. 16 and 17. Over mountainous land, asc. 765 ft. over broken, rocky, SW. slope.
17.00	Leave area of rock ledges.
25.00	Spur, slopes S.20°E.; asc. 85 ft. over SE. slope.
32.90	Spur, slopes S.60°W. from N.; asc. 50 ft. along spur.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock; with a stone, 9x6x4 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone 4 ft. base, to top, for ¼ sec. cor., with brass cap mkd. S 17 S 16 1942
	Asc. 50 ft. over SE. slope.
49.50	Divide, bears N. 85° E. and W.; desc. 150 ft. over N. slope
54.20	Enter ravine, drains N. from S.30°W.; desc. 200 ft. along bottom of ravine.
61.00	Leave ravine, bears N. 10°E.; desc. 510 ft. over broken N. slope.
80.00	True point for cor. falls on a precipitous slope, a place unsuitable for a permanent cor. For witness cor. set, see line bet. secs. 8 and 9. Land, rocky, 4 th. rate. Soil, mountainous. Timber, paloverde and ironwood; undergrowth, creosote brush, catclaw, ocotillo and cacti.

Subdivision of T. 5 N., R. 11 W.

Chains. S. 89° 56' E., on random line, bet. secs. 9 and 16.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 80.36 A point 4 lks. S. of the cor. of secs. 9, 10, 15 and 16.
 Thence, N. 89° 58' W., on true line, bet. secs. 9 and 16.
 Over mountainous land; asc. 180 ft. over steep SE. slope.
 4.95 Spur, slopes S. 50° E.; desc. 50 ft. along S. slope.
 11.90 Hillside drain, course S. 60° E.; asc. E. slope 230 ft.
 21.00 Ridge, bears S. 60° W., 2.00 chs. dist., thence SW., from NE.; desc. 495 ft. along N. slope.
 38.50 Spur, slopes N.; desc. 75 ft.

40.18 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{S 9}{S 16}$$

1942

raise a mound

of stone, 3 ft. base, .2 ft. high, N. of cor.

Desc. 75 ft. over NW. slope.

42.50 Wash, course N. 10° W.

52.00 Spur, slopes N. 30° W., desc. 550 ft. over W. slope.

67.30 Wash, course N. 30° W., thence along N. slope.

74.00 Wash, course N.

80.36 The true point for cor. of secs. 8, 9, 16 and 17.

For witness cor. set see line bet. secs. 8 and 9.

Land, mountainous, Soil, rocky, 4 th. rate.

Timber, paloverde; Undergrowth, oak and creosote brush, catclaw and cacti.

From true point for cor. of secs. 8, 9, 16 and 17,

N. 0° 02' W., bet. secs. 8 and 9.

Over mountainous land, desc. 180 ft. over N. slope.

0.60 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. of secs. 8, 9, 16 and 17, with brass cap mkd.

$$\frac{T5N R11W}{S 8 | S 9}$$

$$\frac{S 17 | S 16}{1942}$$

WC

raise a mound

of stone, 2½ ft. base, 1½ ft. high, W. of cor.

Subdivision of T. 5 N., R. 11 W.

324

Chains.	
7.80	Wash, 25 ft. deep, 50 lks. wide, course N.80°W.; asc. 370 ft. over broken, rocky, SW. slope.
37.60	Spur, slopes N.70°W.; desc. 50 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} \uparrow \\ S\ 8\ \ S\ 9 \\ 1942 \end{array}$ </div> <p style="text-align: right; margin-right: 100px;">raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Desc. 285 ft. over NE. slope.</p>
52.60	Wash, course N.20°W.; desc. 135 ft. along W. slope.
75.20	Spur, slopes W.; desc. 80 ft. over NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground, with a stone, 8x8x3 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 4 ft. base to top, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.
	<div style="text-align: center;"> <p>T5NR11W.</p> $\begin{array}{c} S\ 5\ \ S\ 4 \\ S\ 8\ \ S\ 9 \\ 1942 \end{array}$ </div> <p>Land, mountainous. Soil, rocky, 3rd and 4th. rates. Timber, paloverde and ironwood. Undergrowth, creosote brush, catclaw and cacti.</p>
	S. 89° 58' E., on random line, bet. secs. 4 and 9.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.22	A point 19 lks. S. of the true point for cor. of secs. 3, 4, 9 and 10. For witness cor. set see line bet. secs. 9 and 10.
	<p>Thence,</p> <p>S. 89° 54' W., on true line, bet. secs. 4 and 9.</p> <p>Over mountainous land, asc. 55 ft. over broken S. slope.</p>
3.70	Top of ascent, desc. 440 ft. along broken S. slope.
33.40	Spur, slopes SW.; desc. 175 ft. over broken SW. slope.
40.11	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, with a stone, 10x5x4 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 5 ft. base to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \cdot S\ 4 \\ S\ 9 \\ 1942 \end{array}$ </div>
50.075	Intersect line 2-3, Mineral Survey No. 4120, Valley Stone Placer, at a point S. 18°36' E., 15.41 chs. dist. from Cor. No. 2; an iron post, 1 in. diam., 12 ins. above a mound

Subdivision of T. 5 N., R. 11 W.


Chains.

of stone, with a brass cap mkd.

VSP

4120

From the same point, Cor. No. 3, Mineral Survey No. 4120, Valley Stone Placer, bears S. 18°36'E., 19.20 chs. dist.; an iron post, 1 in. diam., 12 ins. above a mound of stone, with brass cap mkd.



Continue descent of 225 ft. over broken SW. slope.

58.00 Enter wash, 40 yds. wide, course W. from S. 80° E.

62.00 Leave wash, course N. 20° W.


63.20 Old road, bears N. 20° W. and S. 30° E.

70.98 Intersect line 6-1, Mineral Survey No. 4120, Valley Stone Placer, at a point S. 18°39'E., 11.525 chs. dist., from Cor. No. 1; an iron post, 1 in. diam., 12 ins. above a mound of stone, with brass cap mkd.

VSP

4120

From the same point, Cor. No. 6, Mineral Survey No. 4120, Valley Stone Placer, bears S. 18°39'E., 23.005 chs. dist.; an iron post, 1 in. diam., 7 ins. above a mound of stone, with brass cap mkd.



79.60 Spur, slopes N.; desc. 6 ft. over W. slope.

80.22 The cor. of secs. 4, 5, 8 and 9.

Land, mountainous.

Soil, gravelly and rocky, 3rd and 4th rates.

Timber, paloverde and ironwood.

Undergrowth, creosote brush, catclaw, ocotilla and cacti.

N. 0° 18' W., on random line, bet. secs. 4 and 5.

40.00 Set temp. sec. cor.

82.27 A point 23 yds. W. of the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.; described in the field notes of the S. Bdy. of T. 6 N., R. 11 W., surveyed under this group,

Thence,

S. 0° 08' E., on true line, bet. secs. 4 and 5.

Subdivision of T. 5 N., R. 11 W.

Chains	Over rolling desert land, thru scattered timber.
4.80	Wash, 25 lks. wide, course N.20°W.
30.90	Old road, bears S.20°E. and N.20°W.
42.27	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \uparrow \\ S \ 5 \ \ S \ 4 \\ 1942 \end{array}$
	raise a mound
	of stone, 2½ ft. base, 1½ ft. high, W. of cor.
56.90	Wash, course NW., 40 lks. wide; asc. 145 ft. over N. slope.
71.70	Spur, slopes N.80°E. from S.; desc. 90 ft. over E. slope.
77.50	Saddle in same spur, bears N th . and SW.; asc. 30 ft. over NW. slope.
82.27	The cor. of secs. 4,5,8 and 9.
	Land, rolling desert. Soil, sandy and gravelly, 3rd. and 4th. rates. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
	From the cor. of secs. 28,29,32 and 33.
	West, on true line, on sectional correction line, bet. secs. 29 and 32.
	Over rolling desert land.
1.80	Wash, 5 ft. deep, 20 lks. wide, course SW.
13.10	Old road, bears NW. and SE.
39.95	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, over a cross (+) mkd. on bed-rock and in a mound of stone, 5 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \ S \ 29 \\ \frac{1}{4} \ S \ 32 \\ 1942 \end{array}$
	From this point, a house, bears N.1°36'E.
	Cor. stands on S. slope of knoll, bears N. and S.; 10chs. long.
47.75	Wash, 10 lks. wide, course SE.
63.30	Wash, 6 ft. deep, 30 lks. wide, course S.
79.90	At this point, which is N. 0°.03' W., 79.88 chs. dist. from the standard cor. of secs. 31 and 32, on S. bdy. of Tp.,
	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to rock, and in a mound of stone, 4 ft. base, to top, for cor. of secs. 29,30,31 and 32, with brass cap mkd.
	$\begin{array}{c} T5NR11W \\ S \ 30 \ \ S \ 29 \\ S \ 31 \ \ S \ 32 \\ 1942 \end{array}$

Subdivision of T. 5 N., R. 11 W.

Chains.	
	<p>Land, rolling desert. Soil, sandy and gravelly, 3rd and 4th. rates. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.</p>
	<p>From the standard cor. of secs. 31 and 32, on S. bdy. of Tp. N. 0° 03' W., on true line, bet. secs. 31 and 32. Over nearly level desert land.</p>
17.40	Wash, 15 lks. wide, course S. 20° E.
26.60	Wash, 10 lks. wide, course S. 30° E.
39.88	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	<p>S 31 S 32 1942</p>
	<p>raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p>
79.00	Wash, 10 lks. wide, 4 ft. deep, course S. 30° E.
79.88	The cor. of secs. 29, 30, 31 and 32.
	<p>Land, nearly level. Soil, sandy and gravelly, 3rd and 4th. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.</p>
	<p>West, on true line, on sectional correction line, bet. secs. 30 and 31. Over, rolling land.</p>
0.80	Wash, 3 ft. deep, 20 lks. wide, course SE.
9.80	4 strand barbed wire fence, bears N. and S.
24.30	Wash, 8 ft. deep, 1.00 ch. wide, course SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, and in mound of stone, 3 ft. base, to top, for ¼ sec. cor., with brass cap mkd.
	<p>¼ $\frac{S\ 30}{S\ 31}$ 1942</p>
51.85	Spur, slopes SW.
54.10	Wash, 5 ft. deep, 30 lks. wide, course SW.
56.80	Old road, bears SW. and NE.
60.80	Wash, 5 ft. deep, 30 lks. wide, course S.
68.80	Foot of rocky SE. slope, asc. 60 ft.
79.14	The cor. of secs. 30 and 31, on the W. bdy. of the Tp.; described in the field notes of the E. bdy. sec. 36, T. 5 N., R. 12 W., resurveyed under this group.

Subdivision of T. 5 N., R. 11 W.

Chains.

Land, rolling desert.
Soil, sandy, gravelly and rocky, 3rd. and 4th. rates.
Timber, paloverde and ironwood.
Undergrowth, ocotillo, creosote brush and cacti.

From the cor. of secs. 29, 30, 31, and 32
N. $0^{\circ} 03'$ W., on true line, bet. secs. 29 and 30.

Over rolling desert land, asc. 90 ft. over S. slope.

- 3.86 Top of cliff, 50 ft. high, bears E. and NW.; asc. 90 ft.
- 12.60 Top of same cliff, 50 ft. high, bears SW. and NE.; desc. NW. slope, 130 ft.
- 19.15 Wash, 10 ft. deep, 40 lks. wide, course SW.; asc. slight S. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam.; 16 ins. in the ground, and in a mound of stone, 5 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd:

↑
S 30 | S 29
↓
1942

- 48.50 Old road, bears NE. and SW. 1 ch. to road, bears N. and SW.
- 59.50 Same road, bears NE. and SW.
- 60.00 Same road, bears SE., thence alongside same.
- 63.50 Low saddle, bears NW. and SE.
- 67.00 Same road, bears NW. and SE. Thence along W. bank of wash.
- 74.50 Wash, 10 ft. deep, 50 lks. wide, course S. from NW.; asc. 175 ft. over steep, broken SW. slope.
- 80.00 True point for cor. of secs. 19, 20, 29 and 30, falls on face of cliff, 40 ft. high, bears SE., 10 lks., and N., a place unsuitable for a permanent cor. For witness cor. set see line bet. secs. 19 and 20.

Land, rolling desert.
Soil, 3rd. and 4th. rates.
Timber, palo verde and ironwood.
Undergrowth, creosote brush, ocotillo and cacti.

East, on random line, bet. secs. 20 and 29.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 79.80 A point 4 lks. S. of cor. of secs. 20, 21, 28 and 29.
Thence,
S. $89^{\circ} 58'$ W., on true line, bet. secs. 20 and 29.
Over mountainous land,
- 9.40 Wash, 10 lks. wide, course S. 20° W.; asc. 190 ft. over SE. slope.
- 18.80 Spur, slopes S. 20° W., desc. 75 ft. over broken W. slope.

BOOK 4004

Subdivision of T. 5 N., R. 11 W.

Chains.	
25.80	Wash, course SW.; asc. 300 ft. over broken SE. slope.
38.80	Set an iron post, 3 ft. long, 1 in. diam., over a cross (+) mkd. on a rock ledge, with a stone, 9x6x4 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 6 ft. base, to top, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$WC \frac{1}{4} \frac{S \ 20}{S \ 29}$ 1942
38.90	Spur, slopes SE.; desc. 50 ft. over SW. slope.
39.90	True point for $\frac{1}{4}$ sec. cor., falls on precipitous slope, a place unsuitable for a permanent cor. Desc. 20 ft. over SW. slope.
40.45	Wash, course SE.; asc. 215 ft. over E. slope.
48.60	Spur, slopes S.20°W., desc. 440 ft. over NW. slope.
64.50	Wash, 30 lks. wide, course S.; asc. 245 ft. over SE. slope.
65.00	Road, bears S., and N. approximately 10.00 chs. to end.
75.00	Rocky spur, slopes S.; desc. 150 ft. over SW. slope:
79.80	True point for cor. of secs. 19, 20, 29 and 30. For witness cor. set see line bet. secs. 19 and 20. Land, mountainous. Soil, rocky, 4th. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush; ocotilla and cacti.
	West, on random line, bet. secs. 19 and 30.
46.00	Set temp. $\frac{1}{4}$ sec. cor.
79.04	A point 23 lks. S. of the cor. of secs. 19 and 30, on the W. bdy. of the Tp.; described in the field notes of the E. bdy. sec. 25, T. 5 N., R. 12 W., surveyed under this group. Thence, S. 89° 50' E., on true line, bet. secs. 19 and 30. Over mountainous land; desc. 90 ft. over NE. slope.
3.80	Wash, 4 ft. deep, 30 lks. wide, course SE.; asc. 20 ft.
6.35	Spur, slopes SE.; desc. 590 ft. over steep, rocky, E. slope.
25.70	Wash, near head, 15 lks. wide, course NE:
33.35	Spur, slopes NE.; desc. rocky NE. slope, 100 ft.
39.04	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S \ 19}{S \ 30}$ 1942
	raise a mound of stone, 3½ ft. base, 2 ft. high, N. of cor.

Subdivision of T. 5 N., R. 11 W.

Chains

- 44.34 Wash, 15 ft. deep, 50 lks. wide, course NE.
- 57.35 Spur, slopes N. 10°E.; desc. 60 ft.
- 58.04 A mine dump, bears N. 37½°W., a second mine dump, bears N. 41¾°W.
- 63.30 Old road, bears SE. and NW.
- 69.70 Wash, 20 ft. deep, 50 lks. wide, course SE.; asc. 135 ft. over broken SW. slope.
- 79.04 True point for cor. of secs. 19, 20, 29 and 30. For witness cor. set see line bet. secs. 19 and 20.
- Land, rough mountain;
Soil, 4th. rate.
Timber, paloverde and ironwood.
Undergrowth, creosote brush and cacti.
-
- N. 0° 03' W., bet. secs. 19 and 20.
- Over rough mountainous land.
- 1.00 Set an iron post, 3 ft. long, 2 ins. diam., over a cross (+) mkd. on bed rock, and in a mound of stone, 6 ft. base, to top, for witness cor. of secs. 19, 20, 29 and 30, with brass cap mkd.
- T5NR11W
S 19 | S 20
S 30 | S 29
W C
1942
- Asc. 190 ft. along rocky SW. slope.
- 6.11 A mine dump, bears N. 53½°W.; a second mine dump, bears N. 58¼°W.; and a third mine dump, bears N. 60°W.
- 16.10 Rocky spur, slopes SE.; desc. 50 ft. over NE. slope.
- 23.30 Head of wash, course SE.; asc. 70 ft. over SE. slope.
- 25.00 Spur slopes E.; asc. 340 ft. along rough SE. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, for ¼ sec. cor., with brass cap mkd.
- ↑
S 19 | S 20
1942
- Asc. 250 ft. over steep rocky SE. slope.
- 50.80 Rocky point, slopes SE.; desc. 30 ft. over rocky SE. slope.
- 55.75 Head of wash, course SE.; asc. 210 ft. over rocky S. slope.
- 63.19 Spur, slopes N. 80°W., 3 ch. to top of cliff, bears N., and S. then E.; desc. 50 ft. over N. slope.
- 66.00 Wash, course NW.; asc. 270 ft.
- 68.85 Top of vertical cliff, 150 ft. high, bears E., and W. 4 lks. to near vertical W. face, which bears N. for 50 lks.

Subdivision of T. 5 N., R. 11 W.

Chains.

69.15 Top of vertical cliff, bears E. and S. Thence over a series of hillside drains, course W. on steep rocky W. slope, desc. 395 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in the ground, and in a mound of stone, 6 ft. base, to top, for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.

T5NR11W
S 18 | S 17
S. 19 | S. 20
1942

Land, rough mountain.
Soil, rocky, 4th. rate.
Timber, paloverde; undergrowth, creosote brush, cacti.

N. 89° 58' E., on random line, bet. secs. 17 and 20.

40.00 Set temp. 4 sec. cor.

80.06 Intersect cor. of secs. 16, 17, 20 and 21.

Thence,

S. 89° 58' W., on true line, bet. secs. 17 and 20.

Desc. 110 ft. over steep W. slope.

6.00 Wash, 10 lks. wide, course S. 5 chs. thence S. 20° E.; asc. 250 ft. over steep abrupt cliffs facing E.

14.00 Spur, slopes S. 60° E.; asc. 565 ft. along S. slope.

30.50 Spur, slopes SE.; desc. 140 ft.

39.00 Divide, bears NE, and S. 60° W.; desc. 75 ft. over W. slope.

40.03 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, with a stone, 14x10x5 ins., mkd. with a cross (+), deposited at the base, and in a mound of stone, 4 ft. base, to top, for 4 sec. cor., with brass cap mkd.

S 17
S. 20
1942

Desc. 96 ft. over NE slope.

45.00 Foot of descent; asc. 105 ft. over SE. slope.

50.50 Spur, slopes N. 10° E.

53.50 Hillside drain, course N. 10° E.; asc. 200 ft. over NE. slope.

73.00 Divide, bears NW. and SE.; desc. 330 ft. over steep, rocky, W. slope.

80.06 The cor. of secs. 17, 18, 19 and 20.

Land, mountainous.
Soil, 4th. rate.
Timber, paloverde; undergrowth, creosote brush and cacti.

N. 89° 50' W., on random line, bet. secs. 18 and 19.

Subdivision of T. 5 N., R. 11 W.

Chains.	
40.00	Set temp. $\frac{1}{4}$ sec. cor.
78.56	A point, 9 lks. N. of cor. of secs. 18 and 19, on the W. bdy. of the Tp.; described in the field notes of the E. bdy. sec. 24, T. 5 N., R. 12 W.; surveyed under this group. Thence, S. $89^{\circ} 54'$ E., on true line, bet. secs. 18 and 19. Over mountainous land, desc. 190 ft. over NE. slope.
16.65	Enter wash, 20 ft. deep, 20 lks. wide, course E. from NW. Thence along N. bank of same.
24.70	Same wash, course N. 20° E.
34.50	Junction of same wash from NW. and wash from N., 20 ft. deep, 40 lks. wide, course S.; asc. 80 ft.
38.56	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} \frac{1}{4} \text{ S } 18 \\ \frac{1}{4} \text{ S } 19 \\ \hline 1942 \end{array}$
43.55	Spur, slopes S.; desc. 60 ft. along rolling S. slope.
55.85	Wash, 10 ft. deep, 30 lks. wide, course S.; asc. 510 ft. over steep NW. slope.
71.74	The third mine dump, bears S. 57° W.
78.56	The cor. of secs. 17, 18, 19 and 20. Land, mountainous. Soil, 4 th. rate. Timber, paloverde and ironwood. Undergrowth, creosote brush and cacti.
	N. $0^{\circ} 03'$ W., bet. secs. 17 and 18. Over mountainous land, along rough W. slope.
3.70	Divide, bears W. and E.; desc. 50 ft. along rocky W. slope.
7.55	Spur, slopes NW.; desc. 285 ft. along NE. slope.
24.50	Wash, 3 ft. deep, 10 lks. wide, course NW.; desc. 170 ft. over NW. slope.
35.30	Wash, 7 ft. deep, 20 lks. wide, course W.; thence over rolling NW. slope.
39.50	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} \frac{1}{4} \\ \text{W} \text{C} \\ \text{S } 18 \text{S } 17 \\ \hline 1942 \end{array}$ raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

54.

Subdivision of T. 5 N., R. 11 W.

Chains.	
40.00	True point for $\frac{1}{4}$ sec. cor. falls in wash, 10 ft. deep, 40 lks. wide, course NW., a place unsuitable for a permanent cor.
65.30	Four strand barbed wire fence, bears N. $54^{\circ}39'$ W. and S. $54^{\circ}39'$ E.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.
	<p style="text-align: center;">T5NR11W S 7 1 S 8 S 18 1 S 17 1942</p> <p style="text-align: right;">raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high W. of cor.</p>
	<p>Land, mountainous and rolling. Soil, 3rd and 4th. rates. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotilla and cacti.</p>
	N. $89^{\circ}58'$ E., on random line, bet. secs. 8 and 17.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.22	A point 28 lks. N. of the true point for cor. of secs. 8, 9, 16 and 17. For witness cor. set see line bet. secs. 8 and 9.
	Thence,
	N. $89^{\circ}50'$ W., on true line, bet. secs. 8 and 17.
	Over mountainous land, asc. 155 ft. along N. slope.
19.00	Spur, slopes NW.
23.00	Side hill drain, course N.; asc. 150 ft. over E. slope.
34.00	Spur, slopes N. 60° E.; desc. 190 ft. over NW. slope.
40.11	True point for cor. falls on sloping ledge of rock, a place unsuitable for a permanent cor.
40.31	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd..
	<p style="text-align: center;">$\frac{1}{4}$ $\frac{S 8}{S 17}$ W C 1942</p>
	<p style="text-align: right;">raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.</p>
	Desc. 145 ft. over N. slope.
45.00	Spur, slopes N. 30° W.; desc. 300 ft. over W. to NW. slope.
62.00	Wash, 5 ft. deep, 40 lks. wide, course N. 35° W.; asc. 38 ft.
69.00	Spur, slopes N. 60° W., desc. 140 ft. over NW. slope.
78.00	Wash, 10 lks. wide, course N. 10° W.
80.22	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, mountainous; soil, 3rd and 4th. rates. Timber, paloverde; undergrowth creosote brush and cacti.</p>

Subdivision of T. 5 N., R. 11 W.

Chains.	N. 89° 54' W., on random line, bet. secs. 7 and 18,
40.00	Set temp. $\frac{1}{4}$ sec. cor.
78.46	A point 7 lks. N. of the cor. of secs. 7 and 18 on the W. bdy. of the Tp.; described in the field notes of the E. bdy. of sec. 13, T. 5 N., R. 11 W., resurveyed under this group.
	Thence,
	S. 89° 57' E., on true line, bet. secs. 7 and 18.
	Over rolling desert land, thru scattered timber.
1.15	Wash, 6 ft. deep, 20 lks. wide, course NE.
11.00	Wash, 10 ft. deep, 30 lks. wide, course N.
24.00	Wash, 15 ft. deep, 30 lks. wide, course NW.
36.60	Spur, slopes NW..
38.46	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{S 7}{S 18}$ 1942
	raise a mound
	of stone, 3 ft. base, 2 ft. high, N. of cor.
40.25	Small wash, course NW.
52.75	Low spur, slopes NW.
58.96	Four strand barbed wire fence, bears N. 54° 39' W. and S. 54° 39' E.
64.16	Mine shaft, 6x8 ft., 18 ft. deep to water, bears S., 85 lks.
64.95	Wash, 30 lks. wide, 10 ft. deep, course NW.
78.46	Cor. of secs. 7, 8, 17 and 18.
	Land, rolling desert. Soil, 3rd rate, sandy and gravelly. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
	N. 0° 03' W., bet. secs. 7 and 8.
	Over rolling desert land, slopes NW.
3.80	Wash, 10 lks. wide, course N. 60° W.
16.70	Wash, 30 lks. wide, course W.
31.30	Wash, 30 lks. wide, course N. 70° W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to rock, with a stone, mkd. with a cross (+), 8x6x2 ins., deposited at the base, and in a mound of stone, 3 $\frac{1}{2}$ ft. base, to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{S 7}{S 8}$ 1942

56. BOOK 4324

Subdivisions of T. 5 N., R. 11 W.

Chains	
43.30	Wash, 10 lks. wide, course N. 70°W.
66.05	Road, bears N.20°W., and S. 60°E. about 60 chs. to end.
72.50	Wash, 20 lks. wide, course N.80°W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for cor. of secs. 5,6,7 and 8, with brass cap mkd.
	T5NR11W S 6 S 5 S 7 S 8 1942
	raise a mound of stone., 2 ft. base, 1½ ft. high, W. of cor.
	Land, rolling. Soil, 3 rd rate, sandy and gravelly. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
	S. 89° 50' E., on random line, bet. secs. 5 and 8.
40.00	Set temp. ¼ sec. cor.
80.16	A point 17 lks. N. of the cor. of secs. 4,5,8 and 9.
	Thence, N. 89° 43' W., on true line, bet. secs. 5 and 8.
	Over rolling desert land, desc. 115 ft. over W. slope.
8.35	Wash, 30 lks. wide, course NW.; desc. 50 ft. over W.slope.
17.15	Wash, 10 lks. wide, course N. 70°W.
33.55	Spur, slopes NW.
40.08	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	S 5 ¼ S 8 1942
	raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
46.35	Wash, 20lks. wide, course N.80°W
58.55	Wash, 10 lks. wide, course NW.
68.25	Wash, 30 lks. wide, course N.30°W.
80.16	The cor. of secs. 5,6,7 and 8.
	Land, rolling desert. Soil, 3rd rate, sandy and gravelly. Timber, paloverde and ironwood. Undergrowth, creosote brush, ocotillo and cacti.
	N. 89° 57' W., on random line, bet. secs. 6 and 7.
40.00	Set temp. ¼ sec. cor.

Subdivision of T. 5 N., R. 11 W.

Chains.

- 78.34 A point 21 lks. N. of the cor. of secs. 6 and 7 on the W. bdy. of the Tp.; described in the field notes of the E. bdy. of sec. 12, T. 5 N., R. 12 W., resurveyed under this group.
- Thence,
N. 89° 54' E., on true line, bet. secs. 6 and 7.
Over rolling desert land sloping NW.
- 4.80 Wash, 30 lks. wide, 5 ft. deep, course NW.
- 15.00 Wash, 40 lks. wide, 8 ft. deep, course NW
- 38.34 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$ $\frac{S 6}{S 7}$
1942
- raise a mound
- of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
- 48.20 Wash, 3 ft. deep, 30 lks. wide, course NW.
- 53.85 Old road, bears NW and SE. S18
- 78.34 The cor. of secs. 5, 6, 7 and 8.
- Land, rolling desert.
Soil, 3 rd. rate, sandy and gravelly.
Timber, paloverde and ironwood.
Undergrowth, creosote brush, ocotilla and cacti.
-
- N. 0° 09' W., on random, bet. secs. 5 and 6.
- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 81.92 A point 30 lks. W. of the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.; described in the field notes of the S. bdy. of T. 6 N., R. 11 W., surveyed under this group.
- Thence,
S. 0° 04' W., on true line, bet. secs. 5 and 6.
Over rolling desert land, thru thick undergrowth.
- 8.00 Wash, 10 lks. wide, course NW.
- 21.70 Wash, 20 lks. wide, course NW..
- 32.10 Wash, 10 lks. wide, course W.
- 41.92 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$
S 6 | S 5
1942
- raise a mound
- of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
- 43.80 Wash, 10 lks. wide, course W.

BOOK 444

Subdivision of T. 5 N., R. 11 W.

Chains.

- 49.30 Wash, 30 lks. wide, course N. 85° W.
- 55.30 Wash, 15 lks. wide, course N. 70° W.
- 71.90 Wash, 40 lks. wide, course W.
- 81.92 The cor. of secs. 5, 6, 7 and 8.
- Land, rolling desert.
Soil, 3rd rate, sandy and gravelly.
Timber, paloverde and ironwood.
Undergrowth, creosote brush, ocotilla and cacti.

Final Test of Solar Attachment.

May 3, 1942, bet. the hours of 7:30 to 10:30 a.m., and 1:30 to 4:30 p.m., we make the proper settings on the arcs of the solar attachments and ascertain that the resulting orientation of the instruments, when compared with the meridian established by Polaris observation, have a maximum error of less than 1'30".

General Description.

The Harquahala mountains, with a general bearing of S. 60° W. and N. 60° E. through the township from the NE. cor., and with a ridge extending south along the E. bdy., occupy the larger portion of the township. Their highest point, approximately 12 chains east of the NE. corner of the township, is about 5,670 feet above sea level. They divide the drainage of the township, which is NW. in the NW. portion and south to SW. in the remainder of the township. The mountains are rough and rocky with third and fourth rate soil, the remainder of the township is rolling desert land cut by numerous washes originating in the mountains, with third rate gravelly and sandy soil. The lowest portion of the township is along the south bdy. of secs. 32 and 33 with an approximate elevation of 1700 feet above sea level. A scattered growth of palo verde and ironwood over all but the higher elevations and a few mesquite along the larger washes, are the only trees in the township.

The mountainous area of the township is characteristically mineral bearing as is evidenced by numerous prospects throughout the area. The more extensive workings, with shafts and tunnels, are in the N $\frac{1}{2}$ sec. 1, the W $\frac{1}{2}$ sec. 19, the SE $\frac{1}{4}$ sec. 23, the NE $\frac{1}{4}$ sec. 25, and the N $\frac{1}{2}$ sec. 29. Mineral Survey No. 4120 is in secs. 4 and 9 and Mineral Survey No. 3554 A and B in sec. 16. The mineral indications are gold, copper, silver and lead. There are no mining operations being carried out at the present time and it is evident that no operating of any extent has been done for ten or more years.

The water found in the township was a shallow well, about nine chains east of the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, in the bed of a wash, which also contains intermittent pools of water from this point south through sec. 12 to the center of sec. 13. Water was also found in a shaft in the NE $\frac{1}{4}$ sec. 18.

There are no settlements and no settlers in the township at the present time. The nearest settlement is Wenden, situated about 5 $\frac{1}{2}$ miles west of the NW. cor. of the township on U.S. Highway Nos. 60 and 70 and the A.T. & S. Fe RR. The unimproved desert roads in the NW. portion of the township bear NW. about four miles from the township bdy. to different points, east of Wenden, on U.S. Highway Nos. 60

General Description.

Chains.

and 70. Those roads in the remainder of the township bear SW., about four miles from the south bdy., to a point on the graded Salome- Buckeye road approximately sixteen miles SE. of Salome.

The principal interests in the township are mining and stock grazing, the latter limited to the extent to which water can be developed.

The mean magnetic declination for the township is $15\frac{1}{2}^{\circ}$ E.

4-680
(Revised May 1934)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

BOOK 4824

FIELD ASSISTANTS

NAMES	CAPACITY
John Boggs.	Principal Assistant.
Robert M. Warren.	Principal Assistant.
George B. McDevitt.	Principal Assistant.
Robert F. Shrigley.	Principal Assistant.
Mike Knezevich.	Chainman.
Glenn P. Snyder.	Chainman.
Ralph L. Lee.	Chainman.
Ralph L. Lee.	Flagman.
Robert F. Shrigley.	Flagman.
Gladwyn Gregory.	Axeman.
George B. McDevitt.	Moundsman.

CERTIFICATE OF SURVEYOR

We, G. Marvin Litz, Junior Cadastral Engineer, and Bert E. Wakeman, Senior Engineering Aid, General Land Office, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th. day of October, 1941, received from the district cadastral engineer for Arizona, with assignment instructions dated December 22, 1941, and January 16, 1942, we have dependent-ly resurveyed the First Standard Parallel North, through Range 11 West, and a portion of Range 10 West, and surveyed the East boundary and subdivis-ional lines of Township 5 North, Range 11 West, of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~me~~ ^{us} and under ~~my~~ ^{our} direction; and that said ~~survey~~ ^{resurvey and} has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Glendale, Calif., August 11, 1942.
Phoenix, Ariz., November 23, 1942.

G. Marvin Litz
Junior Cadastral Engineer.
Bert E. Wakeman
Senior Engineering Aid,
General Land Office.

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colorado, April 16, 1945.

The foregoing field notes of the dependent resurvey of the First Standard Parallel North, through Range 11 West, and a portion of Range 10 West, and the survey of the East boundary and subdivis-ional lines of Township 5 North, Range 11 West, of the Gila and Salt River Meridian, in the state of Arizona, executed by G. Marvin Litz, Junior Cadastral Engineer, and Bert E. Wakeman, Senior Engineering Aid, General Land Office, under special instructions dated October 29, 1941, and assignment instructions dated Dec. 22, 1941, and Jan. 16, 1942, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the ~~survey~~ ^{resurvey and} therein described, are hereby approved.

[Signature]
Supervisor of Surveys.

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~