

Original

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

Book C

BOOK 4325

FIELD NOTES

Of the Resurvey of

The Subdivisional Lines of Township 17 South,

Range 14 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Raymond F. Moss,

Assistant Cadastral Engineer,

General Land Office.

Under special instructions dated February 5, 1941, which provided for the surveys included under Group No. 231, bearing the approval of the Commissioner of the General Land Office under date of February 15, 1941 and assignment instructions dated November 4, 1940

Survey commenced April 25, 19 41

Survey completed May 3, 19 41

4325

1A

BOOK 4825

INDEX DIAGRAM.

Township 17 South, Range 14 East.

6	45 5	31 4	23 3	15 2	8 1
44	43	31	23	15	7
7	42 8	30 9	22 10	14 11	7 12
41	40	29	21	13	6
18	39 17	28 16	20 15	12 14	5 13
38	3 8	2 8	20	12	5
19	37 20	27 21	19 22	11 23	4 24
35	35	26	18	11	3
30	34 29	25 28	17 27	10 26	2 25
33	33	25	17	9	2
31	32 32	24 33	16 34	8 35	1 36

Dependent Resurvey of the Subdivisional Lines

1B

of T. 17 S., R. 14 E.

4825

Chains

The resurveys herein described were executed by Raymond F. Moss, Assistant Cadastral Engineer, using Gurley transit No. 371537, property of the General Land Office.

For all preliminary data regarding instrument and equipment, observations for azimuth and latitude, and test of solar attachment, see the field notes of the boundaries of Townships 17 and 18 S., R. 14 E., resurveyed under this group.

Preliminary to the resurvey the lines of the original survey are retraced and diligent search is made for all original corners. Identified corners of the original survey are reestablished in their original positions. All lost corners are reestablished at proportionate positions, based on the record of the original survey. The retrace-ment data are thoroughly verified and only the true line notes are given here.

Reestablishment of the surveys executed by T.F. White, Deputy Surveyor in 1872.

From the cor. of secs. 1, 2, 35 and 36 on S. bdy. of the Tp. described in the field notes of the N. bdy. of T. 18 S., R. 14 E., resurveyed under this group.

N.0°09'E., on true line bet. secs. 35 and 36.

Over rolling desert land, through scattered timber and dense undergrowth.

- 8.80 Wash, 30 lks. wide, course NW.
- 18.80 Wash, 40 lks. wide, course N.65°W.
- 22.80 Wash, 10 lks. wide, course NW.
- 29.97 Wash, 10 lks. wide, course N.80°W.
- 39.00 Wash, 50 lks. wide, course NW.
- 40.26 Proportional distance.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$
- S 35 | S 36
- 1941
- from which
- A mesquite, 12 ins. diam., bears S.64 $\frac{1}{2}$ °E., 293 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.
- A mesquite, 8 ins. diam., bears S.60 $\frac{3}{4}$ °W., 36 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.
- 53.35 Drain, course W.
- 60.35 Center of wash, 150 lks. wide, course NW.
- 67.35 Wash, 20 lks. wide, course W.

2 Dependent Resurvey of the Subdivisional Lines
of T. 17 S., R. 14 E.

Chains																	
80.22	Fence, bears E. and W.																
80.52	At this point determined by the method of double proportion Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.																
	<table style="margin: auto;"> <tr><td>T 17</td><td>S</td><td>R 14</td><td>E</td></tr> <tr><td>S 26</td><td> </td><td>S 25</td><td></td></tr> <tr><td>S 35</td><td> </td><td>S 36</td><td></td></tr> <tr><td colspan="4" style="text-align: center;">1941</td></tr> </table>	T 17	S	R 14	E	S 26		S 25		S 35		S 36		1941			
T 17	S	R 14	E														
S 26		S 25															
S 35		S 36															
1941																	
	raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.																
	No bearing trees available.																
	Land, rolling. Soil, sandy, 2nd and 3rd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cacti.																
	From cor. of secs. 25 and 36 on E. bdy. of the Tp., which is an iron post, 2 ins. diam., mkd. and witnessed as described in the field notes of the resurvey of E. bdy. of Tp. N.89°49'W., on true line bet. secs. 25 and 36.																
	Over rolling desert land, through scattered timber and dense undergrowth.																
2.00	Enter sand wash, course NW.																
6.00	Leave wash.																
19.90	Wash, 10 lks. wide, course NW.																
22.40	Wash, 10 lks. wide, course NW.																
40.20	Proportional distance Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.																
	<table style="margin: auto;"> <tr><td>¼</td><td>S 25</td></tr> <tr><td></td><td>S 36</td></tr> <tr><td colspan="2" style="text-align: center;">1941</td></tr> </table>	¼	S 25		S 36	1941											
¼	S 25																
	S 36																
1941																	
	raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.																
	No bearing trees available.																
54.50	Wash, 30 lks. wide, 10 ft. deep, course N.60°W.																
80.40	The cor. of secs. 25, 26, 35 and 36.																
	Land, gently rolling. Soil, sandy, 2nd and 3rd rate. Timber, scattered mesquite; undergrowth, mesquite, sage, greasewood and cacti.																
	N.0°02'E., on true line bet. secs. 25 and 26.																
	Over rolling desert land, through scattered timber and dense undergrowth.																
15.68	Wash, 30 lks. wide, 2 ft. deep, course NW.																

of T. 17 S., R. 14 E.

Chains	
27.85	Wash, 80 lks. wide, 5 ft. deep, course N.80°W.
38.45	Road, bears N.80°W. and S.80°E.
40.26	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ $\begin{array}{c} S\ 26 \mid S\ 25 \\ 1941 \end{array}$ raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
58.80	Dim road, bears NW. and SE.
62.65	wash, 10 lks. wide, course NW.
80.52	At this point determined by the method of double proportion, Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd. $\begin{array}{c} T\ 17\ S\ R\ 14\ E \\ S\ 23 \mid S\ 24 \\ S\ 26 \mid S\ 25 \\ 1941 \end{array}$ raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Land, rolling. Soil, sandy, 2nd and 3rd rate. Timber, scattered mesquite; undergrowth, mesquite, sage, greasewood and cacti.
	From the cor. of secs. 24 and 25, on E. bdy. of the Tp., which is an iron post, 2 ins. diam., mkd. and witnessed as described in the field notes of the resurvey of the E. bdy. of Tp. N.89°21'W., on true line bet. secs. 24 and 25. Over gently rolling desert land, through scattered timber and dense undergrowth.
2.30	Wash, 80 lks. wide, 5 ft. deep, course N.60°W.
20.00	Wash, 10 lks. wide, course NW.
40.18 $\frac{1}{2}$	Proportional distance Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ $\begin{array}{c} S\ 24 \\ S\ 25 \\ 1941 \end{array}$ raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Chains No bearing trees available.

50.80 Wash, 20 lks. wide, course NW.

57.40 Wash, 20 lks. wide, course N.60°W.

80.37 The cor. of secs. 23, 24, 25 and 26.

Land, gently rolling.

Soil, sandy, 2nd and 3rd rate.

Timber, scattered mesquite; undergrowth, mesquite, sage, greasewood and cacti.

N.0°14'W., on true line bet. secs. 23 and 24.

Over gently rolling desert land, through scattered timber and dense undergrowth.

9.00 Wash, course N.80°W.

11.16 Dim road, bears N.80°W. and E.

40.26 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 23 | S 24

1941

from which

A mesquite, 5 ins. diam., bears N.37 $\frac{3}{4}$ °E., 81 lks. dist., mkd. $\frac{1}{4}$ S 24 B T.

A mesquite, 4 ins. diam., bears S.80 $\frac{1}{4}$ °W., 38 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.

41.00 Wash, 10 lks. wide, course N.60°W.

80.52 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.

T 17 S R 14 E

S 14 | S 13

S 23 | S 24

1941

raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

No bearing trees available.

Land, rolling.

Soil, sandy, 2nd and 3rd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood, sage, cacti and grass.

of T. 17 S., R. 14 E.

Chains From the cor. of secs. 13 and 24 on E. bdy. of the Tp., which is an iron post, 2 ins. diam., mkd. and witnessed as described in the field notes of the resurvey of the E. bdy. of Tp.

N.89°28'W., on true line bet. secs. 13 and 24.

Over rolling desert land, through scattered timber and dense undergrowth.

11.10 Wash, 20 lks. wide, 5 ft. deep, course N.10°W.

33.10 Wash, 30 lks. wide, 3 ft. deep, course N.30°W.

40.17 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 13

S 24

1941

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

No bearing trees available.

60.30 Drain, course N.80°W.

63.80 Wash, 20 lks. wide, course N.60°W.

70.68 Wash, 15 lks. wide, course NW.

80.34 The cor. of secs. 13, 14, 23 and 24.

Land, rolling.

Soil, sandy, 2nd and 3rd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cacti.

N.0°25 W., on true line bet. secs. 13 and 14.

Over rolling desert land, through scattered timber and dense undergrowth.

4.89 Wash, 10 lks. wide, course NW.

33.50 Wash, 10 lks. wide, course NW.

40.26 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 14 | S 13

1941

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

No bearing trees available.

80.52 At this point determined by the method of double proportion

6 6001 4025

Dependent Resurvey of the Subdivisional Lines

of T. 17 S., R. 14 E.

Chains Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 11,12,13 and 14, with brass cap mkd.

T 17 S R 14 E
S 11 | S 12
S 14 | S 13
1941

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

No bearing trees available.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood, cacti and sage.

From the cor. of secs. 12 and 13 on E. bdy. of the Tp., which is an iron post, 2 ins. diam., mkd. and witnessed as described in the official record of the resurvey of the E. bdy. of Tp.

N.89°35'W., on true line bet. secs. 12 and 13.

Over rolling desert land, through scattered timber and dense undergrowth.

25.00 Drain, course NW.

40.27½ Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼ S 12
S 13
1941

raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

No bearing trees available.

41.00 Wash, 10 lks. wide, course N.30°W.

50.20 Wash, 10 lks. wide, course NW.

67.55 Wash, 60 lks. wide, course N.30°W.

77.25 Road, bears N.70°W. and S.70°E.

80.55 The cor. of secs. 11,12,13 and 14.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood, sage and cacti.

Dependent Resurvey of the Subdivisional Lines

7

of T. 17 S., R. 14 E.

Chains N.0°19'W., on true line bet. secs. 11 and 12.

Over gently rolling desert land, through scattered timber and dense undergrowth.

.90 Road, bears N.55°W. and S.72½°E.

14.70 Wash, 10 lks. wide, course NW.; continue over series of small drains, course NW.

31.00 Wash, 10 lks. wide, course N.80°W.

40.26 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼
S 11 | S 12
1941

from which

A mesquite, 4 ins. diam., bears N.73½°E., 52 lks. dist., mkd. ¼ S 12 B T.

A mesquite, 4 ins. diam., bears S.34½°W., 98 lks. dist., mkd. ¼ S 11 B T.

65.80 Small wash, course NW.

80.52 At this point determined by the method of double proportion,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.

T 17 S R 14 E
S 2 | S 1
S 11 | S 12
1941

raise a mound
of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, gently rolling.

Soil, sandy, 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, greasewood, sage and cacti.

From the cor. of secs. 1 and 12 on E. bdy. of the Tp., which is an iron post, 2 ins. diam., mkd. and witnessed as described in the official record of the resurvey of the E. bdy. of Tp.

N.89°42'W., on true line bet. secs. 1 and 12.

Over gently rolling desert land, through scattered timber and dense undergrowth.

17.98 Wash, 30 lks. wide, course N.60°W.

40.31 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

Chains	$\frac{1}{4}$ S 1 S 12 1941
80.62	<p style="text-align: right;">raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, N. of cor.</p> <p>The cor. of secs. 1,2,11 and 12.</p> <p>Land, gently rolling. Soil, sandy, 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.</p>
27.32	<p>From the cor. of secs. 1,2,35 and 36 on N. bdy. of the Tp.: described in the field notes of the resurvey of the N. bdy. of T. 17 S., R., 14 E., resurveyed under this group.</p> <p>S.0°05'E., on true line bet. secs. 1 and 2.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>Wash, 10 lks. wide, course NW.</p>
40.24	<p>Proportional distance,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 2 S 1 1941</p>
41.22	<p style="text-align: right;">from which</p> <p>A mesquite, 8 ins. diam., bears S.61$\frac{3}{4}$°E., 37 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.</p> <p>A mesquite, 5 ins. diam., bears N.53°W., 106 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.</p> <p>Road, bears NW. and SE.</p>
80.50	<p>The cor. of secs. 1,2,11 and 12.</p> <p>Land, gently rolling. Soil, sandy loam, 1st rate; and gravelly, 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood, sage and cacti.</p>
3.10	<p>From the cor. of secs. 2,3,34 and 35 on S. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 18 S., R. 14 E.; resurveyed under this group.</p> <p>N.0°14'E., on true line bet. secs. 34 and 35.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>Wash, 50 lks. wide, course NW.</p>
10.50	<p>Wash, 80 lks. wide, course N.30°W.</p>

of T. 17 S., R. 14 E.

Chains	
19.25	Wash, 50 lks. wide, course NW.
29.55	Road, bears E. and S.80°W.
33.30	Drain, course W.
39.32	Road, bears N.44°W. and S. 44°E., from Sahuarita to Helvetia.
40.31	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 34 S 35 1941 from which A mesquite, 12 ins. diam., bears S.85 $\frac{1}{2}$ °E., 73 lks. dist., mkd. $\frac{1}{4}$ S 35 B T. A mesquite, 4 ins. diam., bears N.20°W., 72 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.
49.50	Wash, 20 lks. wide, course W.
54.70	Wash, 20 lks. wide, course N.80°W.
67.40	Wash, 20 lks. wide, course N.70°W.
80.62	At this point determined by the method of double proportion, Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd. T 17 S R 14 E S 27 S 26 S 34 S 35 1941 raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. Land, gently rolling. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.
	From cor. of secs. 25, 26, 35 and 36. S.89°46'W., on true line bet. secs. 26 and 35. Over gently rolling desert land, through scattered timber and dense undergrowth, along wire fence.
17.80	Wash, 100 lks. wide, course N.10°W.
40.22	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Chains	$\frac{1}{4} \begin{array}{l} \text{S } 26 \\ \text{S } 35 \\ 1941 \end{array}$
80.44	<p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, $1\frac{1}{2}$ ft. high; N. of cor.</p> <p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, gently rolling. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood, sage and cacti.</p>
<hr/>	
	<p>N.0°09'E., on true line bet. secs. 26 and 27.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p>
.08	Wire fence, bears S.89°50'W. and N.89°50'E.
19.10	Wash, 10 lks. wide, course NW.
29.00	Road, bears N.60°W. and S.60°E.
34.40	Dim road, bears N.65°W. and S.65°E.
38.20	Wash, 40 lks. wide, course N.60°W.
40.31	Proportional distance,
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\frac{1}{4} \begin{array}{l} \text{S } 27 \mid \text{S } 26 \\ 1941 \end{array}$
	<p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p> <p>No bearing trees available.</p>
41.10	Wash, 80 lks. wide, course W.
80.62	<p>At this point determined by the method of double proportion,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.</p> $\begin{array}{l} \text{T } 17 \text{ S } \text{R } 14 \text{ E} \\ \text{S } 22 \mid \text{S } 23 \\ \text{S } 27 \mid \text{S } 26 \\ 1941 \end{array}$
	<p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p> <p>No bearing trees available.</p> <p>Land, gently rolling. Soil, sandy, 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood, sage and cacti.</p>

of T. 17 S., R. 14 E.

Chains	<p>From cor. of secs. 23, 24, 25 and 26.</p> <p>S.89°50'W., on true line bet. secs. 23 and 26.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>2.96 Wash, 20 lks. wide, course NW.</p> <p>19.48 Wash, 10 lks. wide, course N.80°W.</p> <p>37.41 Wash, 20 lks. wide, course N.60°W.</p> <p>40.16 Proportional distance,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$ 1941</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.</p> <p>No bearing trees available.</p> <p>80.32 The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, gently rolling. Soil, sandy, 2nd rate. Timber, scattered mesquite; undergrowth, greasewood, cacti and mesquite.</p>
	<p>N.0°16'W., on true line bet. secs. 22 and 23.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>23.70 Wash, 10 lks. wide, course N.60°W.; continue over series of small drains.</p> <p>40.31 Proportional distance,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 22 S 23 1941</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p> <p>No bearing trees available.</p> <p>63.50 Wash, 10 lks. wide, course NW.</p> <p>73.00 Dim road, bears N.50°W. and S.50°E.</p> <p>80.62 At this point determined by the method of double proportion,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd.</p>

Chains	T 17 S R 14 E S 15 S 14 S 22 S 23 1941
	<p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p> <p>No bearing trees available.</p> <p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. $89^{\circ}54'$ W., on true line bet. secs. 14 and 23.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p>
19.03	Wash, 10 lks. wide, course NW.
24.93	Wash, 10 lks. wide, course NW.
38.23	Wash, 10 lks. wide, course NW.
40.17	Proportional distance,
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ <u>S 14</u> S 23 1941</p> <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, $1\frac{1}{2}$ ft. high</p> <p>Continue over series of small drains, course NW.</p>
49.93	Leave small drains.
61.93	Wash, 10 lks. wide, course NW.
69.53	Wash, 10 lks. wide, course N. 60° W.
80.34	The cor. of secs. 14, 15, 22 and 23.
	<p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.</p>
	<p>N. $0^{\circ}35'$ W., on true line bet. secs. 14 and 15.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p>
6.00	Wash, course NW.
12.00	Wash; course NW.
28.00	Wash, course NW.

of T. 17 S., R. 14 E.

Chains 36.15	Drain, course NW.
40.31	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ $\begin{array}{c} \text{S } 15 \mid \text{S } 14 \\ \hline 1941 \end{array}$ from which A live mesquite stump, bears S.89°E., 48 lks. dist., mkd. $\frac{1}{4}$ S 14 B T. A mesquite, 4 ins. diam., bears S.22 $\frac{1}{4}$ °W., 77 lks. dist., mkd. $\frac{1}{4}$ S 15 B T.
49.10	Drain, course N.80°W.
68.80	Wash, 10 lks. wide, course NW.
79.20	Drain, course N.70°W.
80.62	At this point determined by the method of double proportion, Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 10,11,14 and 15, with brass cap mkd. $\begin{array}{c} \text{T } 17 \text{ S } \text{R } 14 \text{ E} \\ \text{S } 10 \mid \text{S } 11 \\ \hline \text{S } 15 \mid \text{S } 14 \\ \hline 1941 \end{array}$ raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. No bearing trees available. Land, gently rolling. Soil, sandy, 2nd rate. Timber, scattered mesquite; undergrowth, mesquite,grease-wood and cacti.
12.00	Wash, 10 lks. wide, course NW.
40.31 $\frac{1}{2}$	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{\text{S } 11}{\text{S } 14}$ 1941

Dependent Resurvey of the Subdivisional Lines
of T. 17 S., R. 14 E.

Chains	from which
	<p>A mesquite, 4 ins. diam., bears S.26$\frac{1}{4}$°E., 62 lks. dist., mkd. $\frac{1}{4}$ S 14 B T.</p> <p>Raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, N. of cor.</p>
45.78	Wash, 10 lks. wide, course NW.
80.63	The cor. of secs. 10, 11, 14 and 15.
	<p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.</p>
	<p>N.0°09'W., on true line bet. secs. 10 and 11.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p>
10.60	Drain, course NW.
18.10	Drain, course NW.
40.31	Proportional distance,
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 10 S 11 1941 </p>
	from which
	<p>A mesquite, 4 ins. diam., bears N.74°E., 25 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.</p> <p>A live mesquite stump, bears S.26$\frac{1}{4}$°W., 50 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.</p>
61.70	Wash, 10 lks. wide, course N.70°W.
73.50	Road, bears N.63°W. and S.63°E.
80.62	At this point determined by the method of double proportion,
	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.</p> <p style="text-align: center;"> T 17 S R 14 E S 3 S 2 S 10 S 11 1941 </p>
	from which
	<p>A mesquite, 6 ins. diam., bears N.67$\frac{1}{4}$°E., 74 lks. dist., mkd. T 17 S R 14 E S 2 B T.</p> <p>A mesquite, 6 ins. diam., bears S.23$\frac{3}{4}$°W., 120 lks. dist., mkd. T 17 S R 14 E S 10 B T.</p>
	No other bearing trees available.

of T. 17 S., R. 14 E.

Chains Land, gently rolling.
Soil, sandy, 1st and 2nd rate.
Timber, scattered mesquite; undergrowth, mesquite, grease-wood, sage and cacti.

From the cor. of secs. 1, 2, 11 and 12.

N. 89° 56' W., on true line bet. secs. 2 and 11.

Over gently rolling desert land, through scattered timber and dense undergrowth.

40.20½ Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼ $\frac{S\ 2}{S\ 11}$

1941

of stone, 3 ft. base, 1½ ft. high, N. of cor. raise a mound

No other accessories available.

44.70 Wash, 10 lks. wide, course NW.

48.91 Enter series of small drains, course NW.

73.90 Leave small drains, course NW.

80.41 The cor. of secs. 2, 3, 10 and 11.

Land, gently rolling.
Soil, sandy, 1st and 2nd rate.
Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.

From the cor. of secs. 2, 3, 34 and 35 on N. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 17 S.; R. 14 E., resurveyed under this group.

S. 0° 05' E., on true line bet. secs. 2 and 3.

Over gently rolling desert land, through scattered timber and dense undergrowth.

7.47 Wash, 10 lks. wide, course N. 60° W.

18.87 Drain, course N. 60° W.

38.32 Wash, 10 lks. wide, course NW.

40.25 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼ $\frac{S\ 3}{S\ 2}$

1941

of stone, 2 ft. base, 1½ ft. high, W. of cor. raise a mound

Dependent Resurvey of the Subdivisional Lines
of T. 17 S., R. 14 E.

Chains

50.12 Drain, course N.60°W.

73.72 Drain, course NW.

77.27 Wash, 10 lks. wide, course NW.

80.56 The cor. of secs. 2,3,10 and 11.

Land, gently rolling.

Soil, sandy, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.

From the cor. of secs. 3,4,33 and 34 on S. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 18 S., R. 14 E., resurveyed under this group.

N.0°26'E., on true line bet. secs. 33 and 34.

Over gently rolling land, through scattered timber and dense undergrowth.

24.24 Wash, 20 lks. wide, course NW.

40.32 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ S\ 33\ | \ S\ 34 \\ 1941 \end{array}$$

from which

A mesquite, 6 ins. diam., bears N.63 $\frac{3}{4}$ °E., 221 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.A mesquite, 5 ins. diam., bears S.59°W., 116 lks. dist., mkd. $\frac{1}{4}$ S. 33 B T.

65.46 Wash, 30 lks. wide, 3 ft. deep, course N.15°W.

69.74 Drain, course NW.

80.44 Wire fence, bears E. and W.

80.64 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 27,28,33 and 34, with brass cap mkd.

$$\begin{array}{c} T\ 17\ S\ R\ 14\ E \\ S\ 28\ | \ S\ 27 \\ S\ 33\ | \ S\ 34 \\ 1941 \end{array}$$

raise a mound
of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

No bearing trees available.

The sec. cor. is located on N. side of small wash, course NW.

of T. 17 S., R. 14 E.

Chains	<p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35. N. 89° 49' W., on true line bet. secs. 27 and 34. Over gently rolling desert land, through scattered timber and dense undergrowth.</p>
11.05	Drain, course NW.
18.85	Wash, 10 lks. wide, course N. 40° W.
40.09	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 27 \\ S 34 \end{array}$ <p>1941</p>
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	No bearing trees available.
43.90	Wash, 10 lks. wide, course NW.
44.60	Wash, 10 lks. wide, course N. 30° W.
62.40	Wash, 20 lks. wide, course N. 20° W.
74.20	Road, bears N. 60° W. and S. 60° E., from Sahuarita to Helvetia.
80.18	The cor. of secs. 27, 28, 33 and 34. Land, gently rolling. Soil, sandy, 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.
	<p>N. 0° 05' W., on true line bet. secs. 27 and 28. Over gently rolling desert land, through scattered timber and dense undergrowth.</p>
3.60	Road, bears N. 55° W. and S. 59° E., from Sahuarita to Helvetia.
34.00	Wash, 40 lks. wide, course NW.
34.60	Drain, course NW.
40.32	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Chains

$\frac{1}{4}$
 S 28 | S 27
 1941

from which

A mesquite, 6 ins. diam., bears N.77 $\frac{3}{4}$ °E., 299 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.

A mesquite, 4 ins. diam., bears S.72 $\frac{3}{4}$ °W., 134 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.

50.75 Drain, course NW.

56.45 Wash, 20 lks. wide, course NW.

80.64 At this point determined by the method of double proportion,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T 17 S R 14 E
 S 21 | S 22
 S 28 | S 27
 1941

from which

A mesquite, 4 ins. diam., bears S.15°E., 39 lks. dist., mkd. B T.

A mesquite, 4 ins. diam., bears N.84°W., 117 lks. dist., mkd. T 17 S R 14 E S 21 B T.

No other bearing trees available.

Land, gently rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.

From the cor. of secs. 22, 23, 26 and 27.

N.89°49'W., on true line bet. secs. 22 and 27.

Over gently rolling desert land, through scattered timber and dense undergrowth.

4.50 Wash, 20 lks. wide, course NW.

12.14 Drain, course NW.

23.80 Drain, course N.80°W.

35.90 Drain, course NW.

40.26 $\frac{1}{2}$ Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 22
 S 27
 1941

of T. 17 S., R. 14 E.

Chains	<p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.</p> <p>No bearing trees available.</p> <p>41.90 Drain, course NW.</p> <p>57.30 Dim road, bears N.60°W. and S.60°E.</p> <p>62.90 Wash, 10 lks. wide, course N.60°W.</p> <p>68.75 Wash, 20 lks. wide, course N.30°W.</p> <p>71.90 Road, bears NW. and SE.</p> <p>73.60 Wash, 10 lks. wide, course N.30°W.</p> <p>80.53 The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.</p> <hr/> <p>N.0°16'W., on true line bet. secs. 21 and 22.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>5.80 Wash, course NW.</p> <p>9.70 Road, bears N.50°W. and S.50°E.</p> <p>12.30 Wash, 20 lks. wide, course NW.</p> <p>25.00 Wash, 20 lks. wide, course NW.</p> <p>30.50 Wash, 10 lks. wide, course N.60°W.</p> <p>40.32 Proportional distance,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 21 S 22</p> <p style="text-align: center;">1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 6 ins. diam., bears N.88$\frac{1}{2}$°E., 72 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.</p> <p>A mesquite, 8 ins. diam., bears S.88$\frac{1}{4}$°W., 178 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.</p> <p>40.70 Wash, 10 lks. wide, course NW.</p> <p>80.64 At this point determined by the method of double proportion.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.</p>
--------	--

Chains

T 17 S. R 14 E
 S 16 | S 15
 S 21 | S 22
 1941

from which

A mesquite, 6 ins. diam., bears N.14°W., 147 lks.
 dist., mkd. T 17 S R 14 E S 16 B T.

No other suitable accessory available.

Land, gently rolling.

Soil, sandy, 2nd rate; and gravelly, 3rd rate.

Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.

From the cor. of secs. 14, 15, 22 and 23.

N.89°50'W., on true line bet. secs. 15 and 22.

Over gently rolling desert land, through scattered timber and dense undergrowth.

10.20 Road, bears N.50°W. and S.50°E.

12.15 Wash, 10 lks. wide, 2 ft. deep, course NW.

24.60 Road, bears NW. and SE.

40.26 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 15
 S 22
 1941

of pebbles, 1 ft. base, $\frac{1}{2}$ ft. high, N. of cor. raise a mound

59.50 Wash, 10 lks. wide, course N.70°W.

80.52 The cor. of secs. 15, 16, 21 and 22.

Land, gently rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.

N.0°48'W., on true line bet. secs. 15 and 16.

Over gently rolling desert land, through scattered timber and dense undergrowth.

19.70 Wash, 10 lks. wide, course NW.

40.20 Road, bears N.80°W. and S.80°E.

40.32 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

of T. 17 S., R. 14 E.

Chains

$$\frac{1}{4}$$

S 16		S 15
1941		

from which

A mesquite, 4 ins. diam., bears N.83 $\frac{1}{4}$ °E., 103 lks.
dist., mkd. $\frac{1}{4}$ S 15 B T.

A mesquite, 5 ins. diam., bears S.16 $\frac{1}{4}$ °W., 183 lks.
dist., mkd. $\frac{1}{4}$ S 16 B T.

Windmill tower, bears N.17°38'E., 28.37 chs. dist.

59.18 Intake pipe of large circular water tank, bears N.48°50'E.
12.06 chs. dist.

72.35 Road, bears N.80°W. and S.80°E.

80.64 At this point determined by the method of double pro-
portion,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, for cor. of secs. 9,10,15 and 16, with brass cap
mkd.

T 17	S	R 14	E
S 9		S 10	
S 16	+	S 15	
1941			

raise a mound
of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

No bearing trees available.

Land, gently rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, grease-
wood and cacti.

From the cor. of secs. 10,11, 14 and 15.

N.89°50'W., on true line bet. secs. 10 and 15.

Over gently rolling desert land, through scattered timber
and dense undergrowth.

4.00 Wash, course NW.

40.40 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	S 10
	S 15
1941	

from which

A mesquite, 4 ins. diam., bears S.65°W., 28 lks.
dist., mkd. $\frac{1}{4}$ S 15 B T.

No other bearing tree available.

Dependent Resurvey of the Subdivisional Lines

of T. 17 S., R. 14 E.

Chains

42.00 Wash, course NW.

58.00 Wash, course NW.

64.00 Wash, course NW.

74.50 Wash, course NW.

80.80 The cor. of secs. 9, 10, 15 and 16:

Land, gently rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.

N.0°02'E., on true line bet. secs. 9 and 10.

Over gently rolling desert land, through scattered timber and dense undergrowth.

7.00 Wash, 20 lks. wide, course NW.

13.50 Wash, 60 lks. wide, course NW.


21.50 Wash, 20 lks. wide, course NW.

30.60 Wash, 20 lks. wide, course NW.

35.50 Wash, course NW.

40.32 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which


A mesquite, 5 ins. diam., bears S.77 $\frac{3}{4}$ °E., 39 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.

A mesquite, 10 ins. diam., bears N.80 $\frac{1}{4}$ °W., 45 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.

78.95 Dim road, bears NE. and SW.

80.64 At this point determined by the method of double proportion,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.



from which

of T. 17 S., R. 14 E.

Chains	<p>A mesquite, 14 ins. diam., bears S.85$\frac{1}{2}$°E., 202 lks. dist., mkd. T 17 S R 14 E S 10 B T.</p> <p>A mesquite, 4 ins. diam., bears N.27$\frac{1}{4}$°W., 79 lks. dist., mkd. T 17 S R 14 E S 4 B T.</p> <p>No other bearing trees available.</p> <p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.</p>
	<p>From the cor. of secs. 2,3,10 and 11.</p> <p>N.89°50'W., on true line bet. secs. 3 and 10.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p>
13.50	Dim road, bears N.60°W. and S.60°E.
19.65	Drain, course N.60°W.
40.27	Proportional distance,
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4} \frac{S \ 3}{S \ 10}$ <p>1941</p> </div> <p>No suitable accessory available.</p>
55.50	Road, bears NW. and SE.
78.84	Road, bears NE. and SW.
80.54	The cor. of secs. 3,4,9 and 10.
	<p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.</p>
	<p>From the cor. of secs. 3,4,33 and 34 on N. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 17 S., R. 14 E., resurveyed under this group.</p> <p>S.0°02'W., on true line bet. secs. 3 and 4.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p>
14.23	Wash, 20 lks. wide, course NW.
28.83	Wash, 10 lks. wide, course N.60°W.
40.32	Proportional distance,
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>

BOOK 4395
24Dependent Resurvey of the Subdivisional Lines
of T. 17 S., R. 14 E.

Chains	$\frac{1}{4}$ S 4 S 3 1941
	<p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p> <p>No bearing trees available.</p>
45.53	Road, bears N.50°W. and S.50°E.
65.03	Drain, course NW.
80.54	The cor. of secs. 3,4,9 and 10.
	<p>Land, gently rolling.</p> <p>Soil, sandy, 1st and 2nd rate.</p> <p>Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.</p>
<hr/>	
	<p>From the cor. of secs. 4,5,32 and 33 on S. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 18 S., R. 14 E., resurveyed under this group.</p> <p>N.0°16'E., on true line bet. secs. 32 and 33.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p>
18.90	Wash, 10 lks. wide, course N.5°W.
23.80	Wash, 10 lks. wide, course NW.
29.77	Wash, 10 lks. wide, course NW.
35.00	Wash, 10 lks. wide, course N.50°W.
40.27	Proportional distance,
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	$\frac{1}{4}$ S 32 S 33 1941
	<p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p> <p>No bearing trees available.</p> <p>Continue along wire fence.</p>
50.70	Wash, 10 lks. wide, course N.60°W.
56.75	Wash, 10 lks. wide, course N.60°W.
59.70	Wire fence, bears N.64°W. and S.64°E.
80.54	At this point determined by the method of double proportion,
	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 28,29,32 and 33, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines

25

of T. 17 S., R. 14 E.

Chains

T 17 S R 14 E
S 29 S 28
S 32 S 33
1941

from which

A fence corner, bears S.19°E., 75 lks. dist., from which fences bear E. and S.

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

No bearing trees available.

Land, gently rolling.

Soil, sandy, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.

From the cor. of secs. 27, 28, 33 and 34.

N.89°42'W., on true line bet. secs. 28 and 33.

Over gently rolling desert land, through scattered timber and dense undergrowth.

.30 Wash, 10 lks. wide, course NW.

5.00 Wash, 10 lks. wide, course NW.

7.00 Wash, 50 lks. wide, course N.

40.08 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼ S 28
S 33
1941

from which

A mesquite, 4 ins. diam., bears N.80°E., 105 lks. dist., mkd. ¼ S 28 B T.

A mesquite, 4 ins. diam., bears S.78½°W., 114 lks. dist., mkd. ¼ S 33 B T.

57.00 Wash, 10 lks. wide, course N.30°W.

80.16 The cor. of secs. 28, 29, 32 and 33.

Land, gently rolling.

Soil, sandy, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.

N.0°09'W., on true line bet. secs. 28 and 29.

Over gently rolling desert land, through scattered timber and dense undergrowth.

17.00 Road, bears N.70°W. and S.70°E.

BOON 4225
 26 Dependent Resurvey of the Subdivisional Lines
 of T. 17 S., R. 14 E.

Chains	
33.60	Wash, 20 lks. wide, course NW.
34.50	Wash, 10 lks. wide, course W.
39.00	Wash, 20 lks. wide, course NW.
40.27	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 29 \mid S\ 28 \\ 1941 \end{array}$ from which A mesquite, 5 ins. diam., bears S.67 $\frac{3}{4}$ °E., 36 lks. dist., mkd. $\frac{1}{4}$ S 28 B T. A mesquite, 4 ins. diam., bears S.42 $\frac{1}{2}$ °W., 38 lks. dist., mkd. $\frac{1}{4}$ S 29 B T. The $\frac{1}{4}$ sec. cor. is located on N. bank of small wash, course NW.
55.60	Road, bears N.60°W. and S.60°E., from Sahuarita to Helvetia.
80.54	At this point determined by the method of double proportion, Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 20,21,28 and 29, with brass cap mkd. $\begin{array}{c} T\ 17\ S\ R\ 14\ E \\ S\ 20 \mid S\ 21 \\ S\ 29 \mid S\ 28 \\ 1941 \end{array}$ No suitable accessories available. Land, gently rolling. Soil, sandy, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.
	From the cor. of secs. 21,22,27 and 28. N.89°45'W., on true line bet. secs. 21 and 28. Over gently rolling desert land, through scattered timber and dense undergrowth.
10.50	Wash, 20 lks. wide, course N.
31.70	Wash, 60 lks. wide, course N.60°W.
40.05	Wash, 20 lks. wide, course NW.
40.12 $\frac{1}{2}$	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

of T. 17 S., R. 14 E.

Chains

$$\frac{1}{4} \begin{array}{l} \text{S 21} \\ \text{S 28} \\ 1941 \end{array}$$

from which

A cactus, 4 ins. diam., bears S.35 $\frac{1}{2}$ °W., 72 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.

No other suitable accessory.

40.70 Wash, 40 lks. wide, course N.30°W.

80.25 The cor. of secs. 20, 21, 28 and 29.

Land, gently rolling.
Soil, sandy, 1st and 2nd rate.
Timber, scattered mesquite; undergrowth, greasewood, mesquite and cacti.

N.0°20'W., on true line bet. secs. 20 and 21.

Over gently rolling desert land, through scattered timber and dense undergrowth.

36.50 Wash, 20 lks. wide, course NW.

40.27 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S 20} \mid \text{S 21} \\ 1941 \end{array}$$

from which

A mesquite, 4 ins. diam., bears S.39 $\frac{1}{2}$ °E., 81 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.

A mesquite, 4 ins. diam., bears N.69 $\frac{1}{2}$ °W., 48 lks. dist., mkd. B T.

44.15 Wash, 40 lks. wide, 3 ft. deep, course N.70°W.

57.20 Wash, 20 lks. wide, course N.70°W.

57.90 Dim road, bears N.80°W. and S.80°E.

77.70 Top of flat hill, slopes NW.

80.54 At this point determined by the method of double proportion,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.

$$\begin{array}{l} \text{T 17 S R 14 E} \\ \text{S 17} \mid \text{S 16} \\ \text{S 20} \mid \text{S 21} \\ 1941 \end{array}$$

from which

Chains	<p>A mesquite, 4 ins. diam., bears S.4°E., 9 lks. dist., mkd. B T.</p> <p>A mesquite, 4 ins. diam., bears S.78$\frac{1}{2}$°W., 54 lks. dist., mkd. T 17 S R 14 E S 20 B T.</p> <p>No other bearing trees available.</p> <p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.</p>
	<p>From the cor. of secs. 15,16,21 and 22.</p> <p>N.89°50'W., on true line bet. secs. 16 and 21.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>14.50 Dim road, bears NW. and SE.</p> <p>36.00 Wash, 10 lks. wide, course NW.</p> <p>40.17 Proportional distance,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ <u>S 16</u> S 21 1941 </p> <p style="text-align: right;">from which</p> <p>A mesquite, 4 ins. diam., bears S.65°W., 19 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.</p> <p>No other bearing tree available.</p> <p>57.21 Wash, 10 lks. wide, course N.70°W.</p> <p>57.50 Drain, course NW.</p> <p>80.34 The cor. of secs. 16,17,20 and 21.</p> <p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.</p>
	<p>N.1°04'W., on true line bet. secs. 16 and 17.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>25.90 Wash, 10 lks. wide, course NW.</p> <p>35.90 Wash, 10 lks. wide, course NW.</p> <p>40.27$\frac{1}{2}$ Proportional distance,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>

of T. 17 S., R. 14 E.

Chains

$$\frac{1}{4}$$

$$S \ 17 \ | \ S \ 16$$

$$1941$$

from which

A mesquite, 3 ins. diam., bears N.21°E., 162 lks. dist., mkd. B T.

A mesquite, 4 ins. diam., bears N.70°W., 245 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.

41.60 Dim road, bears N.70°W. and S.70°E.

58.00 Wash, 10 lks. wide, course NW.

67.20 Road, bears NW. and SE.

79.51 Road, bears NW. and SE.

80.55 At this point determined by the method of double proportion,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 8,9,16 and 17, with brass cap mkd.

$$T \ 17 \ S \ R \ 14 \ E$$

$$S \ 8 \ | \ S \ 9$$

$$S \ 17 \ | \ S \ 16$$

$$1941$$

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, gently rolling.

Soil, sandy, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.

From the cor. of secs. 9,10,15 and 16.

N.89°51'W., on true line bet. secs. 9 and 16.

Over gently rolling desert land, through scattered timber and dense undergrowth.

29.50 Drain, course NW.

40.36 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \ S \ 9$$

$$S \ 16$$

$$1941$$

from which

A mesquite, 4 ins. diam., bears N.32 $\frac{3}{4}$ °E., 33 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.

A mesquite, 4 ins. diam., bears S.56°E., 102 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.

43.90 Wash, 10 lks. wide, course NW.

Chains
80.72

The cor. of secs. 8,9,16 and 17.

Land, gently rolling.
Soil, sandy loam, 1st and 2nd rate.
Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.

N.0°07' E., on true line bet. secs. 8 and 9.

Over gently rolling desert land, through scattered timber and dense undergrowth.

9.50 Drain, course NW.

40.27 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 8 | S 9
 1941

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W., of cor. raise a mound

54.30 Wash, 20 lks. wide, course NW.

80.54 At this point determined by the method of double proportion,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 4,5,8 and 9, with brass cap mkd.

T 17 S R 14 E
 S 5 | S 4
 S 8 | S 9
 1941

from which

A mesquite, 8 ins. diam., bears N.22 $\frac{3}{4}$ °E., 172 lks. dist., mkd. T 17 S R 14 E S 4 B T.

A mesquite, 4 ins. diam., bears S.87 $\frac{3}{4}$ °E., 186 lks. dist., mkd. T 17 S R 14 E S 9 B T.

A mesquite, 4 ins. diam., bears N.61 $\frac{1}{2}$ °W., 47 lks. dist., mkd. T 17 S R 14 E S 5 B T.

No other bearing tree available.

Land, gently rolling.
Soil, sandy loam, 1st and 2nd rate.
Timber, scattered mesquite; undergrowth, mesquite-grease-wood and cacti.

of T. 17 S., R. 14 E.

Chains	<p>From the cor. of secs. 3,4,9 and 10.</p> <p>N.89°58'W., on true line bet. secs. 4 and 9.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>5.89 Drain, course NW.</p> <p>40.28$\frac{1}{2}$ Proportional distance,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\frac{1}{4} \begin{array}{c} S 4 \\ S 9 \\ 1941 \end{array}$ <p style="text-align: right;">from which</p> <p>A mesquite, 4 ins. diam., bears N.70$\frac{3}{4}$°E., 10 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.</p> <p>A mesquite, 6 ins. diam., bears S.26$\frac{1}{4}$°W., 58 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.</p>
80.57	<p>The cor. of secs. 4,5,8 and 9.</p> <p>Land, gently rolling.</p> <p>Soil, sandy loam, 1st and 2nd rate.</p> <p>Timber, mesquite; undergrowth, mesquite, greasewood and cacti.</p>
	<p>From the cor. of secs. 4,5,32 and 33 on N. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 17 N., R. 14 E., resurveyed under this group.</p> <p>S.0°04'W., on true line bet. secs. 4 and 5.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>2.00 Road, bears NW. and SE.</p> <p>20.30 Road, bears N.10°E. and S.10°W.</p> <p>20.85 A point 1 lks. W. of an iron pipe, 2 ins. diam., 4 ins. above ground, at cor. of fences which bear S.0°50'W. and S.89°15'E.</p> <p>40.42 Proportional distance,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\frac{1}{4} \begin{array}{c} S 5 S 4 \\ 1941 \end{array}$ <p style="text-align: right;">from which</p> <p>A mesquite, 5 ins. diam., bears N.56$\frac{1}{2}$°E., 94 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.</p> <p>A mesquite, 4 ins. diam., bears S.17$\frac{1}{2}$°W., 18 lks. dist., mkd. $\frac{1}{4}$ S 5 B T.</p>

Chains	
40.94	An iron pipe, 2 ins. diam., 4 ins. above ground, on fence line, bears W. 27 lks. dist.
61.00	An iron pipe, 2 ins. diam., 4 ins. above ground at cor. of wire fence, bears N.89°W. 51 lks. dist., from which fences bear N.0°50'E. and S.89°E.
61.30	Dim road, bears N.71°W. and S.71°E.
80.69	The cor. of secs. 4,5,8 and 9. Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.
	From the cor. of secs. 5,6,31 and 32 on S. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 18 S., R. 14 E., resurveyed under this group. N.0°07'W., on true line bet. secs. 31 and 32. Over rolling desert land, through scattered timber and dense undergrowth.
29.00	Wash, 100 lks. wide, course NW.
40.10	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \text{S } 31 \quad \quad \text{S } 32 \\ \hline 1941 \end{array}$ <p style="text-align: right;">from which</p> <p>A mesquite, 4 ins. diam., bears S.63°E., 22 lks. dist., mkd. $\frac{1}{4}$ S 32 B T.</p> <p>A mesquite, 4 ins. diam., bears S.31$\frac{1}{2}$°W., 111 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.</p>
47.00	Dim road, bears E. and W.
78.90	Wire fence, bears E. and W.
80.20	At this point determined by the method of double proportion, Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 29,30,31 and 32, with brass cap mkd. $\begin{array}{c} \text{T } 17 \text{ S } \text{ R } 14 \text{ E} \\ \text{S } 30 \quad \quad \text{S } 29 \\ \hline \text{S } 31 \quad \quad \text{S } 32 \\ \hline 1941 \end{array}$ <p style="text-align: right;">raise a mound</p> <p>of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.</p>

Dependent Resurvey of the Subdivisional Lines

of T. 17 S., R. 14 E.

BOOK 4325

Chains	From the cor. of secs. 28, 29, 32 and 33, N.89°42'W., on true line bet. secs. 29 and 32. Over gently rolling desert land, through scattering timber and dense undergrowth.
6.00	Fence cor. bears S., 138 lks. dist., from which fences bear N.89½°W. and S.12½°W.
40.13	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap marked $\frac{1}{4} \begin{array}{r} S 29 \\ \hline S 32 \\ 1941 \end{array}$ raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. No bearing trees available. From ¼ sec. cor., wire fence extending easterly and westerly, bears S. 140 lks. dist.
64.10	Wash, 80 lks. wide, course N.
80.26	The cor. of secs. 29, 30, 31 and 32. Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattering mesquite. Undergrowth, mesquite, greasewood and cacti.
<hr/>	
	From the cor. of secs. 25, 30, 31 and 32 on W. bdy. of the Tp., described in the field notes of the W. bdy. of T.17 S., R.14 E., resurveyed under this group. S.89°28'E., on true line bet. secs. 30 and 31. Over rolling land, through scattering timber and dense undergrowth.
2.64	Power line along wire fence, bears N.4¼°E and S.4¼°W.
3.72	U.S. Highway No. 89, bears N.4¼°E. and S.4¼°W.
4.99	Wire fence along right-of-way, bears N.4¼°E. and S.4¼°W.
5.19	Telephone line, bears N.4¼°E. and S.4¼°W.
5.76	E. rail of Southern Pacific R.R., bears N.4¼°E. and S.4¼°W.
7.26	Wire fence along right-of-way, bears N.4¼°E. and S.4¼°W.
23.32	John Alexander's pump house, bears N.156 lks. dist.
38.64	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd. $\frac{1}{4} \begin{array}{r} S 30 \\ \hline S 31 \\ 1941 \end{array}$

- Chains
- raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
 - A fence cor., bears S. 60 lks. dist., from which fences bear W. and S. 2½°W., 5.87 chs. to bend, thence S. 35°W.
 - 42.49 Gravel road, bears N. 20°E. and S. 20°W.
 - 43.41 Fence cor., bears S. 130 lks. dist., from which fences bear S. 12½°W. and E.
 - 45.29 Enter mesa, bears N. and S. Leave Santa Cruz Valley.
 - 53.79 Road, bears NW. and SE.
 - 58.69 Wash, course NW.
 - 78.79 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.
Soil, sandy, 1st and 2nd rate.
Timber, scattering mesquite.
Undergrowth, mesquite, greasewood and cacti.

N. 0° 16' W., on true line bet. secs. 29 and 30.

Over gently rolling desert land, through scattering timber and dense undergrowth.

- 25.90 Wash, 60 lks. wide, course N. 60°W.
- 31.60 Wash, 40 lks. wide, course NW.
- 34.60 Wash, 10 lks. wide, course NW.
- 40.10 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼
S 30 | S 29
1941

from which

A mesquite, 4 ins. diam., bears S. 86°E., 27 lks. dist. mkd. ¼ S 29 B T

No other bearing tree available.

- 41.30 Wash, 10 lks. wide, course N. 60°W.
- 60.20 Dim road, bears S. 70°E. and N. 70°W.
- 80.20 A point determined by the method of double proportion,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

T 17 S R 14 E
S 19 | S 20
S 30 | S 29
1941

from which

of T. 17 S., R. 14 E.

Chains	<p>A mesquite, 4 ins. diam., bears N.55½°E., 69 lks. dist., mkd. B T.</p> <p>A mesquite, 4 ins. diam., bears S.48½°E., 70 lks. dist., mkd. T 17 S R 14 E S 29 B T.</p> <p>A mesquite, 4 ins. diam., bears S.60°W., 169 lks. dist., mkd. T 17 S R 14 E S 30 B T.</p> <p>A mesquite, 5 ins. diam., bears N.19°W., 480 lks. dist., mkd. T 17 S R 14 E S 19 B T.</p> <p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N.89°57'W., on true line bet. secs. 20 and 29.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p>
22.60	Road, bears N.35°W. to Sahuarita, and S.10°E. to Helvetia.
40.16	Proportional distance,
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">¼ $\frac{S\ 20}{S\ 29}$ 1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 4 ins. diam., bears S.29½°W., 89 lks. dist., mkd. ¼ S 29 B T.</p> <p>A mesquite, 5 ins. diam., bears N.84°W., 49 lks. dist., mkd. ¼ S 20 B T.</p>
50.25	Wash, 10 lks. wide, course N.10°W.
59.00	Wash, 60 lks. wide, course NW.
64.30	Wash, 20 lks. wide, course N.30°W.
79.00	Wash, 20 lks. wide, course N.30°W.
80.32	The cor. of secs. 19, 20, 29 and 30.
	<p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.</p>
	<p>From the true point for cor. of secs. 19, 24, 25 and 30 on W. bdy. of the Tp.; described in the field notes of the W. bdy. of T. 17 N., R. 14 E., resurveyed under this group.</p> <p>S.89°18'E., on true line bet. secs. 19 and 30.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>Over bed of Santa Cruz River.</p>

Chains	
3.37	Right bank of Santa Cruz River, course N.20°W.
4.00	Set an iron post, 3-ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. of secs. 19, 24, 25 and 30, Ts. 17 S., Rs. 13 and 14 E., with brass cap mkd.
	T 17 S R 13 E R 14 E WC S 24 S 19 S 25 S 30 1941
	raise a mound
	of stone, 3 ft. base, 2½ ft. high, W. of cor.
10.30	Wire fence, bears N.4¼°E. and S.4¼°W.
10.42	Power line, bears N.4¼°E. and S.4¼°W.
11.32	U.S. Highway No 89 bears N.4¾°E. and S.4¾°W.
11.97	Right-of-way fence, bears N.4¾°E. and S.4¾°W.
12.18	Telephone line, bears N.4¾°E. and S.4¾°W.
12.77	E. rail of Southern Pacific Ry., bears N.4¾°E. and S.4¾°W.
14.27	Right-of-way fence, bears N.4¾°E. and S.4¾°W. Over cultivated land.
35.87	Fence, bears NE. and SW.
38.61	Proportional distance.
	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. below surface of field, with a stone, 6x4x2 ins. mkd. X, buried on cap of post, for ¼ sec. cor., with brass cap mkd.
	¼ S 19 S 30 1941
	from which
	A power line pole, bears N.21°E., 124 lks. dist., mkd. X B O.
	A power line pole, bears S.8½°E., 350 lks. dist., mkd. X B O.
39.13	Wire fence and power line, bear N.30°W. and S.30°E.
39.37	Road, bears N.30°W. and S.30°E.
50.57	Fence, bears N.11°E. and S.11°W.; leave cultivated land.
50.67	Wash, 30 lks. wide, course N.10°E. Asc. 5 ft.
51.17	Road, bears N.11°E. and S.11°W. Asc. 13 ft.
51.47	Edge of mesa, bears N. and S.; leave Santa Cruz Valley.
52.97	Dim road, bears N. and S.
54.97	Dim road, bears N. and S.30°W.
64.47	Dim road, bears NW. and SE.
78.77	The cor. of secs. 19, 20, 29 and 30.
	Land, gently rolling.
	Soil, sandy loam, 1st and 2nd rate.
	Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.

of T. 17 S., R. 14 E.

Chains N.0°19'W., on true line bet. secs. 19 and 20.

Over gently rolling desert land, through scattered timber and dense undergrowth.

5.55 Drain, course W.

13.70 Wash, 10 lks. wide, course N.50°W.

40.10 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4}$$

S 19		S 20
1941		

from which

A mesquite, 6 ins. diam., bears S.85 $\frac{3}{4}$ °E., 72 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.A mesquite, 5 ins. diam., bears N.50 $\frac{1}{2}$ °W., 113 lks. dist., mkd. $\frac{1}{4}$ S 19 B T.

Cor. is located in shallow wash, course NW.

41.00 Wash, 10 lks. wide, course NW.

58.20 Road, bears N.65°W. and S.65°E. from Sahuarita to Helvetia.

65.30 Wash, 10 lks. wide, course N.60°W.

77.70 Wire fence, bears N.67 $\frac{1}{2}$ °W. and S.67 $\frac{1}{2}$ °E.

80.20 At this point determined by the method of double proportion,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 17,18,19 and 20, with brass cap mkd.

T 17	S R	14 E
S 18		S 17
S 19		S 20
1941		

raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.An iron pipe, 2 $\frac{1}{2}$ ins. diam., 8 ins. above ground, bears N.44 $\frac{1}{2}$ °W., 57 lks. dist.

Land, gently rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.

Chains	<p>From the cor. of secs. 16,17,20 and 21.</p> <p>S.89°46'W., on true line bet. secs. 17 and 20.</p> <p>Over gently rolling desert land, through scattered timber and medium undergrowth.</p> <p>20.00 Wash, 20 lks. wide; course NW.</p> <p>24.40 Road, bears NW. and SE.</p> <p>33.00 Road, bears NW. and SE.</p> <p>37.60 Draw, course NW.</p> <p>40.17 Proportional distance,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ <u>S 17</u> S 20</p> <p style="text-align: center;">1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 5 ins. diam., bears N.28$\frac{1}{4}$°E., 247 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.</p> <p>A mesquite, 4 ins. diam., bears S.12$\frac{3}{4}$°W., 125 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.</p> <p>43.40 Wire fence, bears N.4$\frac{1}{4}$°W. and S.4$\frac{1}{4}$°E.</p> <p>62.00 Wash, 70 lks. wide, course N.70°W.</p> <p>70.70 Fence, bears N.73°W. and S.73°E.</p> <p>71.15 Fence, bears N.22°E. and S.22°W.</p> <p>80.34 The cor. of secs 17,18,19 and 20.</p> <p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, medium mesquite, greasewood and cacti.</p>
	<p>From the cor. of secs. 13,18,19 and 24 on W. bdy. of the Tp.; described in the field notes of the W. bdy. of T. 17 S., R. 14 E., resurveyed under this group.</p> <p>S.89°09'E., on true line bet. secs. 18 and 19.</p> <p>Over gently rolling desert land, through scattered timber and dense undergrowth.</p> <p>12.24 SE. cor. of house, bears N. 80 lks. dist.</p> <p>17.40 Wire fence, bears N.4$\frac{3}{4}$°E. and S.4$\frac{3}{4}$°W.</p> <p>18.40 U.S.Highway No.89 bears N.4$\frac{3}{4}$°E. and S.4$\frac{3}{4}$°W.</p> <p>19.05 Fence, bears N.4$\frac{3}{4}$°E. and S.4$\frac{3}{4}$°W.</p> <p>19.15 Telephone line, bears N.4$\frac{3}{4}$°E. and S.4$\frac{3}{4}$°W.</p> <p>19.80 E. rail of Southern Pacific Ry., bears N.4$\frac{3}{4}$°E. and S.4$\frac{3}{4}$°W.</p> <p>21.30 Fence, bears N.4$\frac{3}{4}$°E. and S.4$\frac{3}{4}$°W.</p>

Chains
38.57

Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. below surface of road, with a stone, 5x4x2 ins. mkd. X, buried on cap of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S } 18 \\ \hline \text{S } 19 \end{array}$$

1941

from which

NE. cor. of sheet-iron shed, bears S. $57\frac{1}{2}^{\circ}$ W., 279 lks. dist.

Fence cor. bears N. 54° E., 31 lks. dist., from which fence, bears N. and S.

Angle pole in power line, bears S. $25\frac{3}{4}^{\circ}$ E., 59 lks. dist., mkd. X B O.

Power line pole, bears S. $61\frac{1}{4}^{\circ}$ W., 91 lks. dist., mkd. X B O.

38.80 Wire fence and power line, bears N. and S.

62.15 Wire fence, bears N. $14\frac{3}{4}^{\circ}$ E. and S. $14\frac{3}{4}^{\circ}$ W.; leave Santa Cruz Valley. Asc. 25 ft. over W. slope.

64.65 Road, bears N. $14\frac{3}{4}^{\circ}$ E. and S. $14\frac{3}{4}^{\circ}$ W.

65.25 West edge of mesa, bears N. and S. Over gentle NW. slope.

75.65 Fence, bears NW. and SE.

78.74 The cor. of secs. 17, 18, 19 and 20.

Land, gently rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, greasewood and cacti.

N. $1^{\circ}15'$ W., on true line bet. secs. 17 and 18.

Over gently rolling desert land, through scattered timber and undergrowth.

12.60 Wire fence, bears N. 42° E. and S. 42° W.

23.10 Road, bears E. and W.

33.60 Fence, corner bears E. 8.00 chs. dist., from which fences bear S. $27\frac{1}{4}^{\circ}$ W. and S. 80° E.

40.11 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S } 18 \\ \hline \text{S } 17 \end{array}$$

1941

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Chains	No bearing trees available. Continue along road.				
60.25	NW. cor. of Sanchez' house, bears E. 20 lks. dist.				
72.70	Drain, course NE.				
80.22	At this point determined at intersection of roads which bear N. and W. Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. below surface of road, with a granite stone, 8x6x4 ins., mkd. X, buried on top of post, for cor. of secs. 7, 8, 17 and 18, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>T 17 S R 14 E</td></tr> <tr><td>S. 7 S 8</td></tr> <tr><td>S 18 S 17</td></tr> <tr><td>1941</td></tr> </table> </div> <div style="text-align: right;">from which</div> An angle pole in telephone line, bearing N. and SW., bears N.44°E., 65 lks. dist., mkd. X B O. Fence corner bears S.32½°W., 55 lks. dist., from which fences bear S. and W. An angle pole in power line, bears N.41½°W., 66 lks. dist., mkd. X B O. SE. corner of concrete foundation at pump house, bears N.43½°W., 201 lks. dist., mkd. with an X, chiseled in concrete foundation. Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, mesquite, grease-wood and cacti.	T 17 S R 14 E	S. 7 S 8	S 18 S 17	1941
T 17 S R 14 E					
S. 7 S 8					
S 18 S 17					
1941					
	From the cor. of secs. 8, 9, 16 and 17. S.89°33'W., on true line bet. secs. 8 and 17. Over gentle rolling desert land, through scattered timber and dense undergrowth.				
1.00	Road, bears NW. and SE.				
16.30	Wash, 20 lks. wide, 2 ft. deep, course NW.				
17.70	Road, bears N. and S.				
25.20	Wash, 20 lks. wide, 3 ft. deep, course N.20°W.				
35.00	Road, bears S.70°W. and N.70°E.				
38.00	Wire fence, bears N.15¼°W. and S.15¼°E., 68 lks. thence S.				
40.27	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.				

Dependent Resurvey of the Subdivisional Lines
of T. 17 S., R. 14 E.

Chains	$\frac{1}{4}$ <table style="margin-left: auto; margin-right: auto;"> <tr><td style="text-align: center;">S 8</td></tr> <tr><td style="text-align: center;">—</td></tr> <tr><td style="text-align: center;">S 17</td></tr> <tr><td style="text-align: center;">1941</td></tr> </table>	S 8	—	S 17	1941
S 8					
—					
S 17					
1941					
	from which				
	NW. cor. of adobe house, bears S.2 $\frac{1}{2}$ °W., 240 lks. dist.				
	SW. cor. of water trough, bears N.78 $\frac{1}{2}$ °E., 287 lks. dist.				
	The $\frac{1}{4}$ sec. cor. is located in fence line, bearing N.75 $\frac{1}{2}$ °W. and S.75 $\frac{1}{2}$ °E.				
61.00	Wash, 20 lks. wide, 2 ft. deep, course N. to earthen tank about 4.50 chs. dist.				
80.54	The cor. of secs. 7, 8, 17 and 18. Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattering mesquite. Undergrowth, mesquite, greasewood and cacti.				
<hr/>					
	From the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of Tp., described in the field notes of the W. bdy. of T. 17 S., R. 14 E., resurveyed under this group, S.89°17'E., on true line bet. secs. 7 and 18. Over gently rolling desert land, through scattering timber and undergrowth. Along road.				
18.79	Fence cor., bears N. 45 lks. dist., from which fences bear northerly and easterly.				
23.67	NE. cor. of Roy Brown's store, bears S.17 $\frac{1}{4}$ °W., 120 lks. dist. SE. cor. of B.H. Manelos store, bears N.2 $\frac{1}{4}$ °E.				
23.84	Highway right-of-way fence, bears N.4 $\frac{3}{4}$ °E. and S.4 $\frac{3}{4}$ °W.				
24.84	U.S. Highway No. 89, bears N.4 $\frac{3}{4}$ °E. and S.4 $\frac{3}{4}$ °W.				
25.24	Side track of Southern Pacific R.R., bears N.4 $\frac{3}{4}$ °E. and S.4 $\frac{3}{4}$ °W.				
27.74	E. rail of Southern Pacific R.R., bears N.4 $\frac{3}{4}$ °E. and S.4 $\frac{3}{4}$ °W. 57 lks. dist. to side switch on W. side of lettuce shed. NW. cor. of Cotton Gin No. 1, bears S.55°20'E. NW. cor. of Cotton Gin No. 2, bears S.77°10'E. NE. cor. of lettuce shed, bears S.4°15'E.				
34.13	NW. cor. of house, bears S.50°29'E. NW. cor. of office building, bears S.0°20'W. NW. cor. of sheet iron shed, bears S.36°27'W. NW. cor. of Cotton Gin No. 1, bears S.62°W. NW. cor. of Cotton Gin No. 2, bears S.80°45'W.				

Dependent Resurvey of the Subdivisional Lines

of T. 17 S., R. 14 E.

Chains

38.25

Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. below surface of road, with a stone, 7x7x $\frac{1}{4}$ ins. mkd. X, deposited on top of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 7 \\ \hline S 18 \end{array}$$

1941

from which

Pole on power line, bears N.57°E., 90 lks. dist., from which power line bears NW. and E.

NE. cor. of substation enclosure, bears S.42°W., 89 lks. dist.

SE. cor. of machine shop, bears N.32 $\frac{1}{4}$ °W., 203 lks. dist.

39.28

Fence corner bears S. 42 lks. dist., from which fences bear E. and S.

46.65

Smoke stack at Sahuarita School, bears N.16°27'E.

47.70

Fence, bears S. and W.; continue along road.

58.85

Fence cor., bears S. 42 lks. dist., from which fences bear E. and S.

68.59

Fence cor., bears S. 42 lks. dist., from which fences bear E., W. and S.

69.24

Smoke stack at Sahuarita School, bears N.31°08'W.

78.25

The cor. of secs. 7, 8, 17 and 18.

Land, level.

Soil, sandy loam, 1st rate.

Timber, scattering mesquite.

Undergrowth, mesquite, greasewood and cacti..

N.0°02'E., on true line bet. secs. 7 and 8.

Over level land.

Along road.

20.35

Fence, bears E.

29.89

Adobe house, bears W. 160 lks. dist.

39.80

Drain, course NW.

40.49

Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. below surface of road, with a stone, 8x6x $\frac{1}{4}$ ins. mkd. X buried

Chains on top of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 7 | S 8

1941

from which

A power line pole, bears N.61°W., 52 lks. dist.,
mkd. X B O.

Fence corner bears N.20°W., 133 lks. dist., from which
fences bear northerly., southerly and westerly.

Fence corner bears N.18 $\frac{1}{2}$ °E., 135 lks. dist., from
which fences bear northerly and easterly.

Fence corner bears N.59 $\frac{1}{2}$ °E., 48 lks. dist., from which
fences bear southerly and easterly.

Corner of concrete house, bears N.72°50'E., 504 lks.
dist.

SE. corner of Sahuarita School House, bears S.57°35'W.

NE. corner of adobe house, bears S.8 $\frac{1}{2}$ °W.

65.09 Fence, bears E. about 20 chs. dist.

80.98 At this point determined by proportionate distance in
latitude, and on center line of N. and S. road.

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. below
surface of road, with a stone, 8x6x3 ins., mkd. X, buried
on top of post, for cor. of secs. 5, 6, 7 and 8, with brass
cap mkd.

T 17 S R 14 E

S 6 | S 5

S 7 | S 8

1941

from which

A telephone pole bears N.58 $\frac{1}{2}$ °E., 48 lks. dist., from
which telephone line bears N. and S.

SE. corner of adobe house, bears N.59 $\frac{1}{4}$ °W., 455 lks.
dist.

SW. corner of pump house, bears N.38 $\frac{1}{2}$ °W., 319 lks.
dist.

Land, gently rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, mesquite, grease-
wood and cacti.

From the cor. of secs. 4, 5, 8 and 9.

S.89°54'W., on true line bet. secs. 5 and 8.

Over gently rolling desert land, through scattered timber
and medium undergrowth.

39.60 Wash, 30 lks. wide, course NW.

Chains 40.30	<p>Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\frac{1}{4} \frac{S 5}{S 8}$ <p>1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 4 ins. diam., bears S.24$\frac{1}{2}$°E., 11 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.</p> <p>A mesquite, 4 ins. diam., bears N.44$\frac{1}{2}$°W., 66 lks. dist., mkd. $\frac{1}{4}$ S 5 B T.</p>
40.55	Fence, bears N. and S.
52.10	Fence, bears S. and N. 95 lks. to cor., thence S.88 $\frac{1}{4}$ °W.
62.30	Fence, bears N. and S.
80.60	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, gently rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite; undergrowth, medium mesquite, greasewood and cacti.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12 on W. bdy. of the Tp.; described in the field notes of the W. bdy. of T. 17 S., R. 14 E., resurveyed under this group.</p> <p>S.89°57'E., on true line bet. secs. 6 and 7.</p> <p>Over gently rolling desert land, through scattered timber and medium undergrowth.</p>
.10	Power line, bears N. and S.
9.27	Left bank of Santa Cruz River, course N.13°E.
10.60	Right bank of river.
14.14	Fence, bears S.23 $\frac{1}{2}$ °W. and N.23 $\frac{1}{2}$ °E.; enter cultivated land.
26.63	Fence, bears N.22 $\frac{1}{2}$ °E. and S.22 $\frac{1}{2}$ °W.; leave cultivated land.
27.93	Drain, course N.
31.67	Highway right-of-way fence, bears N.4 $\frac{3}{4}$ °E. and S.4 $\frac{3}{4}$ °W.
32.73	Center of U.S. Highway No. 89, bears N.4 $\frac{3}{4}$ °E. and S.4 $\frac{3}{4}$ °W.
33.35	Southern Pacific Ry., right-of-way fence, bears N.4 $\frac{3}{4}$ °E. and S.4 $\frac{3}{4}$ °W.
33.47	Telephone line, bears N.4 $\frac{3}{4}$ °E., and S.4 $\frac{3}{4}$ °W.
34.07	Center of Southern Pacific R.R. track, bears N.4 $\frac{3}{4}$ °E. and S.4 $\frac{3}{4}$ °W.
34.57	Southern Pacific Ry., right-of-way fence, bears N.4 $\frac{3}{4}$ °E. and S.4 $\frac{3}{4}$ °W.

Dependent Resurvey of the Subdivisional Lines
of T. 17 S., R. 14 E.

45

Chains

35.57 Fence, bears N. and S.

35.93 Enter field, bears NE. and SW.

38.06 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. below surface of field, with a stone, 8x6x2 ins., mkd. X, buried on top of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 6 \\ S 7 \end{array}$$

1941

from which

A mesquite, 4 ins. diam., bears S. $54\frac{3}{4}^{\circ}$ W., 321 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.

A mesquite, 12 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ W., 284 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.

A bench mark on U.S. Highway No 89, painted elevation 2689.56 Sta. 384 00 on W. head wall of box culvert, bears N. $55^{\circ}15'$ W., 6.44 chs. dist.

52.73 Sheet-iron shed, bears approx. 250 lks. N.

53.83 Angle pole in power line easterly and northerly, bears N. 120 lks. dist.

56.13 SE. cor. of house, bears N. 176 lks. dist.

57.83 Road, bears S. and N. 100 lks. to road bearing E. and W.

77.49 Wire fence, bears N. and S.

77.92 The cor. of secs. 5, 6, 7 and 8.

Land gently rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite; undergrowth, medium mesquite, greasewood and cacti.

From the cor. of secs. 5, 6, 31 and 32 on N. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 17 S., R. 14 E., resurveyed under this group.

S. $0^{\circ}08'$ W., on true line bet. secs. 5 and 6.

Over gently rolling desert land, through scattered timber and medium undergrowth.

Along road.

25.15 Fence, bears easterly about 20 lks. dist.

40.55 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. below surface of road, with a stone, 5x5x2 ins., mkd. X, buried on top of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 6 \\ S 5 \end{array}$$

1941

Dependent Resurvey of the Subdivisional Lines
of T. 17 S., R. 14 E.

Chains	from which
	A telephone pole, bears S.25 $\frac{3}{4}$ °E., 98 lks. dist., mkd. X B O.
	A power line pole, bears N.31 $\frac{1}{4}$ °W., 85 lks. dist., mkd. X B O.
79.95	Intersection of roads, bear easterly., westerly., southerly and northerly.
81.04	The cor. of secs. 5,6,7 and 8.

Land, gently rolling.
Soil, sandy loam, 1st and 2nd rate.
Timber, scattered mesquite; undergrowth, medium mesquite, greasewood and cacti.

FINAL TEST OF SOLAR ATTACHMENT.

May 3: In camp in the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 20, T.17 S., R. 14 E., on the meridian described in the field notes of the resurvey of a portion of the San Ignacio de la Canoa Private Land Grant, resurveyed under this group.
At 8h 00m a.m., app.t., I set off 15°40'38" N., on the decl arc; 31°55'50" N., on the lat. arc; and orient the instrument with the solar; the line of sight agrees with the meridian established by Polaris observation.
At 4h 00m p.m., app. t., I set off 31°55'50" N., on the lat. arc; 15°46'32" N., on the decl. arc; and repeat the test of the solar; the line of sight agrees with the meridian established by Polaris observation.

May 3, 1941.

GENERAL DESCRIPTION.

The land embraced within this township is gently rolling desert land. The general elevation of the township is about 3,000 ft. above sea level. The township lies mostly on a slightly rolling mesa on the east side of the Santa Cruz River Valley. The dry bed of the Santa Cruz River skirts along the west boundary of the township following in a northerly direction. A low irregular bluff dividing the bottom lands from the mesa lands, runs from a point about 10 chs. E. of the SW. cor. of the township, approximately N.10°E. to a point lightly east of the $\frac{1}{4}$ section corner on the N. boundary of section 5.

The bottom lands are well developed for agricultural purposes, and are being farmed intensively. The crops consist principally of cotton and head lettuce. The water used to irrigate these lands is pumped from numerous wells which have been developed for that purpose. The mesa lands are gently rolling and slope uniformly to the northwest and are drained by a maze of small sand washes flowing in that direction. Sections 33 to 36 inclusive, lie within the boundary of the U.S. Department of Agriculture Santa Rita Experimental Range. The mesa lands are arid and with the exception of the four sections in the experimental range, have been denuded of their original growth of mesquite timber. In this area erosion of top soil is in an advanced stage and grass production is extremely poor.

The soil is quite sandy, free from any coarse rock, and ranges from 1st to 3rd rate. Vegetation on the undeveloped sections of the township, consist chiefly of greasewood, second growth mesquite, sage and cactus. There is a

Dependent Resurvey of the Subdivisional Lines

of T. 17 S., R. 14 E.

BOOK 4335

Chains

windmill and water tank located in the NW $\frac{1}{4}$ of section 15. U.S. Highway No 89 and a branch of the Southern Pacific Railroad, runs the entire length of the west range of sections of the township. The old Tucson-Nogales road enters the township between sections 5 and 6, and runs south for 2 $\frac{1}{2}$ miles, thence follows the mesa bluff to a point in the SW. corner of section 31. An unimproved road leaves the old Tucson-Nogales road in the northeast corner of section 19, traverses through sections 20, 29, 28, 27, 34 and 35, leaving the township near the $\frac{1}{4}$ section corner of sections 2 and 35 on the south boundary of the township. There are no indications of mineral within the township.

4-680
(Revised May 1934)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

FIELD ASSISTANTS

NAMES	CAPACITY
George B. McDevitt	Principal Assistant
John Drazevich	Chainman
Roy Mashburn	Flagman
John Korfanta	Axeman
Durward W. Schrader	Axeman
Harold T. Bureman	Moundsman
John Boggs	Truckdriver.

49

CERTIFICATE OF SURVEYOR

I, Raymond F. Moss, Assistant Cadastral Engineer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of February, 1941 received from the district cadastral engineer for Arizona, with assignment instructions dated November 4, 1940, I have ~~surveyed~~ resurveyed the Subdivisional Lines of Township 17 South, Range 14 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said ~~re~~ survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona

January 31, 1942

Raymond F. Moss
Assistant Cadastral Engineer
General Land Office

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colorado, April 12, 1945.

The foregoing field notes of the ^{re} survey of the Subdivisional Lines of Township 17 South, Range 14 East, of the Gila and Salt River Meridian in the State of Arizona

executed by Raymond F. Moss, Assistant Cadastral Engineer, under special instructions dated February 5, 1941, and assignment instructions dated November 4, 1940, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

W. H. Stanton
Supervisor of Surveys.

CERTIFICATE OF TRANSCRIPT

~~I certify that the foregoing transcript of the field notes of the above-described surveys in~~
~~is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~