

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

Book B
FIELD NOTES

BOOK 4326

Of the Resurvey of

The Subdivisional Lines of Township 18 South

Range 14 East

4326

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Raymond F. Moss,

Assistant Cadastral Engineer,

General Land Office.

Under special instructions dated February 5, 1941, which provided for the surveys included under Group No. 231, bearing the approval of the Commissioner of the General Land Office under date of February 15, 1941 and assignment instructions dated November 4, 1940.

Survey commenced March 27, 19 41

Survey completed April 22, 19 41

1A

BOOK 4326

INDEX DIAGRAM.

Township 18 South, Range 14 East

San Ignacio
de la Canoa
Private Land
Grant

6	51 5	38 4	29 3	20 2	10 1
50	49	37	28	19	9
7	48 8	36 9	27 10	18 11	8 12
47	47	36	27	17	7
18	46 17	35 16	25 15	16 14	6 13
45	44	34	25	16	6
19	43 20	33 21	24 22	14 23	5 24
42	42	32	23	14	4
30	41 29	31 28	22 27	13 26	3 25
40	39	31	22	12	2
31	39 32	30 33	21 34	11 35	1 30

Dependent Resurvey of the Subdivisional Lines

13

of T. 18 S., R. 14 E.

BOOK 4326

Chains

For all preliminary data regarding instrument and equipment, observations for azimuth and latitude, and test of solar attachment, see the field notes of the boundaries of T. 18 S., R. 14 E., resurveyed under this group.

Preliminary to the resurvey the lines of the original survey are retraced and diligent search is made for all original corners. Identified corners of the original survey are reestablished in their original positions. All lost corners are reestablished at proportionate positions, based on the record of the original survey. The retrace-ment data are thoroughly verified and only the true line notes are given herein.

Reestablishment of the surveys executed by T.F. White, Deputy Surveyor, in 1872, and resurveyed in part by P. Contzen in 1902.

From the cor. of secs. 35 and 36 on S. bdy. of the Tp., which is an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record of the re-survey of the S. bdy. of Tp.
N.0°28'W., bet. secs. 35 and 36.

Over nearly level land, through scattered timber and medium undergrowth.

3.30 Dry wash, 10 lks. wide, 5 ins. deep, course N.60°W. from S.70°E.

20.70 Wash, 60 lks. wide; course N.80°W. from S.70°E.

31.60 Wash, 10 lks. wide, course W.

39.57 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 35 | S 36

1941

from which

A mesquite, 5 ins. diam., bears N.27 $\frac{1}{2}$ °E., 100 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.

A mesquite, 4 ins. diam., bears N.57 $\frac{3}{4}$ °W., 49 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.

49.88 Wash, 40 lks. wide, course N.70°W.

71.58 Wash, 10 lks. wide, course W.

79.14 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

Chains

T 18 S R 14 E
 S 26 | S 25
 +
 S 35 | S 36
 1941

from which

A mesquite, 5 ins. diam., bears S. $32\frac{1}{2}^{\circ}$ E., 111 lks. dist., mkd. T 18 S R 14 E S 36 B T.

A mesquite 5 ins. diam., bears N. $23\frac{3}{4}^{\circ}$ W., 54 lks. dist., mkd. T 18 S R 14 E S 26 B T.

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

No other bearing trees available.

Land, nearly level.

Soil, sandy loam, 2nd rate; and gravelly, 3rd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

From the cor. of secs. 25 and 36 on E. bdy. of the Tp.; described in the field notes of the E. bdy. of T. 18 S., R. 14 E., resurveyed under this group.

S. $89^{\circ}21'$ W., bet. secs. 25 and 36.

Over slightly rolling land, through scattered timber and undergrowth.

- 3.32 Top of flat spur, slopes N. 50° W.
- 14.32 Wash, 30 lks. wide, course N. 65° W.
- 20.72 Right bank of wash, 2 ft. deep, course NW.
- 26.43 Left bank of wash, 20 ft. deep, course NW.
- 26.52 Flat spur, slopes NW.
- 27.44 Road, bears N. 35° W. and S. 35° E.
- 40.16 Proportional distance
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $\frac{1}{4}$ S 25
 S 36
 1941
- from which
- A mesquite, 6 ins. diam., bears N. 42° E., 75 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.
- A mesquite 7 ins. diam., bears S. $62\frac{1}{2}^{\circ}$ W., 114 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.
- 61.70 Center of wash, 60 lks. wide, course N. 80° W.
- 67.30 Low flat spur, slopes N. 60° W.
- 73.90 Wash, 20 lks. wide, course NW.
- 80.32 The cor. of secs. 25, 26, 35 and 36.

Chains N.0°03'W., bet. secs. 25 and 26.

Over nearly level land, through scattered timber and undergrowth.

4.30 Wash, 30 lks. wide, course NW.

7.50 Enter wash, course NW.

12.50 Leave wash.

15.50 Wash, 20 lks. wide, course W.

37.50 Wash, 10 lks. wide, 4 ft. deep, course N.70°W.

39.57 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 26 | S 25

1941

from which

A mesquite, 4 ins. diam., bears N.82 $\frac{1}{2}$ °E., 116 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.

A mesquite, 6 ins. diam., bears S.28 $\frac{1}{2}$ °W., 154 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.

48.57 Center of wash, 80 lks. wide, course N.60°W.

58.00 Wash, 30 lks. wide, course NW.

71.57 Wash, 10 lks. wide, course NW.

78.17 Road, bears N.40°W. and S.30°E.

79.14 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.

T 18 S R 14 E

S 23 | S 24

S 26 | S 25

1941

from which

A mesquite, 6 ins. diam., bears N.54 $\frac{3}{4}$ °E., 21 lks. dist., mkd. T 18 S R 14 E S 24 B T.

A mesquite, 6 ins. diam., bears S.25 $\frac{1}{2}$ °E., 81 lks. dist., mkd. T 18 S R 14 E S 25 B T.

A mesquite, 7 ins. diam., bears S.26°W., 122 lks. dist., mkd. T 18 S R 14 E S 26 B T.

A mesquite, 4 ins. diam., bears N.50 $\frac{1}{4}$ °W., 110 lks. dist., mkd. T 18 S R 14 E S 23 B T.

Land nearly level and rolling.

Chains	Soil, sandy loam, 2nd rate; and gravelly, 3rd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.
	From the cor. of secs. 24 and 25 on E. bdy. of the Tp.; described in the field notes of the E. bdy. of T. 18 S., R. 14 E., resurveyed under this group.
	S.88°45'W., bet. secs. 24 and 25.
	Over rolling land, through scattered timber and desert growth.
9.22	Wash, 20 lks. wide, course N.70°W.
18.53	Wash, 20 lks. wide, course N.70°W.
40.22	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ <u>S 24</u> S 25 1941
	from which
	A mesquite, 6 ins. diam., bears N.4°E., 60 lks. dist., mkd. $\frac{1}{4}$ S.24 B T.
	A mesquite, 6 ins. diam., bears S.61 $\frac{3}{4}$ °E., 73 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.
47.64	Wash, 40 lks. wide, course N.40°W.
58.64	Center of wash, 100 lks. wide, course N.15°W.
64.30	Wash, 40 lks. wide, course NW.
73.30	Wash, 10 lks. wide, course N.W.
80.44	The cor. of secs. 23,24,25 and 26.
	Land, rolling. Soil, sandy loam, 2nd rate; and gravelly, 3rd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.
	N.0°03'E., bet. secs. 23 and 24.
	Over rolling land, through scattered timber and desert grouth.
11.60	Wash, 10 lks. wide, course NW.
22.20	Wash, 10 lks. wide, course N.40°W.
36.42	Wire fence, bears S.31°06'W. and N.31°06'E.
38.00	Center of wash, 100 lks. wide, course N.65°W.
39.57	Proportional distance
	True point for $\frac{1}{4}$ sec. cor. falls in same wash, course N.65°W., a place unsuitable for permanent cor.

Chains
40.57

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 23 | S 24

W C

1941

from which

A mesquite, 4 ins. diam., bears S. $56\frac{1}{2}^{\circ}$ E., 133 lks. dist., mkd. W C $\frac{1}{4}$ S 24 B T.

A mesquite, 6 ins. diam., bears S. 69° W., 42 lks. dist., mkd. W C $\frac{1}{4}$ S 23 B T.

47.92 Center of wash, 60 lks. wide, course N. 40° W.

61.07 Head of drain, course NW.

79.14 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.

T 18 S R 14 E

S 14 | S 13

S 23 | S 24

1941

from which

A mesquite, 5 ins. diam., bears N. 12° E., 70 lks. dist., mkd. T 18 S R 14 E S 13 B T.

A mesquite, 10 ins. diam., bears S. 56° E., 54 lks. dist., mkd. T 18 S R 14 E S 24 B T.

A mesquite, 8 ins. diam., bears S. $70\frac{1}{4}^{\circ}$ W., 172 lks. dist., mkd. T 18 S R 14 E S 23 B T.

A mesquite, 8 ins. diam., bears N. $14\frac{1}{4}^{\circ}$ W., 138 lks. dist., mkd. T 18 S R 14 E S 14 B T.

Land, rolling.

Soil, sandy loam, 2nd rate; and gravelly 3rd rate.

Timber, scattered mesquite and palo verde; undergrowth. mesquite and cactus.

From the cor. of secs. 13 and 24 on E. bdy. of the Tp.; described in the field notes of the E. bdy. of T. 18 S., R. 14 E., resurveyed under this group.

S. $88^{\circ}11'$ W., bet. secs. 13 and 24.

Over nearly level land, through scattered timber and desert growth.

4.35 Wash, 10 lks. wide, course N. 70° W.

33.75 Wash, 40 lks. wide, course NW.

40.25 $\frac{1}{2}$ Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the

Chains ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 13
S 24

1941

from which

A mesquite, 6 ins. diam., bears S.29°W., 130 lks.
dist., mkd. $\frac{1}{4}$ S 24 B T.

A mesquite, 5 ins. diam., bears N.17 $\frac{1}{2}$ °W., 74 lks.
dist., mkd. $\frac{1}{4}$ S 13 B T.

53.96 Fence, bears N.31°16'E. and S.31°16'W.

58.30 Wash, 20 lks. wide, course N.70°W.

64.20 Center of wash, 100 lks. wide, course NW.

76.90 Wash, 50 lks. wide, course N.30°W.

80.00 Wash, 40 lks. wide, course N.30°W.

80.51 The cor. of secs. 13, 14, 23 and 24.

Land, nearly level.

Soil, sandy loam, 2nd rate; and gravelly, 3rd rate.

Timber, scattered mesquite and palo verde; undergrowth,
mesquite and cactus.

N.0°54' W., bet. secs. 13 and 14.

Over rolling land, through scattered timber and under-
growth.

1.40 Wash, 40 lks. wide, course NW.

8.84 Wire fence, bears S.89°40'W. and N.89°40'E.

10.00 Wash, 20 lks. wide, course N.30°W.

16.00 Wash, 20 lks. wide, course N.20°W.

18.70 Wash, 80 lks. wide, course NW.

27.50 Wash, 5 lks. wide, course N.30°W.

36.80 Drain, course NW.

39.57 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 14 | S 13

1941

from which

A mesquite, 5 ins. diam., bears N.45 $\frac{1}{2}$ °E., 126 lks.
dist., mkd. $\frac{1}{4}$ S 13 B T.

A mesquite, 5 ins. diam., bears S.20 $\frac{3}{4}$ ° W., 226 lks.
dist., mkd. $\frac{1}{4}$ S 14 B T.

Chains

49.57 Wash, 30 lks. wide, course N.60°E.

58.27 Wash, 10 lks. wide, course NW.

63.17 Wash, 40 lks. wide, course W.

79.09 Wash, 30 lks. wide, course NW.

79.14 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 11,12,13 and 14, with brass cap mkd.

T 18	S R	14 E
S 11		S 12
S 14		S 13
1941		

from which

A mesquite, 4 ins. diam., bears N.60 $\frac{1}{4}$ °E., 60 lks. dist., mkd. T 18 S R 14 E S 12 B T.

A mesquite, 6 ins. diam., bears S.36 $\frac{3}{4}$ °E., 66 lks. dist., mkd. T 18 S R 14 E S 13 B T.

A mesquite, 5 ins. diam., bears N.6°W., 21 lks. dist., mkd. T 18 S R 14 E S 11 B T.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

No other bearing tree available.

Land, rolling.

Soil, sandy loam, 2nd rate; and gravelly, 3rd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.

From the cor. of secs. 12 and 13 on E. bdy. of the Tp.; described in the field notes of the E. bdy. of T. 18 S., R. 14 E., resurveyed under this group.

S.87°54' W., bet. secs. 12 and 13.

Over rolling land, through scattered timber and dense undergrowth.

.29 Fence, bears N. and S.

.99 Road, bears N. to Sahuarita, and S. to Helvetia.

4.30 Wash, 30 lks. wide, course NW.

12.40 Wash, 10 lks. wide, course NW.

21.00 Wash, 10 lks. wide, course N.10°W.

37.30 Wash, 50 lks. wide, course N.20°W.

40.10 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines

of T. 18 S., R. 14 E.

Chains	$\frac{1}{4}$ <u>S 12</u> S 13 1941 from which A mesquite, 4 ins. diam., bears N.31 $\frac{1}{2}$ °E., 207 lks. dist., mkd. $\frac{1}{4}$ S 12 B T. A mesquite, 12 ins. diam., bears S.18°E., 211 lks. dist., mkd. $\frac{1}{4}$ S 13 B T. 51.80 Wash, 10 lks. wide, course N. 54.00 Wash, 10 lks. wide, course NW. 64.50 Drain, course NW. 70.00 Center of wash, 100 lks. wide, course NW. 80.20 The cor. of secs. 11,12,13 and 14. Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.
	N.0°24'W., bet. secs. 11 and 12. Over rolling land, through scattered timber and dense undergrowth. 4.70 Drain, course NW. 11.90 Wash, 60 lks. wide, course N.60°W. 33.50 Wash, 20 lks. wide, course NW. 39.57 Proportional distance Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S. 11 S. 12 1941 from which A mesquite, 6 ins. diam., bears N.9 $\frac{3}{4}$ °W., 164 lks. dist., mkd. $\frac{1}{4}$ S 11 B T. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. No other bearing tree available. 51.47 Wash, 10 lks. wide, course N.5°W. 55.67 Road bears S.70°E. to Helvetia and W. to Sahuarita. 59.57 Wash, 10 lks. wide, course N.30°W. 62.20 Wash, 10 lks. wide, course N.60°W. 78.64 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the

Chains ground, for witness cor. of secs. 1, 2, 11 and 12, with brass cap mkd.

W C
T 18 S R 14 E
S 2 | S 1
S 11 | S 12

1941

from which

A mesquite, 8 ins. diam., bears N.21 $\frac{1}{4}$ °E., 82 lks. dist., mkd. W C T 18 S R 14 E S 1 B T.

A mesquite, 5 ins. diam., bears S.70 $\frac{3}{4}$ °E., 142 lks. dist., mkd. W C T 18 S R 14 E S 12 B T.

A mesquite 5 ins. diam., bears N.14 $\frac{3}{4}$ °W., 97 lks. dist. mkd W C T 18 S R 14 E S 2 B T.

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high; W. of cor.

No other bearing tree available.

79.14 The true point for cor. of secs. 1, 2, 11 and 12, determined from the original bearing tree, falls in wash, 20 lks. wide, course N.20°W.

from which

The original bearing tree:

A mesquite stump, 12 ins. diam., bears S.7°E., 54 lks. dist., scribe marks visible.

Land, rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.

From the cor. of secs. 1 and 12 on E. bdy. of the Tp.; described in the field notes of the E. bdy. of T. 18 S., R. 14 E., resurveyed under this group.

S.87°54'W., bet. secs. 1 and 12.

Over rolling land, through scattered timber and dense undergrowth.

.65 Drain, course N.20°W.

8.65 Drain, course N.80°W.

17.35 Wash, 10 lks. wide, course NW.

24.15 Wash, 10 lks. wide, course NW.

40.35 The $\frac{1}{4}$ sec. cor., which is a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high.

In center of mound,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Chains	$\frac{1}{4}$ S 1 S 12 1941
	from which
	A mesquite, 6 ins. diam., bears N.9 $\frac{1}{4}$ °E., 54 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
	No other bearing tree available.
42.10	Road; bears N.9°W. and S.40°E.
43.60	Wash; 80 lks. wide, course NW.
45.70	Spur, slopes NW.
49.20	Wash, 10 lks. wide, course N.60°W.
52.70	Drain, course NW.
56.20	Wash, 20 lks. wide, course NW.
64.00	Wash, 50 lks. wide, course N.30°W.
80.70	The cor. of secs. 1,2,11 and 12.
	Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.
	N.0°06'E., bet. secs. 1 and 2.
	Over rolling land, through scattered timber and undergrowth.
25.50	Wash, 40 lks. wide, course N.20°W.
26.80	Wash, 30 lks. wide, course N.80°W.
39.98	Drain, course N.30°W.
40.40	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 2 S 1 1941
	from which
	A mesquite, 4 ins. diam., bears S.45 $\frac{1}{2}$ °E., 154 lks. dist., mkd. $\frac{1}{4}$ S B T.
	A mesquite, 12 ins. diam., bears S.87°W., 97 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.
	Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Chains	
40.18	Wash, 5 lks. wide, course NW.
54.40	Road, bears N.50°W. and S.54°E.
62.10	Wash, 20 lks. wide, course N.60°W.
63.10	Wash, 20 lks. wide, course W.
78.40	Drain, course NW.
80.74	The cor. of secs. 1, 2, 35 and 36 on N. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 18 S., R. 14 E., resurveyed under this group.
	Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, mesquite, and palo verde; undergrowth, mesquite, greasewood and cactus.
	From the cor. of secs. 34 and 35 on S. bdy. of the Tp.; which is an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record of the re-survey of the S. bdy. of Tp. N.0°45'W., bet. secs. 34 and 35.
	Over rolling land, through scattered timber and dense undergrowth.
2.10	Wash, 10 lks. wide, course N.60°W.
8.40	Wash, 60 lks. wide, course N.60°W.
23.10	Wash, 10 lks. wide, course W.
25.00	Road, bears N.71½°W. and S.71½°E.
31.80	Drain, course NW.
36.40	Wash, 10 lks. wide, course N.80°W.
39.69	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	¼
	S 34 S 35
	1941
	from which
	A mesquite, 5 ins. diam., bears S.76¼°E., 167 lks. dist., mkd. ¼ S 35 B T.
	A mesquite, 6 ins. diam., bears S.72¾°W., 105 lks. dist., mkd. ¼ S 34 B T.
43.59	Center of wash, 100 lks. wide, course NW.
49.15	Wash, 20 lks. wide, course NW.
54.89	Wash, 20 lks. wide, course N.80°W.
61.69	Wash, 40 lks. wide, course N.50°W.
63.29	Wire fence, bears S.31°10'W. and N.31°10'E.

Chains	
70.80	Wash, 10 lks. wide, coyrse N.80°W.
73.80	Drain, course W.
79.38	At this point determined by the method of double proportion
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 26,27,34 and 35, with brass cap mkd.
	$\begin{array}{c} T\ 18\ S\ R\ 14\ E \\ S\ 27\ \ S\ 26 \\ S\ 34\ \ S\ 35 \\ 1941 \end{array}$
	from which
	A mesquite, 4 ins. diam., bears N.13°E., 138 lks. dist., mkd. T 18 S R 14 E S 26 B T.
	A mesquite, 6 ins. diam., bears S.64°E., 68 lks. dist., mkd. T 18 S R 14 E S 35 B T.
	A mesquite, 7 ins. diam., bears S.55½°W., 260 lks. dist., mkd. T 18 S R 14 E S 34 B T.
	A mesquite, 8 ins. diam., bears N.19½°W., 49 lks. dist., mkd. T 18 S R 14 E S 27 B T.
	Land, rolling: Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.
	From the cor. of secs. 25,26,35 and 36. N.89°54'W., bet. secs. 26 and 35. Over rolling land, through scattered timber and undergrowth.
15.00	Wash, 20 lks. wide, course N.60°W.
28.00	Wash, 10 lks. wide, course NW.
39.90½	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4}\ S\ 26 \\ S\ 35 \\ 1941 \end{array}$
	from which
	A mesquite, 5 ins. diam., bears N.6¼°E., 71 lks. dist., mkd. ¼ S 26 B T.
	A mesquite, 4 ins. diam., bears S.51¼°W., 32 lks. dist., mkd. ¼ S 35 B T.
47.60	Wash, 80 lks. wide, course N.65°W.
53.91	Draw, 5 lks. wide, course N.60°W.

Dependent Resurvey of the Subdivisional Lines

13

of T. 18 S., R. 14 E.

4326

Chains

61.00 Wash, 30 lks. wide, course NW.

69.20 Wash, 10 lks. wide, course N.50°W.

69.96 Wire fence, bears N.31½°E. and S.31½°W.

70.81 Drain, course NW.

79.81 The cor. of secs. 26,27,34 and 35.

Land, rolling,
Soil, sandy loam, 1st and 2nd rate.
Timber, scattered mesquite and palo verde; undergrowth,
mesquite, greasewood and cactus.

N.0°13'W., bet. secs. 26 and 27.

Over rolling land, through scattered timber and dense undergrowth.

8.70 Drain, course NW.

21.10 Wash, 50 lks. wide, course NW.

23.50 Wash, 10 lks. wide, course NW.

27.30 Center of wash, 150 lks. wide, course NW.

39.69 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼

S 27 | S 26

1941

from which

A mesquite, 5 ins. diam., bears S.49½°E., 77 lks. dist., mkd. ¼ S 26 B T.

A mesquite, 4 ins. diam., bears N.71°W., 97 lks. dist., mkd. ¼ S 27 B T.

54.69 Drain, course N.60°W.

66.00 Wash, 60 lks. wide, course NW.

76.39 Wash, 90 lks. wide, course NW.

79.38 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 22,23,26 and 27, with brass cap mkd.

T 18 S R 14 E

S 22 | S 23

S 27 | S 26

1941

from which

14 BOOK 4326
 Dependent Resurvey of the Subdivisional Lines
 of T. 18 S., R. 14 E.

Chains	<p>A mesquite, 5 ins. diam., bears N.66$\frac{1}{4}$°E., 92 lks. dist., mkd. T 18 S R 14 E S 23 B T.</p> <p>A mesquite, 4 ins. diam., bears S.10°E., 102 lks. dist., mkd. T 18 S R 14 E S 26 B T.</p> <p>A mesquite, 5 ins. diam., bears S.67$\frac{1}{2}$°W., 38 lks. dist., mkd. T 18 S R 14 E S 27 B T.</p> <p>A mesquite, 7 ins. diam., bears N.56°W., 151 lks. dist., mkd. T 18 S R 14 E S 22 B T.</p> <p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, dense mesquite and cactus.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N.89°45'W., bet. secs. 23 and 26.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p> <p>3.05 Road, bears N.40°W. and S.40°E.</p> <p>7.22 Wash, 10 lks. wide, 2 ft. deep, course NW.</p> <p>15.00 Wash, 20 lks. wide, course NW.</p> <p>21.88 Wire fence, bears N.31°11'E. and S.31°11'W.</p> <p>35.80 Wash, 10 lks. wide, course N.60°W.</p> <p>40.02$\frac{1}{2}$ Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\frac{1}{4} \frac{S 23}{S 26}$ <p style="text-align: center;">1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 14 ins. diam., bears S.61$\frac{1}{2}$°W., 63 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.</p> <p>A mesquite, 10 ins. diam., bears N.9$\frac{1}{2}$°W., 134 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.</p> <p>43.05 Wash, 10 lks. wide, course NW.</p> <p>61.55 Drain, course NW.</p> <p>80.05 The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>

of T. 18 S., R. 14 E.

BLK 4326

Chains	N.0°04'W., bet. secs. 22 and 23. Over rolling land, through scattered timber and undergrowth.
4.40	Drain, course NW.
5.60	Drain, course W.
15.30	Wash, 40 lks. wide, course NW.
26.50	Wash, 10 lks. wide, course NW.
28.83	Wash, 10 lks. wide, course NW.
39.69	Proportional distance Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 22 S 23 1941 from which A mesquite, 9 ins. diam., bears S.60 $\frac{3}{4}$ °E., 159 lks. dist., mkd. $\frac{1}{4}$ S 23 B T. A mesquite, 6 ins. diam., bears N.12 $\frac{1}{4}$ °W., 126 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.
40.39	Road, bears N.50°W. and S.50°E.
46.49	Wash, 40 lks. wide, course N.60°W.
55.89	Drain, course NW.
61.59	Wash, 20 lks. wide, course NW.
72.00	Wash, 10 lks. wide, course NW.
79.38	At this point determined by the method of double proportion Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap mkd. T 18 S R 14 E S 15 S 14 S 22 S 23 1941 from which A mesquite, 4 ins. diam., bears N.80 $\frac{3}{4}$ °E., 21 lks. dist., mkd. T 18 S R 14 E S 14 B T. A mesquite, 6 ins. diam., bears S.56°E., 54 lks. dist., mkd. T 18 S R 14 E S 23 B T. A mesquite, 4 ins. diam., bears S.45°W., 102 lks. dist., mkd. T 18 S R 14 E S 22 B T. A mesquite, 10 ins. diam., bears N.43°W., 208 lks. dist., mkd. T 18 S R 14 E S 15 B T.

Chains	<p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p> <hr/> <p>From the cor. of secs. 13,14,23 and 24. N.89°34'W., bet. secs. 14 and 23. Over rolling land; through scattered timber and dense undergrowth.</p> <p>7.50 Wash, 60 lks. wide, course N.30°W.</p> <p>14.18 Wash, 10 lks. wide, course NW.</p> <p>24.24 Wash, 10 lks. wide, course N.60°W.</p> <p>28.59 Drain, course N</p> <p>38.10 Wash, 10 lks. wide, course N.5°W.</p> <p>40.09 Proportional distance</p> <p>True point for $\frac{1}{4}$ sec. cor. falls in wash, 100 lks wide, course N.20°W.</p> <p>41.09 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd,</p> <div style="text-align: center;"> $\frac{1}{4}$ <u>S 14</u> WC S 23 1941 </div> <p style="text-align: right;">from which</p> <p>A mesquite, 6 ins. diam., bears S.40$\frac{1}{4}$°E., 78 lks. dist., mkd. W C $\frac{1}{4}$ S 23 B T.</p> <p>A mesquite, 6 ins. diam., bears N.18$\frac{1}{4}$°W., 107 lks. dist., mkd. W C $\frac{1}{4}$ S 14 B T.</p> <p>48.38 Wash, 10 lks. wide, course NW.</p> <p>53.90 Wash, 10 lks. wide, course NW.</p> <p>58.88 Road, bears N.25°W. and S.25°E.</p> <p>68.50 Wash, 30 lks. wide, course N.65°W.</p> <p>70.38 Wash, 5 lks. wide, course NW.</p> <p>75.60 Wash, 20 lks. wide, course NW.</p> <p>80.18 The cor. of secs. 14,15,22 and 23.</p> <p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.</p>
--------	--

of T. 18 S., R. 14 E.

BOOK 4626

Chains N.0°50'W., bet. secs. 14 and 15.

Over rolling land, through scattered timber and dense undergrowth.

4.10 Wash, 10 lks. wide, course NW.

7.83 Fence, bears E. and W.

20.20 Wash, 60 lks. wide, course N.60°W.

28.20 Wash, 30 lks. wide, course NW.

29.38 Road, bears NW. and SE.

34.40 Drain, course NW.

39.69 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$

S 15 | S 14

1941

from which

A mesquite, 5 ins. diam., bears S.41 $\frac{1}{2}$ °E., 98 lks. dist., mkd. $\frac{1}{4}$ S 14 B T.A mesquite, 6 ins. diam., bears N.34 $\frac{1}{4}$ °W., 80 lks. dist., mkd. $\frac{1}{4}$ S 15 B T.

42.40 Drain, course NW.

54.70 Wash, 40 lks. wide, course N.60°W.

56.60 Wash, 60 lks. wide, course N.60°W.

79.38 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.

T 18 S R 14 E

S 10 | S 11

S 15 | S 14

1941

from which

A mesquite, 16 ins. diam., bears N.6°E., 207 lks. dist., mkd. T 18 S R 14 E S 11 B T.

A mesquite, 8 ins. diam., bears S.67 $\frac{1}{4}$ °E., 188 lks. dist., mkd. T 18 S R 14 E S 14 B T.A mesquite, 6 ins. diam., bears S.52 $\frac{1}{2}$ °W., 80 lks. dist., mkd. T 18 S R 14 E S 15 B T.

A mesquite, 6 ins. diam., bears N.59°W., 37 lks. dist., mkd. T 18 S R 14 E S 10 B T.

Land, rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.

Chains	<p>From the cor. of secs. 11,12,13 and 14.</p> <p>N.89°23'W., bet. secs. 11 and 14.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p> <p>.22 Wash, 30 lks. wide, course NW.</p> <p>20.42 Wash, 60 lks. wide; course N.40°W.</p> <p>26.30 Wash, 60 lks. wide, course NW.</p> <p>31.50 Wash, 30 lks. wide, course NW.</p> <p>36.82 Drain, course NW.</p> <p>40.01$\frac{1}{2}$ Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\frac{1}{4} \frac{S 11}{S 14}$ <p>1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 5 ins. diam., bears N.2$\frac{1}{4}$°E., 140 lks. dist., mkd. $\frac{1}{4}$ S 11 BT.</p> <p>A mesquite, 8 ins. diam., bears S.57$\frac{1}{2}$°E., 60 lks. dist., mkd. $\frac{1}{4}$ S 14 B T.</p> <p>52.02 Wash, 10 lks. wide, course NW.</p> <p>57.70 Wash, 10 lks. wide. course NW.</p> <p>77.70 Wash, 100 lks. wide, course N.20°W.</p> <p>80.03 The cor, of secs. 10,11,14 and 15.</p> <p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.</p> <hr/> <p>N.0°20'W., bet. secs. 10 and 11.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p> <p>5.10 Wash, 60 lks. wide, course N.30°W.</p> <p>19.20 Wash, 30 lks. wide, course N.60°W.</p> <p>35.50 Drain, course N.30°W.</p> <p>39.69 Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
--------	--

of T. 18 S., R. 14 E.

4216

Chains

$\frac{1}{4}$

S 10 | S 11

1941

from which

A mesquite, 6 ins. diam., bears S.74°E., 80 lks.
dist., mkd. $\frac{1}{4}$ S 11 B T.

A mesquite, 8 ins. diam., bears S.43 $\frac{3}{4}$ °W., 14 lks.
dist., mkd. $\frac{1}{4}$ S 10 B T.

41.19 Wash, 30 lks. wide, course NW.

49.99 Wash, 5 lks. wide, course N.10°W.

79.38 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap mkd.

T 18 S R 14 E
S 3 | S 2
S 10 | S 11
1941

from which

A mesquite, 7 ins. diam., bears N.57 $\frac{1}{4}$ °E., 91 lks.
dist., mkd. T 18 S R 14 E S 2 B T.

A mesquite, 6 ins. diam., bears S.73 $\frac{1}{2}$ °E., 170 lks.
dist., mkd. T 18 S R 14 E S 11 B T.

A mesquite, 8 ins. diam., bears S.4 $\frac{3}{4}$ °W., 172 lks.
dist., mkd. T 18 S R 14 E S 10 B T.

A mesquite, 6 ins. diam., bears N.50 $\frac{3}{4}$ °W., 167 lks.
dist., mkd. T 18 S R 14 E S 3 B T.

Land, rolling.
Soil, 1st and 2nd rate.
Timber, mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

From the true point for cor. of secs. 1, 2, 11 and 12.

N.89°14'W., bet. secs. 2 and 11.

Over rolling land, through scattered timber and dense undergrowth.

17.86 Wash, 20 lks. wide, course NW.

26.40 Wash, 40 lks. wide, course NW.

34.38 Drain, course N.60°W.

39.98 Proportional distance

Set an iron post, 3 ft. long, 1 in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 2
S 11
1941

Chains	from which
	A mesquite, 10 ins. diam., bears N.15°E., 118 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.
	A mesquite, 5 ins. diam., bears S.44°E., 122 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.
43.00	Center of wash, 100 lks. wide, course N.30°W.
65.59	Wire fence, bears SE. and NW.
68.29	Wire fence, bears S.52°53'W. and N.52°53'E. in dry wash, 60 lks. wide, course N.30°W,
70.46	Wash, 30 lks. wide, course NW.
74.10	Wash, 20 lks. wide, course N.40°W.
79.00	Wash, 20 lks. wide, course NW.
79.66	Road, bears NW. and SE.
79.96	The cor. of secs. 2,3,10 and 11.
	Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.
	N.0°24'W.; bet. secs. 2 and 3.
	Over rolling land, through scattered timber and dense undergrowth.
.22	Dim road, bears E. and W.
1.98	Wash, 10 lks. wide, course N.30°W.
8.48	Wash, 30 lks. wide, course N.60°W.
17.28	Wash, 40 lks. wide, course N.40°W.
21.38	Wash, 20 lks. wide, course NW.
28.68	Drain, course N.20°W.
39.69	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap, mkd.
	$\frac{1}{4}$
	S 3 S 2
	1941
	from which
	A mesquite, 5 ins. diam., bears S.87½°E., 31 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.
	A mesquite, 8 ins. diam., bears S.79°W., 155 lks. dist., mkd. $\frac{1}{4}$ S 3 B T.
43.22	Wash, 20 lks. wide, course N.20°W.
46.92	Wash, 30 lks. wide, course NW.

Dependent Resurvey of the Subdivisional Lines 21
of T. 18 S., R. 14 E.

4326

Chains 63.72	Drain, course NW.
79.23	<p>The cor. of secs. 2, 3, 34 and 35 on N. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 18 S., R. 14 E., resurveyed under this group.</p> <p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>
	<p>From the cor. of secs. 33 and 34 on S. bdy. of the Tp.; which is an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record of the re-survey of the S. bdy. of Tp. N.1°10'W., bet. secs. 33 and 34.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p>
1.30	Wash, 30 lks. wide, course NW.
12.60	Wash, 20 lks. wide, 2 ft. deep, course N.80°W.
28.60	Drain, course N.60°W.
30.65	Wire fence, bears N.44°55'W. and S.44°55'E.
37.80	Drain, course NW.
39.71	<p>Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\frac{1}{4}$ S 33 S 34 1941 </div> <p style="text-align: right; margin-right: 20px;">from which</p> <p style="margin-left: 40px;">A mesquite, 4 ins. diam., bears N.57°E., 69 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.</p> <p style="margin-left: 40px;">A mesquite, 6 ins. diam., bears S.58½°W., 81 lks. dist., mkd. $\frac{1}{4}$ S 33 B T.</p>
41.81	Drain, course NW.
44.71	Center of wash, 100 lks. wide, course N.70°W.
49.11	Road, bears N.85°E. and S.85°W.
78.92	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. of secs. 27, 28, 33 and 34, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> W C T 18 S R 14 E S 28 S 27 S 33 S 34 1941 </div> <p style="text-align: right; margin-right: 20px;">from which</p>

Chains	<p>A mesquite, 4 ins. diam., bears S. $30\frac{1}{4}^{\circ}$E., 70 lks. dist., mkd. W C T 18 S R 14 E S 34 B T.</p> <p>A mesquite, 4 ins. diam., bears S. $71\frac{3}{4}^{\circ}$W., 19 lks. dist., mkd. W C T 18 S R 14 E S 33 B T.</p> <p>Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p> <p>No other bearing trees available.</p>
79.42	<p>At this point determined by the method of double proportion</p> <p>The true point for cor. of secs. 27, 28, 33 and 34, falls in wash, 100 lks. wide, course NW.</p> <p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. $89^{\circ}57'$W., bet. secs. 27 and 34.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p>
25.63	Center of wash, 100 lks. wide, course NW.
37.46	Drain, course NW.
40.03	<p>Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ <u>S 27</u> S 34 1941 </div> <p style="text-align: right;">from which</p> <p>A mesquite, 4 ins. diam., bears N. $39\frac{3}{4}^{\circ}$E., 19 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.</p> <p>A mesquite, 5 ins. diam., bears S. $47\frac{3}{4}^{\circ}$E., 55 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.</p>
60.50	Center of wash, 100 lks. wide, course NW.
63.31	Road, bears N. and S. 35° E.
64.36	Drain, course NW.
80.06	<p>The true point for cor. of secs. 27, 28, 33 and 34.</p> <p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>

of T. 18 S., R. 14 E.

4826

Chains	<p>N.0°20'W., bet. secs. 27 and 28.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p> <p>1.56 Wire fence, bears N.52°37'E.; enclosure 247 x 395 chs.</p> <p>4.65 Wire fence, bears NE. and SW.; leave enclosure.</p> <p>6.30 Wash, 20 lks. wide, course N.15°W..</p> <p>13.50 Wash, 80 lks. wide, course NW..</p> <p>29.00 Road, bears S.43°W. and N.43°E.</p> <p>39.70 Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 28 S 27</p> <p style="text-align: center;">1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 4 ins. diam., bears N.81$\frac{1}{4}$°E., 114 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.</p> <p>A mesquite, 5 ins. diam., bears N.52°W., 70 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.</p> <p>40.60 Drain, course N.10°W.</p> <p>46.60 Wash, 60 lks. wide, course N.60°W.</p> <p>59.70 Wash, 50 lks. wide, course NW.</p> <p>65.40 Wash, 10 lks. wide, course W.</p> <p>79.40 At this point determined by the method of double proportion</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.</p> <p style="text-align: center;">T 18 S R 14 E</p> <p style="text-align: center;">S 21 S 22</p> <p style="text-align: center;">S 28 S 27</p> <p style="text-align: center;">1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 8 ins. diam., bears N.49$\frac{3}{4}$°E., 188 lks. dist., mkd. T 18 S R 14 E S 22 B T.</p> <p>A mesquite, 4 ins. diam., bears S.44$\frac{1}{4}$°E., 145 lks. dist., mkd. T 18 S R 14 E S 27 B T.</p> <p>A mesquite, 4 ins. diam., bears S.60$\frac{1}{2}$°W., 73 lks. dist., mkd. T 18 S R 14 E S 28 B T.</p> <p>A mesquite, 6 ins. diam., bears N.40$\frac{1}{2}$°W., 242 lks. dist., mkd. T 18 S R 14 E S 21 B T.</p> <p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>
--------	---

Chains	From the cor. of secs. 22,23,26 and 27. S.89°59'W., bet. secs. 22 and 27. Over rolling land, through scattered timber and dense undergrowth.
5.20	Center of wash, 150 lks. wide, course N.65°W.
10.70	Wash, 20 lks. wide, course NW.
29.86	Drain, course NW.
40.11½	Proportional distance Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for ¼ sec. cor., with brass cap mkd. $\frac{1}{4}$ <u>S 22</u> S 27 1941 from which A mesquite, 4 ins. diam., bears North, 80 lks. dist., mkd. ¼ S 22 B T. A mesquite, 6 ins. diam., bears S.62°E., 57 lks. dist., mkd. ¼ S 27 B T.
71.40	Wash, 60 lks. wide, course N.60°W.
78.43	Wash, 5 lks. wide, course NW.
80.23	The cor. of secs. 21,22,27 and 28. Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.
	N.0°10'W., bet. secs. 21 and 22. Over rolling land, through scattered timber and dense undergrowth.
2.90	Wash, 50 lks. wide, course W.
8.90	Drain, course N.60°W.
39.10	Drain, course NW.
39.70	Proportional distance Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 21 S 22 1941 from which A mesquite, 10 ins. diam., bears S.40°E., 284 lks. dist., mkd. ¼ S 22 B T.

of T. 18 S., R. 14 E.

Chains	<p>A mesquite, 6 ins. diam., bears N.70$\frac{3}{4}$°W., 93 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.</p> <p>48.50 Center of wash, 200 lks., wide, course NW.</p> <p>65.45 Wash, 20 lks., wide, course N.60°W.</p> <p>71.00 Road, bears N.75°W. and S.75°E.</p> <p>79.35 Drain, course N.30°W.</p> <p>79.40 At this point determined by the method of double proportion</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 18</td><td>S</td><td>R</td><td>14</td><td>E</td></tr> <tr><td>S</td><td>16</td><td> </td><td>S</td><td>15</td></tr> <tr><td>S</td><td>21</td><td> </td><td>S</td><td>22</td></tr> <tr><td colspan="5" style="text-align: center;">1941</td></tr> </table> </div> <p style="text-align: right;">from which</p> <p>A mesquite, 12 ins. diam., bears N.15$\frac{1}{4}$°E., 129 lks. dist., mkd. T 18 S R 14 E S 15 B T.</p> <p>A mesquite, 9 ins. diam., bears S.56$\frac{1}{4}$°W., 44 lks. dist., mkd. T 18 S R 14 E S 21 B T.</p> <p>Raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, W. of cor.</p> <p>No other bearing trees available.</p> <p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, mesquite and palo verde; undergrowth, mesquite and cactus.</p>	T 18	S	R	14	E	S	16		S	15	S	21		S	22	1941				
T 18	S	R	14	E																	
S	16		S	15																	
S	21		S	22																	
1941																					
3.35 28.65 31.40 40.14 $\frac{1}{2}$	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>West, bet. secs. 15 and 22.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p> <p>Wash, 10 lks. wide, course N.60°W.</p> <p>Wash, 5 lks. wide, course N.60°W.</p> <p>Center of wash, 100 lks. wide, course NW.</p> <p>Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>$\frac{1}{4}$</td><td>S</td><td>15</td></tr> <tr><td></td><td>S</td><td>22</td></tr> <tr><td colspan="3" style="text-align: center;">1941</td></tr> </table> </div> <p style="text-align: right;">from which</p> <p>A mesquite, 8 ins. diam., bears S.8°W., 37 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.</p>	$\frac{1}{4}$	S	15		S	22	1941													
$\frac{1}{4}$	S	15																			
	S	22																			
1941																					

Chains	A mesquite, 8 ins. diam., bears N.71 $\frac{3}{4}$ °W., 93 lks. dist., mkd. $\frac{1}{4}$ S 15 B T.
52.90	Wash, 40 lks. wide, course NW.
80.29	The cor. of secs. 15,16,21 and 22. Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, dense mesquite, greasewood and cactus.
	N.0°47'W., bet. secs. 15 and 16. Over rolling land, through scattered timber and dense undergrowth.
7.50	Wire fence, bears N.89°44'E. and S.89°44'W., in drain course NW.
17.85	Drain, course NW.
25.10	Drain, course N.60°W.
30.05	Wash, 5 lks. wide, course NW.
39.70	Proportional distance Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 16 S 15 1941 from which A mesquite, 6 ins. diam., bears N.83°E., 94 lks. dist., mkd. $\frac{1}{4}$ S 15 B T. A mesquite, 5 ins. diam., bears N.61°W., 106 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
41.60	Wash, 60 lks. wide, course N.60°W.
56.80	Center of wash, 100 lks. wide, course NW.
74.20	Wash, 10 lks. wide, course N.60°W.
79.40	At this point determined by the method of double proportion Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 9,10,15 and 16, with brass cap mkd. T 18 S R 14 E S 9 S 10 S 16 S 15 1941 from which A mesquite, 9 ins. diam., bears N.49°E., 168 lks. dist., mkd. T 18 S R 14 E S 10 B T. A mesquite, 6 ins. diam., bears S.76 $\frac{1}{2}$ °E., 187 lks. dist., mkd. T 18 S R 14 E S 15 B T.

Dependent Resurvey of the Subdivisional Lines

27

of T. 18 S., R. 14 E.

BOOK 4326

Chains	<p>A mesquite, 6 ins. diam., bears S.60$\frac{1}{4}$°W., 53 lks. dist., mkd. T 18 S R 14 E S 16 B T.</p> <p>A mesquite, 5 ins. diam., bears N.44$\frac{1}{4}$°W., 71 lks. dist., mkd. T 18 S R.14 E. S 9 B T.</p> <p>Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N.89°59'W., bet. secs. 10 and 15.</p> <p>Over rolling desert land, through scattered timber and dense undergrowth.</p>
20.20	Wash, 30 lks. wide, course N.30°W.
25.60	Center of wash, 100 lks. wide, course NW.
29.80	Road, bears N.18°W. and S.5°E.
34.62	Wash, 10 lks. wide, course N.10°W.
40.00 $\frac{1}{2}$	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 10}{S\ 15}$ 1941
	from which
	A mesquite, 5 ins. diam., bears N.70 $\frac{1}{4}$ °E., 114 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.
	A mesquite, 4 ins. diam., bears S.6 $\frac{1}{2}$ °W., 94 lks. dist., mkd. $\frac{1}{4}$ S 15 B T.
42.20	Drain, course NW.
62.00	Wash, 10 lks. wide, course N.60°W.
68.70	Wash, 10 lks. wide, course NW.
80.01	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.
	N.0°21'W., bet. secs. 9 and 10.
	Over rolling land, through scattered timber and dense undergrowth.
6.70	Wash, 20 lks. wide, course N.70°W.
8.60	Wash, 30 lks. wide, course N.80°W.
32.70	Wash, 5 lks. wide, course NW.

Chains
39.70

Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$

S 9 | S 10

1941

from which

A mesquite, 7 ins. diam., bears N.43 $\frac{1}{2}$ °E., 110 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.A mesquite, 6 ins. diam., bears N.75°W., 20 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.

41.50 Wash, 5 lks. wide, course NW.

44.50 Wash, 5 lks. wide, course NW.

52.30 Drain, course NW..

71.30 Wash, 20 lks. wide, course N.30°W..

79.40 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 3,4,9 and 10, with brass cap mkd.

T 18 S R 14 E

S 4 | S 3
S 9 | S 10

1941

from which

A mesquite, 4 ins. diam., bears N.78°E., 125 lks. dist., mkd. T 18 S R 14 E S 3 B T.

A mesquite, 5 ins. diam., bears S.87 $\frac{1}{2}$ °E., 106 lks. dist., mkd. T 18 S R 14 E S 10 B T.

A mesquite, 5 ins. diam., bears S.15°W., 62 lks. dist., mkd. T 18 S R 14 E S 9 B T.

A mesquite, 5 ins. diam., bears N.37 $\frac{1}{2}$ °W., 256 lks. dist., mkd. T 18 S R 14 E S 4 B T.

Land, rolling.

Soil, sandy loam, 1st and 2nd rate.

Timber, scattered mesquite and palo verde; undergrowth dense mesquite, greasewood and cactus.

From the cor. of secs. 2,3,10 and 11.

N.89°59'W., bet. secs. 3 and 10.

Over rolling land, through scattered timber and dense undergrowth.

10.86 Road, bears N.35°E. and S.25°W.

27.90 Wash, 10 lks. wide, course NW.

Chains

- 30.98 Wash, 10 lks.wide, course NW.
- 38.90 Wash, 40 lks. wide, course NW.
- 40.09 Proportional distance
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $$\frac{1}{4} \begin{array}{l} S 3 \\ S 10 \end{array}$$
- 1941
- from which
- A mesquite, 4 ins. diam., bears N.5 $\frac{1}{2}$ °E., 84 lks. dist., mkd. $\frac{1}{4}$ S 3 B T.
- A mesquite, 5 ins. diam., bears S.27 $\frac{1}{2}$ °E., 67 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.
- Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
- 51.20 Wash, 20 lks. wide, course NW.
- 57.30 Drain, course N.
- 63.69 Road, bears N.25°W. and S.25°E.
- 79.90 Wash, 5 lks. wide, course N.20°W.
- 80.18 The cor. of secs. 3,4,9 and 10.
- Land, rolling.
Soil, sandy loam, 1st and 2nd rate.
Timber, scattered mesquite and palo verde; undergrowth, dense mesquite, greasewood and cactus.

N.0°35'W.; bet. secs. 3 and 4.

Over rolling land, through scattered timber and dense undergrowth.

- 3.70 Wash, 5 lks. wide, course NW.
- 24.50 Wash, 20 lks. wide, course NW.
- 37.70 Wash, 5 lks. wide, course N.30°W.
- 39.70 Proportional distance
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $$\frac{1}{4} \begin{array}{l} S 4 | S 3 \end{array}$$
- 1941
- from which
- A mesquite, 5 ins. diam., bears S.75 $\frac{1}{2}$ °E., 206 lks. dist., mkd. $\frac{1}{4}$ S 3 B T.
- A mesquite, 8 ins. diam., bears N.77°W., 176 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.

Chains	A bench mark of the U.S. Geological Survey, published elevation 2,963 ft. above mean sea level, bears S.57°19'E., 6.41 chs. dist.
67.00	Drain, course NW.
79.44	The cor. of secs. 3,4,33 and 34 on N. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 18 S., R. 14 E., resurveyed under this group. Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.
	From the cor. of secs. 32 and 33 on S. bdy. of the Tp., which is an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record of the re-survey of the S. bdy. of Tp. N.1°12'W., bet. secs. 32 and 33. Over rolling land, through scattered timber and dense undergrowth.
8.60	Wash, 100 lks. wide, course NW.
40.65	Proportional distance Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S 32 S 33 1941 from which A mesquite, 4 ins. diam., bears N.88 $\frac{1}{4}$ °E., 36 lks. dist., mkd. $\frac{1}{4}$ S 33 B T. A mesquite, 4 ins. diam., bears N.14 $\frac{3}{4}$ °W., 9 lks. dist., mkd. $\frac{1}{4}$ S 32 B T.
40.90	Wash, 60 lks. wide, course N.80°W.
43.05	Wash, 80 lks. wide, course W.
62.35	Continental Madera Canyon Road, bears N.50°40'W. and S.50°40'E.
63.05	Telephone line, bears N.50°40'W. and S.50°40'E.
80.69	Wash, 20 lks. wide, course N.60°W.
81.30	The cor. of secs. 28,29,32 and 33, which is a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high. In center of mound, Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 28,29,32 and 33, with brass cap mkd. T 18 S R 14 E S 29 S 28 S 32 S 33 1941

of T. 18 S., E. 14 E.

1111 213

Chains	from which
	<p>A mesquite, 9 ins. diam., bears S.25°E., 10 lks. dist., mkd. T 18 S R 14 E S 33 B T.</p> <p>A mesquite, 7 ins. diam., bears S.65°W., 51 lks. dist., mkd. T 18 S R 14 E S 32 B T.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>No other bearing trees available.</p> <p>Land, rolling. Soil, sandy, 2nd rate; and rocky 4th rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>
	<p>From the true point for cor. of secs. 27, 28, 33 and 34. N.88°36'W., bet. secs. 28 and 33.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p>
38.37	Road, bears N. and S.
39.92	Proportional distance
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">¼ <u>S 28</u> S 33 1941</p>
	from which
	<p>A mesquite, 6 ins. diam., bears N.4½°E., 87 lks. dist., mkd. ¼ S 28 B T.</p> <p>A mesquite, 9 ins. diam., bears S.77¼°W., 92 lks. dist., mkd. ¼ S 33 B T.</p>
48.81	Wire fence, bears N.44°45'W. and S.44°55'E.
52.24	Road, bears N.15°W. and S.45°E.
64.30	Wash, 60 lks. wide, course N.20°W.
79.84	The cor. of secs. 28, 29, 32 and 33.
	<p>Land, rolling. Soil, sandy loam, 1st rate; and gravelly 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>
	<p>N.0°31'W., bet. secs. 28 and 29.</p> <p>Over rolling land, through scattered timber and undergrowth.</p>
13.00	Wash, 40 lks. wide, course NW.
37.80	Wash, 10 lks. wide, course NW.
39.57	Proportional distance

Chains	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 29 S 28</p> <p style="text-align: center;">1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 5 ins. diam., bears N.22$\frac{1}{2}$°E., 101 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.</p> <p>A mesquite, 5 ins. diam., bears N.73°W., 64 lks. dist., mkd. $\frac{1}{4}$ S 29 B T.</p> <p>48.70 Wash, 10 lks. wide, course NW.</p> <p>53.86 Wash, 20 lks. wide, course NW.</p> <p>61.66 Wash, 20 lks. wide, course NW.</p> <p>70.41 Dim road, bears E. and W.</p> <p>72.46 Center of wash, 150 lks. wide, course N.60°W.</p> <p>72.50 W. end of U.S. Dept. of Agriculture Experimental Plot, bears E. 294 lks. dist.</p> <p>79.14 At this point determined by the method of double proportion</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 20,21,28 and 29, with brass cap mkd.</p> <p style="text-align: center;">T 18 S R 14 E S 20 S 21 S 29 S 28 1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 5 ins. diam., bears S.64$\frac{1}{2}$°E., 194 lks. dist., mkd. T 18 S R 14 E S 28 B T.</p> <p>A mesquite, 7 ins. diam., bears S.56$\frac{1}{2}$°W., 161 lks. dist., mkd. T 18 S R 14 E S 29 B T.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>A fence corner bears S.89$\frac{3}{4}$°W., 195 lks. dist.</p> <p>A fence corner bears S.27$\frac{3}{4}$°W., 423 lks. dist.</p> <p>Land, rolling. Soil, sandy, 2 nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p> <hr/> <p>From the cor. of secs. 21,22,27 and 28. N.88°46'W., bet. secs. 21 and 28.</p> <p>6.93 Wash, 70 lks. wide, course NW.</p> <p>19.63 Drain, course N.60°W.</p>
--------	--

of T. 18 S., R. 14 E.

Chains 31.20 39.57 40.03½	<p>Wash, 50 lks. wide, course NW.</p> <p>Drain, course NW.</p> <p>Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 21}{S\ 28}$</p> <p style="text-align: center;">1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 7 ins. diam., bears S.30°E., 86 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.</p> <p>A mesquite, 10 ins. diam., bears N.1½°W., 262 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.</p> <p>Fence corner on W. side of tank, bears N.7°E., 518 lks. dist.</p> <p>Fence corner on S. side of tank, bears N.59¾°E., 400 lks. dist.</p> <p>Dirt bank, 3 chs. long on E. side of tank, bears N.35°E., 6 chs. dist.</p>
41.07 41.67 55.20 61.50 80.07	<p>Road, bears S.34°W. and N.43½°E.</p> <p>Wash, 5 lks. wide, course NW.</p> <p>Wash, 20 lks. wide, course N. for 2 chs. dist., then turns NW.</p> <p>Fence, bears N.0°08'E. and S.0°08'W.</p> <p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, sandy loam, 1st rate; and gravelly 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>
31.10 35.00 39.57	<p>N.0°12'W., bet. secs. 20 and 21.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p> <p>Wash, 20 lks. wide, course NW.</p> <p>Center of wash, 100 lks. wide, course NW.</p> <p>Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 20 S 21</p> <p style="text-align: center;">1941</p> <p style="text-align: right;">raise a mound</p>


Chains	of stone, 3 ft. base, 2 ft. high, W. of cor.									
44.83	Wash, 20 lks. wide, course NW									
60.57	Wash, 10 lks. wide, course NW.									
68.90	Wash, 30 lks. wide, course NW.									
79.14	At this point determined by the method of double proportion									
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 16,17,20 and 21, with brass cap mkd.									
	<table style="margin: auto;"> <tr><td>T 18</td><td>S R 14</td><td>E</td></tr> <tr><td>S 17</td><td> S 16</td><td></td></tr> <tr><td>S 20</td><td> S 21</td><td></td></tr> </table>	T 18	S R 14	E	S 17	S 16		S 20	S 21	
T 18	S R 14	E								
S 17	S 16									
S 20	S 21									
	1941									
	from which									
	A mesquite, 6 ins. diam., bears N.57 $\frac{3}{4}$ °E., 50 lks. dist., mkd. T 18 S R 14 E S 16 B T.									
	A mesquite, 5 ins. diam., bears S.37 $\frac{1}{4}$ °E., 102 lks. dist., mkd. T 18 S R 14 E S 21 B T.									
	A mesquite, 4 ins. diam., bears N.85°W., 89 lks. dist., mkd. T 18 S R 14 E S 17 B T.									
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.									
	No other bearing trees available.									
	Land, rolling.									
	Soil, sandy loam, 1st rate; and gravelly, 2nd rate.									
	Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.									
	From the cor. of secs. 15,16,21 and 22.									
	N.88°59'W., bet. secs. 16 and 21.									
	Over rolling land, through scattered timber and dense undergrowth.									
.05	Drain, course N.30°W.									
12.05	Wash, 5 lks. wide, course N.60°W.									
22.30	Wash, 5 lks. wide, course N.70°W.									
28.65	Road, bears NW. and SE. on top of spur slopes NW.									
33.60	Wash, 10 lks. wide, course NW.									
38.90	Road, bears N.50°W. and S.50°E.									
40.06	Proportional distance									
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.									

Dependent Resurvey of the Subdivisional Lines
of T. 18 S., R. 14 E.

Chains	$\frac{1}{4}$ S 16 S 21 1941
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	No bearing trees available.
45.00	Drain, course N.80°W.
48.00	Drain, course N.
56.71	Road, bears NW. and SE.
66.50	Center of wash, 100 lks. wide, course NW.
71.20	Wash, 5 lks. wide, course N.
80.12	The cor. of secs. 16,17,20 and 21.
	Land, rolling. Soil, sandy loam, 1st rate; and gravelly, 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.
	N.0°50'W., bet. secs. 16 and 17.
	Over rolling land, through scattered timber and dense undergrowth.
1.30	Drain, course NW.
5.70	Fence, bears N.89°45'E. and S.89°45'W.
8.60	Fence, bears N.89°45'E. and S.89°45'W.
20.00	Center of wash, 200 lks. wide, course NW.
30.30	Junction of washes, 20 lks. wide, course NW. from E. and SE.
39.57	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 17 S 16 1941
	from which
	A mesquite, 6 ins. diam., bears N.66 $\frac{1}{2}$ °E., 102 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
	A mesquite, 5 ins. diam., bears N.15 $\frac{1}{2}$ °W., 214 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.
46.97	Drain, course NW.
51.67	Wash, 10 lks. wide, course NW.
76.97	Wash, 40 lks. wide, course NW.
79.14	At this point determined by the method of double pro- portion

36 BOOK 4826
 Dependent Resurvey of the Subdivisional Lines
 of T. 18 S., R. 14 E.

Chains Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 8,9,16 and 17, with brass cap mkd.



from which

A mesquite, 12 ins. diam., bears N.74°W., 236 lks. dist., mkd. T 18 S R 14 E S 8 B T.

Raise a mound of stone, 3 ft. base, 2 ft. high. W. of cor.

No other bearing trees available.

Land, rolling.

Soil, sandy loam, 1st rate; and gravelly, 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.

From the cor. of secs. 9,10,15 and 16.

N.89°09'W., bet. secs. 9 and 16.


Over rolling land, through scattered timber and undergrowth.

8.46 Wash, 30 lks. wide, course N.

10.10 Wash, 30 lks. wide, course N.

39.99 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A mesquite, 5 ins. diam., bears S.38 $\frac{3}{4}$ °W., 79 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.

A mesquite, 9 ins. diam., bears N.67 $\frac{3}{4}$ °W., 97 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.

56.00 Wash, 10 lks. wide, course NW.

60.92 Road, bears N.20°E. and S.

73.12 Wash, 10 lks. wide, course NW.

79.98 The cor. of secs. 8,9,16 and 17.

Land, rolling.

Soil, 2nd rate, gravelly. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

Dependent Resurvey of the Subdivisional Lines
of T. 18 S., R. 14 E.

ECCO 6020

Chains N.0°19'W., bet. secs. 8 and 9.

Over rolling land, through scattered timber and undergrowth.

5.00 Wash, 20 lks. wide, course W.

13.73 Wash, 20 lks. wide, course N.80°W..

39.57 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S. 8 | S 9

1941

from which

A mesquite, 5 ins. diam., bears S.49 $\frac{1}{4}$ °E., 82 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.

A mesquite, 7 ins. diam., bears S.75 $\frac{1}{2}$ °W., 25 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.

Fence corner bears S.86°W., 31 lks. dist., from which fences bear N., S., and W.

53.27 Wash, 20 lks. wide, course N.40°W..

64.57 Wash, 30 lks. wide, course N.30°W..

79.14 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

T 18 S R 14 E

S 5 | S 4
S 8 | S 9

1941

from which

A mesquite, 5 ins. diam., bears N.19 $\frac{1}{2}$ °E., 115 lks. dist., mkd. T 18 S R 14 E S 4 B T.

A mesquite, 5 ins. diam., bears S.81 $\frac{3}{4}$ °E., 243 lks. dist., mkd. T 18 S R 14 E S 9 B T.

A mesquite, 5 ins. diam., bears S.32 $\frac{1}{2}$ °W., 115 lks. dist., mkd. T 18 S R 14 E S 8 B T.

A mesquite, 5 ins. diam., bears N.17°W., 101 lks. dist., mkd. T 18 S R 14 E S 5 B T.

Land, rolling.

Soil, sandy, 2nd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

Dependent Resurvey of the Subdivisional Lines
of T. 18 S., R. 14 E.

Chains	From the cor. of secs. 3,4,9 and 10.
	N.89°20'W., bet. secs. 4 and 9.
	Over rolling land, through scattered timber and undergrowth.
2.70	Wash, 20 lks. wide, course N.
4.50	Wash, 10 lks. wide, course N.
30.14	Wash, 10 lks. wide, course N.10°W.
40.04	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 4 \\ S 9 \\ 1941 \end{array}$
	from which
	A mesquite, 9 ins. diam., bears N.36°E., 166 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.
	A mesquite, 5 ins. diam., bears S.82 $\frac{1}{2}$ °E., 86 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.
62.80	Wash, 10 lks. wide, course N.20°W.
76.30	Wash, 5 lks. wide, course NW.
80.08	The cor. of secs. 4,5,8 and 9.
	Land, rolling. Soil, sandy loam, 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.
	N.0°29'W., bet. secs. 4 and 5.
	Over rolling land, through scattered timber and undergrowth.
4.50	Wash, 10 lks. wide, course N.30°W.
7.70	Wash, 10 lks. wide, course NW.
18.10	Wash, 5 lks. wide, course NW.
22.05	Wash, 10 lks. wide, course N.80°W.
33.45	Wash, 5 lks. wide, course N.30°W.
39.57	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 5 S 4 \\ 1941 \end{array}$
	from which

Chains	<p>A mesquite, 7 ins. diam., bears N.44$\frac{1}{2}$°E., 114 lks. dist., mkd. $\frac{1}{4}$ S 4 B.T.</p> <p>A mesquite, 4 ins. diam., bears N.70°W., 44 lks. dist., mkd. $\frac{1}{4}$ S 5 B.T.</p>
51.77	Wash, 20 lks. wide, course NW.
68.47	Wash, 20 lks. wide, course NW.
79.00	<p>The cor. of secs. 4,5,32 and 33 on N. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 18 S., R. 14 E., resurveyed under this group.</p> <p>Land, rolling. Soil, sandy loam, 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>
	<p>From the cor. of secs. 31 and 32 on S. bdy. of the Tp., which is an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of Tp. N.1°07'W., bet. secs. 31 and 32.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p>
15.15	Wash, 60 lks. wide, 3 ft. deep, course W.
20.95	Wash, 15 lks. wide, course NW.
25.62	Wash, 20 lks. wide, course W.
39.70	<p>Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S 31 S 32 1941 </div> <p style="text-align: right;">from which</p> <p>A mesquite, 4 ins. diam., bears N.79$\frac{1}{2}$°E., 8 lks. dist., mkd. $\frac{1}{4}$ S 32 B.T.</p> <p>A mesquite, 4 ins. diam., bears N.68°W., 19 lks. dist., mkd. $\frac{1}{4}$ S 31 B.T.</p>
54.89	Wash, 30 lks. wide, course N.60°W.
73.60	Enter wash, course N.30°W.
76.34	Leave wash.
79.40	<p>At this point determined by the method of double proportion</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 29,30,31 and 32, with brass cap mkd.</p> <div style="text-align: center;"> T 18 S R 14 E S 30 S 29 S 31 S 32 1941 </div>

Chains	<p style="text-align: right;">raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>No bearing trees available.</p> <p>Land, rolling. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 88° 21' W., bet. secs. 29 and 32.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p> <p>.10 Wash, 10 lks. wide, course N. 60° W.</p> <p>20.94 Telephone line, bears N. 50° 45' W. and S. 50° 45' E.</p> <p>21.84 Continental Madera Canyon Road, bears N. 50° 45' W. and S. 50° 45' E.</p> <p>39.93 Wash, 40 lks. wide, course N. 70° W.</p> <p>40.14 Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\frac{1}{4} \frac{S \ 29}{S \ 32}$ <p style="text-align: center;">1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 5 ins. diam., bears S. 10° E., 64 lks. dist., mkd. $\frac{1}{4}$ S 32 B T.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>No other bearing tree available.</p> <p>49.18 Drain, course N. 70° W.</p> <p>69.70 Wash, 100 lks. wide, course NW.</p> <p>80.28 The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling. Soil, sandy, 2nd rate; and gravelly; 3rd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p> <hr/> <p>S. 88° 14' W., bet. secs. 30 and 31.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p> <p>1.72 Enter wash, course N. 20° W.</p> <p>3.22 Leave wash.</p>
--------	---

of T. 18 S., R. 14 E.

1920

Chains

25.77 Wash, 10 lks. wide, course NW.

40.16 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

 $\frac{1}{4}$ S 30

S 31

1941

from which

A mesquite, 6 ins. diam., bears N.12°E., 209 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.

A mesquite, 6 ins. diam., bears S.29°W., 121 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.

57.42 Wash, 5 lks. wide, course N.60°W.

64.12 Road, bears N.45°E. and S.45°W.

78.67 Enter wash, course N.80°W.

79.17 Leave wash.

79.42 The cor. of secs. 25, 30, 31 and 36 on W. bdy. of the Tp.; described in the field notes of the W. bdy. of T. 18 S., R. 14 E., resurveyed under this group.

Land, rolling.

Soil, sandy, 2nd rate; and gravelly, 3rd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

From the cor. of secs. 29, 30, 31 and 32.

N.0°34'W., bet. secs. 29 and 30.

Over rolling land, through scattered timber and undergrowth.

16.90 Wash, 80 lks. wide, course N.60°W.

32.60 Wash, 10 lks. wide, course NW.

39.69 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

 $\frac{1}{4}$

S 30 | S 29

1941

from which

A mesquite, 8 ins. diam., bears N.19 $\frac{1}{4}$ °E., 78 lks. dist., mkd. $\frac{1}{4}$ S 29 B T.

A mesquite, 5 ins. diam., bears N.25 $\frac{1}{2}$ °W., 96 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.

Chains

44.09 Continental Madera Canyon Road, bears N.64°09'W. and S.64°09'E.

44.73 Telephone line, bears N.64°09'W. and S.64°09'E.

54.59 Wash, 50 lks. wide, course NW.

79.38 At this point determined by the method of double proportion

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

T 18 S R 14 E
 S 19 | S 20
 S 30 | S 29
 1941

from which

A mesquite, 8 ins. diam., bears S.59½°E., 65 lks. dist., mkd. T 18 S R 14 E S 29 B T.

A mesquite, 5 ins. diam., bears S.1¼°W., 42 lks. dist., mkd. T 18 S R 14 E S 30 B T.

A mesquite, 5 ins. diam., bears N.46¼°W., 64 lks. dist., mkd. T 18 S R 14 E S 19 B T.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

No other bearing tree available.

Land, rolling.

Soil, sandy, 2nd rate; and gravelly, 3rd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

From the cor. of secs. 20, 21, 28 and 29.

S.88°34'W., bet. secs. 20 and 29.

Over rolling land, through scattered timber and dense undergrowth.

1.86 Fence, bears N. and S.

10.20 Wash, 100 lks. wide, course N.30°W.

31.10 Wash, 20 lks. wide, course NW.

35.10 Wash, 10 lks. wide, course NW.

40.14 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼ S 20
 S 29
 1941

from which

A mesquite, 8 ins. diam., bears N.10¼°E., 285 lks.

Chains	<p>dist., mkd. $\frac{1}{4}$ S 20 B T.</p> <p>A mesquite, 9 ins. diam., bears S. $36\frac{3}{4}^{\circ}$ E., 123 lks. dist., mkd. $\frac{1}{4}$ S 29 B T.</p>
41.98	Wash, 5 lks. wide, course N. 80° W.
60.70	Wash, 80 lks. wide, course NW.
79.30	Wash, 10 lks. wide, course N. 60° W.
80.28	The cor. of secs. 19, 20, 29 and 30.
	<p>Land, rolling. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>
	<p>S. $88^{\circ}53'$ W., bet. secs. 19 and 30.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p>
16.29	Wash, 20 lks. wide, course N. 30° W.
28.09	Enter wash, course N.
29.09	Leave wash.
40.08	Proportional distance
	<p>Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	$\frac{1}{4} \begin{array}{r} \text{S } 19 \\ \text{S } 30 \\ 1941 \end{array}$
	from which
	<p>A mesquite, 4 ins. diam., bears N. $70\frac{1}{2}^{\circ}$ E., 70 lks. dist., mkd. $\frac{1}{4}$ S 19 B T.</p>
	<p>A mesquite, 4 ins. diam., bears S. $41\frac{1}{4}^{\circ}$ W., 80 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.</p>
49.05	Drain, course NW.
64.08	Telephone line, bears N. $70^{\circ}50'$ W. and S. $70^{\circ}50'$ E.
64.25	Fence, bears N. $70^{\circ}50'$ W. and S. $70^{\circ}50'$ E.
66.40	Continental Madera Canyon Road, bears N. $70^{\circ}50'$ W. and S. $70^{\circ}50'$ E.
79.05	The cor. of secs. 19, 24, 25 and 30 on W. bdy. of the Tp.; described in the field notes of the W. bdy. of T. 18 S., R. 14 E., resurveyed under this group.
	<p>Land, rolling. Soil, sandy, 2nd rate; and gravelly, 3rd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p>

Chains From the cor. of secs. 19,20,29 and 30.

N.0°21'W., bet. secs. 19 and 20.

Over rolling land, through scattered timber and undergrowth.

.56 Wash, 20 lks. wide, course N.65°W.

11.00 Wash, 5 lks. wide, course NW.

19.70 Wash, 40 lks. wide, course NW.

35.40 Wash, 100 lks. wide, course N.60°W.

39.69 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S 19 | S 20

1941

from which

A mesquite, 5 ins. diam., bears S.70 $\frac{3}{4}$ °E., 35 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.

A mesquite, 6 ins. diam., bears S.37 $\frac{1}{2}$ °W., 109 lks. dist., mkd. $\frac{1}{4}$ S. 19 B T.

39.99 Road, bears NW. and SE.

69.39 Road, bears NW. and SE.

79.38 The cor. of secs. 17,18,19 and 20, which is a sandstone, 8x6x6 ins. above ground, mkd. with 3 notches on S. and 5 notches on E. edge, set in a small mound of stone.

In place of **corner stone** which is buried alongside

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 17,18,19 and 20, with brass cap mkd.

T 18 S R 14 E

S 18 | S 17

S 19 | S 20

1941

from which

A mesquite, 5 ins. diam., bears S.40 $\frac{1}{4}$ °E., 103 lks. dist., mkd. T 18 S R 14 E S 20 B T.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

No other bearing trees available.

Land, rolling.

Soil, sandy, 2nd rate; and gravelly, 3rd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

Chains	<p>From the cor. of secs. 16,17,20 and 21.</p> <p>S.88°41'W., bet. secs. 17 and 20.</p> <p>Over rolling land, through scattered timber and undergrowth.</p> <p>1.65 Wire fence, bears N. and S.</p> <p>10.80 Wash, 10 lks. wide, course NW.</p> <p>17.02 Road, bears NW. and SE.</p> <p>27.80 Wash, 80 lks. wide, course N.10°W.</p> <p>36.72 Road, bears N.40°W. and S.40°E.</p> <p>40.22½ Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ <u>S 17</u> S 20 1941</p> <p style="text-align: right;">from which</p> <p>A mesquite, 5 ins. diam., bears N.70$\frac{3}{4}$°E., 118 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.</p> <p>A mesquite, 5 ins. diam., bears S.62°E., 155 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.</p> <p>61.40 Wash, 30 lks. wide, course N.65°W.</p> <p>73.75 Drain, course NW.</p> <p>77.95 Enter wash, course N.</p> <p>78.95 Leave wash.</p> <p>80.45 The cor. of secs. 17,18,19 and 20.</p> <p>Land, rolling. Soil, sandy loam, 1st rate; and gravelly, 3rd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.</p> <hr/> <p>S.89°06'W., bet. secs. 18 and 19.</p> <p>Over rolling land, through scattered timber and undergrowth.</p> <p>11.00 Drain, course NW.</p> <p>36.26 Wash, 20 lks. wide, course N.60°W.</p> <p>38.79 The $\frac{1}{4}$ sec. cor., which is a granite stone, 8x6 ins., 12 ins. above ground, mkd. $\frac{1}{4}$ 18 on N. face, and 19 on S. face, and witnessed by a mound of stone N. of cor.</p> <p>In place of corner stone which is buried alongside</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
--------	--

Chains

$$\frac{1}{4} \begin{array}{l} \text{S 18} \\ \text{S 19} \\ 1941 \end{array}$$

rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.

No bearing trees available.

Thence

West, bet. secs. 18 and 19.

10.00 Spur, slopes NW.

15.20 Wash, 100 lks. wide, course NW.

35.00 The closing cor. of frac. secs. 18 and 19 on the SE. bdy. of the San Ignacio de la Canoa Private Land Grant; described in the field notes of a portion of the San Ignacio de la Canoa Private Land Grant, resurveyed under this group. N. 22° 56' E., 20.06 chs. to 23½ M. P.

Land, rolling.

Soil, gravelly, 2nd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite and cactus.

From the cor. of secs. 17, 18, 19 and 20.

N. 0° 02' E., bet. secs. 17 and 18.

Over rolling land, through scattered timber and dense undergrowth.

3.50 Wash, 50 lks. wide, course NW.

7.40 Wash, 20 lks. wide, course W.

29.80 Drain, course NW.

39.00 Wash, 30 lks. wide, course NW.

40.15 The $\frac{1}{4}$ sec. cor., which is a granite stone, 8x6 ins., 6 ins. above ground, mkd. $\frac{1}{4}$ 18 on W. face, and $\frac{1}{4}$ 17 on E. face.

In place of **corner stone** which is buried alongside

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4}$$

$$\text{S 18} \mid \text{S 17}$$

$$1941$$

from which

A mesquite, 5 ins. diam., bears N. 37° E., 33 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.

A mesquite, 4 ins. diam., bears S. 87¼° W., 136 lks. dist., mkd. $\frac{1}{4}$ S 18 B T.

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

of T. 18 S., R. 14 E.

FORM 6000

Chains Thence

N.0°56'W., bet. secs. 17 and 18.

4.00 Wash, 10 lks. wide, course N.60°W.

22.10 Drain, course N.60°W.

39.68 The cor. of secs. 7,8,17 and 18, which is a sandstone, 8x8 ins., 6 ins. above ground, mkd. with 4 notches on S. and 5 notches on E. edge.

In place of **corner stone** which is buried alongside.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 7,8,17 and 18, with brass cap mkd.

T 18	S R	14 E
S 7		S 8
S 18		S 17
1941		

from which

The original bearing tree:

A mesquite, 14 ins. diam., bears N.59°E., 155 lks. dist., I do not uncover the marks.

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

No other bearing trees available.

Land, rolling.

Soil, sandy, 2nd rate; and gravelly, 3rd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

From the cor. of secs. 8,9,16 and 17.

S.89°11'W., bet. secs. 8 and 17.

Over rolling land, through scattered timber and undergrowth.

.32 Fence, bears N. and S.

1.82 Wash, 30 lks. wide, course N.

30.50 Wash, 10 lks. wide, course NW.

40.02½ Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼	S 8
	S 17

1941.

from which

A mesquite, 7 ins. diam., bears S.17¾°E., 97 lks. dist., mkd. ¼ S 17 B T.

Raise a mound of stone, 2 ft. base, 1½ ft. high, N.

Chains	of cor.
	No other bearing tree available.
43.44	Wash, 20 lks. wide, course NW.
49.94	Drain, course NW.
59.50	Enter wash, course N.80°W.
61.50	Leave wash.
73.94	Wash, 10 lks. wide, course NW. for 50 lks. dist., then empties into large wash, course N.80°W.
77.90	Wash, 20 lks. wide, course N.
80.05	The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, sandy, 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.
	N.89°53'W., bet. secs. 7 and 18. Over rolling land, through scattered timber and dense undergrowth.
5.20	Drain, course NW.
8.00	Dim road, bears NW. and SE.
10.40	Drain, course NW.
24.00	Wash, 10 lks. wide, course NW.
31.60	Road, bears NW. and SE.
39.05	The closing cor. of frac. secs. 7 and 18 on SE. bdy. of the San Ignacio de la Canoa Private Land Grant; described in the field notes of a portion of the San Ignacio de la Canoa Private Land Grant, resurveyed under this group. N. 22° 56' E., 14.57 chs. to 24½ M. P. Land, rolling. Soil, sandy, 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.
	From the cor. of secs. 7, 8, 17 and 18. N.0°30'W., bet. secs. 7 and 8. Over rolling land, through scattered timber and dense undergrowth.
1.50	Enter wash, course NW.
4.50	Leave wash.
21.10	Spur, slopes NW.
26.38	Wash, 40 lks. wide, course N.60°W.
39.80	Wire fence, bears N.89¼°E. and S.89¼°W.
39.81	The ¼ sec. cor., which is a sandstone, 8x7 ins. 6 ins.

of T. 18 S., R. 14 E.

BOOK 4326

Chains above ground, mkd. $\frac{1}{4}$ 7 on W. face, and 8 on E. face.

In place of corner stone which is buried alongside

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$

S 7 | S 8

1941

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Find no trace of the original NE. and NW. bearing trees.

Thence

N.0°34'W., bet. secs. 7 and 8.

15.50 Wash, 100 lks. wide, course NW.

30.00 Wash, 30 lks. wide, course NW.

40.25 The cor. of secs. 5,6,7 and 8, which is a sandstone, 8x6 ins., 6 ins. above ground, mkd. with 5 notches on S. and 5 notches on E. edge.

In place of corner stone which is buried alongside

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 5,6,7 and 8, with brass cap mkd.

T 18 S R 14 E

S 6 | S 5
S 7 | S 8

1941

from which

The original bearing trees:

A mesquite, 5 ins. diam., bears N.42°W., 108 lks. dist., mkd. T 18 S R 14 E S 6 B T.

A mesquite stump, 10 ins. diam., bears S.84°W., 212 lks. dist.

New bearing tree:

A mesquite, 5 ins. diam., bears S.41 $\frac{1}{2}$ °E., 141 lks. dist., mkd. T 18 S R 14 E S 8 B T.Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

No other bearing trees available.

Land, rolling.

Soil, sandy loam, 1st rate; and sandy, 2nd rate.

Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

Chains	From the cor. of secs. 4,5,8 and 9. S.89°46'W., bet. secs. 5 and 8. Over rolling land, through scattered timber and undergrowth.
.10	Fence, bears N. and S.
9.00	Wash, 20 lks. wide, course NW.
10.93	Wash, 5 lks. wide, course N.30°W.
25.90	Wash, 20 lks. wide, course N.30°W.
40.12	Proportional distance Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{S \ 5}{S \ 8}$ 1941 from which A mesquite, 5 ins. diam., bears S.33 $\frac{3}{4}$ °W., 20 lks. dist., mkd. $\frac{1}{4}$ S 8 B T. A mesquite, 5 ins. diam., bears N.55 $\frac{1}{2}$ °W., 61 lks. dist., mkd. $\frac{1}{4}$ S 5 B T.
40.65	Wash, 10 lks. wide, course NW.
49.25	Dim road, bears NW. and SE.
80.24	The cor. of secs. 5,6,7 and 8. Land, rolling. Soil, sandy, 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.
	S.89°58'W., bet. secs. 6 and 7. Over rolling land, through scattered timber and dense undergrowth.
4.30	Road, bears N.70°E. and S.50°W.
10.00	Same road, bears N.65°W. and S.65°E.
14.10	Wash, 30 lks. wide, course N.60°W.
20.52	Same road, bears N.60°W. and N.60°E. Branch road, bears S.60°E.
29.90	Same road, bears S.60°W. and N.60°E.
37.50	Wash, 100 lks. wide, course NW.
39.98	The $\frac{1}{4}$ sec. cor., determined from the original bearing trees. At point for corner Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

of T. 18 S., R. 14 E.

BOOK 4826

Chains

$$\frac{1}{4} \frac{S 6}{S 7}$$
 1941

from which

The original bearing trees:

A mesquite stump, 8 ins. diam., bears N.77°E., 89 lks. dist.

A mesquite, 12 ins. diam., bears S.57½°W., 96 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

No other bearing trees available.

Thence

N.88°42'W., on true line bet. secs. 6 and 7.

- 3.00 Spur, slopes N.30°W.
- 5.86 Drain, course NW.
- 8.50 Wash, course NW.
- 14.50 Road, bears N.35°W. and S.50°E.
- 35.20 Edge of mesa, bears N. and S.
- 36.00 Enter Santa Cruz Valley, bears N. and S.
- 36.25 Wash, 20 lks. wide, course SE.
- 38.21 The cor. of secs. 1,6,7 and 12 on W. bdy. of the Tp.; described in the field notes of the W. bdy. of T. 18 S., R. 14 E., resurveyed under this group.
- Land, rolling.
Soil, gravelly, 3rd rate.
Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

From the cor. of secs. 5,6, 7 and 8.

N.0°06'W., bet. secs. 5 and 6.

Over rolling land, through scattered timber and dense undergrowth.

- 31.70 Road, bears N.60°W. and E.

- 40.12 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

 $\frac{1}{4}$

S 6 | S 5

1941

from which

Chains	A mesquite, 5 ins. diam., bears N.63 $\frac{3}{4}$ °E., 107 lks. dist., mkd. $\frac{1}{4}$ S 5 B T.
	A mesquite, 7 ins. diam., bears N.22 $\frac{3}{4}$ °W., 61 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.
	NE. cor. of cabin, bears S.86 $\frac{1}{2}$ °W., 10.78 chs. dist.
49.50	Wash, 10 lks. wide, course NW.
58.00	Wash, 10 lks. wide, course N.10°W.
67.20	Wash, 50 lks. wide, course W.
80.17	The cor. of secs. 5,6,31 and 32 on N. bdy. of the Tp.; described in the field notes of the N. bdy. of T. 18 S., R. 14 E., resurveyed under this group.
	Land, rolling. Soil, sandy loam, 1st and 2nd rate. Timber, scattered mesquite and palo verde; undergrowth, mesquite, greasewood and cactus.

For final test of solar, see the field notes of the subdivision of T. 17 S., R. 14 E., resurveyed under this group.

General Description.

The land embraced within this township is gently rolling desert. The general elevation of the township is about 3,500 ft. above sea level, and has a gentle uniform slope NW. through the township. The soil ranges from 1st to 3rd rate sandy loam silt, is generally free from large rock, and erodes readily during heavy rains. The U.S. Department of Agriculture Santa Rita Experimental Range area in secs. 1 to 4, 9 to 16, and 21 to 36 incl., bears a medium growth of mesquite and palo verde timber. The area outside of the range has been denuded of its virgin timber. A medium and heavy growth of mesquite, greasewood, cactus and sage, covers the entire township. Native grasses grow well over the experimental range. The experimental range boundary is fenced with barbed wire strung on steel posts. Several experimental plots have been fenced on the range area, and dirt storage tanks have been developed in some of the larger drains where water for livestock accumulates during the rainy season. The Continental Madera Canyon Road, and Forest Service telephone line enter the township in the SW $\frac{1}{4}$ of sec. 19, and traverse through secs. 19, 30, 29, 32 and 33, leaving the township in the SE $\frac{1}{4}$ of sec. 33. The Sahuarita and Helvetia road, enters the township near the $\frac{1}{4}$ sec. cor. on the E. bdy. of sec. 12, and traverse through secs. 12, 1 and 2, leaving the township near the $\frac{1}{4}$ sec. cor. on the N. bdy. of sec. 2. There are no permanent springs within the township, and no indications of mineral.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

1934 2223

FIELD ASSISTANTS

NAMES	CAPACITY
George B. McDevitt	Principal Assistant
John Drazevich	Chainman
Roy Mashburn	Flagman
John Korfanta	Axeman
Durward W. Schrader	Axeman
Roger Kenneth Waters Jr.,	Axeman
Harold T. Bureman	Moundsman
John Boggs	Truckdriver

54

CERTIFICATE OF SURVEYOR

BOOK 4626

I, Raymond F. Moss, Assistant Cadastral Engineer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of February 1941, received from the district cadastral engineer for Arizona, with assignment instructions dated November 4, 1940, I have surveyed resurveyed the Subdivisional Lines of Township 18 South, Range 14 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said **re** survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona
January 31, 1942

Raymond F. Moss
Assistant Cadastral Engineer
General Land Office

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,
Denver, Colorado, April 12, 1945.

The foregoing field notes of the ^{re} survey of The Subdivisional Lines of Township 18 South, Range 14 East of the Gila and Salt River Meridian in the State of Arizona

executed by Raymond F. Moss, Assistant Cadastral Engineer, under special instructions dated February 5, 1941, and assignment instructions dated November 4, 1940, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

W. H. Horton
Supervisor of Surveys.

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~