

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

Book G

BOOK 4329

FIELD NOTES

OF THE

Resurvey of a Portion of the

East Boundary of Township 6 North, Range 7 West

and the

Survey of the Subdivisional Lines of

Township 6 North, Range 6 West

4329

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Raymond F. Moss, Public Land Surveyor.

General Land Office

Under special instructions dated July 13, 1939, which provided for the surveys included under Group No. 228, Arizona bearing the approval of the Commissioner of the General Land Office under date of August 23, 1939 and assignment instructions dated November 22, 1939.

Survey commenced March 7, 1940

Survey completed April 8, 1940

1A

BOOK 4829

# INDEX DIAGRAM.

		Township 6 North.				Range 6 West.			
		51	49	39	30	21	11		
1		51	51	39	30	21	11	12	
	6	50	5	38	4	29	3	20	2
	49	48		37		28		19	
7		47	8	36	9	27	10	18	11
	46	46		36		26		17	
18		45	17	35	16	26	15	17	14
	44	44		34		25		16	
19		43	20	33	21	24	22	15	23
	42	41		32		23		14	
30		41	29	32	28	23	27	14	26
	40	40		31		22		13	
31		39	38	30	33	21	34	12	35
								2	36

## Township 6 North, Range 6 West

4329

## Chains

The resurveys and surveys hereinafter described were executed with Gurley solar transit No. 371537. The instrument is equipped with the Smith solar attachment and otherwise conforms to the standard requirements of the General Land Office. For test of this instrument, see the final test described in the field notes of the subdivision of T. 6 N., R. 5 W., surveyed under this group.

The azimuth of all the lines of survey herein described were determined with the solar attachment.

All measurements were made with a Lallie steel tape 5 chs. in length, graduated every link for the first 100 links, and the remainder at intervals of 10 links. The tape was tested by comparison with a Lufkin standard steel tape and found correct. All measurements were made on the slope, the vertical angle determined with a clinometer in good adjustment, and the horizontal equivalents entered in the field notes.

-----  
Resurvey of a Portion of the E. Bdy. of T. 6 N., R. 7 W.

-----  
Reestablishment of a survey executed by D. R. Averill in 1929..

-----  
Preliminary to the resurvey, the line of the original survey was retraced and only the true line notes are given here.

-----  
From the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, as evidenced by an iron post, 1 in. diam., set, marked and witnessed as described in the official record.

North between secs. 1 and 6.

Over rolling land, through scattering timber and undergrowth.

Ascend gradually along a broken E. slope..

- 1.75 Spur, slopes E.; desc. 57 ft. over a N. slope.
- 5.50 Ravine, course N. 70° E.; asc. 41 ft. over a SE. slope.
- 12.50 Spur, slopes N. 70° E.; desc. 42 ft. over a N. slope.
- 15.00 Ravine, course N. 80° E.; thence along an E. slope.
- 26.90 Point of spur, from S. 20° W.; desc. 18 ft. over a N. slope.
- 31.00 Wash, 15 lks. wide, course E.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at cor. of lots 4 and 5 of sec. 6 only, with brass cap marked

4  
s1 | — s6  
5

1940

raise a mound  
of stone, 3 ft. base, 3 ft. high, E. of cor.

- 85.88 The closing corner of Ts. 6 N., Rs. 6 and 7 W. as evidenced by an iron post, 3 ins. diam., set, marked and witnessed as described in the official record.

From this corner, the corner of Ts. 7 N., Rs. 6 and 7 W., bears N. 89° 57' E., 10.06 chs. dist., as evidenced by

## Resurvey of a Portion of the E. Bdy. of T. 6 N., R. 7 W.

Chains	an iron post, 3 ins. diam., set, marked and witnessed as described in the official record.
	Land, rolling.
	Soil, rocky, 3rd rate.
	Timber, palo verde and mesquite; undergrowth, greasewood, cats claw and cactus.
-----	
Subdivision of T. 6 N., R. 6 W.	
-----	
	From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp., as evidenced by an iron post, 3 ins. diam., set, marked and witnessed as described in the official record.
	N. 0° 01' W., bet. secs. 35 and 36.
	Over rolling land, through scattering timber and undergrowth.
3.90	Short wash, 10 lks. wide, course S. 30° E.
20.90	Road, bears N. 70° E. and N. 70° W.
25.70	Wash, 30 lks. wide, course S. 50° E.; asc. .60 ft. over a S. slope.
26.70	Dim road, bears N. 70° W. and S. 70° E.
33.20	Top of rocky hill; asc. 11 ft. along a W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, over a cross cut in bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S35   S36 1940
42.10	Head of a wash, course S. 40° W.; asc. 137 ft. over S. slope.
50.30	Rocky spur, slopes SE.; along E. slope.
53.94	Intersect line 1-2 of the Jane Elmore, patented lode mining claim, M.S. No. 2511, 8.35 chs. S. 79° 40' E. of cor. No. 2, an iron post, 1 in. diam., set in a mound of stone, 4 ft. base, 2 ft. high, with brass cap properly marked. Across patented mineral land.
55.40	Ridge, bears S. 20° W. and N. Along top of ridge.
60.40	Ridge, bears N. 40° W. and S.; desc. 86 ft. over NE. slope.
63.06	Intersect line 3-4 of the Jane Elmore patented lode mining claim, M.S. No. 2511, 6.73 chs. S. 79° 27' E. of Cor. No. 3 thereof, an iron post, 1 in. diam., set in a mound of stone, 4 ft. base, 2 ft. high, with brass cap properly marked. Cor. No. 4 of this claim, bears S. 79° 27' E., 15.94 chs. dist., an iron post, 1 in. diam., set in a mound of stone, 4 ft. base, 12 ft. high, with brass cap properly marked. Line 2-3 of this claim is N. 10° 13' E., 8.99 chs. Leave patented mineral land.
69.90	Wash, 10 lks. wide, course S. 60° E.; asc. 43 ft. over S. slope.
75.50	Spur, slopes E.; desc. 34 ft. over N. slope.

## Subdivision of T. 6 N., R. 6 W.

Chains	
80.00	Set an iron post, 3 ft. long, 2 ins. diam.; 8 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 25, 26, 35 and 36, with brass cap marked
	T6N R6W S 26   S 25 S 35   S 36 1940
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde, ironwood and mesquite; undergrowth, greasewood, cactus, cats claw, ocotillo and sage.
	S. 89° 59' E., on a random line bet. secs. 25 and 36.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.04	The cor. of secs. 25, 30, 31 and 36, on the E. bdy. of Tp., as evidenced by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the field notes of the survey of the W. bdy. of T. 6 N., R. 5 W., under this group Thence
	N. 89° 59' W., on true line bet. secs. 25 and 36.
	Over rolling land, through scattering timber and undergrowth.
	Across surveyed but unpatented mineral land.
4.65	Wash, 20 lks. wide, course S. 30° W.
10.75	Road, bears N. 20° W. and S. 10° W.
11.04	Telephone line, bears N. and S.
14.05	Road, bears N. and S. 20° W.
16.75	Wash, 50 lks. wide, course S.
23.00	Short spur, slopes S.; desc. 51 ft. over broken land.
25.05	Road, bears N. 20° W. and S. 20° E.
28.03	From this point, which is on S. end of mine dump: The SW. cor. of steel hoist tower, bears N. 34° W.; 2.58 chs. dist.  The SW. cor. of concrete platform for hoist engine, bears N. 49° E., 2.47 chs. dist.
30.00	Foot of descent; asc. 29 ft. over an E. slope.
33.45	Dirt road, bears NW. and SE.
35.05	Saddle in ridge, bears N. and S.; along N. slope.
38.55	Short spur, slopes N.; desc. 9 ft. over W. slope.
40.02	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S 25 S 36 1940

Subdivision of T. 6 N., R. 6 W.

Chains	Desc. 65 ft. over W. slope.
43.36	Intersect line 2-3, Vulture North Extension No. 10, surveyed but unpatented lode mining claim, M.S. No. 4147, 0.65 chs. N.5°49'W. of Cor. No. 2, thereof, determined from witness cor., S.80°50'E., 11.4 lks. Leave surveyed but unpatented mineral land.
47.25	Center of wash, 150 lks. wide, course S.30°E. Across point of low spur from N.
51.05	Wash, 50 lks. wide, course S.20°E.; asc. 50 ft. over E. slope.
55.45	Short spur, slopes N.; desc. 17 ft. over W. slope.
58.95	Drain, course N.30°E.; asc. 75 ft. over rolling NE. slope to spur.
61.45	Road, bears NW. and SE.; ends about 10 chs. SE.
71.35	Spur, slopes N. Along rolling N. slope:
80.04	The cor. of secs. 25, 26, 35 and 36. Land, rolling. Soil, rocky, 4th rate. Timber, palo verde; ironwood and mesquite; undergrowth, cactus, cats claw and ocotillo.
-----	
	N.0°01'W., bet. secs. 25 and 26. Over rolling land, through scattering timber and undergrowth. Desc. 40 ft. over a N. slope:
9.10	Wash, 20 lks. wide, course N.60°E.
22.80	Wash, 15 lks. wide, course S.30°E.
30.05	Intersect line 1-2; Vulture Northwest Fraction, surveyed but unpatented lode mining claim, M.S. No. 4147, 9.48 chs. S.19°25'E. of Cor. No. 2 thereof. Across surveyed but unpatented mineral land.
37.50	Dim road, bears NW. and SE.
38.76	Intersect line 2-3, Vulture Northwest Fraction, M.S. No. 4147, 3.15 chs. S.85°E. of Cor. No. 2 thereof. Leave surveyed but unpatented mineral land.
38.90	Ravine, course S.30°E. Over rolling land.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at ¼ sec. cor., with brass cap marked.
	<p>S 26   S 25 1940</p>
	from which
	An ironwood, 12 ins. diam., bears N.16°W., 157 lks. dist., marked ¼ S 26 B T.

Subdivision of T. 6 N., R. 6 W.

Chains	
41.90	Wash, 15 lks. wide, course S.30°E.
45.10	Same wash, course S.30°W.
48.00	Same wash, course S.40°E.; asc. 70 ft. over SW. slope.
54.90	Spur, slopes SE.; desc. 40 ft. over NE. slope.
58.10	Ravine, course S.70°E.; asc., 43 ft. over SE. slope.
62.40	From which point: SW. cor. of mine hoist, bears N.69°E. NW. cor. of galvanized iron bldg., bears N.65°57'E. Point is on ridge, bears W. and S.70°E.; desc. 49 ft. over N. slope.
63.80	Wash, 30 lks. wide, in canyon about 30 ft. deep, course S.70°E. Asc. 29 ft. over sharply rolling land.
71.70	Wash, 10 lks. wide, course S.30°E. Over rolling land.
77.10	Road, bears N.60°W. and S.60°E.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 23, 24, 25 and 26, with brass cap marked
	T6N R6W S 23   S 24 S 26   S 25 1940 raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
	Land, 'rolling. Soil, rocky, 4th rate. Timber, palo verde, ironwood and mesquite; undergrowth, greasewood, cactus, ocotillo and sage.
	S.89°59'E., on a random line bet. secs. 24 and 25.
40.00	Set temp. ¼ sec. cor.
80.02	The cor. of secs. 19, 24, 25 and 30, on the E. bdy. of Tp., as evidenced by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the field notes of the survey of W. bdy. of T.6 N., R.5 W., under this group. Thence
	N.89°59'W., on true line bet. secs. 24 and 25.
	Over rolling land, through scattering timber and undergrowth.
3.02	Telephone line, bears N.30½°E. and S.30½°W.
4.10	Wash, 30 lks. wide, course S.30°E.
9.85	Road, bears N.30°E. and S.20°W.
13.90	Drain, 10 lks. wide, course S.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked

## Subdivision of T. 6 N., R. 6 W.

Chains	
	<p style="text-align: center;"> <math>\frac{1}{4}</math> S 24  S 25  1940 </p>
	<p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
50.00	Center of swale, about 10 chs. wide, drains S.
51.60	Wash, 20 lks. wide, course S.
54.80	Junction of roads from NW., N.20°E., and S.20°E.
65.70	Wash, 30 lks. wide, course S.20°W.
74.21	From this point:
	<p style="padding-left: 40px;">The NE. cor. of cabin (1), bears N.41°07'E.</p> <p style="padding-left: 40px;">The SW. cor. of cabin (2), bears N.39°14'E.</p>
80.02	The cor. of secs. 23, 24, 25 and 26.
	<p>Land, level and rolling.</p> <p>Soil, sandy; 2nd rate.</p> <p>Timber, palo verde, ironwood, ocotillo and mesquite;</p> <p>undergrowth, greasewood, cactus, cats claw and sage.</p>
	<p style="text-align: center;">-----</p> <p>N.0°01'W., bet. secs. 23 and 24.</p> <p>Over rolling land, through scattering timber and undergrowth.</p>
6.80	Dim road, bears N.70°E. and S.40°W.
12.56	From this point:
	<p style="padding-left: 40px;">NE. cor. of cabin (1), bears N.80°50'E.</p> <p style="padding-left: 40px;">SW. cor. of cabin (2), bears N.79°50'E.</p>
25.50	Wash, 20 lks. wide, course SE.; asc. 29 ft. over SW. slope.
30.00	Dim road, bears NW. and SE.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked
	<p style="text-align: center;"> <math>\frac{1}{4}</math>  S 23   S 24  1940 </p>
	<p style="text-align: right;">raise a mound</p> <p>of stone, 3 ft. base, 2½ ft. high, W. of cor.</p>
	Asc. 163 ft. over SW. slope.
55.70	Spur, slopes SE.; desc. 130 ft. over NE. slope.
62.80	Ravine, course S.30°E.; asc. 53 ft. over S. slope.
78.60	Point of spur, from N.70°W.; desc. 14 ft. over NE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 13, 14, 23 and 24, with brass cap marked



Subdivision of T. 6 N., R. 6 W.

Chains	<p>T6N R6W                      S 14   S 13                      S 23   S 24                      1940</p>
	<p>Land, rolling.                      Soil, rocky, 4th rate.                      Timber, palo verde, ironwood and mesquite; undergrowth,                      greasewood, cactus, ocotillo and sage.</p>
	<p>S.89°59'E., on a random line bet. secs. 13 and 24.</p>
40.00	Set temp. ¼ sec. cor.
80.06	<p>The cor. of secs. 13, 18, 19 and 24, on the E. bdy. of Tp.,                      as evidenced by an iron post, 2 ins. diam.; firmly set,                      marked and witnessed as described in the field notes of                      the survey of W. bdy. of T. 6 N., R. 5 W., under this group.                      Thence</p>
	<p>N.89°59'W., on true line bet. secs. 13 and 24.</p>
	<p>Over rolling land, through scattering timber and under-                      growth.</p>
	<p>Asc. 38 ft. over E. slope.</p>
2.05	Spur, slopes S.; desc. 67 ft. over W. slope.
8.15	Wash, 15 lks. wide, course S.20°W.; asc. 33 ft. over E. slope.
10.65	Spur, slopes S.; desc. 34 ft. over SW. slope.
13.75	Ravine, course S.30°E.; asc. 43 ft. over NE. slope.
20.05	Spur, slopes S.20°E.; desc. 29 ft. over W. slope.
23.05	Wash, 10 lks. wide, course S.
33.55	Wash, 15 lks. wide, course S.; asc. 32 ft. over rolling land.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked
	<p>¼ S 13                      S 24                      1940</p>
	<p>raise a mound                      of stone, 3 ft. base; 2½ ft. high, N. of cor.</p>
42.85	Road, bears N.30°W. and S.
49.50	Wash, 40 lks. wide, course S.40°E.; asc. 188 ft. over NE. slope.
62.25	Spur, slopes S.60°E.; desc. 90 ft. over SW. slope.
69.15	Head of ravine, course S.30°E.; asc. 10 ft. over E. slope.
70.65	Spur, slopes S.; desc. 130 ft. over W. slope.
77.25	Wash, 15 lks. wide, course S.; asc. 50 ft. over a NE. slope.
80.06	The cor. of secs. 13, 14, 23 and 24.

Subdivision of T. 6 N., R. 6 W.

Chains

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde, ironwood and mesquite; undergrowth,  
greasewood and cactus.

N.0°01'W., bet. secs. 13 and 14.

Over rolling land, through scattering timber and undergrowth.

Desc. 10 ft. over NE. slope.

0.70 Wash, 15 lks. wide, course S.40°E.; asc. 56 ft. over SE. slope.

10.00 Spur, slopes S.20°W.; desc. 31 ft. over NW. slope.

14.50 Ravine, course S.60°W.; asc. 140 ft. over S. slope.

22.80 Spur, slopes W.; along W. slope.

25.30 Spur, slopes S.20°E.; desc. 57 ft. over NE. slope.

38.60 Wash, 50 lks. wide, course S.25°E.; over broken land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at 1/4 sec. cor., with brass cap marked

S 14 | S 13

1940

raise a mound

of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

42.70 Road, bears N.40°W. and S.40°E.

47.80 Ravine, course SW.; asc. 116 ft. over S. slope.

56.50 Spur, slopes W.; desc. 16 ft. over a NW. slope.

58.75 Head of ravine, course W.; asc. 42 ft. over S. slope.

62.00 Spur, slopes W.; desc. 21 ft. over NW. slope.

64.70 Head of ravine, course S.60°W.; asc. 133 ft. over S. slope.

72.50 Top of ascent, thence along W. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground; over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 11, 12, 13 and 14, with brass cap marked

T6N R6W

S 11 | S 12

S 14 | S 13


1940

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde, ironwood and mesquite; undergrowth,  
greasewood and cactus.

Subdivision of T. 6 N., R. 6 W.

Chains	
	S. 89° 59' E., on a random line, bet. secs. 12, and 13.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	Intersect E. bdy. of Tp., 15 lks. S. of cor. of secs. 7, 12, 13 and 18, as evidenced by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the field notes of the survey of the W. bdy. of T. 6 N., R. 5 W., under this group. Thence
	S. 89° 55' W., on true line bet. secs. 12 and 13. Over rolling land, through scattering timber and undergrowth. Desc. over broken SW. slope.
6.00	Main road, bears N. 39 $\frac{1}{4}$ ° E. and S. 39 $\frac{1}{4}$ ° W.; across point of spur from N.
11.20	Wash, 20 lks. wide, course S. 60° E.
19.80	Ravine, course SE.; asc. 39 ft. over NE. slope.
25.60	Spur, slopes S. 40° E.; desc. 32 ft. over W. slope.
29.20	Wash, 15 lks. wide, course S.; over broken land.
37.60	Ravine, course SE.; asc. 29 ft. over broken E. slope.
40.04	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked.
	$\frac{1}{4}$ S 12 S 13 1940
	raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
	Asc. 253 ft. over broken E. slope.
68.40	Ridge, bears N. 30° W. and S. 30° E.; desc. 106 ft. over W. slope.
69.00	Ravine, course S. 25° W.; along S. slope.
77.10	Ravine, course S. 20° W.; asc. 87 ft. over SE. slope.
78.20	Spur, slopes S. 20° W.; desc. 36 ft. over W. slope.
80.08	The cor. of secs. 11, 12, 13 and 14. Land, rolling. Soil, rocky, 4th rate. Timber, palo verde, ironwood and mesquite; undergrowth, greasewood and cactus.
	-----
	N. 0° 01' W., bet. secs. 11 and 12. Over rolling land, through scattering undergrowth. Asc. 54 ft. over a SW. slope.
2.90	Spur, slopes W.; thence along W. slope.
6.40	Spur, slopes NW.; desc. 226 ft. over NW. slope.

Subdivision of T. 6 N., R. 6 W.

Chains	
32.30	Wash, 15 lks. wide, course SW.; asc. 22 ft. over SE. slope.
40.00	Set an iron post, 3 ft. long, 1-in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked
	<div style="text-align: center;">  <p>S 11   S 12 1940</p> </div> <p style="text-align: right;">raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p>
	Asc. 35 ft. over SE. slope.
52.00	Low saddle in spur, slopes S.60°W.; desc. 14 ft. over NW. slope.
53.50	Ravine, course S.60°W.; over rolling land.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 1,2,11 and 12, with brass cap marked
	<div style="text-align: center;"> <p>T6N R6W S 2   S 1 S 11   S 12 1940</p> </div>
	<p>Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.</p>
	----- N.89°55'E., on a random line bet. secs. 1 and 12.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect E. bdy. of Tp., 7 lks. N. of cor. of secs. 1,6, 7 and 12, as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the <del>first</del> <del>of</del> <del>the</del> <del>survey</del> <del>of</del> <del>W. bdy. of T.6 N., R.5 W., under this group.</del> Thence
	S.89°58'W., on true line bet. secs. 1 and 12.
	Over rolling land, through scattering timber and undergrowth.
2.30	Wash, 30 lks. wide, course S.70°E.; asc. 64 ft. over SE. slope.
6.10	Point of spur from SW.; desc. 23 ft. over NW. slope.
10.50	Head of ravine, course NE.; asc. 29 ft. over SE. slope.
13.10	Ridge, bears NW. and S.80°E.; desc. 40 ft. over W. slope.
23.00	Point of spur, from N.20°E.; desc. 35 ft. over W. slope.
25.90	Drain, course S.; asc. 19 ft. over E. slope.
35.00	Small drain, course S.70°E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor. with brass cap marked

Subdivision of T. 6 N., R. 6 W.

BOOK 4529

Chains

S 1  
S 12  
1940

Asc. 52 ft. over SW. slope.

61.50 Point of spur from S.; desc. 29 ft. over gradual W. slope.

80.00 The cor. of secs. 1, 2, 11 and 12.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

N.0°01'W., on true line bet. secs. 1 and 2.

Over rolling land, through scattering undergrowth.

19.60 Road, bears NE. and S.20°W.

30.80 Wash, 15 lks. wide, course N.75°E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at 1/4 sec. cor., with brass cap marked.

S 2 S 1

1940

of stone, 3 ft. base, 2 1/2 ft. high, W. of cor. raise a mound

58.50 Road, bears N.53 1/4°W. and S.53 1/4°E.

80.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at cor. of lots Nos. 4 and 5, sec. 1 and lots Nos. 1 and 8, sec. 2, with brass cap marked

S 2 1/4 S 1  
815

1940

of stone, 3 ft. base, 2 1/2 ft. high, W. of cor. raise a mound

85.70 Wash, 10 lks. wide, course E.

85.78 Intersect S. bdy. of sec. 35, T. 7 N., R. 6 W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing cor. of secs. 1 and 2, T. 6 N., R. 6 W., with brass cap marked.

T7N R6W

S 35

S 2 S 1

T6N R6W

C C

1940

of stone, 3 ft. base, 2 ft. high, S. of cor. raise a mound

From point of intersection, the cor. of secs. 35 and 36 only, T. 7 N., R. 6 W., bears S.89°49'E., 22.26 chs. dist., as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the official record.

Subdivision of T. 6 N., R. 6 W.

Chains

From same point, the  $\frac{1}{4}$  sec. cor. of sec. 35 only, T. 7 N., R. 6 W., bears N. 89° 49' W., 17.75 chs. dist., as evidenced by an iron post, 1 in. diam., set, marked and witnessed as described in the official record.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood.  
Undergrowth, greasewood and cactus.

At midpoint on the N. bdy. of sec. 1,

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, over + marked on bedrock and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor., of sec. 1 only, with brass cap marked

$\frac{1}{4}$  S 1  
1940

From this corner, the  $\frac{1}{4}$  sec. cor. of sec. 36 only, T. 7 N., R. 6 W., bears N. 89° 48' E., 22.24 chs. dist. as evidenced by an iron post, 1 in. diam., set, marked and witnessed as described in the official record.

From the same corner, the corner of secs. 35 and 36 only, T. 7 N., R. 6 W., bears S. 89° 48' W., 17.76 chs. dist.

From cor. of secs. 2, 3, 34 and 35, on S. bdy. of Tp., as evidenced by an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.

N. 0° 01' W., bet. secs. 34 and 35.

Over rolling land, through scattering timber and undergrowth.

- 8.50 Wash, 15 lks. wide, course S. 30° E.
- 11.50 Road, bears N. 60° E. and S. 60° W.
- 13.40 Wash, 20 lks. wide, course SE.
- 20.00 Wash, 20 lks. wide, course S. 20° E.
- 34.40 Road, bears N. 70° W. and S. 50° E.
- 38.10 Wash, 20 lks. wide, course S. 60° E.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S 34 | S 35  
1940

raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

- 51.30 Dim. road, bears N. 30° W. and S. 20° E.
- 55.80 Wash, 10 lks. wide, course S. 30° E.
- 60.40 Wash, 15 lks. wide, course S. 15° E.

Subdivision of T. 6 N., R. 6 W.


4329

Chains

70.50 Enter wash, 20 lks. wide, course S.30°E. from N.

77.50 Leave wash, course S. from N.20°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 26, 27, 34 and 35, with brass cap marked



raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling.

Soil, rocky, 4th rate.

Timber, palo verde, ironwood and mesquite; undergrowth, greasewood and cactus.

S.89°59'E., on a random line bet. secs. 26 and 35.

40.00 Set temp. ¼ sec. cor.

80.02 Intersect N. and S. line, 5 lks. S. of cor. of secs. 25, 26, 35 and 36.

Thence

S.89°59'W., on true line bet. secs. 26 and 35.

Over rolling land, through scattering timber and undergrowth.


Asc. 46 ft. along N. slope.

11.10 Ridge, bears N.20°W. and S.20°E.; desc. 107 ft. over a W. slope.

16.80 Road, bears N.30°W. and S.30°E.

38.20 Wash, 50 lks. wide, course S.20°E.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked



raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

65.50 Wash, 50 lks. wide, course S.

76.40 Wash, 15 lks. wide, course S.25°E.



80.02 The cor. of secs. 26, 27, 34 and 35:

Land, rolling.

Soil, rocky, 4th rate.

Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

## Subdivision of T. 6 N., R. 6 W.

Chains	
	N.0°01'W., bet. secs. 26 and 27. Over rolling land, through scattering timber and undergrowth.
10.30	Wash, 20 lks. wide, course S.60°E.
22.60	Wash, 20 lks. wide, course S.70°E.; asc. 25 ft. over SW. slope.
28.20	Low spur, slopes S.60°E.; desc. 53 ft. over NE. slope.
38.35	Wash, 50 lks. wide, course SE.; asc. 36 ft. over SW. slope.
39.99	Prospect hole, in ledge of solid rock 4x6x6 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked
	
49.00	Drain, course E.; asc. 106 ft. over S. slope.
58.30	Point of spur, slopes E. from N.; along top of spur.
62.80	Leave spur from NW.; desc. 56 ft. along E. slope.
78.35	Gulch, course S.60°E.; about 2½ chs. SE. of junction with wash from N.20°W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of sects. 22, 23, 26 and 27, with brass cap marked
	
	of stone, 3 ft. base, 2½ ft. high, W. of cor. of sec. 26. raise a mound
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	N.89°59'E., on a random line bet. secs. 23 and 26.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.04	Intersect N. and S. line, 2 lks. S. of cor. of secs. 23, 24, 25 and 26.
	Thence
	S.89°58'W., on true line bet. secs. 23 and 26.
	Over rolling land, through scattering timber and undergrowth.
0.45	Road, bears N. and S.



.Subdivision of T. 6 N., R. 6 W.

1920

Chains	
0.95	Wash, 10 lks. wide, course S.20°W.; desc. 36 ft. over E. slope.
20.25	Wash, 50 lks. wide, course S.30°E.; asc. 73 ft. over NE. slope.
25.05	Spur, slopes S.30°E.; desc. 61 ft. over SW. slope.
32.05	Drain near head, course SE.; asc. 44 ft. over SE. slope.
40.02	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at 1/4 sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \text{ S } 23 \\ \text{S } 26 \\ 1940 \end{array}$
40.05	Ridge, bears NE. and SW.; desc. 79 ft. over W. slope.
49.05	Wash, 15 lks. wide, course S.10°E.
53.45	Wash, 15 lks. wide, course S.20°E.
59.95	Wash, 30 lks. wide, course S.
67.95	Wash, 20 lks. wide, course S.40°E.; asc. 59 ft. over NE. slope.
79.55	Wash, 30 lks. wide, course S.20°E.
80.04	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	N.0°01'W., bet. secs. 22 and 23.
	Over rolling land, through scattering timber and undergrowth.
	Desc. 16 ft. over a NE. slope.
4.50	Wash, 20 lks. wide, course S.40°E.; asc. 93 ft. along broken E. slope.
24.90	Ravine, course E.; asc. 74 ft. over broken SW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at 1/4 sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \\ \text{S } 22 \text{ S } 23 \\ 1940 \end{array}$
46.20	Spur, slopes E.; 5 chs. thence SE.; desc. 101 ft. over NE. slope.
53.50	Ravine, course E.; asc. 10 ft. along E. slope.
69.90	Ravine, course S.30°E.; asc. 32 ft. over S. slope.

Subdivision of T. 6 N., R. 6 W.

Chains

- 74.20 Saddle in low ridge, bears E. and W.; desc. 50 ft. over NE. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 14, 15, 22 and 23, with brass cap marked

T6N R6W  
S 15 | S 14  
S 22 | S 23  
1940

raise a mound  
of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

N. 89° 58' E., on a random line bet. secs. 14 and 23.

- 40.00 Set temp. ¼ sec. cor.
  - 80.14 Intersect N. and S. line, 5 lks. N. of cor. of secs. 13, 14, 23 and 24.
- Thence

West, on true line bet. secs. 14 and 23.

Over rolling land, through scattering timber and undergrowth.

Asc. 120 ft. over NE. slope.

- 15.35 Ridge, bears N. and S.; desc. 67 ft. over SW. slope.
- 18.25 Head of ravine, course S. 30° W.; asc. 35 ft. over SE. slope.
- 20.85 Spur, slopes S. 30° W.; desc. 58 ft. over broken SW. slope.
- 30.85 Wash, 15 lks. wide, course S.; asc. 108 ft. over SE. slope.
- 40.07 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at ¼ sec. cor., with brass cap marked


S 14  
S 23  
1940

- 40.15 Rocky spur, slopes S.; desc. 147 ft. over broken SW. slope.
- 60.75 Wash, 15 lks. wide, course S. 30° W.; across point of spur from N.
- 67.15 Ravine, course S. 20° E.; along S. slope.
- 79.35 Wash, 15 lks. wide, course S. 40° E.
- 80.14 The cor. of secs. 14, 15, 22 and 23.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

Subdivision of T. 6 N., R. 6 W.

4329

Chains	
	N.0°01'W., bet. secs. 14 and 15. Over rolling land, through scattering timber and undergrowth.
1.20	Wash, 15 lks. wide, course S.30°E.; along broken W. slope.
6.40	Ravine, course S.60°W.; asc. 120 ft. over S. slope.
16.80	Ridge, bears NE. and S.70°W.; desc. 68 ft. over N. slope.
19.90	Ravine; course W.; asc. 61 ft. over SE. slope.
30.70	Spur, slopes SW.; desc. 72 ft. over NW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked
	
	raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
40.30	Wash, 15 lks. wide, course S.70°W.
62.50	Wash, 30 lks. wide, course SW.; asc. 124 ft. over S. slope.
73.30	Spur, slopes S.10°E.; desc. 40 ft. along E. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 10, 11, 14 and 15; with brass cap marked
	T6N R6W <u>S 10   S 11</u> S 15   S 14 1940
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	East, on a random line bet. secs. 11 and 14.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.16	The cor. of secs. 11, 12, 13 and 14.
	Thence
	West, on true line bet. secs. 11 and 14.
	Over rolling land, through scattering timber and undergrowth.
	Desc. gradually along S. slope.
0.15	Head of ravine, course S.30°W.; asc. 19 ft. over SE. slope.
3.35	Spur, slopes SW.; desc. 193 ft. over NW. slope.
16.25	Ravine, course S.70°W.; asc. 17 ft. over SE. slope.

Subdivision of T: 6 N., R. 6 W.

Chains	
17.45	Point of rocky spur from N.30°E.; desc. 37 ft. over SW. slope.
22.05	Wash, 25 lks. wide, course S.50°E.
27.40	Road, bears NW. and SE.
29.35	Wash, 30 lks. wide, course S.30°E.; asc. 86 ft. over broken NE. slope.
39.08	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, <del>at</del> witness $\frac{1}{4}$ sec. cor., with brass cap marked  $\begin{array}{c} \frac{1}{4} \text{ S } 11 \text{ WC} \\ \text{S } 14 \\ 1940 \end{array}$
40.08	True point for $\frac{1}{4}$ sec. cor. falls in ravine, course N.20°E., where it is impracticable to monument the cor.  Asc. 75 ft. over broken NE. slope.
48.55	Ridge, bears NW. and S.20°E.; along S. slope.
50.85	Spur, slopes SW.; desc. 89 ft. over SW. slope.
56.15	Ravine, course S.20°W.; over broken land.
58.75	Point of spur from N.; desc. 34 ft. over SW. slope.
64.85	Wash, 15 lks. wide, course S.20°W.
70.15	Wash, 10 lks. wide, course S.
71.95	Wash, 15 lks. wide, course SE.; asc. 67 ft. over E. slope.
80.16	The cor. of secs. 10, 11, 14 and 15.  Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
-----	
N.0°01'W., bet. secs. 10 and 11.	
-----	
Over rolling land, through scattering timber and undergrowth. Along E. slope.	
7.50	Wash, 10 lks. wide, course S.70°E.; over point of spur from E.
16.50	Enter wash, 20 lks. wide, course S.20°E.; along bottom of wash.
28.20	Leave wash, course S. from N.30°E.; asc. 45 ft. over SE. slope.
37.90	Road, bears NE. and SW.; on low spur, slopes SW.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked  $\begin{array}{c} \frac{1}{4} \\ \text{S } 10 \text{ S } 11 \\ 1940 \end{array}$

Subdivision of T. 6 N., R. 6 W.

1929

Chains	
42.50	Enter wash, 15 lks. wide, course SW. Continued up wash bottom.
45.80	Leave wash from NE.; asc. 54 ft. over S. slope.
51.90	Top of low hill; desc. 35 ft. over NE. slope.
54.50	Ravine, course SE.; asc. 71 ft. over S. slope.
66.40	Ravine, course S.30°W.; asc. 20 ft. over SW. slope.
69.40	Spur, slopes SE.; desc. 15 ft. over NE. slope.
72.30	Head of ravine, course S.70°E.; asc. 98 ft. over SE. slope.
76.80	Same spur, slopes S.60°W.; desc. 19 ft. over NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 2, 3, 10 and 11, with brass cap marked
	T6N R6W <u>S 3   S 2</u> S 10   S 11 1940
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	East, on a random line bet. secs. 2 and 11.
40.00	Set temp. 1/4 sec. cor.
80.12	The cor. of secs. 1, 2, 11 and 12.
	Thence
	West, on true line bet. secs. 2 and 11.
	Over rolling land, through scattering timber and undergrowth.
5.60	Road, bears N. and S.
23.20	Wash, 15 lks. wide, course S.30°E.; asc. 61 ft. over E. slope.
34.10	Head of a ravine, course SE.; asc. 50 ft. over NE. slope.
40.06	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at 1/4 sec. cor., with brass cap marked
	1/4 <u>S 2</u> S 11 1940
	raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.
	Asc. 71 ft. over NE. slope.
46.20	Ravine, course N.60°E.; asc. 30 ft. over E. slope.
48.80	Ridge, bears N. and W.; desc. 85 ft. along top of ridge.

## Subdivision of T. 6 N., R. 6 W.

Chains	
58.60	Ridge turns S. in low saddle; desc. 78 ft. over W. slope.
63.40	Road in wash, 20 lks. wide, course S.; asc. 58 ft. over E. slope.
72.20	Ravine, course S.20°E.; asc. 98 ft. over E. slope.
75.90	Spur, slopes S.; desc. 68 ft. over NW. slope.
80.12	The cor. of secs. 2, 3, 10 and 11.
	Land, rolling.
	Soil, rocky, 4th rate.
	Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	N.0°01'W., on true line bet. secs. 2 and 3.
	Over rolling land, through scattering timber and undergrowth.
	Desc. 4 ft. over NW. slope.
0.50	Ravine, course SW.; asc. 134 ft. over SW. slope.
7.70	Spur, slopes SE.; asc. 155 ft. over SE. slope.
15.00	Head of ravine, course S.30°E.; asc. 125 ft. over S. slope.
17.40	Ridge, bears SW. and E.; a rocky peak 50 ft. high, bears E. 150 lks. dist.; along west slope.
23.24	Ridge, bears N.15°W. and S.15°E.; desc. 97 ft. along an E. slope.
33.70	Rocky peak on ridge about 120 ft. high, bears W., 2.50 chs. dist.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked
	Asc. 29 ft. along E. slope.
45.00	Ridge, bears NE. and SW.; desc. 202 ft. over NW. slope.
58.90	Ravine, course N.60°E.; asc. 29 ft. over SE. slope.
63.60	Spur, slopes N.80°E.; desc. 35 ft. over NE. slope.
66.70	Ravine, course S.70°E.; asc. 58 ft. over S. slope.
71.10	Spur, slopes N.60°E.; desc. 36 ft. over NW. slope.
74.30	Ravine, near head, course NE.; along E. slope.
80.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, over + marked on bedrock, and in a mound of stone to top, at cor. of lots Nos. 4 and 5, sec. 2, and lots Nos. 1 and 8, sec. 3, with brass cap marked

Subdivision of T. 6 N., R. 6 W.

4829

Chains

S 3  $\frac{14}{85}$  S 2  
1940

85.85 Intersect S. bdy. of sec. 34, T. 7 N., R. 6 W.

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, over + marked on bedrock, and in a mound of stone to top, at closing cor. of secs. 2 and 3, T.6 N., R.6 W., with brass cap marked.

T7N R6W  
S34  
S 3 | S 2  
T6N R6W  
C C  
1940

From point of intersection, the cor. of secs. 34 and 35 only, T. 7 N., R. 6 W., bears N.89°59'E., 22.35 chs. dist., as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the official record.

From same point, the  $\frac{1}{4}$  sec. cor. of sec. 34 only, T.7 N., R.6 W., bears S.89°59'W., 17.74 chs. dist., as evidenced by an iron post, 1 in. diam., set, marked and witnessed as described in the official record.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

At midpoint on the N. bdy. of sec. 2

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor. of sec. 2, with brass cap marked

$\frac{1}{4}$  S 2  
1940

raise a mound of stone, 4 ft. base, 2½ ft. high, S. of cor.

From this corner, the  $\frac{1}{4}$  sec. cor. of sec. 35 only, T.7 N., R.6 W., bears S.89°59'E., 22.27 chs. dist.

From the same corner, the cor. of secs. 34 and 35 only, T.7 N., R.6 W., bears N.89°59'W., 17.67 chs. dist.

From cor. of secs. 3, 4, 33 and 34, on S. bdy. of Tp., as evidenced by an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.

N.0°02'W., bet. secs. 33 and 34.

Over rolling land, through scattering timber and undergrowth.

10.00 Wash, 30 lks. wide, course S.30°E.

21.20 Wash, 20 lks. wide, course S.20°E.; asc. 31 ft. over SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor., with brass cap marked

Subdivision of T. 6 N., R. 6 W.

Chains

\*  
S 33 | S 34  
1940

raise a mound  
of stone, 3 ft. base, 2½ ft. high, W. of cor.

51.10 Bend in wash, 10 lks. wide, course S.20°W. from N.20°W.; asc. 41 ft. over SW. slope.

77.50 Wash, 15 lks. wide, course S.30°E.; asc. 17 ft. over SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 27, 28, 33 and 34, with brass cap marked

T6N R6W  
S 28 | S 27  
S 33 | S 34  
1940

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

S.89°59'E., on a random line bet. secs. 27 and 34.

40.00 Set temp. ¼ sec. cor.

80.02 Intersect N. and S. line, 2' lks. N. of the cor. of secs. 26, 27, 34 and 35.

Thence

N.89°58'W., on true line bet. secs. 27 and 34.

Over rolling land, through scattering timber and undergrowth.

Desc. 16 ft. over W. slope.

0.50 Wash, 15 lks. wide, course S.

7.50 Wash, 10 lks. wide, course S.

13.80 Wash, 10 lks. wide, course S.40°E.

26.20 Wash, 20 lks. wide, course S.10°W.

39.70 Wash, 10 lks. wide, course S.25°W.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at ¼ sec. cor., with brass cap marked

¼ S 27  
S 34  
1940

Desc. 22 ft. over W. slope.

49.20 Wash, 40 lks. wide, course S.30°E.

61.50 Road, bears N.73½°W. and S.44¼°E.



Subdivision of T. 6 N., R. 6 W.


Chains

62.00 Wash, 30 lks. wide, course S.25°E.  
 80.02 The cor. of secs. 27,28,33 and 34.  
 Land, rolling.  
 Soil, rocky, 4th rate.  
 Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

-----  
 N.0°02'W., bet. secs. 27 and 28.

Over rolling land, through scattering timber and undergrowth.


10.60 Road, bears N.60°W. and S.60°E..  
 25.40 Wash, 25 lks. wide, course S.80°E.; asc. 101 ft. over S. slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at ¼ sec. cor., with brass cap marked



Continue ascent of 68 ft. over S. slope.

44.40 Spur, slopes SW.; desc. 82 ft. over NW. slope.  
 51.50 Wash, 20 lks. wide, course S.60°W.; asc. 62 ft. over S. slope.  
 67.30 Spur, slopes W.; from N.20°E.; desc. 24 ft. along a W. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 21,22,27 and 28, with brass cap marked



Land, rolling.  
 Soil, rocky, 4th rate.  
 Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

-----  
 S.89°58'E., on a random line bet. secs. 22 and 27.

40.00 Set temp. ¼ sec. cor.  
 80.00 The cor. of secs. 22,23,26 and 27.

Thence

N.89°58'W., on true line bet. secs. 22 and 27.

Over rolling land, through scattering timber and undergrowth.

## Subdivision of T. 6 N., R. 6 W.

Chains	
	Desc. gradually over broken SW. slope.
2.40	Gulch, course S.60°E.; asc. 126 ft. over SE. slope.
10.70	Spur, slopes S.20°E.; asc. 72 ft. over SE. slope.
21.30	Point of spur, from N.20°E.; desc. 60 ft. over SW. slope.
26.60	Head of ravine, course SE.; asc. 138 ft. over broken SE. slope.
34.90	Sharp spur, slopes SW.; desc. 134 ft. over W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked
	S 22 S 27 1940
	Desc. 68 ft. over W. slope.
44.70	Ravine, course SW.; asc. 43 ft. over SE. slope.
50.10	Spur, slopes SW.; desc. 46 ft. over NW. slope.
58.40	Ravine, course S.30°W.; asc. 37 ft. over E. slope.
60.00	Point of spur, from N.20°E.; desc. 49 ft. over W. slope.
61.10	Wash, 40 lks. wide, course S.; asc. 49 ft. over E. slope.
66.10	Ridge, bears N. and S.; desc. 10 ft. over W. slope.
66.90	Ravine, course S.; asc. 50 ft. over E. slope.
73.50	Spur, slopes S.30°W.; desc. 54 ft. over W. slope.
80.00	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	N.0°02'W., bet. secs. 21 and 22. Over rolling land, through scattering timber and undergrowth. Along west slope.
14.60	Wash, 15 lks. wide, course S.30°W.; asc. 55 ft. over SE. slope.
25.50	Spur, slopes S.30°W.; desc. 32 ft. over NW. slope.
31.20	Wash, 15 lks. wide, course S.20°W.; asc. 58 ft. over SE. slope.
40.00	Point of spur from N.20°E. Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked

## Subdivision of T. 6 N., R. 6 W.

329

## Chains

$\uparrow$   
 S 21 | S 22  
 1940

Along west slope.

49.80 Head of ravine, course S.60°W.; asc. 226 ft. over SW. slope.

68.60 Rocky ridge, bears N.20°W. and S.20°E.; desc. 156 ft. over NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 15, 16, 21 and 22, with brass cap marked

T6N R6W  
 S 16 | S 15  
 S 21 | S 22  
 1940

Land, rolling.

Soil, rocky, 4th rate.

Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

S.89°58'E., on a random line bet. secs. 15 and 22.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.02 The cor. of secs. 14, 15, 22 and 23.

Thence

N.89°58'W., on true line bet. secs. 15 and 22.

Over rolling land, through scattering timber and undergrowth.

Asc. 104 ft. over broken E. slope.

17.40 Ridge, bears N. and S.; desc. 59 ft. over W. slope.

31.10 Ravine, course S.30°W.; asc. 32 ft. over SE. slope.

33.10 Spur, slopes S.40°W.; desc. 71 ft. over NW. slope.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$  S 15  
 S 22  
 1940

Desc. 8 ft. over NW. slope.

41.30 Wash, 30 lks. wide, course S.30°W.; over broken S. slope.

48.35 Ravine, course SW.

53.85 Ravine, course S.30°E.; asc. 299 ft. over E. slope.


64.50 Spur, slopes S.; rocky peak on top of spur, bears South, 2 chs. dist. Low saddle in spur bears N. approx. 15 chs. dist.; desc. 235 ft. over W. slope.

Subdivision of T.6 N., R.16 W.

Chains	
75.80	Wash, 50 lks. wide, course S.; asc. 65 ft. over NE. slope.
80.02	The cor. of secs. 15,16,21 and 22.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	N.0°02'W., bet. secs. 15 and 16.
	Over rolling land, through scattering timber and undergrowth.
	Desc. 52 ft. over NE. slope.
5.50	Wash, 50 lks. wide, course S.30°E.; asc. 94 ft. over SW. slope.
25.90	Spur, slopes S.50°W.; desc. 23 ft. along a W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at ¼ sec. cor., with brass cap marked
	↑ S 16   S 15 1940
67.90	Asc. 43 ft. along W. slope.
68.00	Top of ascent; desc. 13 ft. over a N. slope.
68.60	Ravine, course W. Heads 15 chs. E.; along W. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 9,10,15 and 16, with brass cap marked
	T6N R6W S 9   S 10 S 16   S 15 1940
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	S.89°58'E., on a random line bet. secs. 10 and 15.
40.00	Set temp. ¼ sec. cor.
80.04	Intersect N. and S. line, 9 lks. N. of cor. of secs. 10, 11,14 and 15.
	Thence
	N.89°54'W., on true line bet. secs. 10 and 15.
	Over rolling land, through scattering timber and undergrowth.
	Asc. 31 ft. over E. slope.

Subdivision of T. 6 N., R. 6 W.

Chains	
1.85	Saddle in ridge, bears N. and S.; desc. 98 ft. over SW. slope.
11.95	Head of ravine, course S.; asc. 23 ft. over NE. slope.
18.25	Saddle in spur, slopes SE. (from NE.); desc. 32 ft. over NW. slope.
22.25	Wash, 10 lks. wide, course SW.; asc. 48 ft. over E. slope.
26.45	Point of spur from NE.; desc. 72 ft. over SW. slope.
33.95	Wash, 30 lks. wide, course S. Over rolling land.
36.05	Wash, 20 lks. wide, course S.20°W.; asc. 58 ft. over E. slope.
40.02	Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \text{ S } 10 \\ \text{S } 15 \\ 1940 \end{array}$
41.85	Dim road, bears N. and S.
46.45	Bend in ravine, course S.60°E. from S.75°W.; asc. 170 ft. along S. slope.
53.05	Same ravine, course S.75°E.; asc. 213 ft. over precipitous E. slope.
62.75	Rocky ridge, bears N. and S.; desc. 101 ft. over W. slope.
65.35	Head of ravine, course NW.; along N. slope.
71.35	Spur, slopes NW.; desc. 147 ft. over W. slope.
80.04	The cor. of secs. 9,10,15 and 16.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	N.0°02'W., bet. secs. 9 and 10.
	Over rolling land, through scattering timber and undergrowth.
	Desc. 23 ft. along a W. slope.
10.20	Wash, 30 lks. wide, course S.30°W.; asc. 63 ft. along an E. slope.
25.20	Road, bears N.58°E. and S.27½°W.
38.00	Wash, 15 lks. wide, course S.10°E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked



Chains

	<p>of stone, 3 ft. base, 2½ ft. high, W. of cor. raise a mound</p>
50.20	Wash, 20 lks. wide, course S.60°E.; asc. 60 ft. over a SW. slope.
60.90	Point of spur, slopes S.20°E.; desc. 34 ft. over a NE. slope.
66.00	Drain, course S.60°E.; asc. 14 ft. over a SW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 3, 4, 9 and 10, with brass cap marked
	<p>T6N R6W  <u>S 4   S 3</u>  S 9   S 10  1940</p>
	<p>Land, rolling.  Soil, rocky, 4th rate.  Timber, palo verde and ironwood; undergrowth, greasewood and cactus.</p>
-----	
	S.89°54'E., on a random line bet. secs. 3 and 10.
40.00	Set temp. ¼ sec. cor.
79.98	The cor. of secs. 2, 3, 10 and 11.
	Thence
	N.89°54'W., on true line bet. secs. 3 and 10.
	Over rolling land, through scattering timber and undergrowth.
	Desc. 11 ft. over NW. slope.
0.50	Ravine, course S.; over point of spur from NW.
3.70	Ravine, course S.; asc. 114 ft. over E. slope.
8.60	Ridge, bears N. and S.10°E.; desc. 181 ft. over SW. slope.
18.80	Ravine, course NW.; over spur from S.30°E.
22.50	Ravine, course S.30°W.; asc. 12 ft. over SE. slope.
29.10	Short spur, slopes SW.; desc. 63 ft. over NW. slope.
33.80	Head of ravine, course SW.; asc. 17 ft. over SE. slope.
39.00	Spur, slopes S.30°W.; desc. 10 ft. over NW. slope.
39.99	Set an iron post, 3 ft. long; 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at ¼ sec. cor., with brass cap marked
	<p><u>S 3</u>  S 10  1940</p>
	Desc. 37 ft. over a NW. slope.
48.60	Wash, 20 lks. wide, course S.

Subdivision of T. 6 N., R. 6 W.

4229

Chains	
55.20	Road, bears N.14 $\frac{3}{4}$ °E. and S.14 $\frac{3}{4}$ °W.
58.60	Wash, 25 lks. wide, course S.
63.70	Wash, 15 lks. wide, course S.30°E.
74.30	Wash, 20 lks. wide, course S.
79.98	The cor. of secs. 3,4,9 and 10: Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus:
-----	
	N.0°02'W., on true line bet. secs. 3 and 4. Over rolling land, through scattering timber and undergrowth. Asc. 69 ft. over SE. slope.
6.90	Top of hill; desc. 54 ft. over N. slope.
16.40	Wash, 10 lks. wide; course S.30°E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{c} \uparrow \\ S\ 4 \mid S\ 3 \\ 1940 \end{array}$
	Ascend 26 ft. over broken W. slope.
54.00	Head of ravine, course S.60°W.; asc. 133 ft. over SW. slope.
65.80	Spur, slopes S.30°E. from N.; along top of spur.
74.30	Leave top of spur, slopes S. from NE.; desc. 49 ft. over NW. slope.
79.50	Ravine, course NW.; asc. over S. slope.
80.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of lots Nos. 4 and 5, sec. 3, and lots Nos. 1 and 8, sec. 4, with brass cap marked
	$\begin{array}{c} S\ 4 \mid \frac{1}{8} \frac{4}{5} \mid S\ 3 \\ 1940 \end{array}$
81.80	Spur, slopes N.75°W.; desc. 11 ft. over N. slope.
83.80	Ravine, course N.80°W.; asc. 19 ft. over SW. slope.
85.75	Intersect S. bdy. of sec. 33, T. 7 N., R. 6 W. Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, over + marked on bedrock, at closing cor. of secs. 3 and 4, with brass cap marked

Subdivision of T. 6 N., R. 6 W.

Chains

T7N R6W

S33

S 4 | S 3  
T6N R6W

C C

1940

From point of intersection, the cor. of secs. 33 and 34 only, T. 7 N., R. 6 W., bears N.89°44'E., 22.38 chs. dist., as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the official record.

From the same point, the 1/4 sec. cor. of sec. 33 only, T. 7 N., R. 6 W., bears S.89°44'W., 17.66 chs. dist., as evidenced by an iron post, 1 in. diam., set, marked and witnessed as described in the official record.

Land; rolling:  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

At midpoint on the N. bdy. of sec. 3

Set an iron post, 1 in. diam., 28 ins. in the ground, at 1/4 sec. cor. of sec. 3, with brass cap marked

S 33  
1940

raise a mound  
of stone, 3 ft. base, 2 1/2 ft. high, S. of cor.

From this corner, the 1/4 sec. cor. of sec. 34 only, T. 7 N., R. 6 W., bears S.89°48'E., 22.28 chs. dist.

From the same corner, the cor. of secs. 33 and 34 only, T. 7 N., R. 6 W., bears N.89°48'W., 17.64 chs. dist.

From cor. of secs. 4, 5, 32 and 33, on S. bdy. of Tp., as evidenced by an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.

N.0°02'W., bet. secs. 32 and 33.

Over rolling land, through scattering timber and undergrowth.

Asc. 36 ft. over rolling slopes.

4.75 Wash, 20 lks. wide, course S.40°W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at 1/4 sec. cor., with brass cap marked

S 32 | S 33  
1940

raise a mound  
of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

40.90 Wash, 20 lks. wide, course S.30°E.; asc. 48 ft. over rolling land.

46.20 Same wash, 20 lks. wide, course S.50°W.



## Subdivision of T. 6 N., R. 6 W.

1829

## Chains

- 58.30 Same wash, 20 lks..wide, course S.60°E.
- 64.20 Same wash, 20.lks. wide, course SW.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 28,29,32 and 33, with brass cap marked

T6N R6W.

S 29 | S 28

S 32 | S 33

1940

from which

An ironwood, 6 ins. diam., bears N.81°E., 220 lks. dist., marked T 6 N R 6 W S 28 B T.

An ironwood, 8 ins..diam., bears S.76°E., 465 lks. dist., marked T 6 N R 6 W S 33 B T.

An ironwood, 14 ins. diam., bears S.11½°W., 263 lks. dist., marked T 6 N R 6 W S 32 BT.

An ironwood, 12 ins. diam., bears N.55¾°W., 150 lks. dist., marked T 6 N R 6 W S 29 B T.

Land, rolling..

Soil, rocky, 4th rate.

Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

S.89°59'E., on a random line bet. secs. 28 and 33.

- 40.00. Set temp. ¼ sec. cor.

- 80.00 Intersect N. and S. line, 5 lks. N. of cor. of secs. 27, 28, 33 and 34.

Thence

N.89°57'W., on true line bet. secs. 28 and 33.

Over rolling land, through scattering timber and undergrowth.

Desc. 46 ft. over W. slope.

- 3.20 Wash, 15 lks. wide, course S.30°E.

- 37.00 Wash, 30 lks. wide, course S.20°E.

- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked

¼ S 28

S 33

1940

raise a mound

of stone, 2 ft. base, 2 ft. high, N. of cor.

- 44.80 Wash, 15 lks. wide, course S.

- 52.00 Wash, 30 lks. wide, course S.

- 56.30 Wash, 20 lks: wide; course S.20°E.

- 62.60 Dim road, bears N. and S.

Subdivision of T. 6 N., R. 6 W.

Chains	
74.10	Wash, 20 lks. wide, course S.
80.00	The cor. of secs. 28, 29, 32 and 33.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
----- N.0°02'W., bet. secs. 28 and 29.	
	Over rolling land, through scattering timber and undergrowth.
14.30	Wash, 30 lks. wide, course S.20°E.
40.00	Set an iron post, .3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked
	<p style="text-align: center;">       S 29   S 28        1940     </p>
	raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
42.10	Same wash, 30 lks. wide, course S.20°W.
51.60	Dirt road, bears N.60°W. and S.60°E.
59.10	Same wash, 20 lks. wide, course S.20°E.
71.40	Ravine, course S.30°E.; asc. 64 ft. over S. slope.
71.80	Road, bears N.60°W. and S.60°E.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 20, 21, 28 and 29, with brass cap marked
	<p style="text-align: center;">       T6N R6W        S 20   S 21        S 29   S 28        1940     </p>
	This corner is located on top of a low hill.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
----- S.89°57'E., on a random line bet. secs. 21 and 28.	
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.02	Intersect N. and S. line 5 lks. N. of cor. of secs. 21, 22, 27 and 28.
	Thence
	N.89°55'W., on true line bet. secs. 21 and 28.
	Over rolling land, through scattering timber and undergrowth.

Subdivision of T. 6 N., R. 6 W.

Chains	
	Desc. over W. slope.
1.00	Ravine, course S.
6.60	Wash, 15 lks. wide, course S.15°W.
14.00	Road, bears N.27½°E. and S.27½°W.
17.30	Wash, 40 lks. wide, course S.40°W.
30.50	Wash, 20 lks. wide, course S.20°W.
36.80	Wash, 20 lks. wide, course S.15°E.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at ¼ sec. cor., with brass cap marked
	¼ $\frac{S\ 21}{S\ 28}$ 1940
42.00	Ravine, course S.30°E.; asc. 125 ft. over E. slope.
53.30	Spur, slopes S.; desc. 135 ft. over W. slope.
65.50	Wash, 15 lks. wide, course S.10°E.
67.55	Wash, 25 lks. wide, course S.30°E.
73.70	Head of ravine, course S.; asc. 64 ft. over E. slope.
80.02	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	N.0°02'W., bet. secs. 20 and 21.
	Over rolling land, through scattering timber and undergrowth.
	Desc. 40 ft. over NE. slope.
11.60	Wash, 30 lks. wide, course S.40°E.
21.20	Head of drain, course S.70°W.; asc. 70 ft. over S. slope.
26.90	Rocky spur, slopes S.45°E.; desc. 49 ft. over NE. slope.
30.10	Head of ravine, course E.; asc. 92 ft. over SE. slope.
38.50	Saddle in spur, slopes S.70°W.; desc. 17 ft. over N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at ¼ sec. cor., with brass cap marked
	¼ $\frac{S\ 20}{S\ 21}$ 1940
	Desc. 10 ft. over N. slope.

Subdivision of T. 6 N., R. 16 W.

Chains	Description
40.80	Ravine, course W.; asc. 40 ft. over S. slope.
43.50	Point of rocky spur, slopes W.; desc. 70 ft. over NW. slope.
55.70	Wash, 15 lks. wide, course S. 30° W.; asc. 70 ft. over S. slope.
56.30	Vertical mine shaft, bears W. 10 lks. dist.
57.00	Road, bears NE. and SW.
62.40	Spur, slopes W.; desc. 52 ft. over N. slope.
68.60	Head of ravine, course S. 70° W.; asc. 31 ft. over rolling SE. slope.
79.00	Spur, slopes S. 70° W.; desc. gradual NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 16, 17, 20 and 21, with brass cap marked
	T6N R6W S 17   S 16 S 20   S 21 1940
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
-----	
	S. 89° 55' E., on a random line bet. secs. 16 and 21.
40.00	Set temp. 1/4 sec. cor.
80.06	The cor. of secs. 15, 16, 21 and 22.
	Thence
	N. 89° 55' W., on true line bet. secs. 16 and 21.
	Over rolling land, through scattering timber and undergrowth.
	Asc. 66 ft. over NE. slope.
5.15	Saddle in ridge, bears N. and S.; desc. 128 ft. over W. slope.
22.55	Ravine, course S. 30° W.
27.15	Road, bears N. and S.
30.85	Wash, 20 lks. wide, course S.
37.45	Wash, 20 lks. wide, course SW.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at 1/4 sec. cor., with brass cap marked
	S 16 S 21 1940

Subdivision of T. 6 N., R. 6 W.

1929

Chains

raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

46.45 Head of drain, course S.

51.50 Wash, course S.10°W.; asc. 143 ft. over E. slope.

54.05 Road, bears N.30°E. and S.30°W.

66.55 Top of hill in low range, extending N. and S.; desc. 90 ft. over SW. slope.

77.55 Spur, slopes S.70°W.; desc. 12 ft. over NW. slope.

80.06 The cor. of secs. 16,17,20 and 21.

Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

N.0°02'W., bet. secs. 16 and 17.

Over rolling land, through scattering timber and undergrowth.

Desc. over a gradual NW. slope.

12.70 Wash, 20 lks. wide, course SW.

20.00 Same wash, 20 lks. wide, course S.20°E.

35.00 Wash, 20 lks. wide, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at ¼ sec. cor., with brass cap marked

S 17 | S 16

1940

60.00 Enter wash, 30 lks. wide, course S.20°W.; along wash.

70.00 Leave wash, course S. from NE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 8,9,16 and 17, with brass cap marked

T6N R6W

S 8 | S 9

S 17 | S 16

1940

Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

Subdivision of T. 6 N., R. 16 W.

Chains	S. 89° 55' E., on a random line bet. secs. 9 and 16.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.06	Intersect N. and S. line, 2 lks. N. of cor. of secs. 9, 10, 15 and 16.
	Thence
	N. 89° 54' W., on true line bet. secs. 9 and 16.
	Desc. 18 ft. over W. slope.
3.05	Wash, 40 lks. wide, course S. 15° E.
10.05	Road, bears N. 25° E. and S. 25° W.
30.35	Wash, 20 lks. wide, course S.
40.03	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $\frac{S}{S}$ $\frac{9}{16}$ 1940
44.55	Road, bears N. 2 $\frac{1}{2}$ ° W. and S. 14 $\frac{1}{2}$ ° E.
49.95	Wash, 15 lks. wide, course S. 20° E.; over N. slope of low hill.
56.25	Wash, 20 lks. wide, course S. 15° E.
77.25	Wash, 30 lks. wide, course S. 10° W.
80.06	The cor. of secs. 8, 9, 16 and 17.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	N. 0° 02' W., bet. secs. 8 and 9.
	Over rolling land, through scattering timber and undergrowth.
18.00	Small drain; course SW.; asc. 28 ft. over gradual SE slope.
21.00	Series of low, rocky hills, bear NE. and SW.
39.50	Wash, 10 lks. wide, course S. 60° E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S 8   S 9 1940
	raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
44.00	Enter wash, 10 lks. wide, course S. 30° W.; along bottom of wash.

Subdivision of T. 6 N., R. 6 W.

Chains	
50.00	Leave wash, 10 lks. wide, course S. from NE.
54.90	Road, bears N.30°W. and S.30°E.
70.00	Junction of washes from N. and NW.; course S.20°E.; along bed of wash.
74.60	Leave wash, course S. from NW.; asc. 29 ft. over S. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 4, 5, 8 and 9, with brass cap marked
	$\begin{array}{r} \text{T6N R6W} \\ \text{S } 5   \text{S } 4 \\ \hline \text{S } 8   \text{S } 9 \\ 1940 \end{array}$
	raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
<hr/>	
	S.89°54'E., on a random line bet. secs. 4 and 9.
40.00	Set temp. ¼ sec. cor.
80.02	Intersect N. and S. line, 7 lks. S. of cor. of secs. 3, 4, 9 and 10.
	Thence
	N.89°57'W., on true line bet. secs. 4 and 9.
	Over rolling land, through scattering timber and undergrowth.
	Asc. 34 ft. over E. slope.
3.00	Spur, slopes S.; desc. 45 ft. over W. slope.
7.40	Wash, 10 lks. wide, course S.
16.80	Wash, 15 lks. wide, course SE.
40.01	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked
	$\begin{array}{r} \frac{1}{4} \text{ S } 4 \\ \text{S } 9 \\ 1940 \end{array}$
	raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
64.50	Wash, 10 lks. wide, course S.20°E.; along S. slope.
80.02	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
<hr/>	

.Subdivision of T. 6 N., R. 6 W.

Chains

N.0°02'W., on true line bet. secs. 4 and 5.

Over rolling land, through scattering timber and undergrowth.

Asc. 108 ft. over S. slope.

12.70 Spur, slopes S.10°W. from N.70°W.; desc. 69 ft. over N. slope.

16.30 Ravine, course S.60°E.; asc. 37 ft. over S. slope.

24.40 Same spur, slopes SW.; desc. 113 ft. over N. slope.

30.30 Old mine shaft, bears E. 50 lks. dist.

33.60 Ravine, course SW.; asc. 47 ft. over SE. slope.

35.70 Spur, slopes S.60°W.; desc. 32 ft. over NW. slope.

39.20 Ravine, course SW.; asc. 8 ft. over S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at  $\frac{1}{4}$  sec. cor., with brass cap marked

S 5 | S 4

1940

raise a mound

of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

Asc. 42 ft. over S. slope.

45.50 Spur, slopes S.80°W.; desc. 31 ft. over NE. slope.

53.00 Ravine, course N.20°W.; desc. 24 ft. along a W. slope.

60.20 Wash, 8 lks. wide, course S.80°W.; asc. 37 ft. over SW. slope.

80.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at cor. of lots Nos. 4 and 5 of sec. 4, and lots Nos. 1 and 8, of sec. 5, with brass cap marked

S 5 | 1/4 | S 4  
8 | 5

1940

raise a mound

of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

85.70 Intersect the S. bdy. of sec. 32, T. 7 N., R. 6 W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing cor. of secs. 4 and 5, with brass cap marked

T7N R6W

S32

S 5 | S 4

T6N R6W

C C

1940

raise a mound

of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, S. of cor.



Subdivision of T. 6 N., R. 6 W.

Chains

From point of intersection, the cor. of secs. 32 and 33 only, T. 7 N., R. 6 W., bears S. 89° 57' E., 22.35 chs. dist., as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the official record.

From same point, the 1/4 sec. cor. of sec. 32 only, bears N. 89° 57' W., 17.63 chs. dist., as evidenced by an iron post, 1 in. diam., set, marked and witnessed as described in the official record.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

At midpoint on the N. bdy. of sec. 4.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at 1/4 sec. cor. of sec. 4, with brass cap marked

1/4 S 4

1940

From this corner, the 1/4 sec. cor. of sec. 33 only, T. 7 N., R. 6 W., bears S. 89° 57' E., 22.35 chs. dist.

From the same corner, the cor. of secs. 32 and 33 only, bears N. 89° 57' W., 17.66 chs. dist.

From cor. of secs. 5, 6, 31 and 32, on S. bdy. of Tp., as evidenced by an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.

N. 0° 03' W., bet. secs. 31 and 32.

Over rolling land, through scattering timber and undergrowth.

7.40 Road, bears N. 70° W. and E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at 1/4 sec. cor., with brass cap marked

S 31 | S 32

1940

raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

43.80 Wash, 15 lks. wide, course S. 30° E.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 29, 30, 31 and 32, with brass cap marked

T6N R6W

S 30 | S 29

S 31 | S 32

1940

raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

## Subdivision of T. 6 N., R. 6 W.


Chains	
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	S.89°59'E., on a random line bet. secs. 29 and 32.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.10	Intersect N. and S. line, 2 lks. S. of cor. of secs. 28, 29, 32 and 33.
	Thence
	-----
	West, on true line bet. secs. 29 and 32.
	Over rolling land, through scattering timber and undergrowth.
1.60	Wash, 20 lks. wide, course S.20°E.
17.80	Wash, 15 lks. wide, course S.
34.50	Wash, 30 lks. wide, course S.15°W.
40.05	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked.
	$\begin{array}{r} \frac{1}{4} \text{ S. 29} \\ \text{S. 32} \\ \hline 1940 \end{array}$
	raise a mound
	of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
45.10	Wash, 20 lks. wide, course S.20°E.
63.70	Wash, 20 lks. wide, course S.20°W.
77.90	Wash, 30 lks. wide, course S.10°W.
80.10	Cor. of secs. 29, 30, 31 and 32.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	N.89°59'W., on a random line bet. secs. 30 and 31.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.12	Intersect W. bdy. of Tp. 5 lks. S. of cor. of secs. 25, 30, 31 and 36, as evidenced by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.
	Thence
	S.89°57'E., on true line bet. secs. 30 and 31.
	Over rolling land, through scattering timber and undergrowth.
12.90	Wash, 25 lks. wide, course S.30°W.
22.30	Wash, 15 lks. wide, course S.15°W.

.Subdivision of T. 6 N., R. 6 W.

Chains

31.00 Wash, 15 lks. wide, course S.20°W.

39.12 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked



raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

53.30 Wash, 25 lks. wide, course S.

74.10 Wash, 15 lks. wide, course S.


79.12 The cor. of secs. 29,30,31 and 32.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

N.0°03'W., bet. secs. 29 and 30.

Over rolling land, through scattering timber and undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked




raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

42.40 Wash, 30 lks. wide, course S.10°E.

65.00 Wash, 15 lks. wide, course S.20°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 19,20,29 and 30, with brass cap marked



raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling,  
Soil, Rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

East, on a random line bet. secs. 20 and 29.

40.00 Set temp. ¼ sec. cor.

80.16 Intersect N. and S. line, 2 lks. S. of cor. of secs. 20,21, 28 and 29.

Thence

Subdivision of T. 6 N., R. 6 W.

Chains

S.89°59'W., on true line bet. secs. 20 and 29.

Over rolling land, through scattering timber and undergrowth.

0.65 Top of low hill; desc. 35 ft. over W. slope.

3.45 Ravine, course S.

4.80 Road, bears N.8½°W. and S.11°E.

24.45 Wash, 15 lks. wide, course S.10°E.; asc. 88 ft. over E. slope.

30.25 Spur, slopes S.; desc. 86 ft. over W. slope.

40.08 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked

¼ S 20  
S 29  
1940

raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

40.85 Wash, 30 lks. wide, course S.30°E.; asc. 80 ft. over E. slope.

50.25 Low flat spur, slopes S.; desc. 71 ft. over W. slope.

73.85 Wash, 15 lks. wide, course S.

76.15 Low flat spur, slopes S.

80.16 Cor. of secs. 19,20,29 and 30.

Land, rolling.

Soil, rocky, 4th rate.

Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

N.89°57'W., on a random line bet. secs. 19 and 30.

40.00 Set temp. ¼ sec. cor.

78.93 Intersect W. bdy. of Tp., 7 lks. N. of cor. of secs. 19,24, 25 and 30, as evidenced by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

Thence

East, on true line bet. secs. 19 and 30.

Over rolling land, through scattering timber and undergrowth.

5.35 Wash, 20 lks. wide, course S.30°E.

18.25 Wash, 20 lks. wide, course S.

38.93 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked

¼ S 19  
S 30  
1940

.Subdivision of T. 6 N., R. 6 W.

Chains

from which  
An ironwood, 4 ins. diam., bears N.79°W., 460 lks.  
dist., marked  $\frac{1}{4}$  S 19 B T.

An ironwood, 4 ins. diam., bears S.52°W., 146 lks.  
dist., marked  $\frac{1}{4}$  S 30 B T.

49.35 Wash, 20 lks. wide, course S.15°W.

57.15 Wash, 20 lks. wide, course S.20°E.

60.85 Wash, 20 lks. wide, course S.

74.95 Wash, 30 lks. wide, course S.20°W.

78.93 Cor. of secs. 19,20,29 and 30.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood  
and cactus.

N.0°03'W., bet. secs. 19 and 20.

Over rolling land, through scattering timber and under-  
growth.

8.50 Wash, 25 lks. wide, course SW.; asc. 55 ft. along E.  
slope.

22.30 Head of ravine, course E.; asc. 25 ft. over S. slope.

25.00 Spur, slopes SW.; desc. 17 ft. over N. slope.

28.50 Drain, course SW:

40.00 Set an iron post, 3 ft. long, 1 in. diam.; 28 ins. in the  
ground, at  $\frac{1}{4}$  sec. cor. with brass cap marked

S 19 | S 20

1940

raise a mound  
of stone, 3 ft. base, 2½ ft. high, W. of cor.

44.00 Road, bears N.53½°W. and S.72½°E.

66.10 Head of ravine, course S.60°W.

73.40 Ravine, course S.60°W.; asc. 54 ft. over SE. slope.

79.10 Top of ascent; desc. 5 ft. over NE. slope.

80.00 Set an iron post, 3 ft. long; 2 ins. diam., 28 ins. in the  
ground, at cor. of secs. 17,18,19 and 20, with brass cap  
marked

T6N R6W

S 18 | S 17

S 19 | S 20

1940

raise a mound  
of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling.  
Soil; rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood  
and cactus.

## Subdivision of T. 6 N., R. 6 W.

Chains	
	N.89°59'E., on a random line bet. secs. 17 and 20.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.08	Intersect N. and S. line, 5 lks. N. of cor. of secs. 16, 17, 20 and 21.
	Thence
	N.89°59'W., on true line bet. secs. 17 and 20.
	Over rolling land; through scattering timber and undergrowth.
5.10	Wash, 20 lks. wide, course S.10°E.
15.80	Wash, 30 lks. wide, course S.
24.90	Wash, 20 lks. wide, course S.30°E.
31.70	Wash, 20 lks. wide, course S.10°W.
39.85	Wash, 30 lks. wide, course S.
40.04	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $\frac{S 17}{S 20}$ 1940
77.80	Wash, 15 lks. wide, course S.20°W.
80.08	Cor. of secs. 17, 18, 19 and 20.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
-----	
	West, on a random line bet. secs. 18 and 19.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
78.79	Intersect W. bdy. of Tp., 5 lks. N. of cor. of secs. 13, 18, 19 and 24, as evidenced by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.
	Thence
	N.89°58'E., on true line bet. secs. 18 and 19.
	Over rolling land, through scattering timber and undergrowth.
16.10	Wash, 20 lks. wide, course S.20°W.
38.79	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $\frac{S 18}{S 19}$ 1940
	raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.

Subdivision of T. 6 N., R. 6 W.

Chains

- 42.10 Wash, 30 lks. wide, course S.
- 48.40 Wash, 20 lks. wide, course S.20°W.
- 52.90 Wash, 15 lks. wide, course S.30°W.
- 58.90 Wash, 15 lks. wide, course S.
- 69.40 Wash, 15 lks. wide, course S.; asc. 34 ft. over W. slope.
- 78.00 Top of low hill; desc. 15 ft. over NE. slope.
- 78.79 Cor. of secs. 17,18,19 and 20.


Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

-----  
N.0°03'W., bet. secs. 17 and 18.


Over rolling land, through scattering timber and undergrowth.

Desc. 38 ft. over NE. slope.

- 4.20 Wash, 15 lks. wide, course S.60°W.
- 9.10 Wash, 10 lks. wide, course S.30°W.
- 21.30 Same wash, 10 lks. wide, course S.20°E.
- 25.50 Wash, 10 lks. wide, course SW.
- 30.40 Wash, 10 lks. wide, course SW.; asc. 46 ft. over SE. slope.
- 37.40 Spur, slopes S.30°W.; desc. 14 ft. along a W. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at 1/4 sec. cor., with brass cap marked



- 44.80 Wash, 10 lks. wide, course SW.
- 47.00 Same wash, 10 lks. wide, course SE.; asc. 35 ft. over SW. slope.
- 68.10 Wash, 15 lks. wide, course S.30°W.; asc. 12 ft. over SE. slope.
- 77.40 Wash, 10 lks. wide, course S.15°W.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at cor. of secs. 7,8,17 and 18, with brass cap marked



## Subdivision of T. 6 N., R. 6 W.

## Chains

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

S.89°59'E., on a random line bet. secs. 8 and 17.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.12 Intersect N. and S. line, 9 lks. S. of cor. of secs. 8, 9, 16 and 17.

Thence

S.89°57'W., on true line bet. secs. 8 and 17.

Over rolling land, through scattering timber and undergrowth.

18.60 Wash, 10 lks. wide, course S.; asc. 46 ft. over SE. slope.

30.10 Saddle in spur, slopes S.; desc. 45 ft. over W. slope.

38.10 Wash, 10 lks. wide, course S.15°E.

40.06 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   $\frac{S\ 8}{S\ 17}$   
1940

44.60 Wash, 10 lks. wide, course S.

60.10 Wash, 25 lks. wide, course S.

70.70 Wash, 10 lks. wide, course S.30°W.

72.80 Junction of washes 10 lks. wide, from NE. and N., course S.20°W.

77.60 Wash, 8 lks. wide, course S.30°W.

80.12 Cor. of secs. 7, 8, 17 and 18.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

S.89°58'W., on a random line bet. secs. 7 and 18.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

78.61 Intersect W. bdy. of Tp., 9 lks. N. of cor. of secs. 7, 12, 13 and 18, as evidenced by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

Thence

N.89°54'E., on true line bet. secs. 7 and 18.

Over rolling land, through scattering timber and undergrowth.




## Subdivision of T. 6 N., R. 6 W.


Chains	
	Asc. 14 ft. over NW. slope.
1.70	Spur, slopes S.; desc. 25 ft. over E. slope.
4.20	Head of ravine, course S.; asc. 54 ft. over gradual SW. slope.
13.20	Spur, slopes S.; along S. slope.
17.70	Spur, slopes S.20°W.; desc. 30 ft. over E. slope.
21.00	Ravine, course S.; asc. 42 ft. over W. slope.
24.70	Saddle in spur, slopes SE.; desc. 55 ft. over NE. slope.
32.10	Ravine, course S.; asc. 47 ft. over W. slope.
34.70	Spur, slopes S.30°E.; desc. 27 ft. over E. slope.
38.61	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $\frac{S 7}{S 18}$ 1940
	Desc. 7 ft. over E. slope.
39.80	Ravine, course S.; asc. 25 ft. over W. slope.
42.60	Spur, slopes S.; desc. 27 ft. over NE. slope.
44.70	Ravine, course SE.; asc. 27 ft. over W. slope.
47.10	Spur, slopes SE.; desc. 32 ft. over NE. slope.
50.30	Wash, 10 lks. wide, course S.15°E.
55.60	Wash, 20 lks. wide, course SW.; asc. 30 ft. over NW. slope.
61.60	Desc. 24 ft. over E. slope.
69.40	Wash, 20 lks. wide, course S.15°W.
71.90	Dim road, bears N. and S.
78.61	Cor. of secs. 7, 8, 17 and 18.
	Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	-----
	N.0°03'W., bet. secs. 7 and 8.
	Over rolling land, through scattering timber and undergrowth.
5.80	Dim road, bears N.30°E. and S.30°W.
7.00	Wash, 15 lks. wide, course SW.; asc. 38 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked

Subdivision of T. 6 N., R. 6 W.

Chains




- 45.00 Bend in wash, 10 lks. wide, from NW. to S.10°W.
- 51.00 Same wash, at bend from NW. to SW.; asc. 55 ft. over S. slope.
- 57.00 Short spur, slopes S.30°E.; desc. 34 ft. over NE. slope.
- 72.40 Wash, 10 lks. wide, course S.30°E.; asc. gradually over rolling land.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 5,6,7 and 8, with brass cap marked



raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling.  
Soil, rocky, 4th rate.  
Timber, palo verde and ironwood; undergrowth, greasewood and cactus.

- 40.00 N.89°57'E., on a random line bet. secs. 5 and 8.  
Set temp. ¼ sec. cor.
- 80.18 Intersect N. and S. line, 3 lks. N. of cor. of secs. 4, 5,8 and 9.  
Thence  
S.89°58'W., on true line bet. secs. 5 and 8.  
Over rolling land, through scattering timber and undergrowth.  
Desc. 25 ft. along S. slope.
- 3.10 Ravine, course S.25°W.
- 15.80 Road, bears N. and S.
- 20.80 Wash, 10 lks. wide, course S.20°W.
- 27.60 Wash, 15 lks. wide, course S.20°W.
- 35.00 Wash, 20 lks. wide, course S.10°W.
- 40.09 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked



raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Desc. 18 ft. over a SW. slope.

## Subdivision of T. 6 N., R. 6 W.

Chains	
43.80	Wash, 8 lks. wide, course S.20°E.; asc. 41 ft. over E. slope.
47.50	Spur, slopes S.; desc. 29 ft. over W. slope.
52.50	Wash, 15 lks. wide, course S.; asc. 78 ft. over SE. slope.
62.40	Top of low hill; desc. 54 ft. over SW. slope.
64.70	Ravine, course S.10°E.; asc. 25 ft. over E. slope.
67.40	Spur, slopes S.; desc. 21 ft. over W. slope.
68.90	Ravine, course S.; asc. 44 ft. over E. slope.
72.40	Spur, slopes S.; desc. 45 ft. over W. slope.
77.80	Wash, 15 lks. wide, course S.
80.18	The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
	----- S.89°54'W., on a random line bet. secs. 6 and 7.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
78.42	Intersect W. bdy. of Tp., .9 lks. N. of cor. of secs. 1, 6, 7 and 12, as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the official record.
	Thence N.89°50'E., on true line bet. secs. 6 and 7. Over rolling land, through scattering timber and undergrowth.
10.10	Wash, 20 lks. wide, course S.20°W.
16.40	Old road, bears N.20°W. and S.20°E.
20.20	Ravine, course N.75°W.; asc. 84 ft. over SW. slope.
28.40	Spur, slopes SW.; desc. 32 ft. over SE. slope.
33.70	Ravine, course SW.; asc. 47 ft. over NW. slope.
36.40	Spur, slopes SW.; desc. 5 ft. over SE. slope.
38.42	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$ S 6. S 7 1940
40.80	Ravine, course SW.; asc. 142 ft. over NW. slope.
52.10	Ridge, bears N. and S. Top of hill, 50 ft. high, bears S. about '2 chs. dist.; desc. 48 ft. over NE. slope.
55.50	Spur, slopes N.70°E.; desc. 114 ft. over SE. slope.

.Subdivision of T. 6 N., R. 6 W.

Chains	
68.20	Wash, 15 lks. wide, course S.60°E. at junction of ravines from N.30°W. and S.60°W. Over point of spur from N.
71.20	Same wash at bend; 15 lks. wide, from S.80°W. to SE.; asc. 18 ft. over SW. slope.
74.40	Spur, slopes S. Desc. gradually over rolling land.
78.42	Cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, rocky, 4th rate. Timber, palo verde and ironwood; undergrowth, greasewood and cactus.
-----	
	N.0°03'W., on true line bet. secs. 5 and 6. Over rolling land, through scattering timber and undergrowth.
6.50	Wash, 8 lks. wide, course SE.; asc. 38 ft. along broken E. slope.
26.10	Wash, 15 lks. wide, course S.30°E.; asc. 52 ft. over broken S. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, over + marked on bedrock, and in a mound of stone to top, at ¼ sec. cor., with brass cap marked
	<div style="text-align: center;"> <p>S 6   S 5 ↑ 1/4 1940</p> </div>
	Asc. 17 ft. over S. slope.
45.00	Ridge, bears NW. and S.60°E.; desc. 43 ft. over NE. slope.
56.70	Wash, 10 lks. wide, course N.30°W.
60.20	Same wash, 10 lks. wide, course N.20°E.
68.00	Enter same wash, 10 lks. wide, course N. from SE.; along bottom of wash.
69.00	Leave wash, course NE.
72.50	Same wash at bend, course NE. from SE.
76.50	Same wash, 10 lks. wide, course N.60°W.
80.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at cor. of lots Nos. 4 and 5 of sec. 5, and lots Nos. 1 and 8 of sec. 6, with brass cap marked
	<div style="text-align: center;"> <p>S 6   1/4   S 5 ↑ 8   5 1940</p> </div>
	raise a mound of stone, 3 ft. base; 2½ ft. high, W. of cor.
85.66	Intersect S. bdy. of sec. 31, T.7 N., R.6 W.

## Subdivision of T. 6 N., R. 6 W.

## Chains

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing cor. of secs. 5 and 6, with brass cap marked

T7N R6W  
S31  
-----  
S 6 | S 5  
T6N R6W  
C C  
1940

raise a mound  
of stone, 3 ft. base, 2½ ft. high, S. of cor.

From point of intersection, the corner of secs. 31 and 32 only, T. 7 N., R. 6 W., bears S.89°59'E., 22.57 chs. dist. as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the official record.

From the same point of intersection, the ¼ sec. cor. of sec. 31 only, T. 7 N., R. 6 W., bears N.89°59'W., 17.38 chs. dist., as evidenced by an iron post, 1 in. diam., set, marked and witnessed as described in the official record.

At midpoint on the N. bdy. of sec. 5,

Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground, over + marked on bedrock and in a mound of stone to top, at ¼ sec. cor. of sec. 5, with brass cap marked

¼ S 5  
1940

From this corner, the ¼ sec. cor. of sec. 32 only, T. 7 N., R. 6 W., bears N.89°56'E., 22.47 chs. dist.

From this same corner, the cor. of secs. 31 and 32 only, T. 7 N., R. 6 W., bears S.89°56'W., 17.53 chs. dist.

At a point on the N. bdy. of sec. 6, .40.00 chs. in departure from the closing corner of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor. of sec. 6, with brass cap marked

¼ S 6  
1940

raise a mound  
of stone, 3 ft. base, 2½ ft. high, S. of cor.

From this corner, the ¼ sec. cor. of sec. 31 only, T. 7 N., R. 6 W., bears S.89°59'E., 22.62 chs. dist.

From the same corner, the corner of Ts. 7 N., Rs. 6 and 7 W., bears N.89°59'W., 28.23 chs. dist.

-----  
FINAL TEST OF INSTRUMENT

April 7, 1940:

At station in camp, near center of sec. 31, T. 6 N., R. 6 W., G. & S.R.M., Arizona, in lat. 33°49'N. and longitude 112°49'10"W., examine the adjustments of Gurley transit No. 371537 and find no errors. To test the solar apparatus of this instrument on the true meridian established March 3, 1940, proceed as follows:

BOOK 4329

At 9h.00m., a.m., app.t., with lat. arc set at  $33^{\circ}49'N.$ , and decl. arc set at  $6^{\circ}58'N.$ , determine a meridian with the solar which agrees with the true meridian.

At app. noon, with lat. arc unchanged, observe the sun on the meridian; the resultant reading of the decl. arc is  $7^{\circ}00'N.$ , which agrees with the computed declination of the sun.

At 3h.00m., p.m., app.t., with lat. arc unchanged, set off  $7^{\circ}03'N.$  on decl. arc and determine a meridian with the solar which agrees with the true meridian.

As all of the observations taken during the usual hours of solar work agree within 1' of the true meridian, conclude that the adjustments of the instrument have been maintained during the surveys described in the foregoing notes.

#### GENERAL DESCRIPTION.

This Tp. lies on the south slope of the low, broken Vulture Mountain range, the southernmost tier of secs. merging into the Hassayampa plain. The elevation of the area varies from approximately 2000 to 3000 ft. above sea level. The mountains are broken and quite rocky. An intricate net work of deep ravines and sandy washes drain the Tp. in a southerly direction, losing their identity in the nearly level plain at the foot of the mountains. No permanent springs or water tanks are located in the Tp. Soil on the mountain slopes is largely 3rd rate decomposed granite and is quite shallow. The leveler areas and wash bottoms contain 2nd and 3rd rate sandy soil and silt.

In general, the Tp. supports but a sparse growth of native grasses, but bears a heavy undergrowth, and along the wash bottoms a medium growth of scrub timber exists. Predominating species of undergrowth are greasewood, palo verde, sage, cactus, ocotillo, palo cristo and cats claw. The timber is principally palo verde, ironwood, mesquite and sahuaro cactus.

The entire Tp. is in varying degrees mineralized. The heaviest ore deposits occur in secs. 25, 26, 35 and 36. The Vulture Mine in sec. 36 now comprising about 200 acres of patented mineral lands, has been a heavy gold producing property for over eighty years. This mine is being operated on a considerably reduced scale at the present time. A population of about 100 persons live at the mine or in the immediate vicinity.

There are no cultivated lands in the Tp. The public lands are in general use for cattle and sheep grazing. All improvements in the Tp. have been made in connection with mining activities.

A system of unimproved roads and trails lend access to nearly every part of the Tp. An improved road running between the Vulture Mine and Wickenburg enters the east bdy. of sec. 13 and emerges from the east bdy. of sec. 12, approximately 1 mile north.

Repeated observations to obtain the magnetic variation show a local attraction of about  $1^{\circ}$ . The mean value of these observations is  $14^{\circ}45' E.$



54

CERTIFICATE OF SURVEYOR

BOOK 4829

I, Raymond F. Moss, Assistant Cadastral Engineer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 13th day of July, 1939 received from the district cadastral engineer for Arizona, with assignment instructions dated November 22, 1939, I have ~~surveyed~~ **resurveyed** a portion of the East Boundary of Township 6 North, Range 7 West and surveyed the Sub-divisional Lines of Township 6 North, Range 6 West

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said **resurvey and** survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona  
January 31, 1942

*Raymond F. Moss*  
Assistant Cadastral Engineer  
(formerly Public Land Surveyor)

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,  
Denver, Colorado, July 13, 1945.

The foregoing field notes of the ~~survey of~~ **resurvey of** a portion of the East Boundary of Township 6 North, Range 7 West and the survey of the Subdivisional Lines of Township 6 North, Range 6 West of the Gila and Salt River Meridian, State of Arizona

executed by Raymond F. Moss, Public Land Surveyor, General Land Office, under special instructions dated July 13, 1939, and assignment instructions dated November 22, 1939, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey **and resurvey** therein described, are hereby approved.

*[Signature]*  
Supervisor of Surveys.

CERTIFICATE OF TRANSCRIPT

~~I certify that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys~~