

UNITED STATES
DEPARTMENT OF THE INTERIOR
~~GENERAL LAND OFFICE~~
BUREAU OF LAND MANAGEMENT

BOOK 4350

FIELD NOTES

of the

Resurvey of

The North, East and West Boundaries

and

Subdivisional Lines

of

Township 23 North, Range 3 East.

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Ty White and Claude F. Warner,

Assistant Cadastral Engineers, General Land Office.

Under special instructions dated March 13, 1942, which provided for the surveys included under Group No. 239, bearing the approval of the Commissioner of the General Land Office under date of March 28, 1942 and assignment instructions dated June 1, 1942.

Survey commenced July 27, 1942

Survey completed September 8, 1942

4350

4350

(1)

14A

BOOK 4850

INDEX DIAGRAM.

Township 23 North, Range 3 East.

	24	22	21	20	19	18	
17	6 81	82 5 80	67 4 66	57 3 57	46 2 46	36 1 35	9
15	7 78	79 8 77	65 9 65	55 10 55	44 11 44	34 12 33	7
14	18 76	76 17 75	64 16 63	54 15 53	43 14 42	32 13 31	6
13	19 73	73 20 72	62 21 61	51 22 51	41 23 40	29 24 28	5
11	30 70	70 29 69	60 28 59	49 27 48	39 26 38	27 25 26	3
10	31 81	68 32 82	58 33 83	47 34 84	37 35 85	24 36 86	2

1B

TOWNSHIP 23 NORTH, RANGE 3 EAST

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

———— Indicates surveys executed by Ty White

———— Indicates surveys executed by Claude F. Warner

Date of Survey

East Boundary: July 27 to August 3, 1942
North Boundary: August 6 to August 31, 1942
West Boundary: August 7 to September 1, 1942
Subdivisions: August 4 to September 5, 1942

The resurvey hereinafter described was executed with Buff solar transits Nos. 16724 and 9984, constructed in accordance with the standard specifications of the General Land Office. The instruments were in good adjustment and having been placed in satisfactory adjustment prior to beginning the resurvey and tested and found free from appreciable error, were approved by the district cadastral engineer on June 1, 1942.

The directions of the lines were determined by the solar transit method. The measurements were made with Lallie steel tapes 5 chains in length, graduated every link for the first 100 links, and the balance at intervals of 10 links. The tapes were tested by comparison with a Lufkin standard and found correct. The measurements were made on the slope and the vertical angles ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The data furnished with the special instructions gives the geographic position of the southeast corner of T. 23 N., R. 3 E., G. & S. R. M., as follows: latitude $35^{\circ} 19\frac{1}{2}' N.$, longitude $112^{\circ} 01' W.$

July 19, 1942, at camp in the SE. $\frac{1}{4}$ of sec. 14, T. 23 N., R. 3 E., G. & S. R. M., with Buff solar transit No. 16724, at 7h 24.1m p.m. l.m.t. or 7h 52.2m p.m. by my watch which reads correct 105th meridian time as determined by radio time signals, I make an hour angle observation on Polaris, east of the meridian, making four observations, two each with the telescope in direct and reversed position, and mark the mean point in the line thus determined, on a peg driven firmly in the ground seven chains N. In order to verify the latitude of this station, I also read the vertical angles to Polaris.

Mean watch time of observation, p.m.	7h 52m 12s
Watch fast of l.m.t.	0h 28m 06s
Azimuth of Polaris	$0^{\circ} 27' 48''$

Mean vertical angle to Polaris	$34^{\circ} 26' 38''$
Reduced latitude	$35^{\circ} 21' 45'' N.$

July 20, I lay off the azimuth of Polaris $0^{\circ} 27'.8$ to the west, and mark the line thus determined by a tack in a peg driven firmly in the ground seven chains N.

July 26, 1942, on the meridian above described, every 30 minutes from 8 to 10:30 a.m. and from 1:30 to 4 p.m., we make the proper settings on the arcs of the solar attachments and ascertain that the resulting orientation of the instruments, when compared with the meridian established by Polaris observation; have a maximum error of less than $1' 30''$.

We repeat the tests of the arcs daily by noon observations and verify the meridional indications at frequent intervals throughout the survey.

Preliminary to the resurvey the lines of the original survey are retraced and diligent search is made for all original corners. Identified corners of the original survey are reestablished in their original positions. All lost corners are reestablished by the method of single proportion, double proportion or collateral evidence as appropriate, based on the original record. The retracement data are thoroughly verified and only the true line notes are given herein.

Dependent Resurvey of the East Bdy. of T. 23 N., R. 3 E.

Chains

Reestablishment of the survey executed by W. R. Fitzgerald, Deputy Surveyor, in 1883.

From the cor. of Ts. 22 and 23 N., Rs. 3 and 4 E., an iron post, 3 ins. diam., 9 ins. above ground, firmly set, mkd. and witnessed as described in the field notes of the resurvey of the N. bdy. of T. 22 N., R. 4 E.

N. 0° 21' E., on a true line bet. secs. 31 and 36.

Over mountainous land, through dense timber and undergrowth asc. 19 ft. over a S. slope,

- 1.70 Spur, slopes W.; desc. 11 ft. over a NW. slope.
 3.90 Ravine, course SW.; asc. 13 ft. over a S. slope.
 5.90 Spur, slopes W.; continue ascent over a W. slope.
 6.90 Ravine, course W.; asc. 53 ft. over a SW. slope.
 10.80 Spur, slopes SW.; continue ascent over a W. slope.
 18.30 Ravine, course SW.; asc. 26 ft. over a S. slope.
 20.00 Spur, slopes W.; continue ascent along a W. slope.
 23.20 Ravine, course SW.; ascend 27 ft. over a S. slope.
 24.80 Spur, slopes W.; asc. 83 ft. over a broken W. slope.
 38.90 Ravine, course SW.; asc. 40 ft. over a S. slope.
 39.55 The point for the $\frac{1}{4}$ sec. cor., determined from the original bearing tree.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 36 | S 31
 1942

from which

The original bearing tree:

A pine, 24 ins. diam., bears N. 20° W., 15 lks. dist., mkd. $\frac{1}{4}$ S B T. Additionally mark this tree $\frac{1}{4}$ S 36 B T.

New bearing tree:

A pine, 5 ins. diam., bears S. 39° E., 32 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.

N. 0° 30' E., on a true line bet. secs. 31 and 36.

Ascend 48 ft. over a broken SW. slope.

Dependent Resurvey of the East Bdy. of T. 23 N., R. 3 E. 4650

Chains	
3.80	Spur, slopes S. 70° W.; continue ascent of 93 ft. over a SW. slope.
14.00	Spur, slopes SW.; desc. 17 ft. over a NW. slope.
16.50	Ravine, course SW.; asc. 70 ft. over a SE. slope.
20.50	Spur, slopes SW.; desc. 65 ft. over a NW. slope.
32.80	Ravine, course W.; asc. 89 ft. over a S. slope.
39.08	The point for the cor. of secs. 25, 30, 31 and 36, as determined from the original bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.

T23N	
R3E	R4E
S 25	S 30
S 36	S 31
1942	

from which

Old bearing trees:

A pine, 30 ins. diam., bears N. 67° E., 78 lks. dist., mkd. T 23 N R 4 E S 30 B T.

A pine, 30 ins. diam., bears S. 77½° W., 60 lks. dist., mkd. T 23 N R 3 E S 36 B T.

A pine, 30 ins. diam., bears N. 50½° W., 62 lks. dist., mkd. T 23 N R 3 E S 25 B T.

New bearing tree:

A pine, 8 ins. diam., bears S. 43° E., 20 lks. dist., mkd. T 23 N R 4 E S 31 B T.

Land, mountainous.

Soil, dark loam, rocky and gravelly, 3rd rate.

Timber, Pine, oak and juniper; undergrowth, 2nd growth pine.



N. 0° 19' W., on a true line bet. secs. 25 and 30.

Over mountainous land, thru dense timber and undergrowth.

Ascend along a SW. slope.

3.00	Spur, slopes W.; desc. 112 ft. over a N. slope.
6.60	Ravine, course S. 80° W.; asc. 118 ft. over a steep S. slope.
15.50	Spur, slopes S. 80° W.; desc. 45 ft. over a N. slope.
17.40	Gulch, 10 lks. wide, course S. 80° W.; asc. 376 ft. over a steep S. slope.
29.30	Base of a cliff, bears E. and W.
30.25	Top of cliff, bears E. and W.; continue ascent of 59 ft. over a SW. slope.
36.40	Top of a high spur, slopes W. from SE. This is one of the

Dependent Resurvey of the East Bdy. of T. 23 N., R. 3 E.

Chains	main spurs from Sitgreaves Mountain to the southeast; desc. 64 ft. over a steep N. slope.
38.38	The $\frac{1}{4}$ sec. cor., a sandstone, 8x6x6 ins., mkd. $\frac{1}{4}$ on W. face firmly set in a mound of stone.
	At point for cor.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;">  <p>S 25 S 30 1942</p> </div> <p style="text-align: right;">from which</p>
	The old bearing tree:
	A fir (dead), 10 ins. diam., bears N. $17\frac{1}{2}^{\circ}$ E., 27 lks. dist., mkd. $\frac{1}{4}$ S B T.
	New bearing trees:
	A fir, 10 ins. diam., bears N. 38° E., 39 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.
	A fir, 6 ins. diam., bears S. 83° W., 22 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.
	N. 1° 10' W., on a true line bet. secs. 25 and 30.
	Descend 513 ft. over a steep N. slope.
18.10	Wash, 10 lks. wide, 18 ins. deep, course W. for 3 chs. then NW.; continue along a W. slope.
30.30	Spur, slopes W.; desc. 58 ft. over a NW. slope.
32.80	Gulch, 10 lks. wide, course NW.; along a W. slope.
34.60	Spur, slopes W.; desc. over a N. slope.
35.50	Gulch, 5 lks. wide, course SW. for 2 chs. then N. 70° W.; asc. over a S. slope.
38.08	The point for the cor. of secs. 19, 24, 25 and 30, as determined from the original bearing trees.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 19, 24, 25 and 30, with brass cap mkd.
	<div style="text-align: center;">  <p>T23N R3E R4E S 24 S 19 S 25 S 30 1942</p> </div> <p style="text-align: right;">from which</p>
	The old bearing trees:
	A fir, 8 ins. diam., bears S. $14\frac{3}{4}^{\circ}$ E., 55 lks. dist., mkd. T 23 N R 4 E S 30 B T.
	A fir, 10 ins. diam., bears S. $10\frac{1}{2}^{\circ}$ W., 52 lks. dist., mkd. T 23 N R 3 E S 25 B T.

Dependent Resurvey of the East Bdy. of T. 23 N., R. 3 E.

Chains

A fir, 8 ins. diam., bears N. $60\frac{1}{4}^{\circ}$ W., 31 lks.
dist., mkd. T 23 N R 3 W S 24 B T.

New bearing tree:

A pine, 7 ins. diam., bears N. 43° E., 18 lks.
dist., mkd. T 23 N R 4 E S 19 B T.

Land, mountainous.

Soil, dark loam, rocky, 3rd rate.

Timber, pine, fir, spruce, oak and juniper; undergrowth,
2nd growth pine.

N. $0^{\circ} 47'$ W., on a true line, bet. secs. 19 and 24.

Over mountainous land, thru dense timber and undergrowth.

Descend 296 ft. over a broken NW. slope, a series of small
spurs and ravines.

24.00 Spur, slopes W.; continue descent over a broken NW. slope.

31.50 Drain, 10 lks. wide, 18 ins. deep, course W.; desc. over
a broken NW. slope.

36.00 Spur, slopes W.; continue descent.

39.24 The point for the $\frac{1}{4}$ sec. cor., determined from the orig-
inal bearing tree.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 24 | S 19
 1942

from which

The original bearing tree:

A pine, 28 ins. diam., bears N. 80° W., 7 lks.
dist., mkd. $\frac{1}{4}$ S B T. I additionally mark this tree
 $\frac{1}{4}$ S 24 B T.

New bearing tree:

A pine, 8 ins. diam., bears S. 49° E., 36 lks.
dist., mkd. $\frac{1}{4}$ S 19 B T.

N. $0^{\circ} 07'$ W., on a true line bet. secs. 19 and 24.

Descend 51 ft. over a NE. slope.

3.70 Wash, 10 lks. wide, 1 ft. deep, course NW.; asc. 15 ft.
over a SW. slope.

5.50 Spur, slopes NW.; desc. 257 ft. over a broken NW. slope.

29.60 Spur, slopes NW.; continue descent over a broken NW. slope.

37.30 Spur, slopes NW.; desc. 30 ft. over a NE. slope.


40.10 Small drain, course NW.

40.23 Proportional distance.

Dependent Resurvey of the East Bdy. of T. 23 N., R. 3 E.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 13, 18, 19 and 24, with brass cap mkd.



from which

A pine, 8 ins. diam., bears N. $33\frac{1}{4}^\circ$ E., 10 lks. dist., mkd. T 23 N R 4 E S 18 B T.

A pine, 10 ins. diam., bears S. $29\frac{1}{2}^\circ$ E., 32 lks. dist., mkd. T 23 N R 4 E S 19 B T.

A pine, 5 ins. diam., bears S. 61° W., 12 lks. dist., mkd. T 23 N R 3 E S 24 B T.

A pine, 6 ins. diam., bears N. $36\frac{1}{4}^\circ$ W., 12 lks. dist., mkd. T 23 N R 3 E S 13 B T.

Land, mountainous.

Soil, dark loam, rocky, 3rd rate.

Timber, pine, fir, spruce, oak and juniper; undergrowth, 2nd growth pine.

N. $0^\circ 07'$ W., on a true line bet. secs. 13 and 18.


Over mountainous land, thru dense timber and undergrowth; desc. 139 ft. over a NW. slope.

21.35 Spur, slopes WW.; desc. over a NE. slope.

33.75 Wash, 10 lks. wide, 1 ft. deep, course N. 70° W.; asc. over a gentle WW. slope.

40.23 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A pine, 12 ins. diam., bears S. $49\frac{1}{2}^\circ$ E., 73 lks. dist., mkd. $\frac{1}{4}$ S 18 B T.

A pine, 12 ins. diam., bears S. $69\frac{1}{2}^\circ$ W., 50 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.

52.90 Graded road, bears W. to Red Lake and E. to Spring Valley..

58.80 Wash, 10 lks. wide, 1 ft. deep, course S. 70° W.; asc. 35 ft. over a SE. slope.

80.46 The cor. of secs. 7, 12, 13 and 18, a lava stone, 16x12x10 ins. firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. 4 grooves on S. face and 2 grooves on N. face.

At point for cor.

Dependent Resurvey of the East Bdy. of T. 23 N., R. 3 E.

BOOK 6810

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for cor. of secs. 7, 12, 13 and 18, with brass cap mkd.

T23N	
R3E	R4E
S 12	S 7
S 13	S 18
1942	

from which

Old bearing trees:

A juniper, 36 ins. diam., bears S $2\frac{1}{2}^{\circ}$ E., 136 lks. dist., mkd. T 23 N R 4 E S 18 B T.

A juniper, 36 ins. diam., bears S. 6° W., 165 lks. dist., mkd. T 23 N R 3 E S 13 B T.

No evidence of NW. bearing tree.

New bearing trees:

A pine, 10 ins. diam., bears N. 32° E., 89 lks. dist., mkd. T 23 N R 4 E S 7 B T.

A pine, 12 ins. diam., bears N. $38\frac{1}{2}^{\circ}$ W., 46 lks. dist., mkd. T 23 N R 3 E S 12 B T.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, pine, fir, oak and juniper; undergrowth, 2nd growth pine.

N. 0° 16' W., on a true line bet. secs. 7 and 12.

Over rolling land, thru scattered timber and undergrowth.

Ascend 23 ft. over a SW. slope.

- 6.50 Spur, slopes SW. thence along a W. slope.
- 13.60 Wash, 15 lks. wide, 18 ins. deep, course SW.; asc. 40 ft. over a S. slope.
- 22.00 Spur, slopes W.; desc. 45 ft. over a N. slope.
- 28.20 Wash, 30 lks. wide, 3 ft. deep, course W.; asc. 15 ft. over a S. slope.
- 31.00 Spur, slopes NW.; desc. 20 ft. over a NE. slope.
- 33.00 Wash, 5 lks. wide, course NW.; asc. 21 ft. over a SW. slope.
- 40.10 The $\frac{1}{4}$ sec. cor., a lava stone, 18x12x6 ins. firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent Resurvey of the East Bdy. of T. 23 N., R. 3 E.

Chains

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 12 \mid \text{S } 7 \\ | \\ 1942 \end{array}$$

from which

The old bearing tree:

A juniper, 24 ins. diam., bears N. 6° E., 95 lks. dist., mkd. $\frac{1}{4}$ S B T. I additionally mark this tree $\frac{1}{4}$ S 7 B T.

New bearing tree:

A pine, 12 ins. diam., bears S. $33\frac{1}{2}^{\circ}$ W., 82 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.

N. 1° 24' E., on a true line bet. secs. 7 and 12.

Ascend over a SW. slope.

- 5.00 Spur, slopes W.; desc. 49 ft. over a NW. slope.
- 9.50 Gulch, 10 lks. wide, course S. 80° W.; asc. 31 ft. over a SW. slope.
- 13.50 Spur, slopes S. 80° W.; desc. 46 ft. over a NW. slope.
- 17.50 Draw, drains S. 80° W.; asc. 18 ft. over a gradual S. slope.
- 31.00 Low spur, slopes NW.; desc. 59 ft. over a NE. slope.
- 39.89 The cor. of secs. 1, 6, 7 and 12, a lava stone, 20x18x6 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. 5 grooves on S. face and 1 groove on N. face.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

$$\begin{array}{c} \text{T23N} \\ \text{R3E} \mid \text{R4E} \\ \text{S } 1 \mid \text{S } 6 \\ \hline \text{S } 12 \mid \text{S } 7 \\ 1942 \end{array}$$

from which

Old bearing tree:

A pine, 32 ins. in diam., bears N. 44° E., 48 lks. dist., mkd. T 23N R 4 E S 6 B T.

No evidence of SE. and SW. bearing tree.

New bearing trees:

A pine, 8 ins. diam., bears S. $23\frac{3}{4}^{\circ}$ E., 84 lks. dist., mkd. T 23 NR 4 E S 7 B T.

A pine, 12 ins. diam., bears S. 73° W., 51 lks. dist., mkd. T 23 NR 3 E S 12 B T.

A pine, 6 ins. diam., bears N. $42\frac{1}{4}^{\circ}$ W., 23 lks. dist., mkd. T 23 NR 3 E S 1 B T.

Dependent Resurvey of the East Bdy. of T. 23 N., R. 3 E. 4850

Chains	Land, rolling. Soil, dark loam, rocky, 3rd and 4th rates. Timber, pine, fir, oak and juniper; undergrowth, 2nd growth pine.

	N. 0° 38' E., on a true line bet. secs. 1 and 6. Over rolling land, through scattered timber and undergrowth; desc. 52 ft. over a gradual NE. slope.
36.00	Dim road, bears S. 60° E. and N. 60° W.
40.59	The $\frac{1}{4}$ sec. cor., a lava stone, 14x12x8 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face. At point for cor. Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 1 S 6 ----- 1942 from which
	A pine, 8 ins. diam., bears S. 80 $\frac{1}{2}$ ° E., 77 lks. dist., mkd. $\frac{1}{4}$ S 6 B T. A pine, 8 ins. diam., bears N. 68 $\frac{1}{2}$ ° W., 82 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.
	N. 0° 02' E., on a true line, bet. secs. 1 and 6.
20.60	Wash, 20 lks. wide, 1 ft. deep, course NW.; asc. over a SW. slope.
26.30	Low spur, slopes S. 60° W.; desc. over a gradual N. slope.
40.25	The cor. of Ts. 23 and 24 N., Rs. 3 and 4 E., a lava stone 16x12x4 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high; mkd. 6 grooves on N., E., S. and W. faces. At point for cor. Set an iron post, 3 ft. long, 3 ins. diam., 10 ins. in the ground to bedrock, with the original stone buried alongside and in a mound of stone to top, for cor. of Ts. 23 and 24 N., Rs. 3 and 4 E., with brass cap mkd.
	T24N R3E R4E S 36 S 31 ----- S 1 S 6 T23N 1942 from which
	The old bearing trees: A pine, 36 ins. diam., bears N. 29 $\frac{3}{4}$ ° E., 64 lks. dist., marks not uncovered. A pine, (dead), 40 ins. diam., bears S. 40 $\frac{3}{4}$ ° E., 111 lks. dist., mkd. T 23 N R 4 E S 6 B T.

Dependent Resurvey of the East Bdy. of T. 23 N., R. 3 E.

Chains

A pine (dead), 30 ins. diam., bears S, $28\frac{1}{2}^{\circ}$ W., 105 lks. dist., marks not uncovered.

New bearing trees:

A pine, 10 ins. diam., bears S, $15\frac{1}{2}^{\circ}$ E., 78 lks. dist., mkd. T 23 N R 4 E S 6 B T.

A pine, 8 ins. diam., bears S, $8\frac{1}{2}^{\circ}$ W., 109 lks. dist., mkd. T 23 N R 3 E S 1 B T.

A pine, 10 ins. diam., bears N, $20\frac{1}{2}^{\circ}$ W., 68 lks. dist., mkd. T 24 N R 3 E S 36 B T.

Land, rolling.

Soil, dark loam and clay, rocky, 3rd and 4th rates.
Timber, pine, fir, oak and juniper; undergrowth, 2nd growth pine.

Dependent Resurvey of the West Bdy. of T. 23 N., R. 3 E.

Reestablishment of the survey executed by W. R. Fitzgerald, Deputy Surveyor, in 1883.

From the cor. of Ts. 22 and 23 N., Rs. 2 and 3 E., an iron post, 3 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the field notes of the resurvey of the N. bdy. of T. 22 N., R. 3 E.

N. $0^{\circ} 05'$ W.; on a true line bet. secs. 31 and 36.

Over rolling land, through scattered timber and undergrowth.

10.00 Leave timber; enter a roadway, bears N. and SW., thence along road, with pasture land to the E. and W.

40.40 Proportional distance:

Set a lava stone, 16x10x6 ins., 12 ins. below the surface of the road, for $\frac{1}{4}$ sec. cor., mkd. X, from which

A pinyon, 8 ins. diam., bears N. $67\frac{3}{4}^{\circ}$ E., 157 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.

At a point, S. 45° E., 0:60 chs. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 WC
 S 36 | S 31
 1942


At a point, N. 45° W., 0.60 chs. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent Resurvey of the West Bdy. of T. 23 N., R. 3 E.

BOOK 4850

Chains



The $\frac{1}{4}$ sec. cor. is located near the center line of the road.

Continue along center of road with pasture land to the E. and W.


45.00 Low spur, slopes W.; desc. a gradual N. slope.

80.80 Proportional distance.

Set a lava stone, 16x8x4 ins., 12 ins. below the surface of the road, for cor. of secs. 25, 30, 31 and 36, mkd. X.


At a point, S. 45° E., 0.60 chs. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. of secs. 25, 30, 31 and 36, with brass cap mkd.



At a point, W. 45° W., 0.60 chs. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. of secs, 25, 30, 31 and 36, with brass cap mkd.



The cor. of secs. 25, 30, 31 and 36 is located near the intersection of the center lines of roads from E. and S.

Land, rolling.

Soil, dark loam, rocky, 2nd and 3rd rates.

Timber, pine; undergrowth, none.

N. $0^{\circ} 05'$ W., on a true line bet. secs. 25 and 30.

Over gently rolling pasture land.

0.40 A 4 strand barbed wire fence, on the W. side of the road, bears S. $85^{\circ} 30'$ E., and N. $85^{\circ} 30'$ W. about 20 lks. to a fence cor., from which fences bear northerly, southerly and S. $85^{\circ} 30'$ E.; enter pasture land.

14.00 Wire fence, enclosing an earth reservoir, bears E. and W.; reservoir, bears NE. approx., 2.50 chs. dist.

16.40 Wire fence, enclosing reservoir, bears E. and W.

Dependent Resurvey of the West Bdy. of T. 23 N., R. 3 E.

Chains 31.60 33.35 35.30 39.40 40.40	<p>Left bank of wash, 2 ft. high, bears NW. and SE.</p> <p>Right bank of wash, 2 ft. high, bears NW. and SE.</p> <p>Old right bank of wash, 2 ft. high, bears NW. and SE.</p> <p>Board fence, bears E. and W.; enter corral.</p> <p>Proportional distance.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \\ \text{S } 25 \text{ S } 30 \\ \\ 1942 \end{array}$ </div> <p style="text-align: right;">from which</p> <p style="padding-left: 40px;">The NW. cor of Mc Nulty's house, bears S. $17^{\circ} 40'$ E., 350 lks. dist.</p> <p style="padding-left: 40px;">The NW. cor. of barn, bears S. $61\frac{1}{2}^{\circ}$ E., 106 lks. dist.</p> <p>41.30 Fence, bears E. and W.; leave corral; enter cultivated land.</p> <p>65.50 Slight depression, evidence of old road, bears E. and W.</p> <p>80.40 A 3 strand barbed wire fence, on S. side of county road, bears S. $85^{\circ} 57'$ E.</p> <p>80.80 The point for the cor. of secs. 19, 24, 25 and 30, at the intersection of the center lines of county roads from three directions, E., W., and N. Information obtained from the field book and plat on file in the office of the County Surveyor of Coconino County of a survey made by Frank Goodman in 1917 indicates that the original corner was found at this point.</p> <p>At point for cor.</p> <p>Set a lava stone, 16x8x3 ins., 12 ins. below the surface of the road, for cor. of secs. 19, 24, 25 and 30, mkd. X.</p> <p>At a point, S. 45° E., 0.60 chs. dist.,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for witness cor. of secs. 19, 24, 25 and 30, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{T23N} \\ \text{R2E R3E} \\ \text{WC} \\ \text{S } 24 \text{ S } 19 \\ \hline \text{S } 25 \text{ S } 30 \\ 1942 \end{array}$ </div> <p>At a point, N. 45° W., 0.60 chs. dist.,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. of secs. 19, 24, 25 and 30, with brass cap mkd.</p>
---	--

Dependent Resurvey of the West Bdy. of T. 23 N., R. 3 E.

BOOK 4350

Chains

T23N	
R2E	R3E
S 24	S 19

S 25	S 30
WC	
1942	

Land, gently rolling.
Soil, S. $\frac{1}{2}$ gravelly, 3rd rate; N. $\frac{1}{2}$ dark loam, 1st rate.
Timber, pine; undergrowth, none.

N. 0° 05' E., on a true line bet. secs. 19 and 24.

Over rolling land, along the center of county road, with cultivated land to the E. and W. for approx. 10 chs. along line, then pasture land; asc. a gradual S. slope.

35.00 Wide flat-topped ridge, bears NW. and SE.; desc. a gentle N. slope.

40.40 The point for $\frac{1}{4}$ sec. cor., determined at the center line of a county road bearing N. and S., from which a fence cor., bears East, 43 lks. dist., from which fences bear N., S. and E. and another fence cor., bears West, 43 lks. dist., from which fences bear N., S. and W.

At point for cor.

Set a lava stone, 12x12x4 ins., 12 ins. below the surface of the road for $\frac{1}{4}$ sec. cor., mkd. X.

At a point, S. 45° E., 0.61 chs. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	
WC	
S 24	
S 19	
1942	

At a point, N. 45° W., 0.61 chs. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	
S 24	
S 19	
WC	
1942	

Thence

N. 0° 09' W., on a true line bet. secs. 19 and 24.

Along center of county road with pasture land to the E. and W.; desc. a gradual N. slope.

14.50 Enter a wide draw.

17.95 Culvert; drain, course W.

18.50 Leave draw; enter cultivated land to the E. and W. of road; asc. a gradual SE. slope.

Dependent Resurvey of the West Bdy. of T. 23 N., R. 3 E.

Chains
40.07

The point for the cor. of secs. 13, 18, 19 and 24, determined at the intersection of the center lines of county roads from three directions, N., W. and S.

At point for cor.

Set a lava stone, 14x8x3 ins., 12 ins. below the surface of the road, for cor. of secs. 13, 18, 19 and 24, mkd. X.

At a point, S. 45° E., 0.65 chs. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. of secs. 13, 18, 19 and 24, with brass cap mkd.

T23N	
R2E	R3E
WC	
S 13	S 18

S 24	S 19
1942	

At a point, N. 45° W., 0.65 chs. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. of secs. 13, 18, 19 and 24, with brass cap mkd.

T23N	
R2E	R3E
S 13	S 18

S 24	S 19
WC	
1942	

Land, gently rolling.

Soil, on ridge, gravelly, 2nd and 3rd rates; remainder, dark loam, 1st rate.

Timber, on pasture land, scattered juniper; undergrowth, none.

N. 1° 00' E., on a true line bet. secs. 13 and 18.

Over gently rolling land; along the center of a county road, with cultivated land to the E. and pasture land with a scattered growth of juniper timber to the W.; asc. a gradual SE. slope.

40.58

The point for the $\frac{1}{4}$ sec. cor., determined at the center line of the county road from the S., from which a fence corner, bears East, 28 lks. dist., from which fences bear southerly and easterly.

At point for cor.

Set a lava stone, 12x7x2 ins., 12 ins. below the surface of the road, for $\frac{1}{4}$ sec. cor., mkd. X., from which

A juniper, 6 ins. diam., bears N. 67 $\frac{1}{4}$ ° E., 274 lks. dist., mkd. $\frac{1}{4}$ S 18 B T.

A juniper, 6 ins. diam., bears S. 59 $\frac{3}{4}$ ° W., 119 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.

At a point, S. 45° E., 0.40 chs. dist.,

Dependent Resurvey of the West Bdy. of T. 23 N., R. 3 E.

BOOK 4850

Chains Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \text{WC} \\ \frac{1}{4} \\ \text{S } 13 \mid \text{S } 18 \\ \hline 1942 \end{array}$$

At a point, N. 45° W., 0.40 chs. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 13 \mid \text{S } 18 \\ \text{WC} \\ \hline 1942 \end{array}$$

The $\frac{1}{4}$ sec. cor. is located at the W. end of a cattle gaurd. Thence,

N. 0° 18' E., on a true line bet. secs. 13 and 18.

Leave road, which bears NE.; asc. a gentle S. slope.

12.00 Low spur, slopes SW.; desc. gentle NW. slope.

15.30 Draw, drains SW.

29.80 Drain, course S. 30° W.; asc. 64 ft. over a SE. slope.

39.72 Proportional distance.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 7, 12, 13 and 18, with brass cap mkd.

$$\begin{array}{c} \text{T23N} \\ \text{R2E} \quad \text{R3E} \\ \text{S } 12 \mid \text{S } 7 \\ \hline \text{S } 13 \mid \text{S } 18 \\ \hline 1942 \end{array}$$

from which

A juniper, 16 ins. diam., bears N. 53 $\frac{1}{4}$ ° E., 40 lks. dist., mkd. T 23 N R 3 E S 7 B T.

A pinyon, 8 ins. diam., bears S. 39 $\frac{1}{2}$ ° E., 53 lks. dist., mkd. T 23 N R 3 E S 18 B T.

A pinyon, 14 ins. diam., bears S. 51 $\frac{1}{4}$ ° W., 87 lks. dist., mkd. T 23 N R 2 E S 13 B T.

A pinyon, 12 ins. diam., bears N. 46 $\frac{3}{4}$ ° W., 49 lks. dist., mkd. T 23 N R 2 E S 12 B T.

Land, rolling.

Soil, dark loam, gravelly, 2nd rate.

Timber, juniper and pinyon; undergrowth, none.

N. 0° 18' E., on a true line bet. secs. 7 and 12.

Over rolling land, thru dense timber; asc. 249 ft. over a rolling SW. slope.


2.73 A 3 strand barbed wire fence, bears W., and E. approx. 1.00 ch. dist. to a fence cor., from which fences bear

Dependent Resurvey of the West Bdy. of T. 23 N., R. 3 E.

Chains	
	northerly, southerly and west.
24.10	Spur, slopes W.
37.65	Spur, slopes W.
39.72	The point for the $\frac{1}{4}$ sec. cor., determined from the original bearing tree.
	At point for cor.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \\ S\ 12\ \ S\ 7 \\ \\ 1942 \end{array}$
	from which
	The old bearing tree:
	A pinyon, 12 ins. diam., bears N. 20° W., 28 lks. dist., mkd. $\frac{1}{4}$ S B T. I alter the markings on this tree to read $\frac{1}{4}$ S 12 B T.
	New bearing tree:
	A pinyon, 12 ins. diam., bears N. 54 $\frac{1}{2}$ ° E., 62 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.
	Thence,
	N. 3° 18' E., on a true line, bet. secs. 7 and 12,
	Over mountainous land, thru dense timber; desc. 10 ft. over a NW. slope.
1.05	Wash, 20 lks. wide, 3 ft. deep, course SW.; asc. 88 ft. over a SE. slope.
7.30	Spur, slopes SW.; desc. 24 ft. over a NW. slope.
8.75	Ravine, course S. 20° W.; asc. 25 ft. over a SW. slope.
14.30	Main spur from a mountain to the E., slopes W.; desc. 65 ft. over a NW. slope.
22.10	Ravine, course W.; asc. 13 ft. over a SW. slope.
25.70	Spur, slopes W.; desc. 49 ft. over a NW. slope.
34.85	Drain, course W.; asc. 16 ft. over a SW. slope.
37.65	Spur, slopes W.; desc. 13 ft. over a NW. slope.
39.04	The point for the cor. of secs. 1, 6, 7 and 12, determined from original bearing trees.
	At point for cor.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

Dependent Resurvey of the West Bay. of T. 23 N., R. 3 E.

Chains



from which

Old bearing trees:

A pinyon, 6 ins. diam., bears N. 60° E., 13 lks. dist., mkd. T 23 N R 3 E S 6 B T.

A pinyon (dead), 6 ins. diam., bears S. 6° E., 18 lks. dist., marks indiscernible.

New bearing trees:

A pinyon, 8 ins. diam., bears S. 47½° E., 55 lks. dist., mkd. T 23 N R 3 E S 7 B T.

A pinyon, 8 ins. diam., bears S. 50½° W., 55 lks. dist., mkd. T 23 N R 2 E S 12 B T.

A pinyon, 12 ins. diam., bears N. 51° W., 31 lks. dist., mkd. T 23 N R 2 E S 1 B T.

Land, rolling and mountainous. Soil, dark loam, rocky and gravelly, 3rd rate. Timber, pinyon and juniper; undergrowth, cliff rose.

N. 3° 56' E., on a true line bet. secs. 1 and 6.

Over mountainous land, through dense timber; desc. 14 ft. over a NW. slope.

0.30 Drain, course W.

8.10 Spur, slopes W.; desc. 43 ft. over a N. slope.

10.85 Drain, course W.; asc. 21 ft. over a S. slope.

14.70 Spur, slopes NW.; desc. 75 ft. over a NW. slope.


31.20 Wash, 50 lks. wide, 2 ft. deep, course W.; asc. 106 ft. over a S. slope.

37.10 Wire fence, bears N. 5° W. and S. 5° E.

38.90 The ¼ sec. cor., a lava stone, 18x14x6 ins. firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. ¼ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for ¼ sec. cor., with brass cap mkd.



from which

Dependent Resurvey of the West Bdy. of T. 23 N., R. 3 E.

Chains

A pinyon, 8 ins. diam., bears S. 79° E., 17 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.

A pinyon, 14 ins. diam., bears S. 40 $\frac{1}{2}$ ° W., 54 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.

Thence,

N. 2° 43' E., on a true line bet. secs. 1 and 6.

1.00 Spur, slopes W.; desc. 30 ft. over a NW. slope.

7.95 Head of a ravine, course SW.; asc. 138 ft. over a SW. slope.

17.10 High spur, slopes W.; desc. 274 ft. over a N. slope.

38.82 The cor. of Ts. 23 and 24 N., Rs. 2 and 3 E., an iron post, 3 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the field notes of the resurvey of the N. bdy. of T. 23 N., R. 2 E.

Land, mountainous.

Soil, dark loam, gravelly, 3rd rate.

Timber, pinyon and juniper; undergrowth, cliff rose.

 Dependent Resurvey of the North Bdy. of T. 23 N., R. 3 E.

Reestablishment of the survey executed by W. R. Fitzgerald, Deputy Surveyor, in 1883.

From the cor. of Ts. 23 and 24 N., Rs. 3 and 4 E.

N. 89° 36' W., on a true line bet. secs. 1 and 36.

Over rolling land, through scattered timber; desc. a gradual NW. slope.

20.25 Draw, drains NW.; asc. a gradual NE. slope.

40.27 The $\frac{1}{4}$ sec. cor., a lava stone, 16x12x4 ins., firmly set in the ground, mkd. $\frac{1}{4}$ on W. face, with a small mound of stone S. of cor.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 36

$\frac{1}{4}$

S 1

1942

from which

A pine, 8 ins. diam., bears N. 56° E., 155 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.

A pine, 12 ins. diam., bears S. 44 $\frac{1}{2}$ ° E., 153 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.

Thence,

N. 89° 32' W., on true line bet. secs. 1 and 36.

Ascend a gradual NE. slope.

Dependent Resurvey of the North Bdy. of T. 23 N., R. 3 E.

BOOK 1000

Chains

- 6.70 Spur, slopes NW.; desc. over a NW. slope.
- 20.00 Wash, 10 lks. wide, 1 ft. deep, course SW.
- 40.19 The cor. of secs. 1, 2, 35 and 36, a sandstone, 24x18x6 ins., firmly set in the ground, mkd. 1 groove on E. and 5 grooves on W. faces.
- At point for cor.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, for cor. of secs. 1, 2, 35 and 36, with brass cap mkd.

T24N	R3E
S 35	S 36
S 2	S 1
T23N	
1942	

from which

A juniper, 24 ins. diam., bears N. 16° E., 112 lks. dist., mkd. T 24 N R 3 E S 36 B T.

A juniper, 30 ins. diam., bears S. 77° E., 74 lks. dist., mkd. T 23 N R 3 E S 1 B T.

A pinyon, 6 ins. diam., bears S. 25½° W., 29 lks. dist., mkd. T 23 N R 3 E S 2 B T.

A pinyon, 12 ins. diam., bears N. 68° W., 123 lks. dist., mkd. T 24 N R 3 E S 35 B T.

Land, rolling.

Soil, dark loam, rocky, 3rd rate.

Timber, pine, juniper, pinyon; undergrowth, 2nd growth pine.

N. 89° 49' W., on a true line, bet. secs. 2 and 35.

Over rolling land, thru scattered timber; desc. over a gentle W. slope.

- 22.30 Dim road, bears NW. and SE.
- 22.90 Wash, 15 lks. wide, 1 ft. deep, course NW.; asc. over an E. slope.
- 34.50 Road, bears NE. and SW. to Boulin tank.
- 40.11 The ¼ sec. cor., a lava stone, 16x12x8 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. ¼ on N. face.
- At point for cor.
- Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with the original stone buried alongside and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.

S 35
¼
S 2
1942

from which

Dependent Resurvey of the North Bdy. of T. 23 N., R. 3 E.

Chains

A pine, 18 ins. in diam., bears S. $34\frac{3}{4}^{\circ}$ E., 385 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.

Thence,

N. $89^{\circ} 45'$ W., on a true line bet. secs. 2 and 35.

Ascend a gradual E. slope.

10.00 Ridge, bears N. and SE.; desc. a gradual W. slope.

22.80 Wash, 20 lks. wide, 1 ft. deep, course NW.; asc. over an E. slope.

28.80 Spur, slopes N.; desc. over a W. slope.

34.90 Road, bears NW. and SE. to Boulin tank.

40.20 The cor. of secs. 2, 3, 34 and 35, a lava stone, 18x12x12 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. 2 grooves on E. and 4 grooves on W. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground, with the original stone buried alongside, and in a mound of stone to top, for cor. of secs. 2, 3, 34 and 35, with brass cap mkd.

T24N	R3E	·
S 34		S 35
S 3		S 2
T23N		
1942		

ffrom which

A pine, 12 ins. diam., bears N. 24° E., 277 lks. dist., mkd. T 24 N R 3 E S 35 B T.

A pine, 12 ins. diam., bears S. $42\frac{1}{4}^{\circ}$ E., 210 lks. dist., mkd. T 23 N R 3 E S 2 B T.

A pine, 20 ins. diam., bears S. $46\frac{3}{4}^{\circ}$ W., 166 lks. dist., mkd. T 23 N R 3 E S 3 B T.

A pine, 18 ins. diam., bears N. $53\frac{1}{2}^{\circ}$ W., 140 lks. dist., mkd. T 24 N R 3 E S 34 B T.

Land, rolling.

Soil, dark loam, gravelly, 3rd rate.

Timber, pinyon, pine and juniper; undergrowth, 2nd growth pine.

N. $89^{\circ} 49'$ W., on true line bet. secs. 3 and 34.

Over rolling land, thru scattered timber; asc. over a gentle NE. slope.

40.08 The $\frac{1}{4}$ sec. cor., a lava stone, 16x12x5 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent Resurvey of the North Bdy. of T. 23 N., R. 3 E.

BOOK 4250

Chains

$$\frac{1}{4} \frac{S \ 34}{S \ 3}$$
 1942

from which

A juniper, 5 ins. diam., bears N. $33\frac{1}{4}^{\circ}$ W., 145 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.

A juniper, 5 ins. diam., bears S. 9° E., 133 lks. dist., mkd. $\frac{1}{4}$ S 3 B T.

Thence,

N. $89^{\circ} 24'$ W., on a true line bet. secs. 3 and 34.

7.00 Low spur, slopes NE.; desc. over a gradual NW. slope.

18.60 Road, bears NW. and SE.

40.11 The cor. of secs. 3, 4, 33 and 34, a lava stone, 16x12x8 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. 3 grooves on E. and W. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, for cor. of secs. 3, 4, 33 and 34, with brass cap mkd.

$$\begin{array}{c} T24N \ R \ 3 \ E \\ S \ 33 \ | \ S \ 34 \\ \hline S \ 4 \ | \ S \ 3 \\ T23N \\ 1942 \end{array}$$

from which

A pinyon, 8 ins. diam., bears N. 84° E., 190 lks. dist., mkd. T 24 N R 3 E S 34 B T.

A pinyon, 10 ins. diam., bears S. $27\frac{1}{2}^{\circ}$ E., 39 lks. dist., mkd. T 23 N R 3 E S 3 B T.

A juniper, 5 ins. diam., bears S. 79° W., 116 lks. dist., mkd. T 23 N R 3 E S 4 B T.

A juniper, 8 ins. diam., bears N. $72\frac{1}{2}^{\circ}$ W., 184 lks. dist., mkd. T 24 N R 3 E S 33 B T.

Land, rolling.

Soil, rocky and gravelly, 3rd rate.

Timber, pinyon, juniper and pine; undergrowth, 2nd growth pine.

N. $89^{\circ} 45'$ W., on a true line bet. secs. 4 and 33.

Over rolling land, thru scattered timber.

33.00 Ravine, course WW.; asc. over a gentle E. slope.

40.06 The $\frac{1}{4}$ sec. cor., a lava stone, 12x10x6 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$

Dependent Resurvey of the North Bdy. of T. 23 N., R. 3 E.

Chains

sec. cor., with brass cap mkd.

$$\begin{array}{r} S\ 33 \\ \frac{1}{4} \text{---} \\ S\ 4 \\ 1942 \end{array}$$

from which

A pinyon, 16 ins. diam., bears N. $48\frac{1}{4}^{\circ}$ E., 37 lks. dist., mkd. $\frac{1}{4}$ S 33 B T.

A pinyon, 12 ins. diam., bears S. 23° E., 134 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.

Thence,

N. $88^{\circ} 50'$ W., on a true line bet. secs. 4 and 33.

Ascend a gradual E. slope.

12.40 Spur, slopes N.; desc. over a gradual W. slope.

29.00 Center of a draw, 5 chs. wide, drains N. 20° E.; asc. 44 ft. over the E. slope of a hill.

39.64 Proportional distance.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 4, 5, 32 and 33, with brass cap mkd.

$$\begin{array}{r} T24N\ R3E \\ S\ 32\ | \ S\ 33 \\ \text{---} \\ S\ 5\ | \ S\ 4 \\ T23N \\ 1942 \end{array}$$

from which

A pinyon, 10 ins. diam., bears N. $4\frac{1}{2}^{\circ}$ E., 13 lks. dist., mkd. T 24 N R 3 E S 33 B T.

A pinyon 20 ins. diam., bears S. $56\frac{1}{4}^{\circ}$ E., 61 lks. dist., mkd. T 23 N R 3 E S 4 B T.

A pinyon, 8 ins. diam., bears S. $30\frac{3}{4}^{\circ}$ W., 106 lks. dist., mkd. T 23 N R 3 E S 5 B T.

A juniper, 6 ins. diam., bears N. $42\frac{1}{4}^{\circ}$ W., 217 lks. dist., mkd. T 24 N R 3 E S 32 B T.

Land, rolling.

Soil, dark loam, gravelly, 3rd rate.

Timber, pinyon, juniper and pine; undergrowth, 2nd growth pine.

N. $88^{\circ} 50'$ W., on a true line bet. secs. 5 and 32.

Over mountainous land, thru dense timber; asc. 100 ft. over an E. slope.

9.00 Top of hill, bears N. and S.

30.35 Wash, 30 lks. wide, 2 ft. deep, course N.; asc. 24 ft. over an E. slope.

32.15 Road, bears N. and S.

Dependent Resurvey of the North Bay. of T. 23 N., R. 3 E.

Chains
39.64

The $\frac{1}{4}$ sec. cor., a lava stone, 16x8x6 ins. firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 32

$\frac{1}{4}$
S 5
1942

from which

A pinyon, 10 ins. diam., bears N. 20 $\frac{1}{2}$ ° E., 56 lks. dist., mkd. $\frac{1}{4}$ S 32 B T.

A pinyon, 16 ins. diam., bears S. 38 $\frac{1}{2}$ ° W., 19 lks. dist., mkd. $\frac{1}{4}$ S 5 B T.

Thence,

S. 88° 43' W., on a true line, bet. secs. 5 and 32.

Ascend 116 ft. over an E. slope.

5.70 Top of a bluff, 25 ft. high, bears N. and S., thence over top of a spur, slopes N.

23.80 Leave top of spur; desc. 119 ft. over a W. slope.

33.55 Wash, 15 lks. wide, 3 ft. deep, course N. 20° E.; asc. 24 ft. over an E. slope.

38.11 Proportional distance.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

T24N R3E
S 31 S 32

S 6 S 5
T23N
1942

from which

A pinyon, 8 ins. diam., bears N. 38 $\frac{3}{4}$ ° E., 105 lks. dist., mkd. T 24 N R 3 E S 32 B T.

A juniper, 6 ins. diam., bears S. 39 $\frac{1}{2}$ ° E., 46 lks. dist., mkd. T 23 N R 3 E S 5 B T.

A pinyon, 12 ins. diam., bears S. 49° W., 56 lks. dist., mkd. T 23 N R 3 E S 6 B T.

A pinyon, 8 ins. diam., bears N. 63 $\frac{1}{2}$ ° W., 242 lks. dist., mkd. T 24 N R 3 E S 31 B T.

Land, mountainous.

Soil, rocky and gravelly, 3rd rate.

Timber, pinyon, juniper and pine; undergrowth, 2nd growth pine.

Dependent Resurvey of the North Bdy. of T. 23 N., R. 3 E.

Chains	
	S. 88° 43' W., on a true line bet. secs. 6 and 31. Over mountainous land, through scattered timber.
0.50	Spur, slopes N. 40° E.; desc. 7 ft. over a W. slope.
2.50	Drain, course N.; asc. 29 ft. over an E. slope.
10.50	Spur, slopes NE.; desc. 15 ft. over a W. slope.
22.30	Drain, course N. 40° E.; asc. 23 ft. over a SE. slope.
28.60	Spur, slopes NW.; desc. 15 ft. over a SW. slope.
33.75	Drain, course NW.; asc. over a gentle E. slope.
38.11	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} S\ 31 \\ \hline \frac{1}{4} \\ S\ 6 \\ 1942 \end{array}$ from which A pinyon, 10 ins. diam., bears N. 54 $\frac{1}{2}$ ° E., 37 lks. dist., mkd. $\frac{1}{4}$ S 31 B T. A pinyon, 12 ins. diam., bears S. 9° E., 17 lks. dist., mkd. $\frac{1}{4}$ S 6 B T. Cor. is located on top of a low spur, slopes NW. Descend a gentle W. slope.
46.40	Drain, course N. 30° W.; asc. 23 ft. over an E. slope.
74.31	The cor. of Ts. 23 and 24 N., Rs. 2 and 3 E. Land, mountainous. Soil, dark loam, rocky and gravelly, 3rd rate. Timber, pinyon, juniper and pine; undergrowth, none.
----- Dependent Resurvey of the Subdivisional Lines of T. 23 N., R. 3 E. -----	
Reestablishment of the survey executed by W. R. Fitzgerald, Deputy Surveyor; in 1883. -----	
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the resurvey of the N. bdy. of T. 22 N., R. 3 E. N. 0° 05' W., on a true line bet. secs. 35 and 36. Over mountainous land, through dense timber and undergrowth, along a barbed wire fence which runs irregularly N.; asc. a SW. slope.
2.00	Spur, slopes S. 60° W.; desc. 22 ft. over a NW. slope.
4.40	Draw, drains S. 60° W.; asc. 26 ft. over a SW. slope.
8.30	Spur, slopes S. 60° W.; desc. 34 ft. over a NW. slope.
17.40	Fire road, bears E., and W. to Frenchy Spring road; asc. 37 ft. over a SW. slope.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains	
19.00	Draw, drains W.
33.50	Spur, slopes SW.
35.50	Ravine, course SW.
37.80	Spur, slopes SW.
37.85	Fire road, bears NE. and SW.
39.95	The $\frac{1}{4}$ sec. cor., a sandstone, 18x12x4 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face.
	At point for cor.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \\ S\ 35\ \ S\ 36 \\ \\ 1942 \end{array}$
	from which
	The old bearing tree:
	A white oak, 18 ins. diam., bears N. $57\frac{1}{2}^{\circ}$ E., 28 lks. dist.; blaze decayed, mks. indiscernible.
	New bearing trees:
	A pine, 5 ins. diam., bears N. $89\frac{1}{4}^{\circ}$ E., 34 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.
	A pine, 12 ins. diam., bears N. $79\frac{1}{4}^{\circ}$ W., 15 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.
	Thence,
	N. 0° 41' W., on a true line bet. secs. 35 and 36.
0.50	Spur, slopes NW.
6.90	Wire fence, bears W., and E. 15 lks. to a fence cor., from which fences bear W. and S.
10.00	Spur, slopes W.
27.40	Draw, drains SW.; asc. 57 ft. over a S. slope.
34.10	Fire road, bears E. and W.; top of a spur, slopes W.
39.73	The point for the cor. of secs. 25, 26, 35 and 36, determined from the original bearing trees.
	At point for cor.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.
	$\begin{array}{c} T23N\ R3E \\ S\ 26\ \ S\ 25 \\ \hline S\ 35\ \ S\ 36 \\ \\ 1942 \end{array}$
	from which

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

The old bearing trees:

A pine, 36 ins. diam., bears N. 29° E., 42 lks. dist., mkd. R3E S 25 B T. Other marks not uncovered.

An oak, 12 ins. diam., bears N. 89 $\frac{3}{4}$ ° W., 45 lks. dist.; blaze badly decayed, mks. indiscernible.

New bearing trees:

A pine, 8 ins. diam., bears S. 59 $\frac{1}{4}$ ° E., 39 lks. dist., mkd. T 23 N R 3 E S 36 B T.

A pine, 10 ins. diam., bears S. 56 $\frac{3}{4}$ ° W., 18 lks. dist., mkd. T 23 N R 3 E S 35 B T.

A pine, 16 ins. diam., bears N. 13 $\frac{3}{4}$ ° W., 64 lks. dist., mkd. T 23 N R 3 E S 26 B T.

Land, mountainous.

Soil, dark loam, rocky and gravelly, 3rd and 4th rates. Timber, pine, oak, juniper and pinyon; undergrowth, 2nd growth pine.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.

S. 85° 30' W., on a true line bet. secs. 25 and 36.

Over mountainous land, thru dense timber and undergrowth; desc. 89 ft. over a SW. slope.

- 3.25 Ravine, course SW.; asc. 10 ft. over a S. slope.
6.15 Spur, slopes SW.; desc. 403 ft. over a broken SW. slope.
21.90 Spur, slopes S. 80° W.; desc. along N. slope of same.
34.45 Top of same spur; desc. along top of same.
40.50 Leave top of spur, slopes N. 60° W.; desc. over a SW. slope.
41.215 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 25}{S 36} \\ 1942$$

from which

A pine, 6 ins. diam., bears N. 59° E., 22 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.


A pine, 10 ins. diam., bears S. 17° W., 24 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.

Descend 216 ft. over a SW. slope.

- 67.20 Ravine, course N. 70° W.; asc. 8 ft. over a NE. slope.
68.90 Short spur, slopes NW.
71.70 Spur, slopes N. 30° W.; desc. 104 ft. over a SW. slope.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains 82.43	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, mountainous. Soil, dark loam, gravelly, 3rd rate. Timber, pine, juniper and pinyon; undergrowth, 2nd growth pine.</p> <p>-----</p> <p>N. 0° 08' W., on a true line bet. secs. 25 and 26. Over mountainous land, thru dense timber and undergrowth.</p> <p>0.30 Drain, course W; asc. 27 ft. over a S. slope.</p> <p>2.60 Spur, slopes W.; desc. 29 ft. over a NW. slope.</p> <p>10.90 Wash, 5 lks. wide, 1 ft. deep, course W.; asc. 43 ft. over a S. slope.</p> <p>14.50 Spur, slopes W.; desc. 27 ft. over a N. slope.</p> <p>22.10 Ravine, course SW.; asc. 40 ft. over a SW. slope.</p> <p>30.00 Spur, slopes W.; desc. 52 ft. over a N. slope.</p> <p>35.20 Wash, 10 lks. wide, 10 ins. deep, course W.; asc. 70 ft. over a S. slope.</p> <p>39.40 The point for $\frac{1}{4}$ sec. cor., determined from the original bearing tree.</p> <p>At point for cor.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$  1942 </div> <p style="text-align: right;">from which</p> <p>The old bearing tree:</p> <p style="padding-left: 40px;">The original position of a pine (dead, lying on the ground), 24 ins. diam., bears S. 70° W., 34 lks. dist., mks. visible but indiscernible.</p> <p>New bearing trees:</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears S. 42$\frac{1}{4}$° E., 144 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.</p> <p style="padding-left: 40px;">A pine, 24 ins. diam., bears S. 56$\frac{3}{4}$° W., 70 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.</p> <p>Thence,</p> <p>N. 0° 38' W., on a true line bet. secs. 25 and 26. Ascend 204 ft. over a S. slope.</p> <p>15.00 Top of hill, bears NE. and SW.; desc. 264 ft. over a steep NW. slope.</p> <p>26.00 Wash, 10 lks. wide, 1 ft. deep, course W.; asc. 29 ft. over a SW. slope.</p>
-----------------	---

BOOK 4350

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains											
29.80	Spur, slopes W.; continue over a broken W. slope.										
34.00	Ravine, course W.; asc. 102 ft. over a steep S. slope.										
41.40	Spur, slopes W.; desc. 13 ft. over a NW. slope.										
41.45	Fence, bears W., and E. about 3 chs. to end of fence.										
43.08	The point for the cor. of secs. 23, 24, 25 and 26, determined from the original bearing trees.										
	At point for cor.										
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T23N</td> <td>R3E</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td colspan="2" style="text-align: center;">1942</td> </tr> </table>	T23N	R3E	S 23	S 24	-----		S 26	S 25	1942	
T23N	R3E										
S 23	S 24										

S 26	S 25										
1942											
	from which										
	The old bearing trees:										
	A pine, 24 ins. diam., bears N. 42° E., 48 lks. dist., marks not uncovered.										
	A pine, 36 ins. diam., bears S. 81° E., 52 lks. dist., marks not uncovered.										
	A pine (dead snag), 24 ins. diam., bears N. 16° W., 45 lks. dist., mkd. T23N R3E S 23 B T.										
	New bearing trees:										
	A pine, 8 ins. diam., bears S. 67½° E., 46 lks. dist., mkd. T 23 N R 3 E S 25 B T.										
	A pine, 8 ins. diam., bears N. 51½° W., 87 lks. dist., mkd. T 23 N R 3 E S 23 B T.										
	Land, mountainous.										
	Soil, rocky and gravelly, 3rd and 4th rates.										
	Timber, pine, oak, pinyon and juniper; undergrowth, 2nd growth pine.										

	From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp.										
	S. 89° 45' W., on a true line bet. secs. 24 and 25.										
	Over mountainous land, thru dense timber and undergrowth; desc. 50 ft. over a W. slope.										
2.60	Ravine, course N. 80° W.; asc. 11 ft. over a NE. slope.										
3.45	Spur, slopes N. 80° W.; desc. 61 ft. over a SW. slope.										
10.00	Ravine, course N. 80° W.; asc. 24 ft. over a NE. slope.										
12.05	Spur, slopes NW.; desc. 25 ft. over a SW. slope.										
14.35	Ravine, course N. 50° W.; asc. 29 ft. over a NE. slope.										
15.80	Spur, slopes N. 50° W.; desc. 37 ft. over a SW. slope.										

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains	
19.25	Ravine, course N. 60° W.; asc.; 9 ft. over a NE. slope.
20.75	Spur, slopes N. 60° W.; desc. 143 ft. over a SW. slope.
32.80	Ravine, course N. 50° W.; asc. 29 ft. over a NE. slope.
35.05	Spur, slopes N. 50° W.; desc. 74 ft. over a SW. slope.
40.865	Proportional distance.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} S\ 24 \\ \frac{1}{4} \\ \hline S\ 25 \end{array}$
	1942 from which
	A pine, 12 ins. diam., bears N. 20° E., 29 lks. dist., mkd. $\frac{1}{4}$ S 24 B T.
	A pine, 12 ins. diam., bears S. 60° E., 35 lks. dist. mkd. $\frac{1}{4}$ S 25 B T.
	Descend 40 ft. over a SW. slope.
43.25	Ravine, course N. 80° W.; asc. 40 ft. over a NE. slope.
49.45	Spur, slopes NW.; desc. over a SW. slope.
54.45	Ravine, course N. 80° W.; desc. along a N. slope.
57.30	Spur, slopes W.; desc. 188 ft. along a top of a spur.
61.95	Leave top of spur, slopes SW.; desc. over a N. slope.
64.25	Recross spur, slopes NW.; desc. over a SW. slope.
67.80	Recross spur, slopes SW.; desc. over a NW. slope.
73.00	Head of a ravine, course NW.; asc. 22 ft. over a NE. slope.
78.20	Top of ascent, desc. over a N. slope of a spur.
81.73	The cor. of secs. 23, 24, 25 and 26.
	Land, mountainous.
	Soil, rocky and gravelly, 3rd and 4th rates.
	Timber, pine, oak, pinyon and juniper; undergrowth, 2nd growth pine.

	N. 0° 04' E., on a true line bet. secs. 23 and 24.
	Over mountainous land, through dense timber and undergrowth; desc. 85 ft. over a NW. slope.
7.00	Drain, course W.; asc. over a SW. slope.
10.30	Drain, course W.; asc. over a SW. slope.
12.60	Spur, slopes NW.; desc. 38 ft. over an E. slope.
17.30	Draw, drains NW.; asc. over a SW. slope.
19.50	Spur, slopes NW.; desc. 36 ft. over a N. slope.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.


Chains

21.50 Draw, drains NW.; asc. 38 ft. over a SW. slope.

32.40 Road, bears E. and W.

39.70 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A pine, 10 ins. diam., bears N. 30° E., 14 lks. dist., mkd. $\frac{1}{4}$ S 24 B T.

A pine, 10 ins. diam., bears S. 66° W., 11 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.

Over a rolling NW. slope.

40.40 Road, bears E. and W.

47.00 Wash, 15 lks. wide, 2 ft. deep, course W.

68.30 Wash, 20 lks. wide, 3 ft. deep, course W.


76.50 Spur, slopes NW.; desc. over a NE. slope.

79.00 Drain, course NW.; asc. over a SW. slope.

79.40 The point for the cor. of secs. 13, 14, 23 and 24, determined from the original bearing trees.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.



from which

Old bearing trees:

A pine, 30 ins. diam., bears S. 24° E., 98 lks. dist., mkd. T 23 N R 3 E S 24 B T.

The original position of a pine (now dead, lying on the ground), 24 ins. diam., bears S. 20° W., 78 lks. dist., marks indiscernible. No evidence of NE. bearing tree.

New bearing trees:

A pine, 10 ins. diam., bears N. 38° E., 14 lks. dist., mkd. T 23 N R 3 E S 13 B T.

A pine, 12 ins. diam., bears S. 65° W., 44 lks. dist., mkd. T 23 N R 3 E S 23 B T.

A pine, 16 ins. diam., bears N. 41½° W., 15 lks. dist., mkd. T 23 N R 3 E S 14 B T.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains	Land, S. $\frac{1}{2}$, mountainous; N. $\frac{1}{2}$, rolling. Soil, rocky and gravelly, 3rd and 4th rates. Timber, pine, juniper and oak; undergrowth, 2nd growth pine.
	----- From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp. S. 89° 39' W., on a true line bet. secs. 13 and 24... Over rolling land, through dense timber and undergrowth; asc. 14 ft, over a NE. slope.
3.30	Spur, slopes N. 70° W.; desc. 47 ft. over a W. slope.
8.00	Ravine, course N. 60° W.; asc. 12 ft. over a NE. slope.
10.30	Spur, slopes N. 50° W.; desc. 21 ft. over a W. slope.
11.45	Ravine, course N. 50° W.; asc. 13 ft. over a NE. slope.
13.05	Spur, slopes N. 60° W.; desc. 63 ft. over a broken NW. slope.
22.80	Slope changes, descend over a W. slope.
24.60	Ravine, course N. 70° W.; asc. 8 ft. over a NE. slope.
27.70	Spur, slopes N. 70° W.; desc. 28 ft. over a SW. slope.
29.85	Ravine, course N. 60° W.; asc. 12 ft. over a NE. slope.
31.85	Spur, slopes N. 60° W.; desc. 25 ft. over a NW. slope.
40.53	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> S 13 <hr style="width: 10%; margin: 0 auto;"/> S 24 1942 </div> <div style="text-align: right;">from which</div> A pine, 12 ins. diam., bears N. 29 $\frac{1}{2}$ ° E., 54 lks. dist., mkd. $\frac{1}{4}$ S 13 B T. A pine, 12 ins. diam., bears S. 50 $\frac{1}{2}$ ° E., 44 lks. dist., mkd. $\frac{1}{4}$ S 24 B T.
	Descend 1 ft. over a NW. slope.
40.65	Ravine, course N. 20° W.; asc. 14 ft. over a NE. slope.
43.05	Spur, slopes N. 60° W.; desc. 64 ft. over a SW. slope.
66.90	Ravine, course N.; asc. 13 ft. over an E. slope.
71.10	Spur, slopes N.; desc. over a SW. slope.
77.20	Ravine, course N.; asc. 7 ft. over an E. slope.
78.60	Spur, slopes N.; desc. 23 ft. over a SW. slope.
81.06	The cor. of secs. 13, 14, 23 and 24.

Dependent Resurvey of the Subdivisional Lines of T. 23 N., R. 3 E.

Chains

Land, rolling.
Soil, dark loam, gravelly, 3rd rate.
Timber, pine, oak and juniper; undergrowth, 2nd growth pine.

N. 0° 17' W., on a true line bet. secs. 13 and 14.

Over rolling land, through dense timber and undergrowth.

15.60 Graded road, bears W. to Red Lake Valley and E. to Spring Valley.


16.40 Drain, course W.; an earth reservoir, bears W. approx. 2 chs. dist.

18.40 Dim road, bears NW. and E.

40.41 The point for the 1/4 sec. cor., determined from the original bearing tree.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



from which

The old bearing tree:

A juniper, 40 ins. diam., bears N. 42° E., 114 lks. dist., mkd. 1/4 S B T. I alter the markings on this tree to read 1/4 S 13 B T.

New bearing tree:

A pine, 12 ins. diam., bears N. 18 1/2° W., 88 lks. dist., mkd. 1/4 S 14 B T.

Thence.

N. 0° 50' E., on a true line bet. secs. 13 and 14.


27.30 Drain, course W.

39.00 Drain, course W.

40.01 The cor. of secs. 11, 12, 13 and 14, a lava stone, 12x8x6 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 4 grooves on S. and 1 groove on E. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, for the cor. of secs. 11, 12, 13 and 14, with brass cap mkd.



from which

A juniper, 3 ins. diam., bears N. 24° E., 153 lks. dist., mkd. B T.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 2850

Chains

A pine, 10 ins. diam., bears S. $42\frac{3}{4}^{\circ}$ E., 78 lks.
dist., mkd. T 23 E R 3 E S 13 B T.

A pine, 14 ins. diam., bears S. $49\frac{1}{2}^{\circ}$ W., 132 lks.
dist., mkd. T 23 N R 3 E S 14 B T.

A pine, 2 ins. diam., bears N. $66\frac{1}{2}^{\circ}$ W., 275 lks.
dist., mkd. B T.

Land, rolling,
Soil, dark loam, rocky and gravelly, 3rd and 4th rates.
Timber, Pine and juniper; undergrowth, none.

From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of
the Tp.

S. $89^{\circ} 22'$ W., on a true line bet. secs. 12 and 13.

Over rolling land, thru dense timber and scattered under-
growth.

Descend 29 ft. over a W. slope.

4.25 Center of a grassy draw, 3 chs. wide, drains S.; asc. 15
ft. over a SE. slope.

10.30 Spur, slopes S. 30° W.; desc. 72 ft. over a W. slope.

31.70 Drain, course S. 30° W.; asc. over a SE. slope.

40.31 The $\frac{1}{4}$ sec. cor., a lava stone, 12x6x4 ins., firmly set in
a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N.
face,

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with the original stone buried alongside, for $\frac{1}{4}$
sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 12

 S 13
 1942

from which

The old bearing tree:

The original position of a pine (dead, lying on the
ground), 36 ins. diam., bears N. $42\frac{3}{4}^{\circ}$ E., 100 lks.
dist., mkd. B T.

New bearing trees:

A pine, 12 ins. diam., bears N. 37° W., 62 lks.
dist., mkd. $\frac{1}{4}$ S 12 B T.

A pine, 8 ins. diam., bears S. $29\frac{1}{4}^{\circ}$ W., 26 lks.
dist., mkd. $\frac{1}{4}$ S 13 B T.

Thence,

S. $89^{\circ} 53'$ W., on a true line, bet. secs. 12 and 13.

Ascend 31 ft. over an E. slope.

4.40 Spur, slopes S.; desc. 87 ft. over a W. slope.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains	
13.50	Ravine, course N. 60° W.; asc. over a NE. slope.
18.30	Spur, slopes NW.; desc. over a SW. slope.
39.70	Ditch, 20 lks. wide, 2 ft. deep, course NW. to Boulin Tank.
40.28	The cor. of secs. 11, 12, 13 and 14. Land, rolling. Soil, rocky, 3rd rate. Timber, pine and juniper; undergrowth, 2nd growth pine.

	N. 0° 59' E., on a true line bet. secs. 11 and 12. Over rolling land,, thru scattered timber and undergrowth.
0.23	Ditch, 20 lks. wide, 2 ft. deep, course NW. to Boulin Tank.
9.00	Ridge, bears E. and W.; desc. over a N. slope.
21.30	Wash, 15 lks. wide, 18 ins. deep, course SW.; asc. over a S. slope.
26.40	Spur, slopes SW.; desc. over a NW. slope.
40.05	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \\ \text{S } 11 \mid \text{S } 12 \\ \\ 1942 \end{array}$
	from which
	A pine, 12 ins. diam., bears N. 83° E., 70 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.
	A pine, 14 ins. diam., bears S. 65 $\frac{1}{2}$ ° W., 55 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.
43.20	Wash, 30 lks. wide, 2 ft. deep, course SW.; begin the ascent of the SW. slope of a mountain; asc. 235 ft.
75.60	Top of mountain, bears E. and W. ; desc. 89 ft. over a N. slope.
80.10	The point for the cor. of secs. 1, 2, 11 and 12, determined from original bearing tree. At point for cor. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 1, 2, 11 and 12, with brass cap mkd.
	$\begin{array}{c} \text{T23N R3E} \\ \text{S } 2 \mid \text{S } 1 \\ \hline \text{S } 11 \mid \text{S } 12 \\ 1942 \end{array}$
	from which

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4850

Chains

The old bearing tree:

A pine, 30 ins. diam., bears S. 30° E., 33 lks.
dist., mkd. T 23 N R 3 E S 12 B T.

New bearing trees:

A pine, 12 ins. diam., bears N. 70½° E., 58 lks.
dist., mkd. T 23 N R 3 E S 1 B T.

A pine, 24 ins. diam., bears S. 39° W., 82 lks.
dist., mkd. T 23 N R 3 E S 11 B T.

A pine, 30 ins. diam., bears N. 17° W., 117 lks.
dist., mkd. T 23 N R 3 E S 2 B T.

Land, S. ½, rolling; N. ½, mountainous.

Soil, dark loam, gravelly, 3rd rate.

Timber, pine and juniper; undergrowth, 2nd growth pine.

From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of
the Tp.

N. 89° 55' W., on a true line bet. secs. 1 and 12.

Over mountainous land, thru dense timber and undergrowth;
asc. over a NE. slope.

- 2.15 Slope changes; asc. 13 ft. over a N. slope.
- 8.55 Ridge, bears N. 60° W. and S. 60° E.; descend over a S.
slope.
- 25.10 Slope changes, desc. 102 ft. over a SW. slope.
- 36.10 Draw, drains S.; asc. 15 ft. over an E. slope.
- 40.07 The ¼ sec. cor., a sandstone, 30x30x4 ins., firmly set in
a mound of stone, 3½ ft. base, 2½ ft. high, mkd. ¼ on N.
face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the
ground, to bedrock, with the original stone buried along-
side, and in a mound of stone to top, for ¼ sec. cor.,
with brass cap mkd.

$$\begin{array}{r} S 1 \\ \frac{1}{4} \text{---} \\ S 12 \\ 1942 \end{array}$$

from which

The original bearing tree:

The original position of a pine (dead, lying on
ground), 20 ins. diam., bears S. 30° W., 10 lks.
dist., mkd. ¼ S B T.

New bearing trees:

A pine, 12 ins. diam., bears N. 58½° E., 92 lks.
dist., mkd. ¼ S 1 B T.

A pine, 20 ins. diam., bears S. 41½° W., 72 lks.
dist., mkd. ¼ S 12 B T.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains	
	Thence,
	S. 89° 33' W., on a true line bet. secs. 1 and 12.
	Ascend 13 ft. over a NE. slope.
2.10	Spur, slopes S. 30° E.; desc. 188 ft. over a SW. slope.
20.85	Ravine, course NW.
23.25	Spur, slopes NW.
29.30	Wash, 8 lks. wide, 2 ft. deep, course N. 30° W.; asc. 141 ft. over E. slope of a mountain.
39.05	Spur, slopes NE.; descend a NW. slope.
39.75	The cor. of secs. 1, 2, 11 and 12.
	Land, mountainous.
	Soil, dark loam, rocky, 3rd rate.
	Timber, pine and juniper; undergrowth, 2nd growth pine.

	N. 1° 21' E., on a true line bet. secs. 1 and 2.
	Over mountainous land, thru dense timber, and undergrowth; desc. 188 ft. over a N. slope.
15.00	Foot of the mountain, bears E. and W.; enter rolling land.
21.10	Wash, 30 lks. wide, 2 ft. deep, course N. 70° W.; enter scattered timber.
23.00	Dim road, bears E. and W.
39.80	The $\frac{1}{4}$ sec. cor., a lava stone, 10x8x8 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face.
	At point for cor.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \\ S \ 2 \ \ S \ 1 \\ \\ 1942 \end{array}$
	from which
	A pine, 12 ins. diam., bears N. 77 $\frac{1}{4}$ ° E., 86 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.
	A juniper, 8 ins. diam., bears N. 57 $\frac{3}{4}$ ° W., 98 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.
	Thence,
	N. 1° 35' W., on a true line bet. secs. 1 and 2.
25.00	Low ridge, bears E. and W.; desc. over a N. slope.
35.00	Drain, course W.; asc. over a S. slope.
41.93	The cor. of secs. 1, 2, 35 and 36, on N. bdy. of Tp.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

Land, S. 15 chs. mountainous; remainder of mile rolling. Timber, pine, juniper and pinyon; undergrowth, 2nd growth pine.


From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

N. 0° 57' W., on a true line bet. secs. 34 and 35.

Over rolling land, thru dense timber and undergrowth; desc. over a gradual NW. slope. Along a fence, bears irregularly N.

- 0.90 Draw, drains SW.; asc. 89 ft. over a S. slope.
12.00 Spur, slopes W.; desc. 319 ft. over a NW. slope.
29.00 Draw, drains W.; fence bears northeasterly from this point; asc. 28 ft. over a S. slope.
31.50 Spur, slopes W.; desc. 49 ft. over a N. slope.
40.08 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A pine, 6 ins. diam., bears N. 87 $\frac{1}{2}$ ° E., 54 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.

A pine, 6 ins. diam., bears S. 41° W., 83 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.

Continue descent over a gradual N. slope.

- 41.40 Wash, 10 lks. wide, course SW.; asc. 15 ft. over a SE. slope.
43.00 Spur, slopes SW.; desc. 23 ft. over a NW. slope.
45.50 Ravine, course SW.; asc. 40 ft. over a S. slope.
54.00 Spur, slopes W.; desc. 41 ft. over a N. slope.
57.80 Ravine, course W.; asc. 105 ft. over a S. slope.
66.00 Spur, slopes W.; desc. 125 ft. over a N. slope.
73.95 Ravine, course W.; asc. 54 ft. over a S. slope.
80.16 The original cor. of secs. 26, 27, 34 and 35, a sandstone, 16x12x8 ins., firmly set in the ground, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor., mkd. 1 groove on S. and 2 grooves on E. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with the original stone buried along-side, and in a mound of stone to top, for cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

T23N R3E	
S 27	S 26

S 34	S 35
1942	

from which

The original bearing trees:

A pine, 36 ins. diam., bears N. 73° E., 90 lks.
dist., mkd. T 23 N R 3 E S 26 B T.

A juniper, 14 ins. diam., bears S. 33° W., 35 lks.
dist., mkd. T 23 N R 3 E S 34 B T.

New bearing trees:

A pine, 14 ins. diam., bears N. 85° E., 137 lks.
dist., mkd. T 23 N R 3 E S 26 B T.

A pine, 6 ins. diam., bears S. 4½° E., 92 lks.
dist., mkd. T 23 N R 3 E S 35 B T.

A pine, 14 ins. diam., bears N. 74° W., 180 lks.
dist., mkd. T 23 N R 3 E S 27 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine and juniper; undergrowth, 2nd growth pine.

From the cor. of secs. 25, 26, 35 and 36.

S. 89° 45' W., on a true line bet. secs. 26 and 35.

Over rolling land, thru dense timber and undergrowth; asc.
12 ft. over a N. slope.

6.65 Fire road, bears NW. and SE.

7.95 Spur, slopes NW.; desc. 120 ft. over a broken NW. slope.

40.08 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for ¼ sec. cor., with brass cap mkd.

¼	S 26

	S 35
	1942

from which

A pine, 8 ins. diam., bears North, 22 lks.
dist., mkd. ¼ S 26 B T.

A pine, 10 ins. diam., bears S. 25° E., 84 lks.
dist., mkd. ¼ S 35 B T.

Continue descent over a NW. slope.

44.55 Wash, 20 lks. wide, course SW.

50.45 Wash, at the entrance to an earth reservoir from S. 70° W.

50.95 A 4 strand barbed wire fence, bears SE., and NW. across
reservoir.

53.65 Leave reservoir at SW. edge.; asc. 42 ft. over a NE. slope.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains	
61.35	Ridge, bears N. 70° W., and S. 45° E.; desc. 88 ft. over a SW. slope.
80.16	The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, dark loam, rocky, 3rd rate. Timber, pine, oak and juniper; undergrowth, 2nd growth pine and algerita. ----- N. 0° 20' W., on a true line bet. secs. 26 and 27. Over rolling land, thru dense timber and undergrowth; asc. 34 ft. over a S. slope.
10.00	Ridge, bears E. and W.; desc. 45 ft. over a N. slope.
19.80	A 3 strand barbed wire fence, bears E. and W.
31.00	Wash, 20 lks. wide, course NW.
32.60	A 4 strand barbed wire fence, bears N. 5° W. and S. 5° E.
39.97	The point for the $\frac{1}{4}$ sec. cor., determined from stumps of the original bearing trees. At point for cor. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 27 S 26 1942
	from which
	The old bearing trees: A pine stump, 48 ins. diam., bears N. 31° E., 57 lks. dist., only part of blaze remains, marks not visible. A pine stump, 30 ins. diam., bears N. 10° W., 22 lks. dist., marks indiscernible. New bearing trees: A pine, 9 ins. diam., bears S. 43° E., 171 lks. dist., mkd. $\frac{1}{4}$ S 26 B T. A pine, 7 ins. diam., bears N. 16 $\frac{1}{4}$ ° W., 129 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.
	Thence, N. 0° 03' E., on a true line bet. secs. 26 and 27. Descend gradually over a N. slope.
0.90	Old cabin, bears E. 50 lks. dist.
5.10	Draw, drains W.; asc. 183 ft. over a S. slope.
12.80	West edge of an earth reservoir.
39.20	A 3 strand barbed wire fence, bears E. and W.

BOOK 4350

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.Chains
40.00

The cor. of secs. 22, 23, 26 and 27, a juniper post, 4 ins. square, set in a mound of stone, 2 ft. base, 1 ft. high, mkd. T 23 N S 23 on NE., R 3 E S 26 on SE., S 27 on SW. and S 22 on NW. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original post, buried alongside, for cor. of secs. 22, 23, 26 and 27, with brass cap mkd.

T23N R3E	
S 22	S 23

S 27	S 26
1942	

from which

An old bearing tree, not of record:

A juniper, 42 ins. diam., bears S. 31° W., 99 lks, dist., mkd. T 23 N R 3 E S 27 B T.

New bearing trees:

A pinyon, 7 ins. diam., bears N. 80 $\frac{1}{4}$ ° E., 159 lks. dist., mkd. T 23 N R 3 E S 23 B T.

A juniper, 8 ins. diam., bears N. 18° W., 113 lks. dist., mkd. T 23 N R 3 E S 22 B T.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine, juniper and pinyon; undergrowth, 2nd growth pine and algerita.

From the cor. of secs. 23, 24, 25 and 26,

S. 87° 34' W., on a true line bet. secs. 23 and 26.

Over mountainous land, thru dense timber and scattered undergrowth; desc. 156 ft. over a NW. slope.

11.00 Slope changes to a SW. slope.

18.40 Ravine; course N. 80° W.; asc. 6 ft. over a NE. slope.

20.15 Dim road, bears NW. and SE.

23.40 Spur, slopes NW.; desc. 103 ft. over a SW. slope.

28.55 Ravine, course N. 85° W.

37.75 Dim road, bears NW. and SE.

39.93 The $\frac{1}{4}$ sec. cor., a sandstone, 20x16x12 ins. set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains

$$\frac{1}{4} \begin{array}{r} \text{S } 23 \\ \hline \text{S } 26 \\ 1942 \end{array}$$

from which

The original bearing tree:

The position of the original bearing tree, a pine,
(dead, lying on ground) bears S. 27° W., 52 lks.
dist., mkd. $\frac{1}{4}$ S B T.

New bearing trees:

A pine, 20 ins. diam., bears N. 31° E., 31 lks.
dist., mkd. $\frac{1}{4}$ S 23 B T.

A pine, 16 ins. diam., bears S. 45° W., 91 lks.
dist., mkd. $\frac{1}{4}$ S 26 B T.

This cor. is located on a low spur, slopes NW.

Thence,

S. 88° 00' W., on a true line bet. secs. 23 and 26.

Descend 44 ft. over a SW. slope.

22.00 Road, bears S. to Frenchy Spring and N. to Red Lake-Spring Valley highway.

22.20 Wash, 10 lks. wide, 1 ft. deep, course NW.; asc. 182 ft. over the E. slope of a mountain.

39.89 The cor. of secs. 22, 23, 26 and 27.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, Pine, juniper and pinyon; undergrowth, 2nd growth pine.

N. 0° 26' E., on a true line bet. secs. 22 and 23.

Over mountainous and rolling land, thru dense timber and scattered undergrowth; desc. 254 ft. over a NE. slope.

21.00 Road, bears E. to Frenchy Spring and W. to Red Lake-Spring Valley highway.

25.00 Wash, 20 lks. wide, course NW.

29.20 Wash, 10 lks. wide, course SW.

37.00 Ravine, course W.; asc. a SW. slope.

40.15 Graded road, bears W. to Red Lake Valley and E. to Spring Valley.

41.73 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \begin{array}{r} \text{S } 22 \mid \text{S } 23 \\ 1942 \end{array}$$

Dependent Resurvey of the Subdivisional Lines of
T.23 N., R. 3 E.

Chains

from which

A pine, 8 ins. diam., bears N. 37° E., 178 lks.
dist., mkd. $\frac{1}{4}$ S 23 B T.

A pine, 5 ins. diam., bears N. 59 $\frac{1}{4}$ ° W., 103 lks.
dist., mkd. $\frac{1}{4}$ S 22 B T.

Continue ascent over a SW. slope.

45.00 Spur, slopes W.; desc. over a gradual N. slope.

52.00 Wash, 10 lks. wide, course W.

55.00 Spur, slopes W.; desc. over a gradual N. slope.

62.70 Wash, 10 lks. wide, course W.; asc. a S. slope.

70.00 Spur, slopes W.; desc. a gradual N. slope.

83.46 The cor. of secs. 14, 15, 22 and 23, a malapais stone,
24x16x6 ins. firmly set in a mound of stone, 3 ft. base,
1 ft. high, mkd. 3 grooves on S. and 2 grooves on E.
faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the
ground to bedrock, with the original stone buried along-
side and in a mound of stone to top, for cor. of secs.
14, 15, 22 and 23, with brass cap mkd.

T23N	R3E
S 15	S 14
S 22	S 23
1942	

from which

A pine, 5 ins. diam., bears N. 37 $\frac{1}{2}$ ° E., 66 lks.
dist., mkd. T 23 N R 3 E S 14 B T.

A pine, 5 ins. diam., bears S. 38 $\frac{1}{2}$ ° E., 16 lks.
dist., mkd. T 23 N R 3 E S 23 B T.

A pine, 10 ins. diam., bears S. 14 $\frac{1}{2}$ ° W., 24 lks.
dist., mkd. T 23 N R 3 E S 22 B T.

A pine, 4 ins. diam., bears N. 56 $\frac{1}{2}$ ° W., 350 lks.
dist., mkd. T 23 N R 3 E S 15 B T.

Land, S. 20 chs. rolling; remainder of mile rolling.
Soil, dark loam, rocky and gravelly, 3rd rate.
Timber, pine and juniper; undergrowth, algerita and 2nd
growth pine.

From the cor. of secs. 13, 14, 23 and 24.

N. 89° 13' W., on a true line bet. secs. 14 and 23.

Over rolling land, thru dense timber and undergrowth;
desc. 6 ft. over a SW. slope.

1.15 Draw, drains NW.; asc. 12 ft. over a NE. slope.

3.15 Spur, slopes NW.; desc. over a SW. slope.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains	
12.85	Ditch, 10 lks. wide, 2 ft. deep, course N. 20° W. to an earth reservoir.
22.90	Graded road, bears N. 41½° E. to Spring Valley and S. 41½° W. to Red Lake Valley.
38.85	Road, bears N. 20° W. to Boulin Tank and S. 45° E. to graded road.
39.57	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{c} \text{S 14} \\ \hline \text{S 23} \\ 1942 \end{array}$
	from which
	A pine, 13 ins. diam., bears N. 54½° E., 66 lks. dist., mkd. ¼ S 14 B T.
	A pine, 7 ins. diam., bears S. 25½° W., 104 lks. dist., mkd. ¼ S 23 B T.
59.15	A flat ridge, bears N. and S.; desc. 60 ft. along a N. slope.
79.14	The cor of secs. 14, 15, 22 and 23. Land, rolling. Soil, dark loam, rocky and gravelly, 3rd rate. Timber, pine and juniper; undergrowth, 2nd growth pine.

	N. 0° 23' W., on a true line bet. secs. 14 and 15. Over rolling land, thru dense timber and undergrowth.
20.00	Wash, 20 lks. wide, course W.
30.30	Wash, 40 lks. wide, course SW.; asc. 29 ft. over a S. slope.
37.05	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{c} \text{S 15} \quad \text{S 14} \\ \hline 1942 \end{array}$
	from which
	A pine, 6 ins. diam., bears S. 43½° E., 99 lks. dist., mkd. ¼ S 14 B T.
	A pine, 16 ins. diam., bears S. 22° W., 132 lks. dist., mkd. ¼ S 15 B T.
50.00	Ridge, bears E. and W.; desc. over a gradual NW. slope.
74.10	The cor. of secs. 10, 11, 14 and 15, a malpais stone, 32x28x4 ins., firmly set in a mound of stone, 3 ft. base, 1½ ft. high, mkd. 4 grooves on S. and 2 grooves on E. faces.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.

$$\begin{array}{r} \text{T23N R3E} \\ \text{S 10 | S 11} \\ \hline \text{S 15 | S 14} \\ 1942 \end{array}$$

from which

A juniper, 30 ins. diam., bears N. $1\frac{1}{2}^\circ$ E., 320 lks. dist., mkd. T 23 N R 3 E S 11 B T.

A pine, 16 ins. diam., bears S. $48\frac{1}{2}^\circ$ E., 238 lks. dist., mkd. T 23 N R 3 E S 14 B T.

Land, rolling.

Soil, rocky and gravelly, 3rd rate.

Timber, pine and juniper; undergrowth, 2nd growth pine.

From the cor. of secs. 11, 12, 13 and 14.

S. $86^\circ 10'$ W., on a true line bet. secs. 11 and 14.

Over rolling land, thru scattered timber and undergrowth; desc. 25 ft. over a gradual SW. slope.

8.00 Slope changes, desc. over a NW. slope.

28.05 Wash, 10 lks. wide, course SW.

40.02 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} \text{S 11} \\ \frac{1}{4} \text{ ---} \\ \text{S 14} \\ 1942 \end{array}$$

from which

A pine, 8 ins. diam., bears S. 43° E., 312 lks. dist., mkd. $\frac{1}{4}$ S 14 B T.

A pine, 6 ins. diam., bears S. 15° E., 283 lks. dist., mkd. $\frac{1}{4}$ S 14 B T.

43.15 Road, bears N. to Boulin Tank and S. to graded road.

63.05 Ridge, bears NW. and SW.; desc. 36 ft. over a W. slope.

80.04 The cor. of secs. 10, 11, 14 and 15.

Land, rolling.

Soil, rocky and gravelly, 3rd rate.

Timber, pine and juniper; undergrowth, 2nd growth pine.

N. $0^\circ 04'$ W., on a true line bet. secs. 10 and 11.

Over rolling land, thru scattered timber.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains 28.00	Draw, 20 lks. wide, drains NE.; asc. a gradual S. slope.
32.60	Road, bears NE. to Boulin Tank and SW. to graded road.
40.20	The $\frac{1}{4}$ sec. cor., a lava stone, 8x8x6 ins. set in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face. At point for cor. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \\ \text{S } 10 \mid \text{S } 11 \\ \\ 1942 \end{array}$
	from which
	A pine, 7 ins. diam., bears N. $57\frac{1}{2}^{\circ}$ E., 469 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.
	A juniper, 4 ins. diam., bears N. $46\frac{1}{2}^{\circ}$ W., 196 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.
	Thence, N. $1^{\circ} 00'$ E., on a true line bet. secs. 10 and 11. Ascend 52 ft. over a gradual SE. slope.
15.30	Dim road, bears N. 70° E. and S. 70° W.; foot of a mountain, bears N. 30° E. and S. 60° W.; asc. 219 ft. over a SE. slope.
38.00	Spur, slopes E.; desc. over a NE. slope.
39.76	The cor. of secs. 2, 3, 10 and 11, a lava stone, 30x16x10 ins. set in a mound of stone, 2 ft. base, 1 ft. high, mkd. 5 grooves on S. and 2 grooves on E. faces. At point for cor. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, for the cor. of secs. 2, 3, 10 and 11, with brass cap mkd.
	$\begin{array}{c} \text{T } 23 \text{ N } \text{ R } 3 \text{ E} \\ \text{S } 3 \mid \text{S } 2 \\ \hline \text{S } 10 \mid \text{S } 11 \\ \\ 1942 \end{array}$
	from which
	A pinyon, 3 ins. diam., bears N. 62° E., 74 lks. dist., mkd. B T.
	A pinyon, 7 ins. diam., bears S. 27° E., 187 lks. dist., mkd. T 23 N R 3 E S 11 B T.
	A pinyon, 5 ins. diam., bears S. $21\frac{1}{2}^{\circ}$ W., 225 lks. dist., mkd. T 23 N R 3 E S 10 B T.
	A pinyon, 3 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ W., 136 lks. dist., mkd. B T.
	Land, S. 55.00 chs. rolling; remainder of mile mountainous. Soil, dark loam, rocky and gravelly, 3rd rate. Timber, Pine, pinyon and juniper; undergrowth, algerita.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains	
	From the cor. of secs. 1, 2, 11 and 12.
	S. 86° 13' W., on a true line bet. secs. 2 and 11.
	Over mountainous land, thru dense timber and scattered undergrowth; asc. 35 ft. over a N. slope.
4.45	Spur, slopes NW.; desc. 264 ft. over a NW. slope.
26.70	Ditch, course S. 30° W. to Boulin Tank; leave timber, bears N. and S.
33.13	Board fence, bears NW. and SE.; enter corral.
34.00	Board fence, bears NW. and SE.; leave corral.
40.18	Wash, 10 lks. wide, 2 ft. deep, course N.
40.37	Proportional distance.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S 2}{S 11}$ 1942
	raise a mound
	of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
	This cor. is located 3.50 chs. N. of the top of the dam at Boulin Tank.
	Ascend 102 ft. over a gradual SE. slope.
43.25	Corner of a corral, from which fences bear SW. and SE.
44.30	Dim road, bears NW. and S.; enter scattered timber, bears N. and SW.
56.36	The SE. corner of a cabin, bears N. 1.25 chs.
59.72	A 3 strand barbed wire fence, bears S., and N. 3.10 chs. dist. to a fence cor. from which fences bear southerly and easterly.
60.45	Dim road, bears N. 30° W. and S.
68.50	Foot of mountain, bears N. and S.; asc. 102 ft. over an E. slope.
80.74	The cor. of secs. 2, 3, 10 and 11.
	Land, mountainous.
	Soil, rocky and gravelly, 3rd rate.
	Timber, pine, juniper and pinyon; undergrowth, 2nd growth pine and cliff rose.

	N. 0° 01' E., on a true line bet. secs. 2 and 3.
	Over mountainous and rolling land, thru dense timber; desc. 284 ft. over a NE. slope.
15.00	Foot of steep descent of mountain, bears NW. and SE.
43.61	Proportional distance.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S \ 3 \ | \ S \ 2 \\ | \\ 1942 \end{array}$$

from which

A pine, 10 ins. diam., bears N. $71\frac{1}{4}^{\circ}$ E., 125 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.

A pine, 10 ins. diam., bears N. $74\frac{1}{2}^{\circ}$ W., 62 lks. dist., mkd. $\frac{1}{4}$ S 3 B T.

63.10 Road, bears N. 63° W. and S. 63° E. to Boulin Tank.

87.35 The cor. of secs. 2, 3, 34 and 35, on N. Bdy. of the Tp.

Land, S. 15.00 chs. mountainous; remainder of mile rolling. Soil, rocky and gravelly, 3rd rate.

Timber, pine, pinyon and juniper; undergrowth, 2nd growth pine, algerita and cliff rose.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

N. $0^{\circ} 03'$ E., on a true line bet. secs. 33 and 34.

Over rolling land, thru scattered timber.; asc. a gentle SW. slope.

23.50 Dim road, bears N. 60° E. and S. 60° W.

27.60 Low ridge, bears S. 60° E. and N. 60° W.; desc. 58 ft. over a N. slope.

35.28 A 3 strand barbed wire fence, bears E. and W.

40.43 The $\frac{1}{4}$ sec. cor., a lava stone, 8x6x4 ins., firmly set in a mound of stone, 3 ft. base, 6 ins. high, mkd. $\frac{1}{4}$ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S \ 33 \ | \ S \ 34 \\ | \\ 1942 \end{array}$$

from which

A pine, 10 ins. diam., bears N. $28\frac{3}{4}^{\circ}$ E., 426 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.

Top of a farm house, bears N. $25^{\circ} 25'$ W.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Thence,

N. $0^{\circ} 18'$ W., on a true line bet. secs. 33 and 34.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains	<p>Descend over a gentle N. slope.</p> <p>5.60 Drain, course W. 1.00 ch. to an earth tank.</p> <p>7.20 A 3 strand barbed wire fence, bears E., and W. approx. 5.00 chs. to a fence cor. from which fences bear W. and N.</p> <p>13.60 A 3 strand barbed wire fence, bears E., and W. approx. 2.00 chs. to a fence cor. from which fences bear E., W. and S.; leave cultivated field, bears E. and W.; asc. 21 ft. over a S. slope.</p> <p>17.32 From this point the top of the farm house, bears N. 62° 36' W.</p> <p>17.60 Spur, slopes SW.</p> <p>20.50 Head of a draw, drains SW.</p> <p>23.20 Spur, slopes SW.; desc. 15 ft. over a N. slope.</p> <p>26.70 Old log cabin, bears E. approx. 1.50 chs. dist.</p> <p>40.19 The point for the cor. of secs. 27, 28, 33 and 34, determined at the center line of a lane, from the W., from which a fence cor., bears S., 0.45 lks. dist., from which fences bear W. and S.</p> <p>At point for cor.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T23N</td> <td>R3E</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> <tr> <td colspan="2" style="text-align: center;">1942</td> </tr> </table> <p style="text-align: right;">from which</p> <p>• A pine, 12 ins. diam., bears N. 85° E., 298 lks. dist., mkd. T. 23 N R 3 E S 27 B T.</p> <p>A pine, 20 ins. diam., bears S. 54° E., 391 lks. dist., mkd. T 23 N R 3 E S 34 B T.</p> <p>No evidence of original bearing trees.</p> <p>Land, rolling. Soil, on hills, gravelly, 3rd rate; in little valleys, dark loam, 1st rate. Timber, pine and juniper; undergrowth none.</p> <hr style="border-top: 1px dashed black;"/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89° 00' W., on a true line bet. secs. 27 and 34.</p> <p>Over rolling land, thru dense timber; asc. 6 ft. over an E. slope.</p> <p>3.00 Spur, slopes S.; desc. 76 ft. over a SW. slope.</p> <p>10.40 Head of a ravine, course SW.; asc. 23 ft. over a SE. slope.</p> <p>18.60 Spur, slopes SW; desc. 102 ft. over a SW. slope.</p> </div>	T23N	R3E	S 28	S 27			S 33	S 34	1942	
T23N	R3E										
S 28	S 27										
S 33	S 34										
1942											

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4850

Chains 39.66	<p>Proportional distance.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\begin{array}{r} S\ 27 \\ \frac{1}{4} \overline{\hspace{1.5cm}} \\ S\ 34 \\ 1942 \end{array}$ <p style="text-align: right;">from which</p> <p>A pine, 4 ins. diam., bears N. 34° E., 78 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.</p> <p>A pine, 36 ins. diam., bears S. 40° W., 238 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.</p> <p>Ascend over a SE. slope.</p>
42.00	Spur, slopes SW.; desc. 79 ft. over a gradual W. slope.
43.70	Wash, 10 lks. wide, course SW.
48.46	A 2 strand barbed wire fence, bears N., and S. 80 lks. to a fence cor., from which fences bear N., E. and W.
50.30	Wash, 10 lks. wide, course S.
57.80	House, bears S. approx. 3 chs. dist.
59.10	Dim road, bears N. and S.
59.85	Wire fence, bears N., and S. 23 lks. to a fence cor., from which fences bear E., W. and N.
78.50	A fence cor., from which fences bear NW. and E. along the S. side of a cultivated field.
78.90	Road, bears N. 85° W. and S. 80° E.
79.32	The cor. of secs. 27, 28, 33 and 34.
	<p>Land, rolling. Soil, dark loam, gravelly, 2nd and 3rd rates. Timber, pine and juniper; undergrowth, 2nd growth pine and algerita.</p> <p>-----</p> <p>N. 0° 22' E., on a true line bet. secs. 27 and 28.</p> <p>Over rolling land, thru scattered timber and undergrowth.</p>
0.45	A 4 strand barbed wire fence, bears E. and W.; enter cultivated field.
5.25	A 4 strand barbed wire fence, bears E. and W.; leave cultivated field.; asc. 93 ft. over a S. slope; enter timber, bears E. and W.
17.65	Spur, slopes W.; desc. 40 ft. over a N. slope.
20.05	Barbed wire fence, bears E., and W. approx 5 lks. to a fence cor. from which fences bear E. and W.
31.35	Barbed wire fence, bears E., and W. approx. 15 lks. to a fence cor. from which fences bear N., S. and E.; enter cultivated field.
40.35	Drain, course W.

BOOK 4350

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.Chains
40.68

The point for the $\frac{1}{4}$ sec. cor., determined from the original bearing tree.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 28 \text{ | S } 27 \\ 1942 \end{array}$$

from which

The old bearing tree:

A pine snag, 36 ins. diam., bears N. 40° W., 95 lks. dist., mkd. $\frac{1}{4}$ S B T.

New bearing tree:

A pine, 14 ins. diam., bears S. $81\frac{1}{2}^{\circ}$ W., 346 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Thence,

N. $0^{\circ} 26'$ W., on a true line bet. secs. 27 and 28.

- 0.75 A fence cor. bears W., 50 lks. dist., from which fences bear S. and N. 45° E.
- 1.40 A 3 strand barbed wire fence, bears N. 45° E. and S. 45° W. leave cultivated field; asc. 82 ft. over a S. slope.
- 4.50 Cattle guard in a road, which bears E. and W.
- 4.60 A fence cor. bears E., 2 lks. dist., from which fences bear SW. and E.
- 35.00 Wide flat-topped ridge, bears SE. and NW.; desc. 15 ft. over a N. slope.
- 40.29 The cor. of secs. 21, 22, 27 and 28, a lava stone, 24x12x6 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 2 grooves on S. and 3 grooves on E. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for cor. of secs. 21, 22, 27 and 28; with brass cap mkd.

$$\begin{array}{c} \text{T23N R3E} \\ \text{S } 21 \text{ | S } 22 \\ \hline \text{S } 28 \text{ | S } 27 \\ 1942 \end{array}$$

from which

A pine, 6 ins. diam., bears N. $13\frac{1}{2}^{\circ}$ E., 166 lks. dist., mkd. T 23 N R 3 E S 22 B T.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains

A juniper, 3 ins. diam., bears S. 85° E., 146 lks.
dist., mkd. B T.

A pine, 14 ins. diam., bears S. 35° W., 32 lks.
dist., mkd. T 23 N R 3 E S 28 B T.

A pine, 10 ins. diam., bears N. 81° W., 65 lks.
dist., mkd. T 23 N R 3 E S 21 B T.

Land, rolling.

Soil, on hills, gravelly and rocky, 3rd rate; in valleys,
dark loam, 1st rate.

Timber, pine and juniper; undergrowth, 2nd growth pine.

From the cor. of secs. 22, 23, 26 and 27.

N. 88° 08' W., on a true line bet. secs. 22 and 27.

Over mountainous land, thru scattered timber and under-
growth; asc. 170 ft. over an E. slope.

- 4.50 A 3 strand barbed wire fence, bears NW. and SE.
9.75 Top of mountain; desc. 394 ft. over a W. slope.
25.00 Foot of Mountain, bears N. and S.
28.10 A 3 strand barbed wire fence, bears NW. and SE.
39.46 Proportional distance.
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} \text{S } 22 \\ \hline \text{S } 27 \\ 1942 \end{array}$$

from which

A pine, 5 ins. diam., bears N. 36 $\frac{1}{2}$ ° E., 135 lks.
dist., mkd. $\frac{1}{4}$ S 22 B T.

A pine, 5 ins. diam., bears S. 22 $\frac{1}{4}$ ° E., 208 lks.
dist., mkd. $\frac{1}{4}$ S 27 B T.

- 41.50 Wash, 10 lks. wide, course NW., thence along a N. slope.
78.92 The cor. of secs. 21, 22, 27 and 28.

Land, E. 25 chs., mountainous; remainder of mile rolling.
Soil, rocky and gravelly, 3rd rate.
Timber, pine, pinyon and juniper; undergrowth, 2nd growth
pine, cliff rose and algerita.

N. 0° 07' E., on a true line bet. secs. 21 and 22.

Over rolling land, thru scattered timber; desc. 73 ft.
over a N. slope.

- 0.05 A 3 strand barbed wire fence, bears easterly and westerly.
4.38 A 3 strand barbed wire fence, bears E. and W.
9.25 Ravine, course W.
11.95 Point of low short spur, slopes W.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains 20.80	Wash, 20 lks. wide, 4 ft. deep, course W.; asc. over a gradual SW. slope.
28.00	A 4 strand barbed wire fence, bears E. and W.
28.20	Graded road, bears N. 60° W. to Red Lake Valley and S. 60° E. to Spring Valley.
40.51	The $\frac{1}{4}$ sec. cor., a lava stone, 18x12x6 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face. At point for cor. Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. with brass cap mkd. <div style="text-align: center;"> $\frac{1}{4}$ S 21 S 22 1942 </div> <div style="text-align: right; margin-right: 100px;">from which</div> <p>A pinyon, 10 ins. diam., bears S. 84$\frac{1}{4}$° E., 221 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.</p> <p>A pine, 12 ins. diam., bears N. 11$\frac{3}{4}$° W., 79 lks. dist., mkd. $\frac{1}{4}$ S 21 B T. No evidence of original bearing tree.</p> <p>Thence, N. 1° 59' W., on a true line bet. secs. 21 and 22. Asc. 15 ft. over a SW. slope.</p>
17.10	Low, wide ridge, bears S. 60° E. and N. 60° W.; desc. over a gradual N. slope.
20.40	Dim road, bears N. 60° E. and S. 60° W.
40.31	The cor. of secs. 15, 16, 21 and 22, a lava stone 20x16x10 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 3 grooves on S. and 3 grooves on E. faces. At point for cor. Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for cor. of secs. 15, 16, 21 and 22, with brass cap mkd. <div style="text-align: center;"> T23N R3E S 16 S 15 ----- S 21 S 22 1942 </div> <div style="text-align: right; margin-right: 100px;">from which</div> <p>A pine, 12 ins. diam., bears N. 9° E., 153 lks. dist., mkd. T 23 N R 3 E S 15 B T.</p> <p>A pine, 14 ins. diam., bears S. 31$\frac{1}{4}$° E., 312 lks. dist., mkd. T 23 N R 3 E S 22 B T.</p> <p>A pine, 24 ins. diam., bears S. 78$\frac{1}{4}$° W., 235 lks. dist., mkd. T 23 N R 3 E S 21 B T.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

4850

Chains

A pine, 12 ins. diam., bears N. $51\frac{1}{2}^{\circ}$ W., 199 lks. dist., mkd. T 23 N R 3 E S 16 B T.

Land, rolling.

Soil, gravelly, 3rd rate.

Timber, pine, pinyon and juniper; undergrowth, none.

From the cor. of secs. 14, 15, 22 and 23.

S. $89^{\circ} 57'$ W., on a true line bet. secs. 15 and 22.

Over rolling land, thru scattered timber; desc. 65 ft. over a gradual NW. slope.

36.00 Enter heavy timber, bears N. and S.

40.27 The $\frac{1}{4}$ sec. cor., a sandstone, $8 \times 6 \times 3$ ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} \text{S } 15 \\ \hline \text{S } 22 \\ 1942 \end{array}$$

from which

The old bearing tree;

A pine stump, 25 ins. diam., bears N. $56\frac{1}{2}^{\circ}$ E., 284 lks. dist., no marks visible.

New bearing trees:

A pine, 6 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ W., 114 lks. dist., mkd. $\frac{1}{4}$ S 15 B T.

A pine, 7 ins. diam., bears S. 77° E., 80 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.

Thence,

S. $89^{\circ} 50'$ W., on a true line bet. secs. 15 and 22.

Desc. 15 ft. over a gradual W. slope.

2.80 Junction of washes from NE. and SE., 20 lks. wide, course S. 60° W.

12.50 Recross wash, 20 lks. wide, course NW.

15.00 Leave heavy timber, bears N. and S.

22.50 Dim road, bears N. 70° W. and S. 70° E.

25.00 Enter heavy timber, bears NE. and SW.

32.50 Dim road, bears NE. and SW.

40.38 The cor. of secs. 15, 16, 21 and 22.

Land, rolling.

Soil, rocky and gravelly, 3rd rate.

Timber, pine, and juniper; undergrowth, 2nd growth pine.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains	
	N. 0° 26' W., on a true line bet. secs. 15 and 16. Over rolling land, thru scattered timber and undergrowth.
6.50	Wash, 20 lks. wide, course W.
7.40	Road, bears NE. to Boulin Tank and W. to Red Lake Valley.
7.90	A 4 strand barbed wire fence, bears W., and E. approx. 2 chs. dist. to a fence cor. from which fences bear N. and W.
15.20	Road, bears SE. and W.
15.90	Enter cultivated land, bears E. and W.
31.00	Leave cultivated land, bears E. and W.
37.12	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S } 16 \text{ S } 15 \\ 1942 \end{array}$
	from which
	A pine, 10 ins. diam., bears S. 59° E., 316 lks. dist., mkd. $\frac{1}{4}$ S 15 B T.
	A pine, 12 ins. diam., bears S. 69 $\frac{1}{2}$ ° W., 126 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
	Asc. 15 ft. over a gradual S. slope.
40.52	A 4 strand barbed wire fence, bears W., and E. approx. 3 chs. dist. to a fence cor., from which fences bear W. and S.
74.24	The cor. of secs. 9, 10, 15 and 16, a lava stone 24x12x8 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 4 grooves on S. and 3 grooves on E. faces. At point for cor. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, for cor. of secs. 9, 10, 15 and 16, with brass cap mkd.
	$\begin{array}{c} \text{T23N R3E} \\ \text{S } 9 \text{ S } 10 \\ \hline \text{S } 16 \text{ S } 15 \\ 1942 \end{array}$
	from which
	A juniper, 3 ins. diam., bears N. 37° E., 170 lks. dist., mkd. B T.
	A pine, 3 ins. diam., bears S. 32 $\frac{1}{2}$ ° E., 215 lks. dist., mkd. B T.
	A juniper, 3 ins. diam., bears S. 24° W., 342 lks. dist., mkd B T.
	A pine, 6 ins. diam., bears N. 83° W., 433 lks. dist., mkd. T 23 N R 3 E S 9 B T.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4850

Chains	
	<p>Land, rolling. Soil, S. $\frac{1}{2}$, dark loam, 1st rate; N. $\frac{1}{2}$, rocky 3rd rate. Timber, pine and juniper; undergrowth, 2nd growth pine.</p> <p>-----</p> <p>From the cor. of secs. 10, 11, 14 and 15. S. 89° 46' W., on a true line bet. secs. 10 and 15. Over rolling land, thru scattered timber.; desc. over a gradual W. slope.</p>
21.35	Road, bears S. 80° E. and N. 80° W.; center of a draw, drains SE.
31.35	Dim road, bears S. 60° W., and N. 60° E.
40.15	Road, bears N. to Boulin Tank and S. to Red Lake Valley.
40.35	The $\frac{1}{4}$ sec. cor., a lava stone 15x12x7 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.
	At point for cor.
	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with the original stone buried along-side, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S 10}{S 15}$ 1942
	from which
	A pine, 4 ins. diam., bears N. 71 $\frac{1}{2}$ ° W., 108 lks. dist., mkd. $\frac{1}{4}$ S 10 B T.
	A pine, 14 ins. in diam., bears S. 32 $\frac{1}{2}$ ° E., 193 lks. dist., mkd. $\frac{1}{4}$ S 15 B T.
	Thence,
	S. 89° 56' W., on a true line bet. secs. 10 and 15. Asc. a gentle NE. slope.
8.00	Low ridge, bears NW. and SE.; desc. 4 ft. over a SW. slope.
14.70	Wash, 30 lks. wide, course SW.; asc. 6 ft. over an E. slope.
20.90	Spur, slopes S.; desc. 15 ft. over a SW. slope.
27.20	Head of a ravine, course SW.
40.39	The cor. of secs. 9, 10, 15 and 16.
	<p>Land, rolling. Soil, rocky and gravelly, 3rd rate. Timber, Pine and juniper; undergrowth, none.</p> <p>-----</p> <p>N. 0° 06' E., on a true line bet. secs. 9 and 10. Over rolling land, thru scattered timber; desc. over a gentle NW. slope.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

- 5.70 Head of a drain, course SW.; asc. 45 ft. over a gentle S. slope.
- 25.00 Low ridge, bears SE. and NW.; continue a gradual ascent over an E. slope.
- 40.24 The $\frac{1}{4}$ sec. cor., a lava stone 8x4x4 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face.
- At point for cor.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 9 \quad | \quad S\ 10 \\ | \\ 1942 \end{array}$$
- from which
- A juniper, 3 ins. diam., bears S. $29\frac{1}{2}^{\circ}$ E., 150 lks. dist., mkd. B T.
- A juniper, 8 ins. diam., bears S. $60\frac{1}{2}^{\circ}$ W., 90 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.
- Thence,
- N. 2° 24' E., on a true line bet. secs. 9 and 10.
- Ascend 30 ft. over a gentle S. slope.
- 30.00 Ridge, bears NE. and SW.
- 40.00 Head of a draw, drains W.
- 41.08 The cor. of secs. 3, 4, 9 and 10, a lava stone 20x18x8 ins. firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 5 grooves on S. and 3 grooves on E. faces.
- At point for cor.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.
- $$\begin{array}{c} T23N\ R3E \\ S\ 4 \quad | \quad S\ 3 \\ \hline S\ 9 \quad | \quad S\ 10 \\ | \\ 1942 \end{array}$$
- from which
- A juniper, 3 ins. diam., bears S. 49° E., 463 lks. dist., mkd. B T.
- A pine, 12 ins. diam., bears N. $4\frac{3}{4}^{\circ}$ W., 257 lks. dist., mkd T 23 N R 3 E S 4 B T.
- Raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.
- Land, rolling.
Soil, gravelly, 3rd rate.
Timber, pine and juniper; undergrowth, none.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4850

Chains	
	From the cor. of secs. 2, 3, 10 and 11. N. 89° 13' W., on a true line bet. secs. 3 and 10. Over mountainous land, thru dense timber and undergrowth; Asc. 278 ft. over an E. slope.
10.15	Top of the Mountain; desc. 403 ft. over a W. slope.
23.00	Foot of the Mountain, bears N. and S.; continue descent over a N. slope.
31.30	Slope changes; desc. over a W. slope.
39.53	The $\frac{1}{4}$ sec. cor., a sandstone, 14x10x4 ins. firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face. At point for cor. Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with the original stone buried along- side, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{S \ 3}{S \ 10}$ 1942 from which A pinyon, 6 ins. diam., bears N. 39° W., 103 lks. dist., mkd. $\frac{1}{4}$ S 3 B T. A pinyon, 6 ins. diam., bears S. 40° W., 46 lks. dist., mkd. $\frac{1}{4}$ S 10 B T. Thence, N. 89° 03' W., on a true line bet. secs. 3 and 10. Desc. 42 ft. over a W. slope.
14.00	Slope changes; desc. 5 ft. over a SE. slope.
19.00	Slope changes; desc. 32 ft. over a W. slope.
40.04	The cor. of secs. 3, 4, 9 and 10. Land, mountainous. Soil, rocky and gravelly, 3rd rate. Timber, pine, pinyon and juniper; undergrowth, 2nd growth pine and algerita.

	N. 0° 25' W., on a true line bet. secs. 3 and 4. Over rolling land, thru scattered timber and undergrowth. Ascend a gentle W. slope.
25.00	Ridge, bears NW. and SE.; desc. a gentle NW. slope.
33.10	Head of a draw, drains N. 30° E.
43.46	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 4\ | \ S\ 3 \\ | \\ 1942 \end{array}$$

from which

A pine, 20 ins. diam., bears N. 46° E., 163 lks.
dist., mkd. $\frac{1}{4}$ S 3 B T.

A pine, 12 ins. diam., bears S. 32½° W., 50 lks.
dist., mkd. $\frac{1}{4}$ S 4 B T.

Descend 87 ft. over an E. slope.

49.75 Draw, 1.00 ch. wide, drains N. 30° W.; continue descent
over a N. slope.

86.76 The cor. of secs. 3, 4, 33 and 34, on N. bdy. of Tp.

Land, rolling.

Soil, rocky and gravelly, 3rd rate.

Timber, pine, juniper and pinyon; undergrowth, 2nd growth
pine.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of
the Tp., an iron post, 2 ins. diam., firmly set in a
mound of stone, 3 ft. base, 2 ft. high, mkd. and witnessed
as described in the official record.

N. 1° 28' W., on a true line bet. secs. 32 and 33.

Over rolling land, thru scattered timber and undergrowth.

16.80 Wash, 30 lks. wide, course NW.; asc. 23 ft. over a SW.
slope.

18.70 A 4 strand barbed wire fence, bears E. and W.

40.76 The $\frac{1}{4}$ sec. cor., a lava stone 14x12x4 ins., firmly set
in the ground, mkd. $\frac{1}{4}$ on W. face, with a mound of stone,
3 ft. base, 2 ft. high, N. of cor.

At point for cor.

3 ft. long, 1 in. diam.
Set an iron post, 12 ins. in the ground to bedrock, with
the original stone buried alongside, and in a mound of
stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 32\ | \ S\ 33 \\ | \\ 1942 \end{array}$$

from which

A juniper, 3 ins. diam., bears S. 52° E., 456 lks.
dist., mkd B T.

A juniper, 3 ins. diam., bears S. 61½° W., 408 lks.
dist., mkd. B T.

Thence,

N. 0° 30' W., on a true line bet. secs. 32 and 33.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4850

Chains	Ascend over a gradual SW. slope.										
20.00	Low, flat spur, slopes W.; desc. over a gradual N. slope.										
40.39	The cor. of secs. 28, 29, 32 and 33, a lava stone 16x10x8 ins. firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 1 groove on south and 5 grooves on E. faces. At point for cor. Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.										
	<table style="margin: auto;"> <tr> <td>T23N</td> <td>R3E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td colspan="2" style="text-align: center;">—+—</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> <tr> <td colspan="2" style="text-align: center;">1942</td> </tr> </table>	T23N	R3E	S 29	S 28	—+—		S 32	S 33	1942	
T23N	R3E										
S 29	S 28										
—+—											
S 32	S 33										
1942											
	from which										
	A pine, 12 ins. diam., bears N. 86° E., 195 lks. dist., mkd. T 23 N R 3 E S 28 B T.										
	A pine, 16 ins. diam., bears S. 38½° E., 58 lks. dist., mkd. T 23 N R 3 E S 33 B T.										
	A pine, 3 ins. diam., bears S. 79¼° W., 44 lks. dist., mkd. B T.										
	A pine, 12 ins. diam., bears W. 46¾° W., 93 lks. dist., mkd. T 23 N R 3 E S 29 B T.										
	Land, rolling. Soil, gravelly, 3rd rate. Timber, pine and juniper; undergrowth, none.										

	From the cor. of secs. 27, 28, 33 and 34. S. 88°.32' W., on a true line bet. secs. 28 and 33. Over rolling land, thru scattered timber and undergrowth; along the center of a lane.										
31.00	End of lane; a 4 strand barbed wire fence, bears N. 75 lks. to a fence cor. from which fences bear, northerly and easterly and S. 75 lks. to a fence cor. from which fences bear southerly and easterly.										
31.30	Road, bears N. and S.										
31.50	Drain, course SW.; asc. 15 ft. over an E. slope.										
41.32	The ¼ sec. cor., a lava stone 10x8x8 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. ¼ on N. face. At point for cor. Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.										
	<table style="margin: auto;"> <tr> <td>¼</td> <td>S 28</td> </tr> <tr> <td colspan="2" style="text-align: center;">—+—</td> </tr> <tr> <td>¼</td> <td>S 33</td> </tr> <tr> <td colspan="2" style="text-align: center;">1942</td> </tr> </table>	¼	S 28	—+—		¼	S 33	1942			
¼	S 28										
—+—											
¼	S 33										
1942											

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

from which

A pine, 14 ins. diam., bears N. 36° E., 351 lks.
dist., mkd. $\frac{1}{4}$ S 28 B T.

A juniper, 4 ins. diam., bears S. 74 $\frac{1}{2}$ ° E., 197 lks.
dist., mkd. B T.

Thence,

N. 88° 18' W., on a true line bet. secs. 28 and 33.

Ascend a gentle SE. slope.

10.00 Spur, slopes SE.; desc. 86 ft. over a SW. slope.

24.05 Road, bears N. 70° W. and S. 70° E.

24.95 Wash, 15 lks. wide, 1 ft. deep, course N. 70° W.; asc.
18 ft. over a NE. slope.

40.50 The cor. of secs. 28, 29, 32 and 33.

Land, rolling.

Soil, rocky and gravelly, 3rd rate.

Timber, pine and juniper; undergrowth, none.

N. 0° 24' W., on a true line bet. secs. 28 and 29.

Over rolling land, thru scattered timber; desc. 32 ft.
over a N. slope.

4.65 Wash, 50 lks. wide, 1 ft. deep, course N. 70° W. ; asc.
91 ft. over a S. slope.

5.20 Road, bears N. 70° W. and S. 70° E.

13.10 Slope changes; asc. over a SE. slope.

27.50 Top of ascent; descend over a gentle NW. slope.

40.15 The $\frac{1}{4}$ sec. cor., a lava stone, 16x12x10 ins. firmly set
in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on
W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with the original stone buried alongside, for $\frac{1}{4}$
sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 29 | S 28
 1942

from which

A pine, 3 ins. diam., bears S. 24° E., 258 lks.
dist., mkd. B T.

A juniper, 3 ins. diam., bears S. 30 $\frac{1}{2}$ ° W., 374 lks.
dist., mkd. B T.

Thence,

N. 0° 02' E., on a true line bet. secs. 28 and 29.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

4350

Chains	Descend 15 ft. over a NW. slope.														
27.50	Draw, drains NW.; asc. over a gentle SW. slope.														
29.20	Graded road, bears N. 80° W. to Red Lake Valley and S. 80° E.														
35.00	Low spur, slopes NW.														
40.42	The cor. of secs. 20, 21, 28 and 29, a lava stone, 24x16x10 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 2 grooves on S. and 4 grooves on E. faces. At point for cor. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>T23N</td> <td>R3E</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> <tr> <td colspan="2">1942</td> </tr> </table> </div> <div style="text-align: right;">from which</div> <div style="text-align: center;">bears</div> The SE. corner of S. Pisels' house, N. 65° W. The NW. corner of Lee Pisels' house bears N. 38° 20' E. Raise a mound of stone, 3 ft. base, 2 ft. high W. of cor. Land, rolling. Soil, gravelly, 3rd rate. Timber, pine and juniper; undergrowth, none. ----- From the cor. of secs. 21, 22, 27 and 28. S. 89° 48' W., on a true line bet. secs. 21 and 28. Over rolling land, thru scattered timber; desc. along a general N. slope. 39.50. A 3 strand barbed wire fence, bears S., and N. 150 lks. dist., to a fence cor., from which fences bear easterly, westerly and S. 41.02 Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a stone, 4x4x2 ins., mkd. X deposited at the base, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr> <td>¼</td> <td>S 21</td> </tr> <tr> <td></td> <td>S 28</td> </tr> <tr> <td colspan="2">1942</td> </tr> </table> </div> Descend 102 ft. over a NW. slope. 81.68 A fence cor., from which fences bear easterly and N. 82.04 The cor. of secs. 20, 21, 28 and 29.	T23N	R3E	S 20	S 21	S 29	S 28	1942		¼	S 21		S 28	1942	
T23N	R3E														
S 20	S 21														
S 29	S 28														
1942															
¼	S 21														
	S 28														
1942															

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

Land, rolling.
Soil, gravelly, 3rd rate.
Timber, pine and juniper; undergrowth, none.

N. 0° 02' W., on a true line bet. secs. 20 and 21.

Over nearly level land.

0.75 Enter road, from Red Lake Valley, SW., bears N., thence along center of road.

7.10 Draw, drains W. for 75 lks. then course SW.; enter cultivated land to the E. and W. of road.

9.60 From this point, the SE. cor. of S. Pisels' house, bears S. 50° 30' W. and Lee Pisels' house, bears N. 52° 30' E.

30.20 Leave road, which bears E. to Spring Valley.; leave level cultivated land; asc. 38 ft. over a S. slope.

40.42 The $\frac{1}{4}$ sec. cor., a lava stone 20x10x8 ins. firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 20 \mid \text{S } 21 \\ 1942 \end{array}$$

from which

A pinyon, 3 ins. diam., bears N. 25° E., 64 lks. dist., mkd. B T.

A pinyon, 3 ins. diam., bears N. 74 $\frac{1}{2}$ ° W., 29 lks. dist., mkd. B T.

Thence,

N. 0° 22' E., on a true line bet. secs. 20 and 21.

26.00 Low spur, slopes W.; desc. 15 ft. over a gradual N. slope.

35.65 Wash, 1.00 chain wide, course W.; asc. a gradual S. slope.

40.37 The cor. of secs. 16, 17, 20 and 21, a lava stone 32x16x16 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 3 grooves on S. and 4 grooves on E. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for cor. of secs. 16, 17, 20 and 21, with brass cap mkd.

$$\begin{array}{c} \text{T23N R3E} \\ \text{S } 17 \mid \text{S } 16 \\ \hline \text{S } 20 \mid \text{S } 21 \\ 1942 \end{array}$$

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

LOCK 4350

Chains

from which

A juniper, 3 ins. diam., bears N. $3\frac{1}{2}^{\circ}$ E., 280 lks.
dist., mkd. B T.

A pine, 12 ins. diam., bears S. $69\frac{3}{4}^{\circ}$ E., 295 lks.
dist., mkd. T 23 N R 3 E S 21 B T.

A pine, 3 ins. diam., bears S. 37° W., 257 lks.
dist., mkd. B T.

A juniper, 6 ins. diam., bears N. 30° W., 311 lks.
dist., mkd. T 23 N R 3 E S 17 B T.

Land, S. 30 chs., level; remainder of mile rolling.
Soil, level land, dark loam, 1st rate; hilly land gravelly
and rocky, 3rd rate.
Timber, pine, juniper and pinyon; undergrowth, none.

From the cor. of secs. 15, 16, 21 and 22.

N. $89^{\circ} 16'$ W., on a true line bet. secs. 16 and 21.

Over rolling land, thru scattered timber.

23.45 Road, bears N. 70° E. to Boulin Tank and S. 70° W. to
Red Lake Valley.

40.13 The point for $\frac{1}{4}$ sec. cor., determined from the original
bearing tree.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
ground to bedrock, and in a mound of stone to top, for
 $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 16

 $\frac{1}{4}$ S 21
1942

from which

The old bearing tree:

A pine, 30 ins. diam., bears N. 41° E., 41 lks.
dist., mkd. $\frac{1}{4}$ S B T. I alter the markings on this
tree to read $\frac{1}{4}$ S 16 B T.

New bearing tree:

A pine, 12 ins. diam., bears S. 74° E., 162 lks.
dist., mkd. $\frac{1}{4}$ S 21 B T.

Thence,

S. $89^{\circ} 08'$ W., on a true line bet. secs. 16 and 21.

7.90 Wash, 70 lks. wide, $1\frac{1}{2}$ ft. deep, course S. 60° W.

25.90 Recross wash, 30 lks. wide, $1\frac{1}{2}$ ft. deep, course N. 70° W.

31.40 Recross wash, 30 lks. wide, $1\frac{1}{2}$ ft. deep, course S. 80° W.

40.58 The cor. of secs. 10, 17, 20 and 21.

Land, rolling.
Soil, rocky and gravelly, 3rd rate.
Timber, pine, juniper and pinyon; undergrowth, none.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

N. 0° 23' E., on a true line bet. secs. 16 and 17.

Over rolling land, thru scattered timber and undergrowth; asc. 15 ft. over a gentle S. slope.

33.20 Low ridge, bears E. and W.; desc. a gentle N. slope.

40.13 The $\frac{1}{4}$ sec. cor., a lava stone 18x8x6 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 17 \text{ | S } 16 \\ | \\ 1942 \end{array}$$

from which

A juniper, 6 ins. diam., bears S. 48 $\frac{1}{4}$ ° E., 290 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.

A juniper, 5 ins. diam., bears S. 28° W., 235 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.

Thence,

N. 0° 14' E., on a true line bet. secs. 16 and 17.

Descend a gentle N. slope.

5.00 Draw, drains W.; asc. a gradual S. slope.

13.10 Spur, slopes W.; desc. a N. slope.

40.00 The cor. of secs. 8, 9, 16 and 17, a lava stone 8x8x6 ins. firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 4 grooves on S. and 4 grooves on E. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground; with the original stone buried alongside, for cor. of secs. 8, 9, 16 and 17, with brass cap mkd.

$$\begin{array}{c} \text{T23N R3E} \\ \text{S } 8 \text{ | S } 9 \\ \hline \text{S } 17 \text{ | S } 16 \\ | \\ 1942 \end{array}$$

from which

A pinyon, 8 ins. diam., bears N. 55° E., 342 lks. dist., mkd. T 23 N R 3 E S 9 B T.

A cedar, 3 ins. diam., bears N. 61 $\frac{1}{2}$ ° W., 282 lks. dist., mkd. B T.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly, 3rd rate.

Timber, pine, juniper pinyon and cedar; undergrowth, none.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4850

Chains	
	From the cor. of secs. 9, 10, 15 and 16.
	N. 86° 01' W., on a true line bet. secs. 9 and 16.
	Over rolling land, thru scattered timber; desc. a NW. slope.
9.40	Drain, course S. 60° W.; asc. 15 ft. over an E. slope.
23.50	Ridge, bears NE. and SW.; desc. a W. slope.
39.94	Proportional distance.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S\ 9}{S\ 16}$ 1942
	from which
	A juniper, 20 ins. diam., bears N. 82° E., 126 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.
	A pinyon, 12 ins. diam., bears S. 30° E., 68 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
	Descend a gentle W. slope.
45.65	Draw, drains NW.; asc. over a NE. slope.
58.75	Ridge, bears NW. and S. approx. 3 chs. N. to a saddle; desc. 46 ft. over a W. slope.
79.88	The cor. of secs. 8, 9, 16 and 17.
	Land, rolling.
	Soil, rocky and gravelly, 3rd rate.
	Timber, juniper and pinyon; undergrowth, none.

	N. 0° 07' E., on a true line bet. secs. 8 and 9.
	Over rolling land, thru scattered timber.
	Descend a gentle NW. slope.
8.70	Wash, 20 lks. wide, 2 ft. deep, course S. 50° W.; asc. 15 ft. over a S. slope.
20.00	Low, flat spur, slopes W.; desc. a NW. slope.
26.90	Drain, course SW.; asc. 38 ft. over a SW. slope.
29.10	Road, bears S. 60° W. and N. 60° E.
40.02	The $\frac{1}{4}$ sec. cor., a lava stone 16x12x8 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face.
	At point for cor.
	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the original stone buried alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.,

Chains

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 8 \mid \text{S } 9 \\ | \\ 1942 \end{array}$$

from which

A juniper, 6 ins. diam., bears N. $37\frac{1}{2}^{\circ}$ E., 185 lks.
dist., mkd. $\frac{1}{4}$ S 9 B T.

A juniper, 14 ins. diam., bears N. $73\frac{1}{2}^{\circ}$ W., 109 lks.
dist., mkd. $\frac{1}{4}$ S 8 B T.

Thence,

N. $1^{\circ} 17'$ W., on a true line bet. secs. 8 and 9.

Ascend a gentle W. slope.

16.90 Spur, slopes W.; continue ascent along a W. slope.

22.80 Spur, slopes SW.; desc. 15 ft. over a W. slope.

39.95 The cor. of secs. 4, 5, 8 and 9, a lava stone 10x8x3 ins.
firmly set in a mound of stone, 2 ft. base, 1 ft. high,
mkd. 5 grooves on S. and 4 grooves on E. faces.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, with the original stone buried alongside, for
cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

$$\begin{array}{c} \text{T23N R3E} \\ \text{S } 5 \mid \text{S } 4 \\ \hline \text{S } 8 \mid \text{S } 9 \\ 1942 \end{array}$$

from which

A pinyon, 5 ins. diam., bears N. 50° E., 206 lks.
dist., mkd. T 23 N R 3 E S 4 B T.

A juniper, 3 ins. diam., bears S. 7° E., 269 lks.
dist., mkd. B T.

A pinyon, 6 ins. diam., bears S. $81\frac{1}{4}^{\circ}$ W., 210 lks.
dist., mkd. T 23 N R 3 E S 8 B T.

A pinyon, 6 ins. diam., bears N. 33° W., 114 lks.
dist., mkd. T 23 N R 3 E S 5 B T.

Land, rolling.

Soil, rocky and gravelly, 3rd rate.

Timber, pine, pinyon and juniper; undergrowth, none.

From the cor. of secs. 3, 4, 9 and 10.

N. $87^{\circ} 02'$ W., on a true line bet. secs. 4 and 9.

Over rolling land, thru scattered timber; desc. 15 ft.
over a general W. slope.

18.00 Ravine, course NW.; asc. 5 ft. over a NE. slope.

30.00 Slope changes; desc. 16 ft. over a N. slope; enter heavy
timber, bears N. and S.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4850

Chains 41.21	<p>Proportional distance.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\frac{\frac{1}{4} \text{ S } 4}{\text{S } 9}$ <p style="text-align: center;">1942</p> <p style="text-align: right;">from which</p> <p>A juniper, 8 ins. diam., bears N. $6\frac{1}{4}^{\circ}$ W., 23 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.</p> <p>A juniper, 7 ins. diam., bears S. $30\frac{1}{2}^{\circ}$ E., 93 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.</p>
50.00	Ridge, bears SE. and NW.; desc. 147 ft. over a W. slope.
60.00	Slope changes to a SW. slope.
82.42	The cor. of secs. 4, 5, 8 and 9.
	<p>Land, rolling. Soil, rocky and gravelly, 3rd rate. Timber, pine, juniper and pinyon; undergrowth, none.</p> <p>-----</p> <p>N. $0^{\circ} 43'$ W., on a true line bet. secs. 4 and 5.</p> <p>Over rolling land, thru scattered timber and undergrowth; asc. over a W. slope.</p>
15.00	Ridge, bears N. 60° W. and S. 50° E.; desc. 38 ft. over a N. slope.
24.50	Road, bears N. 60° E. and S. 50° W.
37.90	Recross road, bears S. 60° E. and N. 70° W.
39.13	<p>The $\frac{1}{4}$ sec. cor., a lava stone 10x10x14 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face.</p> <p>At point for cor.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> $\frac{\frac{1}{4}}{\text{S } 5 \text{ } \text{S } 4}$ <p style="text-align: center;">1942</p> <p style="text-align: right;">from which</p> <p>A pine, 8 ins. diam., bears S. $37\frac{1}{2}^{\circ}$ E., 53 lks. dist., mkd. $\frac{1}{4}$ S 4 B T.</p> <p>A pine, 8 ins. diam., bears N. $63\frac{1}{2}^{\circ}$ W., 280 lks. dist., mkd. $\frac{1}{4}$ S 5 B T.</p>
	<p>Thence,</p> <p>N. $3^{\circ} 21'$ E., on a true line bet. secs. 4 and 5.</p> <p>Ascend 214 ft. over a S. slope.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains	
0.50	Wash, 20 lks. wide, course N. 70° W.
13.45	Top of a hill on a ridge, bears NW. and SE.; desc. 117 ft. over a NE. slope.
29.20	Center of a draw, 5.00 chs. wide, drains NE.; asc. 23 ft. over a SE. slope.
44.48	The cor. of secs. 4, 5, 32 and 33, on N. bdy. of Tp. Land, rolling. Soil, rocky and gravelly, 3rd rate. Timber, pine, pinyon and juniper; undergrowth, 2nd growth pine. ----- From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp., an iron post, 2 ins. diam., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. and witnessed as described in the official record. N. 0° 57' E., on a true line bet. secs. 31 and 32. Over rolling land, thru scattered timber.
6.35	Wash, 8 lks. wide, 1 ft. deep, course NW.
20.95	Recross wash, 10 lks. wide, 3 ft. deep, course N. 20° E.
27.80	Recross wash, 10 lks. wide, 3 ft. deep, course NW., approx. 4 chs. to an earth reservoir.
29.30	Leave little valley, asc. a SW. slope.
38.50	Low, wide spur, slopes NW.; desc. over a N. slope.
43.46	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> $\frac{1}{4}$ S 31 S 32 1942 </div> <div style="text-align: right; margin-right: 20px;">from which</div> <p>A pine, 12 ins. diam., bears S. 39$\frac{1}{4}$° E., 308 lks. dist., mkd. $\frac{1}{4}$ S 32 B T.</p> <p>A pine, 24 ins. diam., bears S. 9$\frac{3}{4}$° W., 260 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.</p> <p>The NW. cor. of D. S. Bird's house bears N. 88$\frac{1}{2}$° E., 8.41 chs. dist.</p> <p>Lookout tower on Kendrick Mountain, bears N. 69° 27' E.</p>
43.85	Wash, 30 lks. wide, 2 ft. deep, course NW.
44.31	Wire fence, bears S. 75° E., and N. 75° W. approx. 2 chs. to a fence cor., from which fences bear N., S., and S. 75° E.
44.45	Road, bears N. 75° W. and S. 75° E.
44.55	Enter cultivated land, bears N. 75° W. and S. 75° E.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4850

Chains
80.91

A 3 strand barbed wire fence, bears easterly, and westerly approx. 2 chs. dist. to a fence cor., from which fences bear northerly, southerly and easterly; leave cultivated field.

86.92

The point for the cor. of secs. 29, 30, 31 and 32, determined from original bearing trees.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

T 23 N	R 3 E
S 30	S 29
S 31	S 32
1942	

from which

The old bearing trees:

A pine stump, 32 ins. diam., bears N. $50\frac{1}{2}^{\circ}$ E., 104 lks. dist., mkd. B T.

A pine, 30 ins. diam., bears S. $84\frac{1}{4}^{\circ}$ E., 115 lks. dist., mkd. T 23 N R 3 E S 32 B T.

A pine, 28 ins. diam., bears N. $84\frac{1}{4}^{\circ}$ W., 84 lks. dist., mkd. T 23 N R 3 E S 30 B T.

New bearing trees:

A pine, 10 ins. diam., bears N. $53\frac{1}{2}^{\circ}$ E., 209 lks. dist., mkd. T 23 N R 3 E S 29 B T.

A pine, 12 ins. diam., bears S. $36\frac{1}{4}^{\circ}$ W., 237 lks. dist., mkd. T 23 N R 3 E S 31 B T.

Land, S. $\frac{1}{2}$, rolling; N. $\frac{1}{2}$, nearly level.

Soil, on rolling land, gravelly, 3rd rate; on level land, 1st and 2nd rates.

Timber, pine and juniper; undergrowth, none.

From the cor. of secs. 28, 29, 32 and 33.

N. $86^{\circ} 02'$ W., on a true line bet. secs. 29 and 32.

Over rolling land, thru scattered timber.

38.94 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, with a stone mkd. X deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

	S 29
$\frac{1}{4}$	-----
	S 32
	1942

Descend 33 ft. over a NW. slope.

39.79 A 3 strand barbed wire fence, bears N. and S.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains	
59.95	Dim road, bears N. and S.
60.14	A 3 strand barbed wire fence, bears N. and S.
77.88	The cor. of secs. 29, 30, 31 and 32. Land, rolling. Soil, rocky and gravelly, 3rd rate. Timber, pine and juniper; undergrowth, none.

	S. 89° 54' W., on a true line bet. secs. 30 and 31. Over nearly level land, thru scattered timber.
1.90	A 4 strand barbed wire fence, along the E. side of a road, bears N. 0½° W. and S. 0½° E.
2.30	Center of road, bears N. 0½° W., S. 0½° E.
2.70	A 3 strand barbed wire fence, along the W. side of road, bears N. 0½° W., and S. 0½° E. 5.42 chs. dist., to a fence cor., from which fences bears N. 0½° W. and N. 85¾° W.; enter cultivated land.
22.20	A 4 strand barbed wire fence, bears N. 0¼° W., and S. 0¼° E. approx. 90 lks. dist. to a fence cor., from which fences bear N. 0¼° W. and westerly.
40.99	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in the ground, for ¼ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{S \ 30}{S \ 31}$ 1942 dig pits E. and W. of cor., 3 ft. dist.
55.69	A 3 strand barbed wire fence, bears NW., and SE. approx. 1.50 chs. dist. to a fence cor. from which fences bear N. 85¾° W., S. 85¾° E. and NW.; leave cultivated field, bears NW. and SE.; enter pasture land.
57.60	Right bank of a wash, 3 ft. high, bears NW. and SE.
58.45	Left bank of a wash, 3 ft. high, bears NW. and SE.
75.70	A 3 strand barbed wire fence, along the N. side of a road, bears S. 85¾° E. and N. 85¾° W.
80.42	The cor. of secs. 25, 30, 31 and 36, on W. bdy. of Tp. Land, nearly level. Soil, E. 60 chs., dark loam, 1st and 2nd rates; remainder of mile, gravelly, 3rd rate. Timber, pine; undergrowth, none.

	From the cor. of secs. 29, 30, 31 and 32. N. 2° 12' W., on a true line bet. secs. 29 and 30. Over gently rolling land, thru scattered timber.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.,

BOOK 4850

Chains	
3.90	Enter cultivated field, bears E. and W.
15.05	A 3 strand barbed wire fence, bears E., and W. approx. 1 ch. dist., to a fence cor., from which fences bear northerly, southerly and easterly.
30.78	Leave cultivated land, bears E. and W.
31.45	The SW. cor. of a farm house, bears E. 2 lks. dist.
31.78	The NW. cor. of a farm house.
32.10	A 2 strand barbed wire fence, bears E., and W. approx. 1 ch. dist. to a fence cor., from which fences bear northerly, southerly and easterly.
37.60	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> $\frac{1}{4}$ S 30 S 29 1942 </div> <div style="text-align: right; margin-right: 100px;">from which</div> <p>A juniper, 3 ins. diam., bears N. $38\frac{1}{2}^{\circ}$ E., 188 lks. dist., mkd. B T.</p> <p>A pine, 24 ins. diam., bears S. $10\frac{1}{2}^{\circ}$ W., 320 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.</p> <p>The top of Claud Thomasson's house, bears S. $79^{\circ} 45'$ W.</p>
38.70	Wash, 25 lks. wide, 2 ft. deep, course N. 60° W.
40.80	Wash, 15 lks. wide, $1\frac{1}{2}$ ft. deep, course N. 60° W.; asc. 15 ft. over a SW. slope.
44.70	A 3 strand barbed wire fence, bears E., and W. approx. 60 lks. to a fence cor., from which fences bear E., and S. along the E. side of a road.
52.60	Low, flat spur, slopes W.; desc. a gentle NW. slope.
72.60	Enter E. side of road, bears N. and S.
75.20	The point for cor. of secs. 19, 20, 29 and 30, at the intersection of the center lines of county roads from two directions, W. and S. Information obtained from the field book and plat on file in the office of the County Surveyor of Coconino County of a survey made by Frank Goodman in 1917 indicates that the original corner was found at this point. At point for cor. Set a lava stone 16x8x6 ins., 12 ins. below the surface of the road, for cor. of secs. 19, 20, 29 and 30, mkd. X, from which The NW. cor. of the foundation of the old Red Lake school house, bears S. $21^{\circ} 57'$ E., 2.636 chs. dist. The NE. cor. of the new Red Lake school house, bears S. $78^{\circ} 38'$ W., 4.25 chs. dist.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

The SE. cor. of a dwelling house, bears S. 83° 25' W.,
7.91 chs. dist.

Top of Claud Thomasson's house, bears S. 6° 14' W.

At a point, N. 45° E., 50 lks. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for witness cor. of secs. 19, 20, 29 and 30, with
brass cap mkd.

T23N	R3E
S 19	S 20
S 30	S 29
W C	
1942	

At a point, S. 45° W., 50 lks. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for witness cor. of secs. 19, 20, 29 and 30, with
brass cap mkd.

		W C
T23N	R3E	
S 19	S 20	
S 30	S 29	
		1942

Land, rolling.
Soil, S. 30 chs., 2nd rate; remainder of mile, rocky and
gravelly, 3rd rate.
Timber, pine and juniper; undergrowth, none.

From the cor. of secs. 20, 21, 28 and 29.

West, on a true line bet. secs. 20 and 29.

Over rolling land, thru scattered timber.

0.50 Road, bears NE. to Spring Valley and SW. to Red Lake
Valley.

7.00 Road, bears N. to farm house and S. to graded road.

7.50 Enter wash, from NE. course W.

10.05 Leave wash, 10 lks. wide, course N. 60° W.

27.20 Low ridge, bears N. 60° W. and S. 60° E.; desc. over a
SW. slope.

30.40 Recross road, bears NW. to Red Lake Valley and SE. to
Spring Valley.

40.19 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd:

	S 20
$\frac{1}{4}$	
	S 29
1942	

from which

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains	
	<p>A pinyon, 8 ins. diam., bears N. $21\frac{1}{4}^{\circ}$ W., 149 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.</p> <p>A cedar, 10 ins. diam., bears S. $82\frac{1}{2}^{\circ}$ E., 179 lks. dist., mkd. $\frac{1}{4}$ S 29 B T.</p>
41.90	Dim road, bears NW. and SE.
44.28	Enter draw, drains NW.
46.20	Leave draw, asc. 15 ft. over a NE. slope.
49.30	An earth reservoir, in draw, bears N., approx. 2 chs. dist.
59.45	Spur, slopes NW.; desc. 59 ft. over a gentle NW. slope.
80.38	The cor. of secs. 19, 20, 29 and 30.
	<p>Land, rolling. Soil, gravelly, 3rd rate. Timber, pine, cedar, pinyon and juniper; undergrowth, 2nd growth pine.</p> <p>-----</p> <p>N. $85^{\circ} 57'$ W., on true line bet. secs. 19 and 30.</p> <p>Over nearly level land, along the center of county road, with cultivated land to the N. of road.</p>
39.78	<p>Proportional distance.</p> <p>Set a lava stone, $16 \times 8 \times 3$ ins., 12 ins. below the surface of the road, for $\frac{1}{4}$ sec. cor., mkd. X.</p> <p>At a point, N. 45° E., 52 lks. dist.,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S 19}{WC S 30}$ 1942 </p> <p>At a point, S. 45° W., 52 lks. dist.,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{WC S 19}{S 30}$ </p> <p>Continue along center of county road, with cultivated land to the N. and S. of road.</p>
77.88	<p>The cor. of secs. 19, 24, 25 and 30, on W. bdy. of Tp.</p> <p>Land, nearly level. Soil, 1st rate. Timber, none; undergrowth, none.</p> <p>-----</p> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. $0^{\circ} 06'$ W., on a true line, bet. secs. 19 and 20.</p> <p>Over rolling land, thru scattered timber; along the E. side of a wire fence, with cultivated land to the W.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains
0.50 Leave county road, bears NE. to Spring Valley.
16.40 Draw, drains SW.; asc. 32 ft. over a gentle S. slope.
27.00 Road, bears W. to ranch house, and E. for 50 lks. then S.;
Leave cultivated land on W. side of line.
33.40 Spur, slopes NW.; a fence cor., from which fences bear
NW. and southerly.
40.39 The point for $\frac{1}{4}$ sec. cor., determined from original bearing trees.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 19 \mid \text{S } 20 \\ | \\ 1942 \end{array}$$

from which

The old bearing trees:

A pine, 24 ins. diam., bears N. 10° E., 54 lks. dist., mkd. $\frac{1}{4}$ S B T. I alter the markings on this tree to read, $\frac{1}{4}$ S 20 B T.

A pine, 30 ins. diam., bears S. 30° W. 59 lks. dist., mkd. $\frac{1}{4}$ S B T. I alter the markings on this tree to read, $\frac{1}{4}$ S 19 B T.

Thence,

N. $0^{\circ} 02'$ E., on a true line bet. secs. 19 and 20.

0.80 Wash, 50 lks. wide, course W. for 2 chs. then S. 60° W.;
asc. 24 ft. over a S. slope.
3.40 Top of steep ascent from wash, bears NE. and SW.; asc.
gradually along the top of a low ridge, bears N. and SW.
33.40 Leave top of ridge, bears S. and NE.; continue ascent.
40.26 The cor. of secs. 17, 18, 19 and 20, a mound of stone,
3 ft. base, 1 ft. high. I find no marked stone.

At point for cor. in center of mound.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 17, 18, 19 and 20, with brass cap mkd.

$$\begin{array}{c} \text{T23N R3E} \\ \text{S } 18 \mid \text{S } 17 \\ \hline \text{S } 19 \mid \text{S } 20 \\ | \\ 1942 \end{array}$$

from which

A pine, 6 ins. diam., bears N. $38\frac{1}{2}^{\circ}$ E., 221 lks. dist., mkd. T 23 N R 3 E S 17 B T.

A pinyon, 6 ins. diam., bears S. 73° E., 230 lks. dist., mkd. T 23 N R 3 E S 20 B T.

A juniper, 3 ins. diam., bears S. $36\frac{1}{4}^{\circ}$ W., 250 lks. dist., mkd. B T.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4850

Chains

A juniper, 3 ins. diam., bears N. 67° W., 228 lks. dist., mkd. B T.

This cor. is located in a fence corner, from which fences bear northwesterly and northeasterly.

Land, rolling.

Soil, gravelly and rocky, 3rd rate.

Timber, pine and juniper; undergrowth, none.

From the cor. of secs. 16, 17, 20 and 21.

N. $89^{\circ} 58'$ W., on a true line bet. secs. 17 and 20.

Over rolling land, thru scattered timber; asc. a gentle SE. slope.

28.90 Dim road, bears N. and S.

40.26 The $\frac{1}{4}$ sec. cor., a lava stone, 10x10x4 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 17}{S 20}$$

1942

from which

A juniper, 30 ins. diam., bears N. $11\frac{1}{2}^{\circ}$ W., 350 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.

A pinyon, 6 ins. diam., bears S. 41° W., 345 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.

This cor. is located on top of a low, flat spur, slopes SW.

Thence,

S. $89^{\circ} 50'$ W., on a true line bet. secs. 17 and 20.

Descend over a W. slope.

6.20 Center of a draw, drains SW.; asc. over a SE. slope.

24.20 Low ridge, bears N. 60° E. and S. 60° W.; desc. over a W. slope.

29.70 Road, bears N. 80° E., and S. 80° W.

40.30 Road, bears N. and S.

40.41 The cor. of secs. 17,,18, 19 and 20.

Land, rolling.

Soil, gravelly, 3rd rate.

Timber, juniper and pinyon; undergrowth, none.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

N. 86° 04' W., on a true line bet. secs. 18 and 19.

Over rolling land, thru scattered timber; desc. over a gentle SW. slope, along the N. side of a 3 strand barbed wire fence.

20.00 Low spur, slopes SW.; desc. over a NW. slope.

39.88 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} \text{S } 18 \\ \hline \text{S } 19 \\ 1942 \end{array}$$

from which

A juniper, 3 ins. diam., bears N. 51° W., 245 lks. dist., mkd. B T.

A juniper, 14 ins. diam., bears S. 39 $\frac{3}{4}$ ° E., 255 lks. dist., mkd. $\frac{1}{4}$ S 19 B T.

Descend along a SW. slope.

40.30 A fence cor. bears S., 20 lks. dist., from which fences bear easterly and southerly.

63.00 A 3 strand barbed wire fence, bears N. and S.

68.60 Enter cultivated field, bears N. and S.

77.60 Leave cultivated land, bears N. and S.

77.64 A 4 strand barbed wire fence, along the E. side of a county road, bears N. and S.

77.86 The cor. of secs. 13, 18, 19 and 24, on W. bdy. of Tp.

Land, E. 70 chs. rolling; W. 10 chs. level.

Soil, rolling land, gravelly, 3rd rate; level land, 1st rate.

Timber: juniper; undergrowth, none.

From the cor. of secs. 17, 18, 19 and 20.

N. 0° 08' W., on a true line bet. secs. 17 and 18.

Over rolling land, thru scattered timber; along the W. side of a wire fence, bears northeasterly.

25.00 Low ridge, bears E. and W.; desc. over a gradual N. slope.

29.70 Unimproved road, bears NE. and SW.

40.09 The $\frac{1}{4}$ sec. cor., a mound of stone, 2 ft. base, 1 ft. high, I find no marked stone. No evidence of original bearing tree.

At point for cor., in center of mound.

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, to bedrock, with a stone mkd. X deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 18 \text{ | S } 17 \\ | \\ 1942 \end{array}$$

Thence,

N. 1° 48' E., on a true line bet. secs. 17 and 18.

Continue descent over a gradual N. slope.

- 9.20 Draw, drains W.; asc. a gradual S. slope.
- 15.90 A 4 strand barbed wire fence, bears E. and W.
- 17.80 Gully, 30 lks. wide, course W.; asc. over a gradual S. slope.
- 19.00 Enter cultivated land.
- 27.70 Leave cultivated land.
- 31.50 A 3 strand barbed wire fence, bears E. and W.
- 32.00 Unimproved road, bears N. 70° E., and S. 70° W.
- 40.27 At this point, determined by the method of double proportional measurement.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the cor. of secs. 7, 8, 17 and 18, with brass cap mkd.

$$\begin{array}{c} \text{T23N R3E} \\ \text{S } 7 \text{ | S } 8 \\ \hline \text{S } 18 \text{ | S } 17 \\ 1942 \end{array}$$

from which

A pinyon, 9 ins. diam., bears N. 27° E., 160 lks. dist., mkd. T 23 N R 3 E S 8 B T.

A pinyon, 7 ins. diam., bears S. 51½° E., 161 lks. dist., mkd. T 23 N R 3 E S 17 B T.

A pinyon, 5 ins. diam., bears S. 78½° W., 235 lks. dist., mkd. T 23 N R 3 E S 18 B T.

A juniper, 5 ins. diam., bears N. 71° W., 200 lks. dist., mkd. T 23 N R 3 E S 7 B T.

Land, rolling.

Soil, rocky and gravelly, 3rd rate.

Timber, pine, juniper and pinyon; undergrowth, none.

From the cor. of secs. 8, 9, 16 and 17.

N. 89° 56' W., on a true line bet. secs. 8 and 17.

Over rolling land, thru scattered timber.

- 25.50 Dim, unimproved road, bears N. 20° E., and S. 20° W.
- 35.00 Draw, drains NW.
- 39.925 Proportional distance.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 8}{S 17}$$

1942

from which

A pine, 13 ins. diam., bears N. 11° W., 175 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.

A pine, 10 ins. diam., bears S. 49° W., 295 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.

- 42.20 A 3 strand bared wire fence, bears NE. and SW.
43.40 Wash, 30 lks. wide, course SW.; asc. a gradual SE. slope.
44.00 Enter cultivated land, bears NE. and SW.
49.94 Ranch house, bears N. approx. 20 chs. dist.
62.60 A 3 strand barbed wire fence, bears N. 70° E., and S. 70° W.
63.00 Unimproved road, bears N. 70° E. and S. 70° W.
63.50 Enter heavy timber, bears N. 70° E. and S. 70° W.
79.85 The cor. of secs. 7, 8, 17 and 18.

Land, rolling.

Soil, cultivated area, sandy loam, 1st and 2nd rates; the remainder, gravelly, 3rd rate.

Timber, pine, juniper and pinyon; undergrowth, none.

N. 86° 06' W., on a true line, bet. secs. 7 and 18.

Over rolling land, thru heavy timber; asc. 89 ft. over a general E. slope.

- 12.10 Spur, slopes S.; desc. 17 ft. over a W. slope.
26.60 Wash, 10 lks. wide, course S.; asc. 58 ft. over a SE. slope.
39.91 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 7}{S 18}$$

1942

from which

A juniper, 8 ins. diam., bears N. 19° W., 170 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.

A juniper, 7 ins. diam., bears S. 18 $\frac{1}{4}$ ° E., 67 lks. dist., mkd. $\frac{1}{4}$ S 18 B T.

Descend 55 ft. over a broken SW. slope.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains	
60.80	Wash, 10 lks. wide, course SW., thence along a S. slope.
77.30	A 4 strand barbed wire fence, bears N. and S.
78.04	The cor. of secs. 7, 12, 13 and 18, on W. bdy. of Tp. Land, rolling. Soil, rocky and gravelly, 3rd rate. Timber, pinyon and juniper; undergrowth, algerita.

	From the cor. of secs. 7, 8, 17 and 18. N. 1° 02' W., on a true line bet. secs. 7 and 8. Over rolling land, thru heavy timber; asc. a gradual S. slope.
36.50	Spur, slopes SE.; desc. 26 ft. over a NW. slope.
40.27	The $\frac{1}{4}$ sec. cor., a pine, 12 ins. diam., mkd. $\frac{1}{4}$ S on W. face, from which, the original position of old bearing tree, a pine, 16 ins. diam., (dead, lying on ground) bears S. 47 $\frac{1}{2}$ ° E., 63 lks. dist., markings not visible. Thence, N. 0° 05' E., on a true line bet. secs. 7 and 8.
0.10	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 7 S 8 W C 1942
	from which
	A pine, 20 ins. diam., bears S. 9 $\frac{1}{2}$ ° E., 39 lks. dist., mkd. W C $\frac{1}{4}$ S 8 B T.
	A pinyon, 5 ins. diam., bears N. 20° W., 94 lks. dist., mkd. W C $\frac{1}{4}$ S 7 B T.
	Descend 22 ft. over an E. slope.
5.00	Ravine, course SE.; asc. 272 ft. over a SW. slope.
6.20	Dim, unimproved road, bears NW, and SE.
20.55	Ridge, bears E. and N.; desc. 38 ft. along the top of ridge.
25.20	Leave top of ridge, bears NE. and S.; asc. 22 ft. over a W. slope.
30.40	Top of ascent; desc. 62 ft. over a NW. slope.
35.00	Slope changes; asc. 27 ft. over a SW. slope.
37.00	Top of a mountain, bears E. and W.
39.56	The point for cor. of secs. 5, 6, 7 and 8, determined from an original bearing tree. At point for cor. Set an iron post, 3 ft. long, 2 in. diam., 28 ins. in the

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains

ground, for cor. of secs. 5, 6, 7 and 8, with brass cap
mkd.

T23N R3E	
S 6	S 5

S 7	S 8
1942	

from which

An old bearing tree:

A pine, 10 ins. diam., bears S. 20° W., 6 lks.
dist., mkd. T 23 N R 3 E S 7 B T.

No evidence of SE. bearing tree.

New bearing trees:

A pinyon, 5 ins. diam., bears N. 21 $\frac{3}{4}$ ° E., 17 lks.
dist., mkd. T 23 N R 3 E S 5 B T.

A pinyon, 3 ins. diam., bears S. 87 $\frac{1}{4}$ ° E., 37 lks.
dist., mkd. T 23 N R 3 E S 8 B T.

A pinyon, 3 ins. diam., bears N. 9 $\frac{1}{2}$ ° W., 53 lks.
dist., mkd. T 23 N R 3 E S 6 B T.

Land, S. $\frac{1}{2}$, rolling; N. $\frac{1}{2}$, mountainous.

Soil, rocky and gravelly, 2nd and 3rd rates.

Timber, pine, pinyon and juniper; undergrowth, 2nd growth
pine and algerita.

From the cor. of secs. 4, 5, 8 and 9.

N. 89° 53' W., on a true line bet. secs. 5 and 8.

Over mountainous land, thru scattered timber; desc. 30 ft.
over a W. slope.

6.70 Dim road, bears SW. and N.

14.20 Wash, 10 lks. wide, 1 ft. deep, course S. 20° W.; asc.
30 ft. over an E. slope.

15.10 Road, bears N. 20° E. and S. 20° W.

40.11 The $\frac{1}{4}$ sec. cor., a lava stone 16x12x8 ins., set in a
mound of stone, 3 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the
ground to bedrock, with the original stone buried along
side, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 5	
$\frac{1}{4}$	-----
S 8	
1942	

from which

A juniper, 20 ins. diam., bears N. 42 $\frac{1}{2}$ ° E., 113 lks.
dist., mkd. $\frac{1}{4}$ S 5 B T.

A pinyon, 10 ins. diam., bears S. 82 $\frac{1}{4}$ ° E., 52 lks.
dist., mkd. $\frac{1}{4}$ S 8 B T.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

BOOK 4350

Chains	
	No evidence of original bearing tree.
	Thence,
	S. 89° 55' W., on a true line bet. secs. 5 and 8.
6.55	Wash, 10 lks. wide, course S. 20° E.
12.55	Road, bears S. 30° E. and N. 30° W.
16.75	Ravine, course S. 30° E.; asc. 25 ft. over a NE. slope-
38.05	Spur, slopes NW.; desc. 26 ft. over a W. slope.
39.59	The cor. of secs. 5, 6, 7 and 8.
	Land, W. $\frac{1}{2}$, mountainous; E. $\frac{1}{2}$, rolling. Soil, rocky and gravelly, 3rd rate. Timber, Pine, juniper and pinyon; undergrowth, 2nd growth pine and algerita.

	N. 86° 52' W., on a true line bet. secs. 6 and 7.
	Over mountainous land, thru heavy timber; desc. 101 ft. over a W. slope.
7.35	Wash, 10 lks. wide, 1 ft. deep, course SW.; thence along a S. slope.
13.25	Wash, 10 lks. wide, 1 ft. deep, course S. 20° E.
15.45	Recross wash, course N. 20° E.; asc. 277 ft. over a NE. slope.
25.60	Ravine, course N.
38.17	Proportional distance.
	Set an iron post. 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 6 \\ S 7 \\ 1942 \end{array}$
	from which
	A pine, 14 ins. diam., bears N. 59° W., 35 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.
	A pine, 20 ins. diam., bears S. 39° E., 72 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.
	Asc. 89 ft. over a NE. slope.
44.35	High spur, slopes N. from a mountain approx. 15 chs. S.; desc. 94 ft. over a NW. slope.
48.85	Head of a ravine, course NW.; asc. 11 ft. over a NE. slope.
52.95	Spur, slopes NW.; desc. 288 ft. over a NW. slope.
60.45	Ravine, course N. 30° W.
74.79	A 4 strand barbed wire fence, bears irregularly N. and S.
74.94	The cor. of secs. 1, 6, 7 and 12, on W. bdy. of Tp.

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

Chains	<p>Land, mountainous. Soil, rocky and gravelly, 3rd rate. Timber, pine, pinyon and juniper; undergrowth, 2nd growth pine.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8. N. 2° 42' E., on a true line bet. secs. 5 and 6. Over mountainous land, thru heavy timber; desc. 138 ft. along a W. slope.</p> <p>6.50 Spur, slopes N. from SE., continue descent along top of same.</p> <p>13.00 Toe of the spur.</p> <p>14.50 Ravine, course SE.; asc. 352 ft. over a SE. slope.</p> <p>15.40 Dim, unimproved road, bears E. and W.</p> <p>35.63 Slope changes, desc. 15 ft. over an E. slope.</p> <p>37.83 Slope changes; asc. 35 ft. over a SE. slope.</p> <p>41.70 Top of high hill, bears E. and W. Desc. 25 ft.</p> <p>42.14 Proportional distance.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S 6 S 5 1942 </div> <p style="text-align: right;">from which</p> <p>A pinyon, 6 ins. diam., bears S. 55° E., 28 lks. dist., mkd. $\frac{1}{4}$ S 5 B T.</p> <p>A pinyon, 7 ins. diam., bears S. 10° W., 28 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.</p> <p>Continue descent 565 ft. over NE. slope to cor.</p> <p>50.00 Ravine, course NE.</p> <p>53.00 Spur, slopes NE.</p> <p>62.77 Wash, 15 lks. wide, course NE.</p> <p>83.62 The cor. of secs. 5, 6, 31 and 32, on N. bdy. of the Tp.</p> <p>Land, mountainous. Soil, rocky, 3rd rate. Timber, pinyon, pine and juniper; undergrowth, cliff rose, algerita and oak.</p> <hr/>
--------	---

Dependent Resurvey of the Subdivisional Lines of
T. 23 N., R. 3 E.

For final test of solar attachments, see the field notes of the exterior and subdivisional lines of T. 23 N., R. 4 E., resurveyed under this group.

General Description.

T. 23 N., R. 3 E. is located entirely in the Kaibab National Forest. The land in this township is mostly rolling. There are several mountains in the northeast part, and high spurs in the southeast part, which slope westerly from Sitgreaves Mountain which is located in the township to the E. The mean elevation of the township is about 7000 ft. above sea level.

The soil on the mountainous and rolling land is rocky and gravelly of 3rd rate. In Red Lake Valley in the southwest part of the township and in the little valleys along draws in the central and south-central part, the soil is volcanic ash and sandy loam of 1st and 2nd rates.

There is a scattered growth of pine, juniper and pinyon timber throughout the entire township, with a dense growth of the same variety of timber in the mountainous areas.

The lands in Red Lake Valley and the small valleys draining into it are privately owned and are under cultivation, in the production of beans and small grain. Other privately owned lands which are under cultivation are located along the draws in the central and south-central part of the township. The rolling and mountainous land has a good stand of native grass and is used for sheep and cattle grazing during the Summer months. There were no springs observed within the township during the survey. Water for stock is furnished by numerous earth reservoirs which have been constructed by the U. S. Forest Service along the draws and washes; the largest of these being Boulin Tank which is located in the NE. $\frac{1}{4}$ and the NW. $\frac{1}{4}$ of sec. 11. A ditch approximately $1\frac{1}{2}$ mile long has been constructed in secs. 11 and 13 to catch the run off water from the mountains to the east, for this reservoir.

A graded and surfaced county road enters the township on the W. bdy. at the cor. of secs. 19, 24, 25 and 30 and traverses bet. secs. 19 and 30, and thru secs. 20, 29, 21, 22, 23, 14 and 13, leaving the township about 13 chs. N. of the $\frac{1}{4}$ sec. cor. of secs. 13 and 18. There are numerous secondary roads throughout the township and several U. S. Forest Service Fire roads traverse the high spurs of Sitgreaves Mountain in secs. 25, 26, 35 and 36.

No indications of mineral were observed in the township during the progress of the survey.

85

4-680
(Revised May 1934)

UNITED STATES
DEPARTMENT OF THE INTERIOR
~~GENERAL LAND OFFICE~~

BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
C. Richard Blount	Principal Assistant.
Mike Knezevich	Principal Assistant.
John Boggs	Truckdriver.
Glen A. Bush	Chainman.
Ralph L. Lee	Chainman.
Roy West	Chainman and Axeman.
Arthur G. Dodds	Flagman.
Gladwyn Gregory	Flagman.
John W. Beach, Jr.	Axeman.
James F. Burrows	Axeman.
Wesley B. Farley	Axeman.
Stanley J. Jarocha	Axeman.
Lincoln L. Orvig	Axeman.

86
CERTIFICATE OF SURVEYOR

Associate Cadastral Engineer
We Ty White/and Claude F. Warner,
Assistant Cadastral Engineer

....., HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 13th day of March, 1942
received from the district cadastral engineer for Arizona, with assignment
instructions dated June 1, 1942, We have resurveyed the North, East and
West Boundaries and Subdivisional Lines of Township 23 North, Range
3 East

of the Gila & Salt River Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that said
survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey
of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona,
February 22, 1946.

Ty White
Associate Cadastral Engineer, formerly
Assistant Cadastral Engineer.
Claude F. Warner
Assistant Cadastral Engineer.

CERTIFICATE OF APPROVAL

Chief Cadastral Engineer
OFFICE OF ~~SURVEYOR OF SURVEYS~~,
Denver, Colorado
OCT 20 1947, 19.....

The foregoing field notes of the resurvey of the North, East and West Boundaries
and Subdivisional Lines of Township 23 North, Range 3 East of the Gila
and Salt River Meridian, in the State of Arizona.

executed by Ty White and Claude F. Warner, Assistant Cadastral Engineers,
under special instructions dated March 13, 1942, and assignment
instructions dated June 1, 1942, having been critically examined, and
the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey
therein described, are hereby approved.

Earl G. Harrington
=Supervisor of Surveys=
Acting Assistant Chief Cadastral Engineer.

CERTIFICATE OF TRANSCRIPT

~~I certify that the foregoing transcript of the field notes of the above-described surveys in~~
~~....., is a true copy of the original field notes on file in the public survey office.~~

.....
Supervisor of Surveys.