

Original.

4-679  
(April 1933)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
~~GENERAL LAND OFFICE~~

BOOK 4353

BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Resurvey of

The North, South and East Boundaries

and

Subdivisional Lines

of

Township 23 North, Range 6 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Ty White, Assistant Cadastral Engineer, and

Bert E. Wakeman, Senior Engineering Aid

Under special instructions dated March 13, 19 42, which provided  
for the surveys included under Group No. 239, bearing the approval of the  
Commissioner of the General Land Office under date of March 28, 1942  
and assignment instructions dated May 18, 19 43

Survey commenced June 8, 19 43

Survey completed August 28, 19 43

4353

4353

1A

BOOK 4353

# INDEX DIAGRAM.

Township 23 North, Range 6 East.

	28	26	25	24	22	21	
6	86 5	72 4	61 3	50 2	38 1		19
86	85	72	60	49	38		
7	83 8	70 9	59 10	48 11	36 12		18
83	82	69	58	47	35		
18	81 17	68 16	57 15	46 14	34 13		15
80	79	67	56	45	33		
19	78 20	66 21	55 22	44 23	32 24		14
78	77	66	54	43	31		
30	76 29	64 28	53 27	41 26	30 25		12
75	74	64	52	40	30		
31	73 32	62 31	51 30	39 29	29 28		10
2	3	4	6	7	8		

TOWNSHIP 23 NORTH, RANGE 6 EAST

BOOK 6552

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

———— Indicates surveys executed by Ty White

———— Indicates surveys executed by Bert E. Wakeman

Date of Survey

East Boundary: July 6 to August 21, 1943  
 South Boundary: June 8 to July 2, 1943  
 North Boundary: July 14 to July 23, 1943  
 Subdivisions: June 8 to August 23, 1943

T. 23 N., R. 6 E.

BOOK 4353

The resurveys herein described were executed with Buff solar transits Nos. 16724 and 16730, constructed in accordance with the standard specifications of the General Land Office. The instruments were in good condition and having been placed in satisfactory adjustment prior to beginning the resurvey and tested and found free from appreciable error, were approved by the district cadastral engineer, May 18, 1943.

The directions of the lines were determined by the solar transit method. The measurements were made with Lufkin steel tapes 5 chs. in length, graduated every link for the first 100 lks., and the balance at intervals of 10 lks. The tapes were tested by comparison with a Lufkin standard steel tape and found correct. The measurements were made on the slope and the vertical angles ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

Data furnished with the special instructions give the geographic position of camp, about 20 chs. NW. of the  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, T. 23 N., R. 6 E., G. & S. R. M., as follows: latitude  $35^{\circ} 22' 5''$  N., longitude  $111^{\circ} 47' 19''$  W.

June 5, 1943, at the above station, with Buff solar transit No. 16724, at 6h 58.5m p.m. l.m.t. or 7h 25.6m p.m. by my watch which reads correct 105th meridian time as determined by radio time signals, make an hour angle observation on Polaris, west of the meridian, making four observations, two each with the telescope in direct and reversed positions, and mark the mean point in the line thus determined, on a peg driven firmly in the ground 5 chs. N. To verify the latitude of this station, read the vertical angles to Polaris.

Mean watch time of observation	7h 25.6m
Watch fast of l.m.t.	0h 27.1m
Azimuth of Polaris	0° 34.0'
Mean vertical angle to Polaris	34° 28.4'
Reduced latitude	35° 22.2' N.

June 6, 1943, lay off the azimuth of Polaris  $0^{\circ} 34'$  to the east, and mark the line thus determined by a tack in a peg driven firmly in the ground 5 chs. N.

June 6, 1943, at the same station, with Buff solar transits Nos. 16724 and 16730, every 30 minutes from 8 to 10:30 a.m. and from 1:30 to 4 p.m., make the proper settings on the arcs of the solar attachments and ascertain that the resulting orientation of the instruments, when compared with the meridian established by Polaris observation, have a maximum error of less than  $1' 30''$ .

We repeat the tests of the arcs daily by noon observations and verify the meridional indications at frequent intervals throughout the survey.

-----

Preliminary to the resurvey the lines of the original survey are retraced and diligent search is made for all original corners. Identified corners of the original survey are reestablished in their original positions. All lost corners are reestablished by the method of single proportion, double proportion or collateral evidence as appropriate, based on the original record. The retrace-ment data are thoroughly verified and only the true line notes are given here.

## Chains

## Resurvey of the South Bdy. of T. 23 N., R. 6 E.

-----  
 Reestablishment of a survey executed by W. R. Fitzgerald,  
 Deputy Surveyor, in 1883.  
 -----

From the cor. of Ts. 22 and 23 N., Rs. 5 and 6 E., as evidenced by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of the E. bdy. of T. 22 N., R. 5 E.

N. 89° 54' E., bet. secs. 6 and 31.

Over rolling land, through heavy timber and undergrowth; asc. gradually over a gentle SW. slope.

25.00 Top of ascent, bears NE. and SW.; desc. 30 ft. over a SE. slope.

39.07 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 31}{S 6}$$

1943

from which

An old bearing tree, not of record:

A dead pine, 36 ins. diam., bears N. 9 $\frac{1}{2}$ ° W., 129 lks. dist., mkd. B T.

New bearing trees:

A pine, 24 ins. diam., bears N. 28 $\frac{1}{4}$ ° W., 143 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.

A pine, 20 ins. diam., bears S. 10 $\frac{1}{4}$ ° E., 180 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.

44.32 Wire fence, bears N. 10° E. about 5 chs. then easterly, and S. 10° W. about 50 lks. then easterly.

45.65 Top of earth dam, bears S. 80° E. for 2 chs. and N. for 4 chs. Thence, across bottom of dry reservoir.

50.25 Wire fence, bears N. 3 chs. to a fence cor. and S. 1 ch. to a fence cor.

55.35 Wash, 15 lks. wide, course SW.; asc. 76 ft. over a W. slope.

75.65 Low spur, slopes SW.; asc. along a S. slope.

79.17 The cor. of secs. 5, 6, 31 and 32, as evidenced by a wood post, 3 ins. diam., in a mound of stone, 3 ft. base, 1 ft. high, mkd. T23N S32 on NE., R6E S5 on SE., T22N S6 on SW. and S31 on NW. faces; 1 notch on W. and 5 notches on E. edges.

## Resurvey of the South Bdy. of T. 23 N., R. 6 E.

## Chains

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original wood post buried alongside, at the cor. of secs. 5, 6, 31 and 32, with brass cap mkd,

T23N R6E	
S 31	S 32
-----	
S 6	S 5
T22N	
1943	

from which

## Old bearing trees:

A dead pine, 40 ins. diam., bears S.  $33\frac{1}{4}^{\circ}$  E., 22 lks. dist., markings not uncovered.

The original position of old B T, a dead pine, 36 ins. diam., lying on ground, bears N.  $25^{\circ}$  W., 48 lks. dist., markings not uncovered.

Find no evidence of old SW. bearing tree.

## New bearing trees:

A pine, 12 ins. diam., bears N.  $24\frac{3}{4}^{\circ}$  E., 73 lks. dist., mkd. T 23 N R 6 E S 32 B T.

A pine, 3 ins. diam., bears S.  $60^{\circ}$  E., 67 lks. dist., mkd. B T.

A pine, 18 ins. diam., bears S.  $25^{\circ}$  W. 119 lks. dist., mkd. T 22 N R 6 E S 6 B T.

A pine, 8 ins. diam., bears N.  $58^{\circ}$  W., 53 lks. dist., mkd. T 23 N R 6 E S 31 B T.

Land, rolling.

Soil, dark loam, rocky; 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

-----  
S.  $89^{\circ} 53'$  E., bet. secs. 5 and 32.

Over rolling land, through heavy timber and dense undergrowth; ascend over a gentle SW. slope.

20.00 Unimproved road, bears SW. and NE.

23.30 Dim road, bears N.  $15^{\circ}$  W. and S.  $15^{\circ}$  E.

30.00 Slope changes; asc. gradually over a gentle NW. slope.

40.20 The  $\frac{1}{4}$  sec. cor., determined from old bearing trees.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 32	
-----	
S 5	
1943	

from which

## Old bearing trees:

A pine, 18 ins. diam., bears N.  $71\frac{1}{4}^{\circ}$  E., 52 lks. dist., mkd. B T. Other markings not uncovered.

## Resurvey of the South Bdy. of T. 23 N. R. 6 E.

## Chains

A pine stump, 18 ins. diam., bears S. 73° E., 58 lks. dist., no marks.

## New bearing trees:

A pine, 20 ins. diam., bears N. 62° E., 64 lks. dist., mkd.  $\frac{1}{4}$  S 32 B T.

A pine, 5 ins. diam., bears S. 35½° W., 57 lks. dist., mkd.  $\frac{1}{4}$  S 5 B T.

Thence,

S. 89° 49' E., bet. secs. 5 and 32.

Ascend over a gentle W. slope.

13.00 Draw, drains N.; asc. along a gentle N. slope.

34.90 Graded road,,bears SE. to Flagstaff and NW. to Kendrick Park.

38.50 Draw, drains N. 60° W.; asc. gradually over a SW. slope.

40.16 The cor. of secs. 4, 5, 32 and 33, as evidenced by an old mound of stone, 3 ft. base, 1 ft. high. Find no evidence of old wood post.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, at the cor. of secs. 4, 5, 32 and 33, with brass cap mkd.

T23N R6E	
S 32	S 33
-----	
S 5	S 4
T22N	
1943	

from which

## Old bearing trees:

A pine, 32 ins. diam., bears S. 24¾° E., 62 lks. dist., marks not uncovered; remark on overgrowth T 22 N R 6 E S 4 B T.

A pine, 32 ins. diam., bears S. ¾° W., 62 lks. dist., mkd. S 5, other marks not uncovered; remark on overgrowth, T 22 N R 6 E S 5 B T.

A pine, 48 ins. diam., bears N. 39½° W., 22 lks. dist., marks not uncovered; remark on overgrowth, T 23 N R 6 E S 32 B T.

Land, rolling.

Soil, dark loam, rocky; 3rd rate.

Timber, pine; undergrowth, 2nd growth timber.

-----  
S. 89° 52' E., bet. secs. 4 and 33.

Over rolling land, through heavy timber and undergrowth; asc. 174 ft. over a SW. slope.

16.45 Old road, bears S. 80° W. and N. 80° E.

19.25 Recross road, bears NW. and SE.

20.90 Bend in same road, bears SW. and SE.

## Resurvey of the South Bdy. of T. 23 N., R. 6 E.

## Chains

40.00 Wire fence, bears N., and S. approx. 60 lks. dist. to a fence cor., from which fences extend N. and E.

40.10 The  $\frac{1}{4}$  sec. cor., as evidenced by a wood post, 2 ins. diam. in a mound of stone, 3 ft. base, 1 ft. high, mkd.  $\frac{1}{4}$ .

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, to bedrock, with the original wood post buried alongside, and in a mound of stone to top, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 33.

$\frac{1}{4}$

S 4

1943

from which

## Old bearing tree:

A pine stump, 30 ins. diam., bears S.  $23\frac{3}{4}^{\circ}$  W., 22 lks. dist., mkd.  $\frac{1}{4}$  S B T.

## New bearing trees:

A pine, 8 ins. diam., bears N.  $66\frac{1}{4}^{\circ}$  W., 117 lks. dist., mkd.  $\frac{1}{4}$  S 33 B T.

A pine, 30 ins. diam., bears S.  $35\frac{1}{4}^{\circ}$  W., 24 lks. dist., mkd.  $\frac{1}{4}$  S 4 B T.

Thence,

S.  $89^{\circ} 57'$  E., bet. secs. 4 and 33.

Ascend 235 ft. over a NW. slope.

39.97 The cor. of secs. 3, 4, 33 and 34, as evidenced by a wood post, 3 ins. sq., 30 ins. long, in a mound of stone, 3 ft. base, 1 ft. high, marks faintly visible.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to bedrock, with the original wood post, buried alongside, and in a mound of stone to top, at the cor. of secs. 3, 4, 33 and 34, with brass cap mkd.

T23N R6E

S 33 | S 34

S 4 | S 3

T22N

1943

from which

## Old bearing trees:

The original position of a dead pine, 30 ins. diam., lying on ground, bears N.  $51\frac{1}{2}^{\circ}$  E., 102 lks. dist., mkd. T 23 N R 6 E S 33 B T.

The original position of a dead pine, 40 ins. diam., lying on ground, bears S.  $79\frac{1}{2}^{\circ}$  W., 25 lks. dist., mkd. N R 6 E.; other marks illegible.

## New bearing trees:

A pine, 8 ins. diam., bears N.  $19\frac{3}{4}^{\circ}$  E., 165 lks. dist., mkd. T 23 N R 6 E S 34 B T.



## Resurvey of the South Bdy. of T. 23 N., R. 6 E.

## Chains

A pine, 7 ins. diam., bears S.  $34\frac{3}{4}^{\circ}$  E., 35 lks.  
dist., mkd. T 22 N R 6 E S 3 B T.

A pine, 7 ins. diam., bears S.  $36\frac{1}{2}^{\circ}$  W., 115 lks.  
dist., Mkd. T 22 N R 6 E S 4 B T.

A pine, 6 ins. diam., bears N.  $28^{\circ}$  W., 116 lks.  
dist., mkd. T 23 N R 6 E S 33 B T.

This cor. is located 2 lks. S. of a fence cor., from  
which fences extend N., easterly and westerly.

Land, rolling.

Soil, rocky; 2nd and 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber  
and rosebush.

-----  
N.  $89^{\circ} 54'$  E., bet. secs. 3 and 34.

Over rolling land, through scattered timber; asc. 172 ft.  
over a NW. slope.

Along the S. side of a wire fence.

4.77 The W. gable of a barn, bears N.  $57^{\circ} 09'$  E.

8.20 Wire fence, bears easterly and westerly, thence along N.  
side of fence.

22.50 Leave scattered timber, enter open park, bears SE. and NW.

27.50 Spur, slopes SW.; desc. 106 ft. over an E. slope.

30.40 W. gable of same barn, bears N.  $2^{\circ} 10'$  E.

35.00 Leave open park, enter scattered timber, bears N. and NE.

39.64 Ranch road, bears N. and S.

39.84 Wire fence, bears N., and S. 10 lks. dist. to a fence cor.  
from which fences extend N., E. and W.

40.12 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground at the  $\frac{1}{4}$  sec., with brass cap mkd.

$$\begin{array}{r} S\ 34 \\ \frac{1}{4} \frac{S\ 3}{1943} \end{array}$$

from which

A pine, 4 ins. diam., bears N.  $30\frac{1}{4}^{\circ}$  E., 78 lks.  
dist., mkd.  $\frac{1}{4}$  S 34 B T.

A pine, 5 ins. diam., bears S.  $63\frac{1}{2}^{\circ}$  E., 159 lks.  
dist., mkd.  $\frac{1}{4}$  S 3 B T.

Descend over a gradual E. slope.

63.50 Enter dense aspen and pine timber, bears N. and SW. Foot  
of descent; asc. along a gentle S. slope.

66.00 Low spur, slopes S.; desc. 15 ft. over a SE. slope.

68.90 Small drain, course SE.; asc. over a gradual W. slope.

## Resurvey of the South Bdy. of T. 23 N., R. 6 E.

## Chains

70.70 Center of top of earth dam, at the N. side of a reservoir, bears E. and W.

76.00 Leave heavy timber, enter scattered timber, bears N. and SE.

79.70 A fence cor., from which fences extend N., S. and south-westerly.

80.10 Graded road, bears N. to Hart Prarie and Kendrick Park, and S. to Flagstaff.

80.24 The cor. of secs. 2, 3, 34 and 35, determined from the old bearing tree.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with a stone, 8x6x2 ins., mkd. X deposited at the base, at the cor. of secs. 2, 3, 34 and 35, with brass cap mkd.

T23N R6E	
S 34	S 35
-----	
S 3	S 2
T22N	
1943	

from which

Old bearing tree:

A pine, 36 ins. diam., bears S. 47° E., 97 lks. dist., mkd. T 22 N R 6 E S, other marks not uncovered; remark on over growth, T 22 N R 6 E S 2 B T.

New bearing trees:

A pine, 10 ins. diam., bears N. 45½° E., 333 lks. dist., mkd. T 23 N R 6 E S 35 B T.

A pine, 12 ins. diam., bears S. 39¼° W., 263 lks. dist., mkd. T 22 N R 6 E S 3 B T.

No other trees available.

Land, rolling.

Soil, rocky; 3rd and 4th rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

-----

S. 89° 56' E., bet. secs. 2 and 35.

Over rolling land, through scattered timber; across Hart Prairie, along the S. side of a rail fence; asc. 21 ft. over a gradual SW. slope.

5.00 Wash, 20 lks. wide, course SW., 30 lks. to a junction with a wash, course W.

13.30 Enter wash, 30 lks. wide, course SW. for 30 lks. then W.; asc. 23 ft. along bottom of wash.

18.70 Leave wash, course W. from NE.; asc. 127 ft. over a gradual SW. slope.

39.88 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the ¼ sec. cor., with brass cap mkd.

## Resurvey of the South Bdy. of T. 23 N. R. 6 E.

Chains

$$\frac{1}{4} \frac{S 35}{S 2}$$

1943

raise a mound  
of stone, 3 ft. base, 2 ft. high, N. of cor.

No bearing trees available.

Ascend 242 ft. over a gradual SW. slope.

79.40 Unimproved road, bears N. 30° E. and S. 30° W.

79.54 Wire fence, bears S., and N. 18 lks. to a fence cor. from which fences extend easterly, westerly and S.

79.76 Proportional distance.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at the cor. of secs. 1, 2, 35 and 36, with brass cap mkd.

$$\begin{array}{r|l} T23N R6E & \\ S 35 & S 36 \\ \hline S 2 & S 1 \\ T22N & \\ 1943 & \end{array}$$

raise a mound  
of stone, 3 ft. base, 2 ft. high, W. of cor.

No bearing trees available.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, none; undergrowth, none.

-----  
S. 89° 56' E., bet. secs. 1 and 36.

Over rolling land, across Hart Prairie, along the S. side of a wire fence; asc. 377 ft. over a SW. slope.

18.64 Wire fence, bears S. 20° W., and N. 20° E. to a fence cor. from which fences extend N. 20° E., S. 20° W. and westerly.

22.70 Leave Hart Prairie, enter dense timber, bears S. 30° W. and N. 30° E.

32.15 Graded road, bears S. 30° W. to Flagstaff and N. 30° E. to Snow Bowl Lodge.

39.88 The  $\frac{1}{4}$  sec. cor., determined from the original bearing trees.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 36}{S 1}$$

1943

from which

Old bearing trees:

Resurvey of the South Bdy. of T. 23 N., R. 6 E. BOOK 4353

## Chains

A fir, 40 ins. diam., bears N.  $48\frac{1}{2}^{\circ}$  E., 17 lks. dist., marks not uncovered; remark on overgrowth,  $\frac{1}{4}$  S 36 B T.

An aspen, 16 ins. diam., bears S.  $2^{\circ}$  E., 38 lks. dist., mkd.  $\frac{1}{4}$  S B T. Change these marks to read,  $\frac{1}{4}$  S 1 B T.

Thence,

N.  $89^{\circ} 58'$  E., bet. secs. 1 and 36.

Leave rolling land, begin the ascent of Agassiz Peak of the San Francisco Mountains; asc. 665 ft. over a SW. slope.

- 1.33 Old trail, bears S.  $50^{\circ}$  W. and N.  $50^{\circ}$  E.  
 13.90 Road, bears S.  $40^{\circ}$  W. and N.  $40^{\circ}$  E.  
 15.25 Recross road, bears S.  $50^{\circ}$  E. and N.  $50^{\circ}$  W.  
 30.80 Bend in same road, bears SW. and SE.  
 39.14 The cor. of Ts. 22 and 23 N., Rs. 6 and 7 E., determined from the original bearing trees. The original wood post, 3x4x24 ins., the only marks legible being N R 6 E S 36, was found lying on the ground near the cor.

Set an iron post, 3 ft. long, 3 ins. diam., 6 ins. in the ground, to bedrock, with the old post deposited at base, and in a mound of stone to top, at the cor. of Ts. 22 and 23 N., Rs. 6 and 7 E., with brass cap mkd.

	T23N	
R6E		R7E
S 36		S 31
-----		
S 1		S 6
T22N		
1943		

from which

Old bearing trees:

A spruce, 12 ins. diam., bears S.  $27\frac{3}{4}^{\circ}$  E., 30 lks. dist., marks overgrown; mark T 22 N R 7 E S 6 B T. This bearing tree not of record.

An aspen, 12 ins. diam., bears S.  $74^{\circ}$  W., 13 lks. dist., mkd. T 22 N R 6 E S 1 B T.

An aspen, 12 ins. diam., bears N.  $58\frac{1}{2}^{\circ}$  W., 28 lks. dist., mkd. T 23 N R 6 E S 36 B T.

New bearing tree:

A spruce, 7 ins. diam., bears N.  $7\frac{3}{4}^{\circ}$  E., 36 lks. dist., mkd. T 23 N R 7 E S 31 B T.

Land, W.  $\frac{1}{2}$  rolling; E.  $\frac{1}{2}$  mountainous.  
 Soil, dark loam; rocky; 3rd and 4th rate.  
 Timber, pine, aspen, fir and spruce; undergrowth, 2nd growth timber, fern, rosebush and willow.

## Chains

## Resurvey of the West Bdy. of T. 23 N., R. 7 E.

-----  
 Reestablishment of surveys executed by W. R. Fitzgerald, Deputy Surveyor, in 1883, resurveyed by Oury and Perkins, Deputy Surveyors, in 1894 and retraced in part by Jas. A. Lamport, Deputy Surveyor, in 1903, with the destruction of the Fitzgerald corners along the E. bdy. of secs. 24 and 25 of T. 23 N., R. 6 E. which were used in the proportional restoration of lost cors. in T. 23 N., R. 6 E.  
 -----

From the cor. of Ts. 22 and 23 N., Rs. 6 and 7 E.

N. 0° 59' E., bet. secs. 31 and 36.

Over mountainous land, through dense timber and undergrowth; desc. 277 ft. over a NW. slope.

20.70 Old road, bears E. and W.

23.20 Ravine, course SW.; asc. 141 ft. over a general SW. slope.

37.80 Leave dense timber and undergrowth, enter open park, the Snow Bowl ski course, bears W., and E. 5 chs.

39.51 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 16x12x4 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original stone buried alongside, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 36  $\frac{1}{4}$  S 31

1943

from which

Old bearing trees:

An aspen, 10 ins. diam., bears S. 13 $\frac{1}{2}$ ° E., 185 lks. dist.; mkd.  $\frac{1}{4}$  S 31 B T. This tree not of record.

An aspen, 10 ins. diam., bears S. 7 $\frac{3}{4}$ ° W., 262 lks. dist., mkd.  $\frac{1}{4}$  S 36, other marks illegible. This tree not of record.

New bearing trees:

An aspen, 10 ins. diam., bears S. 14 $\frac{1}{2}$ ° E., 178 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.

An aspen, 10 ins. diam., bears S. 18 $\frac{1}{2}$ ° W., 191 lks. dist., mkd.  $\frac{1}{4}$  S 36 B T.

E. gable of engine house at Snow Bowl ski lift, bears S. 71 $\frac{1}{2}$ ° W., approx. 8 chs. dist.

Thence

N. 0° 05' W., along the W. bdy. of sec. 31.

Ascend 15 ft. along a W. slope.

6.60 Leave open park, enter dense timber, bears W., and E.

## Resurvey of the West Bdy. of T. 23 N., R. 7 E.

## Chains

- 7.20 Low spur, slopes W.; desc. 66 ft. over a NW. slope.
- 15.00 Steep ravine, course N. 80° W.; asc. 65 ft. over a SW. slope.
- 20.00 Slope changes; asc. along a W. slope.
- 39.00 Old wire fence, bears S. 50° W. and N. 50° E.
- 40.22 Intersect line bet. secs. 25 and 36 of T. 23 N., R. 6 E.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at the cor. of secs. 25 and 36 only of R. 6 E., with brass cap mkd.

T23N	T23N
S 25	
S 36	R7E
R6E	S 31
1943	

from which

An aspen, 6 ins. diam., bears S. 72½° W., 19 lks. dist., mkd. T 23 N R 6 E S 36 B T.

An aspen, 8 ins. diam., bears N. 78¾° W., 11 lks. dist., mkd. T 23 N R 6 E S 25 B T.

From point of intersection, the Fitzgerald cor. of secs. 25, 30, 31 and 36, bears S. 89° 44' E., 26 lks. dist. This cor. is evidenced by a granite stone, 8x20x21 ins., in a mound of stone, 2 ft. base, 1 ft. high, mkd. 1 groove on S. and 5 grooves on N. faces, from which

A dead spruce, 24 ins. diam., bears N. 44° E., 18 lks. dist., marks illegible.

An aspen, 8 ins. diam., bears S. 37° E., 46 lks. dist., mkd. T 23 N R 7 E S 31 B T.

A fir, 20 ins. diam., bears S. 12¼° W., 45 lks. dist., marks overgrown, not uncovered.

An aspen, 8 ins. diam., bears N. 85° W., 36 lks. dist., mkd. T 23 N R 6 E S 25 B T.

Destroy all evidence of this cor.

- 47.90 The Oury and Perkins cor. of secs. 25, 30, 31 and 36, as evidenced by a lava stone, 6x14x18 ins., in a mound of stone, 2 ft. base, 1 ft. high, mkd. 1 groove on S. and 5 grooves on N. faces, now refers to secs. 30 and 31 only.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, at the cor. of secs. 30 and 31 only of R. 7 E., with brass cap mkd.

T23N	T23N
R6E	S 30
S 25	S 31
	R7E
1943	

from which

## Resurvey of the West Bdy. of T. 23 N. R. 7 E.

## Chains

## Old bearing trees:

A fir, 16 ins. diam., bears N.  $40\frac{1}{2}^{\circ}$  E., 58 lks. dist., marks overgrown, not uncovered.

An aspen, partly dead, 10 ins. diam., bears S.  $84^{\circ}$  E., 40 lks. dist., marks illegible.

An aspen, 9 ins. diam., bears S.  $43\frac{3}{4}^{\circ}$  W., 23 lks. dist., mkd. T 23 N R 6 E S 36 B T.

An aspen, 9 ins. diam., bears N.  $58\frac{1}{4}^{\circ}$  W., 36 lks. dist., mkd. T 23 N R 6 E S 25 B T.

## New bearing tree:

A fir, 6 ins. diam., bears S.  $56\frac{1}{4}^{\circ}$  E., 39 lks. dist., mkd. T 23 N R 7 E S 31 B T.

Land, mountainous.

Soil, rocky; 2nd and 3rd rate.

Timber, fir, spruce, aspen and pine; undergrowth, 2nd growth timber.

-----  
N.  $1^{\circ} 06'$  W., along the W. bdy. of sec. 30.

Over mountainous land, through heavy timber and undergrowth.

Descend over a gradual NW. slope.

11.50 Ravine, course SW.; asc. over a gradual SW. slope.

18.65 Draw, drains W.; asc. 120 ft. over a SW. slope.

32.78 At this point on the latitudinal center line of sec. 25.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor. of sec. 25 only of R. 6 E., with brass cap mkd.

$\frac{1}{4}$  S 25

1943

from which

A spruce, 14 ins. diam., bears S.  $35^{\circ}$  W., 67 lks. dist., mkd.  $\frac{1}{4}$  S 25 B T.

A spruce, 8 ins. diam., bears N.  $22\frac{1}{2}^{\circ}$  W., 94 lks. dist., mkd.  $\frac{1}{4}$  S 25 B T.

From this cor., the Fitzgerald  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, bears N.  $89^{\circ} 57'$  E., 1.53 chs. dist., as evidenced by an aspen, 16 ins. diam., mkd.  $\frac{1}{4}$  S on W. face, from which

An aspen, 16 ins. diam., bears N.  $50^{\circ}$  E., 5 lks. dist., mkd.  $\frac{1}{4}$  S B T.

Destroy all evidence of this cor.

39.55 The Oury and Perkins  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, as evidenced by a lava stone, 12x18x24 ins. firmly set in ground, mkd.  $\frac{1}{4}$  on W. face. As this cor. now refers to sec. 30 only of R. 7 E., reset original stone, 16 ins. in the ground and change the marks to read  $\frac{1}{4}$  S 30 on E. face, from which

## Resurvey of the West Bdy. of T. 23 N., R. 7 E.

## Chains

## Old bearing trees:

A spruce, 24 ins. diam., bears N. 73° E., 10 lks. dist., mkd.  $\frac{1}{4}$  S B T. Remark on overgrowth,  $\frac{1}{4}$  S 30 B T.

A dead aspen, 7 ins. diam., bears N. 61° W., 10 lks. dist., mkd.  $\frac{1}{4}$  S B T.

## New bearing tree:

A spruce, 10 ins. diam., bears N. 12° E., 30 lks. dist., mkd.  $\frac{1}{4}$  S 30 B T.

Thence,

N. 0° 03' W., along the W. bdy. of sec. 30.

Ascend gradually along a steep W. slope.

9.70 Spur, slopes SW.; desc. 292 ft. over a NW. slope.

34.17 Intersect line bet. secs. 24 and 25 of T. 23 N., R. 6 E.

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, to bedrock and in a mound of stone to top, at the cor. of secs. 24 and 25 only of R. 6 E., with brass cap mkd.

T23N	T23N
S 24	R7E
S 25	S 30
R6E	
1943	

from which

A spruce, 6 ins. diam., bears S. 66½° W., 16 lks. dist., mkd. T 23 N R 6 E S 25 B T.

A spruce, 14 ins. diam., bears N. 57° W., 15 lks. dist., mkd. T 23 N R 6 E S 24 B T.

From point of intersection, the Fitzgerald cor. of secs. 19, 24, 25 and 30, bears N. 89° 26' E., 3.59 chs. dist. This cor. is evidenced by a spruce, 8 ins. diam., mkd. S 25 on SW., T 23 N R 6 E S 24 on NW., T 23 N R 7 E S 19 on NE. and S 30 on SE. faces, from which

A spruce, 24 ins. diam., bears N. 43½° E., 16 lks. dist., marks overgrown, not uncovered.

A fir, 20 ins. diam., bears S. 10½° E., 34 lks. dist., marks overgrown, not uncovered.

A fir, 8 ins. diam., bears S. 71½° W., 14 lks. dist., mkd. T 23 N R 6 E S 25 B T. This tree not of record.

A fir, 16 ins. diam., bears N. 8½° W., 6 lks. dist., marks overgrown, not uncovered. This tree not of record.

.. Destroy all evidence of this cor.

39.36 The Oury and Perkins cor. of secs. 19, 24, 25 and 30, as evidenced by a lava stone, 12x12x20 ins., in a mound of stone, 3 ft. base, 1 ft. high, mkd. 2 notches on S. and 4 notches on N. edges, now refers to secs. 19 and 30 only of R. 7 E.



## Resurvey of the West Bdy. of T. 23 N. R. 7 E.

## Chains

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, at the cor. of secs. 19 and 30 only of R. 7 E., with brass cap mkd.

T23N	T23N
R6E	S 19
S 24	S 30
	R7E
	1943

from which

## Old bearing trees:

A dead spruce, 16 ins. diam., bears N.  $43\frac{3}{4}^{\circ}$  E., 45 lks. dist., mkd. T 23 N R 7 E S 19 B T.

A spruce, 16 ins. diam., bears S.  $36\frac{1}{2}^{\circ}$  E., 19 lks. dist., marks overgrown, mark on overgrowth, T 23 N R 7 E S 30 B T.

A dead spruce, 12 ins. diam., bears S.  $27\frac{3}{4}^{\circ}$  W., 29 lks. dist., mkd. T 23 N R 6 E S 25 B T.

A dead spruce, 8 ins. diam., bears N.  $33\frac{1}{2}^{\circ}$  W., 22 lks. dist., mkd. T 23 N R 6 E S 24 B T.

## New bearing tree:

A spruce, 16 ins. diam., bears N.  $18\frac{3}{4}^{\circ}$  E., 32 lks. dist., mkd. T 23 N R 7 E S 19 B T.

Land, mountainous.

Soil, rocky; 2nd, 3rd and 4th rate.

Timber, fir, spruce, pine and aspen; undergrowth, 2nd growth timber.

N.  $0^{\circ} 06'$  E., along the W. bdy. of sec. 19.

Over mountainous land, through heavy timber and undergrowth; desc. 26 ft. along a W. slope.

- 9.00 Old trail, bears E. and W.
- 11.00 Spur, slopes NW.; desc. 300 ft. over a N. slope.
- 19.00 Draw, 30 lks. wide, drains NW.; continue descent.
- 35.36 At this point on the latitudinal center line of sec. 24.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, and in a mound of stone to top, at the  $\frac{1}{4}$  sec. cor. of sec. 24 only of R. 6 E., with brass cap mkd.

$\frac{1}{4}$ S 24	
	1943

from which

A spruce, 6 ins. diam., bears N.  $88\frac{1}{2}^{\circ}$  W., 40 lks. dist., mkd.  $\frac{1}{4}$  S 24 B T.

A fir, 9 ins. diam., bears N.  $14\frac{1}{2}^{\circ}$  W., 20 lks. dist., mkd.  $\frac{1}{4}$  S 24 B T.

From this cor., the Fitzgerald  $\frac{1}{4}$  sec. cor. of secs. 19

## Resurvey of the West bdy. of T. 23 N. R. 7 E.

## Chains

and 24, bears N.  $88^{\circ} 50'$  E., 2.94 chs. dist., as evidenced by a lava stone, 20x8x6 ins., firmly set in ground, mkd.  $\frac{1}{4}$  on W. face, from which

A fir, 24 ins. diam., bears S.  $19\frac{1}{2}^{\circ}$  W., 40 lks. dist., mkd.  $\frac{1}{4}$  S B T.

Destroy all evidence of this cor.

40.01 The Oury and Perkins  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, as evidenced by a lava stone, 20x10x5 ins., in a mound of stone, 3 ft. base, 1 ft. high, mkd.  $\frac{1}{4}$  on W. face. As this cor. now refers to sec. 19 only of R. 7 E., reset original stone, 16 ins. in the ground and change the marks to read  $\frac{1}{4}$  S 19 on E. face, from which

Old bearing trees:

A fir, 12 ins. diam., bears S.  $53\frac{1}{2}^{\circ}$  E., 20 lks. dist., marks overgrown, mark on overgrowth,  $\frac{1}{4}$  S 19 B T.

A fir, 16 ins. diam., bears S.  $17^{\circ}$  E., 26 lks. dist., marks overgrown, mark on overgrowth,  $\frac{1}{4}$  S 19 B T.

Thence,

N.  $0^{\circ} 18'$  W., along the W. bdy. of sec. 19.

Descend 300 ft. over a broken NW. slope of Humphreys Peak of San Francisco Mt.

4.00 Ravine, course NW.; continue descent.

30.00 Steep ravine, course NW.; continue descent.

34.06 The Oury and Perkins cor. of secs. 13, 18, 19 and 24, as evidenced by an aspen, 12 ins. diam., mkd. S 13 on NW. side; other marks overgrown, not uncovered, from which

Old bearing trees:

An aspen, 12 ins. diam., bears N.  $52\frac{1}{4}^{\circ}$  E., 16 lks. dist., marks overgrown, not uncovered.

An aspen, 12 ins. diam., bears S.  $52^{\circ}$  E., 9 lks. dist., mkd. T 23 N R 7 E S 19 B T.

An aspen, 6 ins. diam., bears S.  $56^{\circ}$  W., 9 lks. dist., mkd. T 23 N R 6 E S 24 B T.

An aspen, 12 ins. diam., bears N.  $42\frac{1}{2}^{\circ}$  W., 21 lks. dist., marks overgrown, not uncovered.

For witness cor. see the field notes of the line along the W. bdy. of sec. 18.

Land, mountainous.

Soil, rocky; 3rd and 4th rate.

Timber, fir, spruce, pine and aspen; undergrowth, 2nd growth timber.

N.  $3^{\circ} 03'$  E., along the W. bdy. of sec. 18.

Over mountainous land, through heavy timber and undergrowth; desc. 366 ft. over a broken NW. slope.

## Resurvey of the West Bdy. of T. 23 N., R. 7 E.

## Chains

0.50 Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, to bedrock, and in a mound of stone to top, at the witness cor. of secs. 18 and 19 only of R. 7 E., with brass cap mkd.

T23N	T23N
	S 18
R6E	
	S 19
S 24	R7E
W C	
1943	

from which

An aspen, 8 ins. diam., bears N.  $63^{\circ}$  E., 43 lks. dist., mkd. W C T 23 N R 7 E S 18 B T.

An aspen, 5 ins. diam., bears S.  $40\frac{3}{4}^{\circ}$  E., 43 lks. dist., mkd. W C T 23 N R 7 E S 18 B T.

1.08 Intersect line bet. secs. 13 and 24 of T. 23 N., R. 6 E.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at the cor. of secs. 13 and 24 only of R. 6 E., with brass cap mkd.

T23N	T23N
S 13	
	R7E
S 24	S 18
R6E	
1943	

from which

A spruce, 14 ins. diam., bears S.  $32\frac{3}{4}^{\circ}$  W., 25 lks. dist., mkd. T 23 N R 6 E S 24 B T.

A pine, 10 ins. diam., bears N.  $37^{\circ}$  W., 7 lks. dist., mkd. T 23 N R 6 E S 13 B T.

From point of intersection, the Fitzgerald cor. of secs. 13, 18, 19 and 24, bears N.  $88^{\circ} 45'$  E., 3.06 chs. dist., a point determined from the original bearing trees, from which

Old bearing trees:

An aspen stump, 14 ins. diam., bears N.  $42\frac{1}{2}^{\circ}$  E., 22 lks. dist., mkd. B T, other marks illegible.

An aspen, 16 ins. diam., bears S.  $61^{\circ}$  E., 33 lks. dist., mkd. T 23 N R 7 E S 19 B T.

Destroy all evidence of this cor.

30.00 Base of San Francisco Mt., enter rolling land and open park, bears NE. and SW.; desc. over a gradual NE. slope.

38.71 The Oury-Perkins  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, as evidenced by a lava stone in place 24x30x3 ins. above ground, mkd.  $\frac{1}{4}$  X on top.

Set a brass tablet,  $3\frac{1}{2}$  ins. diam., 3 in. stem, at the  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, with top mkd.

$\frac{1}{4}$	
S 13	S 18
1943	

## Resurvey of the West Bdy. of T. 23 N., R. 7 E.

Chains

from which

Old bearing tree:

A pine, 48 ins. diam., bears S.  $86\frac{1}{2}^{\circ}$  W., 102 lks. dist., mkd.  $\frac{1}{4}$  S B T. Additionally mark on overgrowth,  $\frac{1}{4}$  S 13 B T.

New bearing tree:

A pine, 8 ins. diam., bears S.  $24\frac{3}{4}^{\circ}$  E., 106 lks. dist., mkd.  $\frac{1}{4}$  S 18 B T.

Find no evidence of the Fitzgerald  $\frac{1}{4}$  sec. cor. in this vicinity.

Thence,

N.  $0^{\circ} 09'$  E., bet. secs. 13 and 18.

Descend gradually over a gentle NE. slope.

- 0.03 Wire fence, bears W. for 30 lks., then southerly, and E. 5 lks. to a fence cor., from which fences extend W., easterly and northerly.
- 0.25 West side of a galvanized water tank, bears E. about 10 lks. dist..
- 23.80 Wire fence, bears N.  $45^{\circ}$  E. and S.  $45^{\circ}$  W.; foot of descent, asc. gradually along a gentle E. slope.
- 25.62 Board fence, bears NE. and SW., enter corral.
- 25.83 Barn, bears W. about 2 chs. dist.
- 26.32 Board fence, bears NE. and SW., leave corral.
- 28.52 Wire fence, bears SW., and NE. 1 ch. dist. to a fence cor., from which fences extend SW., NE. and southerly; enter mountainous land, heavy timber and undergrowth; asc. 127 ft. over the S. slope of White Horse Hill.
- 30.70 Old road, bears E. and W.
- 38.50 Ridge, bears S.  $10^{\circ}$  W. and N.  $10^{\circ}$  E.; continue ascent 14 ft. over a SW. slope.
- 40.02 The cor. of secs. 7, 12, 13 and 18, as evidenced by a lava stone, 24x20x12 ins., in a mound of stone, 3 ft. base, 1 ft. high, mkd. 4 grooves on S. and 2 grooves on N. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, at the cor. of secs. 7, 12, 13 and 18, with brass cap mkd.

T23N	
R6E	R7E
S 12	S 7
-----	
S 13	S 18
1943	

from which

Old bearing trees:

A pine, 28 ins. diam., bears S.  $83\frac{1}{2}^{\circ}$  E., 32 lks. dist., mkd. N S 18, other marks overgrown, mark on overgrowth, T 23 N R 7 E S 18 B T.

## Resurvey of the West Bdy. of T. 23 N., R. 7 E.

## Chains

Original position of a dead pine, 40 ins. diam., lying on ground, bears S. 41° W., 78 lks. dist., marks illegible.

## New bearing trees:

A pine, 12 ins. diam., bears N. 34 $\frac{3}{4}$ ° E., 95 lks. dist., mkd. T 23 N R 7 E S 7 B T.

A pine, 3 ins. diam., bears S. 53 $\frac{1}{2}$ ° W., 68 lks. dist., mkd. B T.

A pine, 9 ins. diam., bears N. 82 $\frac{1}{2}$ ° W., 73 lks. dist., mkd. T 23 N R 6 E S 12 B T.

Land, mountainous and rolling.

Soil, rocky; 2nd and 3rd rate.

Timber, pine, fir and aspen; undergrowth, 2nd growth timber.

-----  
N. 0° 04' W., bet. secs. 7 and 12.

Over mountainous land, through heavy timber and undergrowth; asc. 80 ft. over a SW. slope.

13.60 Slope changes; asc. 22 ft. along a W. slope.

21.30 Head of a ravine, course SW.; asc. 35 ft. over a SE. slope.

27.10 Top of a ridge, bears SE., and NW. to top of White Horse Hill; continue ascent of 58 ft. along a steep E. slope.

39.00 Top of ascent, bears E. and W.; desc. 33 ft. along a steep E. slope.

40.10 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 12x8x4 ins. in a mound of stone, 3 ft. base, 1 ft. high, mkd.  $\frac{1}{4}$  on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 12 | S 7

1943

from which

## Old bearing trees:

A pine, 24 ins. diam., bears S. 68 $\frac{1}{2}$ ° E., 36 lks. dist., mkd.  $\frac{1}{4}$  S B T. Remark on overgrowth  $\frac{1}{4}$  S 7 B T.

A pine, 24 ins. diam., bears S. 33 $\frac{1}{2}$ ° W., 16 lks. dist., mkd.  $\frac{1}{4}$  S B T. Remark on overgrowth  $\frac{1}{4}$  S 12 B T.

Thence,

N. 0° 19' W., bet. secs. 7 and 12.

Descend 261 ft. along a steep E. slope.

11.00 Slope changes; desc. 142 ft. over a NE. slope.

18.70 Ravine, course N. 80° W.; asc. 43 ft. along a W. slope.

## Resurvey of the West Bdy. of T. 23 N., R. 7 E.

## Chains

32.55 Ravine, course W.; asc. gradually along a W. slope.

34.30 Spur, slopes NW.; desc. 62 ft. over a NW. slope.

39.60 The cor. of secs. 1, 6, 7 and 12, as evidenced by a lava stone, 14x12x8 ins., in a mound of stone, 3 ft. base, 1 ft. high, mkd. 5 grooves on S. and 1 groove on N. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, at the cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

T23N	
R6E	R7E
S 1	S 6
S 12	S 7
1943	

from which

Old bearing trees:

A pine, 24 ins. diam., bears N. 65° E., 96 lks. dist., marks overgrown, mark on overgrowth T 23 N R 7 E S 6 B T. This tree not of record.

A pine, 14 ins. diam., bears S. 87½° E., 108 lks. dist., marks overgrown, mark on overgrowth, T 23 N R 7 E S 7 B T. This tree not of record.

Original position of a dead pine, 24 ins. diam., lying on ground, bears S. 36° W., 120 lks. dist., marks illegible.

Original position of a dead pine, 30 ins. diam., lying on ground, bears N. 84½° W., 54 lks. dist., mkd. B T, other marks illegible.

New bearing trees:

A fir, 6 ins. diam., bears S. 44½° W., 42 lks. dist., mkd. T 23 N R 6 E S 12 B T.

A fir, 6 ins. diam., bears N. 84½° W., 54 lks. dist., mkd. T 23 N R 6 E S 1 B T.

Land, mountainous.

Soil, rocky; 2nd and 3rd rate.

Timber, pine, fir and aspen; undergrowth, 2nd growth timber.

-----  
N. 0° 06' W., bet. secs. 1 and 6.

Over mountainous land, through heavy timber and undergrowth; desc. 289 ft. over a NW. slope.

15.50 Wash, 20 lks. wide, course NE.; continue descent of 117 ft. over a NE. slope.

18.10 Wire fence, bears E. and W.

23.80 Old logging road, bears N. 70° E. and S. 70° W.

26.00 Recross road, bears N. 60° W. and S. 60° E.

39.77 The ¼ sec. cor., as evidenced by a malpais stone, 12x8x8

## Resurvey of the West Bdy. of T. 23 N., R. 7 E.

## Chains

ins., in a mound of stone, 3 ft. base, 1 ft. high, mkd.  $\frac{1}{4}$  on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone buried alongside, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 1 | S 6  
 1943

from which

## Old bearing trees:

A dead pine snag, 36 ins. diam., bears S.  $42\frac{1}{4}^{\circ}$  W., 47 lks. dist., mkd.  $\frac{1}{4}$  S B T.

A pine, 48 ins. diam., bears N.  $71^{\circ}$  W., 180 lks. dist., mkd.  $\frac{1}{4}$  S B T. This tree not of record.

## New bearing trees:

A pine, 6 ins. diam., bears N.  $49^{\circ}$  E., 8 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.

A pine, 7 ins. diam., bears N.  $44\frac{1}{4}^{\circ}$  W., 33 lks. dist., mkd.  $\frac{1}{4}$  S 1 B T.

Thence,

N.  $0^{\circ} 45'$  E., bet. secs. 1 and 6.

Descend 136 ft. over a gradual N. slope.

7.50 Wash, 10 lks. wide, course NE.

36.40 Old logging road, bears S.  $70^{\circ}$  W. and N.  $70^{\circ}$  E.

40.37 The cor. of Ts. 23 and 24 N., Rs. 6 and 7 E., as evidenced by a granite stone, 20x18x4 ins. lying on the ground, mkd. 6 grooves on N., S., E. and W. faces. Find no evidence of wood post.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground; with old stone buried alongside, at the cor. of Ts. 23 and 24 N., Rs. 6 and 7 E.; with brass cap mkd.

T24N  
 R6E | R7E  
 S 36 | S 31  
 S 1 | S 6  
 T23N  
 1943

from which

## Old bearing trees:

A pine, 16 ins. diam., bears N.  $49\frac{1}{2}^{\circ}$  E., 19 lks. dist., marks overgrown, mark on overgrowth, T 24 N R 7 E S 31 B T.

A pine, 14 ins. diam., bears S.  $51\frac{3}{4}^{\circ}$  E., 38 lks. dist., mkd. T 23 N R 7 E B T. Remark on overgrowth T 23 N R 7 E S 6 B T.

A dead pine, 12 ins. diam., bears S.  $38\frac{1}{2}^{\circ}$  W., 56 lks. dist., mkd. T 23 N R 6 E B T.

## Resurvey of the West Bdy. of T. 23 N., R. 7 E.

BOOK 4353

## Chains

The original position of a dead pine, 36 ins. diam., lying on ground, bears N. 52° W., 84 lks. dist., mkd. T 24 N 6 E, other marks illegible.

## New bearing trees:

A pine, 12 ins. diam., bears S. 25° W., 62 lks. dist., mkd. T 23 N R 6 E S 1 B T.

A pine, 5 ins. diam., bears N. 71 $\frac{3}{4}$ ° W., 142 lks. dist., mkd. T 24 N R 6 E S 36 B T.

Land, S.  $\frac{1}{2}$  mountainous; N.  $\frac{1}{2}$  rolling.

Soil, rocky; 2nd and 3rd rate.

Timber, pine, fir and aspen; undergrowth, 2nd growth timber.

## Resurvey of the North Bdy. of T. 23 N., R. 6 E.

Reestablishment of surveys executed by W. R. Fitzgerald, Deputy Surveyor, in 1883, resurveyed by F. W. Oury, Deputy Surveyor, in 1894.

From the cor. of Ts. 23 and 24 N., Rs. 6 and 7 E.

N. 89° 37' W., bet. secs. 1 and 36.

Over rolling land, through heavy timber and undergrowth; desc. gradually over a gentle NW. slope.

- 7.50 Wire fence, bears N. and S.
- 18.50 Ravine, 5 lks. wide, course N. 60° E.
- 22.10 Wire fence, bears N. and S.
- 37.30 Dim road, bears N. 70° E. and S. 70° W.
- 40.61 The  $\frac{1}{4}$  sec. cor., as evidenced by a malpais stone, 16x12x6 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} S\ 36 \\ \frac{1}{4} \text{ ---} \\ S\ 1 \\ 1943 \end{array}$$

from which

## Old bearing trees:

A pine stump, 48 ins. diam., bears N. 8° E., 150 lks. dist. Stump badly decayed, marks not visible.

Original position of a dead pine, 24 ins. diam., lying on ground, bears S. 68 $\frac{1}{2}$ ° W., 230 lks. dist., mkd.  $\frac{1}{4}$  S B T.

## New bearing trees:

A pine, 3 ins. diam., bears N. 29° E., 74 lks. dist., mkd.  $\frac{1}{4}$  S 36 B T.



## Resurvey of the North Bdy. of T. 23 N., R. 6 E.

## Chains

A pine, 36 ins. diam., bears S.  $45\frac{3}{4}^{\circ}$  W., 286 lks. dist., mkd.  $\frac{1}{4}$  S 1 B T.

Center of an earth reservoir, 2 chs. diam., bears N.  $3\frac{1}{2}^{\circ}$  E., 10 chs. dist.

Thence,

N.  $88^{\circ} 52'$  W., bet. secs. 1 and 36.

Descend gradually over a gentle NW. slope.

2.10 Wire fence, bears N. and S.

6.30 Old road, bears N.  $70^{\circ}$  W. and S.  $70^{\circ}$  E.

7.60 Ravine, 20 lks. wide, course N.  $50^{\circ}$  E.; asc. 55 ft. over a gradual SE. slope.

21.50 Wire fence, bears NE. and SW.

40.08 The cor. of secs. 1, 2, 35 and 36, determined from the old bearing trees. A wood post, 3 ins. sq., 18 ins. long, mkd. S 35 on one face and T 24 N S 36 on another face, found lying on top of ground.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old wood post buried alongside, at the cor. of secs. 1, 2, 35 and 36, with brass cap mkd.

T24N	R6E	
S 35	S 36	
S 2	S 1	
	T23N	
	1943	

from which

Old bearing trees:

A pine, 24 ins. diam., bears N.  $51^{\circ}$  E., 32 lks. dist., mkd. T 24 N R 6 E S 36 B T.

A pine, 24 ins. diam., bears S.  $18\frac{1}{2}^{\circ}$  E., 13 lks. dist., marks overgrown, not uncovered. This tree is partly dead.

A pine, 26 ins. diam., bears S.  $56\frac{1}{2}^{\circ}$  W., 83 lks. dist., marks overgrown, not uncovered.

A pine, 18 ins. diam., bears N.  $43\frac{1}{2}^{\circ}$  W., 164 lks. dist., marks overgrown, not uncovered.

New bearing tree:

A pine, 12 ins. diam., bears S.  $29^{\circ}$  E., 78 lks. dist., mkd. T 23 N R 6 E S 1 B T.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine; undergrowth, 2nd growth timber.

N.  $88^{\circ} 51'$  W., bet. secs. 2 and 35.

Over nearly level land, through heavy timber and undergrowth.

## Resurvey of the North Bdy. of T. 23 N., R. 6 E.

## Chains

21.06 A fence cor., bears N., approx. 1 ch. dist., from which fences extend westerly and northerly; leave heavy timber and undergrowth, enter Kendrick Park, bears NE. and SW.

22.00 Enter county road, bears N.  $89^{\circ} 56'$  W. and NE., an unimproved road, bears S.; thence along county road.

30.80 An unimproved road, bears SW. from county road.

41.01 The  $\frac{1}{4}$  sec. cor., as evidenced by the intersection of the center line of a county road and a line extended south from a property line fence cor.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. below the surface of the road, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \frac{S 35}{S 2} \\ 1943 \end{array}$$

from which

A fence cor., bears N., 44 lks. dist.; fence extends N. and S.  $89^{\circ} 56'$  E.

At a point N.  $45^{\circ}$  E., 65 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \frac{S 35}{S 2} \\ WC 1943 \end{array}$$

At a point S.  $45^{\circ}$  W., 65 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \frac{S 35 WC}{S 2} \\ 1943 \end{array}$$

Thence,

N.  $89^{\circ} 56'$  W., bet. secs. 2 and 35.

Along center line of county road.

40.20 The cor. of secs. 2, 3, 34 and 35, as evidenced by the intersection of center lines of county road and a graded road from the south.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. below the surface of the road, at the cor. of secs. 2, 3, 34 and 35, with brass cap mkd.

$$\begin{array}{r} T24N R6E \\ S 34 | S 35 \\ \hline S 3 | S 2 \\ T23N \end{array}$$

from which

A property line fence, bears N. 44 lks. dist.; fence extends S.  $89^{\circ} 56'$  E. and N.  $89^{\circ} 57'$  W.

Resurvey of the North Bdy. of T. 23 N., R. 6 E.

Chains

At a point N. 45° E., 66 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. of secs. 2, 3, 34 and 35, with brass cap mkd. as above sec. cor. with additional letters W.C in SW. quadrant.

At a point S. 45° W., 66 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. of secs. 2, 3, 34 and 35, with brass cap mkd. as above sec. cor., with additional letters W C in NE. quadrant.

Land, nearly level.

Soil, volcanic ash, rocky; 3rd rate.

Timber, E. 21 chs. pine; W. 59 chs. none; undergrowth, 2nd growth timber.

-----  
N. 89° 57' W., bet. secs. 3 and 34.

Along center line of county road; asc. slightly.

0.44 A property fence cor., bears N. 44 lks. dist.; fence extends N. 89° 57' W., S. 89° 56' E. and northerly, another property fence cor., bears S. 44 lks. dist.; fence extends N. 89° 57' W. and S.

40.60 The 1/4 sec. cor., as evidenced by the intersection of the center line of county road and a line extended north from a property line fence cor.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. below the surface of road, at the 1/4 sec. cor., with brass cap mkd.

1/4  $\frac{S\ 34}{S\ 3}$   
1943

from which

A property fence line, bears N., 0.455 chs. dist.; fence extends S. 89° 57' E and N. 89° 58' W.

A fence cor., bears S., 0.455 chs. dist.; fence extends S. 89° 57' E., N. 89° 58' W. and S.

At a point N. 45° E., 65 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness 1/4 sec. cor., with brass cap mkd.

1/4  $\frac{S\ 34}{S\ 3}$   
WC  
1943

At a point S. 45° W., 65 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness 1/4 sec. cor., with brass cap mkd.

1/4  $\frac{S\ 34\ WC}{S\ 3}$   
1943

## Resurvey of the North Bdy. of T. 23 N., R. 6 E.

## Chains

Thence,

N. 89° 58' W., bet. secs. 3 and 34.

Along center line of county road; ascend slightly.

40.20 Center of cattle guard, from which fence extends N., 46 lks. dist. to a property fence cor.; fence extends S. 89° 58' E. and northerly; another fence extends S., 46 lks. dist. to a property fence cor.; fence extends S. 0° 32' E. and S. 89° 58' E.

40.65 The cor. of secs. 3, 4, 33 and 34, as evidenced by the intersection of center lines of county roads.

Set an iron post, 3 ft. long, 2 ins. diam., 9 ins. below the surface of road, at the cor. of secs. 3, 4, 33 and 34, with brass cap mkd.

T24N R6E	
S 33	S 34
-----	
S 4	S 3
T23N	
1943	

At a point N. 45° E., 70 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. of secs. 3, 4, 33 and 34, with brass cap mkd. as above sec. cor. with additional letters W C in SW. quadrant.

At a point S. 45° W., 70 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. of secs. 3, 4, 33 and 34, with brass cap mkd. as above sec. cor. with additional letters W C in NE. quadrant.

Land, nearly level.

Soil, volcanic ash; 3rd rate.

Timber, none; undergrowth, none.

-----  
S. 89° 49' W., bet. secs. 4 and 33.

Along center line of road.

0.45 A property fence cor., bears N., 45 lks. dist.; fence extends S. 89° 49' W. and northerly; another property fence cor., bears S., 45 lks. dist.; fence extends S. 89° 49' W. and S. 0° 32' E.

39.95 The  $\frac{1}{4}$  sec. cor., as evidenced by the intersection of the center line of road and a line extended S. from a property fence cor.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. below the surface of road, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 33	
$\frac{1}{4}$	-----
S 4	
1943	

from which

## DOCK 4853 . . . Resurvey of the North Bdy. of T. 23 N., R. 6 E.

## Chains

A fence cor., bears N., 46 lks. dist.; fence extends N. 89° 49' E., S. 89° 24' W. and northerly.

At a point N. 45° E., 65 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 33 \\ \hline \text{S } 4 \\ \text{WC } 1943 \end{array}$$

At a point S. 45° W., 65 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground; for witness  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 33 \text{ WC} \\ \hline \text{S } 4 \\ 1943 \end{array}$$

Thence,

S. 89° 24' W., bet. secs. 4 and 33.

Descend 58 ft. over a gradual W. slope.

40.31 The cor. of secs. 4, 5, 32 and 33, as evidenced by a malpais stone, 18x12x12 ins., firmly set in ground, mkd. 4 grooves on E. and 2 grooves on W. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, at the cor. of secs. 4, 5, 32 and 33, with brass cap mkd.

$$\begin{array}{r} \text{T24N R6E} \\ \text{S } 32 \text{ | S } 33 \\ \hline \text{S } 5 \text{ | S } 4 \\ \text{T23N} \\ 1943 \end{array}$$

raise a mound

of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level.

Soil, volcanic ash; 2nd rate.

Timber, none; undergrowth, none.

-----  
S. 89° 54' W., bet. secs. 5 and 32.

Over nearly level, open land.

11.30 Old road, bears S. 40° W. and N. 40° E.; leave Kendrick Park, enter heavy timber and undergrowth, bears NW. and SE.

41.78 The  $\frac{1}{4}$  sec. cor., as evidenced by a malpais stone, 14x10x6 ins., in a mound of stone, mkd.  $\frac{1}{4}$  on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, with the original stone buried along side, and in a mound of stone to top, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

## Resurvey of the North Bdy. of T 23 N., R. 6 E.

Chains

$$\frac{1}{4} \frac{S 32}{S 5}$$

1943

from which

Old bearing tree:

A pine, 16 ins. diam., partly dead, bears N.  $81\frac{1}{2}^\circ$  E., 85 lks. dist., mkd.  $\frac{1}{4}$  S B T.

New bearing trees:

A pine, 14 ins. diam., bears N.  $65\frac{1}{2}^\circ$  E., 118 lks. dist., mkd.  $\frac{1}{4}$  S 32 B T.

A pine, 14 ins. diam., bears S.  $84\frac{1}{4}^\circ$  E., 122 lks. dist., mkd.  $\frac{1}{4}$  S 5 B T.

Thence,

N.  $89^\circ 39'$  W., bet. secs. 5 and 32.

0.10 Wire fence, bears N. and S. 61 lks. to a fence cor.; fence extends N. and S.  $65^\circ$  W.

39.97 The cor. of secs. 5, 6, 31 and 32, as evidenced by a malpais stone, 15x8x6 ins., in a mound of stone, mkd. 5 grooves on E. and 1 groove on W. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, at the cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

$$\begin{array}{c} T24N R6E \\ S 31 | S 32 \\ \hline S 6 | S 5 \\ T23N \\ 1943 \end{array}$$

from which

Old bearing trees:

A pine, 18 ins. diam., bears N.  $71\frac{1}{4}^\circ$  E., 174 lks. dist., mkd. T 24 N R 6 E S 32 B T.

A pine, 20 ins. diam., bears S.  $17\frac{1}{2}^\circ$  E., 96 lks. dist., mkd. T 23 N R 6 E S 5 B T.

A pine, 24 ins. diam., bears S.  $64\frac{1}{4}^\circ$  W., 83 lks. dist., mkd. T 23 N R 6 E S 6 B T.

A dead, pine, 24 ins. diam., bears N.  $13\frac{1}{4}^\circ$  W., 58 lks. dist., mkd. T 24 N R 6 E S 31 B T.

New bearing tree:

A pine, 5 ins. diam., bears N.  $59^\circ$  W., 26 lks. dist., mkd. T 24 N R 6 E S 31 B T.

Land, E.  $\frac{1}{2}$  nearly level; W.  $\frac{1}{2}$  gently rolling.

Soil, rocky; 2nd and 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

BOOK 4353

## Resurvey of the North Bdy. of T. 23 N., R. 6 E.

## Chains

S, 89° 24' W., bet. secs. 6 and 31.

Over rolling land, through heavy timber and undergrowth; asc. gradually over a gentle SE. slope.

39.22 The  $\frac{1}{4}$  sec. cor., determined from original bearing tree.Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, to bedrock and in a mound of stone to top, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} \text{ S } 31 \\ \hline \text{S } 6 \\ 1943 \end{array}$$

from which

Old bearing tree:

A pine, 10 ins. diam., bears S. 73° E., 31 lks. dist., mkd.  $\frac{1}{4}$  S B T.

New bearing trees:

A pine, 9 ins. diam., bears N. 20° W., 106 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.A pine, 14 ins. diam., bears S. 66 $\frac{1}{2}$ ° E., 63 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.

Thence,

N. 89° 56' W., bet. secs. 6 and 31.

Ascend 119 ft. over a SE. slope.

8.70 Road, bears N. 25° E. to Slate Mt., and S. 25° W. to Flagstaff.

32.00 Point of a spur, slopes SE.; desc. over a gradual SW. slope.

40.00 The cor. of Ts. 23 and 24 N., Rs. 5 and 6 E., as evidenced by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of the E. bdy. of T. 23 N., R. 5 E. in 1942.

Land, rolling.

Soil, rocky; 2nd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

BOOK 3353

## Chains

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

Reestablishment of surveys executed by W. R. Fitzgerald,  
Deputy Surveyor, in 1883.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of  
the Tp.

N. 0° 30' E., bet. secs. 35 and 36.

Over rolling, open land, across Hart Prairie; asc. 53 ft.  
over a gradual SW. slope.

- 0.18 Wire fence, bears E. and W.  
0.90 Old road, bears N. 80° E. and S. 80° W.  
15.00 Low spur, slopes S. 60° W. from E.; desc. 15 ft. along a  
gentle W. slope.  
21.60 Small drain, course NW.; asc. 39 ft. along a W. slope.  
37.50 Low spur, slopes N. 60° W.; desc. gradually over a N.  
slope.  
39.72 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 24x16x10  
ins., in a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, mkd.  
 $\frac{1}{4}$  on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the  
ground, to bedrock, with the original stone buried along-  
side, and in a mound of stone to top, at the  $\frac{1}{4}$  sec. cor.,  
with brass cap mkd.

$\frac{1}{4}$   
 S 35 | S 36  
 1943

Thence,

N. 0° 37' W., bet. secs. 35 and 36.

Through scattered timber; desc. 67 ft. over a N. slope.

- 17.80 Drain, course NW.; asc. along a gentle W. slope.  
40.02 The cor. of secs. 25, 26, 35 and 36, determined by the  
method of double proportional measurement.  
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the  
ground, at the cor. of secs. 25, 26, 35 and 36, with brass  
cap mkd.

T23N R6E  
 S 26 | S 25  
 S 35 | S 36  
 1943

from which

A pine, 3 ins. diam., bears N. 71 $\frac{1}{2}$ ° E., 194 lks.  
dist., mkd. B T.



BOOK 4853

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

A pine, 3 ins. diam., bears S.  $63\frac{3}{4}^{\circ}$  E., 208 lks. dist., mkd. B T.

A pine, 6 ins. diam., bears S.  $36^{\circ}$  W., 148 lks. dist., mkd. T 23 N R 6 E S 35 B T.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine; undergrowth; 2nd growth timber.

-----  
From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp.

N.  $89^{\circ} 44'$  W., bet. secs. 25 and 36.

Over mountainous land, through heavy timber and undergrowth; desc. 190 ft. over a W. slope.

11.35 Ravine, course SW.; desc. 320 ft. over a SW. slope.

39.76 Proportional distance;

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} S 25 \\ \hline S 36 \end{array}$$

from which

An aspen, 6 ins. diam., bears N.  $32\frac{3}{4}^{\circ}$  W., 20 lks. dist., mkd.  $\frac{1}{4}$  S 25 B T.

An aspen, 6 ins. diam., bears S.  $39^{\circ}$  W., 23 lks. dist.; mkd.  $\frac{1}{4}$  S 36 B T.

Descend 218 ft. over a SW. slope.

72.60 Leave heavy timber, enter scattered timber, bears N. and S.; thence, across Hart Prairie.

79.20 Wire fence, bears northerly, and southerly 20 lks. dist. to a fence cor.; fence extends northerly and westerly.

79.78 The cor. of secs. 25, 26, 35 and 36.

Land, mountainous.

Soil, rocky; 2nd and 3rd rate.

Timber, aspen, fir, spruce and pine; undergrowth, 2nd growth timber.

-----  
N.  $0^{\circ} 23'$  E., bet. secs. 25 and 26.

Over rolling land, through scattered timber; asc. along a gentle W. slope.

10.00 Drain, course W.; asc. 87 ft. over a SW. slope.

25.00 Slope changes; ascend gradually along a gentle W. slope.

40.02 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock, and in a mound of stone to top, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4853

Chains															
	$\frac{1}{4}$ <table style="margin: auto;"> <tr> <td style="text-align: center;">S 26</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 25</td> </tr> <tr> <td colspan="3" style="text-align: center;">1943</td> </tr> </table>	S 26		S 25	1943										
S 26		S 25													
1943															
	from which														
	A pine, 4 ins. diam., bears S. $14\frac{1}{4}^{\circ}$ E., 25 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.														
	A pine, 4 ins. diam., bears N. $\frac{1}{2}^{\circ}$ W., 38 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.														
	Along a gentle W. slope.														
40.11	Wire fence, bears W., and E. 20 lks. to a fence cor.; fence extends S. and W.														
56.00	Enter Heavy timber and undergrowth, bears E. and W.														
66.50	Spur, slopes W.; desc. 42 ft. over a NW. slope.														
74.00	Leave heavy timber, enter scattered timber, bears N. $70^{\circ}$ E. and S. $70^{\circ}$ W.														
80.04	The cor. of secs. 23, 24, 25 and 26, as evidenced by a wood post, 2 ins. sq., 24 ins. long, in a mound of stone, 2 ft. base, 1 ft. high, marks illegible.														
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old wood post buried alongside, at the cor. of secs. 23, 24, 25 and 26, with brass cap mkd.														
	<table style="margin: auto;"> <tr> <td colspan="2" style="text-align: center;">T23N R6E</td> </tr> <tr> <td style="text-align: center;">S 23</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 24</td> </tr> <tr> <td colspan="3" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 26</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 25</td> </tr> <tr> <td colspan="3" style="text-align: center;">1943</td> </tr> </table>	T23N R6E		S 23		S 24	-----			S 26		S 25	1943		
T23N R6E															
S 23		S 24													
-----															
S 26		S 25													
1943															
	from which														
	A pine, 3 ins. diam., bears N. $36\frac{1}{2}^{\circ}$ E., 265 lks. dist., mkd. B T.														
	A pine, 3 ins. diam., bears S. $26\frac{3}{4}^{\circ}$ E., 286 lks. dist., mkd. B T.														
	A pine, 3 ins. diam., bears S. $45\frac{1}{4}^{\circ}$ W., 327 lks. dist., mkd. B T.														
	A pine, 3 ins. diam., bears N. $47\frac{3}{4}^{\circ}$ W., 284 lks. dist., mkd. B T.														
	Land, rolling. Soil, rocky; 3rd rate. Timber, pine and aspen; undergrowth, 2nd growth timber.														
	-----														
	From the cor. of secs. 24 and 25 only; on the E. bdy. of the Tp. S. $89^{\circ} 26'$ W., bet. secs. 24 and 25. Over mountainous land, through heavy timber and undergrowth; desc. 467 ft. over a NW. slope.														
28.50	Leave mountainous land, bears NE. and SW.; thence, over rolling land.														
37.44	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the														

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

ground to bedrock, and in a mound of stone to top, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} \text{S } 24 \\ \hline \text{S } 25 \\ 1943 \end{array}$$

from which

A spruce, 4 ins. diam., bears N. 15° W., 73 lks. dist., mkd.  $\frac{1}{4}$  S 24 B T.

A spruce, 6 ins. diam., bears S. 60° E., 24 lks. dist., mkd.  $\frac{1}{4}$  S 25 B T.

Descend 350 ft. over a gradual NW. slope.

45.20 Leave heavy timber, bears SW. and NE.; thence, across Hart Prairie.

46.70 Dim road, bears NE. and S. 60° W.

56.80 Recross road, bears SE. and N. 70° W.

78.47 The cor. of secs. 23, 24, 25 and 26.

Land, E. 28 chs. mountainous; remainder of line rolling. Soil, rocky; 2nd and 3rd rate. Timber, fir, spruce, pine and aspen; undergrowth, 2nd growth timber.

-----  
N. 1° 21' E., bet. secs. 23 and 24.

Over rolling land, through scattered timber; along a W. slope.

5.60 Drain, course S. 60° W.; road, bears S. 60° W. and N. 80° E.; asc. 75 ft. along a gentle W. slope.

15.00 Leave Hart Prairie, enter heavy timber, bears E. and W.

28.00 Spur, slopes W.; desc. 95 ft. over a gentle NW. slope.

39.76 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} \text{S } 23 \mid \text{S } 24 \\ \hline 1943 \end{array}$$

from which

A fir, 3 ins. diam., bears N. 47° E., 12 lks. dist., mkd.  $\frac{1}{4}$  S 24 B T.

A pine, 3 ins. diam., bears N. 77° W., 28 lks. dist., mkd.  $\frac{1}{4}$  S 23 B T.

Center of an earth reservoir, approx. 5 chs. diam., bears N. 35° W., 12 chs. dist.

Along a gentle W. slope.

52.50 E. end of earth dam, bears W., 2 chs. dist.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

65.00 Top of wide ridge, bears SE. and W.; thence along an E. slope.

75.30 Short, rocky spur, slopes E.; desc. 74 ft. over a N. slope.

79.52 The cor. of secs. 13, 14, 23 and 24, determined by the method of double proportional measurement.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, at the cor. of secs. 13, 14, 23 and 24, with brass cap mkd.

T23N R6E	
S 14	S 13
-----	
S 23	S 24
1943	

from which

A pine, 9 ins. diam., bears N.  $72\frac{1}{2}^{\circ}$  E., 92 lks. dist., mkd. T 23 N R 6 E S 13 B T.

A pine, 7 ins. diam., bears S.  $34\frac{1}{2}^{\circ}$  E., 207 lks. dist., mkd. T 23 N R 6 E S 24 B T.

An aspen, 10 ins. diam., bears S.  $27\frac{3}{4}^{\circ}$  W., 65 lks. dist., mkd. T 23 N R 6 E S 23 B T.

An aspen, 7 ins. diam., bears N.  $47\frac{3}{4}^{\circ}$  W., 88 lks. dist., mkd. T 23 N R 6 E S 14 T.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine, aspen, fir and spruce; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp.

S.  $88^{\circ} 45'$  W., bet. secs. 13 and 24.

Over rolling land, through heavy timber and undergrowth; desc. 20 ft. over a NW. slope.

1.00 Ravine, course NW.; desc. 185 ft. over a NW. slope.

27.40 Leave heavy timber, enter open park, bears SE. and NW.

36.50 Drain, course NW.

36.77 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$	S 13
	-----
	S 24
	1943

from which

A pine, 6 ins. diam., bears N.  $10\frac{1}{4}^{\circ}$  E., 83 lks. dist., mkd.  $\frac{1}{4}$  S 13 B T.

A pine, 8 ins. diam., bears S.  $71\frac{1}{4}^{\circ}$  E., 232 lks. dist., mkd.  $\frac{1}{4}$  S 24 B T.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

- 37.55 Old road, bears N. 30° W. and S. 30° E.
- 39.10 Enter heavy timber, bears N. and S.; desc. 90 ft. over a NW. slope.
- 57.50 Ravine, course N. 15° W.; asc. 17 ft. along a N. slope.
- 66.60 Ravine, course N.; asc. 85 ft. over a NE. slope.
- 73.50 Slope changes; asc. 50 ft. along a N. slope.
- 76.61 The cor. of secs. 13, 14, 23 and 24.
- Land, rolling.  
Soil, rocky; 3rd rate.  
Timber, pine, fir, spruce and aspen; undergrowth, 2nd growth timber.
- 
- N. 1° 30' W., bet. secs. 13 and 14.
- Over rolling land, through heavy timber and undergrowth; desc. 68 ft. over a N. slope.
- 13.50 Begin steep descent; desc. 175 ft. over a NE. slope.
- 21.00 Foot of steep descent, bears NW. and SE.; desc. 145 ft. over a gradual NE. slope.
- 36.00 Old road, bears S. 80° E. and N. 80° W.
- 38.35 Road, bears S. 75° E. and W.
- 39.20 Road, bears W., and NE. for 180 lks. then N.
- 39.35 Rail fence cor. bears W., 20 lks. dist.; fence extends N. and W.
- 39.76 Proportional distance,  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $\frac{1}{4}$   
 S 14 | S 13  
 1943
- from which
- An aspen, 9 ins. diam., bears S. 35½° E., 112 lks. dist., mkd.  $\frac{1}{4}$  S 13 B T.
- A pine, 7 ins. diam., bears S. 56½° W., 44 lks. dist., mkd.  $\frac{1}{4}$  S 14 B T.
- Descend 20 ft. over a NE. slope.
- 42.50 Drain, course NW.; desc. 116 ft. over a gradual NW. slope.
- 49.60 Rail fence cor., bears W., 20 lks. dist.; fence extends N., S. and W.
- 79.40 Rail fence cor., bears W., 5 lks. dist.; fence extends S. and W.
- 79.52 The cor. of secs. 11, 12, 13 and 14, determined from old bearing trees.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 200

## Chains

Set an iron post, 3 ft. long, 2 ins. diam., 36 ins. in the ground, at the cor. of secs. 11, 12, 13 and 14, with brass cap mkd.

T23N	R6E
S 11	S 12

S 14	S 13
------	------

1943

from which

## Old bearing trees:

A pine, 32 ins. diam., bears N. 45° E., 95 lks. dist., mkd. T 23 N R 6 E.; other marks overgrown, mark on overgrowth, T 23 N R 6 E S 12 B T.

A pine, 26 ins. diam., bears S. 73½° E., 140 lks. dist.; marks overgrown, mark on overgrowth T 23 N R 6 E S 13 B T.

A pine, 30 ins. diam., bears S. 71¾° W., 92 lks. dist.; marks overgrown, mark on overgrowth, T 23 N R 6 E S 14 B T.

## New bearing tree:

A pine, 18 ins. diam., bears N. 34° W., 113 lks. dist., marked T 23 N R 6 E S 11 B T.

This cor. is located in an old abandoned road, bears NW. and SE.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber and wild rose bushes.

-----  
From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp.

N. 89° 44' W., bet. secs. 12 and 13.

Over mountainous land, through heavy timber and undergrowth; desc. 21 ft. over a SW. slope.

2.30 Ravine, course S.; asc. 55 ft. over a SE. slope.

8.50 Short spur, slopes S.; desc. 55 ft. over a SW. slope.

16.10 Ravine, course S. 10° W.; asc. 44 ft. over a SE. slope.

20.50 Short spur, slopes S. 15 chs. to toe; desc. 194 ft. over a SW. slope.

39.87 The ¼ sec. cor., determined from old bearing tree.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, to bedrock, and in a mound of stone to top, at the ¼ sec. cor., with brass cap mkd.

¼	S 12
	S 13
	1943

from which

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

Old bearing tree:

A pine, 32 ins. diam., bears N. 50° E., 32 lks. dist., mkd.  $\frac{1}{4}$  S B T.

New bearing trees:

A pine, 5 ins. diam., bears N. 19° W., 48 lks. dist., mkd.  $\frac{1}{4}$  S 12 B T.

A pine, 6 ins. diam., bears S. 23 $\frac{3}{4}$ ° W., 24 lks. dist., mkd.  $\frac{1}{4}$  S 13 B T.

Thence,

N. 89° 49' W., bet. secs. 12 and 13.

Descend 146 ft. over a SW. slope.

12.70 Shallow wash, 25 lks. wide, course NW.; leave mountainous land, enter rolling land, bears NW. and SE.; desc. 90 ft. over a gradual NW. slope.

28.10 Old road, bears SE. and NW.

39.85 Old road, bears S., and N. 40 lks. to a junction with a road which bears E. and W.

40.78 The cor. of secs. 11, 12, 13 and 14.

Land, E. 53 chs. mountainous; remainder of line rolling. Soil, rocky; 2nd and 3rd rate. Timber, pine, aspen and fir; undergrowth, 2nd growth timber.

-----  
N. 0° 31' W., bet. secs. 11 and 12.

Over rolling land, through heavy timber and undergrowth; desc. 38 ft. over a NW. slope.

0.40 Road, bears E. and W.

14.20 Ravine, course N. 70° W.; asc. 50 ft. over a SW. slope.

17.00 Slope changes; desc. along a gentle W. slope.

36.00 Slope changes; desc. 54 ft. over a N. slope.

39.67 The  $\frac{1}{4}$  sec. cor., as evidenced by a wood post, 3 ins. sq., 1 ft. long, marks illegible, in a mound of stone, 2 ft. base, 1 ft. high,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old wood post buried alongside, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 11 | S 12  
1943

from which

Old bearing tree:

A pine stump, 24 ins. diam., bears N. 12° E., 19 lks. dist.; remainder of tree lying on ground, marked  $\frac{1}{4}$  S B T.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

DOCN 4000

## Chains

## New bearing trees:

A pine, 16 ins. diam., bears S.  $67^{\circ}$  E., 105 lks. dist., mkd.  $\frac{1}{4}$  S 12 B T.

A pine, 20 ins. diam., bears S.  $81\frac{1}{4}^{\circ}$  W., 84 lks. dist., mkd.  $\frac{1}{4}$  S 11 B T.

Thence,

N.  $0^{\circ} 15'$  E., bet. secs. 11 and 12.

Descend 14 ft. over a N. slope.

- 1.80 Ravine, course N.  $30^{\circ}$  W. for 10 chs. then N.; asc. 35 ft. along a W. slope.
- 10.00 Spur, slopes W.; desc. 18 ft. along a W. slope.
- 13.30 Road, bears NW. and SE.
- 18.00 Slope changes; desc. 46 ft. over a NE. slope.
- 25.50 Ravine, 50 lks. wide, course N.  $30^{\circ}$  W., along a W. slope.
- 35.00 Short spur, slopes NW.; desc. 32 ft. over a NE. slope.
- 40.28 The cor. of secs. 1, 2, 11 and 12, determined from the old bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at the cor. of secs. 1, 2, 11 and 12, with brass cap mkd.

T23N R6E	
S 2	S 1.
-----	
S 11	S 12.
1943	

from which

## Old bearing trees:

An aspen, 18 ins. diam., bears S.  $58^{\circ}$  E, 30 lks. dist., marks overgrown, not uncovered.

Original position of a dead pine, 30 ins. diam., lying on ground, bears S.  $31\frac{3}{4}^{\circ}$  W., 36 lks. dist., mkd. T 23 N R 6 E S 11 B T.

## New bearing trees:

A pine, 6 ins. diam., bears N.  $87\frac{1}{4}^{\circ}$  E., 121 lks. dist., mkd. T 23 N R 6 E S 1 B T.

A pine, 4 ins. diam., bears S.  $10\frac{3}{4}^{\circ}$  E., 53 lks. dist., mkd. T 23 N R 6 E S 12 B T.

A pine, 7 ins. diam., bears S.  $60^{\circ}$  W., 31 lks. dist., mkd. T 23 N R 6 E S 11 B T.

A pine, 4 ins. diam., bears N.  $80\frac{1}{2}^{\circ}$  W., 36 lks. dist., mkd. T 23 N R 6 E S 2 B T.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine, fir and aspen; undergrowth, 2nd growth timber.



## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp.

N. 89° 37' W., bet. secs. 1 and 12.

Over mountainous land, through heavy timber and undergrowth; desc. 32 ft. over a NW. slope.

3.60 Spur, slopes NW.; desc. 142 ft. over a W. slope.

8.75 Ravine, course N. 10° E.; asc. 448 ft. over a steep E. slope.

25.40 Steep spur, slopes SE., 12 chs. to toe; continue ascent of 223 ft. over a steep SE. slope.

34.70 Ridge, bears N. for 1 ch, then NE. for 4 chs. to top of mountain, and S. 15 chs. dist. to a deep saddle; desc. 223 ft. over a SW. slope.

40.29 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} S 1 \\ \hline S 12 \\ 1943 \end{array}$$

from which

A pine, 16 ins. diam., bears N. 27 $\frac{1}{2}$ ° W., 74 lks. dist., mkd.  $\frac{1}{4}$  S 1 B T.

A pine, 12 ins. diam., bears S. 45° E., 32 lks. dist., mkd.  $\frac{1}{4}$  S 12 B T.

Descend 604 ft. over a steep W. slope.

66.10 Ravine, course N. 10° W.; leave mountainous land, enter rolling land, bears N. and S. 20° E.; asc. 40 ft. over a NE. slope.

69.60 Spur, slopes NW.; desc. 20 ft. over a gradual NW. slope.

78.20 Short spur, slopes N.; desc. 22 ft. over a W. slope.

80.35 Ravine, course NW; heads 2 chs. SE.; thence, along a N. slope.

80.58 The cor. of secs. 1, 2, 11 and 12.

Land, E. 66 chs. mountainous, remainder of line rolling. Soil, rocky; 2nd and 3rd rate. Timber, pine, aspen and fir; undergrowth, 2nd growth timber.

-----  
N. 0° 03' E., bet. secs. 1 and 2.

Over rolling land, through heavy timber and undergrowth; desc. over a gentle NE. slope.

0.50 Ravine, course NW.; desc. 20 ft. along a W. slope.

2.15 Old road, bears N. 5° E. and S. 5° W.

4.85 Recross road, bears S. 5° E. and N. 5° W.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

16.00 Spur, slopes NW.; desc. 78 ft. over a NW. slope.

40.46 The  $\frac{1}{4}$  sec. cor., as evidenced by a wood post, 3 ins. sq. 2 ft. long, in a mound of stone, 2 ft. base, 1 ft. high, mkd.  $\frac{1}{4}$  on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old wood post buried alongside, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 2\ | \ S\ 1 \\ 1943 \end{array}$$

from which

Old bearing tree:

A pine, 28 ins. diam., bears N.  $64^{\circ}$  E., 15 lks. dist., marks indiscernible.

New bearing trees:

A pine, 12 ins. diam., bears N.  $26\frac{1}{2}^{\circ}$  E., 63 lks. dist., mkd.  $\frac{1}{4}$  S 1 B T.

A pine, 5 ins. diam., bears S.  $59\frac{1}{4}^{\circ}$  W., 91 lks. dist., mkd.  $\frac{1}{4}$  S 2 B T.

Thence,

N.  $0^{\circ} 33'$  E., bet. secs. 1 and 2.

Descend 68 ft. over a NW. slope.

6.55 Wash, 10 lks. wide, course N.  $40^{\circ}$  E.; asc. gradually over a gentle SE. slope.

18.75 Old road, bears SW. and NE.

40.24 The cor. of secs. 1, 2, 35 and 36, on N. bdy. of Tp.

Land, rolling.

Soil, rocky; 2nd and 3rd rate.

Timber, pine, aspen and fir; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 2, 3, 34 & 35, on the S. bdy. of Tp. N.  $0^{\circ} 07'$  W., bet. secs. 34 and 35.

Over rolling land; asc. gradually along a gentle W. slope.

1.00 Center of a graded road, bears S.  $15^{\circ}$  W. to Flagstaff and N.  $15^{\circ}$  E. to Kendrick Park; thence, along W. side of same.

26.20 Wire fence, bears N.  $5^{\circ}$  E. and S.  $5^{\circ}$  W.

30.00 Top of ascent; desc. 16 ft. along a gentle W. slope.

35.00 Same fence, bears N.  $5^{\circ}$  W. and S.  $5^{\circ}$  E.

40.02 The  $\frac{1}{4}$  sec. cor., as evidenced by a wood post, 2x3 ins., 18 ins. long, in a mound of stone, 2 ft. base, 1 ft. high, marks indiscernible.

BOOK 4353

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the old wood post, buried alongside, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 34 | \text{S } 35 \\ 1943 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Thence,

N.  $0^{\circ} 23'$  E., bet. secs. 34 and 35.

Descend 60 ft. over a rolling W. slope.

- 1.10 Road, bears SE., and NW. to Peter Mitchelback's ranch house.
- 4.00 Old dim road, bears N.  $10^{\circ}$  W. and S.  $10^{\circ}$  E.
- 14.20 Wire fence, bears northeasterly and southwesterly; enter scattered timber.
- 29.60 Old dim road, bears NE. and SW.
- 40.86 The cor. of secs. 26, 27, 34 and 35, as evidenced by an old mound of stone, 2 ft. base, 1 ft. high. Mr. Peter Mitchelback, who owns and has occupied the NE.  $\frac{1}{4}$  of sec. 34, since the year 1894, states that this mound of stone marks the position of this corner and contained the original wood post for many years.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at the cor. of secs. 26, 27, 34 and 35, with brass cap mkd.

$$\begin{array}{c} \text{T23N R6E} \\ \text{S } 27 | \text{S } 26 \\ \hline \text{S } 34 | \text{S } 35 \\ 1943 \end{array}$$

from which

A pine, 4 ins. diam., bears S.  $63^{\circ}$  E., 156 lks. dist., mkd. T 23 N R 6 E S 35 B T.

A pine, 5 ins. diam., bears S.  $68\frac{3}{4}^{\circ}$  W., 167 lks. dist., mkd. T 23 N R 6 E S 34 B T.

Raise a mound of stone,  $3\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

This cor. is located in a fence line, which extends westerly, and easterly 100 lks. to a fence cor.; fence extends westerly and southerly.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine; undergrowth, none.

-----

From the cor. of secs. 25, 26, 35 and 36.

N.  $89^{\circ} 04'$  W., bet. secs. 26 and 35.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4000

Chains	Over rolling land, through scattered timber and undergrowth; desc. 188 ft. over a gradual W. slope. Along the N. side of an old wire fence.
28.40	Drain, course NW.; desc. gradually along a gentle N. slope.
29.90	An iron water tank, 10 ft. high, 27 ft. long, bears S., 1 ch. dist. A spring, bears S. 20° E., 14.25 chs. dist. A pipe line runs from the spring to water tank.
39.37	A fence cor. bears S., 75 lks. dist.; fence extends easterly, westerly and southerly.
39.73	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} S\ 26 \\ \frac{1}{4} \text{ ---} \\ S\ 35 \end{array}$
	from which
	A willow, 10 ins. diam., bears N. 8 $\frac{3}{4}$ ° E., 170 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.
	A willow, 6 ins. diam., bears S. 68° E., 145 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.
	Descend 100 ft. over a NW. slope, along the N. side of a fence line.
69.65	A fence cor., bears S. 35 lks. dist.; fence extends easterly, westerly and southerly.
76.85	A fence, bears N. 10° W. and S. 10° E. 25 lks. to a fence cor.; fence extends N. 10° W. and easterly.
78.25	Graded road, bears southerly to Flagstaff and N. for 1 ch., then N. 10° W. to Kendrick Park.
78.46	A fence cor.; fence extends westerly and southerly.
79.30	Wash, 10 lks. wide, course NW.; asc. slightly to sec. cor.
79.46	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling. Soil, rocky; 3rd rate. Timber, willow and aspen; undergrowth, wild gooseberry and wild rose brush.
	----- N. 0° 05' E., bet. secs. 26 and 27.
	Over rolling land, through scattered timber; desc. over a NE. slope.
0.23	Wash, 10 lks. wide, course NW.; desc. 56 ft. over a NW. slope.
2.80	Graded road, bears SE. to Flagstaff and NW. to Kendrick Park.
4.00	A fence cor., bears E. 15 lks. dist.; fence extends N. and southeasterly.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

- 25.10 Road, bears SW. to graded road and NE. to Fern Mountain Lodge.
- 26.32 Wire fence, bears NW. and NE. 30 lks. to a cattle guard.
- 29.50 Dry creek bed, 12 lks. wide, course SW.; asc. 195 ft. over a SE. slope.
- 33.00 Leave scattered timber, bears SW. and E.
- 38.23 Wire fence, bears E. and W. approx. 1 ch., then S.
- 39.18 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 27 \text{ | S } 26 \\ \hline 1943 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

No bearing trees available.

Ascend 21 ft. along an E. slope.

- 43.00 Top of ascent, bears E. and W.; desc. 172 ft. over a NE. slope.
- 49.00 Enter heavy timber, bears E. and W.
- 53.08 Rail fence, bears NW. and SE.
- 57.20 Small log cabin, bears W. 40 lks. dist.
- 60.15 Office cabin of Fern Mountain Lodge, bears E., 1 ch. dist. and another cabin, bears W., 1 ch. dist.
- 61.75 Center of the W. side of garage, which is on line; a cabin bears E., 1.20 chs. dist.; asc. slightly along an E. slope.
- 63.50 Rail fence, bears E. and W.
- 78.32 Gate in a wire fence, bears E. and W.; road, bears N. 10° E. and S. 5° E.
- 78.36 The cor. of secs. 22, 23, 26 and 27, determined from old bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. below the surface of the road, at the cor. of secs. 22, 23, 26 and 27, with brass cap mkd.

$$\begin{array}{c} \text{T23N R6E} \\ \text{S } 22 \text{ | S } 23 \\ \hline \text{S } 27 \text{ | S } 26 \\ \hline 1943 \end{array}$$

from which

Old bearing trees:

A pine, 40 ins. diam., bears S. 23° E., 46 lks. dist., mkd. T 23 N R 6 E. Additionally mark this tree S 26 B T.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

A pine, 30 ins. diam., bears S.  $49\frac{1}{2}^{\circ}$  W., 160 lks. dist., mkd. N R 6 E, other marks overgrown, remark on overgrowth T 23 N R 6 E S 27 B T.

An aspen stump, bears N.  $62\frac{1}{2}^{\circ}$  W., 162 lks. dist., marks illegible.

New bearing trees:

A pine, 4 ins. diam., bears N.  $65^{\circ}$  E., 87 lks. dist., mkd. T 23 N R 6 E S 23 B T.

A pine, 4 ins. diam., bears N.  $42\frac{1}{2}^{\circ}$  W., 241 lks. dist., mkd. T 23 N R 6 E S 22 B T.

Land, rolling.

Soil, rocky; 1st, 2nd and 3rd rate.

Timber, pine, aspen and fir; undergrowth, 2nd growth timber and fern.

-----  
From the cor. of secs. 23, 24, 25 and 26.

S.  $89^{\circ} 37'$  W., bet. secs. 23 and 26.

Over rolling open land; desc. 224 ft. over a gradual NW. slope.

11.50 Old road, bears N.  $80^{\circ}$  E. and S.  $80^{\circ}$  W.

24.60 Recross road, bears S.  $80^{\circ}$  E. and N.  $60^{\circ}$  W.

29.80 Wire fence, bears N. and S.

39.88 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 23}{S 26} \\ 1943$$

from which

A pine, 5 ins. diam., bears N.  $58\frac{1}{2}^{\circ}$  E., 38 lks. dist., mkd.  $\frac{1}{4}$  S 23 B T.

A pine, 5 ins. diam., bears S.  $9^{\circ}$  E., 48 lks. dist., mkd.  $\frac{1}{4}$  S 26 B T.

A fence cor., bears SE. 4 lks. dist.; fence extends southerly and westerly.

Descend 160 ft. over a NW. slope.

45.00 Enter heavy timber and undergrowth, bears N. and S.

60.00 Leave heavy timber and undergrowth, bears NE., and W. for 3.00 chs. then S.

70.60 Wide draw, drains S.; asc. gradually over a SE. slope.

73.00 An earth reservoir, bears N. approx. 6 chs. dist.

79.70 Road, bears N.  $10^{\circ}$  E. and S.  $5^{\circ}$  E. to Fern Mountain Lodge.

79.76 The cor. of secs. 22, 23, 26 and 27.

## BOOK 2358 Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains	Land, rolling. Soil, rocky; 1st, 2nd and 3rd rate. Timber, pine, aspen and fir; undergrowth, 2nd growth timber.
	-----
	N. 1° 03' W., bet. secs. 22 and 23.
	Over rolling land, through heavy timber and undergrowth; asc. 90 ft. over SE. slope.
1.70	Old road, bears W. and NE.
3.89	Wire fence, bears NE. and S. 80° W.
7.00	Galvanized iron water tank, 7 ft. diam., 7 ft. high, bears E. 15 lks. dist. A 2 in. pipe carries water from this tank to the Fern Mountain Lodge.
7.50	A water well, bears N. 55° E., 5 chs. dist. Water is pumped from this well to tank described above.
15.62	A fence cor., bears NW. 20 lks. dist.; fence extends SE. and northerly.
40.00	The $\frac{1}{4}$ sec. cor., determined from old bearing trees. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 22   S 23 1943
	from which
	Old bearing trees:
	An aspen, 10 ins. diam., bears S. 41 $\frac{1}{2}$ ° E., 9 lks. dist., mkd. $\frac{1}{4}$ S B T.
	An aspen stump, bears N. 25 $\frac{1}{4}$ ° W., 59 lks. dist., stump badly decayed, marks illegible.
	New bearing trees:
	A pine, 9 ins. diam., bears S. 50 $\frac{1}{2}$ ° E., 151 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.
	A pine, 4 ins. diam., bears S. 64° W., 71 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.
	A fence cor. bears W., 1 lk. dist.; fence extends southerly and westerly.
	Thence,
	N. 3° 40' E., bet. secs. 22 and 23.
	Ascend gradually along an E. slope.
11.00	A dividing ridge, bears E. and W.; desc. 234 ft. over a N. slope.
24.00	Graded road, bears W. to Flagstaff and N. 25° E. to Kendrick Park.
25.03	Rail fence, bears W. and N. 25° E.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

29.50 E. A. Baker's house, bears W. 2.50 chs. dist.; slope changes; desc. 31 ft. along a gentle E. slope.

36.10 Barn, bears E. 15 lks. dist.

36.80 Leave heavy timber, enter open pasture land, bears E. and W.

39.72 The cor. of secs. 14, 15, 22 and 23, determined by the method of double proportional measurement.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at the cor. of secs. 14, 15, 22 and 23, with brass cap mkd.

T23N R6E	
6 15	S 14
-----	
S 22	S 23

1943

raise a mound  
of stone, 2 ft. base, 1½ ft. high, W. of cor.

No bearing trees available.

Land, rolling.

Soil, rocky, 2nd and 3rd rate.

Timber, pine, fir and aspen; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 13, 14, 23 and 24.

S. 89° 51' W., bet. secs. 14 and 23.

Over rolling land, through heavy timber and undergrowth; asc. 40 ft. along N. slope.

10.40 Top of ascent; bears N. 80° E. and NW.; desc. 128 ft. over a NW. slope.

19.70 Ravine, course NW.; heads 4 chs. S. 20° E.; asc. gradually along a N. slope.

24.40 Spur, slopes NW.; desc. 100 ft. over a NW. slope.

39.90 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the ¼ sec. cor., with brass cap mkd.

S 14
¼ -----
S 23
1943

from which

A fir, 5 ins. diam., bears N. 22° W., 39 lks. dist., mkd. ¼ S 14 B T.

A fir, 4 ins. diam., bears S. 65° W., 188 lks. dist., mkd. ¼ S 23 B T.

Descend 303 ft. over a NW. slope.

68.10 Graded road, bears S. 30° W. to Flagstaff and N. 30° E. to Kendrick Park.



## Chains

- 68.30 Wire fence, bears S. 30° W. and N. 30° E.
- 72.40 Leave heavy timber, enter open pasture land, bears N. 20° E. and S. 20° W.
- 77.40 Draw, drains N.; ascend gradually over an E. slope.
- 79.81 The cor. of secs. 14, 15, 22 and 23.

Land, rolling.  
Soil, rocky, 2nd and 3rd rate.  
Timber, pine, fir and aspen; undergrowth, 2nd growth timber.

-----  
N. 2° 11' W., bet. secs. 14 and 15.

Over rolling open land; desc. gradually along a gentle E. slope.

- 7.20 Cut wash, 3 lks. wide, 3 ft. deep, course NE.; asc. 54 ft. over a SE. slope.
- 21.00 Enter heavy timber and undergrowth, bears E. and W.
- 23.00 Spur, slopes E.; wire fence, bears E. and W.; asc. 84 ft. along a steep E. slope.
- 39.64 Proportional distance,  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 15 \text{ | S } 14 \end{array}$$

1943

from which

A pine, 12 ins. diam., bears S. 14° E., 8 lks. dist., mkd.  $\frac{1}{4}$  S 14 B T.

A pine, 6 ins. diam., bears N. 83½° W., 38 lks. dist., mkd.  $\frac{1}{4}$  S 15 B T.

Ascend gradually along a steep E. slope.

- 43.70 Top of ascent, bears E. and W.; desc. 45 ft. over a NE. slope.
- 55.00 Short spur, slopes S. 80° E.; desc. 232 ft. over a NE. slope.
- 79.28 The cor. of secs. 10, 11, 14 and 15, determined from the old bearing trees.  
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at the cor. of secs. 10, 11, 14 and 15, with brass cap mkd.

$$\begin{array}{c} \text{T23N R6E} \\ \text{S } 10 \text{ | S } 11 \end{array}$$

$$\text{S } 15 \text{ | S } 14$$

1943

from which

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

## Old bearing trees:

A pine, 20 ins. diam., bears S. 79° E., 46 lks. dist., marks overgrown, not uncovered.

A pine stump, 18 ins. diam., bears S. 62½° W., 65 lks. dist., remainder of tree lying on ground, mkd. T 23 N R 6 E S 15 B T.

## New bearing trees:

A pine, 9 ins. diam., bears N. 79½° E., 42 lks. dist., mkd. T 23 N R 6 E S 11 B T.

A pine, 22 ins. diam., bears S. 75½° W., 147 lks. dist., mkd. T 23 N R 6 E S 15 B T.

A pine, 20 ins. diam., bears N. 32° W., 64 lks. dist., mkd. T 23 N R 6 E S 10 B T.

Land, rolling.

Soil, rocky; 2nd and 3rd rate.

Timber, pine, aspen and fir; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 11, 12, 13 and 14.

S. 89° 40' W., bet. secs. 11 and 14.

Over rolling land, through heavy timber and undergrowth; desc. 90 ft. over a gradual NW. slope. Along a rail fence.

11.67 Fence cor.; rail fence extends easterly and westerly and wire fence extends northerly, thence, along a rail fence which runs irregularly west.

33.00 Leave heavy timber, enter open park, bears N. and S.; end of rail fence.

40.41 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the ¼ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 11}{S 14}$$

1943

from which

A pine, 4 ins. diam., bears N. 43° E., 168 lks. dist., mkd. ¼ S 11 B T.

A pine, 3 ins. diam., bears S. 83¾° E., 300 lks. dist., mkd. B T.

Descend over a gradual W. slope.

41.85 Old road, bears SE. and NW. for 3 chs. to a road which bears E. and W.

45.20 Drain, course N. to a wash course N. 15° E.; remains of an old earth reservoir, bears N., 130 lks. dist.

46.00 Cut wash, 5 lks. wide, 6 ft. deep, course NW. for 1 ch. then N. 15° E.

48.75 Fence cor. bears N., 5 lks. dist.; fence extends north-

BOOK 4353

Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains	erly and westerly.
61.30	Enter heavy timber and undergrowth, bears S. and NE.
63.90	Fence, bears southerly and northerly 20 lks. dist. to a fence cor.; fence extends southerly and easterly.
77.50	Graded road, bears S. to Flagstaff and N. for 3 chs. then NW. to Kendrick Park.
80.82	The cor. of secs. 10, 11, 14 and 15. Land, rolling. Soil, rocky; 1st and 2nd rate. Timber, pine and aspen; undergrowth, 2nd growth timber.
	-----
	N. 0° 28' W., bet. secs. 10 and 11. Over rolling land, through heavy timber and undergrowth; descend gradually over a NE. slope.
5.40	Head of a draw, drains N. 30° W.; graded road, bears N. 30° W. to Kendrick Park and S. 30° E. to Flagstaff; continue gradual descent over a NW. slope.
26.50	Old road, bears E. and W.
31.90	Wash, 20 lks. wide, 1 ft. deep, course NW.; asc. 25 ft. over a SW. slope.
40.66	The $\frac{1}{4}$ sec. cor., determined from old bearing tree. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S } 10^{\circ} \text{ S } 11 \\ 1943 \end{array}$
	from which
	Old bearing tree: A pine, 20 ins. diam., bears N. 39½° W., 25 lks. dist., mkd. $\frac{1}{4}$ S B T. Additionally mark on overgrowth, $\frac{1}{4}$ S 10 B T.
	New bearing tree: A pine, 12 ins. diam., bears N. 42° E., 19 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.
	Thence, N. 0° 24' E., bet. secs. 10 and 11. Ascend 160 ft. along a W. slope.
23.80	Top of ascent, bears E. and W.; desc. 148 ft. over a NW. slope.
39.96	The cor. of secs. 2, 3, 10 and 11, determined from old bearing trees.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4038

## Chains

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at the cor. of secs. 2, 3, 10 and 11, with brass cap mkd.

$$\begin{array}{c} T23N R6E \\ S 3 | S 2 \\ \hline S 10 | S 11 \\ 1943 \end{array}$$

from which

## Old bearing trees:

A pine, 20 ins. diam., bears S.  $70\frac{1}{2}^{\circ}$  E., 58 lks. dist., mkd. T 23 N R 6 E S 11 B T.

An aspen, 14 ins. diam., bears S.  $76\frac{3}{4}^{\circ}$  W., 26 lks. dist., mkd. T 23 N R 6 E S 10 B T. This tree is partly dead.

## New bearing trees:

A pine, 20 ins. diam., bears N.  $77\frac{3}{4}^{\circ}$  E., 56 lks. dist., mkd. T 23 N R 6 E S 2 B T.

A pine, 6 ins. diam., bears S.  $27\frac{1}{2}^{\circ}$  W., 9 lks. dist., mkd. T 23 N R 6 E S 10 B T.

A fir, 3 ins. diam., bears N.  $77\frac{1}{2}^{\circ}$  W., 16 lks. dist., mkd. T 23 N R 6 E S 3 B T.

Land, rolling.

Soil, rocky; 2nd and 3rd rate.

Timber, pine, fir and aspen; undergrowth, 2nd growth timber.

-----

From the cor. of secs. 1, 2, 11 and 12.

N.  $89^{\circ} 32'$  W., bet. secs. 2 and 11.

Over rolling land, through heavy timber and undergrowth; along a N. slope.

0.65 Ravine, course N.; old road in bottom of ravine, bears N. and S.; asc. 25 ft. over a NE. slope.

6.00 Spur, slopes N.; desc. 58 ft. over a NW. slope.

21.00 Old road, bears N. and S.

22.25 Cut wash, 6 ft. deep, 10 lks. wide, course N.; asc. 163 ft. over a NE. slope.

40.18 The  $\frac{1}{4}$  sec. cor., as evidenced by a wood post, 2 ins. sq., 15 ins. long, firmly set in the ground, marks not visible.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S 2 \\ \hline S 11 \\ 1943 \end{array}$$

from which

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains	
	<p>Old bearing tree:</p> <p>A dead pine, 24 ins. diam., bears N. <math>62\frac{1}{2}^{\circ}</math> E., 41 lks. dist., mkd. <math>\frac{1}{4}</math> S B T.</p> <p>New bearing trees:</p> <p>A pine, 7 ins. diam., bears N. <math>28\frac{1}{2}^{\circ}</math> W., 25 lks. dist., mkd. <math>\frac{1}{4}</math> S 2 B T.</p> <p>A fir, 4 ins. diam., bears S. <math>0\frac{3}{4}^{\circ}</math> E., 54 lks. dist., mkd. <math>\frac{1}{4}</math> S 11 B T.</p> <p>Thence,</p> <p>S. <math>89^{\circ} 42'</math> W., bet. secs. 2 and 11.</p> <p>Ascend 56 ft. over a NE. slope.</p> <p>6.00 Top of ascent, bears N. and S.; desc. slightly along a N. slope.</p> <p>20.00 Slope changes; desc. 160 ft. over a NW. slope.</p> <p>40.59 The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, rocky; 2nd and 3rd rate. Timber, pine, fir and aspen; undergrowth, 2nd growth timber.</p> <p>-----</p> <p>N. <math>0^{\circ} 06'</math> W., bet. secs. 2 and 3.</p> <p>Over rolling land, through heavy timber and undergrowth; desc. 70 ft. over a NW. slope.</p> <p>10.00 Foot of steep descent, bears NE. and SW. ; descend over a gradual N. slope.</p> <p>14.60 Dim road, bears E., and W. 50 lks. to junction with a graded road which bears N. and S. <math>80^{\circ}</math> W.</p> <p>18.60 Road, bears N. <math>25^{\circ}</math> E. and S. <math>25^{\circ}</math> W. to junction with graded road.</p> <p>30.40 Leave heavy timber and undergrowth, enter Kendrick Park, bears N. <math>80^{\circ}</math> E. and W.; thence, over nearly level land.</p> <p>39.64 Fence cor., bears W., 73 lks. dist.; fence extends northerly, southerly and westerly.</p> <p>40.62 Proportional distance,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math>  S 3   S 2  1943 </p> <p style="text-align: right;">raise a mound</p> <p style="text-align: center;">of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Ascend over a gradual S. slope.</p> <p>51.40 Graded road, bears N. and S. <math>1^{\circ}</math> W.</p> <p>81.44 The cor. of secs. 2, 3, 34 and 35, on N. bdy. of the Tp.</p>

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4853

## Chains

Land, S.  $\frac{1}{2}$  rolling; N.  $\frac{1}{2}$  nearly level.  
Soil, 1st and 2nd rate.  
Timber, pine, fir and aspen; undergrowth, 2nd growth  
timber.

-----  
From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of  
the Tp.

N.  $0^{\circ} 27' W.$ , bet. secs. 33 and 34.

Over rolling land, through heavy timber and undergrowth;  
along a fence, which extends irregularly N.; desc.  
gradually over a rolling W. slope.

17.00 A fence cor.; fence extends northerly, southerly and west-  
erly.

40.89 The  $\frac{1}{4}$  sec. cor., an old mound of stone, 2 ft. base, 1 ft.  
high.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 33 | S 34  
1943

from which

Old bearing tree:

An aspen, 12 ins. diam., bears S.  $45^{\circ} W.$ , 33 lks.  
dist., mkd.  $\frac{1}{4}$  other marks illegible.

New bearing trees:

A pine, 34 ins. diam., bears S.  $43^{\circ} E.$ , 55 lks.  
dist., mkd.  $\frac{1}{4}$  S 34 B T.

A pine, 20 ins. diam., bears S.  $1^{\circ} W.$ , 113 lks.  
dist., mkd.  $\frac{1}{4}$  S 33 B T.

A fence cor., bears SE., approx. 5 lks. dist.;  
old rail fence, extends N. and S. and a wire fence  
extends E.

Thence N.  $0^{\circ} 05' E.$ , bet. secs. 33 and 34.

Along an old fence which extends irregularly N.; asc. a  
gradual SW. slope.

8.20 Low spur, slopes NW.; desc. 134 ft. over a N. slope.

26.50 Leave heavy timber, bears E. and W.; enter open park.

38.70 Wash, 10 lks. wide, course S.  $60^{\circ} W.$ ; enter heavy timber,  
bears S.  $60^{\circ} W.$  and N.  $60^{\circ} E.$

39.06 The cor. of secs. 27, 28, 33 and 34, as evidenced by an  
old mound of stone, 3 ft. base, 1 ft. high.

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the  
ground, to bedrock, and in a mound of stone to top, at the  
cor. of secs. 27, 28, 33 and 34, with brass cap mkd.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains

T23N R6E	
S. 28	S 27
-----	
S 33	S 34
1943	

from which

Old bearing trees:

A pine stump, 20 ins. diam., bears S.  $68\frac{3}{4}^{\circ}$  E., 22 lks. dist., mkd. T 23 N R 6 E S 33 B T.

A pine, 36 ins. diam., bears N.  $28^{\circ}$  W., 23 lks. dist., mkd. T 23 N R 6 E S 28 B T.

New bearing trees:

A pine, 14 ins. diam., bears N.  $69\frac{1}{2}^{\circ}$  E., 114 lks. dist., mkd. T 23 N R 6 E S 27 B T.

A pine, 36 ins. diam., bears S.  $21\frac{1}{2}^{\circ}$  E., 162 lks. dist., mkd. T 23 N R 6 E S 34 B T.

A pine, 14 ins. diam., bears S.  $69\frac{3}{4}^{\circ}$  W., 33 lks. dist., mkd. T 23 N R 6 E S 33 B T.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 26, 27, 34 and 35.S.  $89^{\circ} 14'$  W., bet. secs. 27 and 34.

Over rolling land, through scattered timber and undergrowth; along a wire fence; desc. 66 ft. over a gradual NW. slope.

6.65 A fence cor.; fence extends easterly, westerly and northerly; leave timber and undergrowth, bears NE. and SW.; thence, along S. side of a lane, 60 lks. wide, bears westerly.

23.30 Road, bears SE. from lane to Peter Mitchelback's ranch house.

23.40 A fence cor. bears S., 3 lks. dist.; fence extends S.  $10^{\circ}$  W., easterly and westerly.

40.29 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$	S 27
	-----
	S 34
	1943

raise a mound

of stone, 3 ft. base, 2 ft. high, W. of cor. Raising a mound of stone in the proper position N. of cor. would interfere with vehicles traveling in lane.

Descend gradually over a gentle NW. slope.

40.37 A fence cor., bears S., 10 lks. dist.; fence extends southerly and easterly, and another fence cor., bears

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

FOCK 3058

Chains	
	N., 50 lks. dist.; fence extends easterly and northerly; enter timber, bears SW. and N.
64.70	Shallow drain, course NW.; continue descent.
68.40	Recross drain, course SW.; desc. gradually over a W. slope.
79.78	Wash, 10 lks. wide, course S. 60° W.; ascend gradually.
80.58	The cor. of secs. 27, 28, 33 and 34.  Land, rolling. Soil, rocky, 2nd and 3rd rate. Timber, pine and aspen; undergrowth, 2nd growth timber.
	-----
	N. 0° 13' W., bet. secs. 27 and 28.  Over rolling land, through heavy timber and undergrowth; asc. 138 ft. over a S. slope.
10.00	Road, bears E. and W.
40.08	The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone, 18x12x6 ins., in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on W. face.  Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original stone buried alongside, at the $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4}$ S 28   S 27 1943  from which  A pine, 24 ins. diam., bears N. 66° E., 126 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.  A pine, 18 ins. diam., bears S. 14 $\frac{1}{4}$ ° W., 148 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.  Find no evidence of the original bearing trees.
	N. 0° 25' W., bet. secs. 27 and 28.  Ascend 45 ft. over a S. slope.
14.00	Rocky spur, slopes SW.; desc. 9 ft. over a NW. slope.
17.00	Foot of descent; ascend 36 ft. over a gradual SE. slope.
25.00	Wire fence, bears E. and W.; enter cultivated field.
37.00	Leave cultivated field, enter heavy timber, bears W. and NE.
40.11	The cor. of secs. 21, 22, 27 and 28, as evidenced by a lava stone, 14x12x6 ins., in a mound of stone, 2 ft. base, 1 ft. high, mkd. 2 grooves on S. and 3 grooves on E. faces.  Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original stone buried alongside, at the cor. of secs. 21, 22, 27 and 28, with brass cap mkd.



Chains

T23N R6E  
 S 21 | S 22  
 -----  
 S 28 | S 27  
 1943

from which

Old bearing tree:

An aspen, 10 ins. diam., bears N.  $60\frac{1}{2}^\circ$  W., 74 lks. dist., mkd. T 23 N R 6 E S 21 B T.

New bearing trees:

A pine, 14 ins. diam., bears N.  $77\frac{1}{4}^\circ$  E., 51 lks. dist., mkd. T 23 N R 6 E S 22 B T.

A pine, 24 ins. diam., bears S.  $74\frac{3}{4}^\circ$  E., 154 lks. dist., mkd. T 23 N R 6 E S 27 B T.

A pine, 14 ins. diam., bears S.  $47\frac{3}{4}^\circ$  W., 234 lks. dist., mkd. T 23 N R 6 E S 28 B T.

Land, rolling.

Soil, rocky; 2nd, 3rd and 4th rate.

Timber, pine and aspen; undergrowth, 2nd growth pine.

-----  
 From the cor. of secs. 22, 23, 26 and 27.

N.  $89^\circ 29'$  W., bet. secs. 22 and 27.

Over rolling land, through scattered timber and undergrowth; asc. gradually over a gentle SE. slope.

0.55 A fence cor., bears S., 5 lks. dist.; fence extends easterly, westerly and a rail fence extends southerly.

3.00 Enter heavy timber bears N. and E.

23.60 Low spur, slopes S.; desc. 14 ft. over a W. slope.

28.00 Wide shallow draw, drains S.  $20^\circ$  E. along a rolling S. slope.

37.10 Road, bears SW. and NE. for 1 ch. then E.; a fence cor. bears S. 25 lks.; fence extends easterly and southerly.

40.51 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, to bedrock, and in a mound of stone to top, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 22  
 $\frac{1}{4}$  -----  
 S 27  
 1943

from which

A pine, 20 ins. diam., bears N.  $0\frac{1}{2}^\circ$  E., 46 lks. dist., mkd.  $\frac{1}{4}$  S 22 B T.

A pine, 5 ins. diam., bears S.  $28\frac{1}{2}^\circ$  E., 28 lks. dist., mkd.  $\frac{1}{4}$  S 27 B T.

Descend along a rolling S. slope.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains	
46.70	Graded road, bears S. 20° E., to Flagstaff and N. 20° W. to Kendrick Park.
47.05	Wire fence, bears S. 20° E. and N. 20° W.
59.00	Old fence line; leave heavy timber, enter open park, bears NW. and SE.
61.00	Swale, drains SE.; asc. 10 ft. along a S. slope.
69.00	Enter heavy timber and undergrowth, bears NE. and SW.
81.02	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, rocky; 3rd rate. Timber, pine and aspen; undergrowth, 2nd growth timber.
-----	
	N. 1° 33' E., bet. secs. 21 and 22.
	Over rolling land, through heavy timber and undergrowth; asc. 124 ft. over a gradual S. slope.
4.90	Wire fence bears E. and W.
15.00	Leave heavy timber, enter scattered timber, bears NW. and SE.
25.00	Leave rolling land, begin steep ascent of a hill; asc. 261 ft. over a S. slope.
38.46	Wire fence, bears E., and W. 77 lks. to a fence cor.; fence extends E. and northerly.
39.79	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \vdots \\ S\ 21 \mid S\ 22 \\ \vdots \\ 1943 \end{array}$
	from which
	A pine, 4 ins. diam., bears N. 71 $\frac{3}{4}$ ° E., 49 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.
	A pine, 5 ins. diam., bears S. 24 $\frac{1}{2}$ ° W., 82 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.
	Ascend 116 ft. over a S. slope.
45.20	Top of ascent, bears E. and W. approx. 3 chs. to top of hill; desc. 403 ft. over a N. slope.
65.20	Ravine, course E.; road, bears E. and W.; a saddle between two hills, to the S. and N., bears W. about 15 chs. dist.; asc. 119 ft. over a SE. slope.
79.58	The cor. of secs. 15, 16, 21 and 22, as evidenced by a wood post, 4 ins. sq., 14 ins. long, set in the ground at a fence cor., mkd. N R 6 S 15, other marks illegible. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old wood post buried alongside, at the cor. of secs. 15, 16, 21 and 22, with brass cap mkd.

BOOK 4353

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains

T23N R6E	
S 16	S 15
-----	
S 21	S 22
1943	

from which

## Old bearing trees:

A pine, 30 ins. diam., bears S.  $4\frac{1}{2}^{\circ}$  E., 36 lks. dist., marks overgrown, mark on overgrowth, T 23 N R 6 E S 22 B T.

A pine, 30 ins. diam., bears N.  $12\frac{3}{4}^{\circ}$  W., 91 lks. dist., mkd. T 23 N R 6 E S 16 B T.

## New bearing trees:

A pine, 5 ins. diam., bears N.  $47^{\circ}$  E., 22 lks. dist., mkd. T 23 N R 6 E S 15 B T.

A fir, 5 ins. diam., bears S.  $48\frac{3}{4}^{\circ}$  W., 58 lks. dist., mkd. T 23 N R 6 E S 21 B T.

This cor. is located at the SW. side of a wood post at a fence cor.; fence extends southerly and easterly.

Land, S. 25 chs. rolling, remainder of line, mountainous. Soil, rocky; 2nd and 3rd rate. Timber, pine, aspen, spruce and fir; undergrowth, 2nd growth timber.

-----

From the cor. of secs. 14, 15, 22 and 23.

N.  $89^{\circ} 35'$  W., bet. secs. 15 and 22.

Over rolling open land; asc. over a gradual NE. slope.

2.32 Wire fence, bears N. and S.

9.00 Cut wash, 3 lks. wide, 10 ft. deep, course N.  $30^{\circ}$  E.; asc. 245 ft. over an E. slope; enter a potato patch, bears NE. 2.50 chs. dist. and SW. 1.50 chs. dist.

12.50 Leave potato patch, bears NE. and SW.

22.75 Wire fence, bears N. and S.

24.00 Leave open land, enter heavy timber, bears S. and NE.

31.80 Short spur, slopes SE.; asc. 77 ft. over a SE. slope.

40.25 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 15	
$\frac{1}{4}$	-----
S 22	
1943	

from which

## Old bearing tree, not of record:

A pine, 24 ins. diam., bears N.  $52^{\circ}$  E., 36 lks. dist., mkd.  $\frac{1}{4}$  S on SW. side, additionally mark on overgrowth  $\frac{1}{4}$  S 15 B T.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

EODR 4000

Chains	
	<p>New bearing tree:</p> <p>A pine, 12 ins. diam., bears S. 76° W., 36 lks. dist., mkd. <math>\frac{1}{4}</math> S 22 B T.</p> <p>Ascend 126 ft. over a SE. slope.</p>
40.70	A fence cor., bears S. 7 lks. dist.; fence extends westerly and southerly.
47.75	Short spur, slopes S. 20° W.; leave heavy timber, bears S. and NW.; desc. 109 ft. over a W. slope.
56.26	From this point, the E. gable of George Hochderffer's house, bears S. 29° 25' W.
57.55	Draw, drains S. for 15 chs., then E.; heads about 20 chs. N.; asc. gradually along a gentle S. slope.
66.21	From this point, E. gable of George Hochderffer's house bears S. 6° 00' W.
66.75	Draw, drains SE.; ascend 71 ft. over a SE. slope.
67.25	Enter heavy timber and undergrowth, bears S. and NE.
80.51	The cor. of secs. 15, 16, 21 and 22.
	<p>Land, rolling. Soil, rocky; 2nd and 3rd rate. Timber, pine and aspen; undergrowth, 2nd growth timber.</p> <p>-----</p> <p>N. 0° 23' W., bet. secs. 15 and 16.</p> <p>Over mountainous land, through heavy timber and undergrowth; asc. 70 ft. over a SE. slope.</p>
8.40	Ravine, course S. 30° E.; asc. 358 ft. over a SW. slope.
33.50	Top of mountain, bears SE. and NW.; desc. 60 ft. over a NE. slope.
39.52	The $\frac{1}{4}$ sec. cor., determined from old bearing tree.
	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the <math>\frac{1}{4}</math> sec. cor., with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math>  S 16   S 15  1943 </p> <p style="text-align: right;">from which</p>
	<p>Old bearing tree:</p> <p>A fir, 28 ins. diam., bears S. 60° W., 30 lks. dist., mkd. <math>\frac{1}{4}</math> S B T. Remark tree <math>\frac{1}{4}</math> S 16 B T.</p> <p>New bearing tree:</p> <p>A spruce, 10 ins. diam., bears S. 46½° E., 43 lks. dist., mkd. <math>\frac{1}{4}</math> S 15 B T. Thence N. 2° 03' W., bet. secs. 15 and 16. Descend 420 ft. over a NE. slope.</p>
20.20	Steep ravine, course E.; asc. 48 ft. over a SE. slope.

BOOK 4358

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

30.00 Slope changes; asc. 28 ft. along a steep E. slope.

39.64 The cor. of secs. 9, 10, 15 and 16, as evidenced by a limestone, 18x8x3 ins., in a mound of stone, 3 ft. base, 1 ft. high, mkd. 4 grooves on S. and 3 grooves on E. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old stone buried alongside, at the cor. of secs. 9, 10, 15 and 16, with brass cap mkd.

T 23 N R 6 E
S 9   S 10
-----
S 16   S 15

1943

from which

A pine, 24 ins. diam., bears S.  $3\frac{1}{4}^{\circ}$  W., 48 lks. dist., marks overgrown, mark on overgrowth, T 23 N R 6 E S 16 B T.A pine, 24 ins. diam., bears N.  $83\frac{1}{4}^{\circ}$  W., 32 lks. dist., marks overgrown, mark on overgrowth, T 23 N R 6 E S 9 B T.

New bearing trees:

A fir, 4 ins. diam., bears N.  $3\frac{3}{4}^{\circ}$  E., 30 lks. dist., mkd. T 23 N R 6 E S 10 B T.A fir, 6 ins. diam., bears S.  $32\frac{1}{4}^{\circ}$  E., 69 lks. dist., mkd. T 23 N R 6 E S 15 B T.

Land, mountainous.

Soil, rocky, 2nd and 3rd rate.

Timber, pine, aspen fir and spruce; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 10, 11, 14 and 15.N.  $89^{\circ} 08'$  W., bet. secs. 10 and 15.

Over rolling land, through heavy timber and undergrowth; asc. 210 ft. over a NE. slope.

40.60 The  $\frac{1}{4}$  sec. cor., determined from old bearing tree.Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 10
-----
S 15
1943

from which

Old bearing tree:

A pine stump, 30 ins. diam., bears N.  $44\frac{1}{2}^{\circ}$  E., 19 lks. dist., mkd. S B T.

New bearing trees:

A fir, 5 ins. diam., bears N.  $40\frac{1}{2}^{\circ}$  W., 16 lks. dist., mkd.  $\frac{1}{4}$  S 10 B T.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

A fir, 6 ins. diam., bears S.  $12\frac{3}{4}^{\circ}$  E., 10 lks. dist., mkd.  $\frac{1}{4}$  S 15 B.T.

S.  $89^{\circ} 28'$  W., bet. secs. 10 and 15.

Over mountainous land; asc. 40 ft. over a NE. slope.

5.00 Low spur, slopes N.; desc. 24 ft. over a NW. slope.

7.00 Steep ravine, course N.; asc. 93 ft. along a N. slope.

13.00 Low spur, slopes N.; desc. 120 ft. over a NW. slope.

22.60 Ravine, course N.; asc. 347 ft. over an E. slope.

38.67 The cor. of secs. 9, 10, 15 and 16.

Land, E.  $\frac{1}{2}$  rolling; W.  $\frac{1}{2}$  mountainous.

Soil, rocky; 2nd and 3rd rate.

Timber, pine, aspen and fir; undergrowth, 2nd growth timber.

-----  
N.  $1^{\circ} 25'$  W., bet. secs. 9 and 10.

Over mountainous land, through heavy timber and undergrowth; desc. slightly along an E. slope.

2.00 Spur, slopes NE.; desc. 611 ft. over a steep NE. slope.

25.00 Leave mountainous land, enter rolling land, bears E. and W.; desc. 136 ft. over a gradual NE. slope.

40.69 The  $\frac{1}{4}$  sec. cor., determined from the old bearing tree.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
S 9 | S 10  
1943

from which

Old bearing tree:

A pine, 20 ins. diam., bears S.  $27^{\circ}$  W., 86 lks. dist., mkd.  $\frac{1}{4}$  S B T.

New bearing trees:

A pine, 6 ins. diam., bears S.  $67\frac{1}{4}^{\circ}$  E., 80 lks. dist., mkd.  $\frac{1}{4}$  S 10 B T.

A pine, 5 ins. diam., bears N.  $25\frac{1}{2}^{\circ}$  W., 48 lks. dist., mkd.  $\frac{1}{4}$  S 9 B T.

A fence which extends N. and S., bears W. about 1 ch. dist.

Thence,

N.  $0^{\circ} 57'$  W., bet. secs. 9 and 10.

Descend 89 ft. over a NE. slope.

2.70 Old road, bears S.  $80^{\circ}$  W. and N.  $80^{\circ}$  E.

BOOK 4858

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains									
16.60	Graded road, bears NW. to Kendrick Park and SE. to Flagstaff.								
16.80	Road, bears NE. to Kendrick Park School and SW. to junction with graded road.								
20.77	SW. cor. of Kendrick Park School, bears N. $88\frac{1}{4}^{\circ}$ E., 3.33 chs. dist.								
22.60	Wire fence, bears easterly, and westerly 20 lks. dist. to a fence cor.; fence extends northerly, southerly and easterly.								
39.65	The cor. of secs. 3, 4, 9 and 10, determined from old bearing trees.  Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. below the surface of the road, at the cor. of secs. 3, 4, 9 and 10, with brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T23N R6E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 9</td><td>S 10</td></tr> </table>	T23N R6E		S 4	S 3	-----		S 9	S 10
T23N R6E									
S 4	S 3								
-----									
S 9	S 10								
	1943								
	from which								
	Old bearing trees:								
	A pine, 20 ins. diam., bears S. $48\frac{3}{4}^{\circ}$ E., 24 lks. dist., mkd. T 23 N R 6 E S 10 B T.								
	A pine, 22 ins. diam., bears S. $55\frac{3}{4}^{\circ}$ W., 34 lks. dist., mkd. T 23 N R 6 E S 9 B T.								
	New bearing trees:								
	A pine, 14 ins. diam., bears N. $32^{\circ}$ E., 58 lks. dist., mkd. T 23 N R 6 E S 3 B T.								
	A pine, 6 ins. diam., bears N. $14\frac{1}{4}^{\circ}$ W., 118 lks. dist., mkd. T 23 N R 6 E S 4 B T.								
	This cor. is located in a graded road, bears SW. and N. $0^{\circ} 32'$ W.								
	Land, S. 25 chs. mountainous; remainder of line rolling. Soil, rocky; 2nd and 3rd rate. Timber, pine, aspen, fir and spruce; undergrowth, 2nd growth timber.								
	-----								
	From the cor. of secs. 2, 3, 10 and 11.								
	N. $89^{\circ} 46'$ W., bet. secs. 3 and 10.								
	Over rolling land, through heavy timber and undergrowth; desc. 70 ft. over a NW. slope.								
10.00	Foot of steep descent, bears NE. and SW.; desc. gradually along a gentle N. slope.								
16.85	Graded road, bears NE. and SW.								
39.30	Dim road, bears N. and S.								
40.08	The $\frac{1}{4}$ sec. cor.; as evidenced by an old mound of stone, 3 ft. base, 1 ft. high. Find no marked stone.								

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4033

## Chains

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground, to bedrock, and in a mound of stone to top, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 3}{S 10}$$

1943

from which

Old bearing tree:

A pine stump, 30 ins. diam., bears N.  $24\frac{1}{2}^{\circ}$  W., 94 lks. dist., find no marks.

New bearing trees:

A pine, 5 ins. diam., bears N.  $36\frac{3}{4}^{\circ}$  W., 46 lks. dist., mkd.  $\frac{1}{4}$  S 3 B T.

A pine, 6 ins. diam., bears S.  $8\frac{1}{2}^{\circ}$  E., 180 lks. dist., mkd.  $\frac{1}{4}$  S 10 B T.

Thence,

S.  $89^{\circ} 52'$  W., bet. secs. 3 and 10.

Along a gentle N. slope.

- 9.70 Wire fence, bears N. and S.
- 15.00 Leave heavy timber and undergrowth, enter cultivated land and Kendrick Park, bears N. and S.
- 30.00 Wire fence, bears N. and S., leave cultivated land.
- 30.40 Private road, bears N. and S. approx. 12 chs. to a ranch house.
- 32.00 Enter heavy timber and undergrowth, leave Kendrick Park, bears N. and S. asc. gradually along a N. slope.
- 40.27 Wire fence, bears northerly and southerly.
- 40.55 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.

Soil, in cultivated field 1st rate; remainder of line, rocky; 3rd rate.

Timber, pine, aspen and fir; undergrowth, 2nd growth timber.

-----

N.  $0^{\circ} 32'$  W., bet. secs. 3 and 4.

Over nearly level land, along a graded road with heavy timber and undergrowth to the E. and W.; desc. gradually.

- 4.00 Leave heavy timber and undergrowth to the E. and W. of road, enter Kendrick Park, bears E. and W.
- 10.00 A fence cor., bears W., 32 lks. dist.; fence extends N.  $0^{\circ} 32'$  W. and westerly.
- 39.40 A fence cor., bears W., 42 lks. dist.; fence extends S.  $0^{\circ} 32'$  E., and westerly.
- 40.77 Proportional distance,



BOOK: 4353

Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

Set a brass tablet,  $3\frac{1}{2}$  ins. diam., 3 in. stem, in a granite stone, 16x10x7 ins., 14 ins. below the surface of the road, at the  $\frac{1}{4}$  sec. cor., with brass tablet mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 4\ | \ S\ 3 \\ 1943 \end{array}$$

At a point N. 45° E., 64 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for witness  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 4\ | \ S\ 3 \\ WC\ 1943 \end{array}$$

At a point S. 45° W., 64 lks. dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 4\ | \ S\ 3 \\ WC \\ 1943 \end{array}$$

Continue along center line of graded road.

51.00 Ranch road, bears W. from graded road.

55.00 A fence cor., bears W., 42 lks. dist.; fence extends N. 0° 32' W. and westerly.

60.10 A fence cor., bears E., 46 lks. dist.; fence extends northerly, southerly and easterly.

81.42 The cor. of secs. 3, 4, 33 and 34, on N. bdy. of the Tp.

Land, nearly level.

Soil, volcanic ash; 2nd and 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp:

N. 0° 18' W., bet. secs. 32 and 33.

Over rolling land, through heavy timber and undergrowth; asc. 55 ft. over a gentle SW. slope:

23.00 Spur, slopes S. 70° W.; desc. 20 ft. over a NE. slope.

26.50 Draw, drains W.; asc. 46 ft. over a SW. slope.

39.88 Proportional distance,

Set an iron post; 3 ft. long, 1 in. diam., 16 ins. in the ground, to bedrock, with a stone mkd. X deposited at the base, and in a mound of stone to top, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 7853

## Chains

$\frac{1}{4}$   
 S 32 | S 33  
 1943

from which

A pine, 12 ins. diam., bears N.  $48^\circ$  E., 119 lks. dist., mkd.  $\frac{1}{4}$  S 33 B T.

A pine, 12 ins. diam., bears N.  $48\frac{3}{4}^\circ$  W., 90 lks. dist., mkd.  $\frac{1}{4}$  S 32 B T.

Ascend over a gradual SW. slope.

54.00 Spur, slopes SW.; desc. 20 ft. over a NW. slope.

58.90 Draw, 1.50 chs. wide, drains SW.

66.40 Old road, bears S.  $60^\circ$  W. and N.  $60^\circ$  E.; asc. 30 ft. over a SW. slope.

79.76 The cor. of secs. 28, 29, 32 and 33, determined from old bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, at the cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

T23N R6E  
 S 29 | S 28  
 ————  
 S 32 | S 33  
 1943

from which

## Old bearing trees:

A pine stump, 20 ins. diam., bears S.  $75\frac{3}{4}^\circ$  E., 100 lks. dist., mkd. T 23 N R 6 E S 32 B T.

A dead pine, 12 ins. diam., bears S.  $65\frac{1}{2}^\circ$  W., 145 lks. dist., mkd. T 23 N R 6 E S 32 B T.

A pine, 20 ins. diam., bears N.  $13\frac{3}{4}^\circ$  W., 10 lks. dist., marks overgrown, mark on overgrowth T 23 N R 6 E S 29 B T.

## New bearing trees:

A pine, 6 ins. diam., bears N.  $37\frac{1}{2}^\circ$  E., 117 lks. dist., mkd. T 23 N R 6 E S 28 B T.

A pine, 6 ins. diam., bears S.  $81\frac{1}{2}^\circ$  E., 130 lks. dist., mkd. T 23 N R 6 E S 33 B T.

A pine, 24 ins. diam., bears S.  $65^\circ$  W., 117 lks. dist., mkd. T 23 N R 6 E S 32 B T.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

Chains	
	From the cor. of secs. 27, 28, 33 and 34. N. 89° 54' W., bet. secs. 28 and 33. Over rolling land, through heavy timber and undergrowth; asc. along a gentle S. slope.
0.12	Old rail fence, bears northerly and southerly.
18.20	Low spur, slopes SW.; desc. 40 ft. over a gradual SW. slope.
40.17	The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone, 20x9x6 ins. in a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on N. face.  Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bedrock, with the old stone buried alongside, and in a mound of stone to top, at the $\frac{1}{4}$ sec. cor., with brass cap mkd.  <div style="text-align: center;">           S 28  <math>\frac{1}{4}</math> —————            S 33.            1943         </div> <div style="text-align: right;">from which</div> <p>A pine, 6 ins. diam., bears N. 30<math>\frac{1}{2}</math>° E., 27 lks. dist., mkd. <math>\frac{1}{4}</math> S 28 B T.</p> <p>A pine, 12 ins. diam., bears S. 46<math>\frac{3}{4}</math>° E., 82 lks. dist., mkd. <math>\frac{1}{4}</math> S 33 B T.</p> <p>Find no evidence of original B Ts.</p> <p>Thence, S. 89° 49' W., bet. secs. 28 and 33. Descend over a gradual SW. slope.</p>
1.15	A fence cor., bears N. 30 lks. dist.; fence extends S. and easterly.
2.20	Old road, bears S. and N. for 1.50 chs. then N. 80° E.
4.20	Shallow draw, drains SW.; asc. along a gentle S. slope.
13.40	Low spur, slopes S. from NE.; desc. gradually over a SW. slope.
17.10	Shallow draw, drains SW. asc. along a gentle S. slope.
40.11	The cor. of secs. 28, 29, 32 and 33.  Land, rolling. Soil, rocky; 3rd rate. Timber, pine and aspen; undergrowth, 2nd growth timber.  -----  N. 2° 19' E., bet. secs. 28 and 29.  Over rolling land, through heavy timber and undergrowth; asc. 121 ft. over a SW. slope.
30.50	Spur, slopes SW.; asc. gradually along a gentle W. slope.
33.80	Road, bears E. to Hart Prairie and W. to a graded road.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4853

## Chains

39.94 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 29 | \text{S } 28 \\ 1943 \end{array}$$

from which

A pine, 6 ins. diam., bears East, 7 lks.  
dist., mkd.  $\frac{1}{4}$  S 28 B T.

A pine, 5 ins. diam., bears N.  $18\frac{1}{2}^\circ$  W., 7 lks.  
dist., mkd.  $\frac{1}{4}$  S 29 B T.

Ascend 29 ft. along a W. slope.

45.00 Top of ascent, bears E. and W., thence, along a W. slope.

57.50 Shallow draw; drains SW.; asc. 35 ft. over a SW. slope.

71.00 Road, bears N.  $10^\circ$  E. and S.  $10^\circ$  W.79.20 Same road, bears N.  $5^\circ$  W. and S.  $5^\circ$  E.

79.88 The cor. of secs. 20, 21, 28 and 29, as evidenced by a sandstone,  $14 \times 12 \times 10$  ins., in a mound of stone, 3 ft. base, 1 ft. high, mkd. 2 grooves on S; and 4 grooves on E: faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old stone buried alongside, at the cor. of secs. 20, 21, 28 and 29, with brass cap mkd.

$$\begin{array}{c} \text{T23N R6E} \\ \text{S } 20 | \text{S } 21 \\ \hline \text{S } 29 | \text{S } 28 \\ 1943 \end{array}$$

from which

A pine, 18 ins. diam., bears N.  $50^\circ$  E., 73 lks.  
dist., mkd. T 23 N R 6 E S 21 B T.

A pine, 5 ins. diam., bears S.  $19^\circ$  E., 37 lks.  
dist., mkd. T 23 N R 6 E S 28 B T.

A pine, 4 ins. diam., bears S.  $13\frac{1}{2}^\circ$  W., 34 lks.  
dist., mkd. T 23 N R 6 E S 29 B T.

A pine, 10 ins. diam., bears N.  $15\frac{1}{2}^\circ$  W., 66 lks.  
dist., mkd. T 23 N R 6 E S 20 B T.

Find no evidence of old B Ts.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

BOOK 4858

Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains

From the cor. of secs. 21, 22, 27 and 28.

S. 89° 44' W., bet. secs. 21 and 28.

Over rolling land, through heavy timber and undergrowth; asc. gradually over a rolling SE. slope.

0.64 Wire fence, bears northerly and southerly.

24.20 Drain, course SW.; desc. 77 ft. along a S. slope.

38.36 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   $\frac{S\ 21}{S\ 28}$   
 1943

from which

A pine, 5 ins. diam., bears N. 8 $\frac{1}{4}$ ° E., 21 lks. dist., mkd.  $\frac{1}{4}$  S 21 B T.

A pine, 5 ins. diam., bears S. 52° W., 26 lks. dist., mkd.  $\frac{1}{4}$  S 28 B T.

Descend 67 ft. along a S. slope.

53.00 Spur, slopes SW.; desc. 52 ft. over a SW. slope.

76.72 The cor. of secs. 20, 21, 28 and 29.

Land, rolling.  
 Soil, rocky; 3rd rate.  
 Timber, pine and aspen; undergrowth; 2nd growth timber.

N. 0° 16' E., bet. secs. 20 and 21.

Over rolling land, through heavy timber and undergrowth; asc. 79 ft. over a SW. slope.

23.20 Spur, slopes S. 30° W.; desc. 23 ft. over a NW. slope.

37.75 Road, bears SW. and NE.

39.84 The  $\frac{1}{4}$  sec. cor., as evidenced by an old mound of stone, 2 ft. base, 1 ft. high.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 20 | S 21  
 1943

from which

Old bearing tree:

An aspen, 24 ins. diam., bears N. 46 $\frac{1}{2}$ ° W., 110 lks. dist., mkd.  $\frac{1}{4}$  S B T.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4010

## Chains

## New bearing trees:

A pine, 6 ins. diam., bears S.  $37\frac{1}{2}^{\circ}$  E., 14 lks.  
dist., mkd.  $\frac{1}{4}$  S 21 B T.

A pine, 5 ins. diam., bears S.  $63\frac{1}{2}^{\circ}$  W., 40 lks.  
dist., mkd.  $\frac{1}{4}$  S 20 B T.

Thence,

N.  $0^{\circ} 03'$  E., bet. secs. 20 and 21.

Descend gradually over a NW. slope.

5.00 Slope changes; asc. 38 ft. over a SW. slope.

40.14 The cor. of secs. 16, 17, 20 and 21, as evidenced by a wood post, 3 ins. sq., 2 ft. long, in a mound of stone, 3 ft. base, 1 ft. high, marks illegible.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the old wood post buried alongside, at the cor. of secs. 16, 17, 20 and 21, with brass cap mkd.

T23N R6E	
S 17	S 16
-----	
S 20	S 21
1943	

from which

## Old bearing trees:

A pine, 24 ins. diam., bears N.  $54\frac{3}{4}^{\circ}$  E., 122 lks.  
dist., mkd. T 23 N R 6 E S 16 B T.

An aspen, 15 ins. diam., bears S.  $65^{\circ}$  W., 74 lks.  
dist., marks indiscernible.

## New bearing trees:

A pine, 5 ins. diam., bears N.  $41^{\circ}$  E., 41 lks.  
dist., mkd. T 23 N R 6 E S 16 B T.

A pine, 7 ins. diam., bears S.  $24\frac{1}{4}^{\circ}$  E., 52 lks.  
dist., mkd. T 23 N R 6 E S 21 B T.

A pine, 6 ins. diam., bears S.  $17\frac{1}{2}^{\circ}$  W., 45 lks.  
dist., mkd. T 23 N R 6 E S 20 B T.

A pine, 5 ins. diam., bears N.  $61^{\circ}$  W., 9 lks.  
dist., mkd. T 23 N R 6 E S 17 B T.

Land, rolling.

Soil, rocky; 2nd and 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 15, 16, 21 and 22.

S.  $89^{\circ} 39'$  W., bet. secs. 16 and 21.

Over mountainous land, through heavy timber and undergrowth; asc. 195 ft. over a SE. slope.

15.24 Wire fence, bears N.  $30^{\circ}$  E. and S.  $10^{\circ}$  W.

Chains	
15.85	Ridge, bears N. 30° E. and S. 30° W. about 20 chs. to a deep saddle; desc. 176 ft. over a W. slope.
22.15	Ravine, course SW.; continue descent of 192 ft. over a SW. slope.
38.84	The $\frac{1}{4}$ sec. cor., determined from the old bearing tree. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S\ 16}{S\ 21}$ 1943
	from which
	Old bearing tree: A pine, 28 ins. diam., bears N. 49 $\frac{1}{2}$ ° E., 120 lks. dist., mkd. $\frac{1}{4}$ S B T. New bearing trees: A pine, 10 ins. diam., bears N. 45 $\frac{1}{2}$ ° E., 101 lks. dist., mkd. $\frac{1}{4}$ S 16 B T. A pine, 16 ins. diam., bears S. 63 $\frac{3}{4}$ ° W., 79 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.
	Thence, N. 89° 21' W., bet. secs. 16 and 21. Over rolling land; desc. 140 ft. over a SW. slope.
16.50	Road, bears N. 60° W. and S. 60° E.
28.00	Spur, slopes W. from NE.; desc. 33 ft. along top of spur.
33.00	Leave top of spur, slopes SW.; desc. 64 ft. over a W. slope.
40.02	The cor. of secs. 16, 17, 20 and 21. Land, E. $\frac{1}{2}$ mountainous; W. $\frac{1}{2}$ rolling. Soil, rocky; 3rd rate. Timber, pine and aspen; undergrowth, 2nd growth timber.
	----- N. 4° 58' W., bet. secs. 16 and 17. Over rolling land, through heavy timber and undergrowth; asc. gradually along a W. slope.
7.30	Ridge, bears E. and W.; desc. 9 ft. over a gradual NW. slope.
11.40	Ravine, course W., thence, along a rolling W. slope.
18.40	Spur, slopes NW.; desc. 15 ft. over a NE. slope.
39.17	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the $\frac{1}{4}$ sec. cor., with brass cap mkd.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOM 1000

Chains

$$\frac{1}{4}$$

$$S 17 \frac{1}{2} S 16$$

$$1943$$

from which

A pine, 5 ins. diam., bears N.  $59\frac{1}{2}^{\circ}$  E., 86 lks. dist., mkd.  $\frac{1}{4}$  S 16 B T.

A pine, 5 ins. diam., bears S.  $79^{\circ}$  W., 103 lks. dist., mkd.  $\frac{1}{4}$  S 17 B T.

Ascend gradually along a W. slope.

43.70 Top of ascent, bears E. and W.; desc. 175 ft. over a NE. slope.

64.70 Enter draw, drains NW.

76.70 Leave draw, drains NW.; asc. gradually over a SW. slope.

78.34 The cor. of secs. 8, 9, 16 and 17, as evidenced by a pine, 28 ins. diam., mkd. S 17 on SW. side, other marks overgrown, not uncovered, from which

Old bearing trees:

A dead pine, 24 ins. diam., bears N.  $45^{\circ}$  E., 9 lks. dist., mkd. T 23 N R 6 E S 9 B T.

A pine stump, 24 ins. diam., bears S.  $25^{\circ}$  W., 69 lks. dist., mkd. B T; marks, on remainder of tree which is lying on ground, overgrown and not uncovered.

For witness cor. see the field notes of the line bet. secs. 8 and 9.

Land, rolling.

Soil, rocky; 2nd and 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

-----

From the cor. of secs. 9, 10, 15 and 16.

S.  $89^{\circ} 24'$  W., bet. secs. 9 and 16.

Over mountainous land, through heavy timber and undergrowth; asc. 43 ft. over an E. slope.

2.00 Spur, slopes N.  $20^{\circ}$  E.; asc. 45 ft. along a steep N. slope.

5.80 Wire fence, bears N. and S.

8.00 Spur, slopes N.; desc. 685 ft. over a W. slope.

33.90 Ravine, course N.; leave mountainous land, bears N. and SW.; thence, over rolling land; desc. 44 ft. over a gradual NW. slope.

41.86 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.



## Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains

$$\frac{1}{4} \frac{S 9}{S 16}$$
 1943

from which

A pine, 3 ins. diam., bears N.  $23\frac{1}{4}^{\circ}$  W., 36 lks.  
dist., mkd.  $\frac{1}{4}$  S 9 B T.

A pine, 10 ins. diam., bears S.  $34^{\circ}$  E., 69 lks.  
dist., mkd.  $\frac{1}{4}$  S 16 B T.

Desc. 90 ft. over a NW. slope; over rolling land.

52.60 Old road, bears NE. and SW.

62.00 Shallow draw, drains N.; asc. gradually over an E. slope.

66.50 Low Spur, slopes N.; thence, along a rolling N. slope.

74.00 Old road, bears N. and S.

83.72 The cor. of secs. 8, 9, 16 and 17.

Land, E.  $\frac{1}{2}$  mountainous; W.  $\frac{1}{2}$  rolling.

Soil, rocky; 3rd and 4th rate.

Timber, pine, aspen, fir and spruce; undergrowth, 2nd growth timber.

-----  
N.  $0^{\circ} 08'$  E., bet. secs. 8 and 9.

Over rolling land, through heavy timber and undergrowth;  
desc. 60 ft. over a gradual N. slope.

0.50 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the  
ground for witness cor. of secs. 8, 9, 16 and 17, with  
brass cap mkd.

$$\begin{array}{c} T23N R6E \\ S 8 | S 9 \\ \hline S 17 | S 16 \\ W C \\ 1943 \end{array}$$

from which

A pine, 10 ins. diam., bears N.  $18\frac{3}{4}^{\circ}$  E., 53 lks.  
dist., mkd. W C T 23 N R 6 E S 9 B T.

A pine, 6 ins. diam., bears S.  $78\frac{1}{2}^{\circ}$  E., 78 lks.  
dist., mkd. W C T 23 N R 6 E S 16 B T.

A pine, 5 ins. diam., bears S.  $48^{\circ}$  W., 128 lks.  
dist., mkd. W C T 23 N R 6 E S 17 B T.

A pine, 12 ins. diam., bears N.  $23\frac{1}{2}^{\circ}$  W., 141 lks.  
dist., mkd. W C T 23 N R 6 E S 8 B T.

40.05 Graded road, bears SW. to Flagstaff and NE. to Kendrick  
Park.

40.39 The  $\frac{1}{4}$  sec. cor., determined from old bearing tree.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the  
ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4253

Chains

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 8 \frac{1}{4} \text{ S } 9 \\ 1943 \end{array}$$

from which

Old bearing tree:

A pine stump, 32 ins. diam., bears N.  $15\frac{1}{4}^\circ$  W., 59 lks. dist., mkd. B T; remainder of tree, lying on ground, mkd.  $\frac{1}{4}$  S.

New bearing trees:

A pine, 5 ins. diam., bears S.  $28^\circ$  E., 154 lks. dist., mkd.  $\frac{1}{4}$  S 9 B T.

A pine, 7 ins. diam., bears S.  $82\frac{1}{2}^\circ$  W., 200 lks. dist., mkd.  $\frac{1}{4}$  S 8 B T.

Descend gradually over a N. slope.

73.09 Old road, bears E. and W.

81.11 The cor. of secs. 4, 5, 8 and 9, as evidenced by a lava stone, 18x12x4 ins., in a mound of stone, 3 ft. base, 1 ft. high, mkd. 5 notches on S. and 4 notches on E. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the old stone buried alongside, at the cor. of secs. 4, 5, 8 and 9, with brass cap mkd.

$$\begin{array}{c} \text{T23N R6E} \\ \text{S } 5 \frac{1}{4} \text{ S } 4 \\ \hline \text{S } 8 \frac{1}{4} \text{ S } 9 \\ 1943 \end{array}$$

from which

Old bearing tree:

A pine, 30 ins. diam., bears N.  $22\frac{1}{2}^\circ$  W., 20 lks. dist., mkd. 6 E S 5 B T; mark on over growth, T 23 N R 6 E S 5 B T. This tree not of record.

New bearing trees:

A pine, 5 ins. diam., bears N.  $44\frac{1}{2}^\circ$  E., 75 lks. dist., mkd. T 23 N R 6 E S 4 B T.

A pine, 5 ins. diam., bears S.  $31^\circ$  E., 91 lks. dist., mkd. T 23 N R 6 E S 9 B T.

A pine, 30 ins. diam., bears S.  $63^\circ$  W., 77 lks. dist., mkd. T 23 N R 6 E S 8 B T.

Land, rolling.

Soil, rocky; 2nd and 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains

From the cor. of secs. 3, 4, 9 and 10.

S. 89° 40' W., bet. secs. 4 and 9.

Over rolling land, through heavy timber and undergrowth; ascend gradually over a rolling NE. slope.

19.05 Ranch road, bears SE. and NW.

33.30 Old road, bears N. and S.

41.50 The 1/4 sec. cor., determined from the old bearing tree.

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, to bedrock, and in a mound of stone to top, at the 1/4 sec. cor., with brass cap mkd.

1/4 S 4  
S 9  
1943

from which

Old bearing tree:

A pine stump, 34 ins. diam., bears N. 87° W., 26 lks. dist., mkd. 1/4 S B T.

New bearing trees:

A pine, 5 ins. diam., bears N. 8 1/2° E., 103 lks. dist., mkd. 1/4 S 4 B T.

A pine, 5 ins. diam., bears S. 38 1/4° E., 39 lks. dist., mkd. 1/4 S 9 B T.

Thence,

N. 89° 45' W., bet. secs. 4 and 9.

Ascend gradually along a rolling N. slope.

16.35 Old road, bears N. and S.

28.45 Low spur, slopes N. 30° E. from S.; desc. gradually over a W. slope.

32.55 Dim road, bears N. 30° E. and S. 30° W.

33.45 Shallow draw, drains N. 30° E.; thence, along a gentle N. slope.

40.43 The cor. of secs. 4, 5, 8 and 9.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

N. 0° 34' E., bet. secs. 4 and 5.

Over rolling land, through heavy timber and undergrowth; ascend gradually.

5.00 Low spur, slopes NE.; desc. 90 ft. over a N. slope.

40.87 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4353

Chains

ground, to bedrock, and in a mound of stone to top, at the  
 $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 5 | S 4  
 1943

from which

A pine, 6 ins. diam., bears N.  $48^{\circ}$  E., 120 lks.  
 dist., mkd.  $\frac{1}{4}$  S 4 B T.

A pine, 4 ins. diam., bears N.  $23^{\circ}$  W., 49 lks.  
 dist., mkd.  $\frac{1}{4}$  S 5 B T.

Descend 67 ft. over a N. slope.

61.70 Draw, drains N.  $80^{\circ}$  E.; asc. 15 ft. over a SE. slope.

68.80 Top of a rocky knoll; desc. 15 ft. over a NE. slope.

71.00 Leave heavy timber and undergrowth, bears SE. and W.;  
 thence, across Kendrick Park, land nearly level.

81.14 The cor. of secs. 4, 5, 32 and 33, on N. bdy. of the Tp.

Land, S. 71 chs. rolling; remainder of line, nearly level.  
 Soil, in rolling land, rocky; 3rd rate; in level land,  
 1st rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

-----  
 From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of  
 the Tp.

N.  $0^{\circ} 12'$  W., bet. secs. 31 and 32.

Over rolling land, through heavy timber and dense under-  
 growth; asc. 14 ft. over a S. slope.

3.50 Low spur, slopes SW.; desc. 20 ft. over a NW. slope.

13.70 Draw, 50 lks. wide, drains SW.; asc. 102 ft. over a SE.  
 slope.

24.60 Road, bears SW. and N.  $60^{\circ}$  E.

37.00 Slope changes; asc. gradually along a gentle W. slope.

39.60 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
 ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   
 S 31 | S 32  
 1943

from which

A pine, 12 ins. diam., bears N.  $74\frac{1}{4}^{\circ}$  E., 178 lks.  
 dist., mkd.  $\frac{1}{4}$  S 32 B T.

A pine, 4 ins. diam., bears S.  $85\frac{3}{4}^{\circ}$  W., 47 lks.  
 dist., mkd.  $\frac{1}{4}$  S 31 B T.

Ascend gradually along a gentle W. slope.

BOOK 4353

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

- 54.60 Low spur, slopes SW.; desc. 23 ft. over a NW. slope.
- 60.80 Road, bears S. 80° W. to Lava River Cave and N. 80° E. to Flagstaff-Kendrick Park road.
- 63.00 Shallow draw, drains SW.; asc. 24 ft. over a S. slope.
- 70.50 Spur, slopes W.; desc. 10 ft. over a NW. slope.
- 79:20 The cor. of secs. 29, 30, 31 and 32, as evidenced by a sandstone, 24x20x7 ins., in a mound of stone, 3 ft. base, 1 ft. high, mkd. 1 notch on S. and 5 notches on E. edges.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old stone buried alongside, at the cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

T23N R6E	
S 30	S 29
-----	
S 31	S 32
1943	

from which

## Old bearing trees:

Original position of a dead pine, lying on ground, bears N. 21½° E., 75 lks. dist., marks indiscernible.

A pine, 24 ins. diam., bears S. 54° E., 30 lks. dist., marks overgrown, mark on overgrowth T 23 N R 6 E S 32 B T.

Original position of a dead pine, lying on ground, bears N. 35½° W., 51 lks. dist., marks indiscernible.

## New bearing trees:

A pine, 6 ins. diam., bears N. 63½° E., 187 lks. dist., mkd. T 23 N R 6 E S 29 B T.

A pine, 5 ins. diam., bears S. 58½° W., 19 lks. dist., mkd. T 23 N R 6 E S 31 B T.

A pine, 5 ins. diam., bears N. 68½° W., 65 lks. dist., mkd. T 23 N R 6 E S 30 B T.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

-----

From the cor. of secs. 28, 29, 32 and 33.

S. 89° 47' W., bet. secs. 29 and 32.

Over rolling land, through heavy timber and dense undergrowth; desc. gradually over a SW. slope.

- 30.00 Spur, slopes SW.; desc. slightly over a gentle NW. slope.

- 40.07 The ¼ sec. cor., as evidenced by a wood post, 3 ins. sq., 30 ins. long, in a mound of stone, 2 ft. base, 1 ft. high, marks indiscernible.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, to bedrock, with the old wood post buried alongside, and in a mound of stone to top, at the ¼ sec. cor.,

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4353

## Chains

with brass cap mkd.

$$\frac{1}{4} \frac{S 29}{S 32}$$

1943

from which

## Old bearing trees:

A pine, 18 ins. diam., bears N.  $65\frac{1}{4}^{\circ}$  W., 23 lks. distance, marks indiscernible.

A pine stump, 24 ins. diam., bears S.  $15\frac{3}{4}^{\circ}$  E., 45 lks. dist., no marks.

## New bearing trees:

A pine, 10 ins. diam., bears N.  $38^{\circ}$  W., 84 lks. dist., mkd.  $\frac{1}{4}$  S 29 B T.

A pine, 7 ins. diam., bears S.  $1\frac{1}{2}^{\circ}$  W., 97 lks. dist., mkd.  $\frac{1}{4}$  S 32 B T.

Thence,

S.  $89^{\circ} 40'$  W., bet. secs. 29 and 32.

Descend 90 ft. over a NW. slope.

25.35 Graded road, bears S.  $15^{\circ}$  E. to Flagstaff and N.  $5^{\circ}$  W. to Kendrick Park.

40.08 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth pine.

-----  
S.  $89^{\circ} 50'$  W., bet. secs. 30 and 31.

Over rolling land, through heavy timber and undergrowth; desc. gradually over a NW. slope.

1.50 Drain, course S.  $20^{\circ}$  W.; desc. gradually over a SW. slope.

15.00 Low spur, slopes SW.; desc. over a gentle NW. slope.

39.97 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 30}{S 31}$$

1943

from which

A pine, 4 ins. diam., bears N.  $53^{\circ}$  W., 76 lks. dist., mkd.  $\frac{1}{4}$  S 30 B T.

A pine, 5 ins. diam., bears S.  $11^{\circ}$  W., 67 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.

Descend over a gradual W. slope.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

- 75.40 Road, bears NW. to Lava River Cave and SE. to Flagstaff-Kendrick Park road.
- 79.11 The cor. of secs. 25, 30, 31 and 36, on W. bdy. of the Tp., described in field notes of T. 23 N., R. 5 E., this group.  
Land, rolling.  
Soil, rocky; 3rd rate.  
Timber, pine and aspen; undergrowth, 2nd growth pine.
- 
- From the cor. of secs. 29, 30, 31 and 32.  
N. 1° 24' E., bet. secs. 29 and 30.  
Over rolling land, through heavy timber and undergrowth; ascend gradually over a SW. slope.
- 2.20 Drain, course S. 20° W.; asc. 73 ft. over a SW. slope.
- 32.50 Top of ascent, bears SW. and NE.; thence, along a W. slope.
- 40.15 Proportional distance,  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $\frac{1}{4}$   
 S 30 | S 29  
 1943
- from which
- A pine, 6 ins. diam., bears S. 11 $\frac{3}{4}$ ° E., 21 lks. dist., mkd.  $\frac{1}{4}$  S 29 B T.
- A pine, 4 ins. diam., bears N. 31 $\frac{3}{4}$ ° W., 23 lks. dist., mkd.  $\frac{1}{4}$  S 30 B T.
- Ascend 98 ft. along a W. slope.
- 43.60 Road, bears W. to Keith's ranch and E. to graded road.
- 55.75 Graded road, bears N. 20° W. to Kendrick Park and S. 20° E. to Flagstaff.
- 66.80 Low spur, slopes W.; desc. 12 ft. along a W. slope.
- 80.30 The cor. of secs. 19, 20, 29 and 30, determined by the method of double proportional measurement.  
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, to bedrock, and in a mound of stone to top, at the cor. of secs. 19, 20, 29 and 30, with brass cap mkd.

T23N R6E  
 S 19 | S 20  
 S 30 | S 29  
 1943

from which

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4853

## Chains

A pine, 5 ins. diam. bears N.  $26\frac{1}{2}^{\circ}$  E., 74 lks.  
dist., mkd. T 23 N R 6 E S 20 B T.

A pine, 10 ins. diam., bears S.  $31^{\circ}$  E., 65 lks.  
dist., mkd. T 23 N R 6 E S 29 B T.

A pine, 18 ins. diam., bears S.  $49^{\circ}$  W., 65 lks.  
dist., mkd. T 23 N R 6 E S 30 B T.

A pine, 20 ins. diam., bears N.  $32^{\circ}$  W., 141 lks.  
dist., mkd. T 23 N R 6 E S 19 B T.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 20, 21, 28 and 29.

N.  $89^{\circ} 44'$  W., bet. secs. 20 and 29.

Over rolling land, through heavy timber and undergrowth;  
desc. gradually along a S. slope.

0.25 Road, bears N.  $5^{\circ}$  W. and S.  $5^{\circ}$  E.

15.00 Low spur, slopes SW.; desc. over a gradual W. slope.

40.18 The  $\frac{1}{4}$  sec. cor., as evidenced by a sandstone, 24x14x6 ins.  
firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face, with a mound  
of stone 2 ft. base, 1 ft. high, S. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, with the old stone buried alongside, at the  $\frac{1}{4}$   
sec. cor., with brass cap mkd.

S 20  
 $\frac{1}{4}$  —————  
S 29  
1943

from which

Old bearing tree:

A pine stump, 30 ins. diam., bears S.  $50\frac{3}{4}^{\circ}$  W., 15 lks.  
dist., mkd.  $\frac{1}{4}$  S B T.

New bearing trees:

A pine, 6 ins. diam., bears N.  $20\frac{1}{2}^{\circ}$  E., 146 lks.  
dist., mkd.  $\frac{1}{4}$  S 20 B T.

A pine, 5 ins. diam., bears S.  $3^{\circ}$  E., 31 lks.  
dist., mkd.  $\frac{1}{4}$  S 29 B T.

Thence,

S.  $89^{\circ} 46'$  W., bet. secs. 20 and 29.

Descend 54 ft. over a gradual W. slope.

41.31 The cor. of secs. 19, 20, 29 and 30.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

-----



BOOK 4353

Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains

S. 89° 39' W., bet. secs. 19 and 30.

Over rolling land, through heavy timber and undergrowth; desc. over a gradual W. slope.

3.00 Graded road, bears S. to Flagstaff and N. to Kendrick Park.

41.16 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the 1/4 sec. cor., with brass cap mkd.

1/4 S 19 / S 30 1943

from which

A pine, 6 ins. diam., bears N. 20 3/4° W., 75 lks. dist., mkd. 1/4 S 19 B T.

A pine, 6 ins. diam., bears S. 71° W., 72 lks. dist., mkd. 1/4 S 30 B T.

Descend 41 ft. over a W. slope.

42.56 Road, bears S. and N. for 3 chs. then NE.

55.51 Road, bears SE. and NW. to Lava River Cave.

80.97 The cor. of secs. 19, 24, 25 and 30, on W. bdy. of the Tp., described in notes of T. 23 N., R. 5 E., this group. Land, rolling. Soil, rocky; 3rd rate. Timber, pine; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 19, 20, 29 and 30.

N. 0° 13' E., bet. secs. 19 and 20.

Over rolling land, through heavy timber and undergrowth; along a gentle W. slope.

14.60 Shallow draw, drains SW.; asc. 59 ft. over a gradual SW. slope.

35.00 Slope changes; asc. over a gradual S. slope.

40.14 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the 1/4 sec. cor., with brass cap mkd.

1/4 S 19 | S 20 1943

from which

A pine, 12 ins. diam., bears S. 53 1/2° E., 69 lks. dist., mkd. 1/4 S 20 B T.

A pine, 5 ins. diam., bears S. 75 1/2° W., 130 lks. dist., mkd. 1/4 S 19 B T.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 455

Chains	Ascend over a gradual S. slope.										
49.00	West end of an earth dam; extends E. across a draw which drains S.										
50.25	Old road, bears N. 80° E. and S. 80° W.										
62.40	Graded road, bears SW. to Flagstaff and NE. to Kendrick Park.										
65.00	Top of low wide ridge, bears E. and W.; desc. over a gradual N. slope.										
80.28	The cor. of secs. 17, 18, 19 and 20, as evidenced by a wood post, 3 ins. sq., 18 ins. long, in a mound of stone, 3 ft. base, 1½ ft. high, mkd. 3 notches on S. and 5 notches on E. edges.										
	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to bedrock, with the old wood post buried alongside, and in a mound of stone to top, at the cor. of secs. 17, 18, 19 and 20, with brass cap mkd.										
	<table style="margin: auto;"> <tr><td>T23N</td><td>R6E</td></tr> <tr><td>S 18</td><td>S 17</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td>S 19</td><td>S 20</td></tr> <tr><td colspan="2" style="text-align: center;">1943</td></tr> </table>	T23N	R6E	S 18	S 17			S 19	S 20	1943	
T23N	R6E										
S 18	S 17										
S 19	S 20										
1943											
	from which										
	A pine, 7 ins. diam., bears N. 81¾° E., 267 lks. dist., mkd. T 23 N R 6 E S 17 B T.										
	A pine, 24 ins. diam., bears S. 53¼° E., 278 lks. dist., mkd. T 23 N R 6 E S 20 B T.										
	A pine, 16 ins. diam., bears S. 66¾° W., 232 lks. dist., mkd. T 23 N R 6 E S 19 B T.										
	A pine, 20 ins. diam., bears N. 2½° W., 72 lks. dist., mkd. T 23 N R 6 E S 18 B T.										
	Find no evidence of old bearing trees.										
	Land, rolling.										
	Soil, rocky; 3rd rate.										
	Timber, pine and aspen; undergrowth, 2nd growth timber.										
	-----										
	From the cor. of secs. 16, 17, 20 and 21.										
	N. 89° 49' W., bet. secs. 17 and 20.										
	Over rolling land, through heavy timber and undergrowth; desc. 150 ft. over a broken W. slope.										
40.64	Proportional distance,										
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the ¼ sec. cor., with brass cap mkd.										
	<table style="margin: auto;"> <tr><td></td><td>S 17</td></tr> <tr><td>¼</td><td>-----</td></tr> <tr><td></td><td>S 20</td></tr> <tr><td colspan="2" style="text-align: center;">1943</td></tr> </table>		S 17	¼	-----		S 20	1943			
	S 17										
¼	-----										
	S 20										
1943											
	from which										
	A pine, 16 ins. diam., bears N. 44¾° E., 73 lks. dist., mkd. ¼ S 17 B T.										

BOOK 4353

Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains	<p>A pine, 16 ins. diam., bears S. <math>23\frac{3}{4}^{\circ}</math> E., 76 lks. dist., mkd. <math>\frac{1}{4}</math> S 20 B T.</p> <p>Descend 107 ft. over a broken W. slope.</p>
80.00	Graded road, bears N. $2^{\circ}$ W. and S. $2^{\circ}$ E.
81.28	The cor. of secs. 17, 18, 19 and 20.
	<p>Land, rolling. Soil, rocky; 2nd and 3rd rate. Timber, pine and aspen; undergrowth, 2nd growth timber.</p> <p>-----</p>
	S. $89^{\circ} 28'$ W., bet. secs. 18 and 19.
	Over rolling land, through heavy timber and undergrowth; asc. 30 ft. along a gentle N. slope.
25.00	Slope changes; asc. 128 ft. over a NE. slope; enter mountainous land, bears NW. and S.
40.99	Proportional distance,
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{S\ 18}{\frac{1}{4}} = S\ 19$ <p>1943.</p>
	from which
	<p>A pine, 8 ins. diam., bears N. <math>74\frac{1}{2}^{\circ}</math> E., 44 lks. dist., mkd. <math>\frac{1}{4}</math> S 18 B T.</p> <p>A pine, 6 ins. diam., bears S. <math>55^{\circ}</math> W., 33 lks. dist., mkd. <math>\frac{1}{4}</math> S 19 B T.</p>
	Along a N. slope.
41.00	Top of ascent, bears N. and S.; desc. 56 ft. along a N. slope.
42.07	A four strand barbed wire fence, bears N. $2\frac{1}{2}^{\circ}$ E. and S. $2\frac{1}{2}^{\circ}$ W. 62 lks. to a fence cor.; fence extends N. $2\frac{1}{2}^{\circ}$ E. and westerly.
51.00	Short spur, slopes NW.; desc. 116 ft. over a W. slope.
56.33	Wire fence, bears northerly, and southerly 60 lks. to a fence cor.; fence extends northerly, easterly and westerly; foot of steep descent; leave heavy timber and undergrowth, bears S. and NE.; thence, over nearly level land, along the S. edge of cultivated field.
77.00	A cabin, 10 x 12 ft., on line.
79.30	George C. Keith's house bears N., about 1 ch. dist.
80.79	<p>The cor. of secs. 13, 18, 19 and 24, on W. bdy. of the Tp., described in notes of T. 23 N., R. 5 E., this group.</p> <p>Land, E. 25 chs., rolling; W. 25 chs. nearly level, remainder of line, mountainous.</p> <p>Soil, W. 25 chains, 1st rate; remainder of line, rocky; 2nd and 3rd rate.</p> <p>Timber, pine, fir and aspen; undergrowth, 2nd growth timber.</p> <p>-----</p>

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 488

Chains	
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0° 31' W., bet. secs. 17 and 18.
	Over rolling land, through heavy timber and undergrowth; desc. over a gradual N. slope.
10.00	Slope changes; desc. over a gradual NW. slope.
26.00	Road, bears W. to a ranch house and E. to graded road.
30.00	W. edge of a bend in a graded road, bears S. 2° E. to Flagstaff and N. 20° E. to Kendrick Park.
32.20	A three strand barbed wire fence, bears N. 10° E. and S. 10° W.; leave rolling land, bears W. and NE.; thence over nearly level land.
39.56	Proportional distance,
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 18   S 17 1943
	from which
	A pine, 7 ins. diam., bears S. 83 $\frac{1}{4}$ ° E., 76 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.
	A pine, 24 ins. diam., bears N. 77° W., 115 lks. dist., mkd. $\frac{1}{4}$ S 18 B T.
	Center of Deer Tank, an earth reservoir, bears N. 38° E., 12.70 chs. dist.
	Over nearly level land.
40.32	A three strand barbed wire fence, bears SW., and NE. for 2 chs. to a fence cor.; fence extends SW., NE. and S. 10° W.; leave timber and undergrowth.
41.50	Enter cultivated land, bears SW. and NE. for 4 chs. then northerly.
47.26	A three strand barbed wire fence, bears NW. and SE. for 5 chs. to a fence cor.; fence extends NW. and southerly; leave cultivated land, enter 2nd growth pine thicket.
53.00	Enter heavy timber and undergrowth, bears E. and W.; asc. 18 ft. over a gradual S. slope.
55.40	Graded road, bears W. to Spring Valley and E. to junction with Flagstaff-Kendrick Park road.
65.00	Enter mountainous land, bears NW. and SE.; asc. 105 ft. over a SW. slope.
73.00	Top of a hill, bears N. 80° W. and E.; desc. 56 ft. over a N. slope.
79.12	The cor. of secs. 7, 8, 17 and 18, as evidenced by a lava stone, 12x7x5 ins., firmly set in the ground, mkd. 4 notches on S. and 5 notches on E. edges.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old stone buried alongside, at the cor. of secs. 7, 8, 17 and 18, with brass cap mkd.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains

T23N R6E	
S 7	S 8
-----	
S 18	S 17

1943

from which

Old bearing trees:

A pine, 36 ins. diam., bears S.  $4\frac{1}{2}^{\circ}$  W., 125 lks. dist., marks overgrown, mark on overgrowth T 23 N R 6 E S 18 B T.

A pine stump, 40 ins. diam., bears N.  $70^{\circ}$  W., 63 lks. dist., mkd. T 23 N R 6 7 B T. Other marks destroyed by decay.

New bearing trees:

A pine, 18 ins. diam., bears N.  $38\frac{3}{4}^{\circ}$  E., 208 lks. dist., mkd. T 23 N R 6 E S 8 B T.

A pine, 5 ins. diam., bears S.  $50^{\circ}$  E., 133 lks. dist., mkd. T 23 N R 6 E S 17 B T.

A pine, 5 ins. diam., bears N.  $67\frac{3}{4}^{\circ}$  W., 114 lks. dist., mkd. T 23 N R 6 E S 7 B T.

Land, S. 32 chs., rolling; N. 14 chs. mountainous, remainder of line, nearly level.

Soil, rolling and mountainous land, rocky; 2nd and 3rd rate; the nearly level land, 1st rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.

From the cor. of secs. 8, 9, 16 and 17.

N.  $88^{\circ} 52'$  W., bet. secs. 8 and 17.

Over rolling land, through heavy timber and undergrowth; desc. 45 ft. over a NW. slope.

6.00 Old road, bears N. and S.

27.30 Graded road, bears S.  $30^{\circ}$  W. to Flagstaff and N.  $30^{\circ}$  E. to Kendrick Park.

35.00 Drain, course N.; asc. gradually over a NE. slope.

37.62 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 8	
$\frac{1}{4}$	-----
S 17	
1943	

from which

A pine, 5 ins. diam., bears N.  $16\frac{1}{2}^{\circ}$  W., 114 lks. dist., mkd.  $\frac{1}{4}$  S 8 B T.

A pine, 4 ins. diam., bears S.  $26\frac{1}{2}^{\circ}$  E., 91 lks. dist., mkd.  $\frac{1}{4}$  S 17 B T.

Ascend 18 ft. over a NE. slope.

45.00 Spur, slopes NW., thence, along a gentle S. slope.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

BOOK 4858

Chains	
55.00	Slope changes; asc. 67 ft. over an E. slope.
65.00	Spur, slopes NW.; desc. 87 ft. over a SW. slope.
75.24	The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, rocky; 2nd and 3rd rate. Timber, pine and aspen; undergrowth, 2nd growth timber.
-----	
	N. 89° 50' W., bet. secs. 7 and 18. Over rolling land, through heavy timber and undergrowth; desc. over a gradual SW. slope.
1.25	Enter a drain, course W. from SE.; desc. 8 ft. along drain.
7.05	Leave drain, course SW.
20.15	Dim road, bears N. and S.
30.00	Low spur, slopes SW.
36.00	Graded road, bears N. 10° E. to Slate Mountain and S. 10° W. to junction with Spring Valley- Kendrick Park road.
40.53	Proportional distance, Set an iron post, 3 ft. long, 1 in. diam., 25 ins. in the ground, to bedrock, and in a mound of stone to top, at the $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4} \frac{S 7}{S 18}$ 1943 from which A pine, 10 ins. diam., bears N. 40° E., 67 lks. dist., mkd. $\frac{1}{4}$ S 7 B T. A pine, 16 ins. diam., bears S. 6° W., 190 lks. dist., mkd. $\frac{1}{4}$ S 18 B T.
51.50	Short spur, slopes NW.; desc. 40 ft. over a W. slope.
56.33	Wire fence, bears N. 70° E. and westerly along line.
57.00	Drain, course N.; asc. 16 ft. over a NE. slope.
64.00	Spur, slopes W. from SE.; asc. gradually along S. slope of same, along S. side of fence.
79.63	The cor. of secs. 7, 12, 13 and 18, on W. bdy. of the Tp., described in field notes of T.23 N., R.5 E., this group. Land, rolling. Soil, rocky; 2nd and 3rd rate. Timber, pine and aspen; undergrowth, 2nd growth timber.
-----	
	From the cor. of secs. 7, 8, 17 and 18. N. 3° 49' W., bet. secs. 7 and 8.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

Over rolling land, through heavy timber and undergrowth; asc. 44 ft. over a SW. slope.

8.30 Spur, slopes W.; desc. 98 ft. over a N. slope.

20.00 Slope changes; desc. gradually along a W. slope.

40.09 Proportional distance,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 7\ | \ S\ 8 \end{array}$$

1943

from which

A pine, 14 ins. diam., bears N.  $26\frac{1}{2}^{\circ}$  E., 63 lks. dist., mkd.  $\frac{1}{4}$  S 8 B T.

A pine, 16 ins. diam., bears N.  $6\frac{3}{4}^{\circ}$  W., 107 lks. dist., mkd.  $\frac{1}{4}$  S 7 B T.

Descend gradually along a gentle W. slope.

76.60 Graded road, bears W. for 150 lks. to a junction with a road which bears NE. and SW. and E. to a junction with a road which bears NW. and SE.

77.90 Graded road, bears NE. to Slate Mountain and S.  $60^{\circ}$  W. to the Spring Valley-Kendrick Park road.

80.18 The cor. of secs. 5, 6, 7 and 8, as evidenced by a malpais stone, 12x12x8 ins., firmly set in the ground, mkd. 5 notches on S. and 5 notches on E. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the old stone buried alongside, at the cor. of secs. 5, 6, 7, and 8, with brass cap mkd.

$$\begin{array}{c} T23N\ R6E \\ S\ 6\ | \ S\ 5 \end{array}$$

$$\begin{array}{c} S\ 7\ | \ S\ 8 \end{array}$$

1943

from which

Old bearing trees:

A pine stump, 24 ins. diam., bears S.  $72^{\circ}$  E., 193 lks. dist., mkd. T XXIII N R VI E S VIII B T.

A pine, 12 ins. diam., bears S.  $31\frac{1}{2}^{\circ}$  W., 233 lks. dist., mkd. T XXIII N R 6 E S VII B T.

A pine stump, 30 ins. diam., bears N.  $84\frac{1}{2}^{\circ}$  W., 43 lks. dist., mkd. T 23 N R 6 E S, remainder of marks indiscernible.

New bearing trees:

A pine, 6 ins. diam., bears N.  $31\frac{3}{4}^{\circ}$  E., 97 lks. dist., mkd. T 23 N R 6 E S 5 B T.

A pine, 6 ins. diam., bears S.  $64^{\circ}$  E., 28 lks. dist., mkd. T 23 N R 6 E S 8 B T.

A pine, 10 ins. diam., bears S.  $67\frac{1}{2}^{\circ}$  W. 158 lks. dist., mkd. T 23 N R 6 E S 7 B T.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Chains

A pine, 10 ins. diam., bears N.  $67\frac{1}{2}^{\circ}$  W., 159 lks. dist., mkd. T 23 N R 6 E S 6 B T.

A fence cor., bears NE., 3 lks. dist.; fence extends northerly and westerly.

Land, rolling.

Soil, rocky; 3rd rate.

Timber, pine; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 4, 5, 8 and 9.

N.  $89^{\circ} 26'$  W., bet. secs. 5 and 8.

Over rolling land, through heavy timber and undergrowth; along a gentle N. slope.

17.40 Low spur, slopes N.; desc. gradually along a gentle N. slope.

35.40 Road, bears NE. and SW.

40.37 The  $\frac{1}{4}$  sec. cor., as evidenced by a lava stone, 16x8x6 ins. in a mound of stone, 2 ft. base, 1 ft. high, mkd.  $\frac{1}{4}$  on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old stone buried alongside, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} S\ 5 \\ \hline S\ 8 \\ 1943 \end{array}$$

from which

Old bearing trees:

A pine stump, 18 ins. diam., bears S.  $51\frac{1}{2}^{\circ}$  E., 58 lks. dist., marks indiscernible.

A pine stump, 24 ins. diam., bears S.  $24\frac{1}{2}^{\circ}$  W., 20 lks. dist., mkd.  $\frac{1}{4}$  S B T.

New bearing trees:

A pine, 6 ins. diam., bears N.  $40\frac{1}{4}^{\circ}$  W., 103 lks. dist., mkd.  $\frac{1}{4}$  S 5 B T.

A pine, 9 ins. diam., bears S.  $20\frac{3}{4}^{\circ}$  E., 78 lks. dist., mkd.  $\frac{1}{4}$  S 8 B T.

Thence,

N.  $89^{\circ} 44'$  W., bet. secs. 5 and 8.

Descend 12 ft. along a gentle N. slope.

4.00 Enter nearly level land, bears SW. and N.

24.00 Road, bears SE. and NW.

37.30 Road, bears SW. and N.  $30^{\circ}$  E. to Slate Mountain.

40.41 The cor. of secs. 5, 6, 7 and 8.

Land, E.  $\frac{1}{2}$  rolling; W.  $\frac{1}{2}$  nearly level.

Soil, rocky; 2nd rate.

Timber, pine and aspen; undergrowth, 2nd growth timber.



BOOK 4853

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

Chains

N. 89° 42' W., bet. secs. 6 and 7.

Over nearly level land, through heavy timber and undergrowth; desc. gradually over a W. slope, along a wire fence.

34.53 The  $\frac{1}{4}$  sec. cor., as evidenced by a malpais stone 16x8x6 ins., firmly set in the ground, mkd.  $\frac{1}{4}$  on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the old stone buried alongside, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S 6}{S 7}$$

1943

from which

Old bearing trees:

A pine stump, 24 ins. diam., bears N. 56 $\frac{3}{4}$ ° E., 51 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.

A pine stump, 30 ins. diam., bears West, 12 lks. dist., mkd.  $\frac{1}{4}$  S VII B T.

New bearing trees:

A pine, 12 ins. diam., bears N. 50 $\frac{1}{4}$ ° W., 158 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.

A pine, 14 ins. diam., bears S. 12 $\frac{3}{4}$ ° W., 212 lks. dist., mkd.  $\frac{1}{4}$  S 7 B T.

A fence bears S. 2 lks. dist.; fence extends N. 83° W. and easterly.

Muderbach's well, bears N. 33° 25' E., 24.15 chs. dist. Thence,

S. 89° 40' W., bet. secs. 6 and 7.

Over nearly level land.

0.26 A fence cor.; fence extends S. 83° E., N. 83° W. and northerly. Thence, along S. side of fence.

10.00 Leave heavy timber and undergrowth, bears N. and S.

30.00 Enter heavy timber and undergrowth; leave nearly level land, bears N. and S.; asc. 74 ft. over a NE. slope.

40.22 The cor. of secs. 1, 6, 7 and 12, on W. bdy. of the Tp., described in field notes of T. 23 N., R. 5 E., this group. Land, W. 10 chs. rolling; remainder of line, nearly level. Soil, rocky; 2nd and 3rd rate. Timber, pine; undergrowth, 2nd growth timber.

-----  
From the cor. of secs. 5, 6, 7 and 8.

N. 0° 04' W., bet. secs. 5 and 6.

Over rolling land, through heavy timber and undergrowth; along a fence; descend gradually over a N. slope.

8.20 Road, bears W. to ranch house and E. to graded road; enter nearly level land, bears SW. and NE.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

2000 4856

## Chains

- 8.23 Center of the E. side of Muderbach's ranch house, bears N.  $85\frac{1}{2}^{\circ}$  W., 5.78 chs. dist.
- 13.60 A fence cor.; fence extends S.  $0^{\circ} 04'$  E. and N.  $85^{\circ}$  W.
- 29.60 Graded road, bears N.  $52^{\circ}$  W., to Slate Mountain and S.  $52^{\circ}$  E. to Spring Valley-Kendrick Park road.
- 38.44 Wire fence, bears N.  $51^{\circ}$  E. and S.  $51^{\circ}$  W.
- 39.96 The  $\frac{1}{4}$  sec. cor., as evidenced by a malpais stone, 18x8x8 ins., in a mound of stone, 3 ft. base, 1 ft. high, mkd.  $\frac{1}{4}$  on W. face.
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground. with the old stone buried alongside, at the  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $$\frac{1}{4}$$

$$S 6 \frac{1}{2} S 5$$

$$1943$$
- from which
- Old bearing trees:
- A pine, 20 ins. diam., bears N.  $65^{\circ}$  E., 95 lks. dist., mkd.  $\frac{1}{4}$  S V B T.
- A pine, 24 ins. diam., bears S.  $19\frac{1}{4}^{\circ}$  W., 330 lks. dist., mkd.  $\frac{1}{4}$  S VI B T.
- New bearing trees:
- A pine, 6 ins. diam., bears N.  $21\frac{3}{4}^{\circ}$  E., 264 lks. dist., mkd.  $\frac{1}{4}$  S 5 B T.
- A pine, 12 ins. diam., bears N.  $51\frac{3}{4}^{\circ}$  W., 309 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.
- Thence,
- N.  $0^{\circ} 05'$  W., bet. secs. 5 and 6.
- Over rolling land; asc. over a gentle SE. slope.
- 40.91 The cor. of secs. 5, 6, 31 and 32, on N. bdy. of the Tp.
- Land, S.  $\frac{1}{2}$  nearly level; N.  $\frac{1}{2}$  rolling.
- Soil, rocky; 2nd and 3rd rate.
- Timber, pine, and aspen; undergrowth, 2nd growth timber.
-

ECCCK 4353

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

## Final Test of Solar Attachments.

August 29, 1943, at camp about 20 chs. NW. of the  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, T. 23 N., R. 6 E., G. & S. R. M., with Buff solar transits Nos. 16724 and 16730, at 9 a.m., app. t., set off  $35^{\circ} 22'$  N. on the lat. arcs;  $9^{\circ} 32'$  N. on the decl. arcs; and orient the instruments with the solar; the line of sight agrees with the meridian established by Polaris observation.

At 3 p.m., app. t., set off  $35^{\circ} 22'$  N. on the lat. arcs;  $9^{\circ} 25'$  N. on the decl. arcs; and repeat the test of the solar; the line of sight agrees with the meridian established by Polaris observation.

## General Description.

T. 23 N., R. 6 E. is located in the Coconino National Forest. The general elevation is about 8,000 to 10,000 ft. above sea level. The west and north portion of the township is rolling. San Francisco Mountain extends into secs. 13, 24, 25 and 36; the highest peak of this mountain has an elevation of 12,611 ft. above sea level. The White Horse Hills are located in secs. 1 and 12, and another hill is located in secs. 15 and 16; these hills are about 9,000 ft. above sea level. Walker Lake is in an old volcanic crater, located in sec. 11.

The soil, in the mountainous and rolling part of the township is very rocky of 3rd and 4th rate; in the valleys and some of the level land, the soil is 1st and 2nd rate. In the past there has been considerable land in cultivation throughout the township but at present the only land being tilled is at George C. Keith's ranch in sec. 18; Peter Mitchelback's ranch in the NE.  $\frac{1}{4}$  of sec. 34 and a few small fields in Kendrick Park which is mostly in secs. 2, 3, and 4. Most of the township is used for the grazing of cattle and sheep. There is a good stand of native grass over the entire township.

A heavy growth of timber covers the greater part of the township with some open grassy parks, the most prominent of these being Kendrick Park in secs. 2, 3, and 4, and Hart Prairie in sec. 25, 26, 35 and 36.

A good spring is located in the NE.  $\frac{1}{4}$  of sec. 35 and another one is near the center of sec. 14. There are water wells at the Mundersbach and Hochderfer ranches. Earth reservoirs have been constructed in the drains and washes of the township for storage of water for stock.

A dividing ridge runs east and west through nearly the center of the township. The direction of the drainage south of this divide is southwest and on the north side the direction is northeast.

Two good graded roads run through the township, north and south; one through the west part and the other through Hart Prairie in the east part.

Snow Bowl Lodge is located in sec. 36. The buildings at this lodge are the property of the United States and are maintained by the United States Forest Service.

## Resurvey of the Subdivision of T. 23 N., R. 6 E.

There are several ski courses near this lodge on the west slope of the San Francisco Mountain, and a ski lift is in operation during the season when the snow is suitable for this sport.

Fern Mountain Lodge which is a privately owned Dude Ranch, is located in sec. 26.

There were no indications of mineral observed within the township during the progress of the survey.

-----

BOOK 4853

4-680  
(Revised May 1934)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
~~GENERAL LAND OFFICE~~

BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Theodore Cole	Principal Assistant.
Ralph L. Lee	Truckdriver.
Gladwyn Gregory	Chainman.
Harold R. Bissell, Jr.	Flagman.
William H. Bissell	Moundsman.
William H. Gaddis	Axeman.
John P. Balen	Axeman.
Roy West	Axeman.
James W. Norman	Axeman.

91

BOOK 4353

CERTIFICATE OF SURVEYOR

We, Ty White, Associate Cadastral Engineer and Bert E. Wakeman, Senior Engineering Aid, HEREBY CERTIFY upon honor that, in

pursuance of special instructions bearing date of the 13th day of March, 1942

received from the district cadastral engineer for Arizona, with assignment

instructions dated May 18, 1943, we have resurveyed the North, South and East Boundaries and the Subdivisional Lines of Township 23 N., Range 6 East

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona, February 22, 1946.

Ty White, Associate Cadastral Engineer, formerly Assistant Cadastral Engineer. Bert E. Wakeman, Senior Engineering Aid.

CERTIFICATE OF APPROVAL

Chief Cadastral Engineer OFFICE OF SUPERVISOR OF SURVEYS, Denver, Colorado OCT 20 1947, 19

The foregoing field notes of the resurvey of the North, South and East Boundaries and the Subdivisional Lines of Township 23 North, Range 6 East of the Gila and Salt River Meridian in the State of Arizona.

executed by Ty White, Assistant Cadastral Engineer and Bert E. Wakeman, Senior Engineering Aid under special instructions dated March 13, 1942, and assignment instructions dated May 18, 1943, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

Earl G. Harrington, Acting Assistant Chief Cadastral Engineer, Supervisor of Surveys

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above described surveys in is a true copy of the original field notes on file in the public survey office.

Supervisor of Surveys.