

Original.

UNITED STATES
DEPARTMENT OF THE INTERIOR
~~GENERAL LAND OFFICE~~
BUREAU OF LAND MANAGEMENT

COX 4355

FIELD NOTES

of
Dependent Resurvey

of

Sixth Standard Parallel North along the
South Boundary of T. 25 N., R. 6 E., and
the South Boundary of East one half of
sec. 36, T. 25 N., R. 5 E.

and

East and West Boundaries

and

Subdivisional Lines of T. 24 N., R. 6 E.

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Ty White, Associate Cadastral Engineer

Bert E. Wakeman, Senior Engineering Aid

Under special instructions dated March 13, 1942, which provided
for the surveys included under Group No. 239, bearing the approval of the
Commissioner of the General Land Office under date of March 28, 1942
and assignment instructions dated June 26, 1944

Survey commenced July 10, 1944

Survey completed September 13, 1944

4355

4355

112

BOOK 4355

INDEX DIAGRAM.

		Township 24 N.				Range 6 E.						
36		31	32	33	34	35	36			36		
11		9	10	11	12	13	14			2		
	97	87	72	61	49	38	27			18		
25	6	86	5	71	4	60	3	48	2	37	1	19
	85	84	70	59	47	36						
24	7	83	8	69	9	58	10	46	11	35	12	17
	82	82	68	57	45	36						
23	18	80	17	67	16	56	15	44	14	33	13	16
	80	79	67	55	43	32						
22	19	78	20	65	21	54	22	42	23	31	24	15
	77	76	64	53	41	30						
21	30	75	29	63	28	52	27	40	26	29	25	14
	74	73	62	51	39	28						
19	31	72	32	61	33	49	34	38	35	27	36	12

TOWNSHIP 24 NORTH, RANGE 6 EAST

36 31 32 33 34 35 36

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

———— Indicates surveys executed by Ty White

———— Indicates surveys executed by Bert E. Wakeman

Date of Survey

East Boundary: July 10 to July 15, 1944
North Boundary: July 14 to Sept. 9, 1944
West Boundary: August 10 to September 6, 1944
Subdivisions: July 22 to September 13, 1944

T.24 N., R.6 E.

BOOK 4355

The resurveys hereinafter described were executed with Buff solar transits Nos. 16724 and 16730, equipped with Smith solar attachments, constructed in accordance with the standard specifications of the General Land Office. The instruments were in good condition and having been placed in satisfactory adjustment prior to the beginning of the resurvey and tested and found free from appreciable error, were approved by the district cadastral engineer.

The directions of the lines were determined by the solar transit method. The measurements were made with Lufkin steel tapes, 5 chs. in length, graduated every link for the first 100 links and the balance at intervals of 10 links. The tapes were tested by comparison with a Lufkin standard steel tape and found correct. The measurements were made on the slope and the vertical angles ascertained with a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

July 7, 1944, in camp, at Curley Seep Guard Station, in the SE $\frac{1}{4}$ SW $\frac{1}{4}$, Sec. 21, T. 24 N., R. 6 E., Gila and Salt River Meridian, Arizona, in approximate latitude 35°26'N. and longitude 111°46'W.; my watch reading correct 105th meridian time, as checked by radio time signals, make an hour angle observation on Polaris, east of the meridian, making four observations, two each with the telescope in direct and reversed positions, reading the horizontal deflection angles from a well defined point on a dead pine, approximately 15 chains northwesterly.

To determine the latitude of the station; read the vertical angles to Polaris.

Mean watch time of observation	8h 07m 27s p.m.
Watch fast of l.m.t.	0h 27m 04s

Mean horizontal deflection angle	1° 31' 30"
Azimuth of Polaris	0° 18' 42"

Bearing of reference point	N. 1° 12' 48" W.
----------------------------	------------------

Mean observed vertical angle	34° 29' 45"
Reduced latitude	35° 26' 44" N.

July 9, 1944, with Buff solar transits Nos. 16724 and 16730, on the meridian above described, every 30 minutes from 8 to 10:30 a.m., and from 1:30 to 4 p.m., make the proper settings on the arcs of the solar attachments and ascertain that the resulting orientation of the instruments when compared with the meridian established by Polaris observation, have a maximum error of less than 1' 30".

We repeat the tests of the arcs daily by noon observations and verify the meridional indications at frequent intervals throughout the survey.

The observed magnetic declination is 14°45'E.

Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 6 E.

Preliminary to the resurvey the lines of the original survey are retraced and diligent search is made for all original corners. Identified corners of the original survey are reestablished in their original positions. All lost corners are reestablished by collateral evidence or the method of single proportion and double proportion, as appropriate, based on the original record. The standard 1/4 sec. cor. of sec. 36, S. bdy. of T. 25 N., R. 6 E., was reestablished by the broken boundary method. The retracement data are thoroughly verified and only the true line notes are given here.

Reestablishment of a survey executed by A.E. Shoemaker, Deputy Surveyor, in 1883, and resurveyed by F.W. Oury, Deputy Surveyor, in 1894.

The standard cor. of Ts. 25 N., Rs. 6 and 7 E., is evidenced by a lava stone 24x20x12 ins., firmly set in the ground, marked SC on N., 6 grooves on E., W. and N. faces.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at standard corner of Ts. 25 N., Rs. 6 and 7 E., with brass cap marked

SC
T25N
R6E | R7E
S36 | S31

1944

of stone, 3 ft. base, 2 ft. high, N. of cor.

Thence

N. 89° 23' W., along the S. bdy. of sec. 36.

Over rolling land, through scattering timber and undergrowth.

Descend gradually over a W. slope.

13.10 Drain, course N.; asc. gradually over an E. slope.

14.70 Road, bears N. 30° E. and S. 30° W.

28.30 Road, bears S. 10° E. and N. 10° W.

40.34 Points determined by the method of broken boundaries.

Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 6 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at standard $\frac{1}{4}$ sec. cor. of sec. 36, with brass cap marked

S C
 $\frac{1}{4}$ S 36
1944

from which

A pinon, 5 ins. diam., bears N.7°W., 212 lks. dist., marked $\frac{1}{4}$ S 36 S C B T.

A pinon, 9 ins. diam., bears N.55 $\frac{1}{2}$ °W., 253 lks. dist., marked $\frac{1}{4}$ S 36 S C B T.

Thence

N.89°53'W., along the S. bdy. of sec. 36.

Ascend gradual E. slope.

0.70 Road, bears NE. and SW.

3.60 Enter heavy timber, bears NE. and SW.

11.20 Enter scattering timber, bears NE. and SW.

38.50 Enter heavy timber, bears NE. and SW.

40.23 The standard cor. of secs. 35 and 36, as evidenced by a decayed, wooden post, 22 ins. long, 2 ins. diam., set in a mound of stone, 2 ft. base, 1 ft. high; marked S 35, other marks illegible.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original wooden cor. post buried alongside, at standard cor. of secs. 35 and 36, with brass cap marked

S C
T25N | R6E
S35 | S36
1944

from which

Original bearing trees:

A pinon, partly dead, 10 ins. diam., bears N.72 $\frac{1}{2}$ °E., 53 lks. dist., marked T 25 N R 6 E S 36 S C B T.

A pinon, partly dead, 10 ins. diam., bears N.78 $\frac{3}{4}$ °W., 42 lks. dist., marked T 25 N R 6 E S 35 S C B T.

New bearing trees:

A pinon, 10 ins. diam., bears N.41°E., 77 lks. dist., marked T 25 N R 6 E S 36 S C B T.

A pinon, 9 ins. diam., bears N.38 $\frac{1}{4}$ °W., 73 lks. dist., marked T 25 N R 6 E S 35 S C B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pinon, juniper, yellow pine; undergrowth, 2nd growth timber and sage.

Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 6 E.

Chains

N.89°31'W., along the S. bdy. of sec. 35

Over rolling land, through heavy timber and scattering undergrowth.

Ascend gradually over an E. slope.

30.35 The closing corner of secs. 1 and 2, T. 24 N., R. 6 E., as evidenced by a lava stone, 10x8x6 ins., firmly set in the ground, marked 1 notch on E. and 5 notches on W. edges and CC on S. face.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at closing cor. of secs. 1 and 2, T. 24 N., R. 6 E., with brass cap marked

T25N	R6E
S35	
S2	S1
T24N	R6E
C C	
1944	

from which

Original bearing trees:

A pinon, 24 ins. diam., bears N. 3½°E., 198 lks. dist., marked T 24 N R 6 E C C S 1 + 2 B T.

A yellow pine, 26 ins. diam., bears S. 2¼°W., 238 lks. dist., marked T 24 N R. 6 E C C S 2 B T.

New bearing trees:

A pinon, 12 ins. diam., bears S. 43½°E., 285 lks. dist., marked T 24 N R 6 E S 1 C C B T.

A juniper, 12 ins. diam., bears S. 34¾°W., 167 lks. dist., marked T 24 N R 6 E S 2 C C B T.

35.00 Low spur, slopes N.25°E.; along N. slope.

40.23 The standard ¼ sec. cor. of sec. 35, as evidenced by a malpais stone, 22x14x12 ins., firmly set in the ground, marked ¼ S C on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at standard ¼ sec. cor. of sec. 35; with brass cap marked

S C	
¼ S 35	
1944	

from which

Original bearing tree:

A yellow pine, 28 ins. in diam., bears N. 26½°E., 52 lks. dist., marks overgrown, mark on overgrowth, ¼ S 35 S C B T.

New bearing tree:

A yellow pine, 32 ins. diam., bears N. 48°W., 130 lks. dist., marked ¼ S 35 S C B T.

N.89°00'W., along the S. bdy. of sec. 35.

Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 6 E.

Chains

Along a gentle N. slope.

16.80

Shallow draw, 2 chs. wide, drains NE.; asc. gradually over E. slope.

40.41

The standard cor. of secs. 34 and 35, as evidenced by a lava stone 12x10x6 ins., set in a mound of stone, 2 ft. base, 10 ins. high, marked 4 grooves on W., 2 grooves on E. and S C on N. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside at standard cor. of secs. 34 and 35, with brass cap marked

S C
T25N R6E
S34|S35

1944

from which

Original bearing tree:

A pinon, partly dead, 12 ins. diam., bears S.62½°W., 31 lks. dist., marked T 24 N R 6 E S C S 34 + 35 B T.

New bearing trees:

A pinon, 5 ins. diam., bears N.53½°E., 124 lks. dist., marked T 25 N R 6 E S 35 S C B T.

A pinon, 12 ins. diam., bears N.29¼°W., 78 lks. dist., marked T 25 N R 6 E S 34 S C B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pinon, juniper and yellow pine; undergrowth, 2nd growth timber and sage.

N.89°37'W., along the S. bdy. of sec. 34.

Over rolling land, through heavy timber and scattering undergrowth.

Ascend gradually over E. slope.

0.83

A 4 strand barbed wire fence, bears N. and S.

9.80

Foot of steep ascent, bears N. and S.20°W.; asc. 127 ft. over E. slope.

20.00

Top of steep ascent bears N. and S.; asc. gradually 33 ft. over NE. slope.

39.85

The standard ¼ sec. cor. of sec. 34, determined from original bearing tree.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground at standard ¼ sec. cor. of sec. 34, with brass cap marked

S C
¼ S 34

1944

from which

Original bearing tree:

Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 6 E.

Chains

A yellow pine, 34 ins. diam., bears N. $15\frac{1}{4}^{\circ}$ W., 53 lks. dist., marks overgrown, mark on overgrowth $\frac{1}{4}$ S 34 S C B T.

New bearing tree:

A yellow pine, 18 ins. diam., bears N. $49\frac{1}{2}^{\circ}$ E., 51 lks. dist., marked $\frac{1}{4}$ S 34 S C B T.

N. $89^{\circ}34'$ W., along the S. bdy. of sec. 34.

Ascend gradually 17 ft. over NE. slope.

5.00 Slope changes, asc. gradually along a gentle N. slope.

16.00 Top of wide ridge, bears N. and S.; desc. gradually along gentle N. slope.

30.00 Slope changes, desc. gradually over NW. slope.

36.50 Drain, course N., heads about 5 chs. S.; asc. E. slope.

39.20 Low spur, slopes N.; desc. gradually over W. slope.

39.59 Original line tree, a pinon, 12 ins. diam., marked 2 notches on E. and W. faces.

40.40 The standard cor. of secs. 33 and 34, as evidenced by a lava stone, 8x8x8 ins., firmly set in the ground, marked 3 grooves on E., 3 grooves on W. and S C on N. faces, with a mound of stone 2 ft. base, 10 ins. high, S. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone and a glass bottle, buried alongside, at standard cor. of secs. 33 and 34, with brass cap marked

. S C
- T25N R6E
S33 | S34

1944

from which

Original bearing tree:

A pinon, partly dead, 24 ins. diam., bears N. 53° E., 74 lks. dist., marked T 25 N R 6 E S 34 S C B T.

New bearing trees:

A pinon, 6 ins. diam., bears N. $42\frac{1}{4}^{\circ}$ E., 69 lks. dist., marked T 25 N R 6 E S 34 S C B T.

A yellow pine, 7 ins. diam., bears N. $70\frac{1}{4}^{\circ}$ W., 73 lks. dist., marked T 25 N R 6 E S 33 S C B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pinon, juniper and yellow pine; undergrowth, 2nd growth timber and sage.

S. $89^{\circ}45'$ W., along the S. bdy. of sec. 33.

Over rolling land, through heavy timber and scattering undergrowth.

Descend over W. slope.

Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 6 E.

Chains	
1.30	Head of a drain, course N.; asc. 29 ft. over E. slope.
8.20	Low spur, slopes N.20°W.; desc. 34 ft. over W. slope.
17.50	Leave heavy timber, enter open park, bears NW. and SE.
24.45	Road, bears NW. and SE.
33.60	Leave open park, enter heavy timber, bears N. and SE. Top of low spur, slopes N.; desc. 30 ft. over SW. slope.
38.20	Draw, drains NW.; asc. gradually over NE. slope.
40.39	The standard $\frac{1}{4}$ sec. cor. of sec. 33, as evidenced by a malpais stone, 16x10x5 ins. firmly set in the ground, marked S C $\frac{1}{4}$ on N. face, with a mound of stone, 2 ft. base, 1 ft. high, S. of cor.
	As this cor. no longer serves as the standard $\frac{1}{4}$ sec. cor. of sec. 33.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at angle point, with brass cap marked
	A P T25N R6E S33
	1944
	from which
	Original bearing tree:
	The original position of a pinon, 12 ins. diam., now dead, lying on ground, bears N.73 $\frac{1}{2}$ °E., 97 lks. dist., marked $\frac{1}{4}$ S B T.
	New bearing trees:
	A pinon, 20 ins. diam., bears N.31°E., 132 lks. dist., marked T 25 N R 6 E S 33 A P B T.
	A pinon, 16 ins. diam., bears N.22°W., 143 lks. dist., marked T 25 N R 6 E S 33 A P B T.
	N.89°16'W., along the S. bdy. of sec. 33.
	Along a rolling N. slope.
20.80	Shallow draw, 150 lks. wide, drains N. from S.20°W., continue along rolling N. slope.
25.00	Enter scattering timber, bears N. and S.
35.92	The closing cor. of secs. 32 and 33, T. 25 N., as evidenced by a malpais stone, 16x12x8 ins., firmly set in the ground, marked C C on N. face, 4 notches on E. and 2 notches on W. edges.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at closing cor. of secs. 32 and 33, with brass cap marked
	C C T25N R6E S32 S33
	1944
	from which

.Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 6 E.

Chains

A juniper, 3 ins. diam., bears N. $63\frac{3}{4}^{\circ}$ E., 228 lks.
dist., marked C C B T.

A pinon, 5 ins. diam.; bears N. 27° W., 179 lks.
dist., marked T 25 N R 6 E S 32 C C B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pinon, juniper and yellow pine; undergrowth, 2nd
growth timber.

N. $89^{\circ}16'$ W., along the S. bdy. of sec. 32.

Over rolling grassy land; through scattering timber.

Ascend gradual SE. slope.

4.63 The standard cor. of secs. 32 and 33, as evidenced by a
malpais stone, 12x10x6 ins., firmly set in the ground,
marked S C on face, 4 notches on E. and 2 notches on W.
edges, witnessed by a mound of stone 2 ft. base, 10 ins.
high, S. of cor.

As this cor. no longer serves as the standard cor. of
secs. 32 and 33

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, with the original cor. stone, buried alongside,
at angle point, with brass cap marked

A P
T25N|R6E
S32

1944

from which

A pinon, 7 ins. diam., bears N. $74\frac{1}{4}^{\circ}$ E., 332 lks. dist.,
marked T 25 N R 6 E S 32 A P B T.

A pinon, 5 ins. diam.; bears N. 82° W., 121 lks. dist.,
marked T 25 N R 6 E S 32 A P B T.

Thence

N. $89^{\circ}33'$ W., along the S. bdy. of sec. 32.

Descend 27 ft. over W. slope.

22.00 Shallow draw, 8 chs. wide, drains N. 20° E.; asc. gradually
over SE. slope.

40.47 The standard $\frac{1}{4}$ sec. cor. of sec. 32, as evidenced by a
malpais stone, 15x7x5 ins., firmly set in a mound of stone,
marked S C $\frac{1}{4}$ on N. face.

As this cor. no longer serves as the standard $\frac{1}{4}$ sec. cor.
of sec. 32.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with the original cor. stone buried alongside, at
angle point, with brass cap marked

A P
T25N|R6E
S32

1944

from which

Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 6 E.

Chains

A pinon, 6 ins. diam., bears N. 32° E., 317 lks. dist., marked T 25 N R 6 E S 32 A P B T.

A pinon, 18 ins. diam., bears N. 15 1/4° W., 186 lks. dist., marked T 25 N R 6 E S 32 A P B T.

Thence

N. 89° 45' W., along the S. bdy. of sec. 32.

Ascend gradually over SE. slope.

3.00 Top of ascent, bears NE. and S. along gentle rolling N. slope.

25.30 Center of a sink, 5 chs. in diam., bears S. about 5 chs. dist.

34.45 The closing cor. of secs. 31 and 32, T. 25 N., as evidenced by a malpais stone, 14x12x6 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, marked C C on N. face, 5 notches on E. and 1 notch on W. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at closing cor. of sets. 31 and 32, with brass cap marked

C	C
T25N	R6E
S31	S32

1944

from which

A yellow pine, 5 ins. diam., bears N. 26 1/2° E., 180 lks. dist., marked T 25 N R 6 E S 32 C C B T.

A pinon, 12 ins. diam., bears N. 47 1/4° W., 367 lks. dist., marked T 25 N R 6 E S 31 C C B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pinon, juniper and yellow pine; undergrowth, none.

N. 89° 45' W., along the S. bdy. of sec. 31.

Over rolling land, through scattering timber and undergrowth.

6.00 The standard cor. of secs. 31 and 32, as evidenced by a malpais stone 22x14x12 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, marked 5 grooves on E., 1 groove on W. and S C on N. faces.

As this cor. no longer serves as the standard cor. of secs. 31 and 32

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to bedrock, with the original stone buried alongside, and in a mound of stone to top at angle point, with brass cap marked

A	P
T25N	R6E
S31	

1944

from which

Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 6 E.

Chains	Original bearing tree:
	A pinon, 16 ins. diam., bears N.75 $\frac{1}{4}$ °W., 48 lks. dist., marked T 25 N R 6 E S 31 B T. Alter the markings on this tree to read T 25 N R 6 E S 31 A P B T.
	New bearing tree:
	A pinon, 18 ins. diam., bears N.44 $\frac{3}{4}$ °E., 276 lks. dist., marked T 25 N R 6 E S 31 A P B T.
	Thence
	N.89°35'W., along the S. bdy. of sec. 31.
	Descend 34 ft. over W. slope.
12.50	Draw, drains N., heads 5 chs. S.; asc. 43 ft. over E. slope.
31.00	Top of ascent, bears N. and S., along gentle N. slope.
40.31	The standard $\frac{1}{4}$ sec. cor. of sec. 31, as evidenced by a malpais stone, 12x8x5 ins., firmly set in the ground, marked S C $\frac{1}{4}$ on N. face, witnessed by a mound of stone 2 ft. base, 1 ft. high, N. of cor.
	As this cor. no longer serves as the standard $\frac{1}{4}$ sec. cor. of sec. 31
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at angle point, with brass cap marked
	A P. T25N R6E S31 <hr style="width: 10%; margin: 0 auto;"/> 1944
	from w hich
	Original bearing tree:
	A yellow pine, 24 ins. diam., bears N.75 $\frac{1}{2}$ °W., 193 lks. dist., markings overgrown, mark on overgrowth, T 25 N R 6 E S 31 A P B T.
	New bearing trees:
	A yellow pine, 4 ins. diam., bears N.20 $\frac{1}{2}$ °E., 51 lks. dist., marked T 25 N R 6 E S 31 A P B T.
	A yellow pine, 5 ins. diam., bears N.39 $\frac{1}{2}$ °W., 58 lks. dist., marked T 25 N R 6 E S 31 A P B T.
	Thence
	S.89°50'W., along the S. bdy. of sec. 31.
	Descend 20 ft. over NW. slope.
6.30	Draw, 2 chs. wide, drains N.; ascend 19 ft. over E. slope.
15.00	Low spur, slopes N.; desc. 39 ft. over a gradual W. slope.
25.00	Enter heavy timber and scattering undergrowth; bears N. and S.
35.20	Draw, 150 lks. wide, drains N.20°E.; asc. 62 ft. over E. slope.

Resurvey of the 6th Stan. Par. N., S. Bdy. T. 25 N., R. 6 E.

Chains

40.36

The standard cor. of Ts. 25 N., Rs. 5 and 6 E., as evidenced by a lava stone 16x12x10 ins., firmly set in the ground, marked S C and 6 grooves on N. and 6 grooves on E. and W. faces, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside at standard cor. of Ts. 25 N., Rs. 5 and 6 E., with brass cap marked

T25N	
R5E	R6E
S36	S31

1944

from which

Original bearing tree:

A yellow pine, 18 ins. diam., bears N.70½°E., 116 lks. dist., markings overgrown, not uncovered.

New bearing trees:

A yellow pine, 9 ins. diam., bears N.26°E., 94 lks. dist.; marked T 25 N R 6 E S 31 S C B T.

A yellow pine, 9 ins. diam., bears N.25°W., 143 lks. dist., marked T 25 N R 5 E S 36 S C B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pinon, juniper and yellow pine; undergrowth, 2nd growth timber.

Resurvey of the 6th Stan. Par. N., along a Portion of
S. Bdy. of T. 25 N., R. 5 E.

Reestablishment of a survey executed by A. E. Shoemaker, Deputy Surveyor, in 1883 and resurveyed by F. W. Oury, Deputy Surveyor, in 1894.

From the standard cor. of Ts. 25 N., Rs. 5 and 6 E.

S.89°37'W. along the S. bdy. of sec. 36.

Over rolling land, through scattering timber.

Ascend 248 ft. over E. slope.

11.50 Top of red cinder hill, bears N. and S.; descend 132 ft. over W. slope.

18.20 Slope changes, desc. 140 ft. over NW. slope.

36.40 Base of hill, bears N. and S.; desc. gradual NW. slope.

38.95 The standard ¼ sec. cor. of sec. 36, as evidenced by a lava stone, 11x8x4 ins., firmly set in the ground, marked S C ¼ on N. face, witnessed by a mound of stone 2 ft. base, 10 ins. high, N. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at standard ¼ sec. cor. of sec. 36, with brass cap marked

Resurvey of the 6th Stan. Par. N., along a Portion of S. Bdy. of T. 25 N., R. 5 E.

Chains

S C
 $\frac{1}{4}$ S 36

1944

from which

A yellow pine, 4 ins. diam., bears N.28°E., 92 lks. dist., marked $\frac{1}{4}$ S 36 S C B T.

A yellow pine, 4 ins. diam., bears N.18°W., 85 lks. dist., marked $\frac{1}{4}$ S.36 S C B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pinon, juniper and yellow pine; undergrowth, none.

 Resurvey of the W. Bdy. of T. 24 N., R. 7 E.

Reestablishment of a survey executed by A. E. Shoemaker, Deputy Surveyor, in 1883.

 From the cor. of Ts. 23 and 24 N., Rs. 6 and 7 E., as evidenced by an iron post, 3 ins. diam., set, marked and witnessed as described in the field notes of the W. bdy. of T. 23 N., R. 7 E., resurveyed under this group.

N.0°03'W., bet. secs. 31 and 36.

Over rolling land, through heavy timber and scattering undergrowth.

Descend 29 ft. over gradual N. slope.

11.20 Road, bears NW. and SE.

11.30 Draw, drains NW.; along gentle W. slope.

20.70 Spur, slopes NW.; desc. 51 ft. over N. slope.

25.60 Forest Service telephone line, bears E. and W.

26.65 Draw, 2 chs. wide, drains E.; asc. 14 ft. over S. slope.

28.80 Rimrock, 10 ft. high, bears W. and N.70°E.; asc. gradual SE. slope.

40.08 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, as evidenced by a mound of stone, 3 ft. base, 1 ft. high. Find no evidence of original wooden cor. post.

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor. of secs. 31 and 36, with brass cap marked

$\frac{1}{4}$
 S36 | S31

1944

from which

Original bearing tree:

A yellow pine, 26 ins. diam., now dead, bears S.70°W.; 31 lks. dist., marked $\frac{1}{4}$ S B T.

Resurvey of the W. Bdy. of T. 24 N., R. 7 E.

Chains

New bearing trees:

A yellow pine, 4 ins. diam., bears N.62°E., 57 lks. dist., marked $\frac{1}{4}$ S 31 B T.

A yellow pine, 4 ins. diam., bears S.64 $\frac{3}{4}$ °W., 88 lks. dist., marked $\frac{1}{4}$ S 36 B T.

A bench mark of the U.S. Geological Survey, as evidenced by a brass tablet, 3 $\frac{1}{2}$ ins. diam., seated in a lava stone in place, 3x2 ft., 1 ft. above ground, marked

Elevation
above sea
7740 feet
Datum
1907
B M

S.79°44'W., 32.40 chs. dist. bears

Center of Kelly Tank, an earthen reservoir, 3 chs. diam., bears S.53°37'W., 15.48 chs. dist.

N.0°27'E., bet. secs. 31 and 36.

Ascend 45 ft. over S. slope.

- 4.10 Graded road, bears NE. to Deadman Cabin and SW. to Kendrick Park.
- 5.00 Enter mountainous land, bears NE. and SW.
- 8.50 Slope changes; asc. 24 ft. along E. slope.
- 17.70 Ravine, course SE.; asc. 187 ft. over SW. slope.
- 37.80 Spur, slopes SE.; desc. 10 ft. along E. slope.
- 39.87 The cor. of secs. 25, 30, 31 and 36, determined from original bearing trees.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground at cor. of secs. 25, 30, 31 and 36, with brass cap marked

T24N
R6E | R7E
S25 | S30
S36 | S31
1944

from which

Original bearing trees;

A yellow pine, 18 ins. diam., bears N.48 $\frac{1}{2}$ °E., 29 lks. dist., marked T 24 N R 7 E S30 B T. Remark on overgrowth T 24 N R 7 E S 30 B T.

The original position of a yellow pine, 12 ins. diam., now dead, lying on ground, bears S.65 $\frac{1}{4}$ °W., 37 lks. dist., marked B T, other marks illegible.

New bearing trees:

A yellow pine, 8 ins. diam., bears S.52°E., 42 lks. dist., marked T 24 N R 7 E S 31 B T.

Resurvey of the W. Bdy. of T. 24 N., R. 7 E.

Chains

A yellow pine, 10 ins. diam., bears S.75½°W., 132 lks. dist., marked T 24 N R 6 E S 36 B T.

A yellow pine, 7 ins. diam., bears N.50°W., 101 lks. dist., marked T 24 N R 6 E S 25 B T.

Land, S. 55 chs. rolling; remainder mountainous. Soil, rocky, 3rd rate. Timber, pine; undergrowth, 2nd growth pine.

N. 0° 03' E., bet. secs. 25 and 30.


Over mountainous land, through heavy timber and scattering undergrowth.

Descend 147 ft. along E. slope.

20.00 Shallow draw, drains E.; asc. 45 ft. over SE. slope.

40.23 The ¼ sec. cor. of secs. 25 and 30, determined from original bearing trees. The original wooden cor. post, 26 ins. long, 4 ins. diam., marked ¼ S found lying on ground near point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. post buried alongside at ¼ sec. cor. of secs. 25 and 30, with brass cap marked



from which

Original bearing trees:

A yellow pine, 36 ins. diam., bears S.46½°E., 30 lks. dist., markings overgrown, not uncovered, mark on overgrowth ¼ S 30 B T.

A yellow pine, 20 ins. diam., bears N.39½°W., 17 lks. dist., markings overgrown, not uncovered, mark on overgrowth ¼ S 25 B T.

N. 0°56'W., bet. secs. 25 and 30.

Ascend 14 ft. over SE. slope.


4.00 Slope changes; along E. slope.

16.00 Low spur, slopes N.80°E.; desc. 142 ft. over NE. slope.

32.00 Slope changes; desc. 25 ft. along gentle E. slope.

40.01 The cor. of secs. 19, 24, 25 and 30, determined from original bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground at cor. of secs. 19, 24, 25 and 30, with brass cap marked



1944

from which

Resurvey of the W. Bdy. of T. 24 N., R. 7 E.

Chains

Original bearing trees:

A yellow pine, 36 ins. diam., bears N. 26°E., 39 lks. dist., blaze badly burned, markings illegible.

The original position of a yellow pine, 24 ins. diam., now dead, lying on ground, bears N. 15°W., 59 lks. dist., marked T 24 N R 6 E S 24 B T.

New bearing trees:

A yellow pine, 8 ins. diam., bears N. 55 $\frac{3}{4}$ °E., 136 lks. dist., marked T 24 N R 7 E S 19 B T.

A yellow pine, 6 ins. diam., bears S. 84 $\frac{1}{4}$ °E., 86 lks. dist., marked T 24 N R 7 E S 30 B T.

A yellow pine, 10 ins. diam., bears S. 7°W., 72 lks. dist., marked T 24 N R 6 E S 25 B T.

A yellow pine, 6 ins. diam., bears N. 55°W., 25 lks. dist., marked T 24 N R 6 E S 24 B T.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, pine, undergrowth; 2nd growth pine.

N. 0°20'W., bet. secs. 19 and 24.

Over rolling land, through heavy timber and scattering undergrowth.

Along E. slope.

- 2.00 Begin descent, descend 34 ft. over NW. slope.
 6.00 Draw, 3 chs. wide, drains NE.; asc. 28 ft. over SE. slope.
 22.00 Slope changes; along rolling E. slope.
 40.31 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. of secs. 19 and 24, with brass cap marked

$\frac{1}{4}$
 S24 | S19
 1944

from which

A yellow pine, 10 ins. diam., bears N. 44 $\frac{1}{2}$ °E., 89 lks. dist., marked $\frac{1}{4}$ S 19 B T.

A yellow pine, 14 ins. diam., bears N. 60 $\frac{1}{2}$ °W., 77 lks. dist., marked $\frac{1}{4}$ S 24 B T.

Descend 193 ft. over rolling NE. slope.

- 75.10 Graded road, bears E. to Deadman Cabin and W. to Curley Seep Guard Station.

- 80.62 The cor. of secs. 13, 18, 19 and 24, determined from original bearing tree.

Resurvey of the W. Bdy. of T. 24 N., R. 7 E.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 13, 18, 19 and 24, with brass cap marked.

T24N	
R6E	R7E
S13	S18
S24	S19

1944 :

Original bearing tree:

A yellow pine, 30 ins. diam., bears N. 70° E.; 36 lks. dist., marked T 24 N R 7 E S 18 B T.

New bearing trees:

A yellow pine, 6 ins. diam., bears N. 55½° E., 71 lks. dist., marked T 24 N R 7 E S 18 B T.

A yellow pine, 7 ins. diam., bears S. 62¼° E., 81 lks. dist., marked T 24 N R 7 E S 19 B T.

A yellow pine, 5 ins. diam., bears S. 76½° W., 16 lks. dist., marked T 24 N R 6 E S 24 B T.

A yellow pine, 7 ins. diam., bears N. 28° W., 116 lks. dist., marked T 24 N R 6 E S 13 B T.

Land, rolling.

Soil, volcanic formation, 3rd rate.

Timber, pines; undergrowth, 2nd growth pine.

N. 0° 13' E., bet. secs. 13 and 18.

Over rolling land, through heavy timber and scattering undergrowth.

Desc. 51 ft. over rolling NE. slope.

20.00 Slope changes; along gentle E. slope.

40.44 The ¼ sec. cor. of secs. 13 and 18 determined from original bearing trees.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor. of secs. 13 and 18, with brass cap marked

¼	
S18	S13

1944.

. . . from which

Original bearing tree:

A yellow pine, 30 ins. diam., now dead, bears N. 12½° W., 123 lks. dist., marked ¼ S B T.

New bearing trees:

A yellow pine, 8 ins. diam., bears S. 78¼° E., 130 lks. dist., marked ¼ S 13 B T.

A yellow pine, 10 ins. diam., bears N. 81¾° W., 110 lks. dist., marked ¼ S 18 B.T.

Resurvey of the W. Bdy. of T. 24 N., R. 7 E.

Chains

N. 0° 15' W., bet. secs. 13 and 18.

Ascend 70 ft. over SE. slope.

6.50 Fire road bears E. and N.80°W.

20.00 Spur slopes E.; desc. 83 ft. over N. slope.

31.40 Draw drains N.80°E.; along gentle E. slope.

39.81 The cor. of secs. 7, 12, 13 and 18 determined from original bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 7, 12, 13 and 18, with brass cap marked

T24N	
R6E	R7E
S12	S7
S13	S18

1944

from which

Original bearing tree:

A yellow pine, 28 ins. diam., bears N. 79½°W., 90 lks. dist., marked T 24 N R 6 E S 12 B T.

New bearing trees:

A yellow pine, 6 ins. diam., bears N. 58°E., 298 lks. dist., marked T 24 N R 7 E S 7 B T.

A pinon, 8 ins. diam., bears S. 19° E., 169 lks. dist., marked T 24 N R 7 E S 18 B T.

A yellow pine, 7 ins. diam., bears S. 77½°W., 214 lks. dist., marked T 24 N R 6 E S 13 B T.

A yellow pine, 5 ins. diam., bears N. 45½°W., 189 lks. dist., marked T 24 N R 6 E S 12 B T.

Land rolling.

Soil, volcanic formation, 3rd rate.

Timber, pine and pinon; undergrowth, 2nd growth timber and sage brush.

N. 0°08' W., bet. secs. 7 and 12.

Over rolling land, through heavy timber and scattering undergrowth.

Desc. gradually along a gentle E. slope.

4.60 Fire road bears SE. and NW.

30.00 Slope changes; desc. 66 ft. over NW. slope.

40.68 The ¼ sec. cor. of secs. 7 and 12, as evidenced by a wooden post, 24 ins. long, 3 ins. in diam., marked ¼ S on W. face, firmly set in a mound of stone, 2 ft. base, 1 ft. high

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, with original cor. post buried alongside and in a mound of stone to top, at ¼ sec. cor. of secs. 7 and 12, with brass cap marked

4355

Resurvey of the W. Bdy. of T. 24 N., R. 7 E.

Chains

$$\begin{array}{c} \frac{1}{4} \\ \text{S12} | \text{S7} \\ \hline \end{array}$$

1944

from which

Original bearing tree:

A yellow pine, 20 ins. diam., bears S. $12\frac{3}{4}^{\circ}$ W., 57 lks. dist., marked $\frac{1}{4}$ S B T.

New bearing trees:

A yellow pine, 10 ins. diam., bears S. $54\frac{1}{4}^{\circ}$ E., 76 lks. dist., marked $\frac{1}{4}$ S 7 B T.

A yellow pine, 18 ins. diam., bears N. $79\frac{1}{4}^{\circ}$ W., 105 lks. dist., marked $\frac{1}{4}$ S 12 B T.

N. $0^{\circ}23'$ W., bet. secs. 7 and 12.

Desc. gradually over N. slope.

- 3.00 Head of a draw, drains N. 30° E.; desc. 8 ft. along E. slope.
- 8.20 Recross draw, 1 ch. wide, drains NW.; asc. 6 ft. along W. slope.
- 12.60 Top of ascent, bears SE. and NW.; desc. 32 ft. over N. slope.
- 16.60 Shallow draw, drains NE.; continue descent, along a rolling E. slope.
- 30.00 Leave heavy, enter scattering timber, bears NW. and E.
- 40.03 The cor. of secs. 1, 6, 7 and 12, determined from original bearing tree
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 1, 6, 7 and 12, with brass cap marked

$$\begin{array}{c} \text{T24N} \\ \text{R6E} | \text{R7E} \\ \hline \text{S1} | \text{S6} \\ \hline \text{S12} | \text{S7} \end{array}$$

1944

from which

Original bearing tree:

A pinon, 24 ins. diam., bears N. 70° W., 126 lks. dist., marked T 24 N R 6 E S 1 B T.

New bearing trees:

A pinon, 5 ins. diam., bears N. $60\frac{1}{2}^{\circ}$ E., 192 lks. dist., marked T 24 N R 7 E S 6 B T.

A pinon, 5 ins. diam., bears S. $75\frac{1}{2}^{\circ}$ E., 168 lks. dist., marked T 24 N R 7 E S 7 B T.

A pinon, 8 ins. diam., bears S. $84\frac{1}{4}^{\circ}$ W., 215 lks. dist., marked T 24 N R 6 E S 12 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, yellow pine, pinon and juniper; undergrowth, 2nd growth timber and sage.

Resurvey of the W. Bdy. of T. 24 N., R. 7 E.

Chains N. 0° 02' W., bet. secs. 1 and 6.
 Over rolling land, through scattering timber and undergrowth.
 Desc. 70 ft. over gradual NE. slope.

39.15 Proportional distance.
 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. of secs. 1 and 6, with brass cap marked

$\frac{1}{4}$
 S1 | S6
 1944

from which

A pinon, 5 ins. diam., bears S. 85° E., 211 lks. dist., marked $\frac{1}{4}$ S 6 B T.

A yellow pine, 7 ins. diam., bears N. 71 $\frac{3}{4}$ ° W., 250 lks. dist., marked $\frac{1}{4}$ S 1 B T.

Desc. gradually over a NE. slope.

46.50 Bottom of drain, course E.; asc. gradually over gentle E. slope.

58.54 Intersect Sixth Standard Parallel North.
 Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, at closing corner of Ts. 24 N., Rs. 6 and 7 E., with brass cap marked

T25N R6E
 S36
 S1 | S6
 R6E | R7E
 C C
 1944

from which

A pinon, 3 ins. diam., bears S. 3 $\frac{1}{2}$ ° E., 103 lks. dist., marked CC BT.

A juniper, 14 ins. diam., bears S. 20 $\frac{1}{2}$ ° W., 132 lks. dist., marked T 24 N R 6 E S 1 C C B T.

From the closing cor., the standard $\frac{1}{4}$ sec. cor., S. bdy. sec. 36, T. 25 N., R. 6 E., bears N. 89° 23' W., 9.00 chs. dist.

Continue on a blank line in sec. 36.

58.73 The original closing cor. of Ts. 24 N., Rs. 6 and 7 E., as evidenced by a juniper post, 3 ft. long, 3 ins. diam., set 24 ins. in the ground. Reset original cor. post, 28 ins. in the ground and additionally mark W.P on S. face.

Land, rolling.
 Soil, rocky and gravelly, 3rd rate.
 Timber, pinon, yellow pine and juniper; undergrowth, 2nd growth timber and sage.

 Resurvey of the W. bdy. of T. 24 N., R. 6 E.

Reestablishment of a survey executed by F.W.Oury, Deputy Surveyor in 1894.

From the cor. of Ts. 23 and 24 N., Rs. 5 and 6 E., as evidenced by an iron post, 3 ins. diam.; set, marked and witnessed as described in the field notes of the E. Bdy. of T. 23 N., R. 5 E., resurveyed under this group.

N. 0° 24' W., bet. secs. 31 and 36.
 Over mountainous land, through heavy timber and scattering

Resurvey of the W. Bdy. of T. 24 N., R. 6 E.

Chains undergrowth.
 Asc. 233 ft. over SE. slope.
 21.70 Ridge, bears E. and W.; desc. 277 ft. over NE. slope.
 40.28 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, determined from the old bearing tree.
 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. of secs. 31 and 36, with brass cap marked

$\frac{1}{4}$
 S36|S31
 1944

from which

Original bearing tree:
 A yellow pine, 26 ins. diam., now dead, bears N. $85\frac{1}{4}^{\circ}$ E., 9 lks. dist., marked $\frac{1}{4}$ S B T.

New bearing trees:
 A fir, 4 ins. diam., bears S. 27° E., 62 lks. dist., marked $\frac{1}{4}$ S 31 B T.
 A yellow pine, 26 ins. diam., bears N. $73\frac{1}{2}^{\circ}$ W., 137 lks. dist., marked $\frac{1}{4}$ S 36 B T.

N. $0^{\circ} 30'$ W., bet. secs. 31 and 36.
 Desc. 40 ft. over NE. slope.

2.50 Base of steep descent, enter rolling land, bears SE. and W.; desc. 33 ft. over gradual N. slope.
 11.50 Drain, course NW.; desc. gradually over a gentle W. slope.
 24.80 Road, bears E. and S. 80° W.
 39.87 The cor. of secs. 25, 30, 31 and 36, as evidenced by a lava stone $16 \times 10 \times 8$ ins., firmly set in the ground, marked 1 groove on S. and 5 grooves on N. faces, witnessed by a mound of stone, 3 ft. base, 10 ins. high, W. of cor.
 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground with the original cor. stone buried alongside, at cor. of secs. 25, 30, 31 and 36, with brass cap marked

T24N
 R5E | R6E
 S25 | S30
 S36 | S31
 1944

from which

Original bearing trees:
 A yellow pine, 9 ins. diam., now dead, bears N. $23\frac{1}{2}^{\circ}$ E., 169 lks. dist., marked T 24 N R 6 E S 30 B T.
 A yellow pine, 18 ins. diam., bears S. $53\frac{3}{4}^{\circ}$ W., 42 lks. dist., markings overgrowth, not uncovered.
 The original position of a yellow pine, 12 ins. diam., now dead, lying on ground, bears N. $54\frac{1}{4}^{\circ}$ W., 62 lks. dist., marked T 24 N R 5 E S 25 B T.

New bearing trees:
 A yellow pine, 5 ins. diam., bears N. $18\frac{3}{4}^{\circ}$ E., 187 lks. dist., marked T 24 N R 6 E S 30 B T.
 A yellow pine, 5 ins. diam., bears S. 6° E., 136 lks. dist., marked T 24 N R 6 E S 31 B T.
 A yellow pine, 16 ins. diam., bears S. $15\frac{3}{4}^{\circ}$ W., 53 lks. dist., marked T 24 N R 5 E S 36 B T.

. Resurvey of the W. Bdy. of T. 24 N., R. 6 E.

Chains

A yellow pine, 16 ins. diam., bears N.31 $\frac{1}{2}$ °W., 185 lks. dist., marked T 24 N R 5 E S 25 B T.

Land, S. $\frac{1}{2}$ mountainous; N. $\frac{1}{2}$ rolling.

Soil, rocky, 3rd rate.

Timber, pine, fir and aspen; undergrowth, second growth timber.

N.0°11'W., bet. secs. 25 and 30.

Over rolling land, thru heavy timber and scattering undergrowth.

Desc. gradually along a gentle W. slope.

15.00 Slope changes; desc. gradually over a rolling N. slope.

39.92 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, as evidenced by a malpais stone 16x6x6 ins. firmly set in the ground, marked $\frac{1}{4}$ on W. face, witnessed by a mound of stone, 2 ft. base, 10 ins. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. of secs. 25 and 30, with brass cap marked

$\frac{1}{4}$
 S25 | S30
 · 1944

from which

Original bearing tree:

A yellow pine, 14 ins. diam., now dead, bears N.36 $\frac{1}{2}$ °W., 61 lks. dist., marked $\frac{1}{4}$ S B T.

New bearing trees:

A yellow pine, 7 ins. diam., bears S.73 $\frac{1}{2}$ °E., 24 lks. dist., marked $\frac{1}{4}$ S 30 B T.

A yellow pine, 4 ins. diam., bears S.58 $\frac{1}{4}$ °W., 23 lks. dist., marked $\frac{1}{4}$ S 25 B T.

N.0°14'W., bet. secs. 25 and 30.

Desc. 60 ft. over gradual N. slope.

7.70 Graded road, bears N.60°W., to Bull Basin and S.60°E., to Flagstaff.

40.74 The cor. of secs. 19, 24, 25 and 30, as evidenced by a malpais stone, 26x18x12 ins. firmly set in a mound of stone $3\frac{1}{2}$ ft. base, marked 2 grooves on S. and 4 grooves on N. faces

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in ground to bedrock with the original cor. stone buried alongside, and in a mound of stone to top, at cor. of secs. 19, 24, 25 and 30, with brass cap marked

T24N
 R5E | R6E
 S24 | S19
 S25 | S30
 1944

Resurvey of the W. Bdy. of T. 24 N., R. 6 E.

Chains

from which

Original bearing trees:

A yellow pine, 14 ins. diam., bears N.17°E., 17 lks. dist., marked T 24 N R 6 E S 19 B T.

A yellow pine, 16 ins. diam., bears S.51½°E., 48 lks. dist., marked T 24 N R 6 E S 30 B T.

A yellow pine, 12 ins. diam., bears S.88¼°W., 38 lks. dist., markings overgrown, mark on overgrowth T 24 N R 5 E S 25 B T.

A yellow pine, 28 ins. diam., bears N.51½°W., 77 lks. dist., markings overgrown, mark on overgrowth T 24 N R 5 E S 24 B T.

Land, rolling.
Soil, rocky, 3rd rate.
Timber, pine, fir and aspen; undergrowth, 2nd growth timber.

N.1°41'E., bet. secs. 19 and 24.


Over rolling land, through heavy timber and scattering undergrowth.

Desc. 110 ft. over gradual N. slope.

35.92 A 4 strand barbed wire drift fence and Forest Service telephone line, bears E. and W.

39.79 The ¼ sec. cor. of secs. 19 and 24, as evidenced by a lava stone 14x10x8 ins., firmly set in the ground, marked ¼ on W. face, witnessed by a mound of stone 2 ft. base, and 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground with the original cor. stone buried alongside, at ¼ sec. cor. of secs. 19 and 24, with brass cap marked



from which

Original bearing trees:

A yellow pine, 24 ins. diam., bears N.14¼°W., 187 lks. dist., marked ¼ S B T., additionally mark on overgrowth, ¼ S 24 B T.

A yellow pine, 22 ins. diam., bears S.5¼°W., 133 lks. dist., markings overgrown, mark on overgrowth, ¼ S 24 B T.

New bearing tree:

A yellow pine, 4 ins. diam., bears N.79½°E., 33 lks. dist., marked ¼ S 19 B T.

N.0°14'W., bet. secs. 19 and 24.

Desc. 137 ft. over gradual N. slope.

40.22 The cor. of secs. 13, 18, 19 and 24, as evidenced by a malpais stone 16x12x10 ins., firmly set in a mound of stone, marked 3 grooves on S. and N. faces.

Resurvey of the W. Bdy. of T. 24 N., R. 6 E.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bedrock, with the original cor. stone buried alongside and in a mound of stone to top, at the cor. of secs. 13, 18, 19 and 24, with brass cap marked

T24N	
R5E	R6E
S13	S18
S24	S19

1944

from which

Original bearing trees:

A yellow pine, 16 ins. diam., bears S. $8\frac{1}{2}^{\circ}$ E., 96 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 6 E S 19 B T.

A yellow pine, 18 ins. diam., bears S. $61\frac{1}{2}^{\circ}$ W., 176 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 24 B T.

A yellow pine, 24 ins. diam., bears N. $17\frac{1}{4}^{\circ}$ W., 112 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 5 E S 13 B T.

New bearing tree:

A yellow pine, 6 ins. diam., bears N. $72\frac{3}{4}^{\circ}$ E., 43 lks. dist., marked T 24 N R 6 E S 18 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

North bet. secs. 13 and 18.

Over rolling land, through heavy timber and scattering undergrowth.

Desc. 75 ft. over gradual N. slope.

24.80 Old road, bears E. and W.

39.88 The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, as evidenced by a malpais stone 16x12x6 ins., firmly set in the ground, marked $\frac{1}{4}$ on W. face, witnessed by a mound of stone, 2 ft. base, 10 ins. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with the original cor. stone buried alongside and in a mound of stone to top, at $\frac{1}{4}$ sec. cor. of secs. 13 and 18, with brass cap marked

$\frac{1}{4}$	
S13	S18

1944

from which

The original bearing trees:

A yellow pine, 32 ins. diam., now dead, bears N. 5° E., 203 lks. dist., marked $\frac{1}{4}$ S B T.

A yellow pine, 28 ins. diam., bears N. 77° E., 168 lks. dist., markings overgrown, not uncovered.

Resurvey of the W. Bdy. of T. 24 N., R. 6 E.

Chains

New bearing trees:

A yellow pine, 8 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ E., 46 lks. dist., marked $\frac{1}{4}$ S 18 B T.

A yellow pine, 6 ins. diam., bears S. $83\frac{1}{4}^{\circ}$ W., 42 lks. dist., marked $\frac{1}{4}$ S 13 B T.

N. $0^{\circ}23'$ E., bet. secs. 13 and 18.

Descend slightly over gently rolling N. slope.

15.00 Leave heavy, enter scattering timber, bears E. and W.

39.94 The original cor. of secs. 7, 12, 13 and 18, as evidenced by a malpais stone $18 \times 12 \times 5$ ins., firmly set in the ground, marked 4 grooves on S. and 2 grooves on N. faces, witnessed by a mound of stone 2 ft. base, 16 ins. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to bedrock, with the original stone buried alongside and in a mound of stone to top, at cor. of secs. 7, 12, 13 and 18, with brass cap marked

T24N	
R5E	R6E
S12	S7
S13	S18

1944

from which

A yellow pine, 5 ins. diam., bears N. 71° E., 250 lks. dist., marked T 24 N R 6 E S 7 B T.

A yellow pine, 3 ins. diam., bears S. $51\frac{1}{4}^{\circ}$ E., 307 lks. dist., marked B T.

A yellow pine, 8 ins. diam., bears S. $7\frac{1}{4}^{\circ}$ W., 201 lks. dist., marked T 24 N R 5 E S 13 B T.

A yellow pine, 5 ins. diam., bears N. 78° W., 244 lks. dist., marked T 24 N R 5 E S 12 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

N. $0^{\circ}10'$ W., bet. secs. 7 and 12.

Over gently rolling land, through scattering timber and undergrowth.

17.70 A 5 strand wire fence, bears NE. for 5 chs., then N.; SW. for 4 chs., then W.


19.50 E. edge of a sink, about 7 chs. diam.

40.00 The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, as evidenced by a malpais stone $20 \times 12 \times 4$ ins., loosely set in the ground, marked $\frac{1}{4}$ on W. face, witnessed by a mound of stone 2 ft. base, 8 ins. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, with brass cap marked

Resurvey of the W. Bdy. of T. 24 N., R. 6 E.

Chains



from which

A yellow pine, 10 ins. diam., bears N.89°22'E., 566 lks. dist., marked $\frac{1}{4}$ S 7 B T.

A juniper, 3 ins. diam., bears N.46 $\frac{1}{2}$ °W., 388 lks. dist., marked B T.

Center of Slate lake, 8 chs. long, N. and S., 5 chs. wide, E. and W., bears N.77°E., 11.85 chs. dist.

Center of another lake, 7 chs. diam., bears N.15°W., 23.50 chs. dist.

N.0°23'E., bet. secs. 7 and 12.

Continue over gently rolling land.

4.50 Leave scattering, enter heavy timber, bears E. and W.


15.60 Ascend slightly over S. slope.

22.00 A 5 strand barbed wire fence, bears SE. and NW. for 10 chs. to a fence cor. from which fences extend N.20°W. and S.

37.95 Graded road bears S.85°W., to Slate Mountain Lookout Station and N.85°E. to junction of main road.

40.00 The cor. of secs. 1, 6, 7 and 12, as evidenced by a malpais stone 14x12x10 ins., firmly set in the ground and marked 5 grooves on S. and 1 groove on N. faces, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground with the original cor. stone buried alongside, at cor. of secs. 1, 6, 7 and 12, with brass cap marked



1944

rebuild mound

of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, gently rolling.

Soil, rocky, 3rd rate.

Timber, pine and juniper; undergrowth, 2nd growth pine.

N.0°27'E., bet. secs. 1 and 6.

Over open rolling land; asc. gradually.

8.00 Top of slight ascent, bears E. and W.; enter scattering growth of pine, bears E. and W., along gentle E. slope.

25.95 Graded road bears N.30°W. to the Grand Canyon and S.30°E. to Flagstaff.

35.10 Drain, course W.; asc. slightly over S. slope.

39.97 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, as evidenced by a lava

Resurvey of the W. Bdy. of T. 24 N., R. 6 E.

Chains

stone 14x12x6 ins., firmly set in the ground, marked $\frac{1}{4}$ on W. face, witnessed by a mound of stone, 2 ft. base, 10 ins. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. of secs. 1 and 6, with brass cap marked

$\frac{1}{4}$
S1|S6
1944

from which

A yellow pine, 5 ins. diam., bears N.73°E., 41 lks. dist., marked $\frac{1}{4}$ S 6 B T.

A yellow pine, 4 ins. diam., bears N.19 $\frac{3}{4}$ °W., 225 lks. dist., marked $\frac{1}{4}$ S 1 B T.

N.1°24'E., bet. secs. 1 and 6.

Asc. 80 ft. over SW. slope.

6.90 Enter heavy timber, bears E. and W., asc. SW. slope of red cinder hill.

15.50 Top of ascent, bears E. and W.; desc. 30 ft. over NW. slope.

20.34 The closing cor. of Ts. 24 N., Rs. 5 and 6 E., as evidenced by a lava stone 16x12x8 ins., firmly set in the ground, marked CC on N. face, 6 grooves on S. face, and 6 notches on E. and W. edges, witnessed by a mound of stone, 3 ft. base, 1 ft. high, NW. of cor.; additionally mark this stone W P.

Original bearing trees:

A yellow pine, 16 ins. diam., bears S.89°E., 29 lks. dist., markings overgrown, not uncovered.

A pinon, 18 ins. diam., bears S.25°W., 114 lks. dist., marked T 24 N R 5 E S 1 B T.

20.64 Intersect Sixth Standard Parallel North.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, at closing cor. of Ts. 24 N., Rs. 5 and 6 E., with brass cap marked

T25N R5E
336
S1|S6
R5E R6E
T24N
C C
1944

from which

Original bearing trees:

A yellow pine, 16 ins. diam., bears S.42 $\frac{3}{4}$ °E., 41 lks. dist., marked on overgrowth, T 24 N R 6 E S 6 C C B T.

A pinon, 18 ins. diam., bears S.20 $\frac{1}{2}$ °W., 142 lks. dist., remark on overgrowth, T 24 N R 5 E S 1 C C B T.

Resurvey of the W. Bdy. of T. 24 N., R. 6 E.

Chains

From this closing corner, the standard $\frac{1}{4}$ sec. cor., S. bdy. of sec. 36, T. 25 N., R. 5 E., bears S.89°37'W., 10.59 chs. dist.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pinon, juniper and pine; undergrowth, 2nd growth timber.

 Resurvey of the Subdivision of T. 24 N., R. 6 E.

Reestablishment of a survey executed by F. W. Oury, Deputy Surveyor in 1894.

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the field notes of the N. bdy. of T. 23 N., R. 6 E., resurveyed under this group.

N.0°22'W., bet. secs. 35 and 36.

Over rolling land, through heavy timber and scattering undergrowth.

Asc. gradual S. slope.

- 6.50 Old road bears E. and W.
 8.00 Low spur, slopes E. from NW.; desc. 25 ft. over N. slope.
 10.30 Forest Service telephone line, bears SW. and NE.
 18.70 Old road, bears E. and W.
 18.90 A draw 150 lks. wide, drains E.; asc. 17 ft. over S. slope.
 20.30 Graded road, bears E. to Deadman Cabin and W. to Kendrick Park.
 23.60 Slope changes, along gentle E. slope.
 33.60 Enter mountainous land, bears NE. and SW.; slope changes; asc. 29 ft. over SE. slope.
 39.86 The $\frac{1}{4}$ sec. cor. determined from original bearing trees
 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$
 S35 | S36
 1944

from which

Original bearing trees:

Original position of a yellow pine, now dead, lying on ground, bears N.51°E., 97 lks. dist., marked $\frac{1}{4}$, other marks illegible.

A yellow pine, 28 ins. diam., bears N.87°W., 47 lks. dist., marked $\frac{1}{4}$ S B T.

CCON 4355

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

New bearing trees:

A yellow pine, 10 ins. diam., bears N.73°E., 37 lks. dist., marked $\frac{1}{4}$ S 36 B T.

A yellow pine, 7 ins. diam., bears S.44 $\frac{1}{2}$ °W., 40 lks. dist., marked $\frac{1}{4}$ S 35 B T.

N.0°42'E., bet. secs. 35 and 36.

Asc. 103 ft. over SE. slope.

4.31 A 4 strand barb wire fence, bears N.69°W., and S.69°E.

12.00 Slope changes; asc. 32 ft. along E. slope.

20.00 Top of ascent; bears E. and W.; desc. 148 ft. over NE. slope.

39.68 The cor. of secs. 25, 26, 35 and 36, determined from original bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 25, 26, 35 and 36, with brass cap marked

T24N R6E

S26|S25

S35|S36

1944

from which

Original bearing trees:

A yellow pine, 36 ins. diam., bears N.81°E., 97 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 6 E S 25 B T.

A yellow pine, 36 ins. diam., now dead, bears S.54 $\frac{1}{2}$ °E., 97 lks. dist., marked T 24 N R 6 E S 36 B T.

A yellow pine, 30 ins. diam., bears S.45°W., 140 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 6 E S 35 B T.

A yellow pine, 18 ins. diam., bears N.79 $\frac{1}{4}$ °W., 31 lks. dist., marks overgrown, mark on overgrowth, T 24 N R 6 E S 26 B T.

New bearing tree:

A yellow pine, 6 ins. diam., bears S.38 $\frac{1}{4}$ °E., 33 lks. dist., marked T 24 N R 6 E S 36 B T.

This cor. located in bottom of a grassy shallow draw, drains E.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, yellow pine; undergrowth, 2nd growth pine.

From the cor. of secs. 25, 30, 31 and 36 on the E. Bdy. of Tp.

N.89°18'W., bet. secs. 25 and 36.

Over mountainous land, through heavy timber and scattering undergrowth.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

4156

Chains	
	Asc. 29 ft. over NE. slope.
1.70	A spur, slopes SE.; continue ascent along S. slope, 120 ft.
17.50	Spur, slopes S.; desc. 227 ft. over a W. slope.
30.00	Enter rolling land, bears NW. and SE.; desc. over a gradual SW. slope.
39.97	The $\frac{1}{4}$ sec. cor. determined from original bearing trees. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ $\frac{S\ 25}{S\ 36}$ 1944
	from which
	Original bearing trees:
	A yellow pine, 32 ins. diam., now dead, bears N.27°E., 124 lks. dist., marked $\frac{1}{4}$ S. B T.
	A yellow pine, 32 ins. diam., bears S.27°W., 122 lks. dist., markings overgrown, mark on overgrowth, $\frac{1}{4}$ S. 36 BT.
	New bearing tree:
	A yellow pine, 12 ins. diam., bears N.43 $\frac{1}{2}$ °W., 180 lks. dist., marked $\frac{1}{4}$ S 25 B T.
	N.89°49'W., bet. secs. 25 and 36.
13.60	Enter open park, bears N. and S.
21.30	Graded road, bears N.10°W., and S. 10°E.
27.40	A drain course S., from N.20°E.; asc. gradual E. slope.
31.30	Enter heavy timber and scattering undergrowth, bears N. and S.
40.77	The cor. of secs. 25, 26, 35 and 36. Land, E: 30 chs. mountainous, remainder rolling. Soil, rocky, 3rd rate. Timber, pine; undergrowth, 2nd growth pine.
	N.0°38'W., bet. secs. 25 and 26. Over rolling land, through heavy timber and scattering undergrowth. Asc. 23 ft. over S. slope.
11.60	Low, short spur, slopes E.; continue ascent along gentle E. slope.
39.77	The $\frac{1}{4}$ sec. cor. determined from original bearing trees. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ S26 S25 1944

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	from which								
	Original bearing trees:								
	A yellow pine, 24 ins. diam., bears N.72°E., 11 lks. dist., marked $\frac{1}{4}$ S B T.								
	A yellow pine, 24 ins. diam., bears S.72°W., 64 lks. dist., marked $\frac{1}{4}$ S B T.								
	New bearing trees:								
	A yellow pine, 6 ins. diam., bears S.70 $\frac{3}{4}$ °W., 45 lks. dist., marked $\frac{1}{4}$ S 26 B T.								
	A yellow pine, 10 ins. diam., bears S.64°E., 53 lks. dist., marked $\frac{1}{4}$ S 25 B T.								
	N.0°54'E., bet. secs. 25 and 26.								
	Along gentle E. slope.								
10.80.	Bottom of draw, 4 chs. wide, drains S.30°E. Graded road, bears S.30°E. and N.30°W.; asc. 16 ft. along gentle W. slope.								
25.00	Enter mountainous land, bears NW. and SE.; base of steep ascent; asc. 151 ft. over SW. slope.								
40.46	At this point, determined by the method of double proportional measurement								
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 23, 24, 25 and 26, with brass cap marked								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T24N R6E</td> </tr> <tr> <td style="border-right: 1px solid black;">S23</td> <td>S24</td> </tr> <tr> <td style="border-right: 1px solid black;">S26</td> <td>S25</td> </tr> <tr> <td colspan="2" style="text-align: center;">1944</td> </tr> </table>	T24N R6E		S23	S24	S26	S25	1944	
T24N R6E									
S23	S24								
S26	S25								
1944									
	from which								
	A yellow pine, 24 ins. diam., bears N.26 $\frac{1}{2}$ °E., 90 lks. dist., marked T 24 N R 6 E S 24 B T.								
	A yellow pine, 10 ins. diam., bears S.77 $\frac{1}{4}$ °E., 89 lks. dist., marked T 24 N R 6 E S 25 B T.								
	A yellow pine, 6 ins. diam., bears S.24°W., 67 lks. dist., marked T 24 N R 6 E S 26 B T.								
	A yellow pine, 5 ins. diam., bears N.73 $\frac{1}{2}$ °W., 29 lks. dist., marked T 24 N R 6 E S 23 B T.								
	Land, S. 65 chs. rolling; remainder mountainous. Soil, rocky, volcanic formation, 3rd rate. Timber, yellow pine and fir; undergrowth, 2nd growth timber.								

	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.								
	N.89°32'W., bet. secs. 24 and 25.								
	Over rolling land, through heavy timber and scattering undergrowth.								
	Asc. gradual E. slope.								

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
1.00	Top of ascent, bears NE. and SW.; desc. gradual NW. slope.
6.50	Draw, drains NE.; enter mountainous land; asc. 578 ft. over SE. slope.
40.02	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4} \begin{array}{r} S 24 \\ S 25 \\ 1944 \end{array}$ <p style="text-align: right;">from which</p>
	A yellow pine, 7 ins. diam., bears N.29 $\frac{1}{4}$ °W., 50 lks. dist., marked $\frac{1}{4}$ S 24 B T.
	A yellow pine, 6 ins. diam., bears S.22 $\frac{1}{2}$ °E., 28 lks. dist., marked $\frac{1}{4}$ S 25 B T.
	Ascend 29 ft. over SE. slope.
43.40	Top of ridge, bears N. and S.; desc. 17 ft. along a S. slope.
51.30	Ravine course SE.; asc. 80 ft. over SE. slope.
59.50	Spur, slopes S., from NW.; desc. 303 ft. over SW. slope.
80.05	The cor. of secs. 23, 24, 25 and 26.
	Land, mountainous. Soil, rocky, 3rd rate. Timber, yellow pine, white pine and fir; undergrowth, 2nd growth pine.
	----- N.2°13'W., bet. secs. 23 and 24.
	Over mountainous land, through heavy timber and scattering undergrowth.
	Asc. 67 ft. over SW. slope.
9.00	Slope changes, along steep W. slope.
14.00	Ridge bears E. and W.; deep saddle bears W. about 8 chs. dist.; desc. 72 ft. along steep W. slope.
27.50	Slope changes; desc. 45 ft. over NW. slope.
35.15	Ravine, course W.; asc. 58 ft. over SW. slope.
40.48	Proportional distance
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{r} S23 S24 \\ 1944 \end{array}$ <p style="text-align: right;">from which</p>
	A yellow pine, 6 ins. diam., bears S.47 $\frac{1}{2}$ °E., 24 lks. dist., marked $\frac{1}{4}$ S 24 B T.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

A yellow pine, 6 ins. diam., bears S.53°W., 6 lks. dist., marked $\frac{1}{4}$ S 23 B T.

Asc. 183 ft. over SW. slope.

62.90 Ridge, bears NW. and SE.; desc. 387 ft. over NE. slope.

80.96 The cor. of secs. 13, 14, 23 and 24, as evidenced by a lava stone 16x14x10 ins. firmly set in the ground, marked 3 grooves on S. and 1 groove on E. faces

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original cor. stone buried alongside, at cor. of secs. 13, 14, 23 and 24, with brass cap marked

T24N R6E
 $\frac{1}{4}$ S14 | S13
 S23 | S24

1944

from which

Original bearing trees:

A yellow pine, 12 ins. diam., bears N.42°E., 50 lks. dist., markings overgrown, not uncovered, mark on overgrowth, T 24 N R 6 E S 13 B T.

A yellow pine, 14 ins. diam., bears S.40°E., 72 lks. dist., markings overgrown, not uncovered, mark on overgrowth, T 24 N R 6 E S 24 B T.

A yellow pine, 18 ins. diam., bears S.58 $\frac{1}{2}$ °W., 36 lks. dist., marked T 24 N R 6 E S 23 B T, additionally mark on overgrowth T 24 N R 6 E S 23 B T.

A yellow pine, 12 ins. diam., bears N.37°W., 82 lks. dist., markings overgrown, not uncovered, mark on overgrowth, T 24 N R 6 E S 14 B T.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, yellow pine and pinon; undergrowth, 2nd growth timber.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of Tp.

N.89°16'W., bet. secs. 13 and 24.

Over mountainous land, through heavy timber and undergrowth.

Asc. 190 ft. over NE. slope.

33.10 Graded road, bears NW. and SE.

41.30 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$ S 13
 S 24
 1944

from which

A yellow pine, 8 ins. diam., bears N.19°E., 25 lks. dist., marked $\frac{1}{4}$ S 13 B T.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	<p>A yellow pine, 8 ins. diam., bears S.59$\frac{1}{4}$°E., 9 lks. dist., marked $\frac{1}{4}$ S 24 B T.</p> <p>Asc. 227 ft. over a NE. slope.</p>
62.90	Head of a draw, course NE.; continue ascent over a NE. slope.
82.60	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, mountainous. Soil, rocky, 3rd rate. Timber, yellow pine; undergrowth, 2nd growth pine.</p> <p>-----</p> <p>N.0°25'E., bet. secs. 13 and 14.</p> <p>Over mountainous land, through heavy timber and scattering undergrowth.</p> <p>Desc. 34 ft. over a NE. slope.</p>
1.15	Graded road, bears N.80°E. to Deadman Cabin and W. to Curley Seep Guard Station.
2.90	A ravine, course E. for 1.50 chs., then NE.; heads 2.50 chs. W.; asc. 40 ft. along E. slope.
9.60	A short spur, slopes E.; desc. 86 ft. over NE. slope.
13.60	Ravine, course E., heads about 5 chs. W.; asc. 444 ft. over SE. slope.
38.76	<p>The $\frac{1}{4}$ sec. cor. as evidenced by a yellow pine, 14 ins. diam., markings on W. face overgrown, not uncovered, from which</p> <p>Original bearing tree:</p> <p>yellow A/pine, 14 ins. diam., bears N.1°W., 27 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>A Forest Service fire control corner, as evidenced by a 3 in. brass tablet, seated in a lava rock in place, 20x20x12 ins. above ground, marked</p> <p style="text-align: center;">.. Fire Control Visible Area Map Point Howard Seep 6-24-1938 Forest Service</p> <p style="text-align: right;">bears</p> <p>N.35°52'W., 5.78 chs. dist. This Forest Service fire control corner is located on top of a high ridge, bears S. and NW.</p> <p>N.1°22'E., bet. secs. 13 and 14.</p> <p>Asc. gradually along E. slope.</p>
0.50	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at witness $\frac{1}{4}$ sec. cor. of secs. 13 and 14, with brass cap marked

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

$\frac{1}{4}$
 S14 | S13
 W C
 1944

from which

A yellow pine, 10 ins. diam., bears N. 87° E., 71 lks. dist., marked W C $\frac{1}{4}$ S 13 B T.

A yellow pine, 7 ins. diam., bears N. 73 $\frac{1}{2}$ ° W., 78 lks. dist., marked W C $\frac{1}{4}$ S 14 B T.

- 1.00 Low spur, slopes E.; desc. 61 ft. over NE. slope.
- 5.35 Steep ravine, course E., heads 2 chs. W.; asc. 48 ft. over SE. slope.
- 11.30 Long spur, slopes NE.; desc. 104 ft. over NW. slope.
- 21.00 Spur, slopes N. from S. 5° E.; desc. 185 ft. along top of spur.
- 31.70 Leave top of spur, slopes N. 5° W.; desc. 100 ft. over NE. slope.
- 39.04 Cor. of secs. 11, 12, 13, and 14, as evidenced by a lava stone 18x10x5 ins. firmly set in the ground, marked 4 grooves on S. and 1 groove on E. faces, witnessed by a mound of stone, 2 ft. base, 10 ins. high, W. of cor..

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 11, 12, 13 and 14, with brass cap marked

T24N R6E
 S11 | S12
 S14 | S13
 1944

from which

Original bearing trees:

A yellow pine, 22 ins. diam., bears S. 51 $\frac{1}{4}$ ° E., 62 lks. dist., marked T 24 N R 6 E S 13 B T.

A yellow pine, 12 ins. diam., bears S. 74 $\frac{1}{4}$ ° W., 104 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 6 E S 14 B T.

New bearing trees:

A yellow pine, 8 ins. diam., bears N. 35 $\frac{1}{2}$ ° E., 64 lks. dist., marked T 24 N R 6 E S 12 B T.

A yellow pine, 6 ins. diam., bears N. 12 $\frac{1}{2}$ ° W., 48 lks. dist., marked T 24 N R 6 E S 11 B T.

Land, mountainous.
Soil, rocky, volcanic formation, 3rd rate.
Timber, yellow pine, pinon and fir; undergrowth, 2nd growth timber.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of Tp.
	S.88°57'W., bet. secs. 12 and 13.
	Over rolling land, through heavy timber and scattering undergrowth.
	Asc. 100 ft. over E. slope.
16.00	Enter mountainous land, bears N. and S.; asc. 617 ft. over E. slope.
35.00	Top of ascent, bears N.30°W. and S.; desc. 51 ft. over SW. slope.
40.58	Proportional distance.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4} \frac{S 12}{S 13}$ 1944
	from which
	A yellow pine, 12 ins. diam., bears N.74°E., 46 lks. dist., marked $\frac{1}{4}$ S 12 B T.
	A yellow pine, 5 ins. diam., bears S.41 $\frac{1}{4}$ °E., 40 lks. dist., marked $\frac{1}{4}$ S 13 B T.
	Desc. 62 ft. over SW. slope.
44.00	A sink, 5 chs. in diam., bears S. 6.25 chs. dist.
52.00	A drain, course SE.; asc. 212 ft. over NE. slope.
70.00	Top of ridge bears N.30°W., and S.30°E.; desc. 243 ft. over a W. slope.
78.20	Ravine, course NW.; asc. 21 ft. along N. slope.
81.16	The cor. of secs. 11, 12, 13 and 14.
	Land, E. 16 chs. rolling, remainder mountainous. Soil, rocky, 3rd. rate. Timber, yellow pine, white pine, pinon and juniper; undergrowth, 2nd growth pine.
	N.1°43'E., bet. secs. 11 and 12.
	Over mountainous land, through heavy timber and scattering undergrowth.
	Desc. 41 ft. over NE. slope.
1.40	Ravine, course NW.; asc. 48 ft. over SW. slope.
7.00	Slope changes; desc. 20 ft. along W. slope.
10.60	Spur, slopes NW.; desc. 305 ft. over broken N. slope.
31.90	A ravine, course NE. for 1.50 chs. then N.; desc. 75 ft. over broken N. slope.
41.30	Proportional distance

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S11} | \text{S12} \\ 1944 \end{array}$$

from which

A yellow pine, 14 ins. diam., bears S. 54° E., 89 lks. dist., marked $\frac{1}{4}$ S 12 B T.

A yellow pine, 16 ins. diam., bears S. 89° W., 15 lks. dist., marked $\frac{1}{4}$ S 11 B T.

Leave mountainous, enter rolling land, bears E. and W.

Desc. 214 ft. over rolling NE. slope.

11.00 Fire road, bears E. and W.

82.60 The cor. of secs. 1, 2, 11 and 12, determined from original bearing trees

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 1, 2, 11 and 12, with brass cap marked

$$\begin{array}{c} \text{T24N R6E} \\ \text{S2} | \text{S1} \\ \text{S11} | \text{S12} \end{array}$$

1944

from which

Original bearing trees:

A yellow pine, 36 ins. diam., bears S. 53° E., 80 lks. dist., marks overgrown, not uncovered, mark on overgrowth, T 24 N R 6 E S 12 B T.

A yellow pine, 16 ins. diam., bears S. 83° W., 236 lks. dist., marked T 24 N R 6 E S 11 B T.

New bearing trees:

A yellow pine, 8 ins. diam., bears N. 44° E., 65 lks. dist., marked T 24 N R 6 E S 1 B T.

A yellow pine, 8 ins. diam., bears S. 26° W., 168 lks. dist., marked T 24 N R 6 E S 11 B T.

A yellow pine, 6 ins. diam., bears N. 41° W., 217 lks. dist., marked T 24 N R 6 E S 2 B T.

Land, S. $\frac{1}{2}$ mountainous, N. $\frac{1}{2}$ rolling.

Soil, rocky, 3rd rate.

Timber, yellow pine and pinon; undergrowth, 2nd growth timber.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of Tp.

S. $89^{\circ}32'$ W., bet. secs. 1 and 12.

Over rolling land, through heavy timber and undergrowth.

Asc. gradual SE. slope.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
33.00	Low spur, slopes NW.; along rolling N. slope.
39.02	The $\frac{1}{4}$ sec. cor. as evidenced by a lava stone 16x14x6 ins. set in a small mound of stone, marked $\frac{1}{4}$ on N. face. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4} \begin{array}{c} S 1 \\ S 12 \\ 1944 \end{array}$ from which Original bearing trees: A pinon, 14 ins. diam., bears S.4 $\frac{1}{2}$ °E., 34 lks. dist., marked $\frac{1}{4}$ S B T., additionally mark on overgrowth $\frac{1}{4}$ S 12 B T. A juniper, 14 ins. diam., bears S.50 $\frac{1}{2}$ °W., 34 lks. dist., marked $\frac{1}{4}$ S B T., additionally mark on overgrowth $\frac{1}{4}$ S 12 B T. New bearing tree: A pinon, 8 ins. diam., bears N.27°W., 33 lks. dist., marked $\frac{1}{4}$ S 1 B T. N.88°59'W., bet. secs. 1 and 12. Along a gentle N. slope.
39.32	The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, rocky, 3rd rate. Timber, pine, pinon and juniper; undergrowth, 2nd growth pine. ----- N.1°17'W., bet. secs. 1 and 2. Over rolling land, through heavy timber and scattering undergrowth. Desc. 78 ft. over rolling NE. slope.
34.20	Fire road, bears NE. and SW.
39.34	Proportional distance. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked $\frac{1}{4} \begin{array}{c} S 2 \\ S 1 \\ 1944 \end{array}$ from which A yellow pine, 18 ins. diam., bears N.37 $\frac{1}{4}$ °E., 93 lks. dist., marked $\frac{1}{4}$ S 1 B T. A yellow pine, 24 ins. diam., bears S.89°W., 177 lks. dist., marked $\frac{1}{4}$ S 2 B T. Desc. gradually along a gentle E. slope.
58.56	Closing cor. of secs. 1 and 2. From the closing cor., the standard $\frac{1}{4}$ sec. cor., S. bdy. sec. 35, T. 25 N., R. 6 E., bears N.89°31'W., 9.88 chs.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

dist.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, yellow pine, pinon and juniper; undergrowth, 2nd growth timber and sage.

At midpoint on the N. bdy. of sec. 1.Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor. of sec. 1, with brass cap marked
$$\begin{array}{c} \frac{1}{4} S 1 \\ 1944 \end{array}$$

from which

Juniper, 14 ins. diam., bears S. $36\frac{1}{2}^{\circ}$ E., 19 lks. dist., marked $\frac{1}{4}$ S 1 B T.A pinon, 3 ins. diam., bears S. $5\frac{1}{2}^{\circ}$ W., 90 lks. dist., marked B T.From this cor. the standard cor. of secs. 35 and 36, T. 25 N., R. 6 E., bears N. $89^{\circ}53'$ W., 9.44 chs. dist.-----
From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of Tp., as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the field notes of the N. bdy. of T. 23 N., R. 6 E., resurveyed under this group.N. $0^{\circ}23'$ E., bet. secs. 34 and 35.

Over nearly level open land; asc. over gradual SW. slope; along center of road right of way.

0.28 Forest Service telephone line, bears E. and W.

0.45 A property fence cor. bears W. 45 lks. dist., from which fences extend westerly and northerly.

19.88 A property fence cor. bears W. 45 lks. dist., from which fences extend N., S., and W.

39.92 The $\frac{1}{4}$ sec. cor. as evidenced by the intersection of the center line of a road right of way and a line extended E. from a property line fence cor.Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked
$$\begin{array}{c} \frac{1}{4} \\ S 34 | S 35 \\ 1944 \end{array}$$

from which

A yellow pine, 4 ins. diam., bears S. $83\frac{1}{4}^{\circ}$ E., 474 lks. dist., marked $\frac{1}{4}$ S 35 B T.A yellow pine, 5 ins. diam., bears S. $88^{\circ}08'$ E., 589 lks. dist., marked $\frac{1}{4}$ S 35 B T.

A property line fence cor., bears W. 45 lks. dist., from which fences extend N., S. and W.

SE. cor. of a rock house, bears N. 6° W., 9.20 chs. dist.N. $0^{\circ}11'$ E., bet. secs. 34 and 35.

Asc. gradual SW. slope.

8.28 Fence cor. bears W. 33 lks. dist., from which fences

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	<p>extend N., S. and W., for about 5 chs., then N.</p>								
19.98	<p>A property line fence cor. bears W. 35 lks. dist., from which fences extend S. and W. End of road right of way.</p>								
20.10	<p>Bend in road, bears S. and W. Enter mountainous land, bears W. and SE.; asc. 74 ft. over SW. slope.</p>								
30.00	<p>Base of steep ascent, bears W. and SE.; enter scattering timber, bears SW. and SE.; asc. 181 ft. over S. slope.</p>								
39.41	<p>The cor. of secs. 26, 27, 34 and 35, determined from original bearing trees.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at cor. of secs. 26, 27, 34 and 35, with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T24N</td> <td>R6E</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2">1944</td> </tr> </table> <p>from which</p> </div> <p>Original bearing trees:</p> <p>A yellow pine, 22 ins. diam., bears N.41°E., 88 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 26 B T.</p> <p>A yellow pine, 26 ins. diam., bears S.12½°E., 201 lks. dist., marked T 24 N R 6 E S 35 B T.</p> <p>A yellow pine, 24 ins. diam., bears N.79°W., 92 lks. dist., marked T 24 N R 6 E S 27 B T.</p> <p>New bearing trees:</p> <p>A yellow pine, 7 ins. diam., bears S.51°E., 50 lks. dist., marked T 24 N R 6 E S 35 B T.</p> <p>A yellow pine, 12 ins. diam., bears S.67°W., 67 lks. dist., marked T 24 N R 6 E S 34 B T.</p> <p>Land, S. 60 chs. nearly level; remainder, mountainous. Soil, S. 60 chs. volcanic formation, 2nd rate; remainder, rocky, 3rd rate. Timber, yellow pine, pinon and white pine; undergrowth, 2nd growth timber and mountain mahogany.</p> <hr style="border-top: 1px dashed black;"/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N.89°31'W., bet. secs. 26 and 35.</p> <p>Over rolling land; through heavy timber and scattering undergrowth.</p> <p>Asc. gradual E. slope.</p>	T24N	R6E	S27	S26	S34	S35	1944	
T24N	R6E								
S27	S26								
S34	S35								
1944									
10.00	<p>Slope changes; asc. 69 ft. over SE. slope.</p>								
20.00	<p>Enter mountainous land; asc. 314 ft. over SE. slope.</p>								
40.51	<p>Proportional distance.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor., with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr> <td>¼</td> <td>S 26</td> </tr> <tr> <td></td> <td>S 35</td> </tr> <tr> <td colspan="2">1944</td> </tr> </table> <p>from which</p> </div>	¼	S 26		S 35	1944			
¼	S 26								
	S 35								
1944									

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	A yellow pine, 8 ins. diam., bears N.74°E., 124 lks. dist., marked 1/4 S 26 B T.
	A yellow pine, 20 ins. diam., bears S.78 1/2°E., 142 lks. dist., marked 1/4 S 35 B T.
	Asc. 184 ft. over SE. slope.
58.00	Ridge, bears SE. and N.; continue ascent along S. slope.
61.00	Spur, slopes S.; desc. 165 ft. over SW. slope.
72.48	Drift fence, bears NW. and SE.
74.10	Slope changes; along S. slope.
81.02	The cor. of secs. 26, 27, 34 and 35.
	Land, E. 20 chs. rolling; remainder, mountainous. Soil, rocky, 3rd rate. Timber, pine; undergrowth, 2nd growth pine.

	N.0°15'E., bet. secs. 26 and 27.
	Over mountainous land, through scattering timber and undergrowth.
	Asc. 62 ft. over S. slope.
4.30	Spur, slopes W.; enter heavy timber, bears SW. and SE.; desc. 117 ft. over NW. slope.
8.44	Drift fence, bears NW. and SE.
13.45	Draw, 3 chs. wide, drains W.; asc. 63 ft. over SW. slope.
21.60	Spur, slopes W.; desc. 45 ft. over N. slope.
28.75	Ravine, course N.80°W.; asc. 254 ft. over SW. slope of Howard Mountain.
39.12	The 1/4 sec. cor. determined from original bearing tree. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at 1/4 sec. cor., with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\ \text{S}27 \mid \text{S}26 \\ \hline .1944 \end{array}$
	from which
	Original bearing tree:
	A yellow pine, 30 ins. diam., bears S.88 1/2°E., 37 lks. dist., marked 1/4 S B T., additionally mark on overgrowth 1/4 S 26 B T.
	New bearing tree:
	A pinon, 14 ins. diam., bears N.54 1/4°W., 113 lks. dist., marked 1/4 S 27 B T.
	N.1°14'E., bet. secs. 26 and 27.
	Asc. 102 ft. over SW. slope of Howard Mountain.
9.30	Top of ascent, bears E. and W.; desc. 368 ft. over NW. slope of Howard Mountain.
40.17	The cor. of secs. 22, 23, 26 and 27, as evidenced by a

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

lava stone 16x8x8 ins., firmly set in the ground, marked 2 grooves on S. and 2 grooves on E. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground; with the original cor. stone buried alongside, at cor. of secs. 22, 23, 26 and 27, with brass cap marked

T24N R6E
 S22 | S23

 S27 | S26
 1944

from which

Original bearing trees:

A fir, 30 ins. diam., bears N.18°E., 25 lks. dist., markings overgrown, not uncovered; mark on overgrowth, T 24 N R 6 E S 23 B T.

A fir, 26 ins. diam., bears S.4½°E., 81 lks. dist., markings overgrown, not uncovered, mark on overgrowth, T 24 N R 6 E S 26 B T.

yellow
 A/pine, 12 ins. diam., bears S.89°W., 26 lks. dist., markings overgrown, not uncovered; mark on overgrowth, T 24 N R 6 E S 27 B T.

New bearing trees:

A fir, 8 ins. diam., bears S.31°E., 90 lks. dist., marked T 24 N R 6 E S 26 B T.

A white pine, 10 ins. diam., bears N.58°W., 104 lks. dist., marked T 24 N R 6 E S 22 B T.

Land, mountainous.
 Soil, rocky, 3rd rate.
 Timber, yellow pine, white pine, pinon and fir; undergrowth, 2nd growth timber.

 From the cor. of secs. 23, 24, 25 and 26.

S.89°52'W., bet. secs. 23 and 26.

Over mountainous land, through heavy timber and scattering undergrowth.

Desc. 109 ft. over SW. slope.

5.50 Ravine, course S.5°E.; asc. 159 ft. over SE. slope.

5.65 Graded road, bears N. and S.5°E.

25.70 Top of ridge, bears NE. and SW., along N. slope of Howard Mountain.

31.10 Drain, course N.; asc. 102 ft. over NE. slope.

40.05 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor. with brass cap marked

¼ S 23
 S 26
 1944

from which

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	A yellow pine, 14 ins. diam., bears N.21 $\frac{1}{2}$ °W., 24 lks. dist., marked $\frac{1}{4}$ S 23 B T.
	A yellow pine, 10 ins. diam., bears S.10 $\frac{1}{2}$ °E., 33 lks. dist., marked $\frac{1}{4}$ S 26 B T.
	Asc. 128 ft. along a steep N. slope.
64.20	A side hill drain, course NE.
70.70	Spur, slopes N.; desc. 242 ft. over NW. slope of Howard Mountain.
80.10	The cor. of secs. 22, 23, 26 and 27.
	Land, mountainous. Soil, rocky, 3rd rate. Timber, yellow pine, white pine and fir; undergrowth, 2nd growth pine.

	N.0°15'E., bet. secs. 22 and 23.
	Over mountainous land, through heavy timber and scattering undergrowth.
	Desc. 137 ft. over NW. slope.
12.00	Leave mountainous, enter rolling land, bears NE. and SW. Desc. 145 ft. over rolling NW. slope.
15.70	Fire road, bears N.10°E., and S.10°W.
39.59	The $\frac{1}{4}$ sec. cor. as evidenced by a malpais stone 16x10x8 ins., firmly set in the ground, marked $\frac{1}{4}$ on W. face, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ S22 S23 1944 from which
	Original bearing tree:
	A yellow pine, 26 ins. diam., bears S.29 $\frac{1}{2}$ °W., 73 lks. dist., marked $\frac{1}{4}$ S B T., mark on overgrowth, $\frac{1}{4}$ S 22 B T.
	New bearing tree:
	A yellow pine, 14 ins. diam., bears S.84 $\frac{1}{4}$ °E., 77 lks. dist., marked $\frac{1}{4}$ S 23 B T.
	N.0°15'E., bet. secs. 22 and 23.
	Desc. 154 ft. over rolling NW. slope.
21.80	Graded road, bears E. to Deadmah Cabin and W. to Curley Seep Guard Station.
31.80	Draw, 150 lks. wide, drains NW. from E.; asc. 19 ft. along W. slope.
32.00	Fire road, bears NW. to Howard Seep and E.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains																	
39.74	<p>The cor. of secs. 14, 15, 22 and 23, as evidenced by a lava stone 14x10x10 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high; marked 3 grooves on S. and 2 grooves on E. faces.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, with the original cor. stone buried alongside and in mound of stone to top, at cor. of secs. 14, 15, 22 and 23, with brass cap marked</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T24N R6E</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td>S22</td><td>S23</td></tr> </table> <p>.1944</p> </div> <p style="text-align: right;">from which</p> <p>Original bearing trees:</p> <p>A yellow pine, 22 ins. diam., bears N.56$\frac{3}{4}$°E., 45 lks. dist., marked T 24 N R 6 E S 14 B T.</p> <p>A yellow pine, 20 ins. diam., bears S.30$\frac{1}{4}$°E., 76 lks. dist., marked S 23 B T, other markings overgrown, not uncovered, mark on overgrowth T 24 N R 6 E S 23 B T.</p> <p>A yellow pine, 22 ins. diam., bears S.6°W., 91 lks. dist., marked T 24 N R 6 E S 22 B T.</p> <p>New bearing tree:</p> <p>A yellow pine, 5 ins. diam., bears N.63$\frac{3}{4}$°W., 63 lks. dist., marked T 24 N R 6 E S 15 B T.</p> <p>Land, S. 13 chs. mountainous, remainder rolling. Soil, rocky, volcanic formation, 3rd rate. Timber, yellow pine, pinon and fir; undergrowth, 2nd growth timber.</p> <hr style="border-top: 1px dashed black;"/> <p>From the cor. of secs. 13, 14, 23 and 24. S.88°35'W., bet. secs. 14 and 23. Over mountainous land, through heavy timber and scattering undergrowth. Asc. 40 ft. over NE. slope.</p> <p>5.00 Top of ridge, bears N. and S.; a saddle in ridge, bears N. about 7 chs. dist. Continue ascent of 23 ft. across the head of a ravine, course N.</p> <p>9.50 Spur, slopes NW.; desc. 52 ft. along S. slope.</p> <p>17.10 Top of same spur, slopes southwesterly, thence along top of same.</p> <p>21.40 Leave spur, slopes NW.; desc. 112 ft. over SW. slope.</p> <p>38.29 Proportional distance</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>$\frac{1}{4}$</td><td>S 14</td></tr> <tr><td></td><td>S 23</td></tr> <tr><td></td><td><hr style="width: 50%; margin: 0 auto;"/></td></tr> <tr><td></td><td>1944</td></tr> </table> </div>	T24N R6E		S15	S14	<hr style="width: 50%; margin: 0 auto;"/>		S22	S23	$\frac{1}{4}$	S 14		S 23		<hr style="width: 50%; margin: 0 auto;"/>		1944
T24N R6E																	
S15	S14																
<hr style="width: 50%; margin: 0 auto;"/>																	
S22	S23																
$\frac{1}{4}$	S 14																
	S 23																
	<hr style="width: 50%; margin: 0 auto;"/>																
	1944																

BOOK 4355

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	<p style="text-align: right;">from which</p> <p>A yellow pine, 6 ins. diam., bears N.12½°E., 24 lks. dist., marked ¼ S 14 B T.</p> <p>A yellow pine, 8 ins. diam., bears S.23°W., 12 lks. dist., marked ¼ S 23 B T.</p> <p>Over rolling land; desc. gradual W. slope.</p> <p>40.20 A graded road bears SW. and NE.</p> <p>76.58 The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, E ½ mountainous, W. ½ rolling. Soil, rocky, 3rd rate. Timber, yellow pine, pinon and fir; undergrowth, 2nd growth pine.</p> <p>-----</p> <p>N.0°04'E., bet. secs. 14 and 15.</p> <p>Over rolling land, through heavy timber and scattering undergrowth.</p> <p>Along a gentle W. slope.</p> <p>39.87 The ¼ sec. cor. as evidenced by a lava stone 16x12x12 ins. firmly set in the ground, marked ¼ on W. face.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at the ¼ sec. cor. with brass cap marked</p> <div style="text-align: center;"> <p>¼</p> <p>S15 S14</p> <p>1944</p> </div> <p style="text-align: right;">from which</p> <p>Original bearing trees:</p> <p>A yellow pine, 32 ins. diam., bears S.10°E.; 46 lks. dist., markings overgrown, mark on overgrowth, ¼ S 14 B T.</p> <p>A yellow pine stump, 14 ins. diam., bears N.58¼°W., 113 lks. dist., markings have been destroyed.</p> <p>New bearing tree:</p> <p>A yellow pine, 10 ins. diam., bears S.89½°W., 99 lks. dist., marked ¼ S 15 B T.</p> <p>N.2°07'W., bet. secs. 14 and 15.</p> <p>Along a rolling W. slope:</p> <p>39.88 The cor. of secs. 10, 11, 14 and 15, as evidenced by a lava stone 14x12x10 ins., firmly set in the ground, marked 4 grooves on S. and 2 grooves on E. faces, witnessed by a mound of stone, 2 ft. base, 1 ft. high, S. of cor.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 10, 11, 14 and 15, with brass cap marked</p> <div style="text-align: center;"> <p>T24N R6E</p> <p>S10 S11</p> <p>S15 S14</p> <p>1944</p> </div>
--------	---

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

from which

Original bearing trees:

A yellow pine stump, 16 ins. diam., bears S.51½°E., 227 lks. dist., marked T 24 N R 6 E S 14 B T.

A yellow pine, 30 ins. diam., bears S.26°W., 97 lks. dist., marked T 24 N R 6 E S 15 B T.

A yellow pine, 40 ins. diam., bears N.76½°W., 119 lks. dist., marked T 24 N R 6 E S 10 B T.

New bearing trees:

A yellow pine, 7 ins. diam., bears N.30¾°E., 75 lks. dist., marked T 24 N R 6 E S 11 B T.

A yellow pine, 10 ins. diam., bears S.61¼°E., 136 lks. dist., marked T 24 N R 6 E S 14 B T.

This corner is located under a 4 wire drift fence, which bears N.15°E., and S.15°W.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, yellow pine; undergrowth, 2nd growth pine.

From the cor. of secs. 11, 12, 13 and 14.

S.89°43'W., bet. secs. 11 and 14.

Over mountainous land, through heavy timber and scattering undergrowth.

Asc. 27 ft. along a broken N. slope.

2.20 Spur, slopes NW. from S.; desc. 24 ft. over broken N. slope.

9.00 Spur, slopes N.; desc. 117 ft. over NW. slope.

21.00 Enter rolling land, bears SW. and NE.; desc. 40 ft. along N. slope.

39.48 The ¼ sec. cor. as evidenced by a red cinder stone 14x10x8 ins. firmly set in the ground, marked ¼ on N. side.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at ¼ sec. cor. with brass cap marked

¼ $\frac{S 11}{S 14}$
1944

from which

Original bearing trees:

A yellow pine, 22 ins. diam., now dead, bears S.48½°E., 70 lks. dist., marked ¼ S B T.

Original position of a yellow pine, 18 ins. diam., now dead, lying on ground, bears S.71°W., 60 lks. dist., markings not visible.

New bearing trees:

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

A yellow pine, 8 ins. diam., bears N.5½°E., 4 lks. dist., marked ¼ S 11 B T.

A yellow pine, 8 ins. diam., bears S.5½°W., 26 lks. dist., marked ¼ S 14 B T.

N.89°41'W., bet. secs. 11 and 14.

Along gentle N. slope.

19.00 A low ridge, bears NW. and SE., along gentle N. slope.

28.10 Forest Service fire road, bears NE. and SW.

39.95 Cor. of secs. 10, 11, 14 and 15.

Land, E. 21 chs. mountainous, remainder rolling. Soil, rocky, 3rd rate.

Timber, yellow pine, white pine, fir and pinon; undergrowth, 2nd growth pine and fir.

N.1°15'W., bet. secs. 10 and 11:

Over rolling land, through heavy timber and scattering undergrowth.


Along gentle W. slope.

27.30 Begin descent; desc. 103 ft. over N. slope.

38.90 Fire road, bears E. and W:

40.40 The ¼ sec. cor. as evidenced by a lava stone 14x12x6 ins. firmly set in the ground, marked ¼ on W. face, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at ¼ sec. cor. with brass cap marked



from which

Original bearing trees:

A yellow pine, 26 ins. diam., bears S.16°E., 124 lks. dist., marked ¼ S B T., additionally mark on overgrowth, ¼ S 11 B T.

A yellow pine, 26 ins. diam., bears S.71°W., 50 lks. dist., marked ¼ S B T., additionally mark on overgrowth, ¼ S 10 B T.

N.1°22'W., bet. secs. 10 and 11.

Desc. over gradual NW. slope.

6.00 Top of steep descent, bears NE. and SW.; desc. 156 ft. over NW. slope.

25.40 Draw, drains NE.; asc. 24 ft. over SE. slope.

39.63 The cor. of secs. 2, 3, 10 and 11, as evidenced by a lava stone 16x12x8 ins., firmly set in the ground, marked 5 grooves on S. and 2 grooves on E. faces, witnessed by a

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

mound of stone, 2 ft. base, 1 ft. high, N. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 2, 3, 10 and 11, with brass cap marked

$$\begin{array}{r} T24N R6E \\ S3 | S2 \\ \hline S10 | S11 \\ 1944 \end{array}$$

from which

Original bearing trees:

A yellow pine, 30 ins. diam., bears N. $35\frac{3}{4}^{\circ}$ E., 119 lks. dist., marked T 24 N R 6 E, other marks illegible, mark on overgrowth, T 24 N R 6 E S 2 B T.

A yellow pine, 30 ins. diam., bears N. $9\frac{1}{2}^{\circ}$ W., 65 lks. dist., marked 24 N S 3 B T, other marks illegible, mark on overgrowth, T 24 N R 6 E S 3 B T.

New bearing trees:

A yellow pine, 9 ins. diam., bears S. $51\frac{3}{4}^{\circ}$ E., 27 lks. dist., marked T 24 N R 6 E S 11 B T.

A yellow pine, 10 ins. diam., bears S. $34\frac{1}{4}^{\circ}$ W., 83 lks. dist., marked T 24 N R 6 E S 10 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, yellow pine; undergrowth, 2nd growth pine.

From the cor. of secs. 1, 2, 11 and 12.

S. $88^{\circ}13'$ W., bet. secs. 2 and 11.

Over rolling land, through heavy timber and undergrowth.

Along rolling NE. slope.

18.20 Wash, 10 lks. wide, 1 ft. deep, course NE.

29.00 Top of low spur, slopes NE.; continue over rolling NE. slope.

40.00 Low spur, slopes NE.

41.80 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{r} \frac{1}{4} S 2 \\ S 11 \\ 1944 \end{array}$$

from which

A yellow pine, 9 ins. diam., bears N. $4\frac{1}{2}^{\circ}$ W., 96 lks. dist., marked $\frac{1}{4}$ S 2 B T.

A yellow pine, 9 ins. diam., bears S. $74\frac{1}{2}^{\circ}$ W., 44 lks. dist., marked $\frac{1}{4}$ S 11 B T.

Continue over rolling NE. slope.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

- 51.70 Center of an earthen reservoir, bears N. about 5.60 chs. dist.
- 63.30 A 4 strand barbed wire fence, bears N. $8\frac{1}{2}^\circ$ E., and S. $8\frac{1}{2}^\circ$ W.
- 63.80 A rocky wash, 10 lks. wide, 1 ft. deep, course NE.; asc. 107 ft. over an E. slope.
- 79.40 A spur, slopes SE.
- 83.60 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.
 Soil, rocky, 3rd rate.
 Timber, yellow pine and pinon; undergrowth, 2nd growth pine.


 N. $1^\circ 56'$ E., bet. secs. 2 and 3.

Over rolling land, through heavy timber and scattering undergrowth.

Asc. 74 ft. over SE. slope.

- 22.30 Ridge, bears NW, and SE.; continue ascent 16 ft. along E. slope.
- 28.00 Spur, slopes NE.; desc. 109 ft. over NE. slope.
- 37.60 Slope changes; desc. slightly along gentle E. slope.
- 41.62 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked



from which

A yellow pine, 20 ins. diam., bears N. $64\frac{1}{2}^\circ$ E., 111 lks. dist., marked $\frac{1}{4}$ S 2 B T.


A yellow pine, 20 ins. diam., bears N. 83° W., 7 lks. dist., marked $\frac{1}{4}$ S 3 B T.

Along gentle E. slope.

- 55.00 Slope changes; desc. gradually over NE. slope.

- 62.08 Intersect Sixth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing cor. of secs. 2 and 3, with brass cap marked



from which

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

Old bearing trees of the original closing corner:

A yellow pine, 30 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ E., 54 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 2 C C B T.

A yellow pine, 24 ins. diam., bears S. $8\frac{3}{4}^{\circ}$ W., 87 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 3 C C B T.

From the closing cor., the standard $\frac{1}{4}$ sec. cor., S. bdy. of sec. 34, T. 25 N., R. 6 E., bears N. $89^{\circ}37'$ W., 10 chs. dist.

Continue on blank line in sec. 34.

- 0.21 The original closing cor. of secs. 2 and 3, as evidenced by a lava stone, 16x8x6 ins., firmly set in the ground, marked CC on S. face, 2 notches on E. and 4 notches on W. edges, additionally mark this cor. stone W P on top.

From this witness point,

The original bearing trees:

A yellow pine, 30 ins. diam., bears S. $22\frac{1}{2}^{\circ}$ E., 72 lks. dist., markings overgrown, not uncovered.

A yellow pine, 24 ins. diam., bears S. $7\frac{1}{4}^{\circ}$ W., 108 lks. dist., markings overgrown, not uncovered.

Land, rolling.

Soil, rocky, 3rd. rate.

Timber, yellow pine, pinon and juniper; undergrowth, 2nd growth timber.

At midpoint on the N. bdy. of sec. 2

Set an iron post, 3 ft. long; 2 ins. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. of sec. 2, with brass cap marked

$\frac{1}{4}$ S 2
1944

from which

A yellow pine, 6 ins. diam., bears S. 45° E., 70 lks. dist., marked $\frac{1}{4}$ S 2 B T.

A yellow pine, 5 ins. diam., bears S. 25° W., 120 lks. dist., marked $\frac{1}{4}$ S 2 B T.

From this cor., the standard cor. of secs. 34 and 35, T. 25 N., R. 6 E., bears N. $89^{\circ}00'$ W., 10.22 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on S. bdy. of Tp. as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the field notes of the N. bdy. of T. 23 N., R. 6 E., resurveyed under this group.

N. $0^{\circ}27'$ W., bet. secs. 33 and 34.

Over open nearly level land, along center line of County Highway.

- 0.36 A bend in Forest Service telephone line, bears E. 38 lks.; telephone line extends E. and N.
- 0.45 A property fence cor. bears E., 45 lks. dist.; fences extend E. and N.; a fence line bears W. 45 lks. dist.; fence extends N. and S.
- 40.00 The point for the $\frac{1}{4}$ sec. cor., at the intersection of the center line of the County Highway and a line between property fence cors. to the E. and W.
- Set an iron post, 2 ft. long, 1 in. diam., 12 ins. below

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

the surface of the County Highway, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$
S33 | S34
1944

At a point S.45°E., 77 lks. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground at reference point to $\frac{1}{4}$ sec. cor., with brass cap marked

RP
S34
1944

At a point N.45°W., 77 lks. dist., set an iron post, 3 ft. long, 1 in. diam., 34 ins. in the ground, at reference point to $\frac{1}{4}$ sec. cor., with brass cap marked

RP
S33
1944

From $\frac{1}{4}$ sec. cor.

A property fence cor. bears E. 55 lks. dist., from which fences extend S. and E.

A property fence cor. bears W. 55 lks. dist., from which fences extend S. and W.

The SW. cor. of A. L. Tillman's Lodge, bears N.64 $\frac{1}{2}$ °E., 95 lks. dist.

Forest Service telephone line, bears E. 45 lks. dist., a line extends N. and S.

N.0°12'W., bet. secs. 33 and 34.

Along County Highway; desc. gradual N. slope.

2.85 A drain, course W.; asc. 51 ft. over S. slope.

13.90 Leave County Highway, bears S.0°12'E. and NW.

15.00 Enter heavy timber and scattering undergrowth, bears E. and W.

21.80 Unimproved road, bears NE. and SW.

27.20 Fence cor. bears E. 50 lks. dist., from which a drift fence extends S. and NE.

40.09 The cor. of secs. 27, 28, 33 and 34, as evidenced by a lava stone 22x14x10 ins., firmly set in the ground, marked 1 groove on S. and 3 grooves on E. faces

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 27, 28, 33 and 34, with brass cap marked

T24N R6E
S28 | S27
S33 | S34
1944

from which

Original bearing trees:

A yellow pine, 24 ins. diam., now dead, bears N.25 $\frac{1}{2}$ °E., 75 lks. dist., marked T 24 N R 6 E S 27 B T.

A yellow pine, 24 ins. diam., bears S.78 $\frac{3}{4}$ °E., 54 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 34 B T.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	<p>A yellow pine, 30 ins. diam., bears S.41½°W., 205 lks. dist., marked T 24 N R 6 E S 33 B T.</p> <p>Original position of a yellow pine, 28 ins. diam., now dead, lying on the ground, bears N.84°W., 97 lks. dist., marked T 24 N R 6 E S 28 B T.</p> <p>New bearing trees:</p> <p>A yellow pine, 5 ins. diam., bears N.59½°E., 153 lks. dist., marked T 24 N R 6 E S 27 B T.</p> <p>A yellow pine, 5 ins. diam., bears N.41½°W., 112 lks. dist., marked T 24 N R 6 E S 28 B T.</p> <p>Land, S.45 chs. nearly level, remainder rolling. Soil, S.45 chs. 2nd rate, remainder rocky, 3rd rate. Timber, yellow pine; undergrowth, 2nd growth pine.</p> <p>-----</p> <p>From the cor. of secs. 26, 27, 34 and 35. N.88°43'W., bet. secs. 27 and 34.</p> <p>Over mountainous land, through heavy timber and scattering undergrowth.</p> <p>Along S. slope.</p>
15.00	Top of spur, slopes W. from N.80°E.; desc. 10 ft. along top of same.
17.00	Leave spur, slopes N.70°W.; desc. 138 ft. along S. slope.
42.25	The ¼ sec. cor. as evidenced by a yellow pine stump, 34 ins. diam., marked ¼ S on N. face.
	S.89°45'W., bet. secs. 27 and 34.
0.50	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at witness ¼ sec. cor. of secs. 27 and 34, with brass cap marked
	$\frac{1}{4} \frac{S \ 27}{S \ 34} WC$ <p>1944</p> <p style="text-align: right;">from which</p>
	<p>A yellow pine, 24 ins. diam., bears N.62¼°W., 157 lks. dist., marked W C ¼ S 27 B T.</p> <p>A yellow pine, 8 ins. diam., bears S.24¼°E., 122 lks. dist., marked W C ¼ S 34 B T.</p> <p>Enter rolling land, bears NE. and SE.; along S. slope.</p>
23.40	Road, bears N. and S.
28.60	Drift fence, bears NE. and SW.
39.91	The cor. of secs. 27, 28, 33 and 34.
	<p>Land, E. ½ mountainous, W. ½ rolling. Soil, rocky, 2nd rate. Timber, yellow pine; undergrowth 2nd growth pine.</p> <p>-----</p>

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	N.0°15'W., bet. secs. 27 and 28. Over rolling land, through heavy timber and scattering undergrowth. Asc. 63 ft. over S. slope.
11.10	Spur, slopes W.; desc. 55 ft. over N. slope.
18.70	Draw, drains W.; asc. 33 ft. over S. slope.
23.40	A rocky point, on spur, slopes W.; desc. 81 ft. over N. slope.
33.25	Old road, bears E. and W.
33.70	Draw, drains N.60°W.; asc. 7 ft. over SW. slope.
39.66	The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone, 16x12x10 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, marked $\frac{1}{4}$ on W. face. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap marked $\begin{array}{c} \frac{1}{4} \\ S28 S27 \\ \hline 1944 \end{array}$ from which Original bearing tree: A yellow pine, 10 ins. diam., bears S.37°E., 102 lks. dist., marked $\frac{1}{4}$ S B T., mark on overgrowth, $\frac{1}{4}$ S 27 B T. New bearing tree: A yellow pine, 5 ins. diam., bears N.68 $\frac{1}{2}$ °W., 32 lks. dist., marked $\frac{1}{4}$ S 28 B T.
	N.0°33'E., bet. secs. 27 and 28. Asc. 6 ft. over SW. slope.
4.00	Spur, slopes W.; desc. 68 ft. over N. slope.
11.55	Ravine, course S.70°W., for 3 chs. then W.; asc. 86 ft. over SW. slope.
20.40	Top of ascent, bears NE. and W., along W. slope.
28.00	A fire road, bears NE. and SW.
35.77	A 4 strand barbed wire drift fence, bears SE. and NW.
39.23	The cor. of secs. 21, 22, 27 and 28, as evidenced by a lava stone 16x12x10 ins., firmly set in the ground, marked 2 grooves on S. and 3 grooves on E. faces, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of cor. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 21, 22, 27 and 28, with brass cap marked $\begin{array}{c} T24N R6E \\ S21 S22 \\ \hline S28 S27 \\ \hline 1944 \end{array}$

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

from which

Original bearing trees:

A yellow pine, 26 ins. diam., bears N.89 $\frac{1}{4}$ °E., 133 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 22 B T.

A yellow pine stump, 26 ins. diam., bears N.45°W., 68 lks. dist., marked T 24 N R 6 E S 21 B T.

New bearing trees:

A yellow pine, 7 ins. diam., bears S.81 $\frac{3}{4}$ °E., 64 lks. dist., marked T 24 N R 6 E S 27 B T.

A yellow pine, 5 ins. diam., bears S.63 $\frac{1}{4}$ °W., 29 lks. dist., marked T 24 N R 6 E S 28 B T.

A yellow pine, 6 ins. diam., bears N.30 $\frac{1}{4}$ °W., 94 lks. dist., marked T 24 N R 6 E S 21 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, yellow pine; undergrowth, 2nd growth pine.

 From the cor. of secs. 22, 23, 26 and 27.

S.87°19'W., bet. secs. 22 and 27.

Over mountainous land, through heavy timber and scattering undergrowth.

Desc. 109 ft. over NW. slope.

10.00 Leave mountainous land; enter rolling land, bears N. and S.

15.50 Fire road, bears N.80°E. and S.

38.04 Drift fence, bears N. and S.

39.62 The $\frac{1}{4}$ sec. cor. as evidenced by a malpais stone 16x12x8 ins., firmly set in a mound of stone, marked $\frac{1}{4}$ S on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$
 1944

from which

Original bearing trees:

A yellow pine, 15 ins. diam., now dead, bears N.51°W., 23 lks. dist., marked $\frac{1}{4}$ S B T.

A yellow pine stump, 40 ins. diam., bears S.62 $\frac{1}{2}$ °W., 27 lks. dist., marked $\frac{1}{4}$ S B T.

New bearing trees:

A yellow pine, 5 ins. diam., bears N.3 $\frac{1}{2}$ °W., 45 lks. dist., marked $\frac{1}{4}$ S 22 B T.

A yellow pine, 7 ins. diam., bears S.14 $\frac{1}{2}$ °E., 48 lks. dist., marked $\frac{1}{4}$ S 27 B T.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	N.87°04'W., bet. secs. 22 and 27.
	Desc. 61 ft. over gradual W. slope.
43.48	The cor. of secs. 21, 22, 27 and 28.
	Land, E. 10 chs. mountainous, remainder rolling.
	Soil, rocky, 3rd. rate.
	Timber, pine; undergrowth, 2nd growth pine.

	N.0°02'E., bet. secs. 21 and 22.
	Over rolling land, through heavy timber and scattering undergrowth.
	Along gentle W. slope.
23.10	Begin descent; desc. 71 ft. over N. slope.
28.00	Ravine, course W., from S.10°E.; asc. 10 ft. over SW. slope.
33.00	Slope changes; along gentle W. slope.
39.78	The $\frac{1}{4}$ sec. cor. as evidenced by a lava stone 18x14x10 ins. firmly set in the ground, marked $\frac{1}{4}$ on W. face, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S21 S22 1944
	from which
	Original bearing trees:
	A yellow pine, 16 ins. diam., bears S.36 $\frac{1}{2}$ °W., 45 lks. dist., marked $\frac{1}{4}$ S B T., mark on overgrowth $\frac{1}{4}$ S 21 B T.
	Original position of a yellow pine, 22 ins. diam., now dead, lying on ground, bears S.82 $\frac{1}{2}$ °W., 20 lks. dist., marked $\frac{1}{4}$ S B T.
	New bearing tree:
	A yellow pine, 9 ins. diam., bears S.37 $\frac{1}{4}$ °E., 42 lks. dist., marked $\frac{1}{4}$ S 22 B T.
	N.1°05'E., bet. secs. 21 and 22.
	Desc. 63 ft. along a gentle W. slope.
13.10	Top of a rocky bluff, bears NE. and SW.; desc. 96 ft. over NW. slope.
17.50	Base of steep descent, bears NE. and SW., along gentle W. slope.
21.20	Graded road, bears E. to Deadman Cabin and S.80°W., to Curley Seep Guard Station.
38.30	Draw, 2 chs. wide, drains N.80°W.; asc. over gradual SW. slope.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

39.62

The cor. of secs. 15, 16, 21 and 22, as evidenced by a malpais stone 14x12x12 ins., firmly set in a mound of stone, 2 ft. base; marked 3 grooves on S. and E. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 15, 16; 21 and 22, with brass cap marked

T24N R6E
S16|S15

S21|S22

1944

from which

Original bearing trees:

A yellow pine, 28 ins. in diam., partly dead, bears N.28°E., 92 lks. dist., markings overgrown, not uncovered.

A yellow pine, 20 ins. in diam., bears S.9¼°E., 84 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 22 B T.

A yellow pine, 28 ins. diam., bears N.32°W., 186 lks. dist., marked N R 6 E S 16 B T, other markings overgrown, mark on overgrowth T 24 N R 6 E S 16 B T.

New bearing trees:

A yellow pine, 5 ins. diam., bears N.39¾°E., 125 lks. dist., marked T 24 N R 6 E S 15 B T.

A yellow pine, 5 ins. diam., bears S.57¾°W., 24 lks. dist., marked T 24 N R 6 E S 21 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 14, 15, 22 and 23.

N.85°02'W., bet. secs. 15 and 22.

Over rolling land, through dense timber and undergrowth.

Desc. gradual W. slope.

11.45

Old road, in bottom of draw, course NW., bears SE. and NW. to Howard Seep; asc. over NE. slope.

22.10

Spur, slopes NW.

28.70

A 4 strand barbed wire fence, bears N. and S.

37.90

Old road, bears NW. and SE.

39.70

The ¼ sec. cor. determined from old bearing trees,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor. with brass cap marked

¼ S 15
S 22
1944

from which

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

Original bearing trees:

A yellow pine, 18 ins. diam., bears N.8½°E., 68 lks. dist., markings overgrown, mark on overgrowth ¼ S 15 B T.

A yellow pine, 24 ins. diam., bears N.61°E., 55 lks. dist., marked ¼ S B T.

New bearing tree:

A yellow pine, 6 ins. diam., bears S.30¾°W., 118 lks. dist., marked ¼ S 22 B T.

Howard Seep Spring, bears N.59°49'E., 19.45chs. dist. S.85°45'W., bet. secs. 15 and 22.

- 4.30 Old road, bears SW. and NE.
- 35.00 Top of spur, slopes NW.; desc. over gradual SW. slope.
- 43.02 Cor. of secs. 15, 16, 21 and 22.

Land, rolling.
Soil, rocky, 3rd rate.
Timber, pine; undergrowth, 2nd growth pine.


N.0°56'W., bet. secs. 15 and 16.

Over rolling land, through heavy timber and scattering undergrowth.

Along gentle W. slope.

- 17.00 Shallow draw, drains W.; continue along gentle W. slope.
- 36.20 Top of rocky bluff, bears NE. and SW.; desc. 31 ft. over NW. slope.
- 38.30 Base of steep descent, bears NE. and SW.; desc. gradually along a gentle W. slope.
- 39.78 The ¼ sec. cor. as evidenced by a malpais stone 16x10x6 ins., firmly set in a mound of stone, marked ¼ on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with original cor. stone buried alongside, and in a mound of stone to top, at ¼ sec. cor. with brass cap marked



1944

from which

Original bearing tree:

A yellow pine, 36 ins. diam., bears S.82¼°W., 74 lks. dist., markings overgrown, not uncovered.

New bearing trees:

A yellow pine, 6 ins. diam., bears S.54°E., 29 lks. dist., marked ¼ S 15 B T.

A yellow pine, 5 ins. diam., bears S.84°W., 29 lks. dist., marked ¼ S 16 B T.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

N.0°01'W., bet. secs. 15 and 16.

Over gentle W. slope.

13.20 Leave heavy timber and undergrowth; enter open park and nearly level land, bears NE. and SW.

15.70 Junction of roads, bears W. 20 lks. dist.; roads bearing NE., N. and S.10°W.

25.00 Road bears N.5°E. and S.5°W.

29.00 Enter heavy timber and dense undergrowth, bears NE. and SW.; asc. gradually over SE. slope.

39.90 Cor. of secs. 9, 10, 15 and 16, as evidenced by a malpais stone 10x10x6 ins., firmly set in the ground, marked 4 grooves on S. and 3 grooves on E. faces, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 9, 10, 15 and 16, with brass cap marked

T24N R6E
S9|S10
S16|S15

1944

from which

Original bearing trees:

A yellow pine stump, 26 ins. diam., bears N.70°E., 52 lks. dist., marked T 24 N R 6 E S 10 B T.

A yellow pine stump, 24 ins. diam., bears S.61°E., 59 lks. dist., marked T 24 N R 6 E S 15 B T.

New bearing trees:

A yellow pine, 3 ins. diam., bears N.80½°E., 20 lks. dist., marked B T.

A yellow pine, 3 ins. diam., bears S.72°E., 28 lks. dist., marked B T.

A yellow pine, 3 ins. diam., bears S.44½°W., 48 lks. dist., marked B T.

A yellow pine, 6 ins. diam., bears N.84¾°W., 24 lks. dist., marked T 24 N R 6 E S 9 B T.

Land, S. 53 chs. rolling; remainder, nearly level.

Soil, S. ½, 3rd rate; N. ½, 2nd rate.

Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 10, 11, 14 and 15.

N.89°53'W., bet. secs. 10 and 15.

Over rolling land, through heavy timber and scattering undergrowth, along a gentle N. slope.

16.50 A ravine, course NW.

40.86 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

ground to bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S 10
S 15
1944

from which

A yellow pine, 18 ins. diam., bears N. $15\frac{1}{2}^{\circ}$ W., 26 lks. dist., marked $\frac{1}{4}$ S 10 B T.

A yellow pine, 5 ins. diam., bears S. $0\frac{3}{4}^{\circ}$ W., 20 lks. dist., marked $\frac{1}{4}$ S 15 B T.

Along N. slope.

49.40 Forest Service fire road, bears SW. and NE., 3 chs. to a side road which bears E.

74.80 A Forest Service fire road, bears NE. and SW.

81.72 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

N. $0^{\circ}02'$ W., bet. secs. 9 and 10.

Over rolling land, through heavy timber and dense undergrowth; asc. 28 ft. over SE. slope.

12.00 Slope changes; along gentle E. slope.

25.00 Slope changes; asc. 17 ft. over SE. slope. Enter scattering undergrowth, bears NE. and SW.

32.40 Low spur, slopes E.; desc. 23 ft. along gentle E. slope.

39.92 The $\frac{1}{4}$ sec. cor. as evidenced by a malpais stone, 14x14x6 ins., firmly set in the ground, marked $\frac{1}{4}$ on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with the original cor. stone buried alongside and in mound of stone to top, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$
S9 | S10
1944

from which

Original bearing trees:

A yellow pine, 20 ins. diam., bears N. $76\frac{1}{2}^{\circ}$ E., 55 lks. dist., marked $\frac{1}{4}$ S B T., mark on overgrowth, $\frac{1}{4}$ S 10 B T.

A yellow pine, 30 ins. diam., bears S. $54\frac{1}{4}^{\circ}$ E., 54 lks. dist., marked $\frac{1}{4}$ S B T., mark on overgrowth, $\frac{1}{4}$ S 10 B T.

New bearing tree:

A yellow pine, 22 ins. diam., bears N. 57° W., 81 lks. dist., marked $\frac{1}{4}$ S 9 B T.

N. $0^{\circ}01'$ W., bet. secs. 9 and 10.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	Desc. 17 ft. along a gentle E. slope.
6.40	Shallow draw, drains E.; asc. gradually over a gentle E. slope.
14.50	A low spur, slopes N.70°E.; desc. 23 ft. over N. slope.
21.60	Shallow draw, drains E.; asc. 10 ft. over SE. slope.
22.40	Fire road, bears E. and W.
30.00	Slope changes; along a gentle E. slope.
32.00	Leave heavy timber and undergrowth; enter open park, bears SE. and NW.
39.89	The cor. of secs. 3, 4, 9 and 10, as evidenced by a lava stone in place, 14x20 ins., 10 ins. above ground, marked 5 grooves on S. and 3 grooves on E. faces, witnessed by a mound of stone; 2 ft. base, 1 ft. high, W. of cor. Set a brass tablet, 3½ ins. diam., 3 in. stem, in top of original cor. stone, at cor. of secs. 3, 4, 9 and 10, marked
	T24N R6E <u> S4 S3 </u> S9 S10 1944
	from which
	A yellow pine, 6 ins. diam., bears S.80½°W., 281 lks. dist., marked T 24 N R 6 E S 9 B T.
	A yellow pine, 5 ins. diam., bears N.83¼°W., 293 lks. dist., marked T 24 N R 6 E S 4 B T.
	Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, rolling. Soil, rocky, 3rd rate. Timber, pine; undergrowth, 2nd growth pine.

	From the cor. of secs. 2, 3, 10 and 11. N. 89°39'W., bet. secs. 3 and 10. Over gently rolling land, through heavy timber and undergrowth. Along rolling S. slope.
12.00	A wide top ridge, bears N. and S.; desc. gradual W. slope.
27.50	Road, bears N.10°E. and S.10°W.
39.93	The ¼ sec. cor., as evidenced by a lava stone 12x12x10 ins., firmly set in the ground, marked ¼ on N. face. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at the ¼ sec. cor., with brass cap marked
	¼ <u> S 3 </u> S 10 1944

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	from which
	Original bearing tree:
	A yellow pine, 36 ins. diam., bears S.17 $\frac{3}{4}$ °W., 146 lks. dist., marked $\frac{1}{4}$ S., other markings overgrown, mark on overgrowth $\frac{1}{4}$ S 10 B T. This tree not of record.
	New bearing tree:
	A yellow pine, 7 ins. diam., bears N.49 $\frac{3}{4}$ °W., 12 lks. dist., marked $\frac{1}{4}$ S 3 B.T.
	S.89°43'W., bet. secs. 3 and 10.
	Continue over rolling land.
	Desc. gradual NW. slope.
15.00	Draw, 1 ch. wide, drains N.; asc. gradual NE. slope.
27.60	Spur, slopes N.
33.00	Draw, 1 ch. wide, drains N.; asc. gradual E. slope.
39.95	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling. Soil, rocky, 3rd rate. Timber, pine, pinon and juniper; undergrowth, 2nd growth pine.

	N.1°27'E., bet. secs. 3 and 4.
	Over open rolling grassy land, along gentle E. slope.
10.00	Enter scattering timber and undergrowth, bears E. and W.
11.50	Slope changes; desc. 68 ft. over N. slope.
41.46	Proportional distance.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4}$ S4 S3 1944
	from which
	A yellow pine, 14 ins. diam., bears S.56 $\frac{1}{4}$ °E., 169 lks. dist., marked $\frac{1}{4}$ S 3 B T.
	A yellow pine, 3 ins. diam., bears S.18 $\frac{3}{4}$ °W., 51 lks. dist., marked $\frac{1}{4}$ S 4 B T.
	Desc. gradually over N. slope.
45.00	Draw, 4 chs. wide, drains NW.; asc. 10 ft. over SW. slope.
46.80	Enter heavy timber, bears NW. and SE.
59.20	Spur, slopes NW.; desc. gradually along E. slope.
62.12	The closing cor. of secs. 3 and 4, as evidenced by a lava stone 16x8x8 ins., firmly set in the ground, marked 3 notches on E. and W. edges and CC on S. face, witnessed

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

by a mound of stone, 2 ft. base, 1 ft. high, N. of cor., additionally mark this cor. stone W P on top.

62.18

Intersect Sixth Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, at closing cor. of secs. 3 and 4, with brass cap marked

T25N R6E
S33

S4|S3
T24N R6E
C C
1944

from which

A yellow pine, 5 ins. diam., bears S.22½°E., 383 lks. dist., marked T 24 N R 6 E S 3 0 C B T.

A pinon, 12 ins. diam., bears S.24½°W., 255 lks. dist., marked T 24 N R 6 E S 4 C C B T.

From the closing cor., the angle point corner on S. bdy. sec. 33, T. 25 N., R. 6 E., bears S.89°45'W., 10.39 chs. dist.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, yellow pine, pinon and juniper; undergrowth, 2nd growth timber.

At midpoint on the N. bdy. of sec. 3

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor. of sec. 3, with brass cap marked

¼ S 3
1944

from which

A yellow pine, 4 ins. diam., bears S.45½°E., 54 lks. dist., marked ¼ S 3 B.T.

A yellow pine, 14 ins. diam., bears S.20¼°W., 51 lks. dist., marked ¼ S 3 B.T.

From this cor., the standard cor. of secs. 33 and 34, T. 25 N., R. 6 E., bears N.89°34'W., 10.20 chs. dist.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of Tp., as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the field notes of N. bdy. of T. 23 N., R. 6 E., resurveyed under this group.

N.0°05'E., bet. secs. 32 and 33.

Over rolling, open land; asc. gradual SW. slope.

3.90

Road, bears N.70°E. and S.70°W.

13:00

Road, bears NE. and SW.

39.97

The ¼ sec. cor. as evidenced by a lava stone 12x10x8 ins. firmly set in a mound of stone, marked ¼ on W. face

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at ¼ sec. cor., with brass cap marked

¼
S32|S33
1944

raise a mound

1655
Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	<p>of stone, 2½ ft. base, 2 ft. high, W. of cor. North, bet. secs. 32 and 33. Asc. gradual SW. slope.</p> <p>20.00 Enter heavy timber and dense undergrowth, bears SW. and E. 25.00 Top of ascent; desc. gradually along gentle W. slope. 40.00 The cor. of secs. 28, 29, 32 and 33, as evidenced by a lava stone 18x12x10 ins., firmly set in the ground, marked 1 groove on S. and 4 grooves on E. faces, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 28, 29, 32 and 33, with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr><td>T24N</td><td>R6E</td></tr> <tr><td>S29</td><td>S28</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td colspan="2">1944</td></tr> </table> <p>from which</p> </div> <p>Original bearing trees:</p> <p>A yellow pine, 24 ins. diam., now dead, bears S.10¼°E., 113 lks. dist., marked T 24 N R 6 E S 33 B T.</p> <p>A yellow pine, 26 ins. diam., bears N.88¾°W., 144 lks. dist., marked S 29 B T, other markings overgrown, mark on overgrowth, T 24 N R 6 E S 29 B T.</p> <p>A yellow pine, 30 ins. diam., bears N.78½°W., 60 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 29 B T.</p> <p>New bearing trees:</p> <p>A yellow pine, 7 ins. diam., bears N.41¼°E., 180 lks. dist., marked T 24 N R 6 E S 28 B T.</p> <p>A yellow pine, 4 ins. diam., bears S.41°E., 50 lks. dist., marked T 24 N R 6 E S 33 B T.</p> <p>A yellow pine, 5 ins. diam., bears S.65°W., 140 lks. dist., marked T 24 N R 6 E S 32 B T.</p> <p>Land, rolling. Soil, rocky, 2nd rate. Timber, yellow pine; undergrowth, 2nd growth pine.</p> <hr style="border-top: 1px dashed black;"/> <p>From the cor. of secs. 27, 28, 33 and 34. S.89°15'W., bet. secs. 28 and 33.</p> <p>Over rolling land, through heavy timber and scattering undergrowth; along S. slope.</p> <p>11.00 Spur, slopes SW.; desc. 142 ft. over W. slope. 16.40 Graded road, bears N.20°W. to the Grand Canyon and S.20°E. to Flagstaff. 27.40 Bluff bears N. and S.10°E. 28.45 Forest Service telephone line, bears N. and S. 29.00 Old road, bears N. and S. 39.30 Leave heavy timber, enter scattering timber, bears N. and S. 39.92 The ¼ sec. cor., as evidenced by a malpais stone 16x8x8</p>	T24N	R6E	S29	S28	S32	S33	1944	
T24N	R6E								
S29	S28								
S32	S33								
1944									

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

ins., firmly set in the ground, marked $\frac{1}{4}$ on N. face, witnessed by a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$ $\frac{S 28}{S 33}$
1944

from which

Original bearing tree:

A yellow pine, 22 ins. diam., bears S.50 $\frac{1}{4}$ °W., 124 lks. dist., markings overgrown, mark on overgrowth $\frac{1}{4}$ S 33 B T.

New bearing tree:

A yellow pine, 8 ins. diam., bears N.52°W., 34 lks. dist., marked $\frac{1}{4}$ S 28 B T.

An earthen reservoir, bears S.35°45'E., 29.45 chs. dist.

S.89°45'W., bet. secs. 28 and 33.

Along a gentle N. slope.

15.00 Drain, course N.

18.70 Enter undergrowth, bears N. and S.

39.86 The cor. of secs. 28, 29, 32 and 33.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

N.0°11'E., bet. secs. 28 and 29.

Over rolling land, through heavy timber and scattering undergrowth.

Along a gentle W. slope.

4.00 Drain, course W.

19.20 Drain, course NE.; asc. over gradual SE. slope.

29.00 Base of steep ascent; enter mountainous land, bears NE. and W.; asc. 194 ft. over SE. slope.

38.91 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$
S29 | S28
1944

from which

A yellow pine, 6 ins. diam., bears N.87°W., 38 lks. dist., marked $\frac{1}{4}$ S 29 B T.

A yellow pine, 8 ins. diam., bears S.10 $\frac{1}{2}$ °W., 69 lks.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

dist., marked $\frac{1}{4}$ S 28 B T.

Asc. 48 ft. over SE. slope.

46.40 Top of ascent, bears E. and W.; along a steep E. slope.

53.00 Begin descent; desc. 301 ft. over NE. slope.

72.00 Base of steep descent; enter rolling land, bears SE. and W.; desc. 44 ft. over gradual N. slope.

77.82 Cor. of secs. 20, 21, 28 and 29, as evidenced by a lava stone, 18x8x8 ins., firmly set in the ground, marked 2 grooves on S. and 4 grooves on E. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 20, 21, 28 and 29, with brass cap marked

T24N R6E

S20|S21

S29|S28

1944

from which

Original bearing trees:

A yellow pine, 32 ins. diam., partly dead, bears S.47°E., 39 lks. dist., marked T 24 N R 6 E S 28 B T.

A yellow pine, 32 ins. diam., bears S.74 $\frac{1}{4}$ °W., 36 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 29 B T.

A yellow pine stump, 32 ins. diam., bears S.86 $\frac{3}{4}$ °W., 40 lks. dist., marked T 24 N R 6 E S 29 B T.

New bearing trees:

A yellow pine, 6 ins. diam., bears N.22 $\frac{1}{2}$ °E., 107 lks. dist., marked T 24 N R 6 E S 21 B T.

A yellow pine, 30 ins. diam., bears S.61 $\frac{1}{2}$ °E., 88 lks. dist., marked T 24 N R 6 E S 28 B T.

A yellow pine, 5 ins. diam., bears N.54°W., 84 lks. dist., marked T 24 N R 6 E S 20 B T.

Land, S. 29 chs. rolling; remainder mountainous.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 21, 22, 27 and 28

S.89°29'W., bet. secs. 21 and 28.

Over rolling land, through heavy timber and scattering undergrowth.

5.28 Fence, bears N.70°W. and S.70°E.

26.60 Graded road, bears N. to the Grand Canyon and S. to Flagstaff.

32.60 Top of rim rock, 8 ft. high, faces W.

34.10 Wash, course N.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

38.50 Forest Service telephone line, bears N. and S.

39.59 The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone, 18x10x6 ins., firmly set in the ground, marked $\frac{1}{4}$ on N. face, witnessed by a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$ $\frac{S\ 21}{S\ 28}$
1944

from which

Original bearing trees:

A yellow pine, 16 ins. diam., bears N. $19\frac{1}{2}^\circ$ E., 28 lks. dist., marks overgrown, mark on overgrowth, $\frac{1}{4}$ S 21 B T.

A yellow pine, 14 ins. diam., bears S. 83° W., 19 lks. dist., marked $\frac{1}{4}$ S B T, mark on overgrowth, $\frac{1}{4}$ S 28 B T.

Curley Seep Spring, bears N. 52° E., 4.34 chs. dist.

The SE. cor. of Curley Seep Guard Station house, bears N. $17\frac{3}{4}^\circ$ W., 6.95 chs. dist.

S. $87^\circ 58'$ W., bet. secs. 21 and 28.

Continue over rolling land, along a gentle N. slope.

40.24 The cor. of secs. 20, 21, 28 and 29.

Land, rolling.
Soil, rocky, 3rd rate.
Timber, pine; undergrowth, 2nd growth pine.

N. $0^\circ 15'$ E., bet. secs. 20 and 21.

Over rolling land, through heavy timber and dense undergrowth.

Desc. 51 ft. over gradual N. slope.

0.18 Fire road, bears E. and W.

0.30 A 4 strand barbed wire drift fence, and Forest Service telephone line, bears E. and W.

39.94 The $\frac{1}{4}$ sec. cor. as evidenced by a lava stone 16x12x10 ins. firmly set in the ground, marked $\frac{1}{4}$ on W. face, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S20 | S21
1944

from which

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

Original bearing tree:

A yellow pine stump, 26 ins. diam., bears N.11½°E., 64 lks. dist., marked ¼ S B T.

New bearing trees:

A yellow pine, 6 ins. diam., bears S.8½°E., 130 lks. dist., marked ¼ S 21 B T.

A yellow pine, 5 ins. diam., bears S.43¼°W., 124 lks. dist., marked ¼ S 20 B T.

N.0°03'E., bet. secs. 20 and 21.

Desc. over gradual N. slope.

- 2.30 A 4 strand barbed wire fence, bears NW. and SE.
- 2.60 Center of an earthen reservoir, bears N.52½°W., 8.30 chs. dist.
- 4.65 Road, bears NW. and SE.
- 8.00 Earthen reservoir, bears W. about 6 chs: dist.
- 16:70 Bend in a graded road, bears E. to Kendrick Park and NW. to Grand Canyon.
- 39.88 The cor. of secs. 16, 17, 20 and 21, as evidenced by a malpais stone 16x14x8 ins., firmly set in the ground, marked 3 grooves on S. and 4 grooves on E. faces, witnessed by a mound of stone, 2½ ft. base, 10 ins. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone buried alongside, at cor. of secs. 16, 17, 20 and 21, with brass cap marked

T24N R6E	
S17	S16
S20	S21

1944

from which

Original bearing trees:

A yellow pine, 38 ins. diam., bears N.10½°E., 33 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 16 B T.

A yellow pine, 28 ins. diam., bears N.87°W., 57 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 17 B T.

New bearing trees:

A yellow pine, 5 ins. diam., bears S.62°E., 24 lks. dist., marked T 24 N R 6 E S 21 B T.

A yellow pine, 18 ins. diam., bears S.45¼°W., 128 lks. dist., marked T 24 N R 6 E S 20 B T.

Land, rolling.
Soil, rocky, 3rd rate.
Timber, yellow pine; undergrowth, 2nd growth pine.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	From the cor. of secs. 15, 16, 21 and 22.
	S.86°13'W., bet. secs. 16 and 21.
	Over rolling land, through dense timber and undergrowth.
33.00	Leave timber, bears N. and S.
34.50	Old road, bears N. to Dead Horse Reservoir and S. to Curley Seep Guard Station.
39.87	The $\frac{1}{4}$ sec. cor. as evidenced by a lava stone 16x12x10 ins. firmly set in a mound of stone, marked $\frac{1}{4}$ on N. face,
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4} \begin{array}{l} \underline{S 16} \\ S 21 \\ 1944 \end{array}$
	raise a mound
	of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
	N.88°15'W., bet. secs. 16 and 21.
5.00	Enter heavy timber and undergrowth, bears N. and S.
7.70	Old road, bear NW. and SE.
12.50	Recross road, bears NE. and SW.
40.57	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling.
	Soil, rocky, 3rd rate.
	Timber, pine; undergrowth, 2nd growth pine.

	N.0°18'E., bet. secs. 16 and 17.
	Over rolling land, through heavy timber and dense undergrowth.
	Desc. gradually over N. slope.
39.85	The $\frac{1}{4}$ sec. cor. determined from original bearing trees.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap marked
	$\frac{1}{4} \begin{array}{l} S17 S16 \\ 1944 \end{array}$
	from which
	Original bearing trees:
	A yellow pine, 30 ins. diam., now dead, bears N.33 $\frac{1}{4}$ °E., 21 lks. dist., marked $\frac{1}{4}$ S B T.
	A yellow pine, 22 ins. diam., partly dead, bears S.33 $\frac{1}{4}$ °W., 112 lks. dist., markings overgrown, not uncovered.
	New bearing trees:
	A yellow pine, 4 ins. diam., bears S.50°E., 26 lks. dist., marked $\frac{1}{4}$ S 16 B T.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

A yellow pine, 5 ins. diam., bears S.26 $\frac{1}{4}$ °W., 48 lks. dist., marked $\frac{1}{4}$ S 17 B T.

N.1°01'W., bet. secs. 16 and 17.

Desc. gradually over N. slope.

40.05. The cor. of secs. 8, 9, 16 and 17, as evidenced by a malpais stone 16x12x6 ins., firmly set in a mound of stone, marked 4 grooves on S. and E. faces

Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to bedrock, with the original cor. stone buried alongside, and in a mound of stone to top, at cor. of secs. 8, 9, 16 and 17, with brass cap marked

T24N R6E
 $\frac{S8}{S17}$ | $\frac{S9}{S16}$
 1944

from which

Original bearing trees:

A yellow pine, 18 ins. diam., bears N.41°E., 25 lks. dist., marked T 24 N R 6 E S 9 B T.

A yellow pine stump, 20 ins. diam., bears S.54°E., 43 lks. dist., marked N R 6E S 16 B T, other markings have been destroyed.

A yellow pine, 18 ins. diam., bears S.87°W., 23 lks. dist., marked T 24 N R 6 E S 17 B T.

A yellow pine, 18 ins. diam., bears N.29 $\frac{1}{2}$ °W., 44 lks. dist., marked T 24 N R 6 E S 8 B T.

New bearing tree:

A yellow pine, 4 ins. diam., bears S.19 $\frac{1}{4}$ °E., 80 lks. dist., marked T 24 N R 6 E S 16 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

 From the cor. of secs. 9, 10, 15 and 16.

N.89°08'W., bet. secs. 9 and 16.

Over rolling land, through scattering timber and dense undergrowth; along a gentle S. slope.

40.07 The $\frac{1}{4}$ sec. cor., as evidenced by a malpais stone 14x10x8 ins. firmly set in the ground, marked $\frac{1}{4}$ on N. face, witnessed by a mound of stone, 2 ft. base, 10 ins. high, N. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$ $\frac{S9}{S16}$
 1944

from which

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

Original bearing trees:

A yellow pine, 18 ins. diam., bears N.11°E., 62 lks. dist., marked $\frac{1}{4}$ S B T, additionally mark on overgrowth $\frac{1}{4}$ S 9 B T.

A yellow pine, 6 ins. diam., bears S.34 $\frac{1}{4}$ °E., 45 lks. dist., markings overgrown, mark on overgrowth, $\frac{1}{4}$ S 16 B T.

These bearing trees are not of record.

S.87°37'W., bet. secs. 9 and 16.

Along gentle S. slope.

37.20 Draw, drains NW. from S.

40.14 The cor. of secs. 8, 9, 16 and 17.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

N.0°21'W., bet. secs. 8 and 9.

Over rolling land, through heavy timber and scattering undergrowth.

Desc. 11 ft. over N. slope.

8.10 A shallow draw, 1 ch. wide, drains NW. along gentle W. slope.

20.00 Low spur, slopes NW.; desc. 19 ft. over NE. slope.

24.60 Draw, 1.50 chs. wide, drains NW.; asc. 67 ft. over SW. slope.

39.81 The $\frac{1}{4}$ sec. cor. as evidenced by a lava stone 14x10x10 ins. firmly set in the ground, marked $\frac{1}{4}$ on W. face, witnessed by a mound of stone, 2 ft. base, 10 ins. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$
S8 | S9
1944

from which

Original bearing trees:

A yellow pine, 32 ins. diam., bears N.84 $\frac{1}{2}$ °E., 156 lks. dist., markings overgrown, mark on overgrowth, $\frac{1}{4}$ S 9 B T.

A yellow pine, 30 ins. diam., bears S.6°W., 40 lks. dist., markings overgrown, mark on overgrowth, $\frac{1}{4}$ S 8 B T.

N.0°19'W., bet. secs. 8 and 9.

Asc. 26 ft. over SW. slope.

8.20 Slope changes, along rolling W. slope.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

11.00 Enter scattering timber, bears NE. and SW.

30.60 Spur, slopes W.; desc. 62 ft. over N. slope.

39.87 The cor. of secs. 4, 5, 8 and 9, as evidenced by a lava stone 22x10x5 ins., firmly set in a mound of stone, 2 ft. base, marked 5 grooves on S. face and 4 notches on E. edge.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 4, 5, 8 and 9, with brass cap marked

T24N R6E

S5|S4

S8|S9

1944

from which

Original bearing tree:

A yellow pine, 24 ins. diam., bears N. $30\frac{1}{4}^{\circ}$ W., 128 lks. dist., marked T 24 N R 6 E S 5 B T, additionally mark on overgrowth T. 24 N R 6 E S 5 B T.

New bearing trees:

A yellow pine, 3 ins. diam., bears N. 33° E., 155 lks. dist., marked B T.

A yellow pine, 3 ins. diam., bears S. $50\frac{1}{4}^{\circ}$ E., 199 lks. dist., marked B T.

A yellow pine, 3 ins. diam., bears S. $26\frac{1}{2}^{\circ}$ W., 200 lks. dist., marked B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 3, 4, 9 and 10.

S. $89^{\circ}07'$ W., bet. secs. 4 and 9.

Over rolling, open, grassy land; asc. 46 ft. over an E. slope.

2.50 Enter heavy timber and scattering undergrowth, bears S. and NW.

5.00 Slope changes, along rolling N. slope.

36.00 Enter open grassy park, bears NE. and SW.

40.29 Proportional distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$ S 4

S 9

1944

from which

A juniper, 18 ins. diam.; bears N. $88\frac{3}{4}^{\circ}$ E.; 313 lks. dist., marked $\frac{1}{4}$ S 4 B T.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	A pinon, 3 ins. diam., bears S.33½°W., 286 lks. dist., marked ¼ S 9 B T.
	Along a gentle N. slope.
44.40	Enter scattering timber and undergrowth, bears N. and SW.; desc. 34 ft. over W. slope.
54.40	Draw, drains N.; asc. 23 ft. over E. slope.
60.00	Slope changes; along rolling N. slope.
80.58	The cor. of secs. 4, 5, 8 and 9. Land, rolling. Soil, rocky, 3rd rate. Timber, pinon, juniper and pine; undergrowth, 2nd growth timber.
	----- N.0°27'E., bet. secs. 4 and 5. Over rolling land, through scattering timber and undergrowth; desc. 46 ft. over N. slope.
12.00	Slope changes; desc. 48 ft. along gentle W. slope.
39.84	The ¼ sec. cor. as evidenced by a malpais stone 14x10x5 ins., firmly set in the ground, marked ¼ on W. face, witnessed by a mound of stone, 2 ft. base, 10 ins. high, W. of cor. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at ¼ sec. cor., with brass cap marked ¼ S5 S4 1944 from which A yellow pine, 6 ins. diam., bears S.71°E., 104 lks. dist., marked ¼ S 4 B.T. A yellow pine, 4 ins. diam., bears S.29°W., 56 lks. dist., marked ¼ S 5 B T.
	N.0°23'E., bet. secs. 4 and 5. Along gentle W. slope.
9.50	Low spur, slopes NW.; desc. 28 ft. over NE. slope.
21.50	Drain, course E.; asc. over gradual SE. slope.
24.19	Intersect Sixth Standard Parallel North. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, at closing cor. of secs. 4 and 5, with brass cap marked T25N R6E S32 S5 S4 T24N R6E C C 1944 from which Old bearing tree of the original closing corner: A yellow pine, 26 ins. diam., bears S.71½°E., 71 lks. dist., markings overgrown, mark on overgrowth, T 24 N R 6 E S 4 C C B T. New bearing tree: A yellow pine, 32 ins. diam., bears S.85¾°W., 211 lks.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

dist., marked T 24 N R 6 E S 5 C C B T.

From this closing cor., the angle point corner on S. bdy. sec. 32, T. 25 N., R. 6 E., bears N.89°33'W., 9.73 chs. dist.

Continue on blank line in sec. 32.

0.04

The original closing cor. of secs. 4 and 5, as evidenced by a malpais stone 14x10x6 ins., firmly set in the ground, marked 4 notches on E. and 2 notches on W. edges and CC on S. face. Additionally mark this cor. stone W P on S. face and reset 11 ins. in the ground. From this **witness point**.

Original bearing trees:

A yellow pine, 24 ins. diam., bears N.71½°E., 17 lks. dist., marked T 24 N R 6 E CC S 4 & 5 B T.

A yellow pine, 26 ins. diam., bears S.68½°E., 75 lks. dist., markings overgrown, not uncovered.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, yellow pine and juniper; undergrowth, 2nd growth timber.

At midpoint on the N. bdy. of sec. 4

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor. of sec. 4, with brass cap marked

$\frac{1}{4}$ S 4
 1944

from which

A pinon, 7 ins. diam., bears S.75°E., 101 lks. dist., marked ¼ S 4 B T.

A pinon, 6 ins. diam., bears S.47¼°W., 230 lks. dist., marked ¼ S 4 B T.

From this cor., the closing cor. of secs. 32 and 33, T. 25 N., R. 6 E., bears N.89°16'W., 5.47 chs. dist.

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of Tp., as evidenced by an iron post, 2 ins. diam., set, marked and witnessed as described in the field notes of the N. bdy. of T. 23 N., R. 6 E., resurveyed under this group.

N.0°08'W., bet. secs. 31 and 32.

Over rolling land, through heavy timber and scattering undergrowth; along gentle E. slope.

34.20

Shallow draw, 2 chs. wide, drains E.; asc. over gradual S. slope.

36.00

Base of steep ascent; enter mountainous land, bears E. and W.; asc. 23 ft. over S. slope.

39.89

The ¼ sec. cor. as evidenced by a mound of stone, 3 ft. base, 10 ins. high. Find no evidence of marked stone.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at ¼ sec. cor. in center of mound of stone, with brass cap marked

$\frac{1}{4}$
 331 | 332
 1944

from which

Original bearing trees:

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

A yellow pine stump, 22 ins. diam., bears S.73°W.,
31 lks. dist., marked $\frac{1}{4}$ S B T.

A yellow pine stump, 22 ins. diam., bears N.45°W.,
29 lks. dist., marked $\frac{1}{4}$ S B T.

New bearing trees:

A yellow pine, 6 ins. diam., bears S.73°E., 37 lks.
dist., marked $\frac{1}{4}$ S 32 B T.

A yellow pine, 6 ins. diam., bears S.55°W., 49 lks.
dist., marked $\frac{1}{4}$ S 31 B T.

N.3°12'W., bet. secs. 31 and 32.

Asc. 163 ft. over S. slope.

13.20 Spur, slopes S.60°E., from NW.; desc. 224 ft. over NE.
slope.

28.80 Ravine, course E.; asc. 55 ft. over SE. slope.

38.76 The cor. of secs. 29, 30, 31 and 32 as evidenced by a
malpais stone 18x8x8 ins. firmly set in a mound of stone,
marked 1 groove on S. and 5 grooves on E. faces, wit-
nessed by a mound of stone, 2 ft. base, 1 ft. high, W. of
cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, with original cor. stone buried alongside, at cor.
of secs. 29, 30, 31 and 32, with brass cap marked

T24N R6E

S30 | S29

S31 | S32

1944

from which

Original bearing trees:

A yellow pine, 20 ins. diam., bears N.5°E., 78 lks.
dist., marked S 29 B T, other markings overgrown, mark
on overgrowth T 24 N R 6 E S 29 B T.

A yellow pine, 20 ins. diam., bears S.28°E., 54 lks.
dist., markings overgrown, mark on overgrowth T 24 N
R 6 E S 32 B T.

A yellow pine, 20 ins. diam., bears S.71°W., 40 lks.
dist., markings overgrown, mark on overgrowth T 24 N
R 6 E S 31 B T.

A yellow pine, 28 ins. diam., bears N.38°W., 98 lks.
dist., marked S 30 B T, other markings overgrown, mark
on overgrowth T 24 N R 6 E S 30 B T.

Land, S.36 chs. rolling; remainder mountainous.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 28, 29, 32 and 33.

S.89°23'W., bet. secs. 29 and 32.

Over rolling land, through heavy timber and scattering
undergrowth.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
5.30	Draw, drains NW. from S.
40.00	The $\frac{1}{4}$ sec. cor. as evidenced by a malpais stone 16x10x8 ins., firmly set in the ground, marked $\frac{1}{4}$ S on N. face, witnessed by a mound of stone, 2 ft. base, 1 ft. high, N. of cor.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $\frac{S\ 29}{S\ 32}$ 1944
	from which
	Original bearing trees:
	A yellow pine, 18 ins. diam., bears N.30°W., 26 lks. dist., markings overgrown, mark on overgrowth $\frac{1}{4}$ S 29 B T.
	A yellow pine, 18 ins. diam., bears S.77 $\frac{1}{2}$ °W., 12 lks. dist., marked $\frac{1}{4}$ S B T, additionally mark on overgrowth $\frac{1}{4}$ S 32 B T.
	S.89°02'W., bet. secs. 29 and 32.
	Along gentle N. slope.
3.80	Fire road, bears N. and S.
5.00	Enter mountainous land, bears NW. and S.; asc. 159 ft. over NE. slope.
17.50	Spur, slopes SE.; desc. 88 ft. over SW. slope.
29.00	Head of a ravine, course SE.; asc. 155 ft. over SE. slope.
44.18	Cor. of secs. 29, 30, 31 and 32.
	Land, rolling. Soil, rocky, 3rd rate. Timber, pine; undergrowth, 2nd growth pine.
	S.88°51'W., bet. secs. 30 and 31.
	Over mountainous land, through heavy timber and scattering undergrowth.
	Asc. 163 ft. over SE. slope.
8.00	Spur, slopes NE., from S.20°W.; desc. 305 ft. over NW. slope.
10.00	Leave heavy, enter scattering timber, bears NE. and SW.
25.00	Leave mountainous, enter rolling land.
38.65	The $\frac{1}{4}$ sec. cor. as evidenced by a mound of stone, 2 ft. base, 10 ins. high. Find no evidence of marked stone.
	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor. in center of old mound of stone, with brass cap marked

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

$$\frac{1}{4} \frac{S 30}{S 31}$$

1944

from which

Original bearing trees:

A yellow pine, 10 ins. diam., bears N. $51\frac{3}{4}^{\circ}$ E., 35 lks. dist., marked $\frac{1}{4}$ S B T, additionally mark on overgrowth $\frac{1}{4}$ S 30 B T.

A yellow pine, 14 ins. diam., bears S. $81\frac{1}{4}^{\circ}$ W., 41 lks. dist., marked $\frac{1}{4}$ S B T, additionally mark on overgrowth $\frac{1}{4}$ S 31 B T.

N. $87^{\circ}00'$ W., bet. secs. 30 and 31.

Along gentle N. slope.

11.60 Drain, course N.

12.40 Graded road, bears S. 15° E. to Flagstaff and N. 15° W. to Bull Basin.

18.10 Fire road, bears NE. and SW.

38.94 The cor. of secs. 25, 30, 31 and 36, on W. bdy. of Tp.

Land, E. 25 chs. mountainous; remainder, rolling.

Soil, rocky, 3rd rate.

Timber, pine and juniper; undergrowth, 2nd growth pine.

From the cor. of secs. 29, 30, 31 and 32.

N. $4^{\circ}05'$ E., bet. secs. 29 and 30.

Over mountainous land, through heavy timber and scattering undergrowth.

Asc. 59 ft. over SE. slope.

7.00 Spur, slopes NE.; desc. 347 ft. over N. slope.

22.30 Ravine, course NE.; leave mountainous, enter rolling land, bears E. and NW.; desc. 44 ft. along gentle E. slope.

31.00 Slope changes; desc. 29 ft. over NE. slope.

38.30 The $\frac{1}{4}$ sec. cor. as evidenced by a malpais stone 16x10x8 ins. firmly set in the ground, marked $\frac{1}{4}$ on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. with brass cap marked

$$\frac{1}{4} \frac{S 30}{S 29}$$

1944

from which

Original bearing tree:

A yellow pine, 32 ins. diam. bears S. $73\frac{1}{4}^{\circ}$ W., 42 lks. dist., marked $\frac{1}{4}$ S B T, additionally mark on overgrowth $\frac{1}{4}$ S 30 B T.

BOOK 4855

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

New bearing tree:

A yellow pine, 6 ins. diam., bears N.29°E., 10 lks. dist., marked $\frac{1}{4}$ S 29 B T.

N.0°21'E., bet. secs. 29 and 30.

Desc. gradual NE. slope.

8.80 Fire road, bears N.80°E. and W.

10.00 Slope changes; desc. gradually along gentle E. slope.

40.04 The cor. of secs. 19, 20, 29 and 30, as evidenced by a malpais stone 16x10x8 ins., firmly set in the ground, marked 2 grooves on S. and 5 grooves on E. faces, witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at cor. of secs. 19, 20, 29 and 30, with brass cap marked

T24N	R6E
S19	S20
S30	S29

1944

from which

Original bearing trees:

A yellow pine, 30 ins. diam., bears N.15 $\frac{3}{4}$ °E., 79 lks. dist., marked T 24 N R 6 E S 20 B T.

A yellow pine, 28 ins. diam., bears S.32 $\frac{3}{4}$ °E., 25 lks. dist., marked T 24 N R 6 E S 29 B T.

A yellow pine, 20 ins. diam., bears S.47 $\frac{3}{4}$ °W., 27 lks. dist., marked T 24 N R 6 E S 30 B T.

A yellow pine, 18 ins. diam., bears N.23 $\frac{1}{2}$ °W., 120 lks. dist., marked T 24 N R 6 E S 19 B T.

Land, S. 22 chs. mountainous; remainder, rolling.

Soil, rocky, 3rd rate.

Timber, pine, fir and aspen; undergrowth, 2nd growth timber.

From the cor. of secs. 20, 21, 28 and 29.

S.89°57'W., bet. secs. 20 and 29.

Over rolling land, through heavy timber and dense undergrowth; along gentle N. slope.

1.00 Fire road, bears N.80°E. and S.80°W.

1.30 Drift fence and Forest Service telephone line, bears N.80°E. and S.80°W.

39.96 The $\frac{1}{4}$ sec. cor. as evidenced by a malpais stone 18x14x12 ins., set in a mound of stone, marked $\frac{1}{4}$ on N. face,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with the original cor. stone buried alongside and in mound of stone to top, at $\frac{1}{4}$ sec. cor. with brass cap marked

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	$\frac{1}{4} \begin{array}{l} S 20 \\ S 29 \\ 1944 \end{array}$ <p style="text-align: right;">from which</p> <p>Original bearing tree:</p> <p>A yellow pine, 30 ins. diam., bears N.62½°W., 55 lks. dist., marks overgrown, mark on overgrowth $\frac{1}{4}$ S 20 B T.</p> <p>New bearing tree:</p> <p>A yellow pine, 5 ins. diam., bears S.16°E., 34 lks. dist., marked $\frac{1}{4}$ S 29 B T.</p> <p>S.89°02'W., bet. secs. 20 and 29.</p> <p>Along gentle N. slope.</p>
0.35	Forest Service telephone line, bears SE. and N.63°W.
22.40	Fire road, bears N.10°W. and S.10°E.
41.41	The cor. of secs. 19, 20, 29 and 30.
	<p>Land, rolling. Soil, rocky, 3rd rate. Timber, pine; undergrowth, 2nd growth pine.</p> <p>-----</p> <p>S.85°53'W., bet. secs. 19 and 30.</p> <p>Over rolling land, through heavy timber and dense undergrowth; along gentle N. slope.</p>
39.36	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at witness $\frac{1}{4}$ sec. cor. with brass cap marked
	$WC \frac{1}{4} \begin{array}{l} S 19 \\ S 30 \\ 1944 \end{array}$ <p style="text-align: right;">from which</p> <p>A yellow pine, 12 ins. diam., bears N.74½°E., 51 lks. dist., marked W C $\frac{1}{4}$ S 19 B T.</p> <p>A yellow pine, 14 ins. diam., bears S.16¾°W., 31 lks. dist., marked W C $\frac{1}{4}$ S 30 B T.</p>
39.86	The $\frac{1}{4}$ sec. cor. as evidenced by a + marked on top of a ledge of rock, 2 ft. wide, 25 ft. long and 2 ft. high, marked $\frac{1}{4}$ W. of +. Witnessed by a mound of stone, 2 ft. base, 1 ft. high, N. of cor. From this cor.
	<p>Original bearing trees:</p> <p>A yellow pine, 24 ins. diam., bears N.23½°E., 31 lks. dist., markings overgrown, mark on overgrowth $\frac{1}{4}$ S 19 B T.</p> <p>A yellow pine, 18 ins. diam., bears S.89½°E., 40 lks. dist., marked $\frac{1}{4}$ S B T., additionally mark on overgrowth $\frac{1}{4}$ S 30 B T.</p> <p>N.80°56'W., bet. secs. 19 and 30.</p> <p>Along a gentle N. slope.</p>
41.54	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of Tp.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

Land, rolling.
Soil, rocky, 3rd rate.
Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 19, 20, 29 and 30.

N:0°01'E., bet. secs. 19 and 20.


Over rolling land, through heavy timber and scattering undergrowth; along gentle E. slope.

20.90 A 4 strand wire drift fence and Forest Service telephone line, bears S.60°E. and N.60°W.

30.00 A low spur, slopes NE.; along gentle W. slope.

40.01 The $\frac{1}{4}$ sec. cor. as evidenced by a malpais stone 20x12x6 ins., firmly set in the ground, marked $\frac{1}{4}$ on W. face, witnessed by a mound of stone, 2 ft. base, 10 ins. high, W. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with the original cor. stone buried alongside and in a mound of stone to top, at $\frac{1}{4}$ sec. cor. with brass cap marked



from which

Original bearing trees:

A yellow pine, 18 ins. diam., bears N.54 $\frac{3}{4}$ °E., 24 lks. dist., markings overgrown, mark on overgrowth $\frac{1}{4}$ S 20 B T.

A yellow pine, 12 ins. diam., bears S.76 $\frac{3}{4}$ °W., 27 lks. dist., markings overgrown, mark on overgrowth $\frac{1}{4}$ S 19 B T.


N.0°58'E., bet. secs. 19 and 20.

Along gentle W. slope.

22.50 Same low spur, slopes NW.; desc. 81 ft. over rolling N. slope.

39.92 The cor. of secs. 17, 18, 19 and 20, as evidenced by a lava stone 16x8x6 ins., firmly set in a mound of stone, marked 3 grooves on S. and 5 grooves on E. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original cor. stone buried alongside at cor. of secs. 17, 18, 19 and 20, with brass cap marked



from which

Original bearing tree:

A yellow pine stump, 32 ins. diam., bears S.63°W.,

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

101 lks. dist., marked T 24 N R 6 E S 19 B T.

New bearing trees:

A yellow pine, 7 ins. diam., bears N.65 $\frac{3}{4}$ °E., 77 lks. dist., marked T 24 N R 6 E S 17 B T.

A yellow pine, 8 ins. diam., bears S.17 $\frac{1}{2}$ °E., 147 lks. dist., marked T 24 N R 6 E S 20 B T.

A yellow pine, 6 ins. diam., bears S.16°W., 99 lks. dist., marked T 24 N R 6 E S 19 B T.

A yellow pine, 6 ins. diam., bears N.63°W., 145 lks. dist., marked T 24 N R 6 E S 18 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 16, 17, 20 and 21.

N.88°54'W., bet. secs. 17 and 20.

Over rolling land, through heavy timber and dense undergrowth.

Desc. over rolling NW. slope.

12.00 Graded road, bears NW. to Grand Canyon and SE. to Flagstaff.

20.10 Old road, bears NE. and SW.

30.00 A dim road, bears N.42°W., and S.42°E.

30.20 A 4 strand barbed wire fence, bears N.42°W. and S.42°E.

39.91 A $\frac{1}{4}$ sec. cor. as evidenced by a lava stone 12x10x4 ins. firmly set in a small mound of stone, marked $\frac{1}{4}$ on N. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S 17
S 20
1944

from which

Original bearing trees:

A yellow pine, 36 ins. diam., now dead, bears N.27°W., 98 lks. dist., marked $\frac{1}{4}$ S B T.

A yellow pine, 30 ins. diam., now dead, bears S.28 $\frac{1}{2}$ °W., 238 lks. dist., marked $\frac{1}{4}$ S B T.

New bearing trees:

A yellow pine, 6 ins. diam., bears N.35 $\frac{1}{2}$ °E., 59 lks. dist., marked $\frac{1}{4}$ S 17 B T.

A yellow pine, 6 ins. diam., bears S.34°W., 53 lks. dist., marked $\frac{1}{4}$ S 20 B T.

S.88°12'W., bet. secs. 17 and 20.

Desc. over gradual W. slope.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
18.00	A draw, near head, drains N.; along a rolling N. slope.
34.60	Slope changes, desc. gradually over W. slope.
40.94	The cor. of secs. 17, 18, 19 and 20.
	Land, rolling. Soil, rocky, 3rd rate. Timber, pine; undergrowth, 2nd growth pine.
	S.85°45'W., bet. secs. 18 and 19.
	Over rolling land, through heavy timber and dense undergrowth; along rolling N. slope.
15.00	Desc. over gradual NW. slope.
21.50	Draw, 5 chs. wide, course NW.; asc. gradual NE. slope.
27.65	A short rocky spur, slopes N.; desc. over W. slope.
33.70	A small draw, drains N.; asc. gradual E. slope.
39.70	The $\frac{1}{4}$ sec. cor., as evidenced by a lava stone 20x16x6 ins., firmly set in the ground, marked $\frac{1}{4}$ on N. face,
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{l} S 18 \\ S 19 \end{array}$ 1944 from which
	Original bearing trees:
	A yellow pine, 16 ins. diam., bears N.42 $\frac{1}{2}$ °W., 7 lks. dist., markings overgrown, mark on overgrowth $\frac{1}{4}$ S 18 B T.
	A yellow pine, 30 ins. diam., bears S.68 $\frac{1}{2}$ °E., 15 lks. dist., markings overgrown, mark on overgrowth $\frac{1}{4}$ S 19 B T
	N.80°46'W., bet. secs. 18 and 19.
	Asc. gradual E. slope.
10.00	Spur, slopes N.; desc. gradual W. slope.
41.36	The cor. of secs. 13, 18, 19 and 24, on W. bdy. of Tp.
	Land, rolling. Soil, rocky, 3rd rate. Timber, pine; undergrowth, 2nd growth pine.
	From the cor. of secs. 17, 18, 19 and 20.
	N.0°02'E., bet. secs. 17 and 18.
	Over rolling land, through scattering timber and undergrowth; desc. over gradual N. slope.
39.95	The $\frac{1}{4}$ sec. cor. as evidenced by a lava stone 14x12x6 ins. firmly set in the ground, marked $\frac{1}{4}$ on W. face.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S18 | S17 \\ 1944 \end{array}$$

from which

Original bearing tree:

A yellow pine, 36 ins. diam., bears N.62 $\frac{1}{2}$ °W., 302 lks. dist., marked $\frac{1}{4}$ S B T.

New bearing trees:

A yellow pine, 7 ins. diam., bears N.15°E., 294 lks. dist., marked $\frac{1}{4}$ S 17 B T.

A yellow pine, 8 ins. diam., bears N.5°W., 181 lks. dist., marked $\frac{1}{4}$ S 18 B T.

N:0°17'W., bet. secs. 17 and 18.

Desc. gradually over NE. slope.

1.20 Draw, 2 chs. wide, drains N.50°W.; asc. over gradual S. slope.

18.45 A 4 strand barbed wire drift fence, bears NW. and SE.

28.50 Top of ascent, bears E. and NW.

39.98 The cor. of secs. 7, 8, 17 and 18, as evidenced by a lava stone 18x16x5 ins., firmly set in a mound of stone, marked 4 grooves on S. and 5 grooves on E. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with the old cor. stone buried alongside, and in a mound of stone to top, at cor. of secs. 7, 8, 17 and 18, with brass cap marked

$$\begin{array}{c} T24N R6E \\ S7 | S8 \\ \hline S18 | S17 \\ 1944 \end{array}$$

from which

A yellow pine, 3 ins. diam., bears N.57 $\frac{1}{4}$ °E., 82 lks. dist., marked B T.

A yellow pine, 4 ins. diam., bears S.56 $\frac{1}{4}$ °E., 22 lks. dist., marked T 24 N R 6 E S 17 B T.

A yellow pine, 6 ins. diam., bears S.32°W., 41 lks. dist., marked T 24 N R 6 E S 18 B T.

A yellow pine, 6 ins. diam., bears N.24 $\frac{1}{2}$ °W., 177 lks. dist., marked T 24 N R 6 E S 7 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	From the cor. of secs. 8, 9, 16 and 17. S.89°48'W., bet. secs. 8 and 17. Over rolling land, through scattering timber and dense undergrowth; along a gentle S. slope.
30.00	Center of open park, 5 chs. wide, extends N. and S.
40.03	The $\frac{1}{4}$ sec. cor. determined from original bearing trees Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4} \begin{array}{r} S 8 \\ S 17 \\ 1944 \end{array}$ from which Original bearing tree: A yellow pine, 12 ins. diam., bears S.21°W., 13 lks. dist., marked $\frac{1}{4}$ S B T. New bearing trees: A yellow pine, 20 ins. diam., bears N.39°W., 36 lks. dist., marked $\frac{1}{4}$ S 8 B T. A yellow pine, 10 ins. diam., bears S.52 $\frac{1}{2}$ °W., 31 lks. dist., marked $\frac{1}{4}$ S 17 B T. S.89°26'W., bet. secs. 8 and 17. Along a gentle S. slope:
10.00	Enter open park, bears NW. and SE.
33.70	Graded road, bears NW. to Grand Canyon and SE. to Flagstaff.
40.51	The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, rocky, 3rd rate. Timber, pine; undergrowth, 2nd growth pine.
	N.89°34'W., bet. secs. 7 and 18. Over rolling land, through scattering undergrowth.
19.20	Drift fence, bears NW. and SE.
39.96	Original $\frac{1}{4}$ sec. cor., a lava stone 16x8x3 ins., firmly set in the ground, marked $\frac{1}{4}$ on N. face, witnessed by a mound of stone, 2 ft. base, 1 ft. high, N. of cor. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4} \begin{array}{r} S 7 \\ S 18 \\ 1944 \end{array}$ from which

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	A yellow pine, 6 ins. diam., bears N.43 $\frac{1}{4}$ °E., 15 lks. dist., marked $\frac{1}{4}$ S 7 B T.
	A yellow pine, 6 ins. diam., bears S.7 $\frac{3}{4}$ °E., 11 lks. dist., marked $\frac{1}{4}$ S 18 B T.
	N.85°20'W., bet. secs. 7 and 18.
16.80	Drain, course N.
40.18	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of Tp. Land, rolling. Soil, rocky, 3rd rate. Timber, pine; undergrowth, 2nd growth pine. -----
	From the cor. of secs. 7, 8, 17 and 18.
	N.0°27'W., bet. secs. 7 and 8.
	Over rolling land, through scattering timber and undergrowth; desc. over gradual N. slope.
5.00	Leave scattering timber, enter open park, bears E. and W.
8.50	Graded road, bears NW. to Grand Canyon and SE. to Flagstaff.
39.95	The $\frac{1}{4}$ sec. cor. as evidenced by a malpais stone 16x10x3 ins., firmly set in the ground, marked $\frac{1}{4}$ on W. face, witnessed by a mound of stone, 2 ft. base, 10 ins. high, W. of cor. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at $\frac{1}{4}$ sec. cor. with brass cap marked <div style="text-align: center;"> $\frac{1}{4}$ S7 S8 1944 </div> rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N.0°27'E., bet. secs. 7 and 8.
	Desc. gradually along gentle E. slope.
20.00	Enter scattering timber, bears NW. and SE.
32.00	Enter heavy timber and scattering undergrowth, bears SE. and NW.
39.91	The cor. of secs. 5, 6, 7 and 8, as evidenced by a lava stone 18x16x5 ins., firmly set in the ground, marked 5 grooves on S. and E. faces, witnessed by a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, with the original cor. stone buried alongside and in a mound of stone to top, at cor. of secs. 5, 6, 7 and 8, with brass cap marked <div style="text-align: center;"> T24N R6E S6 S5 S7 S8 1944 </div> from which

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

Original bearing trees:

A yellow pine, 20 ins. diam., now dead, bears N.9°E., 75 lks. dist. marked T 24 N R 6 E S 5 B T.

A yellow pine, 26 ins. diam.; bears S.43 $\frac{3}{4}$ °E., 31 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 8 B T.

A yellow pine, 24 ins. diam., bears S.80°W., 42 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 7 B T.

A yellow pine, 16 ins. diam., bears N.36°W., 94 lks. dist., markings overgrown, mark on overgrowth T 24 N R 6 E S 6 B T.

New bearing tree:

A yellow pine, 32 ins. diam., bears N.45°E., 85 lks. dist., marked T 24 N R 6 E S 5 B T.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine; undergrowth, 2nd growth pine.

From the cor. of secs. 4, 5, 8 and 9.

N.89°59'W., bet. secs. 5 and 8.

Over rolling land, through scattering timber and undergrowth.

Desc. gradually along N. slope.

5.00 Slope changes; desc. 82 ft. over NW. slope.

22.20 Draw, 1 ch. wide, drains N.; asc. 28 ft. over SE. slope.

39.91 The $\frac{1}{4}$ sec. cor. as evidenced by a malpais stone 12x8x10 ins., firmly set in the ground, marked $\frac{1}{4}$ on N. face, witnessed by a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with the original cor. stone buried alongside, and in a mound of stone to top, at $\frac{1}{4}$ sec. cor. with brass cap marked

$$\frac{1}{4} \begin{array}{r} S 5 \\ S 8 \\ 1944 \end{array}$$

from which

Original bearing trees:

Original position of a yellow pine, 16 ins. diam., now dead, lying on the ground, bears N.41 $\frac{1}{4}$ °E., 38 lks. dist., marked $\frac{1}{4}$ S B T.

A yellow pine, 12 ins. diam., bears S.6 $\frac{3}{4}$ °W., 65 lks. dist., markings overgrown, mark on overgrowth $\frac{1}{4}$ S 8 B T.

New bearing tree:

A yellow pine, 12 ins. diam., bears N.42 $\frac{3}{4}$ °W., 86 lks. dist., marked $\frac{1}{4}$ S 5 B T.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
	S.89°37'W., bet. secs. 5 and 8 Along gentle N. slope.
10.00	Enter open park, bears SE. and N.
27.50	Enter heavy timber and scattering undergrowth, bears SE. and NW.; slope changes, desc. 42 ft. over W. slope.
37.70	Draw, 1.50 chs. wide, course N.20°W.; asc. 40 ft. over E. slope.
39.96	The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, rocky, 3rd rate. Timber, pine, pinon and juniper; undergrowth; 2nd growth timber.
	----- N.88°37'W., bet. secs. 6 and 7. Over rolling land, through heavy timber and scattering undergrowth; desc. gradually over E. slope.
1.30	Slope changes, along gentle N. slope.
2.50	Enter scattering timber, bears S. and NW.
17.40	Enter open park, bears NE. and SW.
25.40	Trail, bears NE. and SW. to Slate Lake.
34.50	Enter scattering timber, bears N. and S.
40.03	The $\frac{1}{4}$ sec. cor. as evidenced by a lava stone 18x10x5 ins. firmly set in the ground, marked $\frac{1}{4}$ on N. face, witnessed by a mound of stone, 2 ft. base, 1 ft. high, N. of cor. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original cor. stone buried alongside, at the $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4} \frac{S 6}{S 7}$ 1944 from which
	Original bearing tree: A pinon 16 ins. diam., bears N.37 $\frac{1}{2}$ °E., 35 lks. dist., markings overgrown, mark on overgrowth $\frac{1}{4}$ S 6 B T. This bearing tree not of record.
	New bearing tree: A pinon, 14 ins. diam., bears S.19°E., 218 lks. dist., marked $\frac{1}{4}$ S 7 B T.
	N.85°58'W., bet. secs. 6 and 7. Along gentle N. slope.
4.00	Trail, bears NE. and SW. to Slate Lake.
22.80	Drain, course N.20°E.
24.15	Graded road, bears NW. to Grand Canyon and SE. to Flagstaff.

BOOK 4855

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains	
24.80	Junction of roads, bears N. 50 lks. dist., roads bear NW., SE. and SW.
29.00	Graded road, bears S. 85° W. to Slate Mountain Lookout Station and N. 85° E. to road junction.
39.92	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of Tp. Land, rolling. Soil, rocky, 3rd rate. Timber, pine, pinon and juniper; undergrowth, 2nd growth timber.

	From the cor. of secs. 5, 6, 7 and 8.
	N. 0° 36' W., bet. secs. 5 and 6.
	Over rolling land, through heavy timber and scattering undergrowth; desc. 30 ft. over NE. slope.
10.00	Draw, 2½ chs. wide, drains NW.; leave heavy timber, enter dense undergrowth of 2nd growth pine, bears NW. and SE.; asc. gradually along a gentle W. slope.
39.94	The ¼ sec. cor. as evidenced by a malpais stone 16x10x8 ins., firmly set in the ground, marked ¼ on W. face, witnessed by a mound of stone, 3 ft. base, 1 ft. high, W. of cor.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original cor. stone buried alongside, at ¼ sec. cor., with brass cap marked
	$\frac{1}{4}$ $S6 S5$ 1944
	from which
	A juniper, 3 ins. diam., bears N. 69° E., 50 lks. dist., marked B T.
	A yellow pine, 3 ins. diam., bears N. 14¼° W., 40 lks. dist., marked B T.
	N. 3° 54' W., bet. secs. 5 and 6.
0.90	A low, long spur, slopes NW., along gentle E. slope.
16.50	Slope changes; desc. gradually over N. slope.
24.71	Intersect Sixth Standard Parallel North.
	Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, at closing cor. of secs. 5 and 6, with brass cap marked
	$T25N R6E$ $S31$ $S6 S5$ $T24NR6E$ $C C$ 1944
	raise a mound of stone, 2½ ft. base, 2 ft. high, S. of cor.
	From this closing cor. the angle point corner on S. bdy. sec. 31, T. 25 N., R. 6 E., bears N. 89° 35' W., 8.01 chs.

Resurvey of the Subdivision of T. 24 N., R. 6 E.

Chains

dist.

Continue on blank line in sec. 31,

0.09. The original closing cor. of secs. 5 and 6, as evidenced by a malpais stone 18x10x8 ins., firmly set in the ground, marked CC on S. face, 5 notches on E. and 1 notch on W. edges. Additionally mark this cor. stone WP on S. face.

Land, rolling.

Soil, rocky, 3rd rate.

Timber, pine, pinon and juniper; undergrowth, 2nd growth timber.

At midpoint on the N. bdy. of sec. 5.Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor. of sec. 5, with brass cap marked $\frac{1}{4}$ S 5

1944

raise a mound

of stone, 3 ft. base, 2 ft. high, S. of cor.

Angle point, S. bdy. sec. 31 bears N. 89° 45' W., 8.94 chs. dist.

At a point on the N. bdy. of sec. 6, 37.92 chs. in

departure from the closing cor. of secs. 5 and 6,

determined by proportional measurement,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in

the ground, at $\frac{1}{4}$ sec. cor. of sec. 6, with brass cap marked $\frac{1}{4}$ S 6

1944

from which

A yellow pine, 7 ins. diam., bears S. 37° E., 34 lks. dist., marked $\frac{1}{4}$ S 6 B T.A yellow pine, 12 ins. diam., bears S. 71° 45' W., 200 lks. dist., marked $\frac{1}{4}$ S 6 B T.-----
From this cor., the standard cor. of Ts. 25 N., Rs. 5 and 6 E., bears S. 89° 50' W., 10.45 chs. dist.

Final Test of Solar Attachments.

September 17, 1945, on the meridian established July 7, 1944, with Buff solar transits Nos. 16724 and 16730, at 9h 00m app.t., set off $35^{\circ} 26' 30''$ N. on the lat. arcs; $2^{\circ} 8\frac{3}{4}'$ N. on the decl. arcs and determine a meridian with the solars which agrees with the true meridian.

At app. noon, with the lat. arcs unchanged, I observe the sun on the meridian; the resulting reading of the decl. arcs is $2^{\circ} 05\frac{3}{4}'$ N., which agrees with the computed declination of the sun.

At 3h 0m p.m., app.t., with the lat. arcs unchanged, set off $2^{\circ} 03'$ N. on the decl. arcs and determine a meridian with the solars which agrees with the true meridian.

As all of the solar observations during the usual hours of solar work come within $1' 30''$ of true meridian, conclude that the adjustments of the instruments are satisfactory.

General Description.

T. 24 N., R. 6 E. is located in the Coconino National Forest. The general elevation is about 7500 feet above sea level. The greater part of the three east tiers of sections are mountainous, the mountain peaks ranging in elevation from about 8200 feet to 8775 feet above sea level. In the four west tiers of sections, the land is rolling. Kendrick Park extends into sections 32, 33, 34 and 35. Slate Lake, which is a natural lake, is located in the SW $\frac{1}{4}$ NW $\frac{1}{4}$ and the NW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 7. Howard Seep Spring is located in the SE $\frac{1}{4}$ of sec. 15 and Curley Seep Spring in the SW $\frac{1}{4}$ SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 21. A mountain ridge runs northwesterly and southeasterly through the eastern portion of the township. The general direction of the drainage of the land west of the ridge is northwesterly and east of the ridge, the drainage is in a northeasterly direction.

The soil in the mountainous and rolling part of the township is rocky of 3rd and 4th rate, and in the valleys and a portion of Kendrick Park of 1st and 2nd rate. The only land within the township under cultivation is at A.L. Tillman's ranch which includes the S $\frac{1}{2}$ N $\frac{1}{2}$ of sec. 34. Most of the township is used for the grazing of cattle and sheep. There is a good stand of native grass throughout the township.

There is a good growth of yellow pine timber on the mountainous land and on the rolling land the juniper and pinon timber predominates.

A good graded road from Flagstaff to Grand Canyon enters the township at the corner of secs. 3, 4, 33 and 34 on the S. bdy. of the township and follows the section line bet. secs. 33 and 34 for about 55 chains, then traverses through secs. 33, 28, 21, 20, 17, 8, 7 and 6, leaving the township about 14 chs. south of the $\frac{1}{4}$ sec. cor. of secs. 1 and 6 on the W. bdy. There are numerous fire roads throughout the township.

There were no indications of mineral observed in the township during the progress of the survey.

69

2011, 2012

4-680
(Revised May 1934)

UNITED STATES
DEPARTMENT OF THE INTERIOR
~~GENERAL LAND OFFICE~~
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John Boggs	Truck driver and Prin. Assistant
Okeson Bonnot	Prin. Assistant
Theodore Cole	Prin. Assistant
Edward D. Loughman, Jr.	Flagman
George C. Hopkins	Axeman
Daniel F. X. Meenan	Moundsman
Richard C. Todd	Axeman
Robert A. Ingraham	Axeman
James R. Kennicott	Axeman
John A. Laken	Axeman
Wheeler Oakman, Jr.	Axeman
James F. Patten	Axeman
Henry Whitney	Axeman
Edwin G. Keppler	Axeman
Harry M. McCullough	Axeman
Robert A. Sullivan	Axeman

92)

CERTIFICATE OF SURVEYOR

We, Ty White, Associate Cadastral Engineer and Bert E. Wakeman, Senior Engineering Aid, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 13th day of March, 1942 received from the district cadastral engineer for Arizona, with assignment instructions dated June 26, 1944, we have surveyed the Sixth Standard Parallel North along the S. bdy. of T.25 N., R.6 E. and part of R.5 E. and the E. bdy., W. bdy. and subdivisional lines of T.24 N., R.6 E. of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said resurvey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona, June 8, 1945.
Phoenix, Arizona, Feb. 4, 1946.

Ty White
Associate Cadastral Engineer.
Bert E. Wakeman
Senior Engineering Aid.

CERTIFICATE OF APPROVAL

Chief Cadastral Engineer
OFFICE OF SUPERVISOR OF SURVEYS,
Denver, Colorado

OCT 20 1947

19

re
The foregoing field notes of the survey of the Sixth Standard Parallel North along the S. bdy. of T.25 N., R.6 E. and part of R.5 E. and the E. bdy., W. bdy. and subdivisional lines of T.24 N., R.6 E., G. & S.R. Mer. executed by Ty White, Associate Cadastral Engineer and Bert E. Wakeman, Senior Engineering Aid, under special instructions dated March 13, 1942, and assignment instructions dated June 26, 1944, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

Carl G. Harrington

Supervisor of Surveys

Acting Assistant Chief Cadastral Engineer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in

is a true copy of the original field notes on file in the public survey office.

Supervisor of Surveys.