

Original

UNITED STATES
DEPARTMENT OF THE INTERIOR
~~GENERAL LAND OFFICE~~
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the BOOK 4356

RESURVEY

OF THE

EAST and WEST BOUNDARIES

and the

SUBDIVISION

of

T. 25 N., R. 5 E.

Of the Gila and Salt River Meridian,

In the State of ARIZONA

EXECUTED BY

Ty White, Associate Cadastral Engineer,

Claude F. Warner, Assistant Cadastral Engineer,

Bert E. Wakeman, Senior Engineering Aid

Under special instructions dated March 13, 1942, which provided
for the surveys included under Group No. 239, bearing the approval of the
Commissioner of the General Land Office under date of March 28, 1942

and assignment instructions dated June 26, 1944
June 16, 1945

Survey commenced September 9, 1944

Survey completed November 14, 1945

4356

4356

1A

BOOK 4356

INDEX DIAGRAM.

Township 25 North, Range 5 East

	78		78		63		52		40		28	
15	6	77	5	62	4	51	3	39	2	27	1	7
	76		76		61		50		38		26	
13	7	74	8	60	9	49	10	36	11	25	12	6
	73		73		59		48		36		24	
12	13	72	17	58	16	47	15	34	14	23	13	5
	71		70		57		46		34		22	
11	19	69	20	56	21	45	22	32	23	20	24	3
	68		67		56		44		31		19	
9	30	66	29	54	28	43	27	30	26	18	25	2
	65		64		54		42		29		17	
8	31	63	32	52	33	41	34	28	35	16	36	1

TOWNSHIP 25 NORTH, RANGE 5 EAST

FORM 4358

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

----- Indicates surveys executed by Ty White in 1945

————— Indicates surveys executed by Ty White in 1944

Date of Survey

East Boundary: Sept. 19 to Sept. 21, 1944
West Boundary: October 3 to November 9, 1945
Subdivisions: Sept. 22 to October 22, 1944 and
Sept. 1 to November 14, 1945
North Boundary: Sept. 29 to October 26, 1944 and
November 6 to November 13, 1945

Resurvey of the East Boundary of T.25 N., R.5 E.

BOOK 4356

Chains

Preliminary to the resurvey the lines of the original survey were retraced and diligent search made for all corners. Identified corners are remonumented in their original positions, lost corners are reestablished at proportionate positions based upon the original record, and the true lines blazed through timber. The retracement data are thoroughly verified and only the true line notes are presented herein. For description and test of instruments see field notes of the resurvey of T.24 N., R.5 E.

Reestablishment of the survey executed by F. W. Oury, Deputy Surveyor, in 1894.

For description of the corners on the S. bdy. of T.25 N., R.5 E., see field notes of the resurvey of the 6th. Standard Parallel North, executed under this Group.

From the standard corner of T.25 N., Rs. 5 and 6 E., an iron post, 3 ins. diam., described in field notes of T.24 N., R.6 E. N.0°17'E. bet. secs. 31 and 36.

Over rolling land, through heavy timber and scattered undergrowth.

Desc. 33 ft. along E. slope.

32.00 Shallow draw, 5 chs. wide, drains NE. Asc. 15 ft. over gentle E. slope.

33.65 Dim roadway, bears NE. and SW.

49.81 The $\frac{1}{4}$ sec. cor., evidenced by a mound of stone, 2 ft. base, 1 ft. high.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, at $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 36 \text{ | S } 31 \end{array}$$

1944

from which

Original bearing trees:

A pinon, 9 ins. diam., bears N.79°E. 22 lks. dist., mkd. $\frac{1}{4}$ S B T. Additionally mark, on partial overgrowth, $\frac{1}{4}$ S31 BT

A pinon, 9 ins. diam., bears S.53 $\frac{3}{4}$ °W. 27 lks. dist., mkd. $\frac{1}{4}$ S B T. Additionally mark $\frac{1}{4}$ S36 BT

N.0°06'E., beginning new measurement.

Along gentle E. slope.

32.10 Wash, 5 lks. wide, course NE. Desc. 50 ft. over NE. slope.

39.78 The cor. of secs. 25, 30, 31 and 36, marked by a dilapidated mound of stone, 2 ft. base, 10 ins. high.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

Resurvey of the East Boundary of T.25 N., R.5 E.

Chains

T25N	
R5E R6E	
S 25	S 30
S 36	S 31

1944

from which

Original bearing trees:

A pinon, 7 ins. diam., bears N.71°E. 11 lks. dist.,
mkd. T25N R6E S30 BT

A pinon, 6 ins. diam., bears S.24 $\frac{3}{4}$ °W. 6 lks. dist.,
mkd. T25N R5E S36 BT

A pinon 8 ins. diam., bears N.82 $\frac{1}{2}$ °W. 15 lks. dist.,
mkd. T25N R5E S25 BT

A pinon 6 ins. diam., bears N.13 $\frac{1}{2}$ °W. 47 lks. dist.,
mkd. T25N R5E S25 BT

New bearing tree:

A pinon, 6 ins. diam., bears S.68 $\frac{3}{4}$ °E. 51 lks. dist.,
mkd. T25N R6E S31 BT

Land, gently rolling.
Soil, rocky, 2nd. and 3rd. rate.
Timber, pinon, juniper and yellow pine.
Undergrowth, 2nd. growth timber.

N.0°10'E. bet. secs. 25 and 30.

Over rolling land, through heavy timber and scattered
undergrowth.

- 0.70 Wash, 5 lks. wide, draining from SE. to N.10°E.
- 3.50 Same wash, 5 lks. wide, course NW. Desc. slightly over NW.
slope.
- 15.50 Enter mountainous land, bearing NW. and SE. Asc. 98 ft.
over SW. slope.
- 30.40 Top of ascent; desc 15 ft. over W. slope.
- 35.40 Small drain, course W. Asc. 70 ft. over SW. slope.
- 39.12 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone, 14 x 12 x 6
ins. firmly set, mkd. $\frac{1}{4}$ on W. face.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the
ground, to bedrock, with old corner stone buried alongside,
and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$	
S 25	S 30
1944	

from which

Original bearing trees:

A juniper, 14 ins. diam., bears N.35 $\frac{1}{2}$ °W. 21 lks. dist.
mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S 25 BT

Resurvey of the East Boundary of T.25 N., R.5 E.

BOOK 4656

A juniper, 14 ins. diam., bears S.28 $\frac{1}{2}$ °W. 45 lks. dist.
mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S 25 BT

New bearing tree:

A juniper, 7 ins. diam., bears S.32 $\frac{1}{4}$ °E. 29 lks. dist.,
mkd. $\frac{1}{4}$ S30 BT

N.0°08'W. beginning new measurement.

Asc. 30 ft. over SW. slope.

- 2.50 Spur, slopes W. Desc. 333 ft. over N. slope.
- 19.30 Top of shattered rimrock, 12 ft. high, bearing SE. and NW.
Desc. 215 ft. over NE. slope.
- 31.60 Change of slope to N., Desc. 57 ft.
- 38.14 Four wire fence, bears E. and W.
- 38.17 The cor. of secs. 19, 24, 25 and 30, evidenced by a lava
stone, 16 x 12 x 8 ins., firmly set, marked with 2 notches
on S. and 4 notches on N. edges.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, with old corner stone buried alongside, with brass
cap mkd.

T25N	
R5E	R6E
S 24	S 19
S 25	S 30

1944

from which

Original bearing trees:

A pinon, 12 ins. diam., bears N.6°E. 80 lks. dist.,
mkd. T25N R6E S19 BT

A pinon, 12 ins. diam., bears S.73 $\frac{1}{4}$ °E. 122 lks. dist.,
mkd. T25N R6E S30 BT

A pinon, 12 ins. diam. bears S.82 $\frac{1}{2}$ °W. 18 lks. dist.,
mkd. T25N R5E S25 BT

A juniper, 12 ins. diam., bears N.27 $\frac{1}{4}$ °W. 76 lks. dist.
mkd. T25N R5E S24 BT

Land, slightly rolling, and mountainous.
Soil, rocky, 2nd. and 3rd. rate.
Timber, pinon, juniper and yellow pine.
Undergrowth, 2nd. growth timber, and cliffrose.

N.0°13'E. bet. secs. 19 and 24.

Desc. 33 ft. over N. slope.

- 3.50 Wash, 10 lks. wide, course N.20°E. Over rolling land.
- 9.20 Low spur, slopes E. Desc. 25 ft. over NE. slope.
- 13.70 Wash, 6 lks. wide, course N.80°E. Asc. 45 ft.
- 18.50 Top of ascent, continue over gentle E. slope.

Resurvey of the East Boundary of T.25 N., R.5 E.

Chains	
30.00	Desc. 50 ft. over N. slope.
37.20	Draw, 2 chs. wide, course E. Continue over gentle E. slope.
39.40	The $\frac{1}{4}$ sec. cor., evidenced by a malpais stone, 16 x 10 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W. Set an iron post, 3 ft. long, 1 ins. diam., 28 ins. in the ground, with old corner stone buried alongside, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \text{S } 24 \mid \text{S } 19 \\ 1944 \end{array}$ <p style="text-align: right;">from which</p> Original bearing trees: A pinon, 12 ins. diam., bears N. $58\frac{3}{4}^{\circ}$ E., 157 lks. dist. mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S19 BT A pinon, 14 ins. diam., bears N. $0\frac{3}{4}^{\circ}$ W. 238 lks. dist., mkd. $\frac{1}{4}$ S BT New bearing tree: A juniper, 6 ins. diam., bears S. $16\frac{1}{2}^{\circ}$ W. 223 lks. dist. mkd. $\frac{1}{4}$ S24 BT N. $0^{\circ}09'$ W., beginning new measurement. Asc. 30 ft. over S. slope.
8.90	Spur, slopes E. Desc. 44 ft. over N. slope.
18.75	Wash, 10 lks. wide, course NE. Over gentle E. slope.
31.00	Change of slope to NW., desc. 16 ft.
39.80	The cor. of secs. 13, 18, 19 and 24, evidenced by a lava stone, 22 x 14 x 8 ins., firmly set, mkd. with three notches on the N. and S. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with old corner stone buried alongside, with brass cap mkd. $\begin{array}{c} \text{T25N} \\ \text{R5E } \text{R6E} \\ \text{S } 13 \mid \text{S } 18 \\ \text{S } 24 \mid \text{S } 19 \\ 1944 \end{array}$ <p style="text-align: right;">from which</p> Original bearing trees: A pinon, 8 ins. diam., bears S. 25° E. 53 lks. dist., mkd. T25N R6E S19 BT A juniper, 12 ins. diam., bears S. $36\frac{1}{4}^{\circ}$ E. 59 lks. dist. mkd. T25N R6E S19 BT A juniper, 6 ins. diam., bears S. $23\frac{3}{4}^{\circ}$ W. 233 lks. dist. mkd. T25N R5E S24 BT

Resurvey of the East Boundary of T.25 N., R.5 E.

DOOR 400

Chains

New bearing tree:

A pinon, 6 ins. diam., bears N.54°E. 181 lks. dist.,
mkd. T25N R6E S18 BT

Reconstruct mound of stone, 3 ft. base, 2 ft. high, W. of
corner.

Land, rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, juniper and pinon, and 2nd. growth.

N.0°08'E. bet. secs. 13 and 18.

Over rolling land, through scattered timber and under-
growth.

Desc. 55 ft. over NW. slope.

15.45 Three wire fence, bears N.10°E. and S.10°W., crossing wash,
8 lks. wide, course NE. Asc. very gradually.

20.00 Road, unimproved, bears E. to Cedar Ranch, and W. to
County highway, in sec. 22.

35.60 Enter heavy growth of timber, bearing NE. and W.

39.91 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone, 22 x 10 x 5 ins.
firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a
mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the
ground, to bedrock, with original cor. stone deposited
alongside, and in a mound of stone to top, with brass cap
mkd.

$\frac{1}{4}$
S 13 | S 18
1944

from which

Original bearing trees:

A juniper, 8 ins. diam., bears S.24 $\frac{1}{4}$ °E., 46 lks. dist.
mkd. $\frac{1}{4}$ C BT . Additionally mark $\frac{1}{4}$ S18 BT

A pine, 10 ins. diam., dead and lying on the ground,
bears S.6 $\frac{1}{2}$ °E. 72 lks. dist., mkd. $\frac{1}{4}$ S BT

New bearing tree:

A juniper, 5 ins. diam., bears N.83 $\frac{3}{4}$ °W., 16 lks. dist.
mkd. $\frac{1}{4}$ S13 BT

N.0°13'E., beginning new measurement.

1.80 Old road, bears S.00°E. to Cedar Ranch, and West about
2 chs., thence NW.

4.00 Enter scattered timber, bearing NE. and W.

20.00 Desc. 30 ft. over gradual NE. slope.

26.50 Change to gentle E. slope.

39.78 The cor. of secs. 7, 12, 13 and 18, evidenced by a lava
stone, 12 x 10 x 5 ins. loosely set in the ground, mkd.

Resurvey of the East Boundary of T.25 N., R.5 E.

Chains

with 4 notches on the S. and 2 notches on the N. edges, and witnessed by a mound of stone 2 ft. base, 10 ins. high to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with old corner stone buried alongside, with brass cap mkd.

T25N
R5E R6E
S 12 | S 7
S 13 | S 18

1944

Raise mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Land, rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, pinon, juniper and 2nd. growth.

N.0°04'E., bet. secs. 7 and 12.

Over gently rolling land, through scattered timber.

20.50 Wash, 10 lks. wide, course S.60°E. Asc. slightly.

39.90 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone, 12 x 10 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on W. face, and witnessed by a mound of stone 2 ft. base, 10 ins. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with old corner stone buried alongside, with brass cap mkd.

$\frac{1}{4}$
S 12 | S 7
1944

from which

An original bearing tree:

A juniper, 6 ins. diam., bears S.61 $\frac{3}{4}$ °E., 149 lks., dist., mkd. $\frac{1}{4}$ S BT. Additionally mark $\frac{1}{4}$ S7 BT

New bearing tree:

A juniper, 3 ins. diam., bears N.10 $\frac{1}{2}$ °W., 242 lks., dist., mkd. $\frac{1}{4}$ S12 BT

N.0°04'W., beginning new measurement.

Continue over gently rolling land.

39.87 The cor. of secs. 1, 6, 7 and 12, evidenced by a limestone 20 x 12 x 6 ins., firmly set, mkd. with 5 notches on the S. and 1 notch on the N. edges, and witnessed by a mound of stone, 2 ft. base, 1 ft. high to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to bedrock, with old corner stone alongside, and in a mound of stone to top, with brass cap mkd.

Resurvey of the East Boundary of T.25 N., R.5 E.

L. 1001 4030

Chains

T25N	
R5E	E6E
S 1	S 6
S 12	S 7

1944

from which

Original bearing trees:

A juniper, 12 ins. diam., now dead, bears N.17 $\frac{3}{4}$ °E. 114 lks. dist., mkd. T25N R6E S6 BT

A pinon stump, 18 ins. diam., 3 ft. high, bears S.31°E. 120 lks. dist., mkd. T25N R6E S7 BT

A juniper, 12 ins. diam., bears S.66 $\frac{1}{4}$ °W., 126 lks. dist., mkd. T25N R5E S12 BT

A pinon, 12 ins. diam., bears N.35°W. 92 lks. dist., mkd. T25N R5E S1 BT

New bearing trees:

A pinon, 8 ins. diam.; bears N.15°E. 194 lks. dist., mkd. T25N R6E S6 BT

A pinon, 18 ins. diam., bears S.39°E., 144 lks. dist., mkd. T25N R6E S7 BT

Land, rolling.

Soil, shallow and rocky, 3rd. and 4th. rate.

Timber, juniper and pinon, and 2nd. growth.

N.0°03'E. bet. secs. 1 and 6.

Over gently rolling land, through scattered timber.

1.00 Four wire fence, bears N.25°W. and S.25°E.

25.00 Desc. slightly over NW. slope.

39.98 The $\frac{1}{4}$ sec. cor., evidenced by a limestone, 16 x 12 x 10 ins., firmly set, mkd. $\frac{1}{4}$ on W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground, to bedrock, with old corner stone alongside, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$
S 1 S 6

1944

from which

Original bearing trees, not of record:

A pinon, 16 ins. diam., bears N.38 $\frac{3}{4}$ °E. 57 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S6 BT

A juniper, 8 ins. diam., bears N.27 $\frac{1}{2}$ °W., 24 lks. dist. mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S1 BT

N.0°20'W., beginning new measurement.

Desc. 20 ft. over gentle NW. slope.

Resurvey of the East Boundary of T.25 N., R.5 E.

Chains

14.25 Draw, 50 lks. wide, course NE. Asc. 25 ft. over SE. slope.

39.83 The cor. of Ts.25 and 26 N., Rs. 5 and 6 E., evidenced by the original monument, a limestone, 22 x 14 x 12 ins., firmly set, mkd. with 6 grooves on the N. S. E. and W. faces, and witnessed by a mound of stone 2½ ft. base, 1 ft. high, to the S.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with old corner stone buried alongside, with brass cap mkd.

T26N	
R5E	R6E
S 36	S 31
S 1	S 6

T25N

1944

Raise mound of stone, 3 ft. base, 2 ft. high, S. of corner.

Wire fencing bears N.3°E. and S.3°W. At a point 5 lks. N. of corner, another wire fence extends west.

Land, gently rolling.

Soil, shallow and rocky, 3rd. rate.

Timber, scattered pinon and juniper, and 2nd. growth.

Resurvey of the West Boundary of T.25 N., R.5 E.

Reestablishment of the survey executed by F. W. Oury, Deputy Surveyor, in 1894; and resurveyed by Marvin Caudle, Deputy Surveyor, in 1903, the function of the corners being changed to refer to the sections of T.25 N., R.5 E. only.

From the standard corner of Ts.25 N., Rs. 4 and 5 E., an iron post, 3 ins. diam., described in notes of T.24 N., R.5 E., N.0°04'W. bet. secs. 31 and 36.

Over gently rolling land, through scattered timber.

6.70 Dim roadway, bears NW. and SE.

22.80 Wash, 15 lks. wide, course NW.

24.70 Wash, 15 lks. wide, course W.

47.16 The ¼ sec. cor. of sec. 31, evidenced by the original monument, a lava stone 14 x 14 x 8 ins., firmly set, mkd. ¼ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W. of corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with old corner stone deposited alongside, with brass cap mkd.

Resurvey of the West Boundary of T.25 N., R.5 E.

BOOK 4880

Chains

	<p style="text-align: center;"> $\frac{1}{4}$ S 31 1945 </p> <p style="text-align: right;">from which</p> <p>An original bearing tree:</p> <p>A juniper, 14 ins. diam., bears S. $82\frac{1}{2}^\circ$E. 85 lks. dist. mkd. $\frac{1}{4}$ S BT. Additionally mark this tree $\frac{1}{4}$ S31 BT.</p> <p>New bearing tree:</p> <p>A pinon, 10 ins. diam., bears N. $68\frac{3}{4}^\circ$E. 115 lks. dist., mkd. $\frac{1}{4}$ S31 BT.</p> <p>N. $0^\circ 49'$E., beginning new measurement.</p> <p>Over rolling land, asc. 70 ft.</p> <p>0.50 Enter heavy growth of timber; bears NW. and SE.</p> <p>18.00 Flat spur, slopes W.</p> <p>27.50 Shallow draw, drains SW.</p> <p>34.55 The original monument for the closing cor. of secs. 25 and 36, of R.4 E., bears East 0.05 chs. dist.; a malpais stone, firmly set, 8 x 6 x 2 ins. above ground, marked with 1 notch on S. and 5 notches on N. edges.</p> <p>40.68 The cor. of secs. 30 and 31, evidenced by a malpais stone, 16 x 10 x 5 ins., firmly set, marked with 1 groove on the S. and 5 grooves on the N. edges.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, to bedrock, with original corner stone deposited at base, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T25N</td> <td>T25N</td> </tr> <tr> <td>R 4 E</td> <td>S 30</td> </tr> <tr> <td>S 25</td> <td>S 31</td> </tr> <tr> <td></td> <td>R 5 E</td> </tr> </table> <p>1945</p> <p style="text-align: right;">from which</p> </div> <p>An original bearing tree:</p> <p>A pinon, 16 ins. diam., bears N. 54°E. 221 lks. dist., mkd. T25N R5E S30 BT.</p> <p>New bearing tree:</p> <p>A cedar, 6 ins. diam., bears S. 38°E. 176 lks. dist., mkd. T25N R5E S31 BT.</p> <p>Land, rolling. Soil, gravelly clay and rock, 3rd. and 4th rate. Timber, pinon and juniper. Undergrowth, 2nd. growth pinon, algerita, gamma grass.</p> <hr/> <p>N. $0^\circ 04'$W., along the W. bdy. of sec. 30.</p> <p>Over rolling land, through heavy timber.</p> <p>14.00 Gulch, course W. Asc. 50 ft.</p> <p>26.00 Top of low hill, bearing E. and W. Desc. 35 ft.</p>	T25N	T25N	R 4 E	S 30	S 25	S 31		R 5 E
T25N	T25N								
R 4 E	S 30								
S 25	S 31								
	R 5 E								


Resurvey of the West Boundary of T.25 N., R.5 E.

Chains

39.73

The 1/4 sec. cor. of sec. 30, evidenced by a lava stone, 16 x 14 x 12 ins., firmly set, mkd. 1/4 on the W. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.



1945

from which

An original bearing tree:

A cedar, now dead, 16 ins. diam., bears N.74°E. 51 lks. dist., mkd. 1/4 S BT.

New bearing trees:

A pinon, 8 ins. diam., bears N.80 3/4°E. 125 lks. dist., mkd. 1/4 S30 BT.

A pinon, 12 ins. diam., bears S.31 1/4°E. 154 lks. dist., mkd. 1/4 S30 BT.

N.1° 21' E., beginning new measurement.

10.20 Road, bears NE. and SW., in grassy swale, draining SW.

25.10 Gulch, course SW.


32.30 Road, bears E. and W.

33.80 Barbed wire fencing, bears E. and W.

34.35 The original monument for the closing cor. of secs. 24 and 25, of R.4 E., bears West 3 1/2 lks. dist.; a lava stone, firmly set, 10 x 10 x 5 ins. above ground, marked with 2 grooves on the S. and 4 grooves on the N. faces. An original bearing tree, a pinon, 12 ins. diam., bears S.22° W. 32 lks. dist., mkd. CC T25N R4E S24 BT.

39.73 The cor. of secs. 19 and 30, evidenced by the original monument, a lava stone, 16 x 10 x 8 ins., firmly set, marked with 2 grooves on the S. and 4 grooves on the N. faces, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.



1945

from which

Resurvey of the West Boundary of T.25 N., R.5 E.

BOOK 435

Chains

Original bearing trees:

A pinon, 10 ins. diam., bears N.74°E. 31 lks. dist.,
mkd. T25N R5E S19 BT

A cedar, 12 ins. diam., bears S.29½°E. 34 lks. dist.,
mkd. T25N R5E S30 BT

Land, rolling.

Soil, cindery clay and rocky, 3rd. and 4th. rate.

Timber, pine, pinon and cedar, and 2nd. growth pinon.

N.1°15'E., along the W. bdy. of sec. 19.

Over rolling land, through heavy growth of timber. Asc.
30 ft. over S. slope.

- 5.20 Top of low hill, desc. 60 ft. over N. slope.
- 19.75 Shallow draw, course W.
- 23.00 Earthen tank, or reservoir, bears East about 12.00 chs.
dist.
- 26.70 Old road, bears E. and W.
- 30.00 Asc. 40 ft. over S. slope.
- 36.00 Small spur, slopes W., descend 20 ft.
- 39.69 The ¼ sec. cor. of sec. 19, evidenced by a lava stone,
13 x 10 x 10 ins., firmly set, mkd. ¼ on the W. face, and
witnessed by a mound of stone 2 ft. base, 1 ft. high, to
the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with original corner stone deposited alongside,
with brass cap mkd.

¼
|
S 19
|
1945

from which

A pinon, 10 ins. diam., bears N.40°E. 140 lks. dist.,
mkd. ¼ S19 BT

A pinon, 12 ins. diam., bears S.18½°E. 132 lks. dist.,
mkd. ¼ S19 BT

The original bearing trees are dead and fallen.

N.0°45'E., beginning new measurement.

- 7.00 Desc. 95 ft. over gradual N. slope.
- 22.20 Wash, 5 lks. wide, course NW. Asc. 45 ft.
- 27.70 Spur, slopes W. Desc. slightly.
- 34.73 The original monument for the closing cor. of secs. 13 and
24, of R.4 E., bears West 8½ lks. dist.; a lava stone,
12 x 10 x 5 ins. above ground, firmly set, marked with 3
grooves on the S. and N. faces, and witnessed by a mound
of stone, 2 ft. base, 1 ft. high, to the E.

Resurvey of the West Boundary of T.25 N., R.5 E.

Chains

39.69 The cor. of secs. 18 and 19, evidenced by the original monument, a lava stone, 20 x 18 x 8 ins., firmly set, mkd. with three notches on the N. and S. edges, and witnessed by a mound of stone 2½ ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.

T25N	T25N
R 4 E	S 18
S 13	S 19
	R 5 E

1945

from which

An original bearing tree:

A pinon, 25 ins. diam., bears N.69½°E. 74 lks. dist., mkd. T25N R5E S18 BT

New bearing tree:

A pinon, 10 ins. diam., bears S.50¼°E. 57 lks. dist., mkd. T25N R5E S19 BT

Wire fence, extending N. and S., bears W. 1½ chs. dist.

Land, rolling.

Soil, gravelly clay, and rocky, 3rd. and 4th. rate.

Timber, pinon and juniper, and 2nd. growth.

N.0°26'W., along the W. bdy. of sec. 18.

Over rolling land, through heavy growth of timber.

39.55 The ¼ sec. cor. of sec. 18, evidenced by a lava stone, 16 x 12 x 8 ins., firmly set, mkd. ¼ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original corner stone deposited alongside, with brass cap mkd.

¼	S 18
	1945

from which

An original bearing tree:

A pinon, 14 ins. diam., now dead, bears S.26¾°E. 50 lks. dist., mkd. ¼ S BT

New bearing trees:

A pinon, 4 ins. diam., bears S.38¼°E. 29 lks. dist., mkd. ¼ S 18 BT

A pinon, 16 ins. diam., bears N.42¼°E. 46 lks. dist., mkd. ¼ S 18 BT

N.1°39'E., beginning new measurement.

Along wire fencing.

Resurvey of the West Boundary of T.25 N., R.5 E.

D.O.C. 4238

Chains

- 10.00 Desc. 170 ft. over NE. slope.
- 34.50 Foot of descent, gully, course E.
- 35.48 The closing cor. of secs. 12 and 13, of R.4 E., evidenced by the original monument, a lava stone, firmly set, 12 x 8 x 6 ins. above ground, mkd. with 4 grooves on the S. and 2 grooves on the N. faces, and witnessed as described in the record of subdivision of T.25 N., R.4 E.

From this point wire fencing extends S. and NW.

- 39.70 The cor. of secs. 7 and 18, evidenced by the original monument, a lava stone, 20 x 16 x 12 ins., firmly set, mkd. with 4 grooves on the S. and 2 grooves on the N. face.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

T25N	T25N
R 4 E	S 7
S 12	S 18
	R 5 E

1945

from which

Original bearing trees:

A pinon, 14 ins. diam., bears N.69 $\frac{3}{4}$ °E. 180 lks. dist., marks are not legible. Remark, on overgrowth of old blaze, T25N R5E S7 BT

A juniper, 10 ins. diam., bears S.10°E. 45 lks. dist., mkd. T25N R5E S18 BT

Land, rolling.

Soil, gravelly and rocky clay, 3rd. and 4th. rate.

Timber, pinon and juniper.

Undergrowth, 2nd. growth juniper, algerita and gamma grass.

N.0°56'W., along the W. bdy. of sec. 7.

Over rolling land, through heavy growth of timber.

Desc. 115 ft. over N. slope.

- 7.00 Wire fencing, bears NE. and SW.
- 11.60 Gulch, from SW. drains E. A small earth reservoir bears East, about 2 chs. dist.
- 13.60 Wire fencing, enclosing reservoir, bears SE. and NW.
- 16.00 Wire fence, bears E. and W., extends west for a distance of 70 lks., thence north.
- Asc. 20 ft. over gentle slope.
- 18.80 Point of spur, sloping E.
- 28.96 Southwest corner of Roy Hancock's cabin bears East, 3.10 chs. dist.
- 33.68 Corner of wire fencing, extending N. S. and W., bears west 12 lks. dist.

Resurvey of the West Boundary of T.25 N., R.5 E.

Chains

37.60 Old road, bears E. and W.

39.20 The $\frac{1}{4}$ sec. cor. of sec. 7, evidenced by a lava stone, 12 x 10 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on the E. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$\frac{1}{4}$
 |
 S 7
 1945

from which

An original bearing tree:

A pinon, 14 ins. diam., bears N.73°E. 237 lks. dist., Mark, on overgrowth of old blaze, $\frac{1}{4}$ S7 BT

New bearing tree:

A juniper, 16 ins. diam., bears S.41 $\frac{1}{2}$ °E. 284 lks. dist., mkd. $\frac{1}{4}$ S7 BT

N.0°13'W., beginning new measurement.

Over gently rolling land.

2.30 Graded roadway, bears E. to Flagstaff and W. to Grand Canyon Highway, near cattle guard, at fencing N. and S.

14.60 Corner of fencing, bearing N. W. and S. Continue along wire fence.

34.56 The original monument for the closing cor. of secs. 1 and 12, of R.4 E., evidenced by a dilapidated mound of stone, witnessed as described in the record of subdivision of T.25 N., R.4 E.

40.00 The cor. of secs. 6 and 7, evidenced by the original monument, a lava stone, 14 x 10 x 8 ins., firmly set, mkd. with 5 notches on the S. and 1 notch on the N. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground, to bedrock, with original corner stone deposited alongside, and in a mound of stone to top, with brass cap mkd.

T25N T25N
 R 4 E | S 6
 S 1 | S 7
 | R 5 E
 1945

from which

An original bearing tree:

A juniper, 10 ins. diam., bears S.76 $\frac{3}{4}$ °E. 226 lks. dist., mkd. T25N R5E S7 BT

New bearing tree:

A pinon, 5 ins. diam., bears N.25 $\frac{1}{2}$ °E. 62 lks. dist., mkd. T25N R5E S6 BT

Land, gently rolling. Soil, gravelly and rocky, 3rd.rate.

Resurvey of the West Boundary of T.25 N., R.5 E.

Chains

Timber, pinon, pine and juniper.
Undergrowth, algerita, 2nd. growth pinon and juniper.

N.0°11'W., along the W. bdy. of sec. 6.

Over gently rolling land, through scattered timber; along wire fencing.

39.89 The $\frac{1}{4}$ sec. cor. of sec. 6, evidenced by a lava stone, 18 x 8 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on the W. face.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone buried alongside, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 6 \\ 1945 \end{array}$$

from which

A cedar, 3 ins. diam., bears N.43 $\frac{3}{4}$ °E. 82 lks. dist., mkd. $\frac{1}{4}$ S6 BT

A cedar, 3 ins. diam., bears S.25°E. 184 lks. dist., mkd. BT.

No evidence of original bearing trees remain.

N.0°08'E., beginning new measurement.

20.60 U.S. Forest Service arboricultural plot bears East 1 ch. dist.

36.80 The closing cor. of Ts.25 and 26 N., R.4 E., evidenced by an iron post, 3 in. diam., set, marked and witnessed as described in the record of survey of the East boundary of T.26 N., R.4 E.,

39.92 The cor. of Ts. 25 and 26 N., R.5 E., evidenced by the original monument, a hewed juniper post, 5 ins. in diam., illegibly marked, supported in a mound of stone.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with old corner post deposited alongside, with brass cap mkd.

$$\begin{array}{cc} T26N & T26N \\ R\ 4\ E & | & R\ 5\ E \\ S\ 36 & | & S\ 31 \\ & | & S\ 6 \\ & & T25N \end{array}$$

1945

from which

An original bearing tree:

A juniper, 14 ins. diam., bears N.61 $\frac{1}{4}$ °E. 266 lks. dist., mkd. T26N R5E S31 BT

New bearing tree:

A juniper, 14 ins. diam., bears S.37 $\frac{3}{4}$ °E. 150 lks. dist., mkd. T25N R5E S6 BT

Wire fencing extends East and South from corner.

Resurvey of the West Boundary of T.25 N., R.5 E.

Chains

Land, gently rolling.
Soil, gravelly and rocky clay, 3rd. rate.
Timber, pinon and juniper.
Undergrowth, 2nd. growth pinon and juniper, and gamma grass.

Resurvey of the Subdivision of T.25 N., R.5 E.
Reestablishment of the survey executed by F. W. Oury,
Deputy Surveyor, in 1894.

From the standard cor. of secs. 35 and 36, on S. bdy. of Tp.
described in the field notes of T.24 N., R.5 E.,
N.0°52'W. bet. secs. 35 and 36.

Over rolling land, through scattered timber and dense 2nd.
growth pine.

Desc. slightly over gradual N. slope.

39.00 Old road, bears NE. and SW.

41.20 Drain, course NW.

47.92 Point for $\frac{1}{4}$ sec. cor., evidenced by the remains of the
original monument, a dilapidated mound of stone.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd.

$\frac{1}{4}$
S 35 | S 36
1944

from which

Original bearing trees:

A pine, 28 ins. diam., bears S.27°E. 177 lks. dist.,
mkd. $\frac{1}{4}$ S BT

A pine, 16 ins. diam., bears S.33 $\frac{1}{4}$ °W. 203 lks. dist.,
mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S35 BT

New bearing tree:

A pine, 12 ins. diam., bears S.7 $\frac{1}{4}$ °E. 152 lks. dist.,
mkd. $\frac{1}{4}$ S36 BT

N.0°04'W., beginning new measurement.

Asc. 20 ft.

9.10 Top of ascent, descend slightly along gentle E. slope.

15.00 Head of draw, draining NW. Enter heavy timber, bears NE.
and SW. Continue along gentle W. slope.

18.00 Graded road, bears SE. to Flagstaff and NW. to Grand
Canyon. A cattle guard across road, in fence line bearing
NW. and S.10°E., bears SE. 2.20 chs. dist.

21.75 Wire fencing, bears SE. and N.1 $\frac{1}{2}$ °W.

25.50 Desc. 40 ft. over NW. slope.

26.25 Wire fencing, bears N.5°E. and S.5°W., continuing
irregularly north.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4886

Chains

35.30 Draw, course N.20°E. Asc. 10 ft.

39.92 The cor. of secs. 25, 26, 35 and 36, evidenced by the original monument, a lava stone 16 x 12 x 8 ins., firmly set, mkd. with 1 groove on the S. and 1 groove on the E. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.

T25N	R5E
S 26	S 25
S 35	S 36

1944

from which

Original bearing trees:

A pinon, 8 ins. diam., partly dead, bears N.37°E. 68 lks. dist., mkd. T25N R5E S25 BT

A pinon, 14 ins. diam., bears S.13¼°W. 330 lks. dist., mkd. T25N R5E S35 BT

A pinon, 7 ins. diam., bears S.60¾°W. 185 lks. dist., mkd. T25N R5E S35 BT

New bearing trees:

A pinon, 5 ins. diam., bears N.29°E. 63 lks. dist., mkd. T25N R5E S25 BT

A pinon, 3 ins. diam., bears S.36¾°E. 60 lks. dist., mkd. BT

A pinon, 6 ins. diam., bears N.43°W. 42 lks. dist., mkd. T25N R5E S26 BT

Land, rolling.

Soil, rocky, 3rd. rate.

Timber, pinon, juniper and yellow pine, and 2nd. growth.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.

S.87°14'W. bet. secs. 25 and 36.

Over rolling land, through heavy growth of timber.

1.50 Wash, 5 lks. wide, course NE. Asc. 25 ft. over E. slope.

11.50 Change of slope to NE., ascend 112 ft.

25.00 Change of slope to N., continue ascent 50 ft.

34.50 Top of ascent, bears N. and S. Desc. 40 ft. over N. slope.

40.85 Point for ¼ sec. cor., determined from the old bearing bearing trees.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains	
	$\frac{1}{4} \begin{array}{l} S 25 \\ S 36 \end{array}$
	1944
	from which
	Original bearing trees:
	Pine, 12 ins. diam., bears S.55½°E. 37 lks. dist., mkd. ¼ S BT
	Fir, 20 ins. diam., bears S.35¾°W. 63 lks. dist., marks overgrown; remark on overgrowth, ¼ S36 BT
	New bearing tree:
	A pine, 4 ins. diam., bears N.65¾°W. 63 lks. dist., mkd. ¼ S25 BT
	S.89°49'W. beginning new measurement.
	Desc. 240 ft. over NW. slope.
12.00	Base of descent, and enter rolling land, bears NE. and S. Desc. 15 ft.
16.80	Wash, 6 lks. wide, course N. Asc. 40 ft. over N. slope.
26.70	Low spur, slopes N. Desc. 53 ft. over NW. slope.
37.10	Four wire drift fencing, bears N. and S.5°W.
37.30	Draw, 1 ch. wide, course N. Asc. 20 ft. over E. slope.
39.78	The cor. of secs. 25, 26, 35 and 36.
	Land, rolling and mountainous. Soil, rocky, 2nd. and 3rd. rate. Timber, pinon, juniper, yellow pine and fir; 2nd. growth pinon and juniper.

	N.0°22'E. bet. secs. 25 and 26.
	Over rolling land, through heavy timber.
3.30	Small spur, slopes N.20°E. Desc. 67 ft. over W. slope.
20.50	Change of slope to NW. Desc. 160 ft.
39.32	The ¼ sec. cor., evidenced by a lava stone 10 x 8 x 8 ins. firmly set, mkd. ¼ on the W. face, and witnessed by a mound of stone 3 ft. base, 1 ft. high, to the W.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 26 \\ S 25 \end{array}$
	1944
	from which
	Original bearing trees:
	A pinon, 12 ins. diam., bears N.1°E., 115 lks. dist., mkd. ¼ S BT . Additionally mark ¼ S25 BT

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4856

Chains

A juniper, 14 ins. diam., bears S.48 $\frac{3}{4}$ °W. 218 lks. dist., mkd. $\frac{1}{2}$ S B T . Additionally mark $\frac{1}{4}$ S26 BT

Four wire fencing, extending N. and S., bears East 2:60 chs. dist.

N.0°05'W., beginning new measurement.

Desc. slightly over NW. slope.

12.00 Drain, course NE. An earthen tank, or reservoir, about 2 chs. in diam., bears NE. 2.50 chs. dist.

16.60 Wire fencing, bears S.5°E. and N.5°W., and continues irregularly north along line.

35.75 Low spur, slopes NE. Desc. slightly over N. slope.

39.83 The cor. of secs. 23, 24, 25 and 26, evidenced by the original monument, a lava stone 16 x 8 x 6 ins., firmly set in a mound of stone 3 ft. base, mkd. with 2 notches on the S. and 1 notch on the E. edges.

Set an iron post, 3 ft. long, 2 in. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.

T25N R5E

S 23 | S 24

S 26 | S 25

1944

from which

Original bearing trees:

A juniper stump, 8 ins. diam., bears S.35°E. 29 lks. dist., marks 25 BT remain thereon.

A pinon, 7 ins. diam., bears N.41 $\frac{3}{4}$ °W. 40 lks. dist., mkd. T25N R5E S23 BT

New bearing trees:

A pinon, 9 ins. diam., bears N.7 $\frac{1}{2}$ °E. 59 lks. dist., mkd. T25N R5E S24 BT

A pinon 6 ins. diam., bears S.25 $\frac{1}{4}$ °E. 17 lks. dist., mkd. T25N R5E S25 BT

A pinon, 8 ins. diam., bears S.74°W. 41 lks. dist., mkd. T25N R5E S26 BT

Corner of fencing, extending to the N. E. and S., bears S.35°E., 31 lks. dist.

Land, slightly rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, pinon, juniper and yellow pine, and 2nd. growth.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.

S.89°51'W. bet. secs. 24 and 25.

Over rolling land, through heavy timber; along wire fencing, extending irregularly E. and W.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains	
	Desc. 10 ft.
3.60	Wash, 8 lks. wide, course NE., Asc, 50 ft. over SE. slope.
12.80	Spur, slopes NE. Continue along gentle N. slope.
21.40	Draw, 1 ch. wide, course NE. Asc. 55 ft. over SE. slope.
34.00	Change of slope to E. Asc. 17 ft.
40.19	Point for $\frac{1}{4}$ sec. cor., at proportionate distance.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{4} \frac{S \ 24}{S \ 25}$ 1944
	from which
	A pinon, 12 ins. diam., bears S.50 $\frac{3}{4}$ °E. 65 lks. dist., mkd. $\frac{1}{4}$ S25 BT
	A pinon, 10 ins. diam., bears N.30 $\frac{1}{2}$ °W. 37 lks. dist., mkd. $\frac{1}{4}$ S24 BT
	Fence line, extending E. and W. bears South 2.25 chs. dist.
	Continue ascent 14 ft. over E. slope.
43.30	Low spur, slopes N., Desc. 25 ft. over W. slope.
45.75	Old road, bears N.20°E. and S.20°W.
48.35	Wash, 5 lks. wide, course N.20°E. Asc. 27 ft.
53.50	Top of ascent. Continue over gentle N. slope.
76.50	Low spur, slopes NE.
80.20	Four wire fencing, bears N. and S.
80.38	The cor. of secs. 23, 24, 25 and 26.
	Land, rolling. Soil, rocky, 3rd. rate. Timber, pinon, juniper and yellow pine, scattered 2nd. growth.

	N.0°05'W. bet. secs. 23 and 24.
	Over rolling land, through heavy growth of timber.
	Desc. 57 ft. over N. slope, along fencing.
7.50	Entered scattered timber, bearing W. and NE.
15.50	Shallow draw, course NE. Continue over gentle E. slope.
25.00	Low spur, slopes NE.
39.77	The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 12 x 10 x 8 ins. firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the

Resurvey of the Subdivision of T.25 N., R.5 E.

FOUNTAIN 4356

Chains

ground, with original corner stone buried alongside, with brass cap mkd.

$$\frac{1}{4}$$

S 23	S 24
1944	

from which

Original bearing trees:

A pinon, 14 ins. diam., bears S.19°W., 240 lks. dist. mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S23 BT

A juniper, 12 ins. diam., bears N.27 $\frac{3}{4}$ °W. 275 lks. dist. mkd. $\frac{1}{4}$ S BT

New bearing tree:

A pinon, 10 ins. diam., bears S.24°E. 264 lks. dist., mkd. $\frac{1}{4}$ S24 BT

Four wire fencing bears N. and S. from corner.

N.0°21'E., beginning new measurement.

Desc. 75 ft. over NW. slope.

30.50 Top of rocky bluff, bearing N.70°E. and S.70°W. Desc. 98 ft. over NW. slope.

39.83 The cor. of secs. 13, 14, 23 and 24, evidenced by the original monument, a lava stone 16 x 10 x 5 ins., firmly set, mkd. with 3 notches on the S. and 1 notch on the E. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\begin{array}{cc} T25N & R5E \\ S 14 & | S 13 \\ \hline S 23 & | S 24 \end{array}$$

1944

from which

Original bearing trees:

A juniper, 8 ins. diam., bears N.5°E. 197 lks. dist., mkd. T25N R5E S13 BT

A juniper, 12 ins. diam., bears N.14°E. 187 lks. dist. mkd. T25N R5E S13 BT

A juniper 14 ins. diam., bears N.25 $\frac{3}{4}$ °E. 186 lks. dist. mkd. T25N R5E S13 BT

A pinon, stump, 12 ins. diam. bears S.72°W. 155 lks. dist., mkd. T25N R5E S24 BT

New bearing trees:

A juniper, 3 ins. diam., bears S.19 $\frac{1}{2}$ °E. 69 lks. dist. mkd. BT

A pinon, 12 ins. diam., bears S.50 $\frac{1}{2}$ °W. 362 lks. dist.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains	
	<p>mkd. T25N R5E S23 BT</p> <p>A juniper, 4 ins. diam., bears N.46°W. 219 lks. dist. mkd. BT</p> <p>Wire fence, extending N. and S. bears west 30 lks. dist.</p> <p>Land, rolling. Soil, rocky 2nd. and 3rd. rate. Timber, pinon and juniper, and 2nd. growth.</p> <p>-----</p> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>N.89°28'W. bet. secs. 13 and 24.</p> <p>Over rolling land, through scattered timber. Desc. 20 ft.</p>
4.40	Draw, 2 chs. wide, course N. Asc. 190 ft. over NE. slope.
15.60	Enter heavy growth of timber, bearing NW. and SE.
27.50	Enter scattered timber, bears NW. and SE.
39.73	<p>The $\frac{1}{4}$ sec. cor., evidenced by a lava stone, 12 x 10 x 4 ins., firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the N.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd:</p> <div style="text-align: center;"> $\frac{1}{4} \begin{array}{l} S 13 \\ S 24 \end{array}$ <p>1944</p> <p style="text-align: right;">from which</p> </div> <p>An original bearing tree:</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N.2$\frac{1}{2}$°E. 231 lks. dist. mkd. $\frac{1}{4}$ S BT</p> <p>New bearing trees:</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears N.13$\frac{1}{2}$°W. 119 lks. dist. mkd. $\frac{1}{4}$ S13 BT</p> <p style="padding-left: 40px;">A pinon, 6 ins. diam., bears S.17$\frac{3}{4}$°E. 239 lks. dist., mkd. $\frac{1}{4}$ S24 BT</p>
	<p>S.89°48'W., beginning new measurement.</p> <p>Asc. 25 ft. over E. slope.</p>
13.40	Spur, slopes NE. Desc. 50 ft. over W. slope.
16.50	Enter heavy growth of timber, bears NE. and S.
21.80	Ravine, course N. Asc. 25 ft.
25.00	Spur, slopes N. Broken rim rock, bears NE. and SW. Desc. 90 ft. over NW. slope.
30.00	Enter scattered timber, bearing NE. and SW.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4334

Chains	
40.50	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling. Soil, rocky, 2nd. and 3rd. rate. Timber, pinon, juniper and yellow pine; 2nd. growth pinon and juniper.</p> <p>-----</p>
	<p>N.0°39'E. bet. secs. 13 and 14.</p> <p>Over slightly rolling land, through scattered timber.</p>
14.98	<p>Corner of fencing extending E. S. and N., bears west 41 lks. dist.</p>
22.50	<p>Shallow draw, course N.60°E.</p>
24.70	<p>Unimproved road, bears E. to Cedar Ranch and W. to County Highway, in section 22.</p>
26.50	<p>Enter heavy timber, bears E. and W.</p>
34.80	<p>Low spur, slopes N.60°E. Desc. 20 ft.</p>
39.70	<p>The $\frac{1}{4}$ sec. cor., evidenced by a malpais stone, 14 x 10 x 5 ins., loosely set, marked $\frac{1}{4}$ on W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.</p>
	<p style="text-align: center;"> $\frac{1}{4}$ S 14 S 13 1944 from which </p>
	<p>Original bearing trees:</p>
	<p>A pinon, 12 ins. diam., bears S.78°E. 55 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S13 BT</p>
	<p>A juniper, 20 ins. diam., bears S.70°W. 9 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S14 BT</p>
	<p>Corner of wire fencing, extending N. S. and E., bears east 6 lks. dist.</p>
	<p>N.0°09'W., beginning new measurement.</p>
	<p>Desc. 20 ft. over gradual NW. slope.</p>
9.60	<p>Wash, 10 lks. wide, course NE.</p>
10.50	<p>Entered scattering timber, bearing NE. and SW.</p>
39.85	<p>The cor. of secs. 11,12,13 and 14, evidenced by the original monument, a lava stone, 14 x 8 x 5 ins., loosely set in mound of stone, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.</p>

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains	<p style="text-align: center;"> $\begin{array}{r} \text{T25N R5E} \\ \text{S 11 S 12} \\ \text{S 14 S 13} \end{array}$ </p> <p style="text-align: center;">1944</p> <p style="text-align: right;">from which</p> <p>Original bearing trees:</p> <p>A juniper, 12 ins. diam., bears S.15$\frac{3}{4}$°E. 76 lks. dist., mkd. T25N R5E S13 BT</p> <p>A juniper, 24 ins. diam., bears S.88°W. 24 lks. dist., mkd. T25N R5E S14 BT</p> <p>A pinon, 9 ins. diam., bears N.84$\frac{1}{2}$°W. 35 lks. dist., mkd. T25N R5E S11 BT</p> <p>New bearing trees:</p> <p>Juniper, 3 ins. diam., bears N.71$\frac{1}{2}$°E. 94 lks. dist., mkd. BT</p> <p>Juniper, 20 ins. diam., bears S.30$\frac{1}{2}$°W. 99 lks. dist., mkd. T25N R5E S14 BT</p> <p>Wire fence, extending N. and S. bears west 10 lks. dist.</p> <p>Land, gently rolling. Soil, rocky, 2nd. and 3rd. rate. Timber, pinon and juniper, and 2nd. growth.</p> <p>-----</p> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p> <p>N.88°33'W. bet. secs. 12 and 13.</p> <p>Over rolling land, through scattered timber. Asc. 40 ft. over E. slope.</p> <p>25.00 Low spur, slopes NE.</p> <p>30.70 Old roadway, bears NE. and SW.</p> <p>40.47 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone, 9 x 6 x 5 ins. firmly set, mkd $\frac{1}{4}$ on the N. face, and witnessed by a mound of stone 2$\frac{1}{2}$ ft. base, 6 ins. high, to the N.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4} \begin{array}{r} \text{S 12} \\ \text{S 13} \end{array}$ </p> <p style="text-align: center;">1944</p> <p style="text-align: right;">from which</p> <p>A juniper, 4 ins. diam., bears N.26$\frac{3}{4}$°E. 233 lks. dist. mkd. $\frac{1}{4}$ S12 BT</p> <p>A juniper, 4 ins. diam., bears S.35°W. 198 lks. dist., mkd. $\frac{1}{4}$ S13 BT</p> <p>S.88°42'W., beginning new measurement.</p> <p>7.00 Enter heavy growth of timber, bears N. and S.</p>
--------	--

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4856

Chains

11.20 Low spur, slopes N.

12.00 Enter scattered timber, bearing NW. and SE.

12.80 Four wire fencing, bears NW. and SE.

26.20 Wash, 5 lks. wide, course NE.

39.62 The cor. of secs. 11,12,13 and 14.

Land, slightly rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, pinon and juniper; and 2nd. growth.

N.0°20'W. bet. secs. 11 and 12.

Over nearly level land, through scattered timber.

9.75 Wire fencing, bears N.20°E. and S.20°W.

20.00 Shallow sink, bears west about 10 chs. dist., about 20 acres in extent, and enclosed by irregular wire fencing.

23.25 Wire fence, bears SE. and NW.

39.85 Point for $\frac{1}{4}$ sec. cor., at proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 11 \mid S\ 12 \\ 1944 \end{array}$$

from which

A juniper, 3 ins. diam., bears N.28°E. 197 lks. dist. mkd. B T

A juniper, 3 ins. diam., bears S.24°W. 106 lks. dist. mkd. $\frac{1}{4}$ S11 BT

40.05 Old road, bears NW. and SE.

43.20 Dim roadway, bears N.15°E. and S.15°W.

60.00 Desc. slightly over NW. slope.

79.70 The cor. of secs. 1, 2, 11 and 12, evidenced by the original monument, a malpais stone, 9 x 8 x 8 ins., firmly set, mkd. with 5 grooves on the S. and 1 groove on the E. faces, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.

$$\begin{array}{c} T25N\ R5E \\ S\ 2 \mid S\ 1 \\ S\ 11 \mid S\ 12 \end{array}$$

1944

from which

Original bearing trees:

Survey of the Subdivision of T.25 N., R.5 E.

Chains

A juniper, 10 ins. diam., bears S.80°E. 237 lks. dist.
mkd. T25N R5E S12 BT

A pinon, 12 ins. diam., bears S.73½°E. 248 lks. dist.,
mkd. T25N R5E S12 BT

A pinon, 7 ins. diam., bears S.67½°E. 320 lks. dist.,
mkd. T25N R5E S12 BT

A pinon, 10 ins. diam., bears S.60½°E. 325 lks. dist.
mkd. T25N R5E S12 BT

New bearing trees:

A juniper, 4 ins. diam., bears N.82°E. 139 lks. dist.,
mkd. T25N R5E S1 BT

A juniper, 4 ins. diam., bears S.71°W. 273 lks. dist.
mkd. BT

A juniper, 3 ins. diam., bears N.60¾°W. 271 lks. dist.
mkd. BT

Land, rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, juniper and pinon, and 2nd. growth.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of
the Tp.

N.89°09'W., bet. secs. 1 and 12.

Over gently rolling land, through scattered timber.

10.30 Drain, 25 lks. wide, 1½ ft. deep, course N.25°E. Asc. 28
ft. over E. slope.

25.00 Low spur, slopes N. Desc. slightly over W. slope.

40.18 The ¼ sec. cor., evidenced by a lava rock, in place, 30 x
18 x 12 ins. above ground, marked with cross + on top,
and ¼ on N. face.

At point for cor., in the original stone, set a brass
tablet, 3½ ins. diam., 3 in. stem, with top mkd.

$$\frac{1}{4} \frac{S \ 1}{S \ 12}$$

1944

from which

A juniper, 4 ins. diam., bears N.25½°E. 400 lks. dist.
mkd. ¼ S1 BT

A juniper, 10 ins. diam., bears S.14½°E. 275 lks.
dist., mkd. ¼ S12 BT

S.89°22'W., beginning new measurement.

30.90 Dim roadway, bears NE. and SW.

33.50 Low spur, slopes N.

40.31 The cor. of secs. 1, 2, 11 and 12.

Land, gently rolling.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4356

Chains

Soil; shallow and rocky, 2nd. and 3rd. rate.
Timber, pinon and juniper, and 2nd. growth.

N.0°09'E. bet. secs. 1 and 2.

Over slightly rolling land, through scattered timber.

11.60 Shallow draw, drains NE.

39.85 The $\frac{1}{4}$ sec. cor., evidenced by a malpais stone 14 x 12 x 4 ins., firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 2 \mid S\ 1 \\ 1944 \end{array}$$

Raise mound of stone 4 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.

N.0°27'W., beginning new measurement.

2.50 Same draw, course NW.

15.00 Desc. 25 ft. over NW. slope.

22.60 Draw, course NE. Asc. 28 ft. over S. slope.

27.60 Enter heavy growth of timber, bearing NE. and W.

29.00 Top of ascent, and over nearly level land.

39.82 The cor. of secs. 1 and 2, on the N. bdy. of the Tp., evidenced by the original monument, a limestone, 9 x 7 x 7 ins., firmly set, mkd. with 1 notch on the E. and with 5 notches on the W. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the N.

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with original corner stone deposited alongside, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} T26N\ R5E \\ S\ 35 \\ \hline S\ 2 \mid S\ 1 \\ T25N\ R5E \end{array}$$

1944

from which

Original bearing trees:

A pinon, 12 ins. diam., bears S.71 $\frac{3}{4}$ °E. 58 lks. dist., mkd. T25N R5E S1 BT

A pinon, 12 ins. diam., bears N.1 $\frac{1}{4}$ °E. 86 lks. dist., mkd. T26N R5E S36 BT

New bearing trees:

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

A pinon, 14 ins. diam., bears S.41 $\frac{3}{4}$ °W. 123 lks. dist.
mkd. T25N R5E S2 BT

The cor. of secs. 35 and 36, T.26 N., R.5 E., bears
S.89°34'E., 0.60 chs. dist., marked by a 3 in. iron
post, conforming to the 1916 resurvey record.

A 4 wire fence line, extending E. and W., bears N.
9 lks. dist.

Land, rolling.

Soil, shallow and rocky, 2nd. and 3rd. rate.

Timber, juniper and pinon, and 2nd. growth.

Undergrowth, algerica brush.

At the $\frac{1}{4}$ sec. cor. on the N. bdy. of sec. 1, evidenced by
the original monument, a malpais stone, 18 x 14 x 5 ins.,
firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a
mound of stone, 2 ft. base, 1 ft. high, to the S.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the
ground, to bedrock, with original corner stone buried
alongside, and in a mound of stone to top, with brass cap
mkd.

$\frac{1}{4}$ S 1

1944

From this corner:

The cor. of Ts. 25 and 26 N., Rs. 5 and 6 E. bears
N.89°46'E., 39.94 chs. dist.

The $\frac{1}{4}$ sec. cor. of sec. 36, bears N.89°34'W. 0.06 chs.
dist., marked by the 1916 resurvey monument, and the
cor. of secs. 1 and 2, bears N.89°34'W. 40.66 chs.
dist.

From the standard cor. of secs. 34 and 35, on S. bdy. of T.,
described in the field notes of T.24 N., R.5 E.,
N.1°52'E. bet. secs. 34 and 35.

Over mountainous land, through heavy growth of timber and
scattered undergrowth.

Along crest of spur, sloping N. 20°E.

0.60 Desc. 102 ft. over N. slope.

8.50 Change of slope to NE., continue descent 85 ft.

13.00 Spur, slopes N.30°E; desc. 467 ft. over N. slope, along
crest of small spur.

20.00 Enter rolling land, continue descent.

48.40 The $\frac{1}{4}$ sec. cor., evidenced by a limestone, 16 x 10 x 5 ins.
firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a
mound of stone 2 ft. base, 1 ft. high to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with original corner stone buried alongside, with
brass cap mkd.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4888

Chains

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 34 \mid \text{S } 35 \\ 1944 \end{array}$$

from which

Original bearing trees:

A pine, 26 ins. diam., bears S.46³°E. 34 lks. dist., marks overgrown; reblaze, and mark $\frac{1}{4}$ S35 BT

A pine, 12 ins. diam., bears S.14³°W. 44 lks. dist., marks overgrown; remark $\frac{1}{4}$ S34 BT

N.3°17'W. beginning new measurement.

Desc. 63 ft. over gentle N. slope.

12.00 Change of slope to W.

21.80 Low spur, slopes N.60°W. Desc. 40 ft. over N. slope.

39.83 The cor. of secs. 26, 27, 34 and 35, evidenced by the original monument, a lava stone, 16 x 12 x 10 ins., firmly set, mkd. with 1 notch on the S. and 2 notches on the E. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original corner stone buried alongside, with brass cap mkd.

$$\begin{array}{c} \text{T25N R5E} \\ \text{S } 27 \mid \text{S } 26 \\ \hline \text{S } 34 \mid \text{S } 35 \end{array}$$

1944

from which

Original bearing trees:

A pinon, 14 ins. diam., bears N.21°E., 23 lks. dist., mkd. T25N R5E S26 BT

A pinon, 6 ins. diam., bears S.79¹°W. 39 lks. dist., mkd. T25N R5E S34 BT

A pinon, 12 ins. diam., bears N.72¹°W. 16 lks. dist., mkd. T25N R5E S27 BT

New bearing tree:

A pinon, 7 ins. diam., bears S.50³°E. 29 lks. dist., mkd. T25N R5E S35 BT

Land, mountainous and rolling.

Soil, rocky, 3rd. rate.

Timber, yellow pine, pinon and juniper.

Undergrowth, 2nd. growth pinon and cliffrose.

From the cor. of secs. 25, 26, 35 and 36.

Over rolling land, through heavy timber.

N.89°00'W. bet. secs. 26 and 35. Asc. 13 ft. over E.slope.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains	
2.00	Spur, slopes N.20°E. Desc. 60 ft. over NW. slope.
8.00	Ravine, course N. Asc. 36 ft. over NE. slope.
14.50	Change of slope to N.
16.80	Graded road, bears N.65°W. to Grand Canyon and S.45°E. to Flagstaff.
23.00	Spur, slopes N.15°W. Desc. 20 ft. over N. slope.
31.50	Low spur, slopes NW. Desc. 35 ft. over SW. slope.
38.91	The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 14 x 14 x 8 ins. firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the N.
	Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground, to bedrock, with original corner stone buried alongside, and in a mound of stone to top, with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 26}{S\ 35}$
	1944
	from which
	Original bearing trees:
	A pinon, 12 ins. diam., bears S.19°W. 48 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S35 BT
	A pinon, 7 ins. diam., bears N.64 $\frac{1}{2}$ ° W. 36 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S26 BT
	S.89°34'W., beginning new measurement.
	Desc. 90 ft. over SW. slope.
17.50	Wash, 10 lks. wide, course NW. Continue over gentle N. slope.
26.00	Change of slope to NW. Desc. slightly.
39.36	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling. Soil, rocky, 2nd. and 3rd. rate. Timber, pinon, juniper and pine; 2nd. growth pinon.
	----- N.2°48'E. bet. secs. 26 and 27.
	Over gently rolling land, through heavy timber.
20.40	Low ledge, or rimrock, bears NW. and SE. Desc. 75 ft. over NE. slope. Enter scattered timber.
34.00	Enter heavy timber, bearing NW. and SE.
38.73	Graded road, bears N.50°W. to Grand Canyon, and S.65°E. to Flagstaff.
40.28	The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 12 x 10 x 8 ins. loosely set, mkd. $\frac{1}{4}$ on the W. face.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 100

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground; with original corner stone deposited alongside, with brass cap mkd.

$$\frac{1}{4}$$

S 27	S 26
------	------

1944

from which

Original bearing trees:

A pinon, 10 ins. diam., bears S.43½°E. 125 lks. dist., mkd. ¼ S BT . Additionally mark ¼ S26 BT

A pinon, 12 ins. diam., bears S.33½°W. 176 lks. dist., mkd. ¼ S BT . Additionally mark ¼ S27 BT

N.1°00'W., beginning new measurement.

Desc. 20 ft. over gentle N. slope.

39.98

The cor. of secs. 22, 23, 26 and 27, evidenced by the original monument, a lava stone 16 x 10 x 8 ins., loosely set, mkd with 2 notches on the S. and E. edges, and witnessed by a mound of stone, 2 ft. base, 1 ft. high to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground, to bedrock, with original corner stone deposited alongside, and in a mound of stone to top, with brass cap mkd.

T25N	R5E
S 22	S 23
S 27	S 26

1944

from which

Original bearing trees:

A juniper, 10 ins. diam., bears N.17½°E. 273 lks. dist., mkd. T25N R5E S23 BT

A juniper, 12 ins. diam., bears S.43½°E. 17 lks. dist., mkd. T25N R5E S26 BT

A juniper, 12 ins. diam. bears S.2°W. 100 lks. dist. mkd. T25N R5E S27 BT

A juniper, 5 ins. diam., bears N.68°W. 40 lks. dist., mkd. T25N R5E S22 BT

Land, rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, juniper, pinon, yellow pine; 2nd. growth.

From the cor. of secs. 23, 24, 25 and 26.

N.88°59'W. bet. secs. 23 and 26.

Over rolling land, through heavy timber. Asc. 15 ft. over N. slope.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

- 8.00 Low spur, slopes N. Desc. 75 ft. over NW. slope.
- 38.12 The $\frac{1}{4}$ sec. cor., evidenced by a malpais stone, 14 x 10 x 4 ins., firmly set, mkd $\frac{1}{4}$ on the N. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the N.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone buried slongside, with brass cap mkd.
- $\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$
- 1944
- from which
- Original bearing trees:
- A pinon, 8 ins. diam., bears N.10 $\frac{1}{2}$ °E. 15 lks. dist., mkd. $\frac{1}{4}$ S BT. Additionally mark $\frac{1}{4}$ S23 BT
- A pinon, 10 ins. diam., bears N.35 $\frac{1}{2}$ °W. 37 lks. dist. mkd. $\frac{1}{4}$ S BT
- New bearing tree:
- A pinon, 6 ins. diam., bears S.18°W. 11 lks. dist., mkd. $\frac{1}{4}$ S26 BT
- N.88°56'W., beginning new measurement.
- Desc. 95 ft. over NW. slope.
- 16.00 Wash, 5 lks. wide, course N. Asc. 45 ft. over E. slope.
- 25.50 Spur, slopes N. Desc. 15 ft.
- 31.40 Wash, 10 lks. wide, course N.10°E. Asc. 20 ft. over E. slope.
- 33.00 Top of ascent, continue over gentle N. slope.
- 39.07 The cor. of secs. 22, 23, 26 and 27.
- Land, rolling.
Soil, rocky, 2nd. and 3rd. rate.
Timber, pinon, juniper and yellow pine; 2nd. growth.
-
- N.0°05'E. bet. secs. 22 and 23.
- Over gently rolling land, through heavy timber.
- 14.30 Shallow draw, course NE.
- 18.50 Enter scattered timber, bearing NE. and SW.
- 39.82 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone, 12 x 8 x 6 ins. firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4856

Chains

$$\frac{1}{4}$$

S 22	S 23
------	------

1944

from which

An original bearing tree:

A pinon, 10 ins. diam., bears N.83°E. 90 lks. dist.
mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S23 BT

New bearing tree:

A pinon, 4 ins. diam., bears N.87 $\frac{1}{2}$ °W. 45 lks. dist.,
mkd. $\frac{1}{4}$ S22 BT

N.0°02'W. beginning new measurement.

Desc. 80 ft. over gradual N. slope.

39.77 Unimproved road, bears NE. to Cedar Ranch, and S.50°W. to County Highway, in section 22.

39.87 The cor. of secs. 14, 15, 22 and 23, evidenced by the original monument, a lava stone 16 x 10 x 9 ins., firmly set, mkd. with 3 notches on the S. and 2 notches on the E. faces, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 in. diam., 20 ins. in the ground, to bedrock, with original corner stone deposited at base, and in a mound of stone to top, with brass cap mkd.

T25N R5E	
S 15	S 14
S 22	S 23

1944

from which

Original bearing trees:

A juniper, 6 ins. diam. bears S.59 $\frac{1}{2}$ °E. 86 lks. dist.
mkd. T25N R5E S23 BT

A pinon, 8 ins. diam. bears S.52 $\frac{1}{2}$ °E. 98 lks. dist.,
mkd. T25N R5E S23 BT

A pinon, 10 ins. diam., bears S.40°E. 130 lks. dist.,
mkd. T25N R5E S23 BT

A juniper, 8 ins. diam., bears N.19 $\frac{3}{4}$ °W. 19 lks. dist.
mkd. T25N R5E S15 BT

New bearing trees:

A juniper, 5 ins. diam., bears N.5 $\frac{3}{2}$ °E. 85 lks. dist.
mkd. T25N R5E S14 BT

A juniper, 7 ins. diam., bears S.32 $\frac{1}{2}$ °W. 119 lks. dist.
mkd. T25N R5E S22 BT

Land, gently rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, juniper, pinon, yellow pine; 2nd. growth.

Undergrowth, algerica.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

From the cor. of secs. 13, 14, 23 and 24.
N.88°01'W., bet. secs. 14 and 23.
Over slightly rolling land, through scattered timber.

- 0.30 Four wire fencing, extends N. and S.
13.20 Drain, course N.20°W.
25.00 Low spur, slopes N.20°E.
32.00 Enter heavy timber, bears N.20°W. and S.
35.10 Wash, 15 lks. wide, course N.20°E.
37.44 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone, 14 x 8 x 6 ins. firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the N.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S 14 \\ S 23 \end{array}$$

1944

from which

Original bearing trees:

A pinon stump, 12 ins. diam. 1 ft. high, bears S.71 $\frac{3}{4}$ °E. 25 lks. dist. the dead tree lying on the ground, mkd. $\frac{1}{4}$ S BT

A juniper, 6 ins. diam. bears S.37 $\frac{1}{4}$ °W. 40 lks. dist., mkd. $\frac{1}{4}$ S BT. Additionally mark $\frac{1}{4}$ S23 BT

New bearing tree:

A juniper, 5 ins. diam., bears N.24 $\frac{1}{4}$ °W. 64 lks. dist. mkd. $\frac{1}{4}$ S 14 BT

N.89°39'W. beginning new measurement.

Asc. 28 ft. over gentle N. slope.

- 20.00 Low spur, slopes N. Desc. slightly.
39.72 Unimproved road, bears NE. to Cedar Ranch and SW. to County Highway.
39.87 The cor. of secs. 14, 15, 22 and 23.
Land, gently rolling.
Soil, rocky, 2nd. and 3rd. rate.
Timber, juniper, pinon and yellow pine; 2nd. growth.

N.0°03'E. bet. secs. 14 and 15.

Over rolling land, through heavy timber.

- 24.50 Enter scattered timber, bears NE. and W.
39.71 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 14 x 8 x 5 ins. firmly set, mkd $\frac{1}{4}$ on W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 407

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 15 \mid S\ 14 \\ 1944 \end{array}$$

from which

Original bearing trees:

A juniper, 14 ins. diam. bears S.38 $\frac{1}{2}$ °E. 128 lks. dist. mkd. $\frac{1}{4}$ S BT. Additionally mark $\frac{1}{4}$ S14 BT

A juniper, 16 ins. diam. bears S.13 $\frac{1}{2}$ °E. 258 lks. dist. mkd. $\frac{1}{4}$ S BT

New bearing tree:

A yellow pine, 5 ins. diam. bears S.75 $\frac{1}{2}$ °W. 134 lks. dist., mkd. $\frac{1}{4}$ S15 BT

N.0°04'W., beginning new measurement.

Desc. slightly.

- 1.80 Drain, 15 lks. wide, 3 ft. deep, course NE., ditched to carry flood waters to sink in section 11.
- 25.80 Old roadway, bears NW. and SE.
- 27.00 Shallow draw, course NW.
- 39.87 The cor. of secs. 10,11,14 and 15, evidenced by the original monument, a lava stone 12 x 0 x 5 ins., firmly set, mkd. with 4 notches on the S. and 2 notches on the E. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\begin{array}{c} T25N\ R5E \\ S\ 10 \mid S\ 11 \\ S\ 15 \mid S\ 14 \end{array}$$

1944

from which

Original bearing trees:

A pinon, 10 ins. diam., bears N.64°E. 138 lks. dist., mkd. T25N R5E S11 BT

A pinon, 12 ins. diam., bears N.86 $\frac{1}{2}$ °E. 131 lks. dist. mkd. recently, on overgrowth of original blaze, T25N R5E S14 BT

A juniper, 12 ins. diam., bears S.86 $\frac{1}{2}$ °E. 146 lks. dist., mkd. T25N R5E S14 BT

A juniper, 8 ins. diam., bears S.78°E. 181 lks. dist. mkd. T25N R5E S14 BT

New bearing tree:

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

A juniper, 3 ins. diam., bears N.70°W. 223 lks. dist.,
mkd. BT

Raise a mound of stone 2½ ft. base, 1½ ft. high, W.
of corner.

Land, gently rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, pinon, juniper, yellow pine; 2nd. growth.

From the cor. of secs. 11, 12, 13 and 14.

N.83°09'W. bet. secs. 11 and 14.

Over rolling land, through heavy timber. Asc. 45 ft. over
E. slope.

- 0.10 Four wire fencing, extends N. and S.
18.50 Top of ascent; continue over gentle N. slope.
28.80 Enter scattered timber, bearing N. and S.
38.23 The ¼ sec. cor., evidenced by a lava stone, 12 x 6 x 5 ins.
firmly set, mkd. ¼ on the N. face, and witnessed by a
mound of stone 2 ft. base, 1 ft. high, to the N.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with original corner stone deposited alongside,
with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 11 \\ S 14 \end{array}$$

1944

from which

A juniper, 10 ins. diam., bears S.24½°W. 319 lks. dist.
mkd. ¼ S14 BT

A juniper, 14 ins. diam., bears N.38¾°W. 427 lks. dist.
mkd. ¼ S11 BT

S.85°43'W., beginning new measurement.

- 20.50 Drain ditch, 38 lks. wide, 6 ft. deep, course N.5°E, to
sink in the SE. ¼ of sec. 11.
39.82 The cor. of secs. 10, 11, 14 and 15.

Land, slightly rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, juniper and pinon; 2nd. growth.

N.0°10'E. bet. secs. 10 and 11.

Over rolling land, through scattered timber.

- 4.30 Enter heavy timber, bears NW. and SE.
28.50 Enter scattered timber, bearing E. and W.
38.80 The ¼ sec. cor., evidenced by a lava stone 10 x 10 x 8 ins.
firmly set, mkd. ¼ on the W. face, and witnessed by a
mound of stone, 2 ft. base, 1 ft. high, to the W.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4888

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone buried at base, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 10 \mid \text{S } 11 \\ 1944 \end{array}$$

from which

Original bearing trees:

A pinon, 18 ins. diam., bears N.19 $\frac{3}{4}$ °E. 196 lks. dist. mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S11 BT

A pinon, 14 ins. diam., bears S.34 $\frac{3}{4}$ °E. 273 lks. dist. mkd. $\frac{1}{4}$ S BT

New bearing tree:

A pinon, 10 ins. diam., bears S.28 $\frac{1}{2}$ °W. 224 lks. dist. mkd. $\frac{1}{4}$ S10 BT

N.0°33'W., beginning new measurement.

Desc. 55 ft. over gentle N. slope.

15.00 Enter heavy growth of timber, bears E. and W.

22.20 Foot of descent, leave timber, bearing E. and W.

31.90 Old road, bears E. and W.

32.20 Wide, shallow draw, course E.

39.81 The cor. of secs. 2, 3, 10 and 11, evidenced by the original monument, a limestone 14 x 8 x 6 ins., firmly set, mkd. with 5 grooves on the S. and 2 grooves on the E. faces, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone buried alongside, with brass cap mkd.

$$\begin{array}{c} \text{T25N R5E} \\ \text{S } 3 \mid \text{S } 2 \\ \text{S } 10 \mid \text{S } 11 \end{array}$$

1944

from which

Original bearing trees:

A juniper, 14 ins. diam., bears N.38 $\frac{3}{4}$ °E. 276 lks. dist., mkd. T25N R5E S2 BT

A juniper, 18 ins. diam., bears N.50°E. 232 lks. dist. mkd. T25N R5E S2 BT

A juniper, 10 ins. diam., bears N.55°E. 248 lks. dist. mkd. T25N R5E S2 BT

A juniper, 16 ins. diam., bears N.74 $\frac{3}{4}$ °E. 304 lks. dist., mkd. T25N R5E S2 BT

New bearing tree:

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

A juniper, 30 ins. diam., bears N.14°W. 276 lks. dist. mkd. T25N R5E S3 BT

Raise mound of stone, 2½ ft. base, 1½ ft. high, W. of corner.

Land, gently rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, juniper, pinon; and 2nd. growth.

From the cor. of secs. 1, 2, 11 and 12.

S.89°16'W.; bet. secs. 2 and 11.

Over rolling land, through scattered timber.

10.50 Wash, 10 lks. wide, course N.25°E. Asc. 45 ft. over SE. slope.

23.00 Enter heavy timber, bears N. and S.

25.00 Low spur, slopes N. Desc. slightly over N. slope.

31.60 Enter scattered timber, bears NW. and SE.

39.84 The ¼ sec. cor., evidenced by a limestone 12 x 10 x 8 ins. firmly set, mkd. ¼ on the N. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the N.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground; with original corner stone deposited alongside, with brass cap mkd.

$$\frac{1}{4} \frac{S \ 2}{S \ 11}$$

1944

from which

A juniper, 16 ins. diam., bears N.44½°W. 340 lks. dist., mkd. ¼ S2 BT

No other tree within limits.

N.88°35'W., beginning new measurement.

Desc. 10 ft. over NW. slope.

11.70 Draw, 1 ch. wide, course NE. Asc. 28 ft. over SE. slope.

13.20 Enter heavy timber, bears NE. and SW.

19.30 Enter scattered timber, bearing N. and S.

23.50 Low spur, slopes S.

27.50 Enter heavy timber, bears SE. and NW.

31.80 Desc. 23 ft. over SW. slope.

33.00 Foot of descent, leave timber, bearing SE. and NW.

37.56 Wire fencing, extends S.51°35'E. from old fence line to the north.

37.61 The cor. of secs. 2, 3, 10 and 11.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4856

Chains

Land, slightly rolling.
Soil, rocky, 2nd. and 3rd. rate.
Timber, juniper, pinon and 2nd. growth.

N.2°03'W. bet. secs. 2 and 3.

Along old fence line, extending N.

2.10 Asc. 23 ft. over S. slope.

4.00 Top of ascent, over nearly level land

34.40 Enter heavy timber, bears SW. and E.

39.35 The $\frac{1}{4}$ sec. cor., evidenced by a limestone 16 x 8 x 4 ins., firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, with original corner stone deposited alongside, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$
S 3 | S 2
1944

from which

Original bearing trees:

A pinon, 10 ins. diam., bears N.38°E. 25 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S2 BT

A pinon, 10 ins. diam., bears N.25 $\frac{3}{4}$ °W. 36 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S3 BT

N.0°53'W., beginning new measurement.

10.00 Top of slight ascent, bears NE. and SW.

19.80 Shallow draw, drains NE.

33.50 Top of slight ascent, bearing NE. and SW.

39.67 The cor. of secs. 2 and 3, on the N. bdy. of the Tp., evidenced by the original monument, a limestone 12 x 8 x 6 ins., firmly set, mkd. with 2 notches on the E. and 4 notches on the W. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the N.

Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground, to bedrock, with original corner stone deposited alongside, and in a mound of stone to top, with brass cap mkd.

T26N R5E
S 35

S 3 | S 2
T25N R5E

1944

from which

Original bearing trees:

Resurvey of the Subdivisions of T.25 N., R.5 E.

Chains

A pinon, 9 ins. diam., bears S.35 $\frac{1}{4}$ °W. 50 lks. dist.,
mkd. T25N R5E S3 BT

A pinon, 9 ins. diam., bears S.78°W. 50 lks. dist.,
mkd. T25N R5E S3 BT

New bearing trees:

A pinon, 7 ins. diam., bears S.17°E. 73 lks. dist.,
mkd. T25N R5E S2 BT

A pinon, 12 ins. diam., bears S.71 $\frac{3}{4}$ °W. 74 lks. dist.,
mkd. T25N R5E S3 BT

The cor. of secs. 34 and 35, T.26 N., R.5 E., bears
S.89°51'W., 0.16 chs. dist., marked by a 3 in. iron
post, conforming to the 1916 resurvey record.

Corner of wire fences, extending E. W. and N., bears
N.45°W. 12 lks. dist.

Land, nearly level.

Soil, rocky, 2nd. and 3rd. rate.

Timber, juniper and pinon; 2nd. growth.

At the $\frac{1}{4}$ sec. cor., on the N. bdy. of sec. 2, evidenced by
the original monument, a limestone 18 x 12 x 6 ins., firmly
set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a mound of
stone 2 ft. base, 1 ft. high, to the N.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with original corner stone deposited at base, with
brass cap mkd.

$\frac{1}{4}$ S 2

1944

from which

The original bearing tree:

A pinon, 18 ins. diam., now dead and fallen, bears
S.14 $\frac{1}{2}$ °E. 79 lks. dist., mkd. $\frac{1}{4}$ S BT

New bearing trees:

A juniper, 6 ins. diam., bears S.9°E. 235 lks. dist.,
mkd. $\frac{1}{4}$ S 2 BT

A pinon, 8 ins. diam., bears S.70 $\frac{3}{4}$ °W. 161 lks. dist.,
mkd. $\frac{1}{4}$ S 2 BT

A four wire fence, extending E. and W., bears N. 25
lks. dist.

From this corner:

The $\frac{1}{4}$ sec. cor. of sec. 35 bears N.89°19'E., 0.43 chs.
dist., marked by an iron post, 1 in. diam., conforming
to the 1916 resurvey record, and the cor. of secs.
1 and 2 bears N.89°19'E. 39.83 chs. dist.

The cor. of secs. 2 and 3, bears N.89°44'W. 39.41 chs.
dist.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

From the standard cor. of secs. 33 and 34, on S.bdy. of T., described in the field notes of T.24 N., R.5 E., N.0°41'W. bet. secs. 33 and 34.

Over rolling land, through heavy growth of timber. Desc. 67 ft. over NW. slope.

27.10 Old road, bears NE. and S.20°W.

29.60 Cut wash, 10 lks. wide, 6 ft. deep, course NE. Asc. 40 ft. over SE. slope.

37.50 Enter scattered timber, bears NE. and SW.

39.00 Top of ascent, continue over nearly level land, draining E.

48.85 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 18 x 14 x 6 ins. firmly set, mkd $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$\frac{1}{4}$

S 33 | S 34

1944

from which

A pine, 7 ins. diam., bears S.43 $\frac{1}{2}$ °E. 216 lks. dist., mkd. $\frac{1}{4}$ S34 BT

A pine, 3 ins. diam., bears N.66 $\frac{1}{2}$ °W. 289 lks. dist., mkd. BT

U.S. Forest Service look-out station, on top of Slate Mountain, bears S.40°38'E. about 83.10 chs. dist.

N.1°01'W., beginning new measurement.

1.70 Old road, bears NE. and SW.

6.50 Desc. 78 ft. over NE. slope.

22.40 Draw, 1 ch. wide, course N.70°E. Continue descent 35 ft. over NE. slope.

39.83 The cor. of secs. 27, 28, 33 and 34, evidenced by the original monument, a lava stone 18 x 10 x 6 ins., firmly set, mkd. with 1 notch on the S. and 3 notches on the E. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

T25N R5E

S 28 | S 27

S 33 | S 34

1944

from which

Original bearing trees:

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

A pinon, 18 ins. diam., bears N.16 $\frac{3}{4}$ °E. 319 lks. dist.
mkd. T25N R5E S27 BT

A juniper, 14 ins. diam., bears N.30°E. 406 lks. dist.
mkd. T25N R5E S27 BT

New bearing trees:

A pine, 7 ins. diam., bears S.24 $\frac{3}{4}$ °E. 288 lks. dist.,
mkd. T25N R5E S34 BT

A pine, 5 ins. diam., bears S.33 $\frac{1}{4}$ °W. 180 lks. dist.,
mkd. T25N R5E S33 BT

A pinon, 6 ins. diam., bears N.15 $\frac{1}{2}$ °W. 281 lks. dist.,
mkd. T25N R5E S28 BT

Land, mountainous and rolling.
Soil, rocky, 2nd. and 3rd. rate.
Timber, yellow pine, juniper and pinon, and 2nd. growth.

From the cor. of secs. 26, 27, 34 and 35.

N.89°46'W. bet. secs. 27 and 34.

Over rolling land, through heavy growth of timber.

17.00 Enter scattered timber, bears NW. and SW.

24.80 Enter heavy timber, bears NW. and S.

38.75 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 10 x 10 x 8 ins.
firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a
mound of stone 2 ft. base, 6 ins. high, to the N.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with original corner stone deposited alongside,
with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S } 27 \\ \text{S } 34 \end{array}$$

from which

Original bearing trees:

A pinon, 8 ins. diam., dead and fallen, bears S.14°W.
29 lks. dist., mkd. $\frac{1}{4}$ S BT

A pinon, 16 ins. diam., dead and fallen, bears
N.39 $\frac{1}{4}$ °W. 49 lks. dist., old blaze decayed and no
marks remain.

New bearing trees:

A pinon, 6 ins. diam., bears N.21 $\frac{1}{2}$ °E. 8 lks. dist.,
mkd. $\frac{1}{4}$ S27 BT

A pinon, 10 ins. diam., bears S.61 $\frac{3}{4}$ °W. 28 lks. dist.,
mkd. $\frac{1}{4}$ S34 BT

U.S. Forest Service lookout station on Slate Mtn.
bears S.8°47'E.

N.89°08'W., beginning new measurement.

19.30 Old road, bears NW. and SE.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 1008

Chains	
21.00	Enter scattered timber, bears N. and S.
25.70	Enter drain ditch, 15 lks. wide, 1½ ft. deep, course west, from SE.
27.30	Leave ditch, course SW.
34.00	Draw, 3 chs. wide, course N.
37.43	Drain ditch, course NW.
39.03	The cor. of secs. 27, 28, 33 and 34. Land, slightly rolling. Soil, rocky, 2nd. and 3rd. rate. Timber, pinon and juniper; 2nd. growth.

	N.0°03'W. bet. secs. 27 and 28. Over slightly rolling land, through scattered timber.
2.10	Drain ditch, 15 lks. wide, 1½ ft. deep, course NW.
17.50	Low spur, slopes NE.
38.30	Spur, slopes NE. Desc. slightly.
39.83	The ¼ sec. cor., evidenced by a lava stone 16 x 14 x 5 ins. firmly set, mkd. ¼ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W. Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground, to bedrock, with original corner stone buried alongside, and in a mound of stone to top, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S } 28 \quad \quad \text{S } 27 \\ 1944 \end{array}$
	from which
	Original bearing trees:
	A pinon, 24 ins. diam., bears N.75½°E. 432 lks. dist. mkd. ¼ S BT
	A pinon, 14 ins. diam., bears N.83°E. 360 lks. dist., mkd. ¼ S BT . Additionally mark ¼ S27 BT
	New bearing tree:
	A pine, 4 ins. diam., bears S.81¼°W. 127 lks. dist., mkd. ¼ S28 BT
	N.0°08'E., beginning new measurement.
	Desc. 35 ft. over NW. slope.
2.95	Old road, bears NW. and SE.
10.00	Change of slope to W., desc. 30 ft.
13.30	Enter heave timber, bears NW. and SE.
27.50	Wash, 12 lks. wide, 3 ft. deep, course N.15°E.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

37.40 Bend in same wash, course N.1°E., from S.5°E.

39.96 The cor. of secs. 21, 22, 27 and 28, evidenced by the original monument, a lava stone 18 x 12 x 10 ins., firmly set, mkd. with 2 notches on the S. and 3 notches on the E. edges, and witnessed by a mound of stone 2 ft. base; 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

T25N	R5E
S 21	S 22
S 28	S 27

1944

from which

Original bearing trees:

A pinon, 14 ins. diam., bears N.80 $\frac{3}{4}$ °E. 83 lks. dist. blaze overgrown. Remark T25N R5E S22 BT

A pinon, 10 ins. diam., dead and fallen, and partly decayed, bears S.47 $\frac{1}{4}$ °E. 140 lks. dist.,

A pinon, 18 ins. diam., bears S.85 $\frac{1}{2}$ °W. 144 lks. dist. blaze overgrown. Remark T25N R5E S28 BT

A pinon, 12 ins. diam., bears N.30 $\frac{1}{2}$ °W. 108 lks. dist., blaze overgrown. Remark T25N R5E S21 BT

New bearing tree:

A pinon, 5 ins. diam., bears S.52 $\frac{1}{4}$ °E. 106 lks. dist., mkd. T25N R5E S27 BT

Land, rolling.

Soil, rocky, 2nd. and 3rd. rate.

Timber, pinon, juniper and yellow pine; 2nd. growth.

From the cor. of secs. 22, 23, 26 and 27.

N.89°46'W. bet. secs. 22 and 27.

Over rolling land, through scattered timber.

21.30 Low spur, slopes N.25°E.

25.70 Graded road, bears NW. to Grand Canyon and SE. to Flagstaff.

26.50 Enter heavy timber, bears NW. and SE.

28.70 Leave timber, bears NW. and SE.

38.82 The $\frac{1}{4}$ sec. cor., evidenced by a malpais stone 16 x 16 x 10 ins., firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the N.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone buried alongside, with brass cap mkd.

$\frac{1}{4}$	S 22
	S 27

1944

Resurvey of the Subdivision of T.25 N., R.5 E.

ECOR 4886

Chains		from which
	An original bearing tree:	
	A pinon, 8 ins. diam., dead and fallen, bears N.53 $\frac{1}{4}$ °E. 103 lks. dist., mkd. $\frac{1}{4}$ S BT	
	New bearing trees:	
	A juniper, 10 ins. diam., bears N.12 $\frac{1}{2}$ °W. 106 lks. dist., mkd. $\frac{1}{4}$ S22 BT	
	A pinon, 9 ins. diam., bears S.74 $\frac{1}{4}$ °E. 92 lks. dist., mkd. $\frac{1}{4}$ S27 BT	
	A log cabin, unoccupied and abandoned, bears N.38°W. 3.20 chs. dist.	
	N.89°43'W., beginning new measurement.	
0.04	An old brush fence, bears NW. and S.	
1.20	A brush fence, bears NE. and SW.	
2.90	Wash, 12 lks. wide, course NE.	
6.80	A brush fence, bears NW. and SE.	
8.40	A brush fence, bears NE. and SW.	
10.50	Small spur, slopes NE., An old roadway, bears NE. and SW. Desc. slightly over NW. slope.	
40.08	Wash, 3 lks. wide, course N.	
40.20	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, rocky, 2nd. and 3rd. rate. Timber, pinon, juniper and yellow pine; 2nd. growth.	

	N.0°03'E. bet. secs. 21 and 22. Over slightly rolling land, through heavy timber. Desc. gradually over NE. slope.	
28.00	Earthen tank, or reservoir, 2.50 chs. in diam., bears E. 5 chs. dist. Ascend slightly.	
39.96	The $\frac{1}{4}$ sec. cor., evidenced by a malpais stone, 16 x 14 x 8 ins., firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.	
	$\frac{1}{4}$ S 21 S 22 1944	from which
	Original bearing trees:	

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

A juniper, 9 ins. diam., bears N.79 $\frac{3}{4}$ °E. 101 lks. dist. mkd. $\frac{1}{4}$ S BT

A juniper, 10 ins. diam., bears S.42 $\frac{3}{4}$ °E. 103 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S22 BT

New bearing tree:

A pinon, 4 ins. diam., bears S.64 $\frac{1}{4}$ °W. 129 lks. dist., mkd. $\frac{1}{4}$ S21 BT

N.0°17'E., beginning new measurement.

- 4.00 Drain, course NE.
 5.05 Road, bears E. and W.
 31.50 Draw, 1 ch. wide, course NE.
 39.89 The cor. of secs. 15, 16, 21 and 22, evidenced by the original monument, a lava stone 18 x 10 x 10 ins., firmly set, mkd. with 4 notches on the S. and 3 notches on the E. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone buried alongside, with brass cap mkd.

T25N	R5E
S 16	S 15
S 21	S 22

1944

from which

A pinon, 3 ins. diam., bears N.75 $\frac{1}{4}$ °E. 30 lks. dist., mkd. BT

A juniper, 3 ins. diam., bears S.41°E. 23 lks. dist., mkd. BT

A pinon, 3 ins. diam., bears S.48°W. 52 lks. dist., mkd. BT

A juniper, 5 ins. diam., bears N.75 $\frac{3}{4}$ °W., 117 lks. dist., mkd. T25N R5E S16 BT

Land, gently rolling.
 Soil, rocky, 2nd. and 3rd. rate.
 Timber, juniper and pinon; 2nd. growth.

 From the cor. of secs. 14, 15,,22 and 23.

N.89°37'W., bet. secs. 15 and 22.

Over rolling land, through heavy growth of timber. Desc. 10 ft. over NW. slope.

- 9.00 Wash, 8 lks. wide, course N.10°E. Asc. slightly over gentle E. slope.
 39.42 Point for $\frac{1}{4}$ sec. cor., at proportionate distance.
 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

Resurvey of the Subdivision of T.25 N., R.5 E.
BOOK 4356

Chains

$$\frac{1}{4} \begin{array}{l} S 15 \\ S 22 \end{array}$$

1944

from which

A juniper, 5 ins. diam., bears N.19 $\frac{1}{2}$ °E. 108 lks. dist.
mkd. $\frac{1}{4}$ S15 BT

A pinon, 10 ins. diam., bears S.61°E. 67 lks. dist.,
mkd. $\frac{1}{4}$ S22 BT

64.80 Top of ascent, bears N. and S., Desc. 40 ft. over W. slope.

75.30 Draw, 150 lks. wide, course N.20°W.

76.40 Graded road, bears NW. to Grand Canyon and S.20°E. to Flagstaff.

78.84 The cor. of secs. 15, 16, 21 and 22.

Land, slightly rolling.
Soil, rocky, 2nd. and 3rd. rate.
Timber, pinon and juniper; 2nd. growth.

N.0°03'W. bet. secs. 15 and 16.

Over nearly level land, through heavy growth of timber.

4.20 Graded road, bears NW. to Grand Canyon and SE. to Flagstaff.

16.00 Enter shallow draw, course N. from S.20°E. Desc. slightly.

39.74 The $\frac{1}{4}$ sec. cor., evidenced by a malpais stone 18 x 10 x 8 ins., firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 16 \\ S 15 \end{array}$$

1944

from which

Original bearing trees:

A pinon, 12 ins. diam., bears N.15°E. 139 lks. dist.,
blaze overgrown; remark $\frac{1}{4}$ S15 BT

A juniper, 20 ins. diam., bears S.18 $\frac{3}{4}$ °W., 97 lks.
dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S16 BT

N.2°30'W., beginning new measurement,

2.30 Leave draw, drains N.20°W., Asc. 25 ft. over SW. slope.

5.00 Top of ascent. Desc. slightly over gentle W. slope.

32.70 Enter same draw, course N.20°E.

37.96 The cor. of secs. 9, 10, 15 and 16, evidenced by the

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

original monument, a lava stone 14 x 8 x 6 ins., firmly set, mkd. with 4 notches on the S. and 3 notches on the E. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 in. diam., 28 ins. in the ground, with original corner stone deposited at base, with brass cap mkd.

T25N	R5E
S 9	S 10
S 16	S 15

1944

from which

Original bearing trees:

A juniper, 12 ins. diam., bears N.15 $\frac{1}{4}$ °E. 55 lks. dist. mkd. T25N R5E S10 BT

A juniper, 14 ins. diam., bears N.39°E. 101 lks. dist. mkd. T25N R5E S10 BT

A juniper, 10 ins. diam., bears S.73 $\frac{1}{2}$ °E. 138 lks. dist. mkd. T25N R5E S15 BT

A juniper, 18 ins. diam., bears S.81°E. 147 lks. dist. mkd. T25N R5E S

New bearing trees:

A juniper, 12 ins. diam., bears S.7°W., 329 lks. dist. mkd. T25N R5E S16 BT

A juniper, 10 ins. diam., bears N.84°W. 382 lks. dist. mkd. T25N R5E S9 BT

Land, slightly rolling.
Soil, rocky, 2nd. and 3rd. rate.
Timber, pinon, juniper; 2nd. growth.

From the cor. of secs. 10, 11, 14 and 15.

S.89°00'W. bet. secs. 10 and 15.

Over slightly rolling land, through scattered timber.

- 4.10 Old road, bears NW. and SE., in shallow draw, draining NW.
9.00 Road, bears NW. and SE.
16.50 Enter dense growth of timber, bears N. and S.
40.28 Point for $\frac{1}{4}$ sec. cor., at proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$	S 10
	S 15

1944

from which

A pinon, 10 ins. diam., bears N.73 $\frac{1}{2}$ °E. 45 lks. dist. mkd. $\frac{1}{4}$ S10 BT

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4356

Chains

A juniper, 5 ins. diam., bears S.26 $\frac{1}{2}$ °W. 45 lks. dist.
mkd. $\frac{1}{4}$ S15 BT

65.00 Top of slight ascent, bears N. and S. Desc. 25 ft. over gentle NW. slope.

79.00 Enter shallow draw, course N.

80.56 The cor. of secs. 9, 10, 15 and 16.

Land, slightly rolling.
Soil, rocky, 2nd. and 3rd. rate.
Timber, pinon and juniper; 2nd. growth.

N.0°27'E., bet. secs. 9 and 10.

Over nearly level land, through heavy growth of timber.
Desc. slightly.

3.40 Old road, bears E. and W.

25.00 Enter scattered timber, bears NE. and SW.

39.79 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 10 x 10 x 10 ins., firmly set, mkd. $\frac{1}{4}$ on the W, face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$\frac{1}{4}$
S 9 | S 10
1944

from which

A pinon, 24 ins. diam., bears N.22°E. 336 lks. dist.,
mkd. $\frac{1}{4}$ S10 BT

A pinon, 3 ins. diam., bears N.24 $\frac{1}{4}$ °W. 143 lks. dist.,
mkd. $\frac{1}{4}$ S9 BT

N.0°05'E., beginning new measurement.

4.00 Enter heavy growth of timber, bears E. and W.

25.00 Enter scattered timber, bears E. and W.

39.68 The cor. of secs. 3, 4, 9 and 10, evidenced by the original monument, a lava stone 16 x 10 x 6 ins., firmly set, mkd. with 5 notches on the S. and 3 notches on the E. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone buried alongside, with brass cap mkd.

T25N R5E
S 4 | S 3

S 9 | S 10
1944

from which

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

Original bearing trees:

A juniper, 10 ins. diam., bears N. $8\frac{1}{4}^{\circ}$ E. 77 lks. dist.
mkd. T25N R5E S3 BT

A pinon, 12 ins. diam., bears N. $53\frac{1}{2}^{\circ}$ E. 100 lks. dist.
mkd. T25N R5E S3 BT

A juniper, 12 ins. diam., bears N. $76\frac{3}{4}^{\circ}$ E. 107 lks.
dist., mkd. T25N R5E S3 BT

A juniper, 12 ins. diam., bears S. $88\frac{1}{4}^{\circ}$ E. 75 lks. dist.
mkd. T25N R5E S; remaining marks overgrown. Addition-
ally mark T25N R5E S10 BT

New bearing trees:

A juniper, 8 ins. diam., bears S. $18\frac{3}{4}^{\circ}$ W. 351 lks. dist.
mkd. T25N R5E S9 BT

A juniper, 8 ins. diam., bears N. $81\frac{3}{4}^{\circ}$ W. 419 lks. dist.
mkd. T25N R5E S4 BT

Land, nearly level.

Soil, rocky, 2nd. and 3rd. rate.

Timber, juniper and pinon; 2nd. growth.

From the cor. of secs. 2, 3, 10 and 11.

S. $86^{\circ}53'$ W. bet. secs. 3 and 10.

Over open level land.

14.00 Old road, bears NW. and SE., in swale draining NW.

40.44 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone, 12 x 8 x 6
ins., firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by
a mound of stone 2 ft. base, 6 ins. high, to the N.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with original corner stone buried alongside, with
brass cap mkd.

$$\frac{1}{4} \frac{S \ 3}{S \ 10}$$

1944

from which

Original bearing trees:

A pinon, 14 ins. diam., bears S. $89\frac{1}{4}^{\circ}$ W. 159 lks. dist.
mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S10 BT

A juniper, 24 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ W. 223 lks.
dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S3 BT

N. $87^{\circ}43'$ W., beginning new measurement.

1.50 Enter scattered timber, bearing N. and S. Asc. 25 ft.

11.00 Enter heavy timber, bears N. and S.

16.50 Top of ascent, continue over nearly level land, draining
N.,

39.54 The cor. of secs. 3, 4, 9 and 10.

Resurvey of the Subdivision of T.25 N., R.5 E.

B. O. N. 1936

Chains

Land, level.
Soil, rocky, 2nd. and 3rd. rate.
Timber, juniper and pinon; 2nd. growth.

N.1°02'W., bet. secs. 3 and 4.

Over nearly level land, through heavy timber. Desc. slightly.

39.81 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 16 x 12 x 6 ins. firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$\frac{1}{4}$
S 4 | S 3
1944

from which

Original bearing trees:

A pinon, 16 ins. diam., bears S.40 $\frac{3}{4}$ °E. 66 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S3 BT

A pinon, 10 ins. diam., bears S.43 $\frac{1}{2}$ °W. 59 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S4 BT

N.1°04'W., beginning new measurement.

Desc. slightly over open NE. slope.

8.00 Swale, draining NW. Old road, bears NW. and SE. Asc. slightly.

15.50 Enter heavy timber, bears NW. and SE.

39.76 The cor. of secs. 3 and 4, on the N. bdy. of the Tp., evidenced by the original monument, a limestone 16 x 14 x 10 ins., firmly set, mkd. with 3 grooves on the E. and W. faces.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the to bedrock, with original corner stone deposited at base, and in a mound of stone to top, with brass cap mkd.

T26N R5E
S 34

S 4 | S 3
T25N R5E

1944

from which

Original bearing trees:

A pinon, 10 ins. diam., bears S.49 $\frac{3}{4}$ °E. 203 lks. dist. mkd. T25N R5E S3 BT

A pinon, 9 ins. diam., bears S.79 $\frac{1}{2}$ °W. 80 lks. dist., mkd. T25N R5E S4 BT

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

New bearing tree:

A juniper, 8 ins. diam., bears S.45 $\frac{1}{2}$ °W. 226 lks. dist. mkd. T25N R5E S4 BT

The cor. of secs. 33 and 34, T.26 N., R.5 E., bears N.85°51'W., 0.00 chs. dist., marked by a 3 in. iron post, conforming to the 1916 resurvey record.

A four wire fence line, extending E. and W. bears N. 4 lks. dist.

Land, nearly level.

Soil, rocky, 2nd. and 3rd. rate.

Timber, pinon and juniper; 2nd. growth.

At the $\frac{1}{4}$ sec. cor., on the N. bdy. of sec. 3, evidenced by the original monument, a limestone 14 x 12 x 5 ins., firmly set, mkd. $\frac{1}{4}$ on the N. face,

Set an iron post, on limestone ledge, with original corner stone deposited at base, supported in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$ S 3

1944

from which

Original bearing trees:

A pinon, 7 ins. diam., bears S.55 $\frac{1}{2}$ °E. 67 lks. dist. mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S3 BT

A pinon, 8 ins. diam., bears S.79°W. 24 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S3 BT

From this corner:

The $\frac{1}{4}$ sec. cor. of sec. 34, T.26 N., R.5 E., bears N.89°56'W., 0.33 chs. dist., marked by an iron post, 1 in. diam., conforming to the 1916 resurvey record; and the cor. of secs. 3 and 4 bears N.89°56'W. 39.53 chs. dist.

The cor. of secs. 2 and 3, bears N.89°51'E. 39.83 chs. dist.

A four wire fence, extending E. and W. bears south 6 lks. dist.

From the standard cor. of secs. 32 and 33, on S. bdy. of T., N.2°07'E. bet. secs. 32 and 33. Over rolling land, through heavy growth of timber. Desc. 85 ft. over NW. slope.

- 5.70 Head of ravine, course W.
- 21.00 Ravine, course W.
- 32.00 Enter scattered timber, bears NE. and SW.
- 49.70 The $\frac{1}{4}$ sec. cor., evidenced by a malpais stone 22 x 20 x 18 ins., firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Resurvey of the Subdivision of T.25 N., R.5 E.

PLAT 4650

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\frac{1}{4}$$

S 32		S 33
1944		

from which

Original bearing trees:

A pinon, 20 ins. diam., bears S.16 $\frac{1}{4}$ °E. 254 lks. dist. mkd. $\frac{1}{4}$ S BT. Additionally mark $\frac{1}{4}$ S33 BT

A juniper, 14 ins. diam., bears S.8°E. 227 lks. dist., mkd. $\frac{1}{4}$ S BT

New bearing tree:

A pine, 5 ins. diam., bears N.7 $\frac{3}{4}$ °W. 222 lks. dist., mkd. $\frac{1}{4}$ S32 BT

N.3°25'W., beginning new measurement.

Desc. 10 ft.

3.00 Enter heavy timber, bears NE. and SW.

5.70 Drain, 20 lks. wide, course NE. Asc. 40 ft. over SE. slope.

18.00 Low spur, slopes E. Desc. 10 ft.

22.75 Drain, course S.70°E. Asc. 65 ft. over SW. slope.

39.67 The cor. of secs. 28, 29, 32 and 33, evidenced by the original monument, a lava stone 16 x 16 x 8 ins., firmly set, mkd. with 1 notch on the S. and 4 notches on the E. edges, and witnessed by a mound of stone 2 $\frac{1}{2}$ ft. base, 2 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\begin{array}{cc} \text{T25N} & \text{R5E} \\ \text{S } 29 & | \text{S } 28 \\ \hline \text{S } 32 & | \text{S } 33 \end{array}$$

1944

from which

Original bearing trees:

A pinon, 14 ins. diam., bears N.14 $\frac{1}{2}$ °E. 39 lks. dist., mkd. T25N R5E S28 BT

A pinon, 10 ins. diam., bears S.29 $\frac{1}{2}$ °E. 7 lks. dist., mkd. T25N R5E S33 BT

A pinon, 14 ins. diam., bears S.50 $\frac{1}{2}$ °W. 10 lks. dist., mkd. T25N R5E S32 BT

A pinon, 16 ins. diam., bears N.27°W. 81 lks. dist., mkd. T25N R5E S29 BT

Land, rolling.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains	
	Soil, rocky, 2nd. and 3rd. rate. Timber, pinon, juniper, yellow pine; 2nd. growth.

	From the cor. of secs. 27, 28, 33 and 34. S.89°51'W. bet. secs. 28 and 33. Over rolling land, through heavy growth of timber. Asc. 57 ft. over E. slope.
7.60	Spur, slopes N. Desc. 20 ft. over NW. slope.
16.50	Small spur, slopes N., Desc. 100 ft. over W. slope.
20.00	Enter scattered timber, bears N. and S.
39.91	The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 16 x 16 x 8 ins., firmly set, mkd. $\frac{1}{4}$ on the N. face. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.
	$\frac{1}{4}$ $\frac{S\ 28}{S\ 33}$
	1944
	from which
	Original bearing trees:
	A pine, 30 ins. diam., bears S.28 $\frac{1}{2}$ °E. 177 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S33 BT
	A pine, 36 ins. diam., bears S.12 $\frac{1}{2}$ °E. 136 lks. dist., blaze overgrown..
	New bearing tree:
	A pine, 6 ins. diam., bears N.36 $\frac{1}{2}$ °W. 62 lks. dist., mkd. $\frac{1}{4}$ S28 BT
	N.89°29'W., beginning new measurement.
0.50	Drain, 5 lks. wide, course NE. Asc. 20 ft. over slightly rolling land.
20.00	Enter scattered timber, bears N. and S.
31.00	Drain, 20 lks. wide, course S.70°E. Asc. 45 ft. over NE. slope.
39.94	The cor. of secs. 28, 29, 32 and 33. Land, rolling. Soil, rocky, 2nd. and 3rd. rate. Timber, pinon, juniper, pine; 2nd. growth.

	N.1°56'E. bet. secs. 28 and 29. Over mountainous land, through heavy growth of timber. Desc. 10 ft.
3.50	Drain, course S.80°E.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4850

Chains

Asc. 450 ft. over broken SE. slope.

39.64 Point for $\frac{1}{4}$ sec. cor., at proportionate dist.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 29 \mid \text{S } 28 \\ 1945 \end{array}$$

from which

A pinon, 12 ins. diam., bears N.64³°E. 37 lks. dist., mkd. $\frac{1}{4}$ S28 BTA pinon, 10 ins. diam., bears S.28°W. 50 lks. dist., mkd. $\frac{1}{4}$ S29 BT

Continue ascent 230 ft. over SE. slope.

42.40 Head of ravine, course SE.

56.50 Spur, slopes E. Top of Red Mountain bears W. about 30 chs. dist.

Desc. 280 ft. over precipitous N. slope.

65.50 Gulch, course E. Asc. 50 ft. over S. slope.

67.60 Spur, slopes E. Desc. 250 ft. over NW. slope.

79.28 Point for cor. of secs. 20, 21, 28 and 29, determined from the original bearing trees:

A pine, 30 ins. diam., bears S.2 $\frac{1}{2}$ °W. 129 lks. dist., original blaze overgrown. Remark T25N R5E S29 BTA pinon, 12 ins. diam., bears S.16 $\frac{1}{2}$ °W. 62 lks. dist., mkd. T25N R5E S29 BT

A pinon, 10 ins. diam., bears N.83°W. 68 lks. dist., blaze overgrown. Remark T25N R5E S20 BT

A pine stump, 18 ins. diam., bears N.54°W. 38 lks. dist. No marks remain.

At corner point,

Set a brass tablet $3\frac{1}{2}$ in. diam., 3 in. stem, cemented in solid rock, and marked
$$\begin{array}{c} \text{T25N R5E} \\ \text{S } 20 \mid \text{S } 21 \\ \text{S } 29 \mid \text{S } 28 \\ 1945 \end{array}$$

from which

A pinon, 12 ins. diam. bears N.42³°E. 154 lks. dist., mkd. T25N R5E S21 BT

A pinon, 8 ins. diam. bears S.75°E. 185 lks. dist., mkd. T25N R5E S28 BT

A small spring of water, in canyon bottom, bears N.34°W. 6.50 chs. dist.

Land, mountainous.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

Soil, rocky, 3rd. rate.
Timber, pinon, juniper and pine; 2nd. growth.

From the cor. of secs. 21, 22, 27 and 28.
S. 89° 43' W. bet. secs. 21 and 28.
Over mountainous land, through heavy growth of timber.

14.00 Old road, bears NW. and SE.

25.00 Drain, course NE. Asc. 130 ft. over E. slope.

35.00 Enter scattered timber, bears N. and S.

36.30 Wash, 10 lks. wide, 3 ft. deep, course NE.

38.57 Point for $\frac{1}{4}$ sec. cor., at proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S } 21 \\ \text{S } 28 \end{array}$$

1945

from which

A pinon, 8 ins. diam., bears N. 23° E. 64 lks. dist.,
mkd. $\frac{1}{4}$ S21 BT

A pinon 6 ins. diam., bears S. 55 $\frac{1}{2}$ ° E. 57 lks. dist.,
mkd. $\frac{1}{4}$ S28 BT

Asc. 400 ft. over SE. slope.

48.30 Enter heavy timber, bears NE. and SW.

70.60 Spur, slopes NE. Desc. 100 ft. over NW. slope.

77.14 The cor. of secs. 20, 21, 28 and 29.

Land, rolling and mountains.
Soil, rocky, 3rd. rate.
Timber, pinon, juniper, pine; 2nd. growth.

N. 0° 15' E. bet. secs. 20 and 21.

Over mountainous land, through heavy growth of timber.

Desc. NW. slope.

17.90 Bottom of canyon, course NE. Asc. 12 ft.

22.90 Spur, slopes E. Desc. 125 ft. over rolling NE. slope.

39.23 The $\frac{1}{4}$ sec. cor., evidenced by a sandstone 14 x 12 x 5 ins.
firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a
mound of stone 2 ft. base, 1 $\frac{1}{2}$ ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S } 20 \mid \text{S } 21 \\ 1945 \end{array}$$

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4356

Chains

from which

Original bearing tree:

A juniper, 16 ins. diam., bears N.64 $\frac{3}{4}$ °E. 154 lks. dist., blaze overgrown; Remark $\frac{1}{4}$ S21 BT

New bearing tree:

A pinon, 12 ins. diam., bears S.63 $\frac{1}{2}$ °W. 54. lks. dist., mkd. $\frac{1}{4}$ S20 BT

N.0°44'W., beginning new measurement.

Desc. 65 ft. through scattered timber.

10.00 Dim roadway, bears E. and W.

12.50 Ravine, drains E. Asc. 30 ft.

26.50 Spur, slopes NE. Continue over nearly level land.

39.51 The cor. of secs. 16, 17, 20 and 21, evidenced by the original monument, a lava stone 14 x 10 x 10 ins., firmly set, mkd. with 3 notches on the S. and 4 notches on the E. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

T25N R5E	
S 17	S 16
S 20	S 21

1945

from which

An original bearing tree:

A pinon, 24 ins. diam., bears N.71 $\frac{1}{2}$ °W. 148 lks. dist. blaze overgrown; Remark T25N R5E S17 BT

New bearing trees:

A pinon, 16 ins. diam., bears N.65 $\frac{1}{2}$ °E. 169 lks. dist. mkd. T25N R5E S16 BT

A pinon, 8 ins. diam., bears S.18°E. 130 lks. dist., mkd. T25N R5E S21 BT

A juniper, 5 ins. diam., bears S.11 $\frac{3}{4}$ °W. 76 lks. dist., m kd. T25N R5E S20 BT

Land, rolling.

Soil, rocky clay, 3rd. and 4th. rate.

Timber, pine, pinon, juniper, and 2nd. growth.

From the cor. of secs. 15, 16, 21 and 22.

S.88°51'W. bet. secs. 16 and 21.

Over rolling land, through heavy growth of timber.

32.00 Spur, slopes NE.

38.88 Point for $\frac{1}{4}$ sec. cor., at proportionate dist.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 16 \\ S 21 \end{array}$$

1945

from which

A pinon, 15 ins. diam., bears N.70 $\frac{1}{4}$ °W. 75 lks. dist., mkd. $\frac{1}{4}$ S16 BT

A pinon, 10 ins. diam., bears S.39 $\frac{1}{4}$ °W. 68 lks. dist., mkd. $\frac{1}{4}$ S21 BT

39.00 Old road, bears N.10°W. and S.10°E.

40.05 Wash, 10 lks. wide, course N. Asc. 135 ft.

65.50 Spur, slopes NE. Desc. slightly.

77.76 The cor. of secs. 16, 17, 20 and 21.

Land, rolling.

Soil, rocky, 3rd. rate.

Timber, pinon; juniper and 2nd. growth.

Undergrowth, a few grasses.

N.0°20'E. bet. secs. 16 and 17.

Over rolling land, through heavy growth of timber.

5.10 Wash, 10 lks. wide, course SE.

10.00 Small spur, slopes SE. Desc. 90 ft. over gradual slope.

15.00 Enter scattered timber, bears E. and W.

24.00 Head of draw, course NE.

28.17 Corner of wire fencing, extending S.55°W. and irregularly N., bears W. 50 lks. dist.

30.00 Low spur, slopes E.

39.87 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 15 x 12 x 8 ins. firmly set, mkd. $\frac{1}{4}$ on the W. face.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, to bedrock, with original corner stone deposited alongside, and in a mound of stone to top, with brass cap mkd.

$$\frac{1}{4} \begin{array}{c} S 17 \\ | \\ S 16 \end{array}$$

1945

from which

Original bearing trees:

A cedar, 8 ins. diam. beard N.13°W. 125 lks. dist., blaze overgrown.

A cedar, 16 ins. diam. bears N.70 $\frac{3}{4}$ °W. 157 lks. dist., mkd. $\frac{1}{4}$ S BT. Additionally mark $\frac{1}{4}$ S17 BT

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4856

Chains

New bearing tree:

A cedar, 5 ins. diam., bears N.69³°E. 12 lks. dist.,
mkd. $\frac{1}{4}$ S16 BT

N.0°38'E., beginning new measurement.

Desc. 45. ft. over NW. slope, along wire fencing.

7.30 Draw, course NE. Asc. 55 ft.

16.60 Rocky spur, slopes E. Desc. 140 ft.

37.72 Graded road, bears NW. to Grand Canyon and SE. to Flagstaff, at cattle guard, in wire fencing, extending N. and S.

39.32 The cor. of secs. 8, 9, 16 and 17, evidenced by the original monument, a lava stone 10 x 8 x 8 ins., firmly set, mkd. with 4 notches on the S. and E. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 in. diam., 28 ins. in the ground, with original corner stone buried alongside, with brass cap mkd.

T25N R5E

S 8	S 9
S 17	S 16

1945

from which

Original bearing trees:

A cedar, 10 ins. diam., bears N.82 $\frac{1}{2}$ °E. 171 lks. dist.
mkd. T25N R5E S9

A cedar, 12 ins. diam., bears S.82 $\frac{1}{2}$ °E. 262 lks. dist.
mkd. T25N R5E S16 BT

A cedar, 14 ins. diam., bears N.40°W. 145 lks. dist.,
blaze overgrown. Remark T25N R5E S8 BT

New bearing tree:

A cedar, 6 ins. diam., bears S.23 $\frac{1}{2}$ °W. 19 lks. dist.,
mkd. T25N R5E S17 BT

Wire fence, bearing N. and S., bears E. 1 lk. dist.

Land, rolling.

Soil, rocky, 3rd. rate.

Timber, pinon, juniper; 2nd. growth.

Undergrowth, scattered gamma grass.

From the cor. of secs. 9, 10, 15 and 16.

S.86°46'W., bet. secs. 9 and 16.

Over nearly level land, through heavy growth of timber.

3.10 Drain, 5 lks. wide, course N.

35.80 The $\frac{1}{4}$ sec. cor., evidenced by a dilapidated mound of stone $1\frac{1}{2}$ ft. base, 4 ins. high.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S \ 9}{S \ 16}$$

1945

from which

Original bearing trees:

A pinon, 14 ins. diam., bears South, 12 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S16 BT

A cedar, 14 ins. diam., bears S.81 $\frac{1}{2}$ °W. 39 lks. dist., blaze overgrown.

New bearing tree:

A cedar, 10 ins. diam., bears N.39 $\frac{3}{4}$ °E., 188 lks. dist. mkd. $\frac{1}{4}$ S9 BT

N.87°23'W., beginning new measurement.

34.30 Old road, bears NW. and SE.

39.76 The cor. of secs. 8, 9, 16 and 17.

Land, level.

Soil, rocky, 3rd. rate.

Timber, pinon, cedar; 2nd. growth.

N.0°06'W., bet. secs. 8 and 9.

Over nearly level land, through heavy timber; along fence line, extending N.

2.70 Old road, bears NW. and SE.

39.98 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 8 x 8 x 5 ins., firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 1 $\frac{1}{2}$ ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\frac{1}{4} \frac{S \ 8 \ | \ S \ 9}{1945}$$

1945

from which

Original bearing trees:

A juniper, 16 ins. diam., bears S.24 $\frac{1}{4}$ °E. 218 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S9 BT

A juniper, 18 ins. diam., bears S.87 $\frac{1}{2}$ °W. 109 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S8 BT

N.0°04'W., beginning new measurement.

39.82 The cor. of secs. 4, 5, 8 and 9, evidenced by the original monument, a lava stone 12 x 10 x 8 ins., firmly set, mkd.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4856

Chains

with 5 notches on the S. and 1 notch on the N. edges, and witnessed by a mound of stone $1\frac{1}{2}$ ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground, to bedrock, with original corner stone deposited alongside, and in a mound of stone to top, with brass cap mkd.

T25N		R5E	
S	5	S	4
S	8	S	9

1945

from which

Original bearing trees:

A pinon, 18 ins. diam., bears N.85°E. 118 lks. dist., mkd. T25N R5E S4 BT

A pinon, 14 ins. diam., bears S.23 $\frac{1}{2}$ °E. 32 lks. dist., marks overgrown. Remark T25N R5E S9 BT on overgrowth.

A pinon, 14 ins. diam., bears S.38 $\frac{3}{4}$ °W. 90 lks. dist., mkd. T25N R5E S8 BT

A pinon, 24 ins. diam., bears N.72 $\frac{1}{2}$ °W. 56 lks. dist., mkd. T25N R5E S5 BT

New bearing tree:

A pinon, 20 ins. diam., bears N.14°E. 110 lks. dist., mkd. T25N R5E S4 BT

Wire fencing, extending N. and S., bears E. 1 lk. dist.

Land, nearly level.

Soil, rocky, 3rd. rate.

Timber, pinon and cedar; 2nd. growth.

From the cor. of secs. 3, 4, 9 and 10.

N.84°11'W., bet. secs. 4 and 9.

Over slightly rolling land, through heavy growth of timber.

30.90 Ditch, 10 lks. wide, 2 ft. deep, course NW.

36.93 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 16 x 14 x 10 ins., firmly set, mkd. $\frac{1}{4}$ on the N. face.

Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground, to bedrock, with original corner stone deposited alongside, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$	S	4
	S	9

1945

from which

Original bearing trees:

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

A pinon, 16 ins. diam., bears S.63½°W. 68 lks. dist.,
mkd. ¼ S BT . Additionally mark ¼ S9 BT

A juniper, 12 ins. diam., bears S.85¾°E. 63 lks.
dist., mkd. ¼ S BT

New bearing tree:

A pinon, 8 ins. diam., bears N.14°E. 63 lks. dist.,
mkd. ¼ S4 BT

S.85°04'W., beginning new measurement.

Continue over nearly level land, through heavy timber.

39.36 The cor. of secs. 4, 5, 8 and 9.

Land, level.

Soil, rocky, 3rd. rate.

Timber, pinon, juniper and 2nd. growth.

N.0°05'E., bet. secs. 4 and 5.

Over slightly rolling land, through heavy growth of timber.
Along wire fence, extending N.

39.84 The ¼ sec. cor., evidenced by a lava stone 16 x 14 x 3 ins.
firmly set, mkd. ¼ on the W. face, and witnessed by a
mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with original corner stone deposited at base, with
brass cap mkd.

¼
S 5 | S 4
1945

from which

An original bearing tree:

A pinon, 28 ins. diam., bears S.15½°E. 100 lks. dist.
mkd. ¼ S BT . Additionally mark ¼ S4 BT

New bearing tree:

A pinon, 5 ins. diam., bears S.73¼°W. 197 lks. dist.
mkd. ¼ S5 BT

Wire fencing extends N. and S. from corner.

N. 0°21'E., beginning new measurement.

40.11 The cor. of secs. 4 and 5, on the N. bdy. of the Tp.,
evidenced by the original monument, a hewed pinon post,
3 ins. square, 30 ins. long, firmly set, with traces of
pits in each section.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, with original corner post deposited alongside,
with brass cap mkd.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 457

Chains

T26N R5E

S 33

S 5 | S 4

T25N R5E

1945

Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of corner.

The cor. of secs. 32 and 33, T.26 N., R.5 E., bears N.88°59'W., 6.57 chs. dist., marked by an iron post, 3 ins. diam., conforming to the 1916 resurvey record.

Land, level.

Soil, rocky, 3rd. rate.

Timber, pinon, juniper and 2nd. growth.

At the ¼ sec. cor., on the N. bdy. of sec. 4, evidenced by a malpais stone 10 x 6 x 3 ins., firmly set, mkd. ¼ on the N. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the S.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, with the original corner stone buried alongside, and in a mound of stone to top, with brass cap mkd.

¼ S 4

1945

The ¼ sec. cor. of sec. 33, T.26 N., R.5 E., bears S.87°10'W., 5.83 chs. dist., marked by an iron post, 1 in. diam., conforming to the 1916 resurvey record; and the cor. of secs. 4 and 5, bears S.87°10'W. 39.31 chs. dist.

The cor. of secs. 3 and 4, bears S.85°51'E., 35.05 chs. dist.

From the standard cor. of secs. 31 and 32, on S. bdy. of Tp. described in the field notes of T.24 N., R.5 E., N.1°43'E., bet. secs. 31 and 32.

Over rolling land, through scattered timber.

18.70 Enter heavy growth of timber, bears E. and W.

19.00 Desc. 40 ft. over N. slope.

21.70 Wash, 30 lks. wide, course W. Asc. slightly.

27.30 Small spur, slopes SW.

30.40 Draw, course SW. Asc. 20 ft.

49.05 The ¼ sec. cor., evidenced by a lava stone 10 x 8 x 6 ins. firmly set, mkd. ¼ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original corner stone buried alongside,

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 31 \mid \text{S } 32 \\ 1945 \end{array}$$

from which

Original bearing trees:

A pinon, 14 ins. diam., bears S. $35\frac{1}{4}^{\circ}$ E. 10 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S32 BT

A pinon, 12 ins. diam., bears N. 10° W., 7 lks. dist., mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S31 BT

N. $0^{\circ} 31' W.$, beginning new measurement.

- 2.50 Small spur, slopes W.
- 26.00 Small spur, slopes W. Desc. 40 ft.
- 30.00 Shallow draw, course SW. Asc. 70 ft. over SE. slope.
- 39.63 The cor. of secs. 29, 30, 31 and 32, evidenced by the original monument, a lava stone 14 x 11 x 8 ins., firmly set, mkd. with 1 notch on the S. and 5 notches on the E. faces.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\begin{array}{c} \text{T25N R5E} \\ \text{S } 30 \mid \text{S } 29 \\ \hline \text{S } 31 \mid \text{S } 32 \\ 1945 \end{array}$$

from which

Original bearing trees:

A pinon, 8 ins. diam., bears S. 69° E. 49 lks. dist., mkd. T25N R5E S32 BT

A pinon, 12 ins. diam., bears S. $29\frac{1}{2}^{\circ}$ W. 5 lks. dist., mkd. T25N R5E S31 BT

New bearing trees:

A pinon, 6 ins. diam., bears N. 16° W. 56 lks. dist., mkd. T25N R5E S30 BT

A pinon, 5 ins. diam., bears N. $18\frac{1}{2}^{\circ}$ E. 39 lks. dist., mkd. T25N R5E S29 BT

Land, rolling.

Soil, gravelly and rocky, 4th. rate.

Timber, pinon, juniper and 2nd. growth.

From the cor. of secs. 28, 29, 32 and 33.

S. $89^{\circ} 36' W.$ bet. secs. 29 and 32.

Over mountainous land, through heavy timber.

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4856

Chains	Asc. 240 ft. over NE. slope.
28.25	Spur, slopes SE. Desc. 115 ft. over SW. slope.
39.03	The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 12 x 8 x 8 ins. firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a mound of stone 2 ft. base, 6 ins. high, to the N. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd. $\frac{1}{4}$ $\frac{S\ 29}{S\ 32}$ 1945 from which Original bearing trees: A pinon, 10 ins. diam., bears N. $52\frac{1}{2}^{\circ}$ E. 14 lks. dist., mkd. $\frac{1}{4}$ S BT Additionally mark $\frac{1}{4}$ S29 BT A pinon, 10 ins. diam., bears S. 27° W., 18 lks. dist., mkd. $\frac{1}{4}$ S BT Additionally mark $\frac{1}{4}$ S32 BT N. $89^{\circ}36'$ W., beginning new measurement. Continue descent 80 ft. 9.40 Draw, course S. Asc. 40 ft. 15.50 Flat spur, slopes SW. Desc. 50 ft. 25.50 Shallow draw, course SW. Asc. 45 ft. 32.25 Small spur, slopes SW. Desc. 40 ft. 33.10 Wire fencing, bears N. 30° W. and S. 30° E. 35.40 Draw, course SE. Asc. 40 ft. over E. slope. 39.40 The cor. of secs. 29, 30, 31 and 32. Land, mountainous and heavily rolling. Soil, rocky, 3rd. rate. Timber, pinon, juniper and 2nd. growth. ----- N. $88^{\circ}06'$ W. bet. secs. 30 and 31. Over rolling land, through heavy growth of timber. Asc. 50 ft. over SE. slope. 10.50 Top of hill, spur slopes to the S. Desc. 155 ft. over W. slope. 29.50 Shallow draw, course SW. Continue over rolling land. 39.23 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 18 x 12 x 6 ins. firmly set, mkd. $\frac{1}{4}$ on the N. face. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

$$\frac{1}{4} \begin{array}{l} \text{S } 30 \\ \text{S } 31 \end{array}$$

1945

from which

Original bearing trees:

A pinon, 18 ins. diam., bears S.31 $\frac{1}{4}$ °W. 13 lks. dist.,
mkd. $\frac{1}{4}$ S BT

A pinon, 20 ins. diam., bears S.83 $\frac{1}{2}$ °W. 27 lks. dist.,
mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S31 BT

New bearing tree:

A pinon, 6 ins. diam., bears N.52°E. 40 lks. dist.,
mkd. $\frac{1}{4}$ S30 BT

S.88°19'W., beginning new measurement.

10.00 Enter scattered timber, bears N. and S.

19.00 Enter heavy timber, bears N. and S.

41.60 The cor. of secs. 30 and 31, on the W. bdy. of the Tp.

Land, rolling.

Soil, gravelly and rocky, 3rd. rate.

Timber, pinon, juniper; 2nd. growth.

Undergrowth, scattered gamma grass.

From the cor. of secs. 29, 30, 31 and 32.

N.1°40'W., bet. secs. 29 and 30.

Over rolling land, through heavy growth of timber.

Asc. 15 ft. over SE. slope.

2.00 Spur, slopes SE. Desc. 20 ft.

8.80 Draw, course SE. Asc. 115 ft. over SW. slope.

32.00 Low ridge, bears W. and S.30°E. Desc. 40 ft. over N. slope.

39.17 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone, 12 x 10 x 8
ins., firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by
a dilapidated mound of stone to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with original corner stone deposited alongside,
with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S } 30 \\ \text{S } 29 \end{array}$$

1945

from which

Original bearing trees:

A pine, 30 ins. diam., dead and fallen, bears N.13 $\frac{1}{2}$ °W.
70 lks. dist., marks overgrown.

A pine, 30 ins. diam., dead and fallen, bears S.37°E.

Resurvey of the Subdivisions of T.25 N., R.5 E.

BOOK 4550

Chains

74 lks. dist., marks overgrown.

New bearing trees:

A pinon, 8 ins. diam., bears N.49 $\frac{1}{4}$ °E. 26 lks. dist.,
mkd. $\frac{1}{4}$ S29 BTA pinon, 6 ins. diam., bears N.71 $\frac{1}{2}$ °W. 17 lks. dist.,
mkd. $\frac{1}{4}$ S30 BT

N.1°37'E., beginning new measurement.

17.50 Swale, drains NW.

23.20 Low sour, slopes NW.

33.00 Corner of wire fencing, at gate therein, extending W. S.
and NE., bears east 32 lks. dist.

35.00 Shallow draw, course NW.

40.32 The cor. of secs. 19, 20, 29 and 30, evidenced by the
original monument, a lava stone 13 x 10 x 3 ins., firmly
set, mkd. with 2 grooves on the S. and 5 grooves on the
E. faces, and witnessed by a mound of stone 1 $\frac{1}{2}$ ft. base,
1 ft. high, to the W.Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, with original corner stone deposited alongside,
with brass cap mkd.

T25N R5E

S 19 | S 20

S 30 | S 29

1945

from which

Original bearing trees:

A pinon, 12 ins. diam., bears N.12°E. 72 lks. dist.,
blaze overgrown. Remark T25N R5E S20 BTA pinon, 10 ins. diam., bears S.85°W. 45 lks. dist.,
mkd. T25N R5E S30 BTA pinon, 10 ins. diam., bears N.17 $\frac{1}{4}$ °W. 46 lks. dist.,
mkd. T25N R5E S19 BT

New bearing tree:

A pinon, 10 ins. diam., bears S.72 $\frac{1}{4}$ °E. 41 lks. dist.,
mkd. T25N R5E S29 BT

Land, rolling.

Soil, rocky, 3rd. rate.

Timber, pinon, juniper, pine; 2nd. growth.

From the cor. of secs. 20, 21, 28 and 29.

N.89°45'W., bet. secs. 20 and 29.

Over mountainous land, through heavy growth of timber.

Desc. 140 ft. over broken NW. slope.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

- 5.00 Bottom of canyon, course NE. Asc. 790 ft. over precipitous NE. slope.
- 26.60 Northern extremity of top of Red Mountain, ridge extends S.20°E. Desc. 280 ft. over W. slope.
- 40.60 Point for $\frac{1}{4}$ sec. cor., at proportionate distance.
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
- $$\frac{1}{4} \frac{S 20}{S 29}$$
- 1945
from which
- A pinon, 8 ins. diam., bears N.11 $\frac{1}{2}$ °W. 16 lks. dist., mkd. $\frac{1}{4}$ S20 BT
- A pinon, 10 ins. diam., bears S.29°E. 42 lks. dist., mkd. $\frac{1}{4}$ S29 BT
- Continue descent 560 ft. over SW. slope.
- 49.00 Change of slope to NW.
- 70.00 Base of slope, and over slightly rolling land.
- 76.80 Wire fencing, extends N.15°E. and S.15°W.
- 81.20 The cor. of secs. 19, 20, 29 and 30.
Land, mountainous.
Soil, rocky, 3rd. rate.
Timber, pinon, juniper, pine; 2nd. growth.
-
- N.89°17'W. bet. secs. 19 and 30.
Over rolling land, through heavy growth of timber.
- 8.20 Ditch, 6 lks. wide, drains NW.
- 23.30 Low spur, slopes NW.
- 34.50 Enter scattered timber, bears NW. and SE.
- 36.75 Shallow draw, course NW.
- 39.27 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 18 x 10 x 3 ins. firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a mound of stone 1 $\frac{1}{2}$ ft. base, 1 ft. high, to the N.
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.
- $$\frac{1}{4} \frac{S 19}{S 30}$$
- 1945
from which
- Original bearing trees:
- A pinon, 14 ins. diam., bears S.44 $\frac{1}{2}$ °W. 198 lks. dist. mkd. $\frac{1}{4}$ S BT . Additionally mark $\frac{1}{4}$ S30 BT

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

A pinon, 14 ins. diam., bears S.62 $\frac{1}{2}$ °W. 188 lks. dist., marks partly overgrown and not legible.

New bearing tree:

A cedar, 16 ins. diam., bears N.34 $\frac{1}{4}$ °E. 272 lks. dist. mkd. $\frac{1}{4}$ S19 BT

S.89°24'W., beginning new measurement.

16.70 Shallow draw, previously noted, course SW.

23.50 Leave timber, bears N. and SW.

31.00 Old roadway, bears NE. and SW. Enter heavy timber, bearing N. and S. Asc. 50 ft.

38.30 S. shoulder of low hill. Desc. 15 ft.

40.68 The cor. of secs. 19 and 30, on the W. bdy. of the Tp.

Land, rolling.

Soil, rocky, 3rd. rate.

Timber, pinon, juniper; 2nd. growth.

From the cor. of secs. 19, 20, 29 and 30.

N.0°41'W., bet. secs. 19 and 20.

Over slightly rolling land, through heavy growth of timber.

17.00 Enter scattered timber, bears E. and W.

28.00 Traces of old roadway, bearing E. and W.

39.76 The $\frac{1}{4}$ sec. cor., evidenced by a sandstone 16 x 10 x 9 ins. firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 19 \text{ --- } | \text{ --- } \text{S } 20 \\ 1945 \end{array}$$

from which

Original bearing trees:

A pinon, 10 ins. diam., bears N.76 $\frac{1}{2}$ °W. 65 lks. dist. blaze overgrown. Remark tree $\frac{1}{4}$ S19 BT

A pinon, 8 ins. diam., bears S.80°W. 69 lks. dist., blaze overgrown.

New bearing tree:

A juniper, 6 ins. diam., bears N.42 $\frac{1}{2}$ °E. 107 lks. dist. mkd. $\frac{1}{4}$ S20 BT

N.0°12'E., beginning new measurement.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains	
21.00	Enter scattered timber, bearing E. and W.
23.00	Low rise, sloping W.
31.00	Shallow swale, draining NE.
39.65	The cor. of secs. 17, 18, 19 and 20, evidenced by the original monument, a lava stone 14 x 12 x 8 ins., firmly set, marked with 3 notches on the S. and 5 notches on the E. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.
	Set an iron post, 3 ft. long, 2 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.
	$\begin{array}{r} \text{T25N R5E} \\ \text{S 18 S 17} \\ \hline \text{S 19 S 20} \end{array}$
	1945
	from which
	Original bearing trees:
	A pinon, 10 ins. diam., bears N.14°E. 156 lks. dist., mkd. T25N R5E S17 BT
	A pinon, 26 ins. diam., bears S.55½°W. 78 lks. dist., mkd. T25N R5E S19 BT
	A pinon, 14 ins. diam., bears N.62°W. 181 lks. dist., mkd. T25N R5E S18 BT
	New bearing tree:
	A pinon, 10 ins. diam., bears S.38½°E. 134 lks. dist., mkd. T25N R5E S20 BT
	Land, nearly level. Soil, rocky, 3rd. rate. Timber, pinon, juniper; 2nd. growth.

	From the cor. of secs. 16, 17, 20 and 21.
	N.89°13'W. bet. secs. 17 and 20.
	Over slightly rolling land, through scattered timber.
20.00	Enter heavy growth of timber, bearing N. and S.
21.00	Wire fencing, extends NE. and SW.
41.54	The ¼ sec. cor., evidenced by a lava stone 14 x 12 x 8 ins. firmly set, mkd. ¼ on the N. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the N.
	Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, to bedrock, with original corner stone deposited alongside, with brass cap mkd.
	$\frac{1}{4} \frac{\text{S 17}}{\text{S 20}}$
	1945
	from which

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

A pinon, 7 ins. diam., bears N.16 $\frac{3}{4}$ °E. 95 lks. dist.,
mkd. $\frac{1}{4}$ S17 BT

A pinon, 6 ins. diam., bears S.48°W. 95 lks. dist.,
mkd. $\frac{1}{4}$ S20 BT

No evidence remains of the originally recorded bearing trees.

N.89°32'W., beginning new measurement.

- 1.50 Small spur, slopes NW.
- 33.50 Shallow draw, drains NE.
- 39.51 The cor. of secs. 17, 18, 19 and 20.
- Land, slightly rolling.
Soil, rocky, 3rd. rate.
Timber, pinon, juniper; 2nd. growth.
-
- N.89°56'W., bet. secs. 18 and 19.
- Over rolling land, through heavy growth of timber.
Asc. 30 ft.
- 4.50 Spur, slopes NE.
- 7.00 Enter scattered timber, bears N. and S.
- 15.00 Enter heavy timber, bears N. and S.
- 21.00 Low spur, slopes NW. Desc. 40 ft.
- 37.20 Shallow draw, course NW.
- 38.86 Point for $\frac{1}{4}$ sec. cor., at proportionate distance.
- Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, to bedrock, and in a mound of stone to top, with brass cap mkd.

$$\frac{1}{4} \frac{S 18}{S 19}$$

1945

from which

A cedar, 8 ins. diam., bears North 60 lks. dist.,
mkd. $\frac{1}{4}$ S18 BT

A pinon, 6 ins. diam., bears S.52 $\frac{1}{2}$ °W. 92 lks. dist.,
mkd. $\frac{1}{4}$ S19 BT

- 62.10 Road, bears N. and S. Asc. 35 ft.
- 73.70 Spur, slopes N. Desc. 50 ft.
- 78.24 The cor. of secs. 18 and 19, on the W. bdy. of the Tp.
- Land, rolling.
Soil, rocky, 3rd. rate.
Timber, pinon, juniper; 2nd. growth.
-

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

From the cor. of secs. 17, 18, 19 and 20.

N.0°04'W., bet. secs. 17 and 18.

Over rolling land, through heavy growth of timber.

Asc. 10 ft.

3.90 Spur, slopes E. Desc. 23 ft.

14.00 Leave heavy timber, bears E. and W.

17.00 Shallow draw, course E.

20.00 Enter heavy timber, bears E. and W.

23.00 Top of broad spur, sloping E. Desc. 35 ft.

39.74 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 16 x 12 x 6 ins. firmly set, mkd. $\frac{1}{4}$ on the W. face, and witnessed by a mound of stone 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, to the W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 18 \text{ | S } 17 \\ 1945 \end{array}$$

from which

An original bearing tree:

A pinon, 14 ins. diam., bears S.52 $\frac{1}{2}$ °E. 24 lks. dist., marks overgrown. Remark $\frac{1}{4}$ S17 BT

New bearing tree:

A pinon, 4 ins. diam., bears S.66 $\frac{3}{4}$ °W. 30 lks. dist., mkd. $\frac{1}{4}$ S18 BT

N.1°35'W., beginning new measurement,

29.50 Shallow draw, course NW.

39.60 The cor. of secs. 7, 8, 17 and 18, evidenced by the original monument, a lava stone 14 x 12 x 8 ins., firmly set, marked with 4 grooves on the S. and 2 grooves on the N. faces, and witnessed by a mound of stone 2 ft. base, 1 $\frac{1}{2}$ ft. high, to the W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.

$$\begin{array}{c} \text{T25N R5E} \\ \text{S } 7 \text{ | S } 8 \\ \text{S } 18 \text{ | S } 17 \end{array}$$

1945

from which

Original bearing trees:

A pinon, 12 ins. diam., bears S.32°E. 227 lks. dist.

Resurvey of the Subdivision of T.25 N., R.5 E.

B. L. P. 4886

Chains

blaze overgrown. Remark tree T25N R5E S17 BT

A pinon, 8 ins. diam., bears S.8°W. 107 lks. dist., without visible markings.

A pinon, 14 ins. diam., bears S.19°W. 85 lks. dist., mkd. T25N R5E S18 BT

A juniper, 10 ins. diam., bears N.51½°W. 40 lks. dist. mkd. T25N R5E S7 BT

New bearing tree:

A pinon, 16 ins. diam., bears N.37½°E. 222 lks. dist. mkd. T25N R5E S8 BT

Land, rolling.

Soil, rocky, 3rd. and 4th. rate.

Timber, pinon, juniper; 2nd. growth.

From the cor. of secs. 8, 9, 16 and 17.

N.89°13'W.; bet. secs. 8 and 17.

Over nearly level land, through heavy growth of timber.

1.90 Graded road, bears NW. to Grand Canyon and S.45°E. to Flagstaff.

20.00 Enter scattered timber, bears N. and S.

29.00 Enter heavy timber, bears N. and S.

41.39 Point for ¼ sec. cor., at proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S 8}{S 17}$$

1945

from which

A pinon, 8 ins. diam., bears N.68°W. 90 lks. dist. mkd. ¼ S8 BT

A pinon, 5 ins. diam., bears S.10¾°E. 27 lks. dist., mkd. ¼ S17 BT

60.40 Wash, 5 lks. wide, in swale, course NE. Asc. 165 ft. over E. slope.

75.00 Spur, slopes N. Desc. slightly.

82.78 The cor. of secs. 7, 8, 17 and 18.

Land, level and rolling.

Soil, rocky, 3rd. rate.

Timber, pinon and juniper; 2nd. growth.

N.89°59'W. bet. secs. 7 and 18.

Over rolling land, through heavy timber.

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains	
1.20	Spur, slopes N. Desc. 25 ft.
6.00	Draw, course NW. Asc. 30 ft.
8.70	Spur, slopes N. Continue ascent 45 ft.
22.00	Spur, slopes NE., Small knoll, or peak, about 80 ft. high, bears SW. 6 chs. dist. Desc. 105 ft. over NW. slope.
35.40	Gulch, course N. Asc. 30 ft.
37.90	Point for $\frac{1}{4}$ sec. cor., at proportionate distance. Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, to bedrock, and in a mound of stone to top, with brass cap mkd. $\frac{1}{4} \begin{array}{l} S 7 \\ S 18 \end{array}$ 1945 from which A pinon, 16 ins. diam., bears N.50 $\frac{1}{2}$ °W. 42 lks. dist. mkd. $\frac{1}{4}$ S7 BT A pinon, 8 ins. diam., bears S.63°E. 20 lks. dist., mkd. $\frac{1}{4}$ S18 BT Asc. 15 ft.
39.60	Spur, slopes N. Desc. 45 ft.
45.10	Gulch, course NE. Asc. 65 ft.
52.90	Spur, slopes NW. Desc. 110 ft.
60.40	Roadway, in draw, course N. Asc. 65 ft.
68.40	Rocky knoll, bears NE. and SW. Desc. 00 ft. over NW. slope.
76.20	The cor. of secs. 7 and 18, on the W. bdy. of the Tp. Land, heavily rolling and broken. Soil, rocky, 3rd. and 4th. rate. Timber, pinon, juniper; 2nd. growth. ----- From the cor. of secs. 7, 8, 17 and 18. N.2°34'E., bet. secs. 7 and 8. Over mountainous land, through heavy growth of timber. Desc. 35 ft.
9.60	Small draw, course NE. Asc. 30 ft.
13.20	Spur, slopes E., Desc. 210 ft. over NE. slope.
36.00	Old road, bears E. and W. Enter scattered timber.
39.39	The $\frac{1}{4}$ sec. cor., evidenced by a hewed pinon post, 3 ins. square, 30 ins. long, firmly supported in a mound of stone, mkd. $\frac{1}{4}$ S on the W. face. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner post deposited alongside,

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4376

Chains

with brass cap mkd.

$$\frac{1}{4}$$

S 7	S 8
-----	-----

1945

from which

An original bearing tree:

A cedar, 8 ins. diam., bears S.27 $\frac{1}{2}$ °W. 49 lks. dist., mkd. $\frac{1}{4}$ S BT. Additionally mark $\frac{1}{4}$ S7 BT

New bearing tree:

A juniper, 8 ins. diam., bears N.19 $\frac{1}{2}$ °E. 282 lks. dist. mkd. $\frac{1}{4}$ S8 BT

N.5°30'E., beginning new measurement.

Over slightly rolling land, through scattered timber.

- 5.10 Graded road, bears N.80°W. to Grand Canyon and S.80°E. to Flagstaff.
- 10.00 Enter heavy timber, bears NW. and SE.
- 39.24 The cor. of secs. 5, 6, 7 and 8, evidenced by the original monument, a lava stone 12 x 9 x 6 ins., firmly set, mkd. with 5 notches on the S. and 1 notch on the N. edges, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the W.
- Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, to bedrock, with original corner stone deposited alongside, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{cc} \text{T25N} & \text{R5E} \\ \hline \text{S 6} & | \text{S 5} \\ \hline \text{S 7} & | \text{S 8} \end{array}$$

1945

from which

Original bearing trees:

A pinon, 14 ins. diam., bears N.6°W. 147 lks. dist., blaze overgrown. Remark tree T25N R5E S6 BT

A juniper, 30 ins. diam., bears N.77 $\frac{1}{2}$ °W. 199 lks. dist., mkd. T25N R5E S6 BT

A pine, 14 ins. diam., dead and fallen, bears N.41 $\frac{3}{4}$ °W., 112 lks. dist., marks partly overgrown.

New bearing trees:

A juniper, 6 ins. diam., bears N.63 $\frac{1}{4}$ °E. 104 lks. dist., mkd. T25N R5E S5 BT

A pinon, 8 ins. diam., bears S.2°W. 261 lks. dist., mkd. T25N R5E S8 BT

A juniper, 8 ins. diam., bears S.79°W. 271 lks. dist. mkd. T25N R5E S7 BT

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains	
	<p>Land, mountainous and slightly rolling. Soil, rocky, 3rd. rate. Timber, pinon, juniper; 2nd. growth.</p> <p>-----</p> <p>From the cor. of secs. 4, 5, 8 and 9. S.88°41'W., bet. secs. 5 and 8. Over nearly level land, through heavy growth of timber.</p> <p>23.00 Enter scattered timber, bears N. and S..</p> <p>32.00 Enter heavy timber, bears N. and S.</p> <p>37.26 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone, 12 x 10 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a mound of stone 2 ft. base, 1 ft. high, to the N.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original corner stone deposited alongside, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4} \frac{S \ 5}{S \ 8}$</p> <p style="text-align: center;">1945</p> <p style="text-align: right;">from which</p> <p>Original bearing trees:</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears N.31°W. 38 lks. dist., mkd. $\frac{1}{4}$ S BT Additionally mark $\frac{1}{4}$ S5 BT</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S.43$\frac{1}{2}$°W. 58 lks. dist. mkd. $\frac{1}{4}$ S BT Additionally mark $\frac{1}{4}$ S8 BT</p> <p>N.88°55'W., beginning new measurement.</p> <p>10.00 Enter scattered timber, bearing N. and S.</p> <p>13.00 Road, bears N. and S.</p> <p>35.00 Enter heavy timber, bears N. and S.</p> <p>39.84 The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, level. Soil, rocky, 3rd. rate. Timber, pinon, juniper; 2nd. growth.</p> <p>-----</p> <p>N.88°05'W., bet. secs. 6 and 7. Over nearly level land, through scattered timber.</p> <p>14.00 Road, bears NE. and SW.</p> <p>42.21 The $\frac{1}{4}$ sec. cor., evidenced by a lava stone 12 x 6 x 5 ins. firmly set, mkd. $\frac{1}{4}$ on the N. face, and witnessed by a mound of stone 1$\frac{1}{2}$ ft. base, 1 ft. high, to the N.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.</p>

Resurvey of the Subdivision of T. 25 N., R. 5 E.

PCOM 4086

Chains	
	$\frac{1}{4} \frac{S 6}{S 7}$ <p style="text-align: center;">1945</p> <p style="text-align: right;">from which</p> <p>A juniper, 10 ins. diam., bears S.1°E. 200 lks. dist. mkd. $\frac{1}{4}$ S7 BT</p> <p>Raise a mound of stone 3 ft. base, 2½ ft. high, S. of corner.</p> <p>S.89°06'W., beginning new measurement.</p>
21.50	Road, bears N.20°W. and S.20°E.
40.39	The cor. of secs. 6 and 7, on the W. bdy. of the Tp.
	Land, nearly level. Soil, rocky, 3rd. rate. Timber, pinon, juniper; 2nd. growth.

	From the cor. of secs. 5, 6, 7 and 8.
	N.4°33'W., bet. secs. 5 and 6.
	Over nearly level land, through heavy growth of timber.
18.50	Road, bears NE. and SW.
40.92	The $\frac{1}{4}$ sec. cor. evidenced by a lava stone 10 x 8 x 6 ins. firmly set, mkd. $\frac{1}{4}$ on the W. face.
	Set an iron post, 3 ft. long, 1 in. diam. 28 ins. in the ground, with original corner stone deposited alongside, with brass cap mkd.
	$\frac{1}{4}$ $S 6 \mid S 5$ <p style="text-align: center;">1945</p> <p style="text-align: right;">from which</p>
	Original bearing trees:
	A juniper, 10 ins. diam., bears S.2¼°W. 278 lks. dist. mkd. $\frac{1}{4}$ S BT
	A juniper, 10 ins. diam., bears S.7°W. 272 lks. dist. mkd. $\frac{1}{4}$ S BT Additionally mark $\frac{1}{4}$ S6 BT
	New bearing tree:
	A pinon, 4 ins. diam., bears S.79¾°E. 62 lks. dist., mkd. $\frac{1}{4}$ S+ BT
	N.0°36'E., beginning new measurement.
	Over level land, through scattered timber.
15.00	Enter heavy growth of timber, bears NW. and SE.
39.87	The cor. of secs. 5 and 6, on the N. bdy. of the Tp., evidenced by the original monument, a lava stone 16 x 14 x 8 ins., firmly set, mkd. with 5 notches on the E. and 1

Resurvey of the Subdivision of T.25 N., R.5 E.

Chains

notch on the W. edges.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, to bedrock, with original corner stone deposited at base, and in a mound of stone to top, with brass cap mkd.

T26N	R5E
S 32	
S 6	S 5
T25N	R5E
1945	

from which

Original bearing trees:

A pinon, 10 ins. diam., bears S.39½°E. 93 lks. dist. mkd. T25N R5E S5 BT

A juniper, 25 ins. diam., bears S.38¼°W. 56 lks. dist. mkd. T25N R5E S6 BT

The cor. of secs. 31 and 32, T.26 N., R.5 E., bears N.89°58'W., 6.43 chs. dist., marked by an iron post, 3 ins. diam., conforming to the 1916 resurvey record.

Land, nearly level.
Soil, rocky, 3rd. rate.
Timber, pinon, juniper; 2nd. growth.
Undergrowth, scattered gamma grass.

At the ¼ sec. cor., on the N. bdy. of sec. 5, evidenced by a hewed pinon post, 2½ ins. square, 3 ft. long, firmly supported in a mound of stone, mkd. ¼S on N. face, with traces of pits E. and W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with original corner post deposited alongside, with brass cap mkd.

¼	S 5
---	-----

1945

Raise a mound of stone 3 ft. base, 2½ ft. high, S. of corner.

From the cor.,

The ¼ sec. cor., of sec. 32, T.26 N., R.5 E., bears S.89°50'W., 6.26 chs. dist., an iron post, 1 in. diam. conforming to the 1916 resurvey record; and the cor. of secs. 5 and 6, bears S.89°50'W., 39.83 chs. dist.

The cor. of secs. 4 and 5, bears S.88°59'E., 40.32 chs. dist.

At the ¼ sec. cor., on the N. bdy. of sec. 6, evidenced by a lava stone 12 x 10 x 10 ins., firmly set, mkd. ¼ on the N. face,

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, to bedrock, with original corner stone deposited at base, and in a mound of stone to top, with brass cap

Resurvey of the Subdivision of T.25 N., R.5 E.

BOOK 4840

Chains.

mkd.

 $\frac{1}{4}$ S 6

1945

from which

Original bearing trees:

A pinon, 12 ins. diam., bears S.79°E. 171 lks. dist.,
mkd. $\frac{1}{4}$ S BT Additionally mark $\frac{1}{4}$ S6 BT

A pinon, 12 ins. diam., bears S.65 $\frac{3}{4}$ °E. 200 lks. dist.,
mkd. $\frac{1}{4}$ S BT Additionally mark $\frac{1}{4}$ S6 BT

From the cor.,

The $\frac{1}{4}$ sec. cor., on the S. bdy. of sec. 31, T.26 N.,
R.5 E., bears S.89°51'W., 6.57 chs. dist., marked by
an iron post, 1 in. diam., conforming to the 1916
resurvey record; and the cor. of Ts.25 and 26 N.,
R.5 E., bears S.89°51'W., 40.01 chs. dist.

The cor. of secs. 5 and 6, bears S.89°58'E., 39.86
chs. dist.

FINAL TEST OF SOLAR ATTACHMENT.

Nov. 14, 1945, on the meridian established July 7, 1944,
in T.24 N., R.6 E., heretofore described, with proper
settings on the arcs of the solar unit, note that the
resulting orientation of the instrument throughout the
usual hours of solar work shows a maximum error not
exceeding 1'30" of arc.

General Description.

T.25 N., R.5 E. lies in a plateau region at a mean elev-
ation of about 7000 ft. above sea level. The area is
fractionally mountainous in the southern portion, draining
northerly to a nearly level terrain. The soil is a rocky
clay of volcanic character or formation, shallow and of
poor quality. There is no water, with the exception of a
seep, or small spring, probably intermittent in flow,
near the SE. corner of section 20, in a canyon near the
base of Red Mountain. There is no undergrowth, in the
usual accepted sense of brushy verdure, although a dense
coverage of young pinon and juniper is encountered through-
out the township. A few yellow pine, not of commercial
quality or quantity, and pinon and juniper, or cedar
timber completes the forestry pattern.

A graded, and well maintained roadway, leading from Flag-
staff to Grand Canyon, extends north-west, obliquely
through the township. Numerous local roads, although in
poor condition, present an easy accessibility to nearly
all sections.

Some slight development, in the form of earthen tanks, or
reservoirs, to impound and conserve flash waters have
been constructed by local cattle interests, and some
extensive range fencing of irregular pattern and extent
is maintained in good repair.

Resurvey of the Subdivision of T.25 N., R.5 E.

One resident is situate in the SW. $\frac{1}{4}$ of sec. 7, closely adjacent to the $\frac{1}{4}$ sec. cor. of that section.

The city of Flagstaff is distant about 25 miles, to the south-east, in T.21 N., R.7 E.

4-680
(Revised May 1934)

UNITED STATES
DEPARTMENT OF THE INTERIOR
~~GENERAL LAND OFFICE~~

BUREAU OF LAND MANAGEMENT
FIELD ASSISTANTS

NAMES	CAPACITY
John Boggs	Truckdriver.
Theodore Cole	Principal Assistant.
George D. Blair	Cornerman.
Sidney G. Tait	Flagman.
Tommy J. Cade	Axman.
Frank L. Harris	Axman.
George C. Hopkins	Axman.
James C. Kennicott	Axman.
George K. Mills, Jr.	Axman.
Richard A. Rogers	Axman.
Henry Whitney	Axman.
Harold R. Muller	Axman.

82

BOOK 4356

CERTIFICATE OF SURVEYOR

Ty White, Associate Cadastral Engineer
We, Bert E. Wakeman, Senior Engineering Aid, Claude F. Warner, Assistant Cadastral Engineer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 13th day of March, 1942

received from the district cadastral engineer for Arizona, with assignment instructions dated June 26, 1944 and June 16, 1945 we have resurveyed the East and West Boundaries and the Subdivision of T.25 N., R.5 E.,

Gila and Salt River of the Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said re survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona, Mar.17,1947
Phoenix, Arizona, Mar.24,1947
Phoenix, Arizona, Mar.17,1947

Ty White, Associate Cadastral Engineer.
Bert E. Wakeman, Senior Engineering Aid.
Claude F. Warner, Assistant Cadastral Engineer.

CERTIFICATE OF APPROVAL

Chief Cadastral Engineer
OFFICE OF SUPERVISOR OF SURVEYS,
Denver, Colorado OCT 20 1947

The foregoing field notes of the dependent resurvey of the East and West Boundaries and the Subdivision of T.25 N., R.5 E.,

executed by Ty White, Associate Cadastral Engineer, Claude F. Warner, Assistant Cadastral Engineer and Bert E. Wakeman, Senior Engineering Aid, under special instructions dated March 13, 1942, and assignment instructions dated June 26, 1944 and June 16, 1945, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

Garland G. Harrington, Acting Assistant Chief Cadastral Engineer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes on file in the public survey office.

Supervisor of Surveys.