

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

BOOK 4360

Of The

Resurvey of the East Boundary in part

and

Survey of the Subdivision

of

Township 1 South, Range 19 West

Of the Gila and Salt River Meridian Meridian,

In the State of Arizona

EXECUTED BY

Dupree R. Averill and G. Marvin Litz, Cadastral Engineers.

Under special instructions dated March 15, 1946, which provided for the surveys included under Group No. 246, bearing the approval of the Commissioner of the General Land Office under date of August 26, 1946 and assignment instructions dated January 7, 1947.

Survey commenced January 8, 1947

Survey completed January 20, 1947

4360

4360

1A 43

BOOK 4360

INDEX DIAGRAM.

Township 1 South, Range 19 West

	53	52	37	30	22	15						
51	6	51	5	36	4	29	3	21	2	14	1	6
	49		49		36		28		21		13	
51	7	48	8	35	9	28	10	20	11	12	12	5
	47		46		35		27		20		12	
48	18	46	17	34	16	27	15	19	14	11	13	4
	44		44		33		26		19		11	
45	19	43	20	33	21	26	22	18	23	10	24	3
	41		41		32		25		17		9	
43	30	40	29	32	28	24	27	17	26	8	25	2
	39		38		31		24		16		8	
40	31	37	32	30	33	23	34	15	35	7	36	

TOWNSHIP 1 SOUTH, RANGE 19 WEST

BOOK 4360

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

- Indicates lines surveyed by Dupree R. Averill.
- Indicates lines surveyed by G. Marvin Litz.
- Indicates lines surveyed by Elliott Pearson, under the direction of Averill.

T. 1 S., R. 19 W.

BOOK 4360

The survey herein noted was executed with Buff and Buff transits Nos. 24849 and 26591, and Gurley transit No. 371537, equipped with Smith solar attachments, and constructed in accordance with the standard specifications of the Bureau of Land Management. The instruments were in satisfactory adjustment prior to beginning the survey, and tested and found to be free from appreciable error.

The directions of all lines were determined by direct observation on the sun for azimuth, supplemented by observations with the solar units. Measurements were made with steel tapes, 5 chains in length, graduated every link for the first 100 links, and the remainder at intervals of 10 links. The tapes were first tested with a Lufkin standard 1 chain tape and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The data presented with the special instructions indicates the geographic position of the southeast corner of T. 1 S., R. 19 W., as follows:

Latitude: $33^{\circ} 17' 17''$ N.

Longitude: $114^{\circ} 10' 00''$ W.

The observed mean magnetic declination is 15° E.

January 8, 1947: at observing station situated in the NE $\frac{1}{4}$, sec. 29, T. 1 S., R. 19 W., at 9h.18.2m a.m., l.m.t., observe Polaris, making three sights each with the telescope in direct and reversed positions, noting the deflection angle to a reference mark about ten miles distant.

Mean horizontal angle to Polaris $102^{\circ} 52' 00''$

Mean vertical angle to Polaris $32^{\circ} 35' 00''$

Reduced bearing to reference mark S. $76^{\circ} 23' 00''$ E.

Reduced latitude $33^{\circ} 18' 47''$ N.

The solar units were tested upon the meridian determined by Polaris observation, and maintained in good adjustment throughout the survey.

The Gila and Salt River Base Line, along the North bdy. of the township, was surveyed by Messrs. Abbey and Gill, U. S. Surveyors, in 1915.

The west bdy. of the township was surveyed by Wm. B. Kimmel, U. S. Surveyor, in 1916; and the south and east bdrs. by Wm. E. Hiester and Ty White, Cadastral Engineers, in 1941.

Resurvey of part of the E. bdy., T. 1 S., R. 19 W.

BOOK 4360

Chains

Independent resurvey superseding the survey executed by William E. Hiester, Cadastral Engineer in 1941.

Due to cumulative errors in measurement of the original survey, it became evident there would be considerable distortion in some sections adjacent to the east boundary. Since this line is subject to rectification, it was deemed advisable to make a resurvey.

The original corners are all monumented with iron posts, and conform to the description as given in the official record.

The iron posts used in the 1941 survey are removed and reset in the new positions.

Begin the resurvey at the 1/4 sec. cor. of secs. 25 and 30, which is monumented with an iron post, 1 in. diam., mkd. and witnessed as described in the official record.

North, bet. secs. 25 and 30, counting the 1/4 sec. cor. as 40.00 chs.

Continue over rolling desert land.

45.40 Dry wash, 15 lks. wide, course W.

58.30 Dry wash, 15 lks. wide, course S. 80° W.; leave rolling land, bears E. and W.; asc. 115 ft. over S. slope.

79.85 The original cor. of secs. 19, 24, 25 and 30.

Remove the iron post and destroy mound of stone.

80.00 Point for cor. of secs. 19, 24, 25 and 30.

Reset the iron post, 3 ft. long, 2 ins. diam., over an 8 in. cross (+) mkd. on bedrock, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.

T1S	
R19W	R18W
S 24	S 19
S 25	S 30

1947
1941

from which

SE. face of rocky ledge, 6 ft. wide, bears S. 3 1/2° W., 14 lks. dist., mkd. B+O.

This is the same bearing object used on the original cor.

Land, mountainous and rolling.
Soil, rocky, 4th rate.
Timber, ironwood and paloverde; undergrowth, greasewood, mesquite, cats claw, sage and cacti.

Resurvey of part of the E. Bdy., T. 1 S., R. 19 W.

BOOK 4360

Chains	
	North, bet. secs. 19 and 24.
	Over mountainous land, through scattering timber and undergrowth.
	Asc. 250 ft. over S. slope.
6.10	Ridge, slopes SE. Along E. slope.
10.70	Short spur, slopes E. Desc. 400 ft. over NE. slope.
32.70	Enter drain, course N. Desc. gradually.
39.85	The point for original $\frac{1}{4}$ sec. cor. in dry wash, 10 lks. wide, course N. 20° W.
40.00	True point for $\frac{1}{4}$ sec. cor.
42.80	The original witness $\frac{1}{4}$ sec. cor. of secs. 19 and 24, marked by an iron post, 2 ins. diam., 8 ins. above ground, with brass cap mkd.
	$\frac{1}{4}$ S 24 S 19 W C 1947 1941
	A mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
	This witness corner now refers to the new point for $\frac{1}{4}$ sec. cor.
	Continue over rolling desert land.
60.80	Dry wash, 30 lks. wide, course W.
64.80	Dry wash, 50 lks. wide, 2 ft. deep, course W.
67.90	Dry wash, 25 lks. wide, 2 ft. deep, course W.
72.80	Dry wash, 15 lks. wide, 2 ft. deep, course W.
79.77	The original cor. of secs. 13, 18, 19 and 24.
	Remove the iron post and destroy mound of stone.
80.00	Point for corner of secs. 13, 18, 19 and 24.
	Reset the iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T1S R19W R18S S 13 S 18 S 24 S 19 1947 1941
	Raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.

BOOK 4360

Resurvey of part of the E. Bdy. of T. 1 S., R. 19 W.

Chains

Land, mountainous, and gently rolling.
Soil, sandy and rocky, 3rd and 4th rate.
Scattering ironwood and paloverde, greasewood, cats claw
and cacti.

North, bet. secs. 13 and 18

Asc. 60 ft. over very gradual S. slope, through
scattering timber and undergrowth.

39.76

The original $\frac{1}{4}$ sec. cor.

Remove the iron post and destroy mound of stone.

40.00

Point for $\frac{1}{4}$ sec. cor. of secs. 13 and 18.

Reset the iron post, 3 ft. long, 1 in. diam., 30 ins.
in the ground, with brass cap mkd.

$\frac{1}{4}$

S 13 | S 18

1947

1941

Raise a mound of stone, 4 ft. base, 3 ft. high,
W. of cor.

41.30

Drain, course SE. Asc. 455 ft. over S. slope.

62.70

Top of flat malpais ridge, from west, slopes gently
east for about 5 chs., thence in abrupt descent.

Desc. 450 ft. over rocky N. slope, changing to NE.

79.66

The original cor. of secs. 7, 12, 13 and 18.

Remove the iron post and destroy mound of stone.

80.00

Point for cor. of secs. 7, 12, 13 and 18.

Reset the iron post, 3 ft. long, 2 ins. diam., 24 ins.
in the ground, to bedrock, and in a mound of stone, 3
ft. base, to top, with brass cap mkd.

T1S

R19W | R18W

S 12 | S 7

S 13 | S 18

1941

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high,
W. of cor.

Land, mountainous and slightly rolling.
Soil, sandy and rocky, 3rd and 4th rate.
Scattering ironwood and paloverde; greasewood, cats claw,
ocotillo and cacti.

Resurvey of part of the E. Bdy. , T. 1 S., R. 19 W.

BOOK 4360

Chains

North, bet. secs. 7 and 12.

Over gently rolling land, through scattering timber and undergrowth.

Desc. 45 ft. over NE. slope.

5.00 Base of slope, bearing NW. and SE.

12.35 Wash, 25 lks. wide, course NW.

39.66 The original $\frac{1}{4}$ sec. cor.

Remove the iron post and destroy mound of stone.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 7 and 12.

Reset the iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S 12 | S 7

1941

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

44.50 Wash, 20 lks. wide, course NW.

48.15 Wash, 25 lks. wide, course NW.

57.90 Wash, 15 lks. wide, course SW.

79.66 The original cor. of secs. 1, 6, 7 and 12,

Remove the iron post and destroy mound of stone.

80.00 Point for cor. of secs. 1, 6, 7 and 12.

Reset the iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1S

R19W		R18W
S 1		S 6
S 12		S 7

1941

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, slightly rolling and level, draining W.

Soil, sandy, 3rd rate.

Scattering ironwood and paloverde; greasewood, cats claw and cacti.

Resurvey of part of the E. Bdy., T. 1 S., R. 19 W.

Chains

North, bet. secs. 1 and 6.

Over nearly level land, through scattering timber and undergrowth.

1.65 Wash, 25 lks. wide, course W.

18.60 Wash, 15 lks. wide, 6 ft. deep, course NW.

39.65 The original $\frac{1}{4}$ sec. cor. of secs. 1 and 6.

Remove the iron post and destroy mound of stone.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 1 and 6.

Reset the iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 1 | S 6
1941

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

53.25 Wash, 20 lks. wide, course W.

63.35 Wash, 20 lks. wide, course W.

69.35 Scraped roadway, leads SE. to Palm Canyon, from Highway 95 in section 33, T. 1 N., R. 19 W.

74.50 Scraped roadway, leads S. 30° E. to Palm Canyon, from NW.

75.24 The closing cor. of secs. 1 and 6, Ts. 1 S., Rs. 18 and 19 W., on the Gila and Salt River Base Line, which is an iron post, 3 ins. diam., firmly set, 10 ins. above ground, with brass cap mkd.

TLN R19W
S 36
S 1 | S 6
R19W | R18W
T1S
C C

1941

Witnessed by a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

The standard cor. of Ts. 1 N., Rs. 18 and 19 W., bears East, 2.30 chs. dist., marked by an iron post, 3 ins. diam., firmly set, 12 ins. above ground, conforming to the record.

Resurvey of part of the E. Bdy., T. 1 S., R. 19 W.

BOOK 4860

Chains

The standard $\frac{1}{4}$ sec. cor., on the S. bdy. of sec. 36, T. 1 N., R. 19 W., bears west, 37.70 chs. dist., marked by an iron post, 1 in. diam., firmly set, 12 ins. above ground, conforming to the record.

Land, nearly level.

Soil, sandy and rocky, 3rd rate.

Scattering paloverde and ironwood; greasewood and cacti.

SUBDIVISION of T. 1 S., R. 19 W.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., firmly set, 10 ins. above ground, conforming to the 1941 survey record.

N. 0° 01' W., bet. secs. 35 and 36.

Over slightly rolling land, through scattering undergrowth.

14.00 Wash, 25 lks. wide, 3 ft. deep, course NE.

26.50 Wash, 10 lks. wide, course N. 10° E.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 35 | S 36

1947

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

42.00 Wash, 15 lks. wide, 2 ft. deep, course N. 15° E.

Continue over washed land, draining N.

72.50 Wash, 15 lks. wide, 2 ft. deep, course NE.

80.00 Point for cor. of secs. 25, 26, 35 and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 32 ins. in the ground, with brass cap mkd.

T1S R19W

S 26 | S 25

S 35 | S 36

1947

Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Land, nearly level, draining to the N.

Soil, gravelly and rocky, 3rd rate.

Scattering ironwood, greasewood, paloverde and cacti.

Subdivision of T. 1. S. 8. R. 19 W.

Chains

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.

N. 89° 56' W., bet. secs. 25 and 36,

Over broken hills, through scattered undergrowth.

Desc. 130 ft. over W. slope.

6.00 Foot of slope. Over slightly rolling land, draining NW.

18.75 Wash, 10 lks. wide, 1 ft. deep, course NW.

30.80 Wash, 30 lks. wide, 2 ft. deep, course NW. Asc. slightly over NE. slope.

39.95 Point for $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, to bedrock, and in a mound of stone, 4 ft. base, 20 ins. high, with brass cap mkd.

$$\frac{1}{4} \frac{S 25}{S 36}$$

1947

Asc. 80 ft. over E. slope.

43.60 Short spur, slopes N. Desc. 100 ft. over W. slope.

50.00 Foot of slope; over level land, draining N.

58.40 Wash, 25 lks. wide, 2 ft. deep, course N. 10° W.

59.10 Wash, 15 lks. wide, 2 ft. deep, course N.

77.70 Wash, 15 lks. wide, 2 ft. deep, course N.

79.90 The cor. of secs. 25, 26, 35 and 36.

Land, slightly broken.
Soil, sandy and rocky, 3rd rate.
Scattering greasewood and cacti.

N. 0° 01' W., bet. secs. 25 and 26.

Over slightly rolling land, through scattering timber and undergrowth.

5.00 Wash, 20 lks. wide, 2 ft. deep, course NW.

28.50 Wash, 50 lks. wide, course NW.

37.00 Enter wash, 50 lks. wide, course N.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 25 and 26.

Subdivision of T. 1 S., R. 19 W.

BOOK 4362

Chains	
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 26 S 25 1947
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. W. of cor.
	Corner monument is situated against west bank of channel of wash, 10 lks. wide, course N. 10° W.
41.00	Leave washed area, course N, 30° W.
43.00	Enter wash area, draining N. and NW.
47.00	Wash, 50 lks. wide, course N. 20° W.
63.00	Wash, 15 lks. wide, course NW.
68.00	Wash, 15 lks. wide, course NW.
80.00	Point for cor. of secs. 23, 24, 25 and 26.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T1S R19W S 23 S 24 S 26 S 25 1947
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, slightly rolling, drains NW. Soil, gravelly, 3rd rate. Scattered ironwood and paloverde; greasewood and cacti.

	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.
	N. $89^{\circ} 56'$ W., bet. secs. 24 and 25.
	Over broken S. slope of rocky hill.
0.75	Gully, course S. Asc. 120 ft.
2.30	Short spur, slopes S.
7.50	Short flat spur, slopes S. Desc. 155 ft. over SW. slope.
16.00	Gully, course S. Desc. 86 ft. over gradual SW. slope.
30.00	Foot of slope, bearing NW. and SE.
34.20	Wash, 20 lks. wide, course S.
39.99	Point for $\frac{1}{4}$ sec. cor. of secs. 24 and 25.

.Subdivision of T. 1 S., R. 19 W.

Chains	
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	$\frac{1}{4} \frac{S\ 24}{S\ 25}$
	1947
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.
	Continue over nearly level land.
60.00	Wash, 10 lks. wide, 2 ft. deep, course N. 15° W.
79.98	The cor. of secs. 23, 24, 25 and 26.
	Land, broken hills in E., level in west half. Soil, rocky and sandy, 3rd and 4th rate. Scattered greasewood and aacti.

	N. 0° 01' W., bet. secs. 23 and 24.
	Over slightly rolling land, through scattered timber and undergrowth.
35.80	Wash, 20 lks. wide, 3 ft. deep, course N. 75° W.
40.00	Point for ¼ sec. cor. of secs. 23 and 24.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	$\frac{1}{4} \frac{S\ 23\ S\ 24}{S\ 23\ S\ 24}$
	1947
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
48.00	Wash, 10 lks. wide, 2 ft. deep, course S. 70° W.
49.00	Wash, 25 lks. wide, 2 ft. deep, course S. 85° W.
80.00	Point for cor. of secs. 13, 14, 23 and 24.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	$\frac{T1S\ R19W}{S\ 14\ S\ 13}$
	$S\ 23\ S\ 24$
	1947

Chains

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, nearly level.

Soil, sandy and rocky, 3rd. rate.

Scattered ironwood and paloverde; greasewood and cacti.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.

N.89°57'W., bet. secs. 13 and 24.

Over level land, through scattered timber and undergrowth.

4.70 Drain, course N.70°W.

39.95 Point for $\frac{1}{4}$ sec. cor. of secs. 13 and 24.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 13 \\ S 24 \end{array}$$

1947

Dig pits, 24 x 18 x 12 ins. E. and W. of cor., 3 ft. dist.

41.00 Wash, 50 lks. wide, course NW.

64.20 Wash, 1 ch. wide, course NW.

79.90 The cor. of secs. 13, 14, 23 and 24.

Land, level desert.

Soil, sandy and rocky, 3rd. rate.

Scattered paloverde, greasewood and cacti.

N.0°01'W., bet. secs. 13 and 14.

Over slightly rolling land, through scattered timber and undergrowth.

17.25 Wash, 1.20 chs. wide, course NW.

35.00 Wash, 75 lks. wide, course N.80°W.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 13 and 14.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 14 \\ S 13 \end{array}$$

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Subdivision of T.1 S., R.19 W.

Chains

56.50 Drain, 10 lks. wide, course N.20°W.

73.75 Wash, 15 lks. wide, 2 ft. deep, course N.15°W.

80.00 Point for cor. of secs. 11, 12, 13 and 14.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1S R19W
S 11 | S 12
S 14 | S 13

1947

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.

Land, slightly rolling.
Soil, rocky, 3rd. rate.
Scattered ironwood and paloverde; greasewood and cacti.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.

N. 89° 58' W. bet. secs. 12 and 13,
Over broken hills, N. slope of detached malpais ridge.

Asc. 220 ft. over NE. slope, changing to N.

22.00 Spur, slopes N.

25.15 Main spur of ridge, slopes N. Desc. 270 ft. over W. slope.

38.00 Foot of slope, bearing N. and S., Wash, 10 lks. wide, 3 ft. deep, course NW.

Over slightly rolling land.

39.96 Point for ¼ sec. cor. of secs. 12 and 13.

Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, to bedrock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

S 12
¼ S 13

1947

72.30 Wash, 15 lks. wide, 1 ft. deep, course N.20°W.

79.92 The cor. of secs. 11, 12, 13 and 14.

Land, broken hills in E. half mile; rolling to level plain in W. half.
Soil, rocky and sandy, 4th. and 3rd. rate.
Scattered greasewood, cacti and paloverde.

N.0°01'W., bet. secs. 11 and 12.

Over nearly level land, through scattered timber and undergrowth.

Chains

14.40 Wash, 15 lks. wide, 2 ft. deep, course W.

21.90 Wash, 8 lks. wide, 2 ft. deep, course S.75°W.

28.10 Wash, 5 lks. wide, 2 ft. deep, course W.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 11 and 12.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4}$$

$$S\ 11\ | \ S\ 12$$

1947

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

60.00 Wash, 15 lks. wide, course W.

73.80 Wash, 15 lks. wide, 3 ft. deep, course N.80°W.

80.00 Point for cor. of secs. 1, 2, 11 and 12.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

$$T1S\ R19W$$

$$S\ 2\ | \ S\ 1$$

$$S\ 11\ | \ S\ 12$$

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, nearly level.

Soil, sandy, subsoil hardpan, 3rd. rate.

Scattered greasewood, paloverde, ironwood and cacti.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.

West, on true line bet. secs. 1 and 12.

Over nearly level land, through scattered undergrowth.

39.94 Point for $\frac{1}{4}$ sec. cor. of secs. 1 and 12.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S\ 1}{S\ 12}$$

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

45.50 Wash, 10 lks. wide, course SW. to W.


Chains

54.25 Confluence of washes, from NE. and SE., course S.80°W.
 62.20 Same wash, 15 lks. wide, 1 ft. deep, course NW.
 79.88 The cor. of secs. 1, 2, 11 and 12.
 Land, level, draining W.
 Soil, sandy, 3rd. rate.
 Scattered greasewood and cacti; a few paloverde and iron-wood.

 N.0°01'W., bet. secs. 1 and 2.

Over nearly level land, through scattered undergrowth.

7.80 Wash, 20 lks. wide, 2 ft. deep, course N.80°W.
 19.50 Wash, 10 lks. wide, 3 ft. deep, course N.60°W.
 40.00 Point for 1/4 sec. cor., of secs. 1 and 2.
 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.




Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

45.60 Wash, 10 lks. wide, 2 ft. deep, course NW.
 56.20 Wash, 15 lks. wide, 2 ft. deep, course N.60°W.
 66.15 Scraped roadway, bears S.80°E. and N.80°W.
 69.50 Wash, 10 lks. wide, 2 ft. deep, course N.60°W.
 72.10 Wash, 20 lks. wide, 2 ft. deep, course W.
 75.16 Intersect the Gila and Salt River Base Line; point for closing cor. of secs. 1 and 2.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.



1947

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.

The standard cor. of secs. 35 and 36, T.1 N., R.19 W. bears N.89°58'E., 2.08 chs. dist., marked by an iron post, 3 ins. diam., firmly set, 12 ins. above ground, conforming to the record.

Chains

The standard $\frac{1}{4}$ sec. cor., on the S. bdy. of sec. 35, T.1 N., R.19 W., bears S.89°58'W., 37.92 chs. dist; marked by an iron post, 1 in. diam., firmly set, 18 ins. above ground, conforming to the record.

Land, level, draining W. and NW.
Soil, sandy, subsoil hardpan, 3rd. rate.
Scattered greasewood, cacti and bayonet; paloverde and ironwood along washes.

At mid-point on the N. bdy. of sec. 1, S.89°58'W., 2.19 chs. dist., from the standard $\frac{1}{4}$ sec. cor. of sec. 36, T.1 N. R.19 W., at point for $\frac{1}{4}$ sec. cor. of sec. 1 only

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 1

1947

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, S. of cor.

The standard cor. of secs. 35 and 36, T.1 N., R.19 W., bears S.89°58'W., 37.81 chs. dist.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., 24 ins. above ground, supported in a mound of stone, 4 ft. base, to top, marked as described in the 1941 survey record.

N.0°01'W., bet. secs. 34 and 35.

Over broken land, through scattered undergrowth. Desc. 50 ft. over gradual NW. slope.

9.60 Wash, 20 lks. wide, 3 ft. deep, course N.80°W.

22.30 Wash, 15 lks. wide, 2 ft. deep, course W.

37.50 Wash, 5 lks. wide, 1 ft. deep, course N.60°W.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 34 and 35.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, to bedrock, with brass cap mkd.

$\frac{1}{4}$

S 34 | S 35

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Asc. 60 ft. over SE. to E. slope of small detached hill.

54.50 Cross small spur, from low rocky peak, extending NE.

Desc. 85 ft.

Subdivision of T.1 S., R.19 W.

Chains							
75.90	Wash, 10 lks. wide, 2 ft. deep, from E. course W. and NW. Continue over nearly level land.						
80.00	Point for cor. of secs. 26, 27, 34 and 35. Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.						
	<table border="0"> <tr><td colspan="2">T1S R19W</td></tr> <tr><td>S 27</td><td>S 26</td></tr> <tr><td>S 34</td><td>S 35</td></tr> </table>	T1S R19W		S 27	S 26	S 34	S 35
T1S R19W							
S 27	S 26						
S 34	S 35						
	1947						
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.						
	Land, broken hills to slightly rolling. Soil, rocky, 3rd. rate. Scattered greasewood and cacti; paloverde, catsclaw and ironwood.						

	From the cor. of secs. 25, 26, 35 and 36.						
	S.89°59'W., bet. secs. 26 and 35.						
	Over broken and hilly land, through scattered undergrowth.						
2.50	Asc. 100 ft. over E. slope.						
13.20	Small spur, slopes N.20°E. Desc. 90 ft. over NW slope.						
20.00	Wash, 30 lks. wide, course N. Asc. 110 ft. over a gradually increasing NE. slope.						
32.00	Gully, course N. to NE. Change of slope to E.						
39.00	Change of slope to N., small spur slopes to NE.						
40.00	Point for ¼ sec. cor. of secs. 26 and 35. Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, to bedrock, and in a mound of stone, 5 ft. base, 1½ ft. high, with brass cap mkd.						
	<table border="0"> <tr><td>¼</td><td>S 26</td></tr> <tr><td></td><td>S 35</td></tr> </table>	¼	S 26		S 35		
¼	S 26						
	S 35						
	1947						
	Desc. 210 ft. over N. to NW. slope.						
63.50	Gully, course NW. Continue over slightly rolling land.						
69.80	Wash, 10 lks. wide, course NW.						
80.00	The cor. of secs. 26, 27, 34 and 35.						
	Land, broken. Soil, rocky, 3rd. and 4th. rate. Scattered greasewood and cacti; a few catsclaw and palo-verde.						

Subdivision of T.1 S., R.19 W.

BOOK 4360

Chains

N.0°01'W., bet. secs. 26 and 27.

Over nearly level land, through scattered undergrowth.

26.50 Wash, 10 lks. wide, course W. to SW.

33.00 Wash, 5 lks. wide, course W.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 26 and 27.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S 27 | S 26

1947

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

49.90 Wash, 15 lks. wide, course N.80°W.

54.90 Wash, 5 lks. wide, course N.75°W.

70.50 Wash, 8 lks. wide, 2 ft. deep, course N.60°W.

80.00 Point for cor. of secs. 22, 23, 26 and 27.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1S R19W

S 22 | S 23

S 27 | S 26

1947

Land, level, draining W.

Soil, sandy, 3rd. rate.

Scattered greasewood and cacti; a few paloverde and iron-wood along washes.

From the cor. of secs. 23, 24, 25 and 26.

N.89°58'W., bet. secs. 23 and 26.

Desc. slightly over flat NW. slope, through scattered undergrowth.

8.70 Wash, 10 lks. wide, 2 ft. deep, course N.20°W.

10.60 Wash, 20 lks. wide, course N.

18.30 Wash, 8 lks. wide, 2 ft. deep, course N.15°W.

20.80 Wash, 10 lks. wide, 1 ft. deep, course N.

27.60 Wash, 5 lks. wide, 1 ft. deep, course N.20°W.

39.95 Point for $\frac{1}{4}$ sec. cor. of secs. 23 and 26.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 23 \\ S 26 \end{array}$$

1947

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

67.00 Wash, 10 lks. wide, course NW.

77.80 Wash, 5 lks. wide, 1 ft. deep, course NW.

79.90 The cor. of secs. 22, 23, 26 and 27.

Land, nearly level, draining NW.

Soil, sandy, 3rd. rate.

Scattered ironwood, paloverde, greasewood and cacti.

N.0°01'W., bet. secs. 22 and 23.

Over level land, through scattered undergrowth.

12.90 Wash, 50 lks. wide, course N.70°W.

40.00 Point for ¼ sec. cor. of secs. 22 and 23.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 22 | S 23 \end{array}$$

1947

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

44.50 Flat wash, 1 ch. wide, course NW.

58.10 Wash, 1.50 chs. wide, course N.70°W. Enter flood plain, W. and NW.

80.00 Point for cor. of secs. 14, 15, 22 and 23.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{l} T1S R19W \\ S 15 | S 14 \\ S 22 | S 23 \end{array}$$

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, level, draining NW.

Soil, sandy, 3rd. rate.

Scattered greasewood and cacti; paloverde and ironwood.

Chains

From the cor. of secs. 13, 14, 23 and 24.

N.89°58'W., bet. secs. 14 and 23.

Over level land, through scattered undergrowth.

39.95 Point for $\frac{1}{4}$ sec. cor. of secs. 14 and 23.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 14 \\ S 23 \end{array}$$

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

61.00 Enter wash, or flood area, draining NW.

68.50 Channel of wash, 30 lks. wide, course NW.

72.90 Wash, 20 lks. wide, course N.60°W.

79.90 The cor. of secs. 14, 15, 22 and 23.

Land, level, draining W. and NW.

Soil, sandy, 3rd. rate.

Scattered greasewood and cacti; paloverde and ironwood.

N.0°01'W., bet. secs. 14 and 15.

Across wash area, through scattered undergrowth.

4.70 Wash channel, 10 lks. wide, 2 ft. deep, course N.70°W.

5.60 Wash, 10 lks. wide, 2 ft. deep, course W.

Continue over nearly level land.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 14 and 15.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 15 \\ S 14 \end{array}$$

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

43.40 Wash, 10 lks. wide, 2 ft. deep, course W.

80.00 Point for cor. of secs. 10, 11, 14 and 15.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{l} T1S R19W \\ S 10 | S 11 \\ S 15 | S 14 \end{array}$$

1947

Subdivision of T.1 S., R.19 W.

Chains

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, level, draining W. and NW.
Soil, sandy, 3rd. rate.
Scattered greasewood and cacti; paloverde and ironwood.

From the cor. of secs. 11, 12, 13 and 14.

N.89°58'W., bet. secs. 11 and 14.

Over level land, through scattered undergrowth.

2.70 Wash, 10 lks. wide, 2 ft. deep, course N.10°W.

Asc. 125 ft. over E. slope.

11.20 Top of low malpais hill, from S., small spur slopes to NW.

Desc. 125 ft.

20.00 Foot of descent, wash, 5 lks. wide, drains N.20°W.

Continue over nearly level land.

37.00 Wash, 15 lks. wide, 1 ft. deep, course N.10°W.

39.98 Point for ¼ sec. cor. of secs. 11 and 14.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

S 11
¼ S 14

1947

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

79.96 The cor. of secs. 10, 11, 14 and 15.

Land, nearly level; low detached, black malpais hill in E. portion.

Soil, sandy, and rocky, 3rd. rate.
Scattered greasewood and cacti.

N.0°01'W., bet. secs. 10 and 11.

Over level land, through scattered undergrowth.

9.70 Wash, 1 ch. wide, course NW.

40.00 Point for ¼ sec. cor. of secs. 10 and 11.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

¼
S 10 | S 11

1947

Chains

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

80.00 Point for cor. of secs. 2, 3, 10 and 11.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1S R19W
S 3 | S 2

S 10 | S 11

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, level, draining NW.

Soil, sandy, 3rd. rate.

Scattered greasewood and cacti; a few paloverde and iron-wood along washes.

From the cor. of secs. 1, 2, 11 and 12.

N. 89°57'W., bet. secs. 2 and 11.

Over level land, through scattered undergrowth.

9.70 Wash, 6 lks. wide, 1 ft. deep, course N.60°W.

13.90 Wash, 8 lks. wide, 1 ft. deep, course N.60°W.

23.70 Enter open gravel flat.

39.98 Point for ¼ sec. cor. of secs. 2 and 11.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

S 2
¼ | S 11

1947

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

61.75 Leave open gravel flat. Continue through scattered undergrowth.

79.96 The cor. of secs. 2, 3, 10 and 11.

Land, nearly level, draining NW.

Soil, sand and gravel, subsoil hardpan, 3rd. rate.

Scattered greasewood and cacti.

N.0°01'W., bet. secs. 2 and 3.

Over level land, through scattered undergrowth.

40.00 Point for ¼ sec. cor. of secs. 2 and 3.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 3 | S. 2

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

44.20 Drain, 10 lks. wide, course N.70°W.

48.00 Wash, 20 lks. wide, 2 ft. deep, course NW.

51.00 Wash, 10 lks. wide, 2 ft. deep, course W.

75.02 Intersect the Gila and Salt River Base line; point for closing cor. of secs. 2 and 3.

Set an iron post, 3 ft. long, .2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1N R19W

S 34

S 3 | S 2

CC

T1S R19W

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

The standard cor. of secs. 34 and 35, T.1 N., R.19 W., bears N.89°58'E., 2.06 chs. dist., marked by an iron post, 3 ins. diam., firmly set, conforming to the record.

The standard $\frac{1}{4}$ sec. cor., of sec. 34, T.1 N., R.19 W., bears S.89°58'W., 37.94 chs. dist., marked by an iron post, 1 in. diam., firmly set, 12 ins. above ground, conforming to the record.

Land, nearly level.

Soil, sandy, 3rd. rate.

Scattered greasewood, paloverde and cacti.

At mid-point on the N. bdy. of sec. 2, S.89°58'W., 2.07 chs. dist. from the standard $\frac{1}{4}$ sec. cor. of sec. 35, T.1 N., R.19 W., point for $\frac{1}{4}$ sec. cor. of sec. 2 only,

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 2

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, S. of cor.

Chains

The standard cor. of secs. 34 and 35, T.1 N., R.19 W., bears S.89°58'W., 37.93 chs. dist.


From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., firmly set, 8 ins., above ground, marked and witnessed as described in the 1941 survey record.

N.0°02'W., bet. secs. 33 and 34.

Over level land, through scattered undergrowth.

- 0.70 Wash, 10 lks. wide, 1 ft. deep, course N.75°W.
- 13.40 Wash, 15 lks. wide, 1 ft. deep, course NW.
- 21.40 Wash, 10 lks. wide, course N.80°W.
- 32.00 Wash, 10 lks. wide, 1 ft. deep, course NW.
- 40.00 Point for 1/4 sec. cor. of secs. 33 and 34.


Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with braas cap mkd.



Dig pits, 24 x 18 x 12 ins. N. and S. of cor., 3 ft. dist.

- 44.30 Wash, 10 lks. wide, 2 ft. deep, course N.70°W.
- 50.80 Wash, 10 lks. wide, 1 ft. deep, course N.80°W.
- 63.20 Drain ditch, scraped, course S.75°W.
- 73.20 Three wire power transmission line, on double wood poles, bears S.21°43'W., and N.21°43'E.
- 76.00 Scraped drainage ditch, course S.60°W.
- 79.60 State Highway No. 95, bears S.25°49'W., to Yuma, turning North, to Quartzsite.
- 80.00 Point for cor. of secs. 27, 28, 33 and 34, on margin of highway.

Set an iron post, 3 ft. long, 2 ins. diam., 50 ins. in the ground, with granite stone 9 x 9 x 3 ins., marked with cross + deposited alongside, with brass cap mkd.



1947

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor., 25 lks. dist., (beyond drainage ditch paralleling highway.)

Subdivision of T.1 S., R.19 W.

Chains

Pole No. 564, the center pole of three, at angle in power transmission line, bears N.40°57'E., 8.45 chs. dist.,

Pole No. 565, the near pole of two, in power transmission line, bears S.36°46'E., 3.01 chs. dist.

Land, level, draining NW.
Soil, sandy, 3rd. and 2nd. rate.
Scattered greasewood and cacti.

From the cor. of secs. 26, 27, 34 and 35.

Over level land, through scattered undergrowth.

S.89°59'W., bet. secs. 27 and 34.

- 4.80 Wash, 15 lks. wide, 1 ft. deep, course N.30°W.
- 23.00 Enter wash, 10 lks. wide, 2 ft. deep, course W. from SE.
- 27.80 Leave wash, course NW.
- 35.10 Wash, 10 lks. wide, 2 ft. deep, course N.20°E.
- 40.01 Point for $\frac{1}{4}$ sec. cor. of secs. 27 and 34.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ $\begin{matrix} S 27 \\ S 34 \end{matrix}$

1947

Dig pits, 24 x 18 x 12 ins., E. and W. of cor., 3 ft. dist.

- 49.00 Wash, 10 lks. wide, 2 ft. deep, course N.60°W.
- 69.50 Wash, - scraped drainage ditch, course NW.
- 75.90 Wash, 10 lks. wide, 1 ft. deep, course N.60°W.
- 77.17 Power transmission line, 3 wire on double wood poles, bears S.21°43'W., and N.21°43'E. North.
- 78.20 Scraped drainage ditch, course S.60°W.
- 79.75 State Highway No. 95, on curve, SW. to North.
- 80.02 Margin of Highway, and cor. of secs. 27, 28, 33 and 34.

Land, nearly level, draining NW.
Soil, sandy, 3rd. and 2nd. rate.
Scattered greasewood and cacti.

N.0°02'W., bet. secs. 27 and 28.

Over level land, through scattered undergrowth.

- 9.90 Wash, 40 lks. wide, course W.
- 30.00 Wash, 1.50 chs. wide, course N.70°W.

Subdivision of T.1 S., R.19 W.

BOOK 4360

Chains 39.50	Wash, 1 ch. wide, course N.80°W.
40.00	Point for $\frac{1}{4}$ sec. cor. of secs. 27 and 28. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 28 \mid S\ 27 \\ 1947 \end{array}$ from which A mesquite, 10 ins. diam., bears N.35 $\frac{1}{2}$ °W., 41 lks. dist., mkd. $\frac{1}{4}$ S28 BT A mesquite, 10 ins. diam., bears S.79 $\frac{1}{2}$ °E., 107 lks. dist., mkd. $\frac{1}{4}$ S27 BT
44.50	Wash, 2 chs. wide, course N.80°W.
56.00	Wash, 1.50 chs. wide, course N.75°W.
80.00	Point for cor. of secs. 21, 22, 27 and 28. Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd. $\begin{array}{c} T1S\ R19W \\ S\ 21 \mid S\ 22 \\ S\ 28 \mid S\ 27 \\ 1947 \end{array}$ Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor. Land, nearly level, draining NW. and W. Soil, sandy, 2nd. and 3rd. rate. Scattered greasewood and cacti; some mesquite along washes.

	From the cor. of secs. 22, 23, 26 and 27. N.89°59'W., bet. secs. 22 and 27. Over level land, through scattered undergrowth.
4.50	Wash, 30 lks. wide, course NW.
34.60	Wash, 70 lks. wide, course NW.
40.03	Point for $\frac{1}{4}$ sec. cor. of secs. 22 and 27. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 22 \\ S\ 27 \\ 1947 \end{array}$ Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
74.86	Three wire power transmission line, on double wood poles, bears N.0°14'W. and S.0°14'E.
75.50	Drainage ditch, paralleling highway.

Subdivision of T.1 S., R.19 W.

Chains	
76.95	State Highway, No. 95, bears N.0°13'W. and S.0°13'E.
80.06	The cor. of secs. 21, 22, 27 and 28. Land, level, draining NW. Soil, sandy, 2nd. and 3rd. rate. Scattered greasewood and cacti.

	N.0°02'W., bet. secs. 21 and 22. Over level land, through scattered undergrowth.
28.00	Drain, 25 lks. wide, course NW. to W.
40.00	Point for $\frac{1}{4}$ sec. cor. of secs. 21 and 22. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 21 S 22 1947
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
75.00	Drain, 20 lks. wide, course N.75°W.
80.00	Point for cor. of secs. 15, 16, 21 and 22. Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T1S R19W S 16 S 15 S 21 S 22 1947
	Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. Land, nearly level, draining NW. and W. Soil, sandy, 2nd. rate. Scattered greasewood and cacti.

	From the cor. of secs. 14, 15, 22 and 23. N.89°58'W., bet. secs. 15 and 22. Over level land, through scattered undergrowth.
22.40	Wash, 15 lks. wide, 2 ft. deep, course N.35°W.
40.05	Point for $\frac{1}{4}$ sec. cor. of secs. 15 and 22. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 15 S 22 1947
	Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
54.10	Wash, 20 lks. wide, course NW.

Chains

75.18 Power transmission line, bears N.0°14'W., and S.0°14'E.

77.25 State Highway No. 95, bears N.0°13'W. and S.0°13'E.

80.10 The cor. of secs. 15, 16, 21 and 22.

Land, level.

Soil, gravelly, 2nd. and 3rd. rate.

Scattered greasewood and cacti.

N.0°02'W., bet. secs. 15 and 16.

Over level land, through scattered undergrowth.

23.70 Wash, 70 lks. wide, course N.70°W.

29.50 Scraped roadway, extends N.60°W. from highway.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 15 and 16.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 16 \mid \text{S } 15 \\ 1947 \end{array}$$

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

53.40 Wash, 1 ch. wide, course NW.

80.00 Point for cor. of secs. 9, 10, 15 and 16.

Set an iron post, 3 ft. long, 2 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T1S R19W} \\ \text{S } 9 \mid \text{S } 10 \\ \text{S } 16 \mid \text{S } 15 \\ 1947 \end{array}$$

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, level, draining NW.

Soil, sandy, 2nd. rate.

Scattered greasewood and cacti.

From the cor. of secs. 10, 11, 14 and 15.

N.89°58'W., bet. secs. 10 and 15.

Over level land, through scattered undergrowth.

40.05 Point for $\frac{1}{4}$ sec. cor. of secs. 10 and 15.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \text{ S } 10 \\ \text{S } 15 \end{array}$$

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Subdivision of T.1 S., R.19 W.

Chains	
74.80	Drain, 30 lks. wide, course NW.
75.45	Power transmission line, 3 wire, on double poles, bears N.0°14'W. and S.0°14'E.
76.60	Drainage ditch, parallels highway.
77.50	State Highway No. 95, bears N.0°13'W. and S.0°13'E.
80.10	The cor. of secs. 9, 10, 15 and 16.
	Land, level. Soil, sandy, 2nd. rate. Scattered greasewood and cacti; a few paloverde.
	----- N.0°02'W., bet. secs. 9 and 10.
	Over level land, through scattered undergrowth.
3.10	Drain, course NW.
6.80	Wash, 15 lks. wide, 2 ft. deep, course NW.
38.20	Drain, 60 lks. wide, course NW.
40.00	Point for $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S\ 9\ \ S\ 10 \\ 1947 \end{array}$
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
80.00	Point for cor. of secs. 3, 4, 9 and 10.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} T1S\ R19W \\ S\ 4\ \ S\ 3 \\ S\ 9\ \ S\ 10 \\ 1947 \end{array}$
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Land, level, draining NW. Soil, sandy, 2nd. rate. Scattered greasewood and cacti; paloverde and catsclaw along washes.
	----- From the cor. of secs. 2, 3, 10 and 11.
	West, bet. secs. 3 and 10.
	Over level land, across open gravel flat.
4.00	Enter scattered undergrowth.
40.06	Point for $\frac{1}{4}$ sec. cor. of secs. 3 and 10.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S \ 3}{S \ 10}$$

1947

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

68.00 Scraped drainage ditch, 20 lks. wide, course NW.

75.75 Power transmission line, 3 wire, on double poles, bears N.0°14'W. and S.0°14'E.

77.77 State Highway No. 95; bears N.0°13'W. and S.0°13'E.

80.12 The cor. of secs. 3, 4, 9 and 10.

Land, level.
Soil, gravelly, 2nd. and 3rd. rate.
Scattered greasewood and cacti.

N.0°02'W., bet. secs. 3 and 4.

Over level land, through scattered undergrowth.

1.70 Drain, 75 lks. wide, course NW.

17.50 Wash, 50 lks. wide, course N.30°W.

40.00 Point for ¼ sec. cor. of secs. 3 and 4.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S \ 4 \mid S \ 3}{S \ 3}$$

1947

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

59.00 Wash, 1 ch. wide, course N.20°W.

74.90 Intersect the Gila and Salt River Base Line; point for closing cor. of secs. 3 and 4.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{l} \text{TLN R19W} \\ S \ 33_1 \\ \hline S \ 4 \mid S \ 3 \\ \text{CC} \\ \text{TLN R19W} \end{array}$$

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, S. of cor.

Chains

The standard cor. of secs. 33 and 34, T.1 N., R.19 W. bears N.89°56'E., 2.16 chs. dist., marked by the brass cap from original iron post monument 3 ins. diam., buried 30 ins. below the surface of State Highway No. 95.

Bury a lava stone, 12 x 6 x 6 ins., marked with a cross, +, under the brass cap.

From this standard corner monument, wooden markers, sawed pine posts, 4 ins. square, firmly set, 12 ins. above ground, bear East and West, 50 lks. dist. Pole No. 525, the near one of two on the power transmission line, bears N.89°58'E., 1.76 chs. dist.

From the closing cor. of secs. 3 and 4, the standard 1/4 sec cor. of sec. 33, T.1 N., R.19 W., bears S.89°56'W., 37.84 chs. dist., marked by an iron post, 1 in. diam., firmly set, 12 ins. above ground, conforming to the record,

Land, nearly level, draining NW.

Soil, sandy, 2nd. rate.

Scattered greasewood and cacti; some paloverde and cats-claw along washes.

At mid-point on the N. bdy. of sec. 3, S.89°58'W., 2.11 chs. dist. from the standard 1/4 sec. cor. of sec. 34, T.1 N. R.19 W., the point for 1/4 sec. cor. of sec. 3 only

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

1/4 S 3

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, S. of cor.

The standard cor. of secs. 33 and 34, T.1 N., R.19 W. bears S.89°58'W., 37.89 chs. dist.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., firmly set, 10 ins. above ground, marked and witnessed as described in the 1941 survey record.

N.0°02'W., bet. secs. 32. and 33.

Over nearly level land, through scattered timber and undergrowth.

30.30 Drainage ditch, parallels roadway.

38.20 Graded, and surfaced roadway, from Yuma to Quartzsite, now closed to traffic, bears S.10°15'W. to State Highway No. 95, and N.10°15'E.

39.10 Drain ditch, parallels road.

Chains

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 32 \mid \text{S } 33 \\ 1947 \end{array}$$

from which

A mesquite, 12 ins. diam., bears S. $6\frac{1}{4}^{\circ}$ E., 383 lks. dist., mkd. $\frac{1}{4}$ S33 BT

A mesquite, 10 ins. diam., bears S. $30\frac{1}{4}^{\circ}$ W., 278 lks. dist., mkd. $\frac{1}{4}$ S32 BT

Corner is situated on W. bank of old roadway.

80.00 Point for cor. of secs. 28, 29, 32 and 33.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T1S R19W} \\ \text{S } 29 \mid \text{S } 28 \\ \text{S } 32 \mid \text{S } 33 \end{array}$$

1947

from which

A catsclaw, 3 ins. diam., bears S. $19\frac{1}{4}^{\circ}$ E., 11 lks. dist., mkd. B T

Dig pits, 24 x 19 x 12 ins., in each section, 3 ft. dist., from corner monument.

Land, level, draining NW.

Soil, sand and silt, 2nd. rate.

Scattered greasewood, mesquite, catsclaw, paloverde and cacti.

From the cor. of secs. 27, 28, 33 and 34.

S. $89^{\circ}57'$ W., bet. secs. 28 and 33.

Over nearly level land, through scattered undergrowth.

40.04 Point for $\frac{1}{4}$ sec. cor. of secs. 28 and 33.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{\text{S } 28}{\text{S } 33}$$

1947

Dig pits, 24 x 19 x 12 ins., E. and W. of cor., 3 ft. dist.

50.00 Wash, 20 lks. wide, course NW.

Subdivision of T.1 S., R.19 W.

Chains

71.90 Drain, 5 lks. wide, course N.20°W.

73.50 Old graded roadway, bears N.10°15'E. and S.10°15'W.

80.08 The cor. of secs. 28, 29, 32 and 33.

Land, level.
Soil, sandy, 2nd. rate.
Scattered greasewood and cacti.

N.0°02'W., bet. secs. 28 and 29.

Over level land, through scattered undergrowth.

16.50 Wash, 10 lks. wide, course NW.

24.70 Wash, 10 lks. wide, course NW.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 28 and 29.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 29 | S 28
1947

Dig pits, 24 x 18 x 12 ins., N. and S. of cor., 3 ft. dist.

43.20 Wash, 10 lks. wide, 3 ft. deep, course W., turning to NW.

80.00 Point for cor. of secs. 20, 21, 28 and 29.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1S R19W
S 20 | S 21
S 29 | S 28

1947

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Land, level, draining NW.
Soil, sand and silt, 2nd. rate.
Scattered greasewood and cacti.

From the cor. of secs. 21, 22, 27 and 28:

S.89°56'W., bet. secs. 21 and 28.

Over level land, through scattered undergrowth.

40.03 Point for $\frac{1}{4}$ sec. cor. of secs. 21 and 28.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

Chains

$$\frac{1}{4} \frac{S 21}{S 28}$$

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

56.15 Old graded road, bears N., and curves slightly to SW.

80.06 The cor. of secs. 20, 21, 28 and 29.

Land, level, draining W. and NW.
Soil, sandy, 2nd. and 3rd. rate.
Scattered greasewood and cacti.

N.0°02'W., bet. secs. 20 and 21.

Over level land, through scattered undergrowth.

22.00 Enter washed area, draining NW.

39.50 Leave wash area.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 20 and 21.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4}$$

S 20	S 21
------	------

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

54.50 Flat wash, 1 ch. wide, course NW.

80.00 Point for cor. of secs. 16, 17, 20 and 21.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1S R19W	
S 17	S 16
S 20	S 21

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, level, draining NW.
Soil, sandy silt, 2nd. rate.
Scattered greasewood and cacti.

From the cor. of secs. 15, 16, 21 and 22.

S.89°56'W., bet. secs. 16 and 21.

Over level land, through scattered undergrowth.

Chains

24.60 Wash, 15 lks. wide, course NW.

32.50 Wash, 30 lks. wide, course NW.

40.05 Point for $\frac{1}{4}$ sec. cor. of secs. 16 and 21.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

54.50 Old graded road, bears N. and S.

80.10 The cor. of secs. 16, 17, 20 and 21.

Land, level, draining NW.
Soil, sandy, 2nd. rate.
Scattered greasewood and cacti.

N.0°02'W., bet. secs. 16 and 17.

Over level land, through scattered undergrowth.

33.00 Flat wash, 1.30 chs. wide, course N.60°W.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 16 and 17.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 17 | S 16

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

44.30 Road, bears N.80°W. and S.80°E.

66.20 Scraped roadway, bears N.75°W. and S.75°E.

80.00 Point for cor. of secs. 8, 9, 16 and 17.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1S R19W
S 8 | S 9
S 17 | S 16

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, level, draining NW.
Soil, sandy loam, 2nd. rate.

Chains

Scattered greasewood and cacti; a few paloverde and cats-claw along washes.

From the cor. of secs. 9, 10, 15 and 16.

S.89°53'W., bet. secs. 9 and 16.

Over level land, through scattered undergrowth.

40.02 Point for $\frac{1}{4}$ sec. cor. of secs. 9 and 16.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 9 \\ S 16 \end{array}$$

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

57.45 Old graded roadway, bears N. and S.

61.75 Wash, 10 lks. wide, course N.70°W.

80.04 The cor. of secs. 8, 9, 16 and 17.

Land, level, draining W. and NW.

Soil, sandy, 2nd. and 3rd. rate.

Scattered greasewood and cacti, paloverde and catsclaw.

N.0°02'W., bet. secs. 8 and 9.

Over level land, through scattered undergrowth.

2.00 Wash, 10 lks. wide, course N.70°W.

37.70 Wash, 20 lks. wide, course N.70°W.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 8 and 9.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 8 \\ S 9 \end{array}$$

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

55.80 Wash, 50 lks. wide, course N.70°W.

67.20 Wash, 25 lks. wide, course N.70°W.

80.00 Point for cor. of secs. 4, 5, 8 and 9.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

Chains

T1S R19W

S 5 | S 4

S 8 | S 9

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, level desert, draining W. and NW.
Soil, sandy silt, 2nd. rate.
Scattered greasewood.

From the cor. of secs. 3, 4, 9 and 10.

S.89°57'W., bet. secs. 4 and 9.

Over level land, through scattered undergrowth.

40.06 Point for 1/4 sec. cor. of secs. 4 and 9.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

1/4 S 4
S 9

1947

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

58.10 Old graded road, bears N. and S.

64.60 Wash, 50 lks. wide, course N.70°W.

80.12 The cor. of secs. 4, 5, 8 and 9.

Land, level, draining NW.
Soil, sandy silt, 2nd. rate.
Scattered greasewood and cacti.

N.0°02'W., bet. secs. 4 and 5.

Over level land, through scattered undergrowth.

15.00 Drain, 5 chs. wide, course N.20°W.

40.00 Point for 1/4 sec. cor. of secs. 4 and 5.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

1/4
S 5 | S 4

1947

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

64.00 Drain, 1 ch. wide, course N.20°W.

Subdivision of T.1 S., R.19 W.

BOOK 4360

Chains

74.90

Intersect the Gila and Salt River Base Line; point for closing cor. of secs. 4 and 5.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1N R19W

S 32

S 5 | S 4

CC

T1S R19W

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

The standard cor. of secs. 32 and 33, T.1 N., R.19 W., bears N.89°58'E., 2.36 chs. dist., marked by an iron post, 3 ins. diam., firmly set, 12 ins. above ground, conforming to the record.

The standard $\frac{1}{4}$ sec. cor. of sec. 32, T.1 N., R.19 W. bears S.89°58'W., 37.64 chs. dist., marked by an iron post, 1 in. diam., firmly set, 12 ins. above ground, conforming to the record.

Land, level desert, draining NW.

Soil, sandy, 2nd. rate.

Scattered greasewood and cacti.

At mid-point on the N. bdy. of sec. 4, S.89°56'W., 2.26[✓] chs. dist. from the standard $\frac{1}{4}$ sec. cor. of sec. 33, T.1 N. R.19 W., the point for $\frac{1}{4}$ sec. cor. of sec. 4 only

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 4

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

The standard cor. of secs. 32 and 33, T.1 N., R.19 W. bears S.89°56'W., 37.74' chs. dist.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., firmly set, 8 ins. above ground, marked and witnessed as described in the 1941 survey record.

N.0°03'W., bet. secs. 31 and 32.

Over nearly level land, through scattered undergrowth.

40.00

Point for $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

Chains	
	$\frac{1}{4}$ S 31 S 32 1947 Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
54.70	Drain, 40 lks. wide, course NE.
70.50	Wash, 1 ch. wide, course NE.
80.00	Point for cor. of secs. 29, 30, 31 and 32. Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd. T1S R19W S 30 S 29 S 31 S 32 1947 Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, level, draining NE. Soil, sandy, 2nd. rate. Scattered greasewood and cacti.

	From the cor. of secs. 28, 29, 32 and 33. West, bet. secs. 29 and 32. Over level land, through scattered undergrowth.
3.00	Enter washed ares, 7 chs. wide, draining N.
28.00	Enter drainage area, timbered and brushy, course N.
29.20	Main wash, 1.20 chs. wide, course N.
35.00	Leave wash area.
40.03	Point for $\frac{1}{4}$ sec. cor. of secs. 29 and 32. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S 29 S 32 1947 Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
80.06	The cor. of secs. 29, 30, 31 and 32. Land, nearly level, draining N. Soil, sandy silt, 2nd. rate. Scattered greasewood and cacti; ironwood, mesquite, palo-verde and catsclaw along water course.

Subdivision of T.1 S., R.19 W.

BOOK 4360

Chains

West, bet. secs. 30 and 31.

Over level land, draining NE., through scattered undergrowth.

- 4.20 Drain, 15 lks. wide, course NE.
 10.00 Asc. a gradually increasing E. slope. 320 ft. over rocky land.
 40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 30 and 31.

Set an iron post, 3 ft. long, 1 in. diam., 22 ins. in the ground, to rock, and in a mound of stone, 4 ft. base, 14 ins. high, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 30 \\ \hline \frac{1}{4} \text{ S } 31 \end{array}$$

1947

Continue ascent 210 ft. over rocky E. slope.

- 56.00 Top of ascent, short ridge, bears N. and S. Desc. 300 ft. over W. slope.
 71.90 Gulch, course N.15°E., Asc. 60 ft. over precipitous NE. slope.
 74.30 Intersect the E. bdy. of T.1 S., R.20 W., Point for closing cor. of secs. 30 and 31.

Set an iron post, 3 ft. long, 2 ins. diam., on surface rock, supported in a mound of stone 6 ft. base, 30 ins. high, with brass cap mkd.

$$\begin{array}{r} \text{T1S} \\ \text{T1S} \text{ | R19W} \\ \text{S } 25 \text{ | S } 30 \text{ CC} \\ \text{R20W} \text{ | S } 31 \end{array}$$

1947

Deposit a conglomerate stone, 12 x 8 x 6 ins. marked with a cross + at base of post.

The cor. of secs. 25, 30, 31 and 36 bears South, 11.10 chs. dist., marked by an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the 1916 survey record. This corner is changed to refer to secs. 25 and 36, of R.20 W.,

Alter markings on brass cap to read

$$\begin{array}{r} \text{T1S} \\ \text{R20W} \text{ |} \\ \text{S } 25 \text{ |} \\ \text{S } 36 \text{ |} \end{array}$$
1947
1916

From the closing cor. of secs. 30 and 31, the $\frac{1}{4}$ sec. cor. of secs. 25 and 30 bears North, 28.90 chs. dist., marked by an iron post, 1 in. diam., firmly set, marked and witnessed as described in the 1916 survey record.

Chains

This corner is changed to a $\frac{1}{4}$ sec. cor. of sec. 25 only.
Alter markings on the brass cap to read

$\frac{1}{4}$
S 25
1947
1916

Land, level and mountainous.
Soil, sandy silt to rock, 2nd. to 4th. rate.
Scattered greasewood and cacti.

At mid-point on the W. bdy. of sec. 31, and point for $\frac{1}{4}$ sec. cor. of sec. 31 only

Set an iron post, 3 ft. long, 1 in. diam., on surface rock, supported in a mound of stone 8 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$
S 31
1947

Corner monument is situated on north edge of drain, course E., on rocky E. slope, visible from the East only.

The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, bears South 11.09 chs., dist., marked by an iron post, 1 in. diam., firmly set, marked and witnessed as described in the 1916 survey record. This corner is changed to a $\frac{1}{4}$ sec. cor. of sec. 36 only.

Alter markings on the brass cap to read

$\frac{1}{4}$
S 36
1947
1916

From this $\frac{1}{4}$ sec. cor., the closing cor., of secs. 6 and 31 Ts.1 & 2 S., R.19 W., bears South 28.92 chs. dist., marked by an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the 1941 survey record.

From the cor. of secs. 29, 30, 31 and 32.

N.0°03'W., bet. secs. 29 and 30.

Over level land, through scattered undergrowth.

4.00 Drain, course NE.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 29 and 30.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

Chains

$\frac{1}{4}$
S 30 | S 29
1947

Dig pits, 24 x 18 x 12 ins., N. and S. of cor., 3 ft. dist.

80.00 Point for cor. of secs. 19, 20, 29 and 30.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1S R19W
S 19 | S 20
S 30 | S 29
1947

Land, level, draining NE.
Soil, sandy silt, 2nd. rate.
Scattered greasewood and cacti.

From the cor. of secs. 20, 21, 28 and 29.

N.89°59'W., bet. secs. 20 and 29.

Over level land, through scattered undergrowth.

16.75 Wash, main water course, 30 lks. wide, 3 ft. deep, course N.20°W., from South.

40.02 Point for $\frac{1}{4}$ sec. cor. of secs. 20 and 29.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 20
S 29
1947

Dig pits, 20 x 18 x 12 ins., E. and W. of cor., 3 ft. dist.

80.04 The cor. of secs. 19, 20, 29 and 30.

Land, level, draining N.
Soil, sandy silt, 2nd. rate.
Scattered greasewood; mesquite, paloverde, ironwood and catsclaw along wash.

West, bet. secs. 19 and 30.

Over nearly level land, draining NE., through scattered undergrowth.

22.00 Drain, 5 lks. wide, course NE.

33.00 Wash, 40 lks. wide, course N.30°E.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 19 and 30.

Subdivision of T.1 S., R.19 W.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 19 \\ \hline \text{S } 30 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

43.50 Wash, 50 lks. wide, 2 ft. deep, course N.20°W., from SW. Asc. 180 ft. over SE. slope of volcanic hill.

66.50 Top of ascent, spur slopes S.30°W., to low divide. Desc. 160 ft. over SW. slope.

73.50 Gully, course NW. Continue over gradual N. slope.

74.20 Intersect the E. bdy. of sec. 24, T.1 S., R.20 W., Point for closing cor. of secs. 19 and 30.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, to bedrock, with brass cap mkd.

$$\begin{array}{r} \text{T1S} \\ \text{R20W} \mid \text{R19W} \\ \text{S } 24 \mid \text{S } 19 \\ \hline \text{S } 30 \end{array} \text{CC}$$

1947

Raise a mound of stone, 2½ ft. base, 2 ft. high, E. of cor.

The cor. of secs. 19, 24, 25 and 30, bears South, 11.14 chs. dist., marked by an iron post, 3 ins. diam., firmly set, 10 ins. above ground, marked and witnessed as described in the 1916 survey record. This corner is changed to refer to secs. 24 and 25 only, of R.20 W.,

Alter the markings on brass cap to read

$$\begin{array}{r} \text{T1S} \\ \text{R20W} \\ \text{S } 24 \mid \\ \hline \text{S } 25 \end{array}$$

1947
1916

From the closing cor. of secs. 19 and 30, the ¼ sec. cor. of secs. 19 and 24 bears North 28.86° chs. dist., marked by an iron post, 1 in. diam., firmly set, marked and witnessed as described in the 1916 survey record.

This corner is changed to a ¼ sec. cor. of sec. 24 only.

Alter the markings on brass cap to read


$$\begin{array}{r} \frac{1}{4} \\ \text{S } 24 \mid \\ \hline 1947 \\ 1916 \end{array}$$

Chains

Land, nearly level in E. $\frac{1}{2}$; mountainous in W. $\frac{1}{2}$.
Soil, sandy to rock, 2nd. and 4th. rate.
Scattered greasewood and cacti; a few ironwood and palo-
verde along washes.

At mid-point on the W. bdy. of sec. 30, and point for $\frac{1}{4}$
sec. cor. of sec. 30 only

Set an iron post, 3 ft. long, 1 in. diam., over cross + ,
on surface rock, in a mound of stone, 8 ft. base, to top,
with brass cap mkd.



Corner is situated on apex of rocky spur, sloping E.

The $\frac{1}{4}$ sec. cor. of sec. 25 bears South, 11.12 chs.
dist., and the cor. of secs. 24 and 25, bears North
28.88 chs. dist.


From the cor. of secs. 19, 20, 29 and 30.

N.0°03'W., bet. secs. 19 and 20.

Over level land, through scattered undergrowth.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 19 and 20.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the
ground, with brass cap mkd.




Raise a mound of stone 2 $\frac{1}{2}$ ft. base, 2 ft. high, W.
of cor.

64.50 Wash, 1 ch. wide, course NW.

80.00 Point for cor. of secs. 17, 18, 19 and 20.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the
ground, with brass cap mkd.



Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W.
of cor.

Land, level.
Soil, sandy, 2nd. rate.
Scattered greasewood and cacti.

Subdivision of T.1 S., R.19 W.

Chains	
	From the cor. of secs. 16, 17, 20 and 21. West, bet. secs. 17 and 20. Over level land, through scattered undergrowth.
25.50	Enter washed area, draining NW.
38.60	Main wash, 60 lks. wide, 3 ft. deep, course N.20°W., dense growth of timber and underbrush along wash.
40.00	Point for $\frac{1}{4}$ sec. cor. of secs. 17 and 20. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. $\frac{1}{4} \begin{array}{l} S 17 \\ S 20 \end{array}$ 1947 Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
46.00	Leave wash area, draining N.20°W.
80.00	The cor. of secs. 17, 18, 19 and 20. Land, level. Soil, sandy silt, 2nd. rate. Scattered greasewood; mesquite, ironwood, paloverde and catsclaw along wash.

	West, bet. secs. 18 and 19. Over level land, draining N. and NW., through scattered undergrowth.
18.00	Flat wash, 1 ch. wide, course N.30°W.
40.00	Point for $\frac{1}{4}$ sec. cor. of secs. 18 and 19. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. $\frac{1}{4} \begin{array}{l} S 18 \\ S 19 \end{array}$ 1947 Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.
55.00	Drain, 5 chs. wide, course N.20°W., from S. and SW.
70.00	Wash, 50 lks. wide, course N.20°E.
74.17	Intersect the E. bdy. of sec. 13, T.1 S., R.20 W., Point for closing cor. of secs. 18 and 19. Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

Chains

T1S	
R20W	R19W
S 13	S 18
	S 19

CC

1947

Raise a mound of stone, 2½ ft. base, 2 ft. high, E. of cor.

The cor. of secs. 13, 18, 19 and 24, bears South 11.10 chs. dist., marked by an iron post, 3 ins. diam., firmly set, 6 ins. above ground, marked and witnessed as described in the 1916 survey record. This corner is changed to refer to secs. 13 and 24 only, of R.20 W.

Alter the markings on brass cap to read

T1S	
R20W	
S 13	
S 24	

1947
1916

From the closing cor. of secs. 18 and 19, the ¼ sec. cor. of secs. 13 and 18 bears North, 28.90 chs. dist., marked by an iron post, 1 in. diam., firmly set, 6 ins. above ground, marked and witnessed as described in the 1916 survey record.

This corner is changed to a ¼ sec. cor. of sec. 13 only.

Alter the markings on brass cap to read

¼	
S 13	

1947
1916

Land, nearly level, draining N. and NW.
Soil, sandy, 2nd. rate.
Scattered greasewood and cacti.

At mid-point on the W. bdy. of sec. 19, and point for ¼ sec. cor. of sec. 19 only

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

¼

S 19

1947.

Raise a mound of stone, 2 ft. base, 2 ft. high, E. of cor.

Subdivision of T.1 S., R.19 W.

Chains	
	<p>The $\frac{1}{4}$ sec. cor. of sec. 24 bears South, 11.12 chs. dist., and the cor. of secs. 13 and 24 bears North, 28.88 chs. dist.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20 N.0°03'W., bet. secs. 17 and 18.</p> <p>Over level land, through scattered undergrowth.</p>
40.00	<p>Point for $\frac{1}{4}$ sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S 18 S 17 1947 </div> <p>Dig pits, 24 x 18 x 12 ins., N. and S. of cor., 3 ft. dist.</p>
71.30	Road, bears N.80°W. and S.80°E.
72.70	Road, bears E. and W., (segment of same road).
75.00	Drain, 10 lks. wide, course NW.
80.00	<p>Point for cor. of secs. 7, 8, 17 and 18.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T1S R19W S 7 S 8 S 18 S 17 1947 </div> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>Land, level. Soil, sandy, 2nd. rate. Scattered greasewood and cacti.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17. N.89°59'W., bet. secs. 8 and 17.</p> <p>Over level land, through scattered undergrowth.</p>
1.00	Wash, 15 lks. wide, course N.80°W.
36.80	Scraped roadway, bears N.40°W. and S.30°E.
39.99	<p>Point for $\frac{1}{4}$ sec. cor. of secs. 8 and 17.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p>

Subdivision of T.1 S., R.19 W.

BOOK 1960

Chains

$$\frac{1}{4} \begin{array}{l} S 8 \\ S 17 \end{array}$$

1947

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 58.30 Channel of wash, 20 lks. wide, course N.20°W.
- 59.40 Channel of wash, 20 lks. wide, course N.20°W., Dense growth of mesquite, ironwood, paloverde and catsclaw along washes.
- 79.98 The cor. of secs. 7, 8, 17 and 18.
- Land, level.
Soil, sandy silt, 2nd. rate.
Scattered greasewood and cacti.

West, bet. secs. 7 and 18.

Over level land, through scattered undergrowth.

- 5.20 Drain, 1 ch. wide, course NW
- 40.00 Point for ¼ sec. cor. of secs. 7 and 18.
- Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 7 \\ S 18 \end{array}$$

1947

Dig pits, 24 x 18 x 12 ins., E. and W. of cor., 3 ft. dist.

- 54.00 Drain, 2 chs. wide, course NW.
- 61.90 Road, bears N.70°W. and S.80°E.
- 74.07 Intersect the E. bdy. of sec. 12, T.1 S., R.20 W., Point for closing cor. of secs. 7 and 18.
- Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{l} T1S \\ R19W \\ R20W \left| \begin{array}{l} S 7 \\ S 18 \end{array} \right. CC \\ S 12 \left| \begin{array}{l} S 7 \\ S 18 \end{array} \right. \end{array}$$

1947

Raise a mound of stone, 2 ft. base, 2 ft. high, E. of cor.

The cor. of secs. 7, 12, 13 and 18, bears S.0°03'W. 11.10 chs. dist., marked by an iron post, 3 ins. diam., firmly set, 8 ins. above ground, marked and witnessed as described in the 1916 survey record. This corner is changed to refer to secs. 12 and 13 only, of R.20 W.

Chains

Alter markings on brass cap to read

T1S
R20W
S 12
S 13
1947
1916

From the closing cor. of secs. 7 and 18, the $\frac{1}{4}$ sec. cor. of secs. 7 and 12 bears N.0°03'E., 28.90 chs. dist., marked by an iron post, 1 in. diam., firmly set, 2 ins. above ground, marked and witnessed as described in the 1916 survey record.

This corner is changed to a $\frac{1}{4}$ sec. cor. of sec. 12 only.

Alter the markings on brass cap to read

$\frac{1}{4}$
S 12
1947
1916

Land, level.
Soil, sandy, 2nd. rate.
Scattered greasewood and cacti.

At mid-point on the W. bdy. of sec. 18, and point for $\frac{1}{4}$ sec. cor. of sec. 18 only

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 18
1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

The $\frac{1}{4}$ sec. cor. of sec. 13 bears South, 11.10 chs. dist., and the cor. of secs. 12 and 13 bears North, 28.90 chs. dist.

From the cor. of secs. 7, 8, 17 and 18.

N.0°03'W., bet. secs. 7 and 8.

Over level land, through scattered undergrowth.

15.50 Scraped road, bears N.80°W. and S.80°E.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 7 and 8.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

Chains

$$\frac{1}{4}$$

S 7		S 8
-----	--	-----

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

80.00 Point for cor. of secs. 5, 6, 7 and 8.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1S R19W		
S 6		S 5
S 7		S 8

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, level.
Soil, gravelly silt, 2nd. rate.
Scattered greasewood.

From the cor. of secs. 4, 5, 8 and 9.

N.89°59'W., bet. secs. 5 and 8.

Over level land, through scattered undergrowth.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 5 and 8.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S 5}{S 8}$$

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

63.10 Wash, main drainage channel, 50 lks. wide, 2 ft. deep, course N.10°W. Dense growth of ironwood, paloverde and mesquite along water course.

80.00 The cor. of secs. 5, 6, 7, and 8.

Land, level.
Soil, gravelly silt, 2nd. rate.
Scattered greasewood and cacti.

West, bet. secs. 6 and 7.

Over level land, through scattered undergrowth.

34.00 Wash, 40 lks. wide, course N.20°W.

Subdivision of T.1 S., R.19 W.

Chains

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 6 and 7.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 6
S 7

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

73.91 Intersect the E. bdy. of sec. 1, T.1 S., R.20 W., Point for closing cor. of secs. 6 and 7.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T1S
T1S R19W
R20W | S 6
S 1 | S 7 CC

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

The cor. of secs. 1, 6, 7 and 12, bears South, 11.14 chs. dist., marked by an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the 1916 survey record. This corner is changed to refer to secs. 1 and 12, only, of R.20 W.

Alter the markings on brass cap to read.

T1S
R20W |
S 1 |
S 12 |

1947
1916

From the closing cor. of secs. 6 and 7, the $\frac{1}{4}$ sec. cor. of secs. 1 and 6 bears North, 28.86 chs. dist., marked by an iron post, 1 in. diam., firmly set, 10 ins. above ground, marked and witnessed as described in the 1916 survey record.

This corner is changed to a $\frac{1}{4}$ sec. cor. of sec. 1 only.

Alter the markings on brass cap to read

$\frac{1}{4}$
S 1 |
1947
1916

Land, level.
Soil, gravelly silt, 2nd. rate.
Scattered greasewood and cacti.

Chains

At mid-point on the W. bdy. of sec. 7, and point for $\frac{1}{4}$ sec. cor. of sec. 7 only,

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S 7

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

The $\frac{1}{4}$ sec. cor. of sec. 12 bears S.0°03'W., 11.12 chs. dist., and the cor. of secs. 1 and 12 bears N.0°03'E., 28.88 chs. dist.

At 40.00 chs. North, on the W. bdy. of sec. 6, and point for $\frac{1}{4}$ sec. cor. of sec. 6 only

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S 6

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

The $\frac{1}{4}$ sec. cor. of sec. 1 bears South, 11.14 chs. dist.,

The closing cor. of secs. 1 and 6, Ts.1 S., Rs. 19 and 20 W., bears North, ~~34.84~~ chs. dist., marked by an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the 1916 survey record.

From the cor. of secs. 5, 6, 7 and 8.

N.0°03'W., bet. secs. 5 and 6.

Over level land, through scattered undergrowth.

27.00 Drain, 1.50 chs. wide, course NW.

36.00 Drain, 1 ch. wide, course N.30°W.

40.00 Point for $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S 6 | S 5


1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Subdivision of T.1 S., R.19 W.

Chains
 51.90 Enter main drainage wash, 25 lks. wide, 3 ft. deep, course N., Dense growth mesquite, ironwood, and paloverde along same.
 60.00 Leave wash, course N.10°W.
 70.90 Channel of main wash, 15 lks. wide, 2 ft. deep, course N.10°E.
 74.84 Intersect the Gila and Salt River Base Line; point for closing cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.



1947

Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.


The standard cor. of secs. 31 and 32, T.1 N., R.19 W. bears N.89°59'E., 2.40 chs. dist., marked by an iron post, 3 ins. diam., firmly set, 8 ins. above ground, conforming to the record.

The standard ¼ sec. cor. of sec. 31 bears S.89°59'W. 37.60 chs. dist., marked by an iron post, 1 in. diam. firmly set, 8 ins. above ground, conforming to the record.

Land, level, draining N.
 Soil, gravelly and sandy silt, 2nd. rate.
 Scattered greasewood and cacti.

 At mid-point on the N. bdy. of sec. 5, S.89°58'W., 2.38^v chs. dist. from the standard ¼ sec. cor. of sec. 32, T.1 N. R.19 W., the point for ¼ sec. cor. of sec. 5 only.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.



1947

Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.

The standard cor. of secs. 31 and 32, T.1 N., R.19 W. bears S.89°58'W., 37.62^v chs. dist.

 At 40.00 chs. in departure on the N. bdy. of sec. 6, and point for ¼ sec. cor. of sec. 6 only

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

Chains

 $\frac{1}{4}$ S 6

1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

The standard $\frac{1}{4}$ sec. cor. of sec. 31, T.1 N., R.19 W. bears N.89°54'E., 2.40 chs. dist.

The closing cor. of secs. 1 and 6, Ts.1 S., Rs. 19 and 20 W., bears S.89°54'W., 33.93 chs. dist.

The standard cor. of secs. 31 and 36, Ts.1 N., Rs. 19 and 20 W., bears S.89°54'W., 37.60 chs. dist. marked by an iron post, 3 ins. diam., firmly set, conforming to the record.

 GENERAL DESCRIPTION

This township lies in the upper, or southern reaches of La Posa Plain, embracing some of the detached hills of the Castle Dome mountain range in the south-east, and to a stringer of the Chocolate mountains in the westerly portion of sections 31 and 30. The soil is an alluvial sand and gravel, with a silt deposit predominating in the central drainage basin. There is no water; rainfall is minimal. and the vegetation characteristic of the desert regions.

Settlement is non-existent, there is no grazing or animal husbandry; no indications of mineral deposits. State Highway No. 95, an improved gravelled surfaced road, from Yuma, 60 miles, North to Quartzsite, 25 miles distant, extends through the center of the township. A lateral road, scraped but unsurfaced, extends westerly through sections 16 to 7, to the Colorado River and the Cibola district.

98
54

4-680
(Revised May 1934)

UNITED STATES
DEPARTMENT OF THE INTERIOR
~~GENERAL LAND OFFICE~~
BUREAU OF LAND MANAGEMENT.

BOOK 4360

FIELD ASSISTANTS

NAMES	CAPACITY
Elliott Pearson	Engineering Aide.
John G. Coverdale	Principal Assistant.
C. Albert White	Principal Assistant.
Eugene C. Ramstedt	Chainman.
Ross C. Holden	Chainman.
James R. Caywood	Chainman.
Anastacio P. Chavez	Chainman.
Robert D. Stevens	Flagman.
Bonie B. Perea	Flagman.
George R. Connolly	Cornerman.
William M. Nauta	Cornerman.

99
55

BOOK 4360

CERTIFICATE OF SURVEYOR

We, Dupree R. Averill and G. Marvin Litz, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th. day of March, 1946 received from the regional district cadastral engineer for Arizona, with assignment instructions dated January 7, 1947, we have resurveyed, part of the East Boundary and surveyed the subdivisions of T.1 S., R.19 W.,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

June 19, 1947
Glendale, California.

Dupree R. Averill
Dupree R. Averill
G. Marvin Litz
G. Marvin Litz

CERTIFICATE OF APPROVAL

Bureau of Land Management
OFFICE OF SUPERVISOR OF SURVEYS,
Washington, D.C. MAR 4 1949

part of
The foregoing field notes of the resurvey of the East Boundary, and survey of the subdivision of T.1 S., R.19 W.,

executed by Dupree R. Averill and G. Marvin Litz under special instructions dated March 15, 1946, and assignment instructions dated January 7, 1947, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

Earl G. Harrington
Chief, Division of Engineering

~~CERTIFICATE OF TRANSCRIPT~~

~~I certify that the foregoing transcript of the field notes of the above-described surveys in Arizona, is a true copy of the original field notes on file in the public survey office.~~

~~Supervisor of Surveys.~~