

134.

4376

①

Original

4-679  
(April 1933)

BOOK 4876

4376

# FIELD NOTES

of the survey of the

Subdivisional Lines of

Township 10 South, Range 7 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Ty White and Claude F. Warner, Cadastral Engineers

Under special instructions dated October 15, 1947, which provided  
for the surveys included under Group No. 255, bearing the approval of the  
Director, Bureau of Land Management under date of November 3, 1947  
and assignment instructions dated November 29, 1948

Survey commenced January 21, 1949

Survey completed March 1, 1949

4376

135

(11)

BOOK 4376

## INDEX DIAGRAM.

36	<i>Township</i>	10 South	,	<i>Range</i>	7 West	36
37	37	28	21	15	8	
6	35 5	26 4	20 3	13 2	7 1	
35	35	26	20	13	6	
7	34 8	25 9	19 10	12 11	5 12	
33	33	25	19	12	5	
18	32 17	24 16	18 15	11 14	4 13	
32	32	24	18	11	4	
19	31 20	24 21	17 22	10 23	3 24	
31	30	23	17	10	3	
30	29 29	23 28	16 27	9 26	2 25	
29	29	22	16	9	1	
31	28 32	21 33	15 34	8 35	1 36	

6-161

Lines surveyed by Ty White are shown in red, thus ———

Lines surveyed by Claude F. Warner are shown in blue, thus ———

T. 10 S., R. 7 W.

4876

The survey was made with Buff and Buff light mountain transits Nos. 16724 and 23816. For description of the instruments, determination of meridian and other preliminary data, see the field notes of T. 10 S., R. 5 W., surveyed under this group.

The geographic position of the SE. cor. of T. 10 S., R. 7 W., as determined by data furnished with the special instructions, is latitude  $32^{\circ} 30' 13''$  N., longitude  $112^{\circ} 55' 57''$  W.

January 23, 1949, on the meridian established on Dec. 11, 1948, at half hour intervals from 8:00 a.m. to 4:00 p.m., we make orientation tests of Buff and Buff transits Nos. 16724 and 23816, including a latitude test by noon observation. The tests give a maximum error in orientation of less than  $1' 30''$ .

The observed magnetic declination is  $15^{\circ}$  E.

Chains

## Subdivision of T. 10 S., R. 7 W.

Beginning the subdivisional survey at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

N.  $0^{\circ} 01'$  W., bet. secs. 35 and 36.

Over rolling land, through scattering timber.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 35 and 36.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
 S35 | S36  
 1949

dig pits  $18 \times 18 \times 12$  ins., N. and S. of post, 3 ft. dist.

46.60 Old road, bears NE. and SW.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T10S R7W  
 S26 | S25  
 S35 | S36  
 1949

dig pits  $18 \times 18 \times 12$  ins., in each sec. 3 ft. dist.

Land, rolling.

Soil, sandy.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

S.  $89^{\circ} 52'$  W., bet. secs. 25 and 36.

Subdivision of T. 10 S., R. 7 W.

Chains.

Over nearly level land, through scattering timber.

40.03 Point for the 1/4 sec. cor. of secs. 25 and 36.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S25  
S36  
1949

from which

A mesquite, 3 ins. diam., bears N. 17 1/4° W., 63 lks. dist., mkd. BT.

A mesquite, 3 ins. diam., bears S. 69° W., 275 lks. dist., mkd. 1/4 S 36 BT.

43.36 Old road, bears N. and S.

80.06 The cor. of secs. 25, 26, 35 and 36.

Land, nearly level.

Soil, sandy.

Timber, paloverde and mesquite; undergrowth, greasewood and cacti.

N. 0° 01' W., bet. secs. 25 and 26.

Over nearly level land, through scattering timber.

40.00 Point for the 1/4 sec. cor. of secs. 25 and 26.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4  
S26 | S25  
1949

from which

A mesquite, 3 ins. diam., bears S. 71 1/4° W., 95 lks. dist., mkd. BT.

Dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.

52.50 Ungraded road, from Highway 85 to Tony's Well, bears E. and W.

80.00 Point for the cor. of secs. 23, 24, 25 and 26.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T10S R7W  
S23 | S24  
S26 | S25  
1949

dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Land, nearly level.

Soil, sandy.

Timber, paloverde and mesquite; undergrowth, greasewood.

## Subdivision of T. 10 S., R. 7 W.

## Chains.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

S. 89° 53' W., bet. secs. 24 and 25.

Over nearly level land, through scattering timber.

40.05 Point for the  $\frac{1}{4}$  sec. cor. of secs. 24 and 25.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S24} \\ \hline \text{S25} \\ 1949 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

42.60 Ditch, 20 lks. wide, course N. 60° W.

44.35 Unimproved road, bears N. 30° W. and S. 30° E.

80.10 The cor. of secs. 23, 24, 25 and 26.

Land, nearly level.

Soil, sandy.

Timber, paloverde and mesquite; undergrowth, greasewood.

N. 0° 01' W., bet. secs. 23 and 24.

Over nearly level land, through scattering timber.

17.50 Wash, 10 lks. wide, 2 ft. deep, course S. 60° W.

29.60 Old road, bears NE. and SW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 23 and 24.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ \text{S23} \mid \text{S24} \\ 1949 \end{array}$$

dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.

Continue over nearly level land.

80.00 Point for the cor. of secs. 13, 14, 23 and 24.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T10S R7W} \\ \text{S14} \mid \text{S13} \\ \hline \text{S23} \mid \text{S24} \\ 1949 \end{array}$$

dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Land, nearly level.

Soil, sandy.

Timber, paloverde and mesquite; undergrowth, greasewood.

Subdivision of T. 10 S., R. 7 W.

Chains.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

S. 89° 56' W., bet. secs. 13 and 24.

Over nearly level land, through scattering timber.

40.07 Point for the 1/4 sec. cor. of secs. 13 and 24.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S13  
S24  
1949

dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over nearly level land.

80.14 The cor. of secs. 13, 14, 23 and 24.

Land, nearly level.

Soil, sandy loam.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 01' W., bet. secs. 13 and 14.

Over nearly level land, through scattering timber.

39.20 Wash, 20 lks. wide, 3 ft. deep, course W.

40.00 Point for the 1/4 sec. cor. of secs. 13 and 14.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4  
S14 | S13  
1949

from which

A mesquite, 14 ins. diam., bears S. 59 1/2° E., 180 lks. dist., mkd. 1/4 S13 BT.

A mesquite, 12 ins. diam., bears S. 85 1/2° W., 169 lks. dist., mkd. 1/4 S14 BT.

49.20 Channel of Rio Cornez Wash, 50 lks. wide, course W.

53.80 Channel of same wash, 30 lks. wide, course W.

58.60 Channel of same wash, 40 lks. wide, 4 ft. deep, course W.

66.00 Unimproved road, bears E. and W.

80.00 Point for the cor. of secs. 11, 12, 13 and 14.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of T. 10 S., R. 7 W.

K 4876

Chains.

T10S R7W

S11 | S12

S14 | S13

1949

dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Land, nearly level.

Soil, sandy loam.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

S. 89° 59' W., bet. secs. 12 and 13:

Over mountainous land, through scattering timber.

1.30 Foot of ascent, bears N. and S.; asc. 366 ft. over E. slope.

14.30 Main ridge of Crater Mountains, bears N. and S.; desc. 185 ft. over W. slope.

25.00 Ravine, course S. 40° W.; asc. 40 ft. over SE: slope.

27.20 Spur, slopes S. 40° W.; desc. 203 ft. over NW. slope.

40.14 Point for the 1/4 sec. cor. of secs. 12 and 13.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S12

S13

1949

raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.

Over nearly level land

68.20 Wash, 30 lks. wide, 2 ft. deep, course S. 30° W.

80.28 The cor. of secs. 11, 12, 13 and 14.

Land, E 1/2 mi. mountainous, W 1/2 nearly level.

Soil, E 1/2 mi. rocky, W 1/2 sandy.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N..0° 01' W., bet. secs. 11 and 12.

Over nearly level land, through scattering timber.

40.00 Point for the 1/4 sec. cor. of secs. 11 and 12.

Set an iron post, .3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S11 | S12

1949

## Subdivision of T. 10 S., R. 7 W.

Chains.	raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
44.00	Leave nearly level, enter mountainous land, bears E. and W.; asc. 290 ft. over S. slope.
63.00	Top of ascent, bears NNW. and SSE.; along broken top.
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set an iron post, 3 ft. long, 2 ins. diam., over a cross (X) chiselled in solid rock, and in a mound of stone to top, with brass cap mkd.
	T10S R7W S 2   S 1 S11   S12 1949
	Land, S½ mi. nearly level, N½ mountainous. Soil, S½ mi. gravelly loam; N½ rocky. Timber, paloverde and ironwood; undergrowth, greasewood.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record. S. 89° 53' W., bet. secs. 1 and 12. Over rolling land, through scattering timber.
20.30	Leave rolling, enter mountainous land, bears N. and S.; asc. 262 ft. over E. slope.
37.45	Top of ascent, bears N. and S.; over rolling top.
40.12	Point for the ¼ sec. cor. of secs. 1 and 12. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	¼ S1 S12 1949
40.25	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Top of main ridge of Crater Mountains, bears N. and S.; desc. 183 ft. over W. slope.
57.50	Wash, 15 lks. wide, 2 ft. deep, course S.; asc. 91 ft. over NE. slope.
65.40	Rocky spur, slopes S. 80° E.; continue asc. over broken E. slope, across head of a ravine, course SE..
71.30	Spur, slopes S.; over rolling top of spur.
80.24	The cor. of secs. 1, 2, 11 and 12. Land, mountainous and rolling. Soil, rocky and gravelly loam. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.



## Subdivision of T. 10 S., R. 7 W.

Chains.

N. 0° 01' W., bet. secs. 1 and 2.

Over mountainous land, through scattering timber. Along and near top of spur, sloping S.

23.00 Across head of ravine, course SE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S2 | S1 \\ | \\ 1949 \end{array}$$

Bury a malpais stone 8x8x6 ins., mkd. X, alongside the iron post.

42.60 Leave top of spur, slopes S., from NW.; desc. 74 ft. over NE. slope.

44.20 Wash, in bottom of canyon, course S. 40° E.; asc. 64 ft. over rocky SW. slope.

66.00 Main ridge of Crater Mountains, bears N. 70° W. and S. 60° E. Over top.

72.00 Desc. 205 ft. over N. slope.

80.00 Point for the  $\frac{1}{16}$  sec. cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{16} \\ | \\ S2 | S1 \\ | \\ 80 \\ | \\ 1949 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Cor. is at foot of descent, bears E. and W.; thence over rolling land.

87.34 Intersect the 2nd. Standard Parallel South.

Point for the closing cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T9S R7W \\ \hline S35 \\ S2 | S1 \\ T10S R7W \\ C C \\ 1949 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

From point of intersection the standard  $\frac{1}{4}$  sec. cor., S. bdy. of sec. 35, T. 9 S., R. 7 W., bears East 33 lks. dist., and is monumented with a malpais stone 10x8x8 ins. above ground, firmly set, marked and witnessed as described in the official record.

Subdivision of T. 10 S., R. 7 W.

Chains.

From the same point the standard cor. of secs. 34 and 35, T. 9 S., R. 7 W., bears West, 39.67 chs. dist., and is monumented with a malpais stone 10x10x8 ins. above ground, firmly set, marked and witnessed as described in the official record.

Land, mountainous.  
Soil, rocky and gravelly.  
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

Point for the N.  $\frac{1}{4}$  sec. cor. of sec. 1, at midpoint.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S1  
1949

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor., the standard cor. of secs. 35 and 36, T. 9 S., R. 7 W., bears East, 09 lks. dist., and is monumented with a malpais stone 8x8x6 ins. above ground, firmly set, marked and witnessed as described in the official record.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

N. 0° 01' W., bet. secs. 34 and 35.

Over nearly level land, through scattering timber.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 34 and 35.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S34 | S35  
1949

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

45.70 Dim road, bears N. 70° E., and S. 70° W.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T10S R7W  
S27 | S26  
S34 | S35  
1949

dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Subdivision of T. 10 S., R. 7 W.

Chains.

Land, nearly level.  
Soil, sandy loam.  
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.


From the cor. of secs. 25, 26, 35 and 36.

S. 89° 50' W., bet. secs. 26 and 35.

Over nearly level land, through scattering timber.

40.01 Point for the 1/4 sec. cor. of secs. 26 and 35.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over nearly level land.

80.02 The cor. of secs. 26, 27, 34 and 35.


Land, nearly level.  
Soil, sandy loam.  
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 01' W., bet. secs. 26 and 27.

Over nearly level land, through scattering timber.

40.00 Point for the 1/4 sec. cor. of secs. 26 and 27.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.




dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

55.50 Ungraded road, from Highway No. 85 to Tony's Well, bears E. and W.

80.00 Point for the cor. of secs. 22, 23, 26 and 27.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



dig pits, 18x18x12 ins., in each section, 3 ft. dist.

Land, nearly level.  
Soil, sandy.  
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

Subdivision of T. 10 S., R. 7 W.

Chains.	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89° 49' W., bet. secs. 23 and 26.</p> <p>Over nearly level land, through scattering timber.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 26.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math> S23  <math>\frac{1}{4}</math> S26                  1949             </p> <p>dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.</p> <p>Continue over nearly level land.</p> <p>80.00 The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, nearly level. Soil, sandy. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.</p> <hr/> <p>N. 0° 01' W., bet. secs. 22 and 23.</p> <p>Over nearly level land, through scattering timber.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math>                  S22   S23                  1949             </p> <p>dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.</p> <p>76.90 Wash, 15 lks. wide, course NW.</p> <p>80.00 Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">                 T10S R7W                  S15   S14                  S22   S23                  1949             </p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, nearly level. Soil, sandy. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.</p> <hr/>
---------	--

146

BOOK 4078

Subdivision of T. 10 S., R. 7 W.

Chains.

From the cor. of secs. 13, 14, 23 and 24.

S. 89° 48' W., bet. secs. 14 and 23.

Over nearly level land, through scattering timber.

39.99 Point for the 1/4 sec. cor. of secs. 14 and 23.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S14  
S23  
1939

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

Continue over nearly level land.

79.98 The cor. of secs. 14, 15, 22, and 23.

Land, nearly level.  
Soil, sandy.  
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 01' W., bet. secs. 14 and 15.

Over nearly level land, through scattering timber.

40.00 Point for the 1/4 sec. cor. of secs. 14 and 15.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S15 | S14  
1949

dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.

50.60 Enter wash area, bears E. and W.

52.00 Channel of Rio Cornez Wash, course S. 70° W.

53.50 Channel of Rio Cornez Wash, 20 fks. wide, course S. 70° W.

57.00 Main channel of same wash, 150 fks. wide, course W.

59.00 Leave wash area, bears E. and W.; continue over nearly level land.

80.00 Point for the cor. of secs. 10, 11, 14 and 15.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T10S R7W  
S10 | S11  
S15 | S14  
1949

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level.  
Soil, sandy, and gravelly in wash area.  
Timber, paloverde and mesquite; undergrowth, greasewood.

Subdivision of T. 10 S., R. 7 W.

Chains.

From the cor. of secs. 11, 12, 13 and 14.

S. 89° 47' W., bet. secs. 11 and 14.

Over nearly level land, through scattering timber.

34.62 Unimproved road, bears N. 80° W., S. 80° E.

40.01 Point for the 1/4 sec. cor. of secs. 11 and 14.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S11  
S14  
1949

raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.

60.70 Wash, 10 lks. wide, course SW.

80.02 The cor. of secs. 10, 11, 14 and 15.

Land, nearly level.

Soil, sandy.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 01' W., bet. secs. 10 and 11.

Over rolling land, through scattering timber.

13.40 Unimproved road, bears NW and SE.

40.00 Point for the 1/4 sec. cor. of secs. 10 and 11.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S10 | S11  
1949

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

46.20 Wash, 15 lks. wide, course W.

56.90 Wash, 10 lks. wide, course S. 80° W.

68.70 Leave nearly level, enter mountainous land, bears N. 80° W. and E. Asc. 225 ft. over SW. slope.

77.00 Spur, slopes SE.; desc. gradually, along E. slope.

80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set an iron post, 3 ft. long, 2 ins. diam., 3 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.

T10S R7W  
S 3 | S 2  
S10 | S11  
1949

Bury a malpais stone 6x4x2 ins., mkd. X, alongside the iron post.

## Subdivision of T. 10 S., R. 7 W.

## Chains.

Land, nearly level and mountainous.  
Soil, sandy, gravelly and rocky.  
Timber, paloverde and ironwood; undergrowth, greasewood  
and cacti.

From the cor. of secs. 1, 2, 11 and 12.

S. 89° 47' W., bet. secs. 2 and 11.

Over mountainous land, through scattering timber; desc.  
140 ft. over W. slope.

13.00 Foot of descent, enter valley, bears N. and S.

20.40 Wash, 20 lks. wide, course S.

26.00 Leave valley, bears N. and S.; asc. 185 ft. over E. slope.

30.00 Spur, slopes S.; desc. 180 ft. over W. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 2 and 11.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the  
ground, to bedrock and in a mound of stone to top, with  
brass cap mkd.

$\frac{1}{4}$  S2  
S11  
1949

Bury a gneiss stone, 6x4x2 ins., mkd. X, alongside the  
iron post.

40.90 Wash, 15 lks. wide, course S.; asc. 140 ft. over E. slope.

44.00 Spur, slopes SE. Thence over a series of jagged pinnacles,  
facing S.

68.00 Desc. 190 ft. over W. slope.

75.00 Wash, 20 lks. wide, course S.; asc. 86 ft. over E. slope.

80.00 The cor. of secs. 2, 3, 10 and 11.

Land, mountainous.  
Soil, rocky, and sandy and gravelly in the valley.  
Timber, paloverde; undergrowth, greasewood in the valley,  
and cacti.

N. 0° 01' W., bet. secs. 2 and 3.

Over mountainous land, through scattering timber. Desc.  
85 ft. over NE. slope.

6.45 Ravine, 10 lks. wide, course SE.; asc. 300 ft. over SW.  
slope.

18.30 Spur, slopes SW.; along E. slope.

24.30 Spur, slopes E.; desc. 237 ft. over cliffs on N. slope.


30.50 Wash, 20 lks. wide, in bottom of canyon, course E. Asc.  
278 ft. over cliffs, facing SE.

38.00 Point for the witness  $\frac{1}{4}$  sec. cor. of secs. 2 and 3.

Subdivision of T. 10 S., R. 7 W.

Chains.

Set an iron post, 3 ft. long, 1 in. diam., over a cross (X) chiselled on bedrock, and in a mound of stone to top, with brass cap mkd.



Cor. stands on rocky point, 10 lks. S. of a cliff facing N.

40.00 True point for  $\frac{1}{4}$  sec. cor. of secs. 2 and 3 falls on insecure ground, on the face of a precipitous cliff.


Desc. 400 ft. over cliffs on N. slope.

47.00 Wash, 20 lks. wide, course E., in bottom of canyon. Asc. 410 ft. over small cliffs on S. slope.

60.00 Top of ascent, bears E. and W.; thence across top of mesa.

80.00 Point for the  $\frac{1}{16}$  sec. cor. of secs. 2 and 3.

Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.




Bury a malpais stone, 6x4x2 ins., mkd. X, alongside the iron post.

80.70 Head of small ravine, 5 lks. wide, course E.

87.71 Intersect the 2nd. Standard Parallel South.

Point for the closing cor. of secs. 2 and 3.

Set an iron post, 3 ft. long, .2 ins. diam., 6 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.



Bury a malpais stone 8x6x4 ins., mkd. X, alongside the iron post.

From point of intersection the standard  $\frac{1}{4}$  sec. cor., S. bdy. of sec. 34, T. 9 S., R. 7 W., bears East 49 lks. dist., and is monumented with a malpais stone 12x10x9 ins., above ground, firmly set, marked and witnessed as described in the official record.

From the same point the standard cor. of secs. 33 and 34, T. 9 S., R. 7 W., bears West 39.51 chs. dist., and is monumented with a malpais stone 14x12x10 ins. above a mound of stone, marked and witnessed as described in the official record.



Subdivision of T. 10 S., R. 7 W.

Chains.

Land, mountainous.  
Soil, rocky.  
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

Point for the N. 1/4 sec. cor. of sec. 2, at midpoint.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S2  
1949

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. From this cor., the standard cor. of secs. 34 and 35, T. 9 S., R. 7 W., bears East, 41 lks. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

N. 0° 02' W., bet. secs. 33 and 34.

Over nearly level land, through scattering timber.

40.00 Point for the 1/4 sec. cor. of secs. 33 and 34.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4  
S33 | S34  
1947

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

71.40 Dim road, bears E. and W.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T10S R7W  
S28 | S27  
S33 | S34  
1949

from which

A mesquite, 6 ins. diam., bears N. 55 3/4° E., 20 lks. dist., mkd. BT.

A mesquite, 4 ins. diam., bears S. 47° E., 156 lks. dist., mkd. BT.

A mesquite, 6 ins. diam., bears S. 22 3/4° W., 74 lks. dist., mkd. BT.

A mesquite, 8 ins. diam., bears N. 74 1/2° W., 131 lks. dist., mkd. BT.

Land, rolling and nearly level.  
Soil, sandy.  
Timber, paloverde and mesquite; undergrowth, greasewood.

Subdivision of T. 10 S., R. 7 W.

Chains.


From the cor. of secs. 26, 27, 34 and 35.

S. 89° 51' W., bet. secs. 27 and 34.

Over nearly level land, through scattering timber.

39.95 Point for the 1/4 sec. cor. of secs. 27 and 34.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



from which

A mesquite, 6 ins. diam., bears N. 30° E., 185 lks. dist., mkd. 1/4 S27 BT.

A mesquite, 6 ins. diam., bears S. 0°30' E., 333 lks. dist., mkd. 1/4 S34 BT.

45.20 Dim road, bears N. 10° E. and S. 10° W.

79.90 The cor. of secs. 27, 28, 33 and 34.

Land, nearly level.

Soil, sandy.


Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.

N. 0° 02' W., bet. secs. 27 and 28.

Over nearly level land, through scattering timber.

40.00 Point for the 1/4 sec. cor. of secs. 27 and 28.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.




dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.

65.60 Ungraded road, from Highway 85 to Tony's Well, bears E. and W.

80.00 Point for the cor. of secs. 21, 22, 27 and 28.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Land, nearly level.

Soil, sandy.

Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.

ECCO

Subdivision of T. 10 S., R. 7 W.

Chains.


From the cor. of secs. 22; 23, 26 and 27.

S. 89° 53' W., bet. secs. 22 and 27.

Over nearly level land; through scattering timber.

39.95 Point for the 1/4 sec. cor. of secs. 22 and 27.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over nearly level land.

79.90 The cor. of secs. 21, 22, 27 and 28.

Land, nearly level.

Soil, sandy.


Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 02' W., bet. secs. 21 and 22.

Over nearly level land, through scattering timber.

40.00 Point for the 1/4 sec. cor. of secs. 21 and 22.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.




dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

Continue over nearly level land.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

Land, nearly level.

Soil, sandy.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

Subdivision of T. 10 S., R. 7 W.

Chains.	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89° 53' W., bet. secs. 15 and 22.</p> <p>7.40 Wash, 10 lks. wide, 3 ft. deep, course N. 60° W.</p> <p>39.95 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 15 and 22.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \frac{1}{4} \text{ S15} \\ \text{S22} \\ 1949 \end{array}</math> </div> <p>Dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.</p> <p>Over nearly level land.</p> <p>79.90 The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, nearly level. Soil, sandy. Timber, scattering paloverde and ironwood; undergrowth, greasewood and cacti.</p> <hr/> <p>N. 0° 02' W., bet. secs. 15 and 16.</p> <p>Over nearly level land, through scattering timber.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 15 and 16.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \frac{1}{4} \\ \text{S16}   \text{S15} \\ 1949 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S. 43° E., 220 lks. dist., mkd. <math>\frac{1}{4}</math> S15 BT.</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N. 55° W., 118 lks. dist., mkd. <math>\frac{1}{4}</math> S16 BT.</p> <p>55.00 Channel of Rio Cornez Wash, 70 lks. wide, 3 ft. deep, course W.</p> <p>59.00 Channel of same wash, 50 lks. wide, 4 ft. deep, course W.</p> <p>80.00 Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \text{T10S R7W} \\ \text{S 9}   \text{S10} \\ \text{S16}   \text{S15} \\ 1949 \end{array}</math> </div> <p>dig pits, 18x18x12 ins., in each sec., 3 ft. dist.</p> <p>Land, nearly level. Soil, sandy and gravelly. Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.</p>
---------	---

## Subdivision of T. 10 S., R. 7 W.

## Chains.

From the cor. of secs. 10; 11, 14 and 15.

S. 89° 53' W., bet. secs. 10 and 15.

Over nearly level land, through scattering timber.

39.96 Point for the  $\frac{1}{4}$  sec. cor. of secs. 10 and 15.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \text{ S10} \\ \text{S15} \\ 1949 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

40.42 Wash, 10 lks. wide, 2 ft. deep, course N. 60° W.

79.92 The cor. of secs. 9, 10, 15 and 16.

Land, nearly level.

Soil, sandy.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 02' W., bet secs. 9 and 10.

Over nearly level land, through scattering timber.

11.20 Wash, 15 lks. wide, 3 ft. deep, course N. 60° W.

40.00 True point for the  $\frac{1}{4}$  sec. cor. of secs. 9 and 10 falls on insecure ground in the center of a wash, 20 lks. wide, course S. 60° W.

40.50 Point for the witness  $\frac{1}{4}$  sec. cor. of secs. 9 and 10.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \uparrow \\ \text{S9} | \text{S10} \\ \text{W C} \\ 1949 \end{array}$$

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

77.70 Ungraded road, bears E. and W.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T10S R7W} \\ \text{S4} | \text{S3} \\ \hline \text{S9} | \text{S10} \\ 1949 \end{array}$$

raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, nearly level.

Soil, sandy.

Timber, paloverde and ironwood; undergrowth, greasewood.

Subdivision of T. 10 S., R. 7 W.

Chains.	
	From the cor. of secs. 2, 3, 10 and 11. S. 89° 53' W., bet. secs. 3 and 10. Over mountainous land, through scattering timber; asc. 79 ft. over E. slope.
2.00	Spur, slopes S.; desc. 330 ft. over SW. slope.
24.90	Foot of descent, leave mountainous, enter nearly level land, bears N. 60° W. and S. 60° E.
39.94	Point for the 1/4 sec. cor. of secs. 3 and 10. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <math>\frac{S3}{S10}</math>                      1949                 </div>
40.68	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Ungraded road, bears N. 10° W.; S. 10° E.
64.68	Same road, bears N. 30° E.; S. 30° W.
79.88	The cor. of secs. 3, 4, 9 and 10.  Land, W. 55 chs. nearly level, remainder, mts. Soil, W. 55 chs. gravelly loam, remainder rocky. Timber, paloverde, ironwood and mesquite; undergrowth, greasewood.
	N. 0° 02' W., bet. secs. 3 and 4. Over nearly level land, through scattering timber.
5.00	Wash, 15 lks. wide, course S. 40° W.
20.00	Leave nearly level, enter mountainous land, bears NE. and SW.; asc. 303 ft. along E. slope of a spur.
39.50	Cross a ravine, near head, course S. 40° E.; asc. 11 ft. over SW. slope.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4. Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.  <div style="text-align: center;"> <math>\frac{S4}{S3}</math>                      1949                 </div>
	Asc. 219 ft. over SW. slope.
54.50	Spur, slopes SE., from N. 10° W.; thence along top of spur.
79.60	Leave spur, slopes S., from NE.; desc. 10 ft.
80.00	Point for the 1/16 sec. cor. of secs. 3 and 4. Set an iron post, 3 ft. long, 1 in. diam., on bedrock, with X marked on bedrock and in a mound of stone to top, with brass cap mkd.

## Subdivision of T. 10 S., R. 7 W.

Chains.

1/16

S4 | S3

80.

1949

Desc. gradually.

80.50 Drain, course W.; asc. 65 ft. over S. slope.

87.75 Intersect the 2nd. Standard Parallel South.

Point for the closing cor. of secs. 3 and 4.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.

T9S R7W

S33

S4 | S3

T10S R7W

C C

1949

Cor. stands on top of a spur, slopes S. 10° E.

From point of intersection the standard  $\frac{1}{4}$  sec. cor., S. bdy. of sec. 33, T. 9 S., R. 7 W., bears East 39 lks. dist., and is monumented with a malpais stone 24x16x8 ins., firmly set in a mound of stone, marked and witnessed as described in the official record.

From the same point the standard cor. of secs. 32 and 33, T. 9 S., R. 7 W., bears West 39.61 chs. dist., and is monumented with a malpais stone 24x12x8 ins., firmly set in a mound of stone, marked and witnessed as described in the official record.

Land, mountainous, and rolling.

Soil, gravelly and rocky.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

Point for the N.  $\frac{1}{4}$  sec. cor. of sec. 3, at midpoint.

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.

 $\frac{1}{4}$  S3

1949

Bury a malpais stone 6x5x3 ins., mkd. X, alongside the iron post.

From this cor. the standard cor. of secs. 33 and 34, T. 9 S., R. 7 W., bears East; 44 lks. dist.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

N. 0° 02' W., bet. secs. 32 and 33.

Subdivision of T. 10 S., R. 7 W.

Chains.

Over rolling land, through scattering timber.

24.70 Wash, 20 lks. wide, course NW.

40.00 Point for the 1/4 sec. cor. of secs. 32 and 33.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S32 | S33

1949

raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.  
Continue over rolling land.

80.00 Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T10S R7W

S29 | S28

S32 | S33

1949

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  
Land, rolling.  
Soil, sandy loam, and gravelly.  
Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 27, 28, 33 and 34.

S. 89° 45' W., bet. secs. 28 and 33.

Over nearly level land, through scattering timber.

39.98 Point for the 1/4 sec. cor. of secs. 28 and 33.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S28

1/4 | S33

1949

raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.  
Continue over nearly level land.

79.96 The cor. of secs. 28, 29, 32 and 33.

Land, nearly level.  
Soil, sandy loam.  
Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.



## Subdivision of T. 10 S., R. 7 W.

## Chains.

N. 0° 02' W., bet. secs. 28 and 29.

Over nearly level land, through scattering timber.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 29.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \dagger \\ | \\ \text{S29} | \text{S28} \\ | \\ 1949 \end{array}$$

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

78.50 Unimproved road, from Highway 85 to Tony's Well, bears E. and W.

80.00 Point for the cor. of secs. 20, 21, 28 and 29.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T10S R7W} \\ \text{S20} | \text{S21} \\ \hline \text{S29} | \text{S28} \\ 1949 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level.

Soil, sandy.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 21, 22, 27 and 28.

S. 89° 43' W., bet. secs. 21 and 28.

Over nearly level land, through scattering timber.

39.99 Point for the  $\frac{1}{4}$  sec. cor. of secs. 21 and 28.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \dagger \text{ S21} \\ | \\ \text{S28} \\ | \\ 1949 \end{array}$$

dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over nearly level land.

79.98 The cor. of secs. 20, 21, 28 and 29.

Land, nearly level.

Soil, sandy.

Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.

Subdivision of T. 10 S., R. 7 W.

Chains.	<p>N. 0° 02' W., bet. secs. 20 and 21...</p> <p>Over nearly level land, through scattering timber.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 20 and 21.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \frac{1}{4} \\   \\ \text{S20}   \text{S21} \\   \\ 1949 \end{array}</math> </div> <p>dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.</p> <p>Continue over nearly level land.</p> <p>80.00 Point for the cor. of secs. 16, 17, 20 and 21.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \text{T10S R7W} \\ \hline \text{S17}   \text{S16} \\ \hline \text{S20}   \text{S21} \\ 1949 \end{array}</math> </div> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, nearly level. Soil, sandy. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89° 41' W., bet. secs. 16 and 21.</p> <p>39.99 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 16 and 21.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\frac{1}{4} \frac{\text{S16}}{\text{S21}} \\ 1949</math> </div> <p>raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.</p> <p>Over rolling land, through scattering timber.</p> <p>79.98 The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sandy. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.</p> <hr/> <p>N. 0° 02' W., bet. secs. 16 and 17.</p> <p>Over rolling land, through scattering timber.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 16 and 17.</p>
---------	--

## Subdivision of T. 10 S., R. 7 W.

## Chains.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \dagger \\ \text{S17} \mid \text{S16} \end{array}$$

1949

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

70.40 Enter wash area, bears E. and W.

74.30 Channel of Rio Cornez Wash, 100 lks. wide, course W.

76.80 Channel of same wash; 40 lks. wide, course N. 80° W.

78.90 Leave wash area, bears E. and W.

80.00 Point for the cor. of secs. 8, 9, 16 and 17.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \dagger \\ \text{T10S R7W} \\ \text{S 8} \mid \text{S 9} \\ \text{S17} \mid \text{S16} \end{array}$$

1949

raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly.

Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 9, 10, 15 and 16.

S. 89° 46' W., bet. secs. 9 and 16.

Over rolling land, through scattering timber.

40.00 Point for the ¼ sec. cor. of secs. 9 and 16.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \dagger \\ \frac{1}{4} \text{ S9} \\ \text{S16} \end{array}$$

1949

raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Continue over rolling land.

80.00 The cor. of secs. 8, 9, 16 and 17.

Land, rolling.

Soil, sandy.

Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 02' W., bet. secs. 8 and 9.

Over rolling land, through scattering timber.

Subdivision of T. 10 S., R. 7 W.

Chains. 36.50	Wash, 25 lks, wide, course W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S8}   \text{S9} \\ \hline 1949 \end{array}$
	raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor. Continue over rolling land.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{T10S R7W} \\ \text{S5}   \text{S4} \\ \hline \text{S8}   \text{S9} \\ \hline 1949 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, rolling, Soil, sandy. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.
<hr/>	
	From the cor. of secs. 3, 4, 9 and 10.
	S. 89° 46' W., bet. secs. 4 and 9.
4.80	Wash, 20 lks, wide, course S, 40° W. Unimproved road, bears NW. and SE.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \text{ S4} \\ \hline \text{S9} \\ \hline 1949 \end{array}$
	raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor. Over rolling land, through scattering timber.
80.02	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling. Soil, sandy and gravelly. Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.
<hr/>	
	N. 0° 02' W., bet. secs. 4 and 5.
	Over rolling land, through scattering timber.
29.95	Wash, 5 lks. wide, course SW.

## Subdivision of T. 10 S., R. 7 W.

Chains.	
37.00	Unimproved road, bears NW. and E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S5   S4 1949
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
52.80	Foot of ascent, bears E. and W.; asc. 77 ft. over S. slope.
55.80	Detached spur, slopes E. about 6.00 chs., and W. about 6.00 chs.; desc. 71 ft. over N. slope.
58.20	Foot of descent, bears E. and W.; thence over rolling land.
80.00	Point for the $\frac{1}{16}$ sec. cor. of secs. 4 and 5. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{16}$ S5   S4 80 1949
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
87.98	Intersect the 2nd. Standard Parallel South. Point for the closing cor. of secs. 4 and 5. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	T9S R7W S32 ----- S5   S4 T10S R7W C C 1949
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From point of intersection the standard $\frac{1}{4}$ sec. cor., S. bdy. of sec. 32, T. 9 S., R. 7 W., bears East 41 lks. dist.; and is monumented with a malpais stone 8x6x6 ins. above ground, firmly set, marked and witnessed as described in the official record.
	From the same point the standard cor. of secs. 31 and 32, T. 9 S., R. 7 W., bears West 39.59 chs. dist., and is monumented with a malpais stone 10x10x6 ins. above ground, firmly set, marked and witnessed as described in the official record.
	Land, rolling, with detached spur in N. $\frac{1}{2}$ mi. Soil, sandy, gravelly and rocky. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

Subdivision of T. 10 S., R. 7 W.

Chains.

Point for the N.  $\frac{1}{4}$  sec. cor. of sec. 4, at midpoint..

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S4  
1949

Bury a malpais stone, 6x4x2 ins., mkd. X, alongside the iron post.

From this cor. the standard cor. of secs. 32 and 33, T. 9 S., R. 7 W., bears East, 40 $\frac{1}{2}$  lks. dist.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

N. 0° 03' W., bet. secs. 31 and 32.

Over nearly level land, through scattering timber.

15.00 Leave nearly level, enter mountainous land, bears NW. and SE.; asc. 158 ft. over SW. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 32.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
S31 | S32  
1949

raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor. Asc. 40 ft. over SW. slope.

46.00 Spur, slopes N. 40° W.; descend 192 ft. along W. slope of main spur.

64.40 Bottom of descent, bears N. 30° E. and S. 30° W.; over nearly level land.

72.00 Barbed wire fence, bears N. 31 $\frac{1}{4}$ ° W., S. 31 $\frac{1}{4}$ ° E., for about 7 chs., to the point of a spur.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T10S R7W  
S30 | S29  
S31 | S32  
1949

raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of cor.

Land, mountainous for 50 chs., 30 chs. nearly level. Soil, rocky in mountainous land, gravelly loam in level. Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.

## Subdivision of T. 10 S., R. 7 W.

Chains.	From the cor. of secs. 28, 29, 32 and 33. S. 89° 44' W., bet. secs. 29 and 32. Over nearly level land, through scattering timber.
39.94	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\frac{1}{4} \frac{S29}{S32}$ 1949
51.90	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Wash, course NW.
79.88	The cor. of secs. 29, 30, 31 and 32. Land, nearly level. Soil, gravelly loam. Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.
7.00	S. 89° 50' W., bet. secs. 30 and 31. Over nearly level land, through scattering timber. Barbed wire fence, bears N. 31 $\frac{1}{2}$ ° W., S. 31 $\frac{1}{2}$ ° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\frac{1}{4} \frac{S30}{S31}$
56.00	raise a mound of stone; 3 ft. base; 2 ft. high, N. of cor. Old road, bears NE. and SW.
77.85	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record. Land, nearly level. Soil, sandy and gravelly loam. Timber, scattering paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.
34.00	From the cor. of secs. 29, 30, 31 and 32. N. 0° 03' W., bet. secs. 29 and 30. Over nearly level land, through scattering timber. Wash, course N. 40° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of T. 10 S., R. 7 W.

Chains.

#  
S30 | S29  
1949

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

Continue over nearly level land.

80.00 Point for the cor. of secs. 19, 20, 29 and 30.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T10S R7W  
S19 | S20  
S30 | S29  
1949

from which

A mesquite, 12 ins. diam., bears N. 45½° E., 160 lks. dist., mkd. T10S R7W S20 BT.

A mesquite, 8 ins. diam., bears S. 12¼° E., 98 lks. dist., mkd. T10S R7W S29 BT.

A mesquite, 6 ins. diam., bears S. 70° W., 115 lks. dist., mkd. BT.

A mesquite, 14 ins. diam., bears N. 9° W., 375 lks. dist., mkd. T10S R7W S19 BT.

Land, nearly level.

Soil, sandy.

Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.

From the cor. of secs. 20, 21, 28 and 29.

S. 89° 46' W., bet. secs. 20 and 29.

Over nearly level land, through scattering timber.

7.32 Unimproved road, from Highway 85 to Tony's Well, bears N. 70° W., S. 70° E.

39.96 Point for the ¼ sec. cor. of secs. 20 and 29.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

¼ S20  
S29  
1949

dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over nearly level land.

79.92 The cor. of secs. 19, 20, 29 and 30.

Land, nearly level.

Soil, sandy loam.

Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.



## Subdivision of T. 10 S., R. 7 W.

Chains.	<p>S. 89° 47' W., bet. secs. 19 and 30.</p> <p>Over nearly level land, through scattering timber.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 30.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} \frac{1}{4} \frac{S19}{S30} \\ 1949 \end{array}$ <p>dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.</p> <p>64.50 Shallow wash, course N. 40° W.</p> <p>72.50 Barbed wire fence, bears N. 31<math>\frac{3}{4}</math>° W., S. 31<math>\frac{3}{4}</math>° E.</p> <p>77.80 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.</p> <p>Land, nearly level. Soil, sandy. Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 03' W., bet. secs. 19 and 20.</p> <p>Over nearly level land, through scattering timber.</p> <p>10.50 Unimproved road, from Highway 85 to Tony's Well, bears E. and W.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} \frac{1}{4} \\ S19   S20 \\ 1949 \end{array}$ <p>dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.</p> <p>Continue over nearly level land.</p> <p>80.00 Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} T10S R7W \\ S18   S17 \\ \hline S19   S20 \end{array}$ <p>dig pits, 18x18x12 ins., in each sec., 3 ft. dist.</p> <p>Land, nearly level. Soil, sandy. Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.</p>

Subdivision of T. 10 S., R. 7 W.

Chains.

From the cor. of secs. 16, 17, 20 and 21.

S. 89° 47' W., bet. secs. 17 and 20.

Over nearly level land, through scattering timber.

39.94 Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 20.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   $\frac{S17}{S20}$

1949

dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over nearly level land.

79.88 The cor. of secs. 17, 18, 19 and 20.

Land, nearly level.

Soil, sandy.

Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.

S. 89° 43' W., bet. secs. 18 and 19.

Over nearly level land, through scattering timber.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 18 and 19.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   $\frac{S18}{S19}$

1949

dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

Continue over nearly level land.

77.78 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

Land, nearly level.

Soil, sandy.

Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 17, 18, 19 and 20.

N. 0° 03' W., bet. secs. 17 and 18.

Over nearly level land, through scattering timber.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 18.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

## Subdivision of T. 10 S., R. 7 W.

Chains.

$$\begin{array}{c} \dagger \\ \text{S18} | \text{S17} \\ \hline 1949 \end{array}$$

dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

Continue over nearly level land.

80.00 Point for the cor. of secs. 7, 8, 17 and 18.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T10S R7W} \\ \text{S 7} | \text{S 8} \\ \hline \text{S18} | \text{S17} \\ 1949 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level.

Soil, sandy.

Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 8, 9, 16 and 17.

S. 89° 44' W., bet. secs. 8 and 17.

Over rolling land, through scattering timber.

19.86 Channel of Rio Cornez Wash, 30 lks. wide, course N. 70° W.

37.53 Point for the witness  $\dagger$  sec. cor. of secs. 8 and 17.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{WC } \dagger \frac{\text{S8}}{\text{S17}} \\ 1949 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

37.86 Enter a channel of Rio Cornez Wash, 60 lks. wide, course W., from N. 80° E. Along channel of wash.

39.93 True point for the  $\dagger$  sec. cor. of secs. 8 and 17 falls in channel of wash, 60 lks. wide, course W.

45.85 Leave channel of wash, course N. 80° W., from E. Over rolling land.

79.86 The cor. of secs. 7, 8, 17 and 18.

Land, rolling and wash bottom.

Soil, sandy and gravelly.

Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.

S. 89° 43' W., bet. secs. 7 and 18.

Over nearly level land, through scattering timber.

Subdivision of T. 10 S., R. 7 W.

Chains.  
40.00

Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 18.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S7  
 $\frac{1}{4}$  S18  
1949

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  
Continue over nearly level land.

77.70

The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of Tp.; which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

Land, nearly level.  
Soil, sandy.  
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

From the cor. of secs. 7, 8, 17 and 18.  
N. 0° 03' W., bet. secs. 7 and 8.

10.70

Center of a channel of Rio Cornez Wash, 150 lks. wide, course N. 80° W.

21.70

Channel of same wash, 80 lks. wide, course N. 80° W.

29.40

Wash, 20 lks. wide, course W.

40.00

Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 8.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
S7 | S8  
1949

dig pits 18x18x12 ins., N. and S. of post, 3 ft. dist.  
Over nearly level land, through scattering timber.

80.00

Point for the cor. of secs. 5, 6, 7 and 8.  
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T10S R7W  
S6 | S5  
S7 | S8  
1949

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  
Land, nearly level.  
Soil, sandy, and gravelly along wash.  
Timber, paloverde, mesquite and ironwood, along wash; undergrowth, greasewood and cacti.

BOOK 1372


Subdivision of T. 10 S., R. 7 W.

Chains.	
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89° 41' W., bet. secs. 5 and 8.</p> <p>Over rolling land, through scattering timber.</p>
9.95	Wash, 10 lks. wide, course S. 30° W.
19.05	Wash, 20 lks. wide, course S. 10° W.
39.92	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> $\frac{1}{4} \frac{S5}{S8}$ <p style="text-align: center;">1949</p> <p>raise a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, N. of cor.</p> <p>Continue over rolling land.</p>
79.84	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling.</p> <p>Soil, sandy and gravelly.</p> <p>Timber, paloverde, mesquite and ironwood; undergrowth, greasewood and cacti.</p>
40.00	<p>S. 89° 42' W., bet. secs. 6 and 7.</p> <p>Over nearly level land, through very scattering timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 7.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> $\frac{1}{4} \frac{S6}{S7}$ <p style="text-align: center;">1949</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Continue over nearly level land.</p>
77.67	<p>The cor. of secs. 1, 6, 7 and 12. on the W. bdy. of Tp., which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.</p> <p>Land, nearly level.</p> <p>Soil; sandy and gravelly.</p> <p>Timber, paloverde and ironwood; undergrowth, greasewood and cacti.</p>
40.00	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0° 03' W., bet. secs. 5 and 6.</p> <p>Over rolling land, through scattering timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 6.</p>

Subdivision of T. 10 S., R. 7 W.

Chains.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

51.40 Wash, 10 lks. wide, course S. 80° W.


58.00 Foot of ascent, bears E. and W.; asc. 164 ft. over S. slope.

64.30 Spur, slopes E.; descend 83 ft. over N. slope.

72.70 Wash, 10 lks. wide, course SE.; thence over rolling land.

80.00 Point for the 1/16 sec. cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.




raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

88.30 Intersect the 2nd. Standard Parallel South.

Point for the closing cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From point of intersection the standard ¼ sec. cor., S. bdy. of sec. 31, T. 9 S., R. 7 W., bears East 29 lks. dist., and is monumented with a malpais stone 14x10x6 ins. above ground, firmly set, marked and witnessed as described in the official record.

From the same point the standard cor. of Ts. 9 S., Rs. 7 and 8 W., bears West 39.71 chs. dist., and is monumented with an iron post, 3 ins. diam., firmly set 14 ins. in the ground and the remaining length in a mound of stone, marked and witnessed as described in the official record.

Land, rolling and mountainous.  
Soil, sandy, gravelly and rocky.  
Timber, paloverde and ironwood; undergrowth, greasewood and cacti.

## Subdivision of T. 10 S., R. 7 W.

Point for N.  $\frac{1}{4}$  sec. cor. of sec. 5, at midpoint.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S5

1949

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor., the standard cor. of secs. 31 and 32, T. 9 S., R. 7 W., bears East, 35 $\frac{1}{2}$  lks. dist.

Point for the N.  $\frac{1}{4}$  sec. cor. of sec. 6, 40 chs. W. of the closing cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S6

1949

Bury a malpais stone, 6x4x2 ins., mkd. X, alongside the iron post.

From this cor., the standard cor. of Ts. 9 S., Rs. 7 and 8 W., bears East, 29 $\frac{1}{2}$  lks. dist.

#### Test of Solar Orientation.

March 6: At camp near the center of sec. 30, T. 10 S., R. 6 W., at 8h 30m a.m., app.t., make the proper setting on the arcs and orient the instruments with the solars; the line of sight agrees with the meridian established by Polaris observation.

At 4h 30m p.m., app.t., make the proper settings on the arcs and repeat the test of the solars, the line of sight agrees with the meridian established by Polaris observation.

March 6, 1949.

#### General Description.

The greater portion of the land in T. 10 S., R. 7 W. is nearly level and rolling, with the Crater range of mountains, which are rough and rocky, in the NE. portion and along the North Boundary of the township, and the extreme N. end of the Growler Mountains in secs. 31 and 32. The soil is sandy and gravelly loam in the rolling land, and rocky in the mountainous areas. The elevation ranges from 1150 to 1600 ft. above sea level.

The principal drainage is the Rio Cornez Wash, a long, wide watercourse, with several channels, which has a westerly course through secs. 13, 14, 15, 16, 17, 7 and 8. There are several tributary washes draining into it, mostly from the Crater Mountains, to the NE. There is no living water in the township, the washes being dry except

## General Description, continued.

during periods of heavy rains, at which times they carry considerable water for a short time.

The timber is a scattering growth of paloverde, iron-wood and mesquite, being more prevalent along the washes. It is of no commercial value except for firewood. The undergrowth is greasewood and cacti.

There is an unimproved but well travelled road, bearing westerly to Tony's Well, and easterly to State Highway No. 85, and thence to Ajo, through the south central portion of the township. Another road, used principally by wood haulers, skirts the base of the Crater Mountains, in the NE. portion.

A limited number of horses and cattle graze the area. There is no settlement. No mineral indications were discovered during the progress of the survey.



174  
(3)

4-680  
(August 1947)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Robert D. Stevens	Survey Aid, SP 3.
John G. Coverdale	Survey Aid, SP 3.
Daniel D. Frank	Survey Aid, SP 2.
Conner D. Wilkerson	Survey Aid, SP 2.
Carl P. Lyons	Survey Aid, SP 2.
Raymond C. Lee, Jr.	Survey Aid, SP 2.
Herman E. Wood	Survey Aid, SP 2.
Charles S. Amosch	Survey Aid, SP 2.
Frank A. Mercurio	Survey Aid, SP 2.
George Lyons Jr.	Survey Aid, SP 2.
Lavor Q. Boggs	Survey Aid, SP 2.

175  
40

CERTIFICATE OF CADASTRAL ENGINEER

We, Ty White and Claude F. Warner, HEREBY CERTIFY upon honor that, in  
pursuance of special instructions bearing date of the 15th. day of October, 1947  
we have surveyed the Subdivisional Lines of Township 10 South, Range 7 West

of the G. and S. R. Meridian, in the State of Arizona, which are  
represented in the foregoing field notes as having been executed by us and under our direction; and that  
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the  
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing  
field notes.

Phoenix, Arizona, July 30, 1949.  
Phoenix, Arizona, July 30, 1949.

Ty White  
Cadastral Engineer  
Claude F. Warner  
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., DEC 4 1950, 19    

The foregoing field notes of the survey of the Subdivisional Lines of Township  
10 South, Range 7 West, of the G. and S. R. Meridian, in the  
State of Arizona.

executed by Ty White and Claude F. Warner, Cadastral Engineers  
having been critically examined and found correct, are hereby approved.

James Clement  
Chief, Branch of Engineering and Construction,  
Assistant Chief, Division  
of Cadastral Engineering

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in~~  
~~is a true copy of the original field notes.~~

~~Chief, Branch of Engineering and Construction,  
Chief, Division of Engineering~~