

Original

4-679  
(April 1933)

**RECEIVED**  
U. S. LAND OFFICE  
Phoenix, Arizona

JAN 28 1952

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

**FIELD NOTES**

OF THE

Dependent Resurvey of a portion of the section boundaries and the

Partial subdivision of

Sections 5, 6, 7, 18, 21, 23, 25, 26 and 27, T. 3 N., R. 5 E.

Section 11, T. 3 N., R. 3 E.

and

Section 12, T. 3 N., R. 4 E.

Of the Gila and Salt River Meridian,

In the State of Arizona

**EXECUTED BY**

Ty White and Claude F. Warner, Cadastral Engineers

Under special instructions dated Dec. 9, 1948 & July 29, 1949, which provided  
for the surveys included under Group No. 259, bearing the approval of the  
Director, Bureau of Land Management  
Commissioner of the General Land Office under date of Jan. 11, 1949 and Aug. 9, 1949  
and assignment instructions dated October 10, 1949

Survey commenced January 3, 1950

Survey completed February 16, 1950

61  
1A

BOOK 1986

# INDEX DIAGRAM.

Township 3 North, Range 5 East

	3	42				
R.4 E.	3 6	41 5	4	3	2	1
	2 10	41				
69						
70-73	8 7	10 8	9	10	11	12
	9					
	16 18	17 17	16	15	14	13
	16		21			
	19	20	20 21	22	25 23	26 24
				48	24	33
	30	29	28	50 27	47 26	56 25 31
				49		31
	31	32	33	34	35	36

6-151

Subdivision of Sections

Sec. No.	Pages
6	4-8
7	10-16
18	18-20
21	22-23
23	26-30
25	34-40
5	42-47
27	51-55
26	56-62

T.3 N., R.3 E.  
Sec. 11

64
66 11 63
65

Subdivision Pgs. 67-69

The boundaries of section 11, T. 3 N., R. 3 E., were surveyed by J. H. Martineau, Deputy Surveyor, in 1894. The boundaries of section 12, T. 3 N., R. 4 E., were surveyed by R. C. Powers, Deputy Surveyor, in 1892 and resurveyed by Sidney E. Blout, Surveyor, in 1914. The south boundary of sections 25, 26, and 27, T. 3 N., R. 5 E., which is a portion of the north boundary of the Salt River Indian Reservation, was surveyed by L. D. Chillson, Deputy Surveyor, in 1888 and resurveyed by Robert A. Farmer, Topographer, in 1911. The remaining boundaries of the sections involved in this survey were surveyed by Sidney E. Blout, Surveyor, in 1914.

The survey herein described was initiated for the purpose of providing a basis for the location of small tracts on the ground for sale or lease. A resurvey of a portion of the boundaries of the involved sections was made in addition to the limited subdivision of sections.

Before restoring the corners, the lines of the original survey were retraced, and diligent search made for any evidence of the original corners, bearing trees and other calls of the record. When duly identified, the corner positions were remonumented and where needed reference monuments were established. Lost corners were reestablished and remonumented at proportionate positions based upon the original record. The retracement data are thoroughly verified and only the true line field notes are given herein.

The survey was executed with light mountain solar transits made by Buff and Buff, serial numbers 16724 and 23816, and W. and L. E. Gurley, serial number 371537, all constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instruments were in good condition and were placed in satisfactory adjustment prior to the beginning of the survey.

The direction of all lines were determined by hour angle observations on Polaris for azimuth and carried forward by transit line. The measurements were made with Lufkin steel tapes, 5 chains in length, graduated to tenths of a link for the first 10 links, every link for the balance of the first 100 links and the remainder at intervals of 10 links. The tapes were tested by comparison with a standard 1 chain steel tape and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents only are entered in this field note record.

December 29, 1949, at the cor. of Tps. 3 and 4 N., Rs. 4 and 5 E., in latitude  $33^{\circ} 38' 14''$  N., and longitude  $111^{\circ} 54' 13''$  W. as determined from data furnished with the special instructions, elevation approximately 1,500 ft., I make an hour angle observation on Polaris E. of the meridian for azimuth and latitude; making four observations, two each with the telescope in direct and reversed positions, observing simultaneously the vertical angle to Polaris and the horizontal angle from a well defined point on the sky line approximately 15 miles northeasterly, W. to Polaris. My watch reads correct Mountain Standard Time as checked by radio time signals.

Mean watch time of observation, p.m.	5h 28m 54s
Watch fast of l.m.t.	0h 27m 36s
Mean horizontal deflection angle	$28^{\circ} 20' 52''$
Azimuth of Polaris	$0^{\circ} 39' 00''$
True bearing to reference point	N. $28^{\circ} 59' 52''$ E.
Mean observed vertical angle	$34^{\circ} 27' 49''$
Reduced latitude	$33^{\circ} 38' 28''$ N.

January 17, 1950, at the cor. of secs. 21, 22, 27 and 28, T. 3 N., R. 5 E., in latitude  $33^{\circ} 34' 45''$  N. and longitude  $111^{\circ} 51' 07''$  W. as determined from data furnished

Chains

with the special instructions, I make an hour angle observation on Polaris E. of the meridian for azimuth; making four observations, two each with the telescope in direct and reversed positions, reading the deflection angle from the east side of a tower at Loyd Wright's ranch, approximately two miles northerly, E. to Polaris. My watch reads correct Mountain Standard Time as checked by radio time signals.

Mean watch time of observation, p.m.	5h 42m 08s
Watch fast of l.m.t.	0h 27m 24s
Mean horizontal deflection angle	11° 15' 23"
Azimuth of Polaris	0° 14' 00"
True bearing to reference point	N. 11° 01' 23" W.

February 8, 1950, at the cor. of secs. 11, 12, 13 and 14, T. 3 N., R. 3 E., in latitude 33° 36' 29" N. and longitude 112° 00' 42" W. as determined from data furnished with the special instructions, I make an hour angle observation on Polaris W. of the meridian for azimuth, making four observations, two each with the telescope in direct and reversed positions, reading the deflection angle from the east edge of a power line pole, approximately 1 mile northerly, E. to Polaris. My watch reads correct Mountain Standard Time as checked by radio time signals.

Mean watch time of observation, p.m.	6h 12m 21s
Watch fast of l.m.t.	0h 28m 00s
Mean horizontal deflection angle.	0° 35' 00"
Azimuth of Polaris	0° 21' 15"
True bearing to reference monument	N. 0° 56' 15" W.

The observed magnetic declination is 14<sup>3</sup>/<sub>4</sub>° E.

Dependent Resurvey of a Portion of the Boundaries of Section 6, T. 3 N., R. 5 E.

Reestablishment of the Survey Executed by R. C. Powers, Deputy Surveyor, in 1892 and the Resurvey and Survey Executed by Sidney E. Blout, Surveyor, in 1914.

From the  $\frac{1}{4}$  sec. cor. of secs. 6 and 7, T. 3 N., R. 5 E., which is monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.

WEST, bet. secs. 6 and 7.

Over nearly level land, through scattering timber and undergrowth.

20.000 Point for the W 1/16 sec. cor. of secs. 6 and 7.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S 6  
W 1/16  
S 7  
1950

37.860 The closing cor. of secs. 6 and 7, which is monumented with an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

Land, nearly level.  
Soil, gravelly loam. Timber, Palo verde, ironwood and mesquite.

Dependent Resurvey of a Portion of the Boundaries of Section 6,  
T. 3 N., R. 5 E.

BOOK 4385

Chains	N. $0^{\circ} 33'$ E., along the W. bdy. of sec. 6. Over nearly level land, through scattering timber and undergrowth.
20.000	Point for the S $1/16$ sec. cor. of sec. 6. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{c}   \\ \text{S } 1/16 \text{ S } 6 \\ 1950 \end{array}$
37.140	The $\frac{1}{4}$ sec. cor. of sec. 1, T. 3 N., R. 4 E. which is monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record. Thence N. $1^{\circ} 18'$ E., continuing the same measurement.
40.000	Point for the $\frac{1}{4}$ sec. cor. of sec. 6. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{c}   \\ \frac{1}{4} \text{ S } 6 \\ 1950 \end{array}$ raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.
52.940	Rio Verde Canal, bears S. $80^{\circ}$ W. and N. $80^{\circ}$ E.
60.000	Point for the N $1/16$ sec. cor. of sec. 6. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{c}   \\ \text{N } 1/16 \text{ S } 6 \\ 1950 \end{array}$ Raise a mound of stone, $1\frac{1}{2}$ ft. base, 1 ft. high, E. of cor.
70.000	Point for the N N $1/64$ sec. cor. of sec. 6. Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. N-N $1/64$ S 6 on E. face.
77.140	The cor. of Tps. 3 and 4 N., Rs. 4 and 5 E., which is monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record. Land, nearly level. Soil, gravelly, loam. Timber, palo verde, ironwood and mesquite; undergrowth, greasewood.
	EAST, bet. secs. 6 and 31. Over nearly level land, through scattering timber and undergrowth.
6.240	Point for the W W $1/64$ sec. cor. of secs. 6 and 31. Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. W-W $1/64$ S 6-31.
16.240	Point for the W $1/16$ sec. cor. of secs. 6 and 31.

Dependent Resurvey of a Portion of the Boundaries of Section 6,  
T. 3 N., R. 5 E.

Chains	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{S } 31 \\ \text{W } 1/16 \text{ ---} \\ \text{S } 6 \\ 1950 \end{array}$
26.240	Point for the EW $1/64$ sec. cor. of secs. 6 and 31. Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. W $1/64$ S 6-31.
36.240	The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, which is monumented with an iron post, 1 in. diam.; firmly set; mkd. and witnessed as described in the official record. Land, nearly level. Soil, sandy loam, gravelly. Timber, palo verde, ironwood and mesquite; undergrowth, greasewood.
Subdivision of Section 6, T. 3 N., R. 5 E.	
20.009	From the $\frac{1}{4}$ sec. cor. of secs. 6 and 7. N. $0^{\circ} 17'$ W., on the N. and S. center line of sec. 6. Point for the C S $1/16$ sec. cor. of sec. 6. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{C} \\ \text{S } 1/16 \text{ ---} \\ \text{S } 6 \\ \text{C} \\ 1950 \end{array}$
30.013	Point for the CNS $1/64$ sec. cor. of sec. 6. Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S $1/64$ S 6.
40.018	Point for the C $\frac{1}{4}$ sec. cor. of sec. 6, at the intersection with the E. and W. center line. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{C } \frac{1}{4} \text{ S } 6 \\ 1950 \end{array}$
	From this cor. The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, bears S. $89^{\circ} 58'$ E., 40.018 chs. dist.
48.870	Rio Verde Canal, course N. $80^{\circ}$ W.
50.012	Point for the CSN $1/64$ sec. cor. of sec. 6, at proportionate distance Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N $1/64$ S 6.
60.005	Point for the C N $1/16$ sec. cor. of sec. 6, at proportionate distance

## Subdivision of Section 6, T. 3 N., R. 5 E.

Chains Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

C  
N 1/16 S 6  
1950

69.999 Point for the C N N 1/64 sec. cor. of sec. 6, at proportionate dist.  
Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N-N 1/64 S 6.

77.172 The ¼ sec. cor. of secs. 6 and 31.

From the C ¼ sec. cor. of sec. 6.

N. 89° 58' W., on the E. and W. center line of sec. 6.

10.000 Point for the CEW 1/64 sec. cor. of sec. 6.

Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W 1/64 S 6.

20.000 Point for the C W 1/16 sec. cor. of sec. 6.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

W 1/16  
C ————— C  
S 6  
1950

37.266 The ¼ sec. cor. of sec. 6, on the W. bdy. of the Tp.

Subdivision of the SW ¼.

From the W 1/16 sec. cor. of secs. 6 and 7.

N. 0° 15' W., on the N. and S. center line of the SW ¼ of sec. 6.

20.000 Point for the SW 1/16 sec. cor. of sec. 6, at the intersection with the E. and W. center line.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S W 1/16 S 6  
1950

30.009 Point for the C N SW 1/64 sec. cor. of sec. 6.

Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N-SW 1/64 S 6.

40.018 The C W 1/16 sec. cor. of sec. 6.

From the C S 1/16 sec. cor. of sec. 6.

WEST, on the E. and W. center line of the SW ¼ of sec. 6.

10.012 Point for the C E SW 1/64 sec. cor. of sec. 6.

Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E-SW 1/64 S 6.

<p>Chains 20.024 37.586</p>	<p>The SW 1/16 sec. cor. of sec. 6.</p> <p>The S 1/16 sec. cor. of sec. 6 on the W. bdy. of the Tp.</p>
	<p>Subdivision of NE 1/4 SW 1/4.</p>
<p>10.005 20.011</p>	<p>From the C E SW 1/64 sec. cor. of sec. 6.</p> <p>N. 0° 16' W., on the N. and S. center line of the NE 1/4 SW 1/4 of sec. 6.</p> <p>Point for the NE SW 1/64 sec. cor. of sec. 6, at the intersection with the E. and W. center line. Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. NE-SW 1/64 S 6.</p> <p>The CEW 1/64 sec. cor. of sec. 6.</p>
<p>10.007 20.013</p>	<p>From the CNS 1/64 sec. cor. of sec. 6.</p> <p>N. 89° 59' W., on the E. and W. center line of the NE 1/4 SW 1/4 of sec. 6.</p> <p>The NE SW 1/64 sec. cor. of sec. 6.</p> <p>The C N SW 1/64 sec. cor. of sec. 6.</p>
	<p>Subdivision of the NW 1/4.</p>
<p>10.000 10.500 20.000 30.002 37.163</p>	<p>From the C W 1/16 sec. cor. of sec. 6.</p> <p>N. 0° 16' W., on the N. and S. center line of the NW 1/4 of sec. 6.</p> <p>Point for the C S NW 1/64 sec. cor. of sec. 6. Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S-NW 1/64 S 6.</p> <p>Rio Verde Canal, course N. 80° W.</p> <p>Point for the NW 1/16 sec. cor. of sec. 6, at the intersection with the E. and W. center line. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 6 1950</p> <p>Point for the C N NW 1/64 sec. cor. of sec. 6. Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N-NW 1/64 S 6.</p> <p>The W 1/16 sec. cor. of secs. 6 and 31.</p>
<p>10.005</p>	<p>From the C N 1/16 sec. cor. of sec. 6.</p> <p>N. 89° 57' W., on the E. and W. center line of the NW 1/4 of sec. 6.</p> <p>Point for the C E NW 1/64 sec. cor. of sec. 6. Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E-NW 1/64 S 6.</p>



## Subdivision of Section 6, T. 3 N., R. 5 E.

Chains	
20.007	The NW 1/16 sec. cor. of sec. 6.
30.007	Point for the C W NW 1/64 sec. cor. of sec. 6. Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in hte ground, mkd. C-W-NW 1/64 S 6.
36.714	The N 1/16 sec. cor. of sec. 6 on the W. bdy. of the Tp.
Subdivision of the SE ¼ NW ¼.	
	From the CEW 1/64 sec. cor. of sec. 6. N. 0° 16' W., on the N. and S. center line of the SE ¼ NW ¼ of sec. 6.
9.50	Rio Verde Canal, course N. 80° W. and S. 80° E.
10.000	Point for the SE NW 1/64 sec. cor. of sec. 6, at the intersection with the E. and W. center line. Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SE-NW 1/64 S 6.
20.002	The C E NW 1/64 sec. cor. of sec. 6.
	From the CSN 1/64 sec. cor. of sec. 6. N. 89° 59' W., on the E. and W. center line of the SE ¼ NW ¼ of sec. 6.
9.995	The SE NW 1/64 sec. cor. of sec. 6.
19.987	The C S NW 1/64 sec. cor. of sec. 6.
Subdivision of the NE ¼ NW ¼.	
	From the C E NW 1/64 sec. cor. of sec. 6. N. 0° 16' W., on the N. and S. center line of the NE ¼ NW ¼ of sec. 6.
9.992	Point for the NE NW 1/64 sec. cor. of sec. 6, at the intersection with the E. and W. center line. Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. NE-NW 1/64 S 6.
17.157	The EW 1/64 sec. cor. of secs. 6 and 31.
	From the C N N 1/64 sec. cor. of sec. 6. N. 89° 55' W., on the E. and W. center line of the NE ¼ NW ¼ of sec. 6.
10.008	The NE NW 1/64 sec. cor. of sec. 6.
20.010	The C N NW 1/64 sec. cor. of sec. 6.
Subdivision of the NW ¼ NW ¼.	
	From the C W NW 1/64 sec. cor. of sec. 6. N. 0° 14' W., on the N. and S. center line of the NW ¼ NW ¼ of sec. 6.

Chains 10.002	Point for the NW NW 1/64 sec. cor. of sec. 6, at the intersection with the E. and W. center line.  Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. NW-NW 1/64 S 6.
17.156	The W W 1/64 sec. cor. of secs. 6 and 31.
	From the C N NW 1/64 sec. cor. of sec. 6.  N. 89° 55' W., on the E. and W. center line of the NW 1/4 NW 1/4 of sec. 6.
9.996	The NW NW 1/64 sec. cor. of sec. 6.
16.432	The N N 1/64 sec. cor. of sec. 6 on the W. bdy. of the Tp.
Dependent Resurvey of a Portion of the Boundaries of Section 7, T. 3 N., R. 5 E.	
Reestablishment of the Survey Executed by R. C. Powers, Deputy Surveyor, in 1892 and the Resurvey and Survey Executed by Sidney E. Blout, Surveyor, in 1914.	
	From the cor. of secs. 12 and 13 on the E. bdy. of T. 3 N., R. 4 E., which is monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.  N. 0° 32' E., along the E. bdy. of sec. 12.  Over nearly level land, through scattering timber and undergrowth.
2.960	The closing corner of secs. 7 and 18, T. 3 N., R. 5 E., which is monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.
40.040	The 1/4 sec. cor. of sec. 12, which is monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.
42.970	Point for the 1/4 sec. cor. of sec. 7.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.    1/4 S 7 1950
	deposit a bottle along the E. side of the iron post.
50.051	Point for the SN 1/64 sec. cor. of sec. 12.  Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. N 1/64 S 12 on W. face.
52.973	Point for the SN 1/64 sec. cor. of sec. 7.  Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. N 1/64 S 7 on E. face.
60.061	Point for the N 1/16 sec. cor. of sec. 12.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Boundaries of Section 7,  
T. 3 N., R. 5 E.

4530

## Chains

	<p style="text-align: center;">N 1/16 S 12 1950</p>
62.976	<p>Point for the N 1/16 sec. cor. of sec. 7.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 7 1950</p>
70.071	<p>Point for the N N 1/64 sec. cor. of sec. 12.</p> <p>Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. N N 1/64 S 12 on W. face.</p>
80.081	<p>The Cor. of secs. 1 and 12, which is monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.</p> <p>Land, nearly level. Soil, loam, gravelly. Timber, palo verde; ironwood and mesquite; undergrowth, greasewood.</p>
2,900	<p>N. 0° 33' E., along the E. bdy. of sec. 1.</p> <p>Over nearly level land, through scattering timber and undergrowth.</p> <p>The closing corner of secs. 6 and 7, T. 3 N., R. 5 E.</p>
10.000	<p>From the ¼ sec. cor. of secs. 7 and 18, which is monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.</p> <p>EAST, bet. secs. 7 and 18.</p> <p>Over nearly level land, through scattering timber and undergrowth.</p> <p>Point for the WE 1/64 sec. cor. of secs. 7 and 18.</p> <p>Set a wooden stake, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. E 1/64 S 7-18.</p>
20.000	<p>Point for the E 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 7 E 1/16 S 18 1950</p>
30.000	<p>Point for the E E 1/64 sec. cor. of secs. 7 and 18.</p> <p>Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. E-E 1/64 S 7-18.</p>
38.000	<p>Center of wash, 80 lks. wide, 3 ft. deep, course S. 10° E.</p>
40.000	<p>The cor. of secs. 7, 8, 17 and 18, which is monumented with an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.</p>

Dependent Resurvey of a Portion of the Boundaries of Section 7,  
T. 3 N., R. 5 E.

Chains

N. 0° 03' W., bet. secs. 7 and 8.

Over nearly level land, through scattering timber and undergrowth.

10.000 Point for the S S 1/64 sec. cor. of secs. 7 and 8.

Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. S-S 1/64 S. 7-8.

19.500 Center of wash, 20 lks. wide, 2 ft. deep, course S. 40° E.

20.000 Point for the S 1/16 sec. cor. of secs. 7 and 8.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S 1/16  
S 7 | S 8  
1950

40.000 The 1/4 sec. cor. of secs. 7 and 8, which is monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.

60.000 Point for the N 1/16 sec. cor. of secs. 7 and 8.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

N 1/16  
S 7 | S 8  
1950

80.000 The cor. of secs. 5, 6, 7 and 8, which is monumented with an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

Land, nearly level.  
Soil, loam, gravelly.  
Timber, palo verde, ironwood and mesquite; undergrowth, greasewood.

WEST, bet. secs. 6 and 7.

Over nearly level land, through scattering timber and undergrowth.

20.000 Point for the E 1/16 sec. cor. of secs. 6 and 7.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S 6  
E 1/16  
S 7  
1950

40.000 The 1/4 sec. cor. of secs. 6 and 7.

Subdivision of Section 7, T. 3 N., R. 5 E.

From the 1/4 sec. cor. of secs. 7 and 18.

N. 0° 03' W., on the N. and S. center line of sec. 7.

Subdivision of Section 7, T. 3 N., R. 5 E.

PLAT 4885

Chains

10.000


Point for the C-S-S 1/64 sec. cor. of sec. 7.

Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S-S 1/64 S 7.

20.000

Point for the C S 1/16 sec. cor. of sec. 7.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



30.000


Point for the CNS 1/64 sec. cor. of sec. 7.

Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S 1/64 S 7.

40.000

Point for the C 1/4 sec. cor. of sec. 7, at the intersection with the E. and W. center line.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



1950

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

50.005


Point for the CSN 1/64 sec. cor. of sec. 7.

Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N 1/64 S 7.

60.010

Point for the C N 1/16 sec. cor. of sec. 7.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



80.020

The 1/4 sec. cor. of secs. 6 and 7.

From the 1/4 sec. cor. of secs. 7 and 8.

N. 89° 59' W., on the E. and W. center line of sec. 7.


13.700

Wash, 25 lks. wide, 3 ft. deep, course S.

20.000

Point for the C E 1/16 sec. cor. of sec. 7.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



+	Chains 30.000	Point for the C <sup>✓</sup> W <sup>✓</sup> E 1/64 sec. cor. of sec. 7.  Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E 1/64 S 7.
	40.000	The C ¼ sec. cor. of sec. 7.
	60.000	Point for the C W 1/16 sec. cor. of sec. 7.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  W 1/16 C———C S 7 1950
	70.000	Point for the C W W 1/64 sec. cor. of sec. 7.  Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W-W 1/64 S 7.
	78.270	The ¼ sec. cor. of sec. 7.

Subdivision of the NE. ¼.

		From the C E 1/16 sec. cor. of sec. 7. N. 0° 04' W., on the N. and S. center line of the NE. ¼ of sec. 7.
	9.999	Point for the CSNE 1/64 sec. cor. of sec. 7.  Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S-NE 1/64 S 7.
	19.998	Point for the NE 1/16 sec. cor. of sec. 7.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  NE 1/16 S 7 1950
	40.020	The E 1/16 sec. cor. of secs. 6 and 7.

		From the N 1/16 sec. cor. of secs. 7 and 8. N. 89° 59' W., on the E. and W. center line of the NE. ¼ of sec. 7.
	6.500	Wash, 1 ch. wide, 4 ft. deep, course S. 55° E.
	20.031	The NE 1/16 sec. cor. of sec. 7.
	28.000	Wash, 30 lks. wide, 1 ft. deep, course S. 10° E.
	30.027	Point for the C-W-NE 1/64 sec. cor. of sec. 7.  Set a wooden 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W-NE 1/64 S 7.
	40.023	The C N 1/16 sec. cor. of sec. 7.

Subdivision of the SW. ¼, NE. ¼.

From the C<sup>✓</sup>W<sup>✓</sup>E 1/64 sec. cor. of sec. 7.

## Subdivision of Section 7, T. 3 N., R. 5 E.

4825

Chains	N. 0° 03' W., on the N. and S. center line of the SW. $\frac{1}{4}$ , NE. $\frac{1}{4}$ .
10.002	Point for the SW. NE. $\frac{1}{64}$ sec. cor. of sec. 7, at the intersection with the E. and W. center line.  Set a wooden post, 2 $\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SW-NE $\frac{1}{64}$ S 7.
19.994	The C W NE. $\frac{1}{64}$ sec. cor. of sec. 7.
<hr/>	
	From the C S NE. $\frac{1}{64}$ sec. cor. of sec. 7.
	N. 89° 59' W., on the E. and W. center line of the SW. $\frac{1}{4}$ , NE. $\frac{1}{4}$ .
4.100	Wash, 30 lks. wide, 1 ft. deep, course S. 10° E.
9.998	The SW NE. $\frac{1}{64}$ sec. cor. of sec. 7.
19.994	The C S N. $\frac{1}{64}$ sec. cor. of sec. 7.
<hr/>	
Subdivision of the SE. $\frac{1}{4}$ .	
<hr/>	
	From the E. $\frac{1}{16}$ sec. cor. of secs. 7 and 18.
	N. 0° 02' W., on the N. and S. center line of the SE. $\frac{1}{4}$ of sec. 7.
10.000	Point for the C S SE. $\frac{1}{64}$ sec. cor. of sec. 7.  Set a wooden post, 2 $\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S-SE $\frac{1}{64}$ S 7.
20.002	Point for the SE. $\frac{1}{16}$ sec. cor. of sec. 7, at the intersection with the E. and W. center line.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  SE $\frac{1}{16}$ S 7  1950
27.600	Wash, 30 lks. wide, 2 $\frac{1}{2}$ ft. deep, course S. 20° W.
30.004	Point for the C N SE. $\frac{1}{64}$ sec. cor. of sec. 7.  Set a wooden post, 2 $\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N-SE $\frac{1}{64}$ S 7.
40.006	The C E. $\frac{1}{16}$ sec. cor. of sec. 7.
<hr/>	
	From the S. $\frac{1}{16}$ sec. cor. of secs. 7 and 8.
	West, on the E. and W. center line of the SE. $\frac{1}{4}$ of sec. 7.
10.008	Point for the C E SE. $\frac{1}{64}$ sec. cor. of sec. 7.  Set a wooden post, 2 $\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E-SE $\frac{1}{64}$ S 7.
20.016	The SE. $\frac{1}{16}$ sec. cor. of sec. 7.
21.800	Wash, 60 lks. wide, 3 ft. deep, course S. 10° W.
30.016	Point for the C W SE. $\frac{1}{64}$ sec. cor. of sec. 7.  Set a wooden post, 2 $\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W-SE $\frac{1}{64}$ S 7.

Subdivision of Section 7, T. 3 N., R. 5 E.

BOOK 4385

Chains  
40.016

The C S. 1/16 sec. cor. of sec. 7.

Subdivision of the SE. 1/4, SE. 1/4.

From the E E. 1/64 sec. cor. of secs. 7 and 18.

N. 0° 02' W., on the N. and S. center line of the SE. 1/4, SE. 1/4 of sec. 7.

10.002 Point for the SE SE. 1/64 sec. cor. of sec. 7, at the intersection with the E. and W. center line.

Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SE-SE 1/64 S 7.

20.006 The C E SE. 1/64 sec. cor. of sec. 7.

From the S S. 1/64 sec. cor. of secs. 7 and 8.

West, on the E. and W. center line of the SE. 1/4, SE. 1/4 of sec. 7.

4.200 Wash, 30 lks. wide, 3 ft. deep, course S. 10° W.

9.996 The SE SE. 1/64 sec. cor. of sec. 7.

20.000 The C S SE. 1/64 sec. cor. of sec. 7.

Subdivision of the SW. 1/4, SE. 1/4.

From the WE. 1/64 sec. cor. of secs. 7 and 18.

N. 0° 02' W., on the N. and S. center line of the SW. 1/4, SE. 1/4 of sec. 7.

10.000 Point for the SW SE. 1/64 sec. cor. of sec. 7, at the intersection with the E. and W. center line.

Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SW-SE 1/64 S 7.

20.000 The C W SE. 1/64 sec. cor. of sec. 7.

From the C S SE. 1/64 sec. cor. of sec. 7.

West, on the E. and W. center line of the SW. 1/4, SE. 1/4 of sec. 7.

10.000 The SW SE. 1/64 sec. cor. of sec. 7.

20.004 The C S S. 1/64 sec. cor. of sec. 7.

Subdivision of the NW. 1/4, SE. 1/4.

From the C W SE. 1/64 sec. cor. of sec. 7.

N. 0° 02' W., on the N. and S. center line of the NW. 1/4, SE. 1/4 of sec. 7.

10.000 Point for the NW SE. 1/64 sec. cor. of sec. 7, at the intersection with the E. and W. center line.

Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. NW-SE 1/64 S 7.

20.006 The C W E. 1/64 sec. cor. of sec. 7.



## Subdivision of Section 7, T. 3 N., R. 5 E.

Chains	
	From the C N SE $1/64$ sec. cor. of sec. 7.
	West, on the E. and W. center line of the NW. $\frac{1}{4}$ , SE. $\frac{1}{4}$ of sec. 7.
4.100	Wash, 30 lks. wide, 1 ft. deep, course S. $10^{\circ}$ E.
10.006	The NW SE $1/64$ sec. cor. of sec. 7.
20.006	The CNS $1/64$ sec. cor. of sec. 7.
Subdivision of the NW. $\frac{1}{4}$ .	
	From the C W $1/16$ sec. cor. of sec. 7.
	N. $0^{\circ} 03'$ W., on the N. and S. center line of the NW. $\frac{1}{4}$ of sec. 7.
10.004	Point for the C S NW $1/64$ sec. cor. of sec. 7.
	Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S-NW $1/64$ S 7.
20.008	Point for the NW $1/16$ sec. cor. of sec. 7, at intersection with the E. and W. center line.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	NW $1/16$ S 7
	1950
40.024	The W. $1/16$ sec. cor. of secs. 6 and 7.
	From the C N $1/16$ sec. cor. of sec. 7.
	N. $89^{\circ} 57'$ W., on the E. and W. center line, of the NW. $\frac{1}{4}$ of sec. 7.
20.005	The NW. $1/16$ sec. cor. of sec. 7.
30.005	Point for the C W NW $1/64$ sec. cor. of sec. 7.
	Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W-NW $1/64$ S 7.
38.070	The N. $1/16$ sec. cor. of sec. 7.
Subdivision of the SW. $\frac{1}{4}$ , NW. $\frac{1}{4}$ .	
	From the C W W $1/64$ sec. cor. of sec. 7.
	N. $0^{\circ} 03'$ W., on the N. and S. center line of the SW. $\frac{1}{4}$ , NW. $\frac{1}{4}$ of sec. 7.
10.004	Point for the SW NW $1/64$ sec. cor. of sec. 7, at intersection with the E. and W. center line.
	Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SW-NW $1/64$ S 7.
20.008	The C W NW. $1/64$ sec. cor. of sec. 7.
	From the C S NW. $1/64$ sec. cor. of sec. 7.
	N. $89^{\circ} 57'$ W., on the E. and W. center line of the SW. $\frac{1}{4}$ , NW. $\frac{1}{4}$ of sec. 7.

Chains  
10.000 The SW NW 1/64 sec. cor. of sec. 7.  
18.174 The SE 1/64 sec. cor. of sec. 7.

Dependent Resurvey of a Portion of the Boundaries of  
Section 18, T. 3 N., R. 5 E.

Reestablishment of the Survey Executed by R. C. Powers,  
Deputy Surveyor, in 1892 and the Resurvey and Survey  
Executed by Sidney E. Blout, Surveyor, in 1914.

From the cor. of secs. 13 and 24, on the E. bdy. of T. 3 N., R. 4 E.,  
which is monumented with an iron post, 3 ins. diam., firmly set,  
mkd. and witnessed as described in the official record.

N. 0° 16' E., along the E. bdy. of sec. 13.

Over nearly level land, through scattering timber and undergrowth.

2.960 The closing cor. of secs. 18 and 19, T. 3 N., R. 5 E., which is  
monumented with an iron post, 3 ins. diam., firmly set, mkd. and  
witnessed as described in the official record.

40.000 The 1/4 sec. cor. of sec. 13, which is monumented with an iron post,  
1 in. diam., firmly set, mkd. and witnessed as described in the  
official record.

42.960 Point for the 1/4 sec. cor. of sec. 18.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground,  
with brass cap mkd.

1/4 S 18

1950

The position of this cor. is identical with a local 1/4 sec. cor.,  
which is an iron pipe, 1 in. diam., 14 ins. long, firmly set in  
the ground. Deposit iron pipe alongside the new monument.

80.000 The cor. of secs. 12 and 13, which is monumented with an iron post,  
3 ins. diam., firmly set, mkd. and witnessed as described in the  
official record.

Land, nearly level.  
Soil, sandy loam, gravelly.  
Timber, palo verde, ironwood and mesquite.  
Undergrowth, greasewood, sage and cacti.

N. 0° 32' E., along the E. bdy. of sec. 12.

Over nearly level land, through scattering timber and undergrowth.

2.960 The closing cor. of secs. 7 and 18, which is an iron post, 3 ins. diam.,  
firmly set, mkd. and witnessed as described in the official record.

From the cor. of secs. 17, 18, 19 and 20, which is an iron post, 2  
ins. diam., firmly set and projecting 10 ins. above ground, mkd.  
and witnessed as described in the official record.

West, bet. secs. 18 and 19.

Over nearly level desert land, through scattering timber and  
undergrowth; along an unimproved road.

7.300 Wash, 50 lks. wide, 1 1/2 ft. deep, course S. 20° W.

Dependent Resurvey of a Portion of the Boundaries of  
Section 18, T. 3 N., R. 5 E.

Chains 20.008	Point for the E. 1/16 sec. cor. of secs. 18 and 19.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  $\begin{array}{c} \text{E } 1/16 \quad \frac{\text{S } 18}{\text{S } 19} \\ 1950 \end{array}$ <p>raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.</p>
40.016	The ¼ sec. cor. of secs. 18 and 19, which is monumented by an iron post, 1 in. diam., firmly set and projecting 8 ins. above ground, mkd. and witnessed as described in the official record.  Land, nearly level. Soil, sandy loam. Timber, palo verde, ironwood and mesquite. Undergrowth, greasewood, sage and cacti.
	From the cor. of secs. 17, 18, 19 and 20.  N. 0° 02' W., bet. secs. 17 and 18.  Over nearly level desert land, through scattering timber and undergrowth.
14.700	Wash, 20 lks. wide, course SW.
20.012	Point for the S. 1/16 sec. cor. of secs. 17 and 18.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  $\begin{array}{c} \text{S } 1/16 \\ \text{S } 18 \quad   \quad \text{S } 17 \\ 1950 \end{array}$ <p>raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p>
30.018	Point for the NS. 1/64 sec. cor. of secs. 17 and 18.  Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. S 1/64 on the S.; S 17 on the E. and S 18 on W. faces.
40.025	The ¼ sec. cor. of secs. 17 and 18, which is marked by an iron post, 1 in. diam., firmly set 14 ins. in the ground, and in a small mound of stone.  At the corner point  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  $\begin{array}{c} \frac{1}{4} \\ \text{S } 18 \quad   \quad \text{S } 17 \\ 1950 \end{array}$ <p>raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p>
74.92	Wash, 30 lks. wide, 2 ft. deep, course S. 10° W.
80.050	The cor. of secs. 7, 8, 17 and 18, which is monumented by an iron post, 2 ins. diam., firmly set and projecting 8 ins. above the

Dependent Resurvey of a Portion of the Boundaries of  
Section 18, T. 3 N., R. 5 E.

Chains

ground, mkd. and witnessed as described in the official record.

Land, nearly level.  
Soil, sandy loam, gravelly.  
Timber, palo verde, ironwood and mesquite.  
Undergrowth, greasewood, sage and cacti.


Subdivision of Section 18, T. 3 N., R. 5 E.

From the  $\frac{1}{4}$  sec. cor. of secs. 18 and 19:

N.  $0^{\circ} 02'$  W., on the N. and S. center line of sec. 18.

20.007 Point for the C S  $\frac{1}{16}$  sec. cor. of sec. 18.

Set an iron post, 3 ft. long, 1 in. diam., 29 ins. in the ground, with brass cap mkd.




the position of this cor. is identical with a local S.  $\frac{1}{16}$  sec. cor. which is an iron pipe, 1 in. diam., firmly set 12 ins. in the ground. Deposit iron pipe alongside the new monument.

30.010 Point for the CNS  $\frac{1}{64}$  sec. cor. of sec. 18.

Set a wooden post,  $2\frac{1}{2}$  ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S  $\frac{1}{64}$  S 18.

40.014 Point for the C  $\frac{1}{4}$  sec. cor. of sec. 18, at intersection with the E. and W. center line.

Set an iron post, 3 ft. long, 1 in. diam., 29 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

The position of this cor. is identical with a local C  $\frac{1}{4}$  sec. cor., which is an iron pipe, 1 in. diam., firmly set 28 ins. in the ground. Deposit iron pipe alongside the new monument.

From this cor. the  $\frac{1}{4}$  sec. cor. of secs. 7 and 18, bears N.  $0^{\circ} 02'$  W., 40.018 chs. dist., which is an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.

From the same point, the  $\frac{1}{4}$  sec. cor. on the W. bdy. of sec. 18, bears N.  $89^{\circ} 58'$  W., 38.88 chs. dist.

From the  $\frac{1}{4}$  sec. cor. of secs. 17 and 18.

N.  $89^{\circ} 58'$  W., on the E. and W. center line of sec. 18.

10.000 Point for the C E E  $\frac{1}{64}$  sec. cor. of sec. 18.

Set a wooden post,  $2\frac{1}{2}$  ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E-E  $\frac{1}{64}$  S 18.

20.000 Point for the C E  $\frac{1}{16}$  sec. cor. of sec. 18.

## Subdivision of Section 18, T. 3 N., R. 5 E.

Chains	
30.000	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} \text{E } 1/16 \\ \text{C} \frac{\quad}{\quad} \text{C} \\ \text{S } 18 \end{array}</math> </p> <p style="text-align: center;">1950</p> <p>Point for the C <math>\frac{1}{16}</math> S 18 sec. cor. of sec. 18.</p>
40.000	<p>Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E 1/64 S 18.</p> <p>The C ¼ sec. cor. of sec. 18.</p>
Subdivision of the SE. ¼.	
20.002	<p>From the E. 1/16 sec. cor. of secs. 18 and 19.</p> <p>N. 0° 02' W., on the N. and S. center line of the SE. ¼ of sec. 18.</p> <p>Point for the SE. 1/16 sec. cor. of sec. 18, at intersection with the E. and W. center line.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 29 ins. in the ground, with brass cap mkd.</p>
30.007	<p style="text-align: center;">SE 1/16 S 18</p> <p style="text-align: center;">1950</p> <p>Point for the C N SE 1/64 sec. cor. of sec. 18.</p> <p>Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N-SE 1/64 S 18.</p>
40.012	<p>The C E 1/16 sec. cor. of sec. 18.</p>
10.002	<p>From the S. 1/16 sec. cor. of secs. 17 and 18.</p> <p>West, on the E. and W. center line of the SE. ¼ of sec. 18.</p> <p>Point for the C E SE 1/64 sec. cor. of sec. 18.</p> <p>Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E-SE 1/64 S 18.</p>
20.004	<p>The SE 1/16 sec. cor. of sec. 18.</p>
30.007	<p>Point for the C W SE 1/64 sec. cor. of sec. 18.</p> <p>Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W-SE 1/64 S 18.</p>
40.010	<p>The C S 1/16 sec. cor. of sec. 18.</p>
Subdivision of the NE. ¼, SE. ¼.	
10.004	<p>From the C E SE 1/64 sec. cor. of sec. 18.</p> <p>N. 0° 02' W., on the N. and S. center line of the NE. ¼, SE. ¼ of sec. 18.</p> <p>Point for the NE SE 1/64 sec. cor. of sec. 18, at intersection with the E. and W. center line.</p> <p>Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. NE-SE 1/64 S 18.</p>

Subdivision of Section 18, T. 3 N., R. 5 E.

Chains  
20.008

The C E E 1/64 sec. cor. of sec. 18.

From the NS. 1/64 sec. cor. of secs. 17 and 18.

West, on the E. and W. center line of the NE. 1/4, SE. 1/4 of sec. 18.

10.000

The NE SE 1/64 sec. cor. of sec. 18.

20.000

The C N SE 1/64 sec. cor. of sec. 18.

Subdivision of the NW. 1/4, SE. 1/4.

From the C W SE 1/64 sec. cor. of sec. 18.

N. 0° 02' W., on the N. and S. center line of the NW. 1/4, SE. 1/4 of sec. 18.

10.001

Point for the NW SE 1/64 sec. cor. of sec. 18, at intersection with the E. and W. center line.

Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. NW-SE 1/64 S 18.

20.001

The C E 1/64 sec. cor. of sec. 18.

From the C N SE 1/64 sec. cor. of sec. 18.

N. 89° 59' W., on the E. and W. center line of the NW. 1/4, SE. 1/4 of sec. 18.

10.010

The NW SE 1/64 sec. cor. of sec. 18.

20.020

The CNS 1/64 sec. cor. of sec. 18.

Dependent Resurvey of a Portion of the Boundaries of  
Section 21, T. 3 N., R. 5 E.

Reestablishment of the Survey Executed by  
Sidney E. Blout, Surveyor, in 1914.

From the 1/4 sec. cor. of secs. 20 and 21, which is monumented by an iron post, 1 in. diam., firmly set and projecting 10 ins. above the ground, mkd. and witnessed as described in the official record.

N. 0° 02' W., bet. secs. 20 and 21.

Over nearly level land, through scattering timber and undergrowth.

20.000

Point for the N. 1/16 sec. cor. of secs. 20 and 21.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

N 1/16

S 20 | S 21

1950

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

30.000

Point for the N N 1/64 sec. cor. of secs. 20 and 21.

## Chains

- Set a wooden post,  $2\frac{1}{2}$  ft. long, 2 ins. sq., 16 ins. in the ground, mkd. N-N  $\frac{1}{64}$  on S., S 20 on W. and S 21 on E. faces.
- 40.000 The cor. of secs. 16, 17, 20 and 21, which is monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.
- Land, nearly level desert.  
Soil, sandy loam, gravelly.  
Timber, palo verde, ironwood and mesquite.  
Undergrowth, greasewood, sage and cacti.
- 
- From the cor. of secs. 15, 16, 21 and 22, which is monumented by an iron post, 2 ins. diam., firmly set and projecting 10 ins. above ground, mkd. and witnessed as described in the official record.
- N.  $89^{\circ} 53'$  W., bet. secs. 16 and 21.
- Over nearly level land, through scattering timber and undergrowth.
- 39.850 Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 21, determined longitudinally by proportionate measurement, which is substantiated by falling on the center line of a graded road, bearing N. and S. The 1 in. iron post, with brass cap properly marked was found lying loose on top of the ground, along W. side of the road.
- Reset the orig. iron post, 3 ft. long, 1 in. diam., 42 ins. in the ground, with brass cap mkd.
- $$\frac{1}{4} \frac{S 16}{S 21}$$
- 1914
- from which
- An iron post, 3 ft. long, 1 in. diam., set 29 ins. in the ground, for a reference monument, bears S.  $45^{\circ}$  E., 70.7 lks. dist., with brass cap mkd.  $\frac{1}{4}$  S21 RM 1950 and an arrow pointing to the corner.
- An iron post, 3 ft. long, 1 in. diam., set 29 ins. in the ground, for a reference monument, bears N.  $45^{\circ}$  W., 70.7 lks. dist., with brass cap mkd.  $\frac{1}{4}$  S16 RM 1950 and an arrow pointing to the corner.
- 59.784 Point for the W.  $\frac{1}{16}$  sec. cor. of secs. 16 and 21.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
- $$W \frac{1}{16} \frac{S 16}{S 21}$$
- 1950
- raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.
- 69.751 Point for the W W.  $\frac{1}{64}$  sec. cor. of secs. 16 and 21.
- Set a wooden post,  $2\frac{1}{2}$  ft. long, 2 ins. sq., 16 ins. in the ground, mkd. W-W  $\frac{1}{64}$  on W., S 16 on N. and S 21 on the S. faces.
- 79.718 The cor. of secs. 16, 17, 20 and 21.
- Land, nearly level desert.  
Soil, sandy loam, gravelly.  
Timber, palo verde, ironwood and mesquite.  
Undergrowth, greasewood, sage and cacti.

Subdivision of Section 21, T. 3 N., R. 5 E.


Chains

From the  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, which is monumented by an iron post, 1 in. diam., firmly set and projecting 10 ins. above ground, mkd. and witnessed as described in the official record.

S.  $89^{\circ} 54'$  E., on the N. and W. center line of sec. 21.

19.945 Point for the C W.  $\frac{1}{16}$  sec. cor. of sec. 21.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



1950

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

39.890 Point for the C  $\frac{1}{4}$  sec. cor. of sec. 21, at the intersection of the N. and S. center line.

Set an iron post, 2 ft. <sup>long,</sup> 1 in. diam., embedded in a block of concrete,  $14 \times 12 \times 10$  ins., 36 ins. in the ground, with brass cap mkd.



1950

from which

An iron post, 3 ft. long, 1 in. diam., set 29 ins. in the ground, for a reference monument, bears S.  $45^{\circ}$  E., 70.7 lks. dist., with brass cap mkd. C  $\frac{1}{4}$  S 21 RM 1950 and an arrow pointing to the cor.

An iron post, 3 ft. long, 1 in. diam., set 29 ins. in the ground, for a reference monument, bears N.  $45^{\circ}$  W., 70.7 lks. dist., with brass cap mkd. C  $\frac{1}{4}$  S 21 RM 1950 and an arrow pointing to the cor.

From this cor. the  $\frac{1}{4}$  sec. cor. of secs. 21 and 22, bears S.  $89^{\circ} 54'$  E., 39.89 chs. dist., which is an iron post, 1 in. diam., firmly set and projecting 8 ins. above the ground, mkd. and witnessed as described in the official record.


From the same cor. point, the  $\frac{1}{4}$  sec. cor. of secs. 21 and 28, bears South, 40.00 chs. dist., which is an iron post, 1 in. diam., firmly set 3 ins. below the surface, and on the center line of Shea Blvd., with brass cap mkd. as described in the official record.

From the C.  $\frac{1}{4}$  sec. cor. of sec. 21.

North, on the N. and S. center line of sec. 21.

20.005 Point for the C N.  $\frac{1}{16}$  sec. cor. of sec. 21

Set an iron post, 3 ft. long, 1 in. diam., 42 ins. in the ground, and on the center line of a graded road, bearing N. and S., with brass cap mkd.



1950

from which

An iron post, 3 ft. long, 1 in. diam., set 29 ins. in the ground, for a reference monument, bears EAST, 50 lks. dist., with brass cap mkd. C-N  $\frac{1}{16}$  S 21 RM 1950 and an arrow pointing to the cor.

An iron post, 3 ft. long, 1 in. diam., set 29 ins. in the ground,



## Subdivision of Section 21, T. 3 N., R. 5 E.

Chains	for a reference monument, bears WEST, 50 lks. dist., with brass cap mkd. C-N 1/16 S 21 RM 1950 and an arrow pointing to the cor.
40.010	The $\frac{1}{4}$ sec. cor. of secs. 16 and 21.
Subdivision of the NW. $\frac{1}{4}$ .	
	From the C W 1/16 sec. cor. of sec. 21.
	North, on the N. and S. center line of the NW. $\frac{1}{4}$ of sec. 21.
20.000	Point for NW. 1/16 sec. cor. of sec. 21, at the intersection of the E. and W. center line.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	NW 1/16 S 21 1950
	raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
30.008	Point for the C N NW 1/64 sec. cor. of sec. 21.
	Set a wooden post, 2 $\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N-NW 1/64 S 21.
40.016	The W. 1/16 sec. cor. of secs. 16 and 21.
	From the C N 1/16 sec. cor. of sec. 21.
	N. 89° 54' W., on the E. and W. center line of the NW. $\frac{1}{4}$ of sec. 21.
19.936	The NW. 1/16 sec. cor. of sec. 21.
29.903	Point for the C W NW 1/64 sec. cor. of sec. 21.
	Set a wooden post, 2 $\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W-NW 1/64 S 21.
39.870	The N. 1/16 sec. cor. of secs. 20 and 21.
Subdivision of the NW. $\frac{1}{4}$ , NW. $\frac{1}{4}$ .	
	From the C W NW 1/64 sec. cor. of sec. 21.
	North, on the N. and S. center line of the NW. $\frac{1}{4}$ , NW. $\frac{1}{4}$ of sec. 21.
10.002	Point for the NW. NW. 1/64 sec. cor. of sec. 21 at the intersection of the E. and W. center line.
	Set a wooden post, 2 $\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. NW-NW 1/64 S 21.
20.004	The W W. 1/64 sec. cor. of secs. 16 and 21.
	From the C N NW 1/64 sec. cor. of sec. 21.
	N. 89° 54' W., on the E. and W. center line of the NW. $\frac{1}{4}$ , NW. $\frac{1}{4}$ , of sec. 21.
9.966	The NW NW. 1/64 sec. cor. of sec. 21.
19.933	The N N. 1/64 sec. cor. of secs. 20 and 21.

Dependent Resurvey of a Portion of the Boundaries of Section 23,  
T. 3 N., R. 5 E.

## Chains

Reestablishment of the Survey Executed by  
Sidney E. Blout, Surveyor, in 1914.

From the cor. of secs. 23, 24, 25 and 26, which is monumented by an iron post, 2 ins. in diam., firmly set 4 ins. below the surface of the ground, on the center line of Shea Blvd., bearing E. and W., with brass cap mkd. as described in the official record.

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears N. 45° E., 70.7 lks. dist., with brass cap mkd. T3N R5E S24 RM 1950 and an arrow pointing to the corner.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears S. 45° W., 70.7 lks. dist., with brass cap mkd. T3N R5E S26 RM 1950 and an arrow pointing to the corner.

N. 89° 58' W., bet. secs. 23 and 26.

Over rolling desert land, through scattering timber and undergrowth; along the center line of graded Shea Blvd.

9.984 Point for the E.E. 1/64 sec. cor. of secs. 23 and 26.

Set a washed boulder, 8x8x6 ins., marked with an X on top, 12 ins. below the surface of the ground,

from which

A wooden stake, 1 ft. long, 2 ins. sq., set 8 ins. in the ground, bears N. 0° 01' W., 50 lks. dist.

15.501 Left bank of wash, 4 ft. high, bears SW. and NE.

18.80 Right bank of wash, 4 ft. high, bears SW. and NE.

19.968 Point for the E. 1/16 sec. cor. of secs. 23 and 26.

Set a washed boulder, 10x6x5 ins., mkd. with a X, 12 ins. below the surface of the ground,

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears N. 45° E., 70.7 lks. dist., with brass cap mkd. E 1/16 S.23 RM 1950 and an arrow pointing to the corner.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears S. 45° W., 70.7 lks. dist., with brass cap mkd. E 1/16 S.26 RM 1950 and an arrow pointing to the corner.

29.952 Point for the W.E. 1/64 sec. cor. of secs. 23 and 26.

Set an iron pipe, 14 ins. long, 1 1/4 ins. diam., 6 ins. below the surface of the ground,

from which

A wooden stake, 1 ft. long, 2 ins. sq., set 8 ins. in the ground, bears NORTH, 50 lks. dist.

39.936 The 1/4 sec. cor. of secs. 23 and 26, which is monumented by an iron post, 1 in. diam., firmly set 6 ins. below the surface of the ground, with brass cap mkd. as described in official record.

Dependent Resurvey of a Portion of the Boundaries of Section 23,  
T. 3 N., R. 5 E.

## Chains

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears S.  $45\frac{1}{4}^{\circ}$  E., 70.7 lks. dist., with brass cap mkd.  $\frac{1}{4}$  S 26 RM 1950 and an arrow pointing to the cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears N.  $45\frac{1}{4}^{\circ}$  W., 70.7 lks. dist., with brass cap mkd.  $\frac{1}{4}$  S 23 RM 1950 and an arrow pointing to the cor.

S.  $89^{\circ} 58'$  W., beginning new measurement.

Continue along center line of Shea Blvd.

9.990 Point for the EW.  $1/64$  sec. cor. of secs. 23 and 26.

Set a washed boulder,  $12 \times 6 \times 4$  ins., mkd. with a X on top, 12 ins. below the surface of the ground.

from which

A wooden stake, 1 ft. long, 2 ins. sq., set 8 ins. in the ground, bears N.  $0^{\circ} 01'$  W., 50 lks. dist.

19.980 Point for the W.  $1/16$  sec. cor. of secs. 23 and 26.

Set a washed boulder,  $12 \times 5 \times 3$  ins., mkd. with a X on top, 12 ins. below the surface of the ground.

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears S.  $45^{\circ}$  E., 70.7 lks. dist., with brass cap mkd. W  $1/16$  S 26 RM 1950 and an arrow pointing to the corner.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears N.  $45^{\circ}$  W., 70.7 lks. dist., with brass cap mkd. W  $1/16$  S 23 RM 1950 and an arrow pointing to the corner.

29.970 Point for the WW  $1/64$  sec. cor. of secs. 23 and 26.

Set a washed boulder,  $8 \times 6 \times 5$  ins., mkd. with a X on top, 12 ins. below the surface of the ground,

from which

A wooden stake, 1 ft. long, 2 ins. sq., set 8 ins. in the ground, bears N.  $0^{\circ} 01'$  W., 50 lks. dist.

39.960 The cor. of secs. 22, 23, 26 and 27, which is an iron post, 2 ins. diam., mkd. and witnessed as described in the field notes of 1950 resurvey of the boundaries of sec. 27, hereinafter described.

Land, rolling desert.

Soil, sandy loam, rocky.

Timber, palo verde, ironwood and mesquite; undergrowth, sage and cacti.

N.  $0^{\circ} 01'$  W., bet. secs. 22 and 23.

Over rolling land, through scattering timber and undergrowth.

10.000 Point for the S S  $1/64$  sec. cor. of secs. 22 and 23.

Set a wooden post,  $2\frac{1}{2}$  ft. long, 2 ins. sq., 16 ins. in the ground, mkd. S-S-  $1/64$  on S., S 22 on W. and S 23 on E. faces.

20.000 Point for the S.  $1/16$  sec cor. of secs. 22 and 23.

DOCP 400

Dependent Resurvey of a Portion of the Boundaries of Section 23,  
T. 3 N., R. 5 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to solidrock and in a mound of stone to top, with brass cap mkd.

S 1/16

S 22 | S 23

1950

40.000 The 1/4 sec. cor. of secs. 22 and 23, which is monumented by an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.

Land, rolling desert.  
Soil, sandy loam, rocky.  
Timber, palo verde, ironwood and mesquite.  
Undergrowth, greasewood, sage and cacti.

From the cor. of secs. 23, 24, 25 and 26, hereinbefore described.  
N. 0° 01' W., bet. secs. 23 and 24.

Over rolling land, through scattering timber and undergrowth.

2.200 Wash, 30 lks. wide, 2 ft. deep, course S. 60° W.

9.900 Left bank of wash, 6 ft. high, bears SW. and NE.; enter wash area.

10.007 Point for the S S 1/64 sec. cor. of secs. 23 and 24.

Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 in. in the ground, mkd. S-S- 1/64 on S., S 23 on W. and S 24 on the E. faces.

10.600 Main channel of wash, 40 lks. wide, course SW.

14.500 Right bank of wash, 4 ft. high, bears SW. and NE.; leave wash area.

20.014 Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S 1/16

S 23 | S 24

1950

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

40.028 The 1/4 sec. cor. of secs. 23 and 24, which is monumented by an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.

Land, rolling desert.  
Soil, sandy loam, rocky.  
Timber, palo verde, ironwood and mesquite.  
Undergrowth, greasewood, sage and cacti.

Subdivision of Section 23, T. 3 N., R. 5 E.

From the 1/4 sec. cor. of secs. 23 and 26.

North, on the N. and S. center line of sec. 23.


0.500 Set a wooden stake, 1 ft. long, 2 ins. sq., 8 ins. in the ground.

10.007 Point for the C S S 1/64 sec. cor. of sec. 23.

Chains  
Set a wooden post,  $2\frac{1}{2}$  ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S-S-  $\frac{1}{64}$  S 23.


20.015 Point for the C S.  $\frac{1}{16}$  sec. cor. of sec. 23.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to solidrock and in a mound of stone to top, with brass cap mkd.



40.030 Point for the C.  $\frac{1}{4}$  sec. cor. of sec. 23, at the intersection of the E. and W. center line.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to solidrock, and in a mound of stone to top, with 3 ft. base, with brass cap mkd.




80.060 The  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, which is monumented by an iron post, 1 in. diam., firmly set and projecting 9 ins. above ground, mkd. and witnessed as described in the official record.

From the  $\frac{1}{4}$  sec. cor. of secs. 23 and 24.

West, on the E. and W. center line of sec. 23.

19.975 Point for the C E.  $\frac{1}{16}$  sec. cor. of sec. 23.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.




raise a mound of stone, 3 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

39.950 The C.  $\frac{1}{4}$  sec. cor. of sec. 23.

59.925 Point for the C W  $\frac{1}{16}$  sec. cor. of sec. 23.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

79.900 The  $\frac{1}{4}$  sec. cor. of secs. 22 and 23.

Subdivision of the SE.  $\frac{1}{4}$ .

From the E,  $\frac{1}{16}$  sec. cor. of secs. 23 and 26.

North, on the N. and S. center line of the SE.  $\frac{1}{4}$  of sec. 23.

## Subdivision of Section 23, T. 3 N., R. 5 E.

Chains	
0.500	Set a wooden stake, 1 ft. long, 2 ins. sq., 8 ins. in the ground,
10.012	Point for the C S SE $1/64$ sec. cor. of sec. 23. Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S-SE- $1/64$ S 23.
20.025	Point for the SE. $1/16$ sec. cor. of sec. 23. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  SE $1/16$ S 23  1950
40.040	The C E. $1/16$ sec. cor. of sec. 23. <hr/> From the S. $1/16$ sec. cor. of secs. 23 and 24. N. $89^{\circ} 58'$ W., on the E. and W. center line of the SE. $\frac{1}{4}$ of sec. 23.
9.997	Point for the C E SE $1/64$ sec. cor. of sec. 23. Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E-SE- $1/64$ S 23.
13.500	Wash, 8 lks. wide, 3 ft. deep, course S.
19.994	The SE $1/16$ sec. cor. of sec. 23.
28.200	Wash, 80 lks. wide, course S.
29.984	Point for the C W SE $1/64$ sec. cor. of sec. 23. Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W-SE $1/64$ S 23.
39.974	The C S $1/16$ sec. cor. of sec. 23. <hr/> Subdivision of the SE. $\frac{1}{4}$ , SE. $\frac{1}{4}$ . <hr/> From the E E $1/64$ sec. cor. of sec. 23. N. $0^{\circ} 01'$ W., on the N. and S. center line of the SE. $\frac{1}{4}$ , SE. $\frac{1}{4}$ of sec. 23.
.50	Wooden stake on line.
7.000	Wash, 35 lks. wide, 20 ft. deep, course SW.
10.014	Point for the SE SE $1/64$ sec. cor. of sec. 23, at the intersection of the E. and W. center line. Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SE-SE $1/64$ S 23.
20.015	The C E SE $1/64$ sec. cor. of sec. 23. <hr/> From the S S $1/64$ sec. cor. of secs. 23 and 24. N. $89^{\circ} 58'$ W., on the E. and W. center line of the SE. $\frac{1}{4}$ , SE. $\frac{1}{4}$ sec. 23.
0.400	Wash, 30 lks. wide, 2 ft. deep, course SW.
4.300	Same wash, 80 lks. wide, 1 ft. deep, course NW.
8.700	Same wash, 40 lks. wide, 2 ft. deep, course S. $30^{\circ}$ W.

## Subdivision Of Section 23, T. 3 N., R. 5 E.

4355

Chains	
10.000	The SE SE 1/64 sec. cor. of sec. 23.
19.994	The C S SE. 1/64 sec. cor. of sec. 23.
Subdivision of the SW. 1/4, SE. 1/4.	
	From the WE. 1/64 sec. cor. of sec. 23.
	North, on the N. and S. center line of the SW. 1/4, SE. 1/4 of sec. 23.
.50	Wooden stake on line.
10.008	Point for the SW. SE. 1/64 sec. cor. of sec. 23, at the intersection of the E. and W. center line. Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SW-SE 1/64 S 23.
20.024	The C W SE 1/64 sec. cor. of sec. 23.
Subdivision of the SW. 1/4, SE. 1/4.	
	From the C S SE. 1/64 sec. cor. of sec. 23.
	N. 89° 58' W., on the E. and W. center line of the SW. 1/4, SE. 1/4 of sec. 23.
4.800	Wash, 30 lks. wide, 1 ft. deep, course S.
8.800	Wash, 20 lks. wide, 3 ft. deep, course S.
9.992	The SW SE 1/64 sec. cor. of sec. 23.
19.964	The C S S 1/64 sec. cor. of sec. 23.
Subdivision of the SW. 1/4.	
	From the W. 1/16 sec. cor. of sees. 23 and 26.
	North, on the N. and S. center line of the SW. 1/4 of sec. 23.
10.001	Point for the C S SW 1/64 sec. cor. of sec. 23, Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S-SW 1/64 S 23.
20.002	Point for the SW. 1/16 sec. cor. of sec. 23, at the intersection of the E. and W. center line. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to solidrock and in a mound of stone to top, with brass cap mkd. SW 1/16 S 23 1950
40.003	The C W. 1/16 sec. cor. of sec. 23.
	From the C S 1/16 sec. cor. of sec. 23.
	S. 89° 58' W., on the E. and W. center line of the SW. 1/4 of sec. 23.
0.500	Wash, 30 lks. wide, 6 ft. deep, course S. 30° W.
9.982	Point for the C E SW 1/64 sec. cor. of sec. 23. Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E-SW 1/64 S 23.
19.964	The SW 1/16 sec. cor. of sec. 23.

## Subdivision of Section 23, T. 3 N., R. 5 E.

Chains	
29.950	Point for the C W SW $1/64$ sec. cor. of sec. 23. Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W-SW $1/64$ S 23.
30.100	Wash, 10 lks. wide, 1 ft. deep, course S.
35.400	Left bank of wash, bears N. and S.
37.100	Right bank of wash, bears N. and S.
39.936	The S. $1/16$ sec. cor. of secs. 22 and 23.

Subdivision of the SE.  $\frac{1}{4}$ , SW.  $\frac{1}{4}$ .

	From the E. $1/64$ sec. cor. of secs. 23 and 26. N. $0^{\circ} 01'$ W., on the N. and S. center line of the SE. $\frac{1}{4}$ , SW. $\frac{1}{4}$ of sec. 23. .50 Wooden stake on line. 5.000 Wash, 50 lks. wide, 10 ft. deep, course S. $70^{\circ}$ W.
10.007	Point for the SE SW. $1/64$ sec. cor. of sec. 23, at the intersection of the E. and W. center line Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SE-SW $1/64$ S 23.
20.024	The C E SW. $1/64$ sec. cor. of sec. 23.

From the C S S  $1/64$  sec. cor. of sec. 23.

	S. $89^{\circ} 58'$ W., on the E. and W. center line of the SE. $\frac{1}{4}$ , SW. $\frac{1}{4}$ of sec. 23.
5.900	Wash, 20 lks. wide, 3 ft. deep, course S. $20^{\circ}$ W.
9.990	The SE SW $1/64$ sec. cor. of sec. 23.
19.984	The C S SW, $1/64$ sec. cor. of sec. 23.

Subdivision of the SW.  $\frac{1}{4}$ , SW.  $\frac{1}{4}$ .

	From the W W $1/64$ sec. cor. of secs. 23 and 26. N. $0^{\circ} 01'$ W., on the N. and S. center line of the SW. $\frac{1}{4}$ , SW. $\frac{1}{4}$ of sec. 23. .50 Wooden stake on line. 9.998 Point for the SW SW. $1/64$ sec. cor. of sec. 23, at the intersection of the E. and W. center line. Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SW-SW $1/64$ S 23.
20.010	The C W SW $1/64$ sec. cor. of sec. 23.
	From the C S SW $1/64$ sec. cor. of sec. 23. S. $89^{\circ} 58'$ W., on the E. and W. center line of the SW. $\frac{1}{4}$ , SW. $\frac{1}{4}$ , sec. 23.
9.985	The SW SW. $1/64$ sec. cor. of sec. 23.
16.600	Wash, 40 lks. wide, 2 ft. deep, course S. $20^{\circ}$ W.
19.979	The S S $1/64$ sec. cor. of secs. 22 and 23.



Dependent Resurvey of a Portion of the Boundaries of  
Section 25, T. 3 N., R. 5 E.

4385

Chains

Reestablishment of Resurvey Executed by Robert  
A. Farmer, Topographer, in 1911 and the Survey  
Executed by Sidney E. Blout, Surveyor, in 1914.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the T.,  
which is monumented by an iron post, 3 ins. diam., firmly set and  
projecting 2 ins. above ground, with brass cap mkd.

R5E T3N	R6E
S 36	S 31
SRIR	

1911

change markings on above brass cap to read

T3N	
R5E	R6E
S 25	S 30
R5E T3N	R6E
S 36	S 31
SRIR	

1950

1911

raise a mound of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

N.  $89^{\circ} 58'$  W., bet. secs. 25 and 36.

Over nearly level desert land, through scattering timber and under-  
growth; 50 lks. N. of Salt River Indian Reservation bdy. fence.

6.90 Wash, 40 lks. wide, 2 ft. deep, course S.

9.974 Point for the E E.  $1/64$  sec. cor. of secs. 25 and 36.

Set a wooden post,  $2\frac{1}{2}$  ft. long, 2 ins. sq., 16 ins. in the ground,  
mkd. E-E  $1/64$  on W., S 25 on N. and S 36 on S. faces.

19.948 The E.  $1/16$  sec. cor. of secs. 25 and 36, which is an iron post, 1  
in. diam., firmly set, and projecting 10 ins. above ground, mkd.  
as described in the official record.

N.  $89^{\circ} 52'$  W., beginning new measurement.

20.003 The  $\frac{1}{4}$  sec. cor. of secs. 25 and 36, which is monumented by an iron  
post, 1 in. diam., firmly set and projecting 10 ins. above the  
ground, with brass cap mkd. as described in the official record.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the T.

N.  $0^{\circ} 05'$  W., bet. secs. 25 and 30.

Over gently rolling desert land, through scattering timber and  
undergrowth; ascend gradually.

9.995 Point for the S S.  $1/64$  sec. cor. of secs. 25 and 30.


Set a wooden post,  $2\frac{1}{2}$  ft. long, 2 ins. sq., 16 ins. in the ground,  
mkd. S-S  $1/64$  on S., S 25 on W. and S 30 on E. faces.

Dependent Resurvey of a Portion of the Boundaries of  
Section 25, T. 3 N., R. 5 E.

Chains  
19.990

Point for the S. 1/16 sec. cor. of secs. 25 and 30.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

24.300 Wash, 15 lks. wide, course SW.

39.600 Wash, 80 lks. wide, course SE.

39.980 True <sup>point</sup> for the ¼ sec. cor. of secs. 25 and 30, falls on edge of wash, not safe to set.

N. 0° 01' W., beginning new measurement.

1.000 Witness ¼ sec. cor. of secs. 25 and 30, which is monumented by an iron post, 1 in. diam., firmly set and projecting 10 ins. above ground, with brass cap mkd. and witnessed as described in the official records.


12.800 Enter wash, bears NE. and S. 20° W.

16.000 Main channel of same wash, 80 lks. wide, course SW.

17.800 Leave wash, bears NE. and SW.

20.015 Point for the N. 1/16 sec. cor. of secs. 25 and 30.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

40.030 Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron rod, 16 ins. long, 1 in. diam., 6 ins. below the surface of the ground

from which

An iron post, 3 ft. long, 1 in. diam., set 20 ins. in the ground, to solid rock, and in a mound of stone to top, for a reference monument, bears N. 45° E., 70.7 lks. dist., with brass cap mkd. T3N R6E S19 RM 1950 and an arrow pointing to the corner.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears S. 45° W., 70.7 lks. dist., with brass cap mkd. T3N R5E S25 RM 1950 and an arrow pointing to the corner.

The cor. of secs. 13, 18, 19 and 24, bears N. 0° 01' W., 80.06 chs. dist.

Dependent Resurvey of a Portion of the Boundaries of  
Section 25, T. 3 N., R. 5 E.

4385

Chains	
	N. 89° 54' W., bet. secs. 24 and 25.
	Over gently rolling desert land, through scattering timber and undergrowth; along the center line of graded Shea Blvd.
20.000	Point for the E. 1/16 sec. cor. of secs. 24 and 25.
	Set a washed boulder, 12x5x4 ins., marked with a X on top, 12 ins. below the surface of the ground,
	from which
	An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears N. 45° E., 70.7 lks. dist., with brass cap mkd. E 1/16 S24 RM 1950 and arrow pointing to the cor.
	An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears S. 45° W., 70.7 lks. dist., with brass cap mkd. E 1/16 S25 RM 1950 and arrow pointing to the cor.
30.000	Point for the WE. 1/64 sec. cor. of secs. 24 and 25.
	Set a washed boulder, 10x7x4 ins., mkd. with a X on top, 12 ins. below the surface of the ground,
	from which
	A wooden stake, 1 ft. long, 2 ins. sq., set 8 ins. in the ground, bears S. 0° 02' E., 50 lks. dist.
30.300	Wash, 35 lks. wide, 9 ft. deep, course S. 20° W.
40.000	The $\frac{1}{4}$ sec. cor. of secs. 24 and 25, which is monumented by an iron post, 1 in. diam., firmly set 8 ins. below the surface of the road, with brass cap mkd. as described in the official record.
	from which
	An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears S. 45° E., 70.7 lks. dist., with brass cap mkd. $\frac{1}{4}$ S25 RM 1950 and an arrow pointing to the cor.
	An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears N. 45° W., 70.7 lks. dist., with brass cap mkd. $\frac{1}{4}$ S24 RM 1950 and an arrow pointing to the cor.
50.000	Point for the EW. 1/64 sec. cor. of secs. 24 and 25.
	Set a washed boulder, 10x8x4 ins., with a X mkd. on top, 12 ins. below the surface of the ground,
	from which
	A wooden stake, 1 ft. long, 2 ins. sq., set 8 ins. in the ground, bears S. 0° 02' E., 50 lks. dist.
60.000	Point for the W. 1/16 sec. cor. of secs. 24 and 25.
	Set a washed boulder, 9x5x4 ins., mkd. with a X on top, 12 ins. below the surface of the ground,
	from which
	An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears NORTH, 50 lks. dist., with brass cap mkd. W 1/16 S24 RM 1950 and an arrow pointing to the corner.
	An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears SOUTH, 50 lks. dist., with brass cap mkd. W 1/16 S25 RM 1950 and an arrow pointing to the corner.

Dependent Resurvey of a Portion of the Boundaries of  
Section 25, T. 3 N., R. 5 E.

Chains 70.000	<p>Point for the W W. 1/64 sec. cor. of secs. 24 and 25.</p> <p>Set a washed boulder, 9x6x5 ins., mkd. with a X on top, 12 ins. below the surface of the ground,</p> <p>from which</p> <p style="padding-left: 40px;">A wooden stake, 1 ft. long, 2 ins. sq., set 8 ins. in the ground, bears S. 0° 01' E., 50 lks. dist.,</p>
80.000	<p>The cor. of secs. 23, 24, 25 and 26, which is an iron post, 2 ins. diam., mkd. and witnessed as described in the field notes of 1950 resurvey, of the boundaries of sec. 23, herein described.</p> <p>Land, gently rolling desert. Soil, sandy loam, rocky. Timber, palo verde, ironwood and mesquite. Undergrowth, greasewood, sage and cacti.</p>
<hr/> <p>Subdivision of Section 25, T. 3 N., R. 5 E.</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0° 03' W., on the N. and S. center line of sec. 25.</p>
20.009	<p>Point for the C.S. 1/16 sec. cor. of sec. 25.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> </div>
26.600	<p>Wash, 60 lks. wide, 1 ft. deep, course SW.</p>
40.018	<p>Point for the C. 1/4 sec. cor. of sec. 25, at the intersection of the E. and W. center line</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to solid rock and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> </div>
44.300	<p>Wash, 150 lks. wide, 1 ft. deep, course S. 20° E.</p>
50.027	<p>Point for the CSN. 1/64 sec. cor. of sec. 25.</p> <p>Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N 1/64 S25.</p>
51.30	<p>Wash, 60 lks. wide, course SW.</p>
60.036	<p>Point for the C N. 1/16 sec. cor. of sec. 25.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> </div>

## Subdivision of Section 25, T. 3 N., R. 5 E.

BOOK 4388

Chains 70.045	Point for the C N N. 1/64 sec. cor. of sec. 25.  Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N-N 1/64 S 25.
80.054	The ¼ sec. cor. of secs. 24 and 25.
	From the true point for the ¼ sec. cor. of secs. 25 and 30. N. 89°-56' W., on the E. and W. center line of sec. 25.
0.40	Wash, 80 lks. wide, 1 ft. deep, course S. 10° E., ascend 114 ft. over NE. slope of rocky hill.
11.700	Top of spur, slopes SE., descend 81 ft. over SW. slope.
19.960	Point for the C E 1/16 sec. cor. of sec. 25.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \frac{\quad}{\text{S } 25} \text{C} \\ 1950 \end{array}$
	raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.
29.940	Point for the C W E 1/64 sec. cor. of sec. 25.  Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E 1/64 S 25.
36.50	Left bank of wash, bears N. 10° W. and S. 10° E.
38.000	Main channel of wash, course S. 10° E.
39.100	Right bank of wash, bears N. 10° W. and S. 10° E.
39.920	The C ¼ sec. cor. of sec. 25.
49.924	Point for the C E W 1/64 sec. cor. of sec. 25.  Set a wooden post, 2½ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W 1/64 S 25.
59.928	Point for the C W 1/16 sec. cor. of sec. 25.  Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, to solid rock and in a mound of stone to top, with brass cap mkd.
	$\begin{array}{c} \text{W } 1/16 \\ \text{C} \frac{\quad}{\text{S } 25} \text{C} \\ 1950 \end{array}$
69.932	Point for the C W W 1/64 sec. cor. of sec. 25.  Set a wooden post, 2½ ft. long, 2 in. sq., 16 ins. in the ground, mkd. C-W-W 1/64 S 25.
79.936	The ¼ sec. cor. of secs. 25 and 26, which is an iron post, 1 in. diam., projecting 10 ins. above ground, mkd. and witnessed as described in the official record.

Subdivision of the NE. ¼.

Subdivision of Section 25, T. 3 N.; R. 5 E.

Chains	
	From the C E 1/16 sec. cor. of sec. 25.
	N. 0° 01' W., on the N. and S. center line of the NE. 1/4, sec. 25.
	Ascend 125 ft. over S. slope.
7.500	Top of spur, slopes SE., descend 88 ft. over NE. slope.
10.004	Point for the C S NE. 1/64 sec. cor. of sec. 25.
	Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S-NE 1/64 S 25.
15.000	Bottom of descent, bears SE. and W.
20.007	Point for the NE. 1/16 sec. cor. of sec. 25, at the intersection of the E. and W. center line.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	NE 1/16 S 25
	1950
	raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.
24.300	Wash, 50 lks. wide, 5 ft. deep, course S. 70° W.
30.017	Point for the C N NE 1/64 sec. cor. of sec. 25.
	Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-N-NE 1/64 S 25.
40.027	The E. 1/16 sec. cor. of secs. 24 and 25.
<hr/>	
	From the N. 1/16 sec. cor. of secs. 25 and 30.
	N. 89° 56' W., on the E. and W. center line of the NE. 1/4, sec. 25.
19.988	The NE. 1/16 sec. cor. of sec. 25.
28.200	Wash, 80 lks. wide, 6 ft. deep, course S.
29.976	Point for the C W NE. 1/64 sec. cor. of sec. 25.
	Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-W-NE 1/64 S 25.
36.800	Wash, 50 lks. wide, 2 ft. deep, course S.
39.964	The C N. 1/16 sec. cor. of sec. 25.
<hr/>	
Subdivision of the SW. 1/4, NE. 1/4.	
<hr/>	
	From the C W E. 1/64 sec. cor. of sec. 25.
	N. 0° 02' W., on the N. and S. center line of the SW. 1/4, NE. 1/4, of sec. 25.
2.400	Base of rocky hill; ascend 200 ft. over S. slope.
10.005	Point for the SW-NE. 1/64 sec. cor. of sec. 25, at the intersection of the E. and W. center line.
	Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SW-NE 1/64 S 25.

## Subdivision of Section 25, T. 3 N., R. 5 E.

4686

Chains	
10.200	Top of spur, slopes N. 70° E.; descend 158 ft. over N. slope.
17.300	Wash, 20 lks. wide, course S. 80° W.
20.011	The C W NE. 1/64 sec. cor. of sec. 25.
	From the C S NE. 1/64 sec. cor. of sec. 25.
	N. 89° 56' W., on the E. and W. center line of the SW. 1/4, NE. 1/4 of sec. 25.
4.700	Top of spur, slopes SE.; descend slightly along S. slope.
7.800	Saddle in same spur, bears N., 1.00 ch. dist.; ascend 77 ft. over E. slope of rocky butte.
9.980	The SW. NE. 1/64 sec. cor. of sec. 25.
12.000	Top of rocky butte, bears S. 50 lks. dist.; descend 272 ft. over rocky NW. slope.
19.970	The CSN. 1/64 sec. cor. of sec. 25.
	Subdivision of the NW. 1/4, NE. 1/4.
	From the C W NE. 1/64 sec. cor. of sec. 25.
	N. 0° 02' W., on the N. and S. center line of the NW. 1/4, NE. 1/4, sec. 25.
10.010	Point for the NW. NE. 1/64 sec. cor. of sec. 25 at the intersection of the E. and W. center line.
	Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. NW-NE 1/64 S 25
19.520	Wooden stake on line.
20.020	The WE. 1/64 sec. cor. of secs. 24 and 25.
	From the C N NE. 1/64 sec. cor. of sec. 25.
	N. 89° 55' W., on the E. and W. center line of the NW. 1/4, NE. 1/4, sec. 25.
9.975	The NW. NE. 1/64 sec. cor. of sec. 25.
14.800	Wash, 90 lks. wide, 10 ft. deep, course S. 30° W.
19.977	The C N N. 1/64 sec. cor. of sec. 25.
	Subdivision of the SE. 1/4.
	From the E. 1/16 sec. cor. of secs. 25 and 36.
	N. 0° 07' W., on the N. and S. center line of the SE. 1/4 of sec. 25.
10.002	Point for the C S SE. 1/64 sec. cor. of sec. 25.
	Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-S-SE 1/64 S 25
20.004	Point for the SE. 1/16 sec. cor. of sec. 25 at the intersection of the E. and W. center line.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	SE 1/16 S 25
	1950
	raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.
40.004	The C E. 1/16 sec. cor. of sec. 25..
	From the S. 1/16 sec. cor. of secs. 25 and 30.
	N. 89° 57' W., on the E. and W. center line of the SE. 1/4.
1.800	Wash, 20 lks. wide, 1 ft. deep, course S.
9.990	Point for the C E SE. 1/64 sec. cor. of sec. 25.
	Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. C-E-SE 1/64 S 25

Subdivision of Section 25, T. 3 N., R. 5 E.

Chains	
19.980	The SE. 1/16 sec. cor. of sec. 25.
39.965	The C S. 1/16 sec. cor. of sec. 25.
Subdivision of the SE. 1/4, SE. 1/4.	
From the E E. 1/64 sec. cor. of secs. 25 and 36.	
N. 0° 07' W., on the N. and S. center line of the SE. 1/4, SE. 1/4 of sec. 25.	
9.998	Point for the SE. SE. 1/64 sec. cor. of sec. 25 at the intersection of the E. and W. center line. <small>DISOP</small>
Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SE-SE 1/64 S 25.	
19.996	The C E SE. 1/64 sec. cor. of sec. 25.
From the S S. 1/64 sec. cor. of secs. 25 and 30.	
N. 89° 59' W., on the E. and W. center line of SE. 1/4, SE. 1/4 of sec. 25.	
6.600	Wash, 1 ch. wide, 1 ft. deep, course SW.
9.978	The SE. SE. 1/64 sec. cor. of sec. 25.
19.938	The C S SE. 1/64 sec. cor. of sec. 25.
Subdivision of the NW. 1/4.	
From the C W. 1/16 sec. cor. of sec. 25.	
N. 0° 01' W., on the N. and S. center line of the NW. 1/4 of sec. 25.	
2.100	Unimproved road, bears SW. and NE.
3.500	Dry wash, drains SW.
9.999	Point for the C S NW. 1/64 sec. cor. of sec. 25.
Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 14 ins. in the ground, mkd. C-S-NW 1/64 S 25.	
19.998	Point for the NW. 1/16 sec. cor. of sec. 25 at the intersection of the E. and W. center line.
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd. NW 1/16 S 25 1950	
30.003	Point for the CN. NW. 1/64 sec. cor. of sec. 25.
Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 14 ins. in the ground, mkd. C-N-NW 1/64 S 25.	
33.080	Dry wash, drains SW.
40.008	The W. 1/16 sec. cor. of secs. 24 and 25.
From the CN. 1/16 sec. cor. of sec. 25.	
N. 89° 55' W., on the E. and W. center line of the NW. 1/4 of sec. 25.	
10.000	Point for the C E NW. 1/64 sec. cor. of sec. 25.
Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 14 ins. in the ground, mkd. C-E-NW 1/64 S 25.	
20.000	The NW. 1/16 sec. cor. of sec. 25.
29.995	Point for the CW. NW. 1/64 sec. cor. of sec. 25.
Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 14 ins. in the ground, mkd. C-W-NW 1/64 S 25.	
39.990	The N. 1/16 sec. cor. of secs. 25 and 26.



## Subdivision of Section 25, T. 3 N., R. 5 E.

Chains	Subdivision of the NE. $\frac{1}{4}$ , NW. $\frac{1}{4}$ .
	From the CE NW. $\frac{1}{64}$ sec. cor. of sec. 25. N. $0^{\circ} 02' W.$ , on the N. and S. center line of the NE. $\frac{1}{4}$ , NW. $\frac{1}{4}$ of sec. 25
6.60	Wash, 5 lks. wide, course SW.
10.001	Point for the NE. NW. $\frac{1}{64}$ sec. cor. of sec. 25 at the intersection of the E. and W. center line.
19.517	Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. NE-NW $\frac{1}{64}$ S 25.
20.017	Wooden stake on line. The EW. $\frac{1}{64}$ sec. cor. of secs. 24 and 25.
	From the C N N. $\frac{1}{64}$ sec. cor. of sec. 25. N. $89^{\circ} 55' W.$ , on the E. and W. center line of the NE. $\frac{1}{4}$ , NW. $\frac{1}{4}$ of sec. 25.
9.992	The NE. NW. $\frac{1}{64}$ sec. cor. of sec. 25.
19.986	The C N NW. $\frac{1}{64}$ sec. cor. of sec. 25.
	Subdivision of the SE. $\frac{1}{4}$ , NW. $\frac{1}{4}$ .
	From the CEW. $\frac{1}{64}$ sec. cor. of sec. 25. N. $0^{\circ} 02' W.$ , on the N. and S. center line of the SE. $\frac{1}{4}$ , NW. $\frac{1}{4}$ , sec. 25.
10.000	Point for the SE. NW. $\frac{1}{64}$ sec. cor. of sec. 25 at the intersection of the E. and W. center line.
	Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 16 ins. in the ground, mkd. SE-NW $\frac{1}{64}$ S 25.
19.998	The C E NW. $\frac{1}{64}$ sec. cor. of sec. 25.
	From the CSN $\frac{1}{64}$ sec. cor. of sec. 25. N. $89^{\circ} 54' W.$ , on the E. and W. center line of the SE. $\frac{1}{4}$ , NW. $\frac{1}{4}$ of sec. 25.
0.900	Wash, 100 lks. wide, 3 ft. deep, course S.
10.012	The SE. NW. $\frac{1}{64}$ sec. cor. of sec. 25.
17.21	Wash, 40 lks. wide, 2 ft. deep, course S.
20.012	The C S NW. $\frac{1}{64}$ sec. cor. of sec. 25.
	Subdivision of the SW. $\frac{1}{4}$ , NW. $\frac{1}{4}$ .
	From the C W W. $\frac{1}{64}$ sec. cor. of sec. 25. N. $0^{\circ} 01' W.$ , on the N. and S. center line of the SW. $\frac{1}{4}$ , NW. $\frac{1}{4}$ of sec. 25.
9.998	Point for the SW. NW. $\frac{1}{64}$ sec. cor. of sec. 25 at the intersection of the E. and W. center line.
	Set a wooden post, $2\frac{1}{2}$ ft. long, 2 ins. sq., 14 ins. in the ground, mkd. SW-NW $\frac{1}{64}$ S 25.
19.999	The C W NW. $\frac{1}{64}$ sec. cor. of sec. 25.

Subdivision of Section 25, T. 3 N., R. 5 E.

Chains

From the C S NW. 1/64 sec. cor. of sec. 25.

N. 89° 55' W., on the E. and W. center line of the SW. 1/4, NW. 1/4 of sec. 25.

10.000 The SW. NW. 1/64 sec. cor. of sec. 25.

19.994 The SN. 1/64 sec. cor. of secs. 25 and 26.

Subdivision of the NW. 1/4, NW. 1/4.

From the C W NW. 1/64 sec. cor. of sec. 25.

N. 0° 01' W., on the N. and S. center line of the NW. 1/4, NW. 1/4 of sec. 25.

10.000 Point for the NW. NW. 1/64 sec. cor. of sec. 25 at the intersection of the E. and W. center line.

Set a wooden post, 2 1/2 ft. long, 2 ins. sq., 14 ins. in the ground, mkd. NW-NW 1/64 S 25.

10.150 Dry wash, drains SW.

13.600 Dry Wash, drains SW.

19.510 Wooden stake on line.

20.010 The W W. 1/64 sec. cor. of secs. 24 and 25.

From the C N NW. 1/64 sec. cor. of sec. 25.

N. 89° 54' W., on the E. and W. center line of the NW. 1/4, NW. 1/4 of sec. 25.

5.090 Dry wash, drains SW.

10.002 The NW. NW. 1/64 sec. cor. of sec. 25.

19.994 The N N. 1/64 sec. cor. of secs. 25 and 26.

Dependent Resurvey of a Portion of the Boundaries of Section 5,  
T. 3 N., R. 5 E.

Chains.

... has been established by the Survey Executed  
by Sidney E. Bibut, Surveyor, in 1914.

From the  $\frac{1}{4}$  sec. cor. of secs. 5 and 8, which is monumented by an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, marked and witnessed as described in the official record.

N. 89° 52' W., bet. secs. 5 and 8.

Over rolling land, through scattering timber.

13.40 Power line maintenance road, under construction, bears NW. and SE.

20.015 Point for the W 1/16 sec. cor. of secs. 5 and 8.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S5  
W 1/16  $\frac{S5}{S8}$   
1950

25.75 Unimproved road, bears NE. and SW.

40.03 The cor. of secs. 5, 6, 7 and 8, which is monumented by an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, marked and witnessed as described in the official record.

Land, rolling.

Soil, gravelly.

Timber, scattering paloverde; undergrowth, greasewood and cacti.

N. 0° 17' W., bet. secs. 5 and 6.

Over rolling land, through scattering timber.

20.006 Point for the S 1/16 sec. cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S 1/16  
S6 | S5  
1950

21.00 Wash, 20 lks. wide, course SW.

36.80 Power line maintenance road, under construction, bears NW. and SE.

40.012 The  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, which is monumented by an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, marked and witnessed as described in the official record.

45.00 Old Verde Irrigation Canal, course NW.

49.993 Point for the SN 1/64 sec. cor. of secs. 5 and 6.

Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. N 1/64 on W. face.

59.974 Point for the N 1/16 sec. cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

N 1/16  
S6 | S5  
1950

Dependent Resurvey of a Portion of the Boundaries of Section 5,  
T. 3 N., R. 5 E.

Chains. 69.955	Point for the NN 1/64 sec. cor. of secs. 5 and 6.  Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. NN 1/64 on W. face.
77.162	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of Tp., which is monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, marked and witnessed as described in the official record.  Land, rolling. Soil, sandy loam, and gravelly. Timber, paloverde and ironwood; undergrowth, greasewood and cacti.
East, bet. secs. 5 and 32.  Over rolling land, through scattering timber and undergrowth.	
9.50	Wash, 15 lks. wide, course S.
10.00	Point for the WW 1/64 sec. cor. of secs. 5 and 32.  Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. WW 1/64 on N. face.
20.00	Point for the W 1/16 sec. cor. of secs. 5 and 32.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <math display="block">\begin{array}{r} S32 \\ W\ 1/16 \text{ ---} \\ S\ 5 \\ 1950 \end{array}</math> </div>
20.15	Wash, 15 lks. wide, course S.
30.00	Point for the W 1/64 sec. cor. of secs. 5 and 32.  Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. W 1/64 on N. face.
40.00	The 1/4 sec. cor. of secs. 5 and 32, which is monumented by an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, marked and witnessed as described in the official record.  Land, rolling. Soil, sandy loam, and gravelly. Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.
Subdivision of Section 5, T. 3 N., R. 5 E.	
From the 1/4 sec. cor. of secs. 5 and 8.	
N. 0° 18' W., on the N. and S. center line of sec. 5.	
10.90	Wash, 10 lks. wide, course SW.
18.00	Old Verde Irrigation Canal, banks 6 ft. high, 40 lks. wide, course NW.
19.99	Point for the CS 1/16 sec. cor. of sec. 5.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <math display="block">\begin{array}{c} C \\   \\ S\ 1/16\  S5 \\   \\ C \\ 1950 \end{array}</math> </div>

## Subdivision of Section 5, T. 3 N., R. 5 E.

BOOK 4885

Chains. 29.985	Point for the $\text{CS} \frac{1}{64}$ sec. cor. of sec. 5.  Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CS $\frac{1}{64}$ on W. face.
39.98	Point for the $\text{C} \frac{1}{4}$ sec. cor. of sec. 5, at the intersection of the E. and W. center line.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  $\text{C} \frac{1}{4} \text{ S5}$  1950  From this cor., the $\frac{1}{4}$ sec. cor. of secs. 4 and 5 bears $\text{S. } 89^{\circ} 51' \text{ E.}$ , 40.03 chs. dist., and is monumented by an iron post, 1 in. diam., projecting 26 ins. above ground, surrounded by a mound of stone, with brass cap marked as described in the official record.
49.966	Point for the $\text{CSN} \frac{1}{64}$ sec. cor. of sec. 5, at proportionate distance.  Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CN $\frac{1}{64}$ on W. face.
59.952	Point for the $\text{CN} \frac{1}{16}$ sec. cor. of sec. 5, at proportionate distance.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  $\begin{array}{c} \text{C} \\ \text{N } \frac{1}{16} \text{ S5} \\ \text{C} \\ 1950 \end{array}$
66.70	Wash, 10 lks. wide, course SE.
69.938	Point for the $\text{CNN} \frac{1}{64}$ sec. cor. of sec. 5, at proportionate distance.  Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CNN $\frac{1}{64}$ on W. face.
77.258	The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, on N. bdy. of Tp. <hr/> From the $\text{C} \frac{1}{4}$ sec. cor. of sec. 5.  N. $89^{\circ} 51'$ W., on the E. and W. center line of sec. 5.
9.998	Point for the $\text{CW} \frac{1}{64}$ sec. cor. of sec. 5.  Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CW $\frac{1}{64}$ on N. face.
13.00	Unimproved road, bears NE. and SW.
19.996	Point for the $\text{CW} \frac{1}{16}$ sec. cor. of sec. 5.  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.  $\begin{array}{c} \text{W } \frac{1}{16} \\ \text{C} \text{ --- } \text{C} \\ \text{S5} \\ 1950 \end{array}$
27.00	Old Verde Irrigation Canal, 40 lks. wide, banks 6 ft. high, course NW.
29.994	Point for the $\text{CWW} \frac{1}{64}$ sec. cor. of sec. 5.  Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CWW $\frac{1}{64}$ on N. face.
39.992	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

Subdivision of Section 5, T. 3 N., R. 5 E.

Chains.	
	Subdivision of the SW $\frac{1}{4}$ .
	From the W 1/16 sec. cor. of secs. 5 and 8.
	N. 0° 17' W., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 5.
10.00	Power line maintenance road, bears NW. and SE.
19.995	Point for the SW 1/16 sec. cor. of sec. 5, at the intersection of the E. and W. center line.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	SW 1/16 S5 1950
30.004	Point for the CNSW 1/64 sec. cor. of sec. 5.
	Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CNSW 1/64 on W. face.
37.10	Old Verde Irrigation canal, 30 lks. wide, banks 6 ft. high, course NW.
40.013	The CW 1/16 sec. cor. of sec. 5.
	From the SC 1/16 sec. cor. of sec. 5.
	N. 89° 51' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 5.
1.50	Old Verde Irrigation Canal, 30 lks. wide, W. bank 6 ft. high, course NW.
10.002	Point for the CESW 1/64 sec. cor. of sec. 5.
	Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CESW 1/64 on N. face.
20.004	The SW 1/16 sec. cor. of sec. 5.
27.758	Power line maintenance road, bears NW. and SE.
40.008	The S 1/16 sec. cor. of secs. 5 and 6.
	Subdivision of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ .
	From the CESW 1/64 sec. cor. of sec. 5.
	N. 0° 17' W., on the N. and S. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 5.
10.00	Point for the NESW 1/64 sec. cor. of sec. 5, at the intersection of the E. and W. center line.
	Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. NESW 1/64 on W. face.
12.60	Verde Irrigation Canal, 30 lks. wide, SW. bank 6 ft. high, course NW.
20.004	The <del>CW</del> 1/64 sec. cor. of sec. 5.
	From the <del>CNS</del> 1/64 sec. cor. of sec. 5.
	N. 89° 51' W., on the E. and W. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 5.
7.50	Old Verde Irrigation Canal, 30 lks. wide, course NW.

## Subdivision of Section 5, T. 3 N., R. 5 E.

Chains.	
10.003	The NESW 1/64 sec. cor. of sec. 5.
20.006	The CNSW 1/64 sec. cor. of sec. 5.
Subdivision of the NW $\frac{1}{4}$ .	
	From the CW 1/16 sec. cor. of sec. 5.
	N. 0° 16' W. on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 5.
9.978	Point for the CSNW 1/64 sec. cor. of sec. 5. Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CSNW 1/64 on W. face.
19.956	Point for the NW 1/16 sec. cor. of sec. 5, at the intersection of the E. and W. center line. Set an iron post, 3 ft. long, 1 in. diam., 1 $\frac{1}{4}$ ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd. NW 1/16 S5 1950
29.939	Point for the CNNW 1/64 sec. cor. of sec. 5, at proportionate distance. Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CNNW 1/64 on W. face.
37.201	The W 1/16 sec. cor. of secs. 5 and 32, on the N. bdy. of Tp.
Subdivision of the NE $\frac{1}{4}$ , NW $\frac{1}{4}$ .	
	From the CN 1/16 sec. cor. of sec. 5.
	N. 89° 51' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 5.
5.80	Unimproved road, bears N. and S.
9.997	Point for the CENW 1/64 sec. cor. of sec. 5. Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CENW 1/64 on N. face.
19.994	The NW 1/16 sec. cor. of sec. 5.
29.985	Point for the CWNW 1/64 sec. cor. of sec. 5. Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CWNW 1/64 on N. face.
39.60	Unimproved road, bears N. and S.
39.976	The N 1/16 sec. cor. of secs. 5 and 6.
9.984	Point for the NENW 1/64 sec. cor. of sec. 5, at the intersection of the E. and W. center line. Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. NENW 1/64 on W. face.

Subdivision of Section 5, T. 3 N., R. 5 E.

Chains. 17.28	<p>The W. 1/64 sec. cor. of secs. 5 and 32.</p> <hr/> <p>From the CNN 1/64 sec. cor. of sec. 5.</p> <p>N. 89° 51' W., on the E. and W. center line of the NE 1/4 NW 1/4 of sec. 5.</p>
9.996	The NENW 1/64 sec. cor. of sec. 5.
19.993	The CNNW 1/64 sec. cor. of sec. 5.
<p>Subdivision of the SE 1/4 NW 1/4.</p> <hr/>	
	<p>From the CEN 1/64 sec. cor. of sec. 5.</p> <p>N. 0° 16' W., on the N. and S. center line of the SE 1/4 NW 1/4 of sec. 5.</p>
9.988	Point for the SENW 1/64 sec. cor. of sec. 5, at the intersection of the E. and W. center line.
	Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. SENW 1/64 on W. face.
19.973	The CENW 1/64 sec. cor. of sec. 5.
<p>Subdivision of the SW 1/4 NW 1/4.</p> <hr/>	
	<p>From the CWN 1/64 sec. cor. of sec. 5.</p> <p>N. 0° 16' W., on the N. and S. center line of the SW 1/4 NW 1/4 of sec. 5.</p>
9.988	Point for the SWNW 1/64 sec. cor. of sec. 5, at the intersection of the E. and W. center line.
	Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. SWNW 1/64 on W. face.
19.958	The CWNW 1/64 sec. cor. of sec. 5.
<p>Subdivision of the SW 1/4 NW 1/4.</p> <hr/>	
	<p>From the CSN 1/64 sec. cor. of sec. 5.</p> <p>N. 89° 51' W., on the E. and W. center line of the SW 1/4 NW 1/4 of sec. 5.</p>
9.997	The SWNW 1/64 sec. cor. of sec. 5.
19.992	The SW 1/64 sec. cor. of secs. 5 and 6.
<p>Subdivision of the NW 1/4 NW 1/4.</p> <hr/>	
	<p>From the CWNW 1/64 sec. cor. of sec. 5.</p> <p>N. 0° 16' W., on the N. and S. center line of the NW 1/4 NW 1/4 of sec. 5.</p>
9.986	Point for the NWNW 1/64 sec. cor. of sec. 5, at the intersection with the E. and W. center line.



## Subdivision of Section 5, T. 3 N., R. 5 E.

Chains.	
	Set a wooden post, 2 ins. sq., 2½ ft. long., 15 ins. in the ground, mkd. NWNW 1/64 on W. face.
17.212	The WW 1/64 sec. cor. of secs. 5 and 32, on the N. bdy. of Tp.
	From the CNNW 1/64 sec. cor. of sec. 5.
	N. 89° 51' W., on the E. and W. center line of the NW¼ NW¼ of sec. 5.
9.996	The NWNW 1/64 sec. cor. of sec. 5.
19.992	The NN 1/64 sec. cor. of secs. 5 and 6.
	Dependent Resurvey of a portion of the Boundaries of Section 27, T. 3 N., R. 5 E.
	Reestablishment of the Surveys Executed by Sidney E. Blout, Surveyor, in 1914, and Robert A. Farmer, Topographer, of the Indian Service, in 1911.
	From the cor. of secs. 26, 27, 34 and 35, which is monumented by an iron post, 1 in. diam., projecting 16 ins. above ground, surrounded by a mound of stone, with brass cap mkd. as described in the official record.
	N. 0° 01' E., bet. secs. 26 and 27.
	Over rolling land, through scattering timber.
5.05	Wash, 10 lks. wide, course SW.
10.002	Point for the SS 1/64 sec. cor. of secs. 26 and 27.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. SS 1/64 on W. face.
10.20	Wash, 10 lks. wide, course SW.
20.004	Point for the S 1/16 sec. cor. of secs. 26 and 27.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. S 1/16 S27   S26 1950
20.10	Wash, 10 lks. wide, course SW.
22.10	Wash, 15 lks. wide, course SW.
25.70	Unimproved road, bears NE. and SW.
28.45	Power line maintenance road, under construction, bears NW. and SE.
30.007	Point for the NS 1/64 sec. cor. of secs. 26 and 27.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. S 1/64 on W. face.
40.01	The ¼ sec. cor. of secs. 26 and 27, which is monumented by an iron post, 1 in. diam., projecting 16 ins. above ground, surrounded by a mound of stone, with brass cap marked as described in the official record.

Dependent Resurvey of a Portion of the Boundaries of Section 27,  
T. 3 N., R. 5 E.

Chains.

N. 0° 02' E., beginning new measurement.

9.995 Point for the  $\frac{1}{64}$  sec. cor. of secs. 26 and 27.

Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. N 1/64 on W. face.

19.99 Point for the N 1/16 sec. cor. of secs. 26 and 27.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

N 1/16

S27 | S26

1950

28.00 Wash, 20 lks. wide, course WSW.

29.985 Point for the NN 1/64 sec. cor. of secs. 26 and 27.

Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. NN 1/64 on W. face.

39.98 The cor. of secs. 22, 23, 26 and 27, which is monumented by an iron post, 3 ft. long, 2 ins. diam., buried 12 ins. below the surface of a graded County road, with brass cap marked as described in the official record.

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears S. 45° E., 70.7 lks. dist., with brass cap mkd. T3N R5E S26 RM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears N. 45° W., 70.7 lks. dist., with brass cap mkd. T3N R5E S22 RM 1950 and an arrow pointing to the true cor.

Land, rolling.

Soil, sandy and gravelly.

Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.

N. 89° 52' W., bet. secs. 22 and 27.

Along the center line of Shea Boulevard, a graded County road, bearing E. and W.

40.03 The ¼ sec. cor. of secs. 22 and 27, which is monumented by an iron post, 3 ft. long, 1 in. diam., buried 12 ins. below the surface of road, with brass cap marked as described in the official record.

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears N. 45° W., 70.7 lks. dist., with brass cap mkd. ¼ S22 RM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears S. 45° E., 70.7 lks. dist., with brass cap mkd. ¼ S27 RM 1950 and an arrow pointing to the true cor.

Continue along Shea Boulevard.

Dependent Resurvey of a Portion of the Boundaries of Section 27,  
T. 3 N., R. 5 E.

Chains.  
80.02

The cor. of secs. 21, 22, 27 and 28, which is monumented by an iron post, 3 ft. long, 2 ins. diam., buried 12 ins. below the surface of road, with brass cap marked as described in the official record.

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears N. 45° E., 70.7 lks. dist., with brass cap mkd. T3N R5E S22 RM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears S. 45° W., 70.7 lks. dist., with brass cap mkd. T3N R5E S28 RM 1950 and an arrow pointing to the true cor.

Land, rolling.

Soil, sandy loam, and gravelly.

Timber, none; undergrowth, none.

---

From the cor. of secs. 26, 27, 34 and 35.

N. 89° 26' W., bet. secs. 27 and 34, along the N. Bdy. of the Salt River Indian Reservation.

Over rolling land, through scattering timber. Reservation fence is 50 lks. S. of line.

9.975 Point for the EE 1/64 sec. cor. of secs. 27 and 34.

Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. EE 1/64 on N. face.

10.05 Wash, 10 lks. wide, course SW.

13.40 Unimproved road, bears NE. and SW.

19.95 The E 1/16 sec. cor. of secs. 27 and 34, which is monumented by an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

1/16 S27

SRIR

S34

1911

---

S. 89° 54' W., beginning new measurement.

7.50 Wash, 10 lks. wide, course SW.

10.035 Point for the WE 1/64 sec. cor. of secs. 27 and 34.

Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. E 1/64 on N. face.

14.05 Wash, 10 lks. wide, course SW.

20.07 The ¼ sec. cor. of secs. 27 and 34, which is monumented by an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, marked and witnessed as described in the official record.

---

N. 89° 57' W., beginning new measurement.

20.00 The W 1/16 sec. cor. of secs. 27 and 34, which is monumented by an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Boundaries of Section 27,  
T. 3 N., R. 5 E.

Chains.	
	1/16 S27 S1R S34 1911
	<hr/> S. 89° 58' W., beginning new measurement.
10.004	Point for the WW 1/64 sec. cor. of secs. 27 and 34. Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. WW 1/64 on N. face.
20.008	The cor. of secs. 27, 28, 33 and 34, which is monumented by an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, marked and witnessed as described in the official record.  Land, rolling. Soil, gravelly. Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.
	<hr/> N. 0° 02' W., bet. secs. 27 and 28.  Over rolling land, through scattering timber.
0.50	Unimproved road, bears NE. and SW.
10.002	Point for the SS 1/64 sec. cor. of secs. 27 and 28, which is identical with the position of a local survey cor., marked by a steel rod, ¾ in. diam., set 6 ins. above ground. Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. SS 1/64 on W. face. Bury the steel rod alongside the wooden post.
20.005	Point for the S 1/16 sec. cor. of secs. 27 and 28, which is identical with the position of a local survey cor., marked by a steel rod, ¾ in. diam., set 6 ins. above ground. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	S 1/16 S28   S27 1950
	Bury the steel rod alongside the iron post.
30.007	Point for the NS 1/64 sec. cor. of secs. 27 and 28, which is identical with the position of a local survey cor., marked by a steel rod, ¾ in. diam., set 6 ins. above ground. Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. S 1/64 on W. face. Bury the steel rod alongside the wooden post.
40.01	The ¼ sec. cor. of secs. 27 and 28, which is monumented by an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, marked and witnessed as described in the official record.  Land, rolling. Soil, sandy loam, and gravelly. Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.

## Subdivision of Section 27, T. 3 N., R. 5 E.

Chains.	
	From the $\frac{1}{4}$ sec. cor. of secs. 27 and 34. N. $0^{\circ} 04'$ W., on the N. and S. center line of sec. 27.
9.98	Point for the CSS $1/64$ sec. cor. of sec. 27. Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CSS $1/64$ on W. face.
18.70	Wash, 10 lks. wide, course SW.
19.96	Point for the CS $1/16$ sec. cor. of sec. 27. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} C \\ S\ 1/16\   \ S27 \\ C \\ 1950 \end{array}$
27.90	Unimproved road, bears NE. and SW.
29.94	Point for the CSS $1/64$ sec. cor. of sec. 27. Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CS $1/64$ on W. face.
39.92	Point for the C $\frac{1}{4}$ sec. cor. of sec. 27, at the intersection with the E. and W. center line. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} C\ \frac{1}{4}\ S27 \\ 1950 \end{array}$
56.30	Wash, 20 lks. wide, course SW.
79.91	The $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	From the $\frac{1}{4}$ sec. cor. of secs. 26 and 27. N. $89^{\circ} 53'$ W., on the E. and W. center line of sec. 27.
8.80	Power line maintenance road, bears NW. and SE.
10.004	Point for the CEE $1/64$ sec. cor. of sec. 27. Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CEE $1/64$ on N. face.
12.50	Wash, 10 lks. wide, course SW.
17.00	Wash, 15 lks. wide, course SW.
20.007	Point for the CE $1/16$ sec. cor. of sec. 27. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} C\ \frac{E\ 1/16\ C \\ S27 \\ 1950 \end{array}$
30.011	Point for the CEE $1/64$ sec. cor. of sec. 27.

Subdivision of Section 27, T. 3 N., R. 5 E.

Chains.	<p>Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CE 1/64 on N. face.</p> <p>35.50 Wash, 20 lks. wide, course SW.</p> <p>40.014 The C ¼ sec. cor. of sec. 27.</p> <p>60.019 Point for the CW 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C <math>\frac{W 1/16}{S27}</math> C</p> <p style="text-align: center;">1950</p> <p>70.021 Point for the CWW 1/64 sec. cor. of sec. 27.</p> <p>Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CWW 1/64 on N. face.</p> <p>80.023 The ¼ sec. cor. of secs. 27 and 28.</p>
Subdivision of the SE¼.	
	<p>From the E 1/16 sec. cor. of secs. 27 and 34.</p> <p>N. 0° 08' W., on the N. and S. center line of the SE¼ of sec. 27.</p> <p>9.935 Point for the CSSE 1/64 sec. cor. of sec. 27.</p> <p>Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CSSE 1/64 on W. face.</p> <p>19.871 Point for the SE 1/16 sec. cor. of sec. 27, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S27</p> <p style="text-align: center;">1950</p> <p>29.86 Point for the CNSE 1/64 sec. cor. of sec. 27.</p> <p>Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CNSE 1/64 on W. face.</p> <p>39.849 The CE 1/16 sec. cor. of sec. 27.</p>
	<p>From the S 1/16 sec. cor. of secs. 26 and 27.</p> <p>N. 89° 54' W., on the E. and W. center line of the SE¼ of sec. 27.</p> <p>2.20 Wash, 10 lks. wide, course SSW.</p> <p>9.992 Point for the CESE 1/64 sec. cor. of sec. 27.</p> <p>Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CESE 1/64 on N. face.</p> <p>19.984 The SE 1/16 sec. cor. of sec. 27.</p>

## Subdivision of Section 27, T. 3 N., R. 5 E.

100574885

Chains. 30.008	Point for the CWSE $1/64$ sec. cor. of sec. 27.  Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. CWSE $1/64$ on N. face.
40.032	The CS $1/16$ sec. cor. of sec. 27.
Subdivision of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ .	
	From the CESE $1/64$ sec. cor. of sec. 27.  N. $0^{\circ} 04'$ W., on the N. and S. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 27.
9.994	Point for the NESE $1/64$ sec. cor. of sec. 27, at the intersection with the E. and W. center line.  Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. NESE $1/64$ on W. face.
19.997	The CEE $1/64$ sec. cor. of sec. 27.
	From the NS $1/64$ sec. cor. of secs. 26 and 27.  N. $89^{\circ} 53'$ W., on the E. and W. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 27.
1.60	Power line maintenance road, bears NW. and SE.
9.993	The NESE $1/64$ sec. cor. of sec. 27.
19.989	The CNSE $1/64$ sec. cor. of sec. 27.
Subdivision of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ .	
	From the EE $1/64$ sec. cor. of secs. 27 and 34.  N. $0^{\circ} 04'$ W., on the N. and S. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 27.
9.967	Point for the SESE $1/64$ sec. cor. of sec. 27, at the intersection with the E. and W. center line.  Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. SESE $1/64$ on W. face.
19.932	The CESE $1/64$ sec. cor. of secs. 22 and 27.
	From the SS $1/64$ sec. cor. of secs. 26 and 27.  N. $89^{\circ} 42'$ W., on the E. and W. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 27.
9.982	The SESE $1/64$ sec. cor. of sec. 27.
19.969	The CSSE $1/64$ sec. cor. of sec. 27.
Subdivision of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ .	
	From the WE $1/64$ sec. cor. of secs. 27 and 34.  N. $0^{\circ} 06'$ W., on the N. and S. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 27.
9.963	Point for the SWSE $1/64$ sec. cor. of sec. 27, at the intersection with the E. and W. center line.

Subdivision of Section 27, T. 3 N., R. 5 E.

Chains.	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. SWSE 1/64 on W. face.
19.918	The CWSE 1/64 sec. cor. of sec. 27.
	From the CSSE 1/64 sec. cor. of sec. 27.
	West, on the E. and W. center line of the SW¼ SE¼ of sec. 27.
10.03	The SWSE 1/64 sec. cor. of sec. 27.
20.06	The CSS 1/64 sec. cor. of sec. 27.
	Subdivision of the NW¼ SE¼.
	From the CWSE 1/64 sec. cor. of sec. 27.
	N. 0° 06' W., on the N. and S. center line of the NW¼ SE¼ of sec. 27.
9.982	Point for the NWSE 1/64 sec. cor. of sec. 27, at the intersection with the E. and W. center line.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. NWSE 1/64 on W. face.
19.966	The CWE 1/64 sec. cor. of sec. 27.
	From the CNSE 1/64 sec. cor. of sec. 27.
	N. 89° 53' W., on the E. and W. center line of the NW¼ SE¼ of sec. 27.
10.012	The NWSE 1/64 sec. cor. of sec. 27.
20.026	The CNS 1/64 sec. cor. of sec. 27.
	Subdivision of the SW¼.
	From the W 1/16 sec. cor. of secs. 27 and 34.
	N. 0° 03' W., on the N. and S. center line of the SW¼ of sec. 27.
9.981	Point for the CSSW 1/64 sec. cor. of sec. 27.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CSSW 1/64 on W. face.
19.962	Point for the SW 1/16 sec. cor. of sec. 27, at the intersection with the E. and W. center line.
	Set an iron post, 3 ft. long, 1 in. diam., 13 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.
	SW 1/16 S27
	1950
29.955	Point for the CNSW 1/64 sec. cor. of sec. 27.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CNSW 1/64 on W. face.
39.948	The CW 1/16 sec. cor. of sec. 27.



## Subdivision of Section 27, T. 3 N., R. 5 E.

## Chains.

From the CS 1/16 sec. cor. of sec. 27.  
N. 89° 54' W., on the E. and W. center line of the SW $\frac{1}{4}$  of sec. 27.

19.992 The SW 1/16 sec. cor. of sec. 27.

29.996 Point for the CWSW 1/64 sec. cor. of sec. 27.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. CWSW 1/64 on N. face.

40.00 The S 1/16 sec. cor. of secs. 27 and 28.

Subdivision of the SW $\frac{1}{4}$  SW $\frac{1}{4}$ .

From the WW 1/64 sec. cor. of secs. 27 and 34.

N. 0° 02' W., on the N. and S. center line of the SW $\frac{1}{4}$  SW $\frac{1}{4}$  of sec. 27.

9.991 Point for the SWSW 1/64 sec. cor. of sec. 27, at the intersection with the E. and W. center line.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. SWSW 1/64 on W. face.

19.985 The CWSW 1/64 sec. cor. of sec. 27.

From the CSSW 1/64 sec. cor. of sec. 27.

N. 89° 57' W., on the E. and W. center line of the SW $\frac{1}{4}$  SW $\frac{1}{4}$  of sec. 27.

10.001 The SWSW 1/64 sec. cor. of sec. 27.

20.003 The SS 1/64 sec. cor. of secs. 27 and 28.

Subdivision of the NW $\frac{1}{4}$  SW $\frac{1}{4}$ .

From the CWSW 1/64 sec. cor. of sec. 27.

N. 0° 02' W., on the N. and S. center line of the NW $\frac{1}{4}$  SW $\frac{1}{4}$  of sec. 27.

9.998 Point for the NWSW 1/64 sec. cor. of sec. 27, at the intersection with the E. and W. center line.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. NWSW 1/64 on W. face.

19.998 The CWW 1/64 sec. cor. of sec. 27.

From the CNSW 1/64 sec. cor. of sec. 27.

N. 89° 53' W., on the E. and W. center line of the NW $\frac{1}{4}$  SW $\frac{1}{4}$  of sec. 27.

10.004 The NWSW 1/64 sec. cor. of sec. 27.

20.008 The S 1/64 sec. cor. of secs. 27 and 28.

Dependent Resurvey of a Portion of the Boundaries of Section 26,  
T. 3 N., R. 5 E.

Reestablishment of the Survey Executed by Sidney E. Blout,  
Surveyor, in 1914.

Dependent Resurvey of a Portion of the Boundaries of Section 26,  
T. 3 N., R. 5 E.

Chains.

From the  $\frac{1}{4}$  sec. cor. of secs. 25 and 26, which is monumented by an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, marked and witnessed as described in the official record.

N. 0° 01' W., bet. secs. 25 and 26.

Over rolling land, through scattering timber.

5.15 Wash, 10 lks. wide, banks 5 ft. high, course SW.

10.00 Point for the  $\frac{1}{64}$  sec. cor. of secs. 25 and 26.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. N  $\frac{1}{64}$  on W. face.

13.70 Wash, 20 lks. wide, banks 4 ft. high, course SW.

20.00 Point for the N  $\frac{1}{16}$  sec. cor. of secs. 25 and 26.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

N  $\frac{1}{16}$

S26 S25

1950

20.75 Wash, 20 lks. wide, banks 5 ft. high, course SW.

23.50 Wash, 20 lks. wide, banks 4 ft. high, course SW.

30.00 Point for the NN  $\frac{1}{64}$  sec. cor. of secs. 25 and 26.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. NN  $\frac{1}{64}$  on W. face.

40.00 The cor. of secs. 23, 24, 25 and 26.

Land, rolling.

Soil, sandy loam, and gravelly.

Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.

Subdivision of Section 26, T. 3 N., R. 5 E.

From the  $\frac{1}{4}$  sec. cor. of secs. 25 and 26.

N. 89° 57' W., on the E. and W. center line of sec. 27.

7.65 Wash, 10 lks. wide, banks 5 ft. high, course SW.

9.99 Point for the CEE  $\frac{1}{64}$  sec. cor. of sec. 26.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. CEE  $\frac{1}{64}$  on N. face.

19.98 Point for the CE  $\frac{1}{16}$  sec. cor. of sec. 26.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

C  $\frac{E 1/16}{S26}$  C

1950

25.30 Wash, 20 lks. wide, banks 5 ft. high, course SW.

Subdivision of Section 26, T. 3 N., R. 5 E.

Chains.	
27.55	Wash, 20 lks. wide, banks 4 ft. high, course SW.
29.97	Point for the $CNE \frac{1}{64}$ sec. cor. of sec. 26. Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. $CNE \frac{1}{64}$ on N. face.
32.40	Wash, 15 lks. wide, course SW.
39.96	Point for the $C \frac{1}{4}$ sec. cor. of sec. 26, at the intersection with the N. and S. center line. Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd. $C \frac{1}{4} S26$ 1950 From this cor., the $\frac{1}{4}$ sec. cor. of secs. 26 and 35 bears S: $0^{\circ}01'W$ ., 39.94 chs. dist., and is monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, surrounded by a mound of stone, with brass cap marked as described in the official record.
49.955	Point for the $CNW \frac{1}{64}$ sec. cor. of sec. 26. Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. $CW \frac{1}{64}$ on N. face.
58.60	Wash, 20 lks. wide, banks 4 ft. high, course SW.
59.95	Point for the $CW \frac{1}{16}$ sec. cor. of sec. 26. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $C \frac{W \frac{1}{16}}{S26} C$ 1950
66.25	Wash, 15 lks. wide, course SW.
69.945	Point for the $CWW \frac{1}{64}$ sec. cor. of sec. 26. Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. $CWW \frac{1}{64}$ on N. face.
79.94	The $\frac{1}{4}$ sec. cor. of secs. 26 and 27. From the $C \frac{1}{4}$ sec. cor. of sec. 26. N. $0^{\circ} 01' E$ ., on the N. and S. center line of sec. 26.
10.003	Point for the $CWN \frac{1}{64}$ sec. cor. of sec. 26. Set a wooden post, 2 ins. sq., $2\frac{1}{2}$ ft. long, 15 ins. in the ground, mkd. $CN \frac{1}{64}$ on W. face.
16.40	Wash, 20 lks. wide, course SW.
20.005	Point for the $CN \frac{1}{16}$ sec. cor. of sec. 26. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $C$ $N \frac{1}{16}   S26$ $C$ 1950

Subdivision of Section 26, T. 3 N., R. 5 E.

Chains. 30.008	Point for the CNN 1/64 sec. cor. of sec. 26.  Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. CNN 1/64 on W. face.
33.00	Wash, 20 lks. wide, course SW.
36.70	Unimproved road, bears NE. and SW.
40.01	The 1/4 sec. cor. of secs. 23 and 26.

Subdivision of the NE 1/4.

	From the CE 1/16 sec. cor. of sec. 26.  N. 0° 01' E., on the N. and S. center line of the NE 1/4 of sec. 26.
1.80	Wash, 20 lks. wide, course SW.
10.002	Point for the CSNE 1/64 sec. cor. of sec. 26.  Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. CSNE 1/64 on W. face.
20.005	Point for the NE 1/16 sec. cor. of sec. 26, at the intersection with the E. and W. center line.  Set an iron post, 3 ft. long, 1 in. diam., 1 1/4 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.
	NE 1/16 S26  1950
30.007	Point for the CNNE 1/64 sec. cor. of sec. 26.  Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. CNNE 1/64 on W. face.
39.20	Wash, 20 lks. wide, course SW.
40.01	The E 1/16 sec. cor. of secs. 23 and 26.

	From the N 1/16 sec. cor. of secs. 25 and 26.  N. 89° 58' W., on the E. and W. center line of the NE 1/4 of sec. 26.
3.80	Wash, 20 lks. wide, course SW.
9.991	Point for the CENE 1/64 sec. cor. of sec. 26.  Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. CENE 1/64 on N. face.
19.983	The NE 1/16 sec. cor. of sec. 26.
20.00	Wash, 10 lks. wide, course SW.
29.971	Point for the CWNE 1/64 sec. cor. of sec. 26.  Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. CWNE 1/64 on N. face.
39.958	The CN 1/16 sec. cor. of sec. 26.

## Subdivision of Section 26, T. 3 N., R. 5 E.

## Chains.

Subdivision of the NE $\frac{1}{4}$  NE $\frac{1}{4}$ .

From the CENE 1/64 sec. cor. of sec. 26.

North, on the N. and S. center line of the NE $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 26.

7.75 Wash, 15 lks. wide, course SW.

10.004 Point for the NENE 1/64 sec. cor. of sec. 26, at the intersection with the E. and W. center line.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. NENE 1/64 on W. face.

20.007 The EE 1/64 sec. cor. of secs. 23 and 26.

From the NN 1/64 sec. cor. of secs. 25 and 26.

N. 89° 58' W., on the E. and W. center line of the NE $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 26.

6.70 Wash, 15 lks. wide, course SW.

9.984 The NENE 1/64 sec. cor. of sec. 26.

19.97 The CNNE 1/64 sec. cor. of sec. 26.

Subdivision of the SE $\frac{1}{4}$  NE $\frac{1}{4}$ .

From the CEE 1/64 sec. cor. of sec. 26.

North, on the N. and S. center line of the SE $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 26.

10.003 Point for the SENE 1/64 sec. cor. of sec. 26, at the intersection with the E. and W. center line.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. SENE 1/64 on W. face.

10.25 Wash, 15 lks. wide, course SW.

13.70 Wash, 20 lks. wide, course SW.

20.005 The CENE 1/64 sec. cor. of sec. 26.

From the N 1/64 sec. cor. of secs. 25 and 26.

N. 89° 57' W., on the E. and W. center line of the SE $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 26.

9.996 The SENE 1/64 sec. cor. of sec. 26.

11.35 Wash, 15 lks. wide, course SW.

19.992 The CSNE 1/64 sec. cor. of sec. 26.

Subdivision of the SW $\frac{1}{4}$  NE $\frac{1}{4}$ .

From the CWE 1/64 sec. cor. of sec. 26.

N. 0° 01' E., on the N. and S. center line of the SW $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 26. Dry wash, drains SW.

3.90  
10.00 Point for the SWNE 1/64 sec. cor. of sec. 26, at the intersection with the E. and W. center line.

Subdivision of Section 26, T. 3 N., R. 5 E.

Chains.	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. SWNE 1/64 on W. face.
19.996	The CWNE 1/64 sec. cor. of sec. 26.
	From the CSNE 1/64 sec. cor. of sec. 26.
	N. 89° 58' W. on the E. and W. center line of the SW¼ NE¼ of sec. 26.
7.45	Wash, 15 lks. wide, course SW.
9.99	The SWNE 1/64 sec. cor. of sec. 26.
19.98	The CSN 1/64 sec. cor. of sec. 26.
	Subdivision of the NW¼ NE¼ of sec. 26.
	From the CWNE 1/64 sec. cor. of sec. 26.
	N. 0° 01' E., on the N. and S. center line of the NW¼ NE¼ of sec. 26.
10.002	Point for the NWNE 1/64 sec. cor. of sec. 26, at the intersection with the E. and W. center line.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. NWNE 1/64 on W. face.
20.006	The WE 1/64 sec. cor. of secs. 23 and 26.
	From the CNNE 1/64 sec. cor. of sec. 26.
	N. 89° 58' W., on the E. and W. center line of the NW¼ NE¼ of sec. 26.
9.988	The NWNE 1/64 sec. cor. of sec. 26.
19.98	The CNN 1/64 sec. cor. of sec. 26.
	Subdivision of the NW¼.
	From the CW 1/16 sec. cor. of sec. 26.
	N. 0° 02' E., on the N. and S. center line of the NW¼ of sec. 26.
9.998	Point for the CSNW 1/64 sec. cor. of sec. 26.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CSNW 1/64 on W. face.
19.50	Unimproved road, bears NE. and SW.
19.996	Point for the NW 1/16 sec. cor. of sec. 26, at the intersection with the E. and W. center line.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	NW 1/16 S26
	1950
27.40	Wash, 20 lks. wide, course SW.
29.995	Point for the CNNW 1/64 sec. cor. of sec. 26.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CNNW 1/64 on W. face.
39.994	The W 1/16 sec. cor. of secs. 23 and 26.

## Subdivision of Section 26, T. 3 N., R. 5 E.

## Chains.

- From the CN 1/16 sec. cor. of sec. 26.  
N. 89° 59' W., on the E. and W. center line of the NW $\frac{1}{4}$  of sec. 26.
- 9.992 Point for the CENW 1/64 sec. cor. of sec. 26.  
Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. CENW 1/64 on W. face.
- 14.50 Unimproved road, bears NE. and SW.
- 19.985 The NW 1/16 sec. cor. of sec. 26.
- 29.975 Point for the CWNW 1/64 sec. cor. of sec. 26.  
Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. CWNW 1/64 on N. face.
- 39.965 The N 1/16 sec. cor. of secs. 26 and 27.
- 
- Subdivision of the NE $\frac{1}{4}$  NW $\frac{1}{4}$ .
- 
- From the CENW 1/64 sec. cor. of sec. 26.  
N. 0° 01' E., on the N. and S. center line of the NE $\frac{1}{4}$  NW $\frac{1}{4}$  of sec. 26.
- 8.70 Wash, 20 lks. wide, course SW.
- 9.994 Point for the NENW 1/64 sec. cor. of sec. 26, at the intersection with the E. and W. center line.  
Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. NENW 1/64 on W. face.
- 20.002 The EW 1/64 sec. cor. of secs. 23 and 26.
- 
- From the CNN 1/64 sec. cor. of sec. 26.  
West, on the E. and W. center line of the NE $\frac{1}{4}$  NW $\frac{1}{4}$  of sec. 26.
- 9.994 The NENW 1/64 sec. cor. of sec. 26.
- 19.982 The CNNW 1/64 sec. cor. of sec. 26.
- 
- Subdivision of the SE $\frac{1}{4}$  NW $\frac{1}{4}$ .
- 
- From the CW 1/64 sec. cor. of sec. 26.  
N. 0° 01' E., on the N. and S. center line of the SE $\frac{1}{4}$  NW $\frac{1}{4}$  of sec. 26.
- 9.996 Point for the SENW 1/64 sec. cor. of sec. 26, at the intersection with the E. and W. center line.  
Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. SENW 1/64 on W. face.
- 19.994 The CENW 1/64 sec. cor. of sec. 26.

Subdivision of Section 26, T. 3 N., R. 5 E.

Chains. From the CSW 1/64 sec. cor. of sec. 26.  
N. 89° 58' W., on the E. and W. center line of the SE 1/4 NW 1/4 of sec. 26.  
9.995 The SENW 1/64 sec. cor. of sec. 26.  
19.987 The CSNW 1/64 sec. cor. of sec. 26.

Subdivision of the SW 1/4 NW 1/4.

From the CWW 1/64 sec. cor. of sec. 26.  
N. 0° 02' E. on the N. and S. center line of the SW 1/4 NW 1/4 of sec. 26.  
5.750 Unimproved road, bears NE. and SW.  
9.995 Point for the SWNW 1/64 sec. cor. of sec. 26, at the intersection with the E. and W. center line.  
Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. SWNW 1/64 on W. face.  
19.991 The CWNW 1/64 sec. cor. of sec. 26.

From the CSSW 1/64 sec. cor. of sec. 26.  
N. 89° 58' W., on the E. and W. center line of the SW 1/4 NW 1/4 of sec. 26.  
5.40 Unimproved road, bears NE. and SW.  
9.993 The SWNW 1/64 sec. cor. of sec. 26.  
19.985 The SW 1/64 sec. cor. of secs. 26 and 27.

Subdivision of the NW 1/4 NW 1/4.

From the CWNW 1/64 sec. cor. of sec. 26.  
N. 0° 02' E., on the N. and S. center line of the NW 1/4 NW 1/4 of sec. 26.  
8.55 Wash, 20 lks. wide, course SW.  
9.991 Point for the NWNW 1/64 sec. cor. of sec. 26, at the intersection with the E. and W. center line.  
Set a wooden post, 2 ins. sq., 2 1/2 ft. long, 15 ins. in the ground, mkd. NWNW 1/64 on W. face.  
19.993 The WW 1/64 sec. cor. of secs. 23 and 26.

From the CNNW 1/64 sec. cor. of sec. 26.  
West, on the E. and W. center line of the NW 1/4 NW 1/4 of sec. 26.  
Along wash, 20 lks. wide, general course W. Cross and recross wash.  
9.988 The NWNW 1/64 sec. cor. of sec. 26.  
19.978 The NN 1/64 sec. cor. of secs. 26 and 27.



## Dependent Resurvey of the Boundaries of Section 11, T. 3 N., R. 3 E.

## Chains.

Reestablishment of the survey executed by J. H. Martineau in 1894.

The cor. of secs. 11, 12, 13 and 14 is marked by an iron pipe, 1 in. diam., 12 ins. long, buried 12 ins. below the surface of graded road, at the intersection of the center line of a graded County road bearing N. and S., with long established property lines extending E. and W.

At the corner point

Bury a granite stone 10x8x8 ins., 12 ins. in the ground, mkd. X.

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears N.  $45^{\circ}$  W., 70.7 lks. dist., with brass cap mkd. T3N R3E S11 RM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears S.  $45^{\circ}$  E., 70.7 lks. dist., with brass cap mkd. T3N R3E S13 RM 1950 and an arrow pointing to the true cor.

N.  $0^{\circ} 15'$  W., bet. secs. 11 and 12.

Along the center line of a graded County road.

10.185 Point for the SS  $1/64$  sec. cor. of secs. 11 and 12.

Bury a conglomerate stone 10x8x5 ins., 12 ins. in the ground, mkd. X.

from which

A pine stake, 2 ins. sq., 12 ins. long, set 8 ins. in the ground, bears S.  $89^{\circ} 12'$  W., 50 lks. dist.

20.37 Point for the S  $1/16$  sec. cor. of secs. 11 and 12.

Bury a conglomerate stone 8x8x6 ins., 12 ins. in the ground, mkd. X.

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears N.  $45^{\circ}$  W., 70.7 lks. dist., with brass cap mkd. S  $1/16$  S11 RM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears S.  $45^{\circ}$  W., 70.7 lks. dist., with brass cap mkd. S  $1/16$  S12 RM 1950 and an arrow pointing to the true cor.

30.555 Point for the NS.  $1/64$  sec. cor. of secs. 11 and 12.

Bury a quartzite stone 10x8x8 ins., 12 ins. in the ground, mkd. X.

from which

A pine stake, 2 ins. sq., 12 ins. long, set 8 ins. in the ground, bears S.  $89^{\circ} 05'$  W., 50 lks. dist.

40.74 The  $\frac{1}{4}$  sec. cor. of secs. 11 and 12, which is marked by a malpais stone 12x10x8 ins., buried 12 ins. in the ground, mkd.  $\frac{1}{4}$  on W. and X on top faces.

from which

Dependent Resurvey of the Boundaries of Section 11, T. 3 N., R. 3 E.

Chains.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears N. 45° W., 70.7 lks. dist., with brass cap mkd. 1/4 S11 EM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears S. 45° E., 70.7 lks. dist., with brass cap mkd. 1/4 S12 EM 1950 and an arrow pointing to the true cor.

Continue along the center line of a graded County road.

81.48

The cor. of secs. 1, 2, 11 and 12, which is marked by an iron pipe, 2 ins. diam., 18 ins. long, buried 14 ins. below the surface of graded road, at the intersection of the center lines of graded County roads extending N., S., E. and W.

At the corner point

Bury a sandstone 10x8x8 ins., 14 ins. in the ground, mkd. X.

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears N. 45° E., 70.7 lks. dist., with brass cap mkd. T3N R3E S1 EM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears S. 45° W., 70.7 lks. dist., with brass cap mkd. T3N R3E S11 EM 1950 and an arrow pointing to the true cor.

Land, level.

Soil, sandy and gravelly.

Timber, none; undergrowth, none.

S. 89° 59' W., bet. secs. 2 and 11.

Along the center line of a graded County road.

40.17

The 1/4 sec. cor. of secs. 2 and 11, which is marked by a quartzite stone, 12x8x6 ins., buried 12 ins. below the surface of road, mkd. 1/4 on N. and X on top faces.

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears N. 45° E., 70.7 lks. dist., with brass cap mkd. 1/4 S2 EM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears S. 45° W., 70.7 lks. dist., with brass cap mkd. 1/4 S11 EM 1950 and an arrow pointing to the true cor.

S. 89° 38' W., beginning new measurement.

Along the center line of a graded County road.

39.97

The cor. of secs. 2, 3, 10 and 11, which is perpetuated with an iron pipe, 1 in diam., buried 12 ins. below the surface of an oil surfaced highway, protected by an iron covered cylinder, at the intersection of the center lines of a graded County road from the E. and the center line of oil surfaced highway extending N. and S.

from which

## Dependent Resurvey of the Boundaries of Section 11, T. 3 N., R. 3 E.

## Chains.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears N. 45° W., 70.7 lks. dist., with brass cap mkd. T3N R3E S3 RM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears S. 45° E., 70.7 lks. dist., with brass cap mkd. T3N R3E S11 RM 1950 and an arrow pointing to the true cor.

Land, level.

Soil, gravelly clay loam.

Timber, none; undergrowth, none.

From the cor. of secs. 11, 12, 13 and 14.

S. 89° 16' W., bet. secs. 11 and 14.

Over rolling land, through scattering timber.

10.023 Point for the EE 1/64 sec. cor. of secs. 11 and 14.

Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. EE 1/64 on N. face.

20.046 Point for the E 1/16 sec. cor. of secs. 11 and 14.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

E 1/16  $\frac{S11}{S14}$   
1950

40.092 The ¼ sec. cor. of secs. 11 and 14, which is marked with a granite stone 12x8x6 ins., firmly set, mkd. ¼ on N. face.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.

¼  $\frac{S11}{S14}$   
1950

Bury the original corner stone alongside the iron post.

S. 89° 22' W., beginning new measurement.

Over mountainous land, through scattering timber; asc. 74 ft. over SE. slope.

15.00 Top of ascent; desc. gradually.

20.25 Wash, 10 lks. wide, course SE.; asc. 175 ft. over SE. slope.

28.25 Spur, slopes S. Along broken S. slope; desc. 79 ft.

31.60 Ravine, near head.

35.25 Spur, slopes SW.; desc. 94 ft. over W. slope.

40.04 The cor. of secs. 10, 11, 14 and 15, which is marked by a granite stone 20x8x6 ins., firmly set, mkd. with 4 notches on S. edge.

at the corner point

Dependent Resurvey of the Boundaries of Section 11, T. 3 N., R. 3 E.

Chains.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T3N	R3E
S10	S11
S15	S14

1950

raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. and bury the original corner stone alongside the iron post.

Land, ½ mi. rolling, ½ mi. mountainous.

Soil, gravelly and rocky.

Timber, scattering paloverde and ironwood; undergrowth, greasewood and cacti.

N. 0° 17' W., bet. secs. 10 and 11.

Over mountainous land, through scattering timber; asc. 176 ft. over broken S. slope.

8.60 Spur, slopes W.; desc. 186 ft. over N. slope.

18.90 Wash, 10 lks. wide, course W.; asc. 69 ft. over S. slope.

24.90 Spur, slopes W.; desc. 177 ft. over NW. slope.

40.29 The ¼ sec. cor. of secs. 10 and 11, which is marked by a granite stone 14x10x5 ins., firmly set, mkd. ¼ on W. face.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.

	¼
S10	S11
	1950

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears N. 45° E., 70.7 lks. dist., with brass cap mkd. ¼ S11 RM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground for a reference monument, bears S. 45° E., 70.7 lks. dist., with brass cap mkd. ¼ S11 RM 1950 and an arrow pointing to the true cor.

Bury the original cor. stone alongside the iron post.

N. 0° 13' W., beginning new measurement.

1.80 Enter oil surfaced highway, bearing N. 0° 13' W., from SW. Along center line of highway.

41.88 The cor. of secs. 2, 3, 10 and 11.

Land, mountainous ½ mi.; nearly level ½ mi.

Soil, rocky ½ mi.; sandy and gravelly ½ mi.

Timber, scattering paloverde and ironwood; undergrowth, greasewood and cacti.

## Subdivision of Section 11, T. 3 N., R. 3 E.

4385

## Chains.

From the  $\frac{1}{4}$  sec. cor. of secs. 11 and 14.

N.  $0^{\circ} 19' W.$ , on the N. and S. center line of sec. 11.

8.85 Wash, 10 lks. wide, course SE.

20.27 Point for the CS  $\frac{1}{16}$  sec. cor. of sec. 11.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, to bedrock and in a mound of stone to top, with brass cap mkd.

C

S  $\frac{1}{16}$  S11

C

1950

40.54 Point for the C  $\frac{1}{4}$  sec. cor. of sec. 11, at the intersection of the E. and W. center line, which is identical with the position of a local survey cor., mkd. by an iron pipe, 1 in. diam.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

C  $\frac{1}{4}$  S11

1950

Bury the iron pipe alongside the iron post.

From the C  $\frac{1}{4}$  sec. cor. of sec. 11, the  $\frac{1}{4}$  sec. cor. of secs. 2 and 11 bears N.  $0^{\circ} 19' W.$ , 41.44 chs. dist.

From the same point the  $\frac{1}{4}$  sec. cor. of secs. 10 and 11 bears S.  $89^{\circ} 01' W.$ , 40.04 chs. dist.

From the  $\frac{1}{4}$  sec. cor. of secs. 11 and 12.

S.  $89^{\circ} 01' W.$ , on the E. and W. center line of sec. 11.

10.031 Point for the CEE  $\frac{1}{64}$  sec. cor. of sec. 11.

Set a wooden post, 2 ins. sq.,  $2\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. CEE  $\frac{1}{64}$  on N. face.

20.063 Point for the CE  $\frac{1}{16}$  sec. cor. of sec. 11, which is identical with the position of a local survey cor., mkd. by an iron pipe, 1 in. diam.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

E  $\frac{1}{16}$   
C ——— C  
S11

1950

Bury the iron pipe alongside the iron post.

40.126 The C  $\frac{1}{4}$  sec. cor. of sec. 11.

## Subdivision of Section 11, T. 3 N., R. 3 E.

## Chains.

Subdivision of the SE  $\frac{1}{4}$ .

From the E  $\frac{1}{16}$  sec. cor. of secs. 11 and 14.

N.  $0^{\circ} 17' W.$ , on the N. and S. center line of the SE  $\frac{1}{4}$  of sec. 11.

10.163 Point for the CSSE  $\frac{1}{64}$  sec. cor. of sec. 11.

Set a wooden post, 2 ins. sq.,  $2\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. CSSE  $\frac{1}{64}$  on W. face.

20.326 Point for the SE  $\frac{1}{16}$  sec. cor. of sec. 11, at the intersection of the E. and W. center line.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

SE  $\frac{1}{16}$ -S11

1950

30.492 Point for the CN SE  $\frac{1}{64}$  sec. cor. of sec. 11.

Set a wooden post, 2 ins. sq.,  $2\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. CNSE  $\frac{1}{64}$  on W. face.

40.658 The CE  $\frac{1}{16}$  sec. cor. of sec. 11.

From the S  $\frac{1}{16}$  sec. cor. of secs. 11 and 12.

S.  $89^{\circ} 08' W.$  on the E. and W. center line of the SE  $\frac{1}{4}$  of sec. 11.

10.027 Point for the CSE  $\frac{1}{64}$  sec. cor. of sec. 11.

Set a wooden post, 2 ins. sq.,  $2\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. CSE  $\frac{1}{64}$  on N. face.

20.054 The SE  $\frac{1}{16}$  sec. cor. of sec. 11.

40.103 The CS  $\frac{1}{16}$  sec. cor. of sec. 11.

Subdivision of the NE  $\frac{1}{4}$  SE  $\frac{1}{4}$ .

From the CSE  $\frac{1}{64}$  sec. cor. of sec. 11.

N.  $0^{\circ} 16' W.$ , on the N. and S. center line of the NE  $\frac{1}{4}$  SE  $\frac{1}{4}$  of sec. 11.

10.178 Point for the NESE  $\frac{1}{64}$  sec. cor. of sec. 11, at the intersection of the E. and W. center line.

Set a wooden post, 2 ins. sq.,  $2\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. NESE  $\frac{1}{64}$  on N. face.

20.351 The CEE  $\frac{1}{64}$  sec. cor. of sec. 11.

From the S  $\frac{1}{64}$  sec. cor. of secs. 11 and 12.

S.  $89^{\circ} 05' W.$ , on the E. and W. center line of the NE  $\frac{1}{4}$  SE  $\frac{1}{4}$  of sec. 11.

10.03 The NESE  $\frac{1}{64}$  sec. cor. of sec. 11.

20.061 The CNSE  $\frac{1}{64}$  sec. cor. of sec. 11.

## Subdivision of Section 11, T. 3 N., R. 3 E.

Chains.

Subdivision of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ .

From the EE  $\frac{1}{64}$  sec. cor. of secs. 11 and 14.

N.  $0^{\circ} 16' W.$ , on the N. and S. center line, of the SE $\frac{1}{4}$  SE $\frac{1}{4}$  of sec. 11.

10.172 Point for the SESE  $\frac{1}{64}$  sec. cor. of sec. 11, at the intersection of the E. and W. center line.

Set a wooden post, 2 ins. sq.,  $2\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. SESE  $\frac{1}{64}$  on N. face.

20.352 The CESE  $\frac{1}{64}$  sec. cor. of sec. 11.

From the SS  $\frac{1}{64}$  sec. cor. of secs. 11 and 12.

S.  $89^{\circ} 12' W.$ , on the E. and W. center line of the SE $\frac{1}{4}$  SE $\frac{1}{4}$  of sec. 11.

10.025 The SESE  $\frac{1}{64}$  sec. cor. of sec. 11.

20.051 The CSSE  $\frac{1}{64}$  sec. cor. of sec. 11.

Dependent Resurvey of the North Boundary of Section 12, T. 3 N., R. 4 E.

Reestablishment of the survey executed by R. C. Powers, Deputy Surveyor, in 1892, and the resurvey executed by Sidney E. Blout, Surveyor, in 1914.

From the cor. of secs. 1 and 12, on the E. bdy. of Tp., which is an iron post, 3 ins. diam., mkd. as described in the official record. N.  $89^{\circ} 33' W.$ , bet. secs. 1 and 12.

Over nearly level land, through scattering timber.

9.993 Point for the EE  $\frac{1}{64}$  sec. cor. of secs. 1 and 12.

Set a wooden post, 2 ins. sq.,  $2\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. EE  $\frac{1}{64}$  on N. face.

19.986 Point for the E  $\frac{1}{16}$  sec. cor. of secs. 1 and 12.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S1  
E  $\frac{1}{16}$  ———  
S12

1950

29.979 Point for the WE  $\frac{1}{64}$  sec. cor. of secs. 1 and 12.

Set a wooden post, 2 ins. sq.,  $2\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. E  $\frac{1}{64}$  on N. face.

39.972 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 12, which is monumented with an iron post, 1 in. diam., firmly set, marked and witnessed as described in the official record.

Continue over nearly level land, through scattering timber.

43.50 Wash, 10 lks. wide, course SE.

71.50 Wash, 15 lks. wide, course SE.

Dependent Resurvey of the North Boundary of Section 12, T. 3 N., R. 4 E.

Chains.

79.932 The cor. of secs. 1, 2, 11 and 12, which is monumented with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

Land, nearly level.  
Soil, sandy loam and gravelly.  
Timber, paloverde, ironwood and mesquite; undergrowth, greasewood and cacti.

---

Subdivision of Section 12, T. 3 N., R. 4 E.

---

From the  $\frac{1}{4}$  sec. cor. of sec. 12, on the E. bdy. of Tp.  
N.  $89^{\circ} 35'$  W., on the E. and W. center line of sec. 12.

10.008 Point for the CEE $\frac{1}{64}$  sec. cor. of sec. 12.  
Set a wooden post, 2 ins. sq.,  $2\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. CEE  $\frac{1}{64}$  on N. face.

10.30 Wash, 10 lks. wide, course S.

20.016 Point for the CE  $\frac{1}{64}$  sec. cor. of sec. 12.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

E  $\frac{1}{16}$   
C  $\frac{1}{16}$  S12 C  
1950

30.024 Point for the CNE  $\frac{1}{64}$  sec. cor. of sec. 12.  
Set a wooden post, 2 ins. sq.,  $2\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. CNE  $\frac{1}{64}$  on N. face.

40.032 Point for the C $\frac{1}{4}$  sec. cor. of sec. 12, at the intersection with the N. and S. center line, which is identical with the position of a local survey cor., mkd. by an iron pipe, 1 in. diam.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

C  $\frac{1}{4}$  S12  
1950

Bury the iron pipe alongside the iron post.

---

From the C  $\frac{1}{4}$  sec. cor. of sec. 12, the  $\frac{1}{4}$  sec. cor. of secs. 11 and 12, bears N.  $89^{\circ} 35'$  W., 40.02 chs. dist., and is monumented by an iron post, 1 in. diam., firmly set, marked and witnessed as described in the official record.

From the same point, the  $\frac{1}{4}$  sec. cor. of secs. 12 and 13 bears S.  $0^{\circ} 38'$  W., 40.06 chs. dist., and is monumented by an iron post, 1 in. diam., firmly set, marked and witnessed as described in the official record.

---

From the C  $\frac{1}{4}$  of sec. 12.

N.  $0^{\circ} 38'$  E., on the N. and S. center line of sec. 12.

10.015 Point for the OSN  $\frac{1}{64}$  sec. cor. of sec. 12.



Subdivision of Section 12, T. 3 N., R. 4 E. SOLK 4885

Chains.	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CN 1/64 on W. face.
11.50	Wash, 10 lks. wide, course S. 10° W.; along right bank of wash.
20.03	Point for the CN 1/16 sec. cor. of sec. 12.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	C N 1/16 S12
	C. 1949
25.60	Same wash, course S. 20° E.
30.045	Point for the CNN 1/64 sec. cor. of sec. 12.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CNN 1/64 on W. face.
40.06	The ¼ sec. cor. of secs. 1 and 12.
Subdivision of the NE ¼.	
	From the CE 1/16 sec. cor. of sec. 12.
	N. 0° 35' E., on the N. and S. center line of the NE ¼ of sec. 12.
10.011	Point for the CSNE 1/64 sec. cor. of sec. 12.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CSNE 1/64 on W. face.
20.022	Point for the NE 1/16 sec. cor. of sec. 12, at the intersection with the E. and W. center line.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	NE 1/16 S12. 1950
30.035	Point for the CNNE 1/64 sec. cor. of sec. 12.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CNNE 1/64 on W. face.
40.048	The E. 1/16 sec. cor. of secs. 1 and 12.
	From the N. 1/16 sec. cor. of sec. 12, on the E. bdy. of Tp.
	N. 89° 34' W., on the E. and W. center line of the NE ¼ of sec. 12.
10.00	Point for the CENE 1/64 sec. cor. of sec. 12.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CENE 1/64 on N. face.
10.90	Dry wash, drains S.
20.00	The NE 1/16 sec. cor. of sec. 12.
29.998	Point for the CWNE 1/64 sec. cor. of sec. 12.
	Set a wooden post, 2 ins. sq., 2½ ft. long, 15 ins. in the ground, mkd. CWNE 1/64 on N. face.
39.996	The CN 1/16 sec. cor. of sec. 12.

## Subdivision of Section 12, T. 3 N., R. 4 E.

## Chains.

Subdivision of the NE $\frac{1}{4}$  NE $\frac{1}{4}$ .

From the CENE 1/64 sec. cor. of sec. 12.

N. 0° 34' E., on the N. and S. center line of the NE $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 12.

- 10.013 Point for the NENE 1/64 sec. cor. of sec. 12, at the intersection of the E. and W. center line.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. NENE 1/64 on W. face.

- 20.027 The EE 1/64 sec. cor. of secs. 1 and 12.

From the NN 1/64 sec. cor. of sec. 12, on the E. bdy. of Tp.

N. 89° 34' W., on the E. and W. center line of the NE $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 12.

- 9.996 The NENE 1/64 sec. cor. of sec. 12.  
19.991 The CNNE 1/64 sec. cor. of sec. 12.

Subdivision of the SE $\frac{1}{4}$  NE $\frac{1}{4}$ .

From the CEE 1/64 sec. cor. of sec. 12.

N. 0° 34' E., on the N. and S. center line of the SE $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 12.

- 10.014 Point for the SENE 1/64 sec. cor. of sec. 12.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. SENE 1/64 on W. face.

- 20.028 The CENE 1/64 sec. cor. of sec. 12.

From the SN 1/64 sec. cor. of sec. 12, on the E. bdy. of Tp.

N. 89° 35' W., on the E. and W. center line of the SE $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 12.

- 10.008 The SENE 1/64 sec. cor. of sec. 12.  
20.016 The CSNE 1/64 sec. cor. of sec. 12.

Subdivision of the SW $\frac{1}{4}$  NE $\frac{1}{4}$ .

From the CWE 1/64 sec. cor. of sec. 12.

N. 0° 37' E., on the N. and S. center line of the SW $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 12.

- 10.012 Point for the SWNE 1/64 sec. cor. of sec. 12, at the intersection of the E. and W. center line:

Set a wooden post, 2 ins. sq.; 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. SWNE 1/64 on W. face.

- 20.025 The CWNE 1/64 sec. cor. of sec. 12.

From the CSNE 1/64 sec. cor. of sec. 12.

N. 89° 35' W., on the E. and W. center line of the SW $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 12.

- 10.004 The SWNE 1/64 sec. cor. of sec. 12.  
20.008 The CSN 1/64 sec. cor. of sec. 12.

Subdivision of Section 12, T. 3 N., R. 4 E.

Chains.

Subdivision of the NW $\frac{1}{4}$  NE $\frac{1}{4}$ .

From the CWNE 1/64 sec. cor. of sec. 12.

N. 0° 37' E., on the N. and S. center line of the NW $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 12.

10.018 Point for the NWNE 1/64 sec. cor. of sec. 12, at the intersection of the E. and W. center line.

Set a wooden post, 2 ins. sq., 2 $\frac{1}{2}$  ft. long, 15 ins. in the ground, mkd. NWNE 1/64 on W. face.

20.034 The WE 1/64 sec. cor. of secs. 11 and 12.

From the CNNE 1/64 sec. cor. of sec. 12.

N. 89° 33' W., on the E. and W. center line of the NW $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 12.

9.998 The NWNE 1/64 sec. cor. of sec. 12.

19.994 The CNN 1/64 sec. cor. of sec. 12.

155  
74

4-680  
(August 1947)

BOOK 4385

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Bert E. Wakeman	Surveying Aid
Douglas D. Lakin	Cartographic Survey Aid
Herman E. Wood	Surveying and Cartographic Aid
Carl P. Lyons	ditto
John H. Hoersch	ditto
Wayne E. Hendrickson	ditto
Phillip M. Slightam	ditto
Robert D. Stevens	ditto
Max Lester	ditto
John M. Willy	ditto
Natale N. Liuzzo	ditto

136  
75

### CERTIFICATE OF CADASTRAL ENGINEER

Cadastral Engineer

We Ty White, Cadastral Engineer, Claude F. Warner, HEREBY CERTIFY upon honor that, in

pursuance of special instructions bearing date of the 9th day of December 1948,  
29th " " July 1949

~~we have surveyed~~

we have resurveyed the section boundaries and surveyed the subdivision-of-section lines in Townships 3 North, Ranges 3, 4 and 5 East

of the G. & S.R. Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~me~~ us and under ~~my~~ our direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Albuquerque, New Mexico  
April 16, 1951  
Phoenix, Arizona.  
May 1, 1951

*Ty White*  
Cadastral Engineer  
*Claude F. Warner*  
Cadastral Engineer

### CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., JAN 16 1952, 19

The foregoing field notes of the <sup>re</sup> survey of section boundaries and survey of subdivision-of-section lines in Townships 3 North, Ranges 3, 4 and 5 East of the Gila and Salt River Meridian, Arizona

executed by Ty White and Claude F. Warner

having been critically examined and found correct, are hereby approved.

*Harry Harrington*  
~~Chief, Branch of Engineering and Construction.~~  
Chief, Division of Cadastral Engineering

### CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.~~

~~Chief, Branch of Engineering and Construction.~~