

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT



FIELD NOTES

BOOK 4399

Of the Dependent Resurvey of the Boundaries and

the Survey of Subdivision-of-Section Lines of

Sections 26 and 35,

Township 10 North, Range 6 West.

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Ty White, Cadastral Engineer

Under special instructions dated February 6, 1950, which provided
for the surveys included under Group No. 268, approved March 27, 1950
and assignment instructions dated January 14, 1952.

Survey commenced January 16, 1952

Survey completed February 4, 1952

4399

4399



111

BOOK 4399

INDEX DIAGRAM

Township 10 North, Range 6 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Handwritten annotations in the diagram:

- Section 26: A vertical line with '7' above it and '9' below it.
- Section 25: A horizontal line with '8' on the left, '10' on the right, and '6' on the far right.
- Section 25: A horizontal line with '11' on the left and '4' on the right.
- Section 35: A horizontal line with '15' above it and '14' on the right.
- Section 35: A horizontal line with '5' on the left and '3' on the right.
- Section 35: A vertical line with '13' below it.
- Section 26: A vertical line with '1' at the bottom.

T. 10 N., R. 6 W.

BOOK 4899

This survey was executed with a light mountain solar transit made by W. and L. E. Gurley, Serial No. 461263, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition and having been placed in satisfactory adjustment prior to the beginning of the survey, was tested and found free from any appreciable error.

The measurements were made with a narrow steel tape, 5 chains in length, graduated to tenths of a link for the first 10 links, every link for the remainder of the first 100 links and the balance at intervals of 10 links. The tape was tested by comparison with a standard 1 chain steel tape and found correct. The measurements were made on the slope, and the vertical angles of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

All the azimuths in this record were determined by the method of deflection angles referred to the meridian established by Polaris observation as follows:

January 19, 1952, at camp in the NW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 26, in latitude 34° 10' 46" N. and longitude 112° 50' 40" W. I make an hour angle observation on Polaris E. of the meridian for azimuth, making four observations, two each with the telescope in direct and reversed positions, reading the horizontal angles from a well defined point on the skyline two miles N., E. to Polaris. My watch reads correct Mountain Standard Time as checked by radio time signals.

Mean watch time of observation.	5h 50m 06s p.m.
Watch fast of l.m.t.	0h 31m 18s
Mean horizontal deflection angle	3° 31' 22"
Azimuth of Polaris	0° 11' 23"
Bearing of reference point	N. 3° 19' 59" W.

The geographic position of the cor. of secs. 25, 26, 35 and 36 as determined from data furnished with the special instructions is latitude 34° 10' 33" N. and longitude 112° 49' 50" W.

Preliminary to the resurvey the lines of the original survey are retraced and diligent search is made for all corners and other calls of the record. Identified corners are monumented in their original positions, lost corners are reestablished and monumented at proportionate positions based upon the original record. The retracement data are thoroughly verified and only the true line field notes are given herein.

The south boundary of Township 10 North, Range 6 West was surveyed by P. Contzen, in 1897 and the involved subdivisional lines were surveyed by John F. Hesse, in 1904.

The following field notes describe the dependent resurvey, or re-establishment, of the boundaries of sections 26 and 35 and limited survey of subdivision-of-section lines of those sections, to meet administrative requirements in connection with the identification of lands under the Small Tract Act of June 1, 1938.

Dependent Resurvey of the S. Bdy. of Sec. 35, T. 10 N., R. 6 W.

Reestablishment of a Survey Executed by
P. Contzen, Deputy Surveyor, in 1897.

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., which is monumented with a granite stone, 16x12x8 ins., firmly set in the ground. The top of the stone was broken off and lying on the ground along side the corner, mkd. 1 groove on E. and 2 grooves on W. Other marks destroyed.

At the corner point

Dependent Resurvey of the S. Bdy. of Sec. 35, T. 10 N., R. 6 W.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 10 N R 6 W
 S 35 | S 36
 ————
 S 2 | S 1
 T 9 N
 1904
 1952.

Bury the original corner stone alongside the iron post.

An A. & T. & S. Fe R. R. property line marker is set alongside this corner and is a steel rail, 3 ft. above ground painted white and mkd. A. T. & S. Fe R. R.

WEST, bet. secs. 2 and 35.

Over gently rolling land.

- 3.34 Wire fence, bears N. and S.
- 4.54 Fence, bears N. and S.; enter stock loading pens.
- 7.74 Fence, bears N. and S.; leave pens.
- 12.65 Power line, bears N. and S.
- 13.35 Center of U. S. Highway No. 89, bears N. and S.
- 14.60 Side track of the A. T. & S. Fe. R. R., bears NE. and SW.
- 17.15 Center of main track of the A. T. & S. Fe. R. R., bears N. and S.
- 17.75 Telephone line, bears N. and S.
- 21.65 Power line, bears N. and S.
- 21.75 Right of way fence, bears N. and S.
- 26.35 Wash, 20 lks. wide, course S.
- 40.04 The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, which is monumented with a malpais stone, 18x14x8 ins., firmly set in the ground, mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ — S 35
 ————
 S 2
 1952
 1897

Bury the original corner stone alongside the iron post.

Corner is located at a fence corner from which fences extend N. W. and S.

S. 89° 58' W., beginning new measurement.

- 23.85 Wash, 15 lks. wide, course SW.
- 40.03 The cor. of secs. 2, 3, 34 and 35, which is monumented with a granite stone, 20x10x9 ins., firmly set in the ground, mkd. 2 grooves on E. and 4 notches on W. faces.

At the corner point

Dependent Resurvey, of the S. Bdy. of Sec. 35, T. 10 N., R. 6 W.

Chains:

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 10 N R. 6 W
 S 34 | S 35
 S 3 | S 2
 T 9 N
 1897
 1952

Bury the original stone alongside the iron post.

This corner is located at a fence corner from which fences extend N., S. and E.

Land, gently rolling.

Soil, sandy.

Timber, none; undergrowth, none.


Dependent Resurvey, Portion of Bdrs. of Section 35, T. 10 N., R. 6 W.

Reestablishment of a Survey Executed by
 John F. Hesse, Deputy Surveyor in 1904.

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp.

N. 0° 05' W., bet. secs. 35 and 36.

Over rolling land, through scattering timber.

- 0.75 Wire fence, bears E. and W.
- 3.75 Spur track of the A. T. & S. Fe R. R., bears E. and W.
- 5.55 Road, bears E. and W.
- 6.15 Wire fence, bears E. and W.
- 7.05 Telephone line, bears E. and W.
- 24.05 Power line, bears NE. and SW.
- 32.95 Descend, 20 ft. over N. slope.
- 39.05 Center U. S. Highway No. 89, bears W. 80° E. and S. 80° W.
- 40.06 The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, which is monumented with a granite stone, 18x8x3 ins., firmly set in the ground, mkd. $\frac{1}{4}$ on W. face.
- At the corner point
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
- 
- Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
 Bury the original corner stone alongside the iron post.
- 40.40 Wash, 20 lks. wide, course NE.
- 46.30 Wash, 50 lks. wide, course SE.

Dependent Resurvey, Portion of Bdrs., of Section 35, T. 10 N., R. 6 W.

Chains

57.20

Spur, slopes SE.

80.08

The cor. of secs. 25, 26, 35 and 36 which is monumented with a granite stone, 13x10x10 ins., firmly set, in the ground, mkd. 1 groove on S. and 1 groove on E. faces

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground to solid rock and in a mound of stone, to top, with brass cap mkd.

T 10 N R 6 W

S 26 | S 25

S 35 | S 36

1904

1952

Bury the original corner stone alongside the iron post.

Land, rolling.

Soil, sandy.

Timber, palo verde; undergrowth, none.

N. 89° 57' W., bet. secs. 26 and 35.

Over rolling land, through scattering timber.

Ascend 18 ft. over E. slope.

4.45

Spur, slopes S.; desc. 72 ft. over W. slope.

8.95

Wash, 20 lks. wide, course S.; asc. 41 ft. over E. slope.

12.05

Spur, slopes S.; desc. W. slope.

15.55

Wash, 15 lks. wide, course S.

16.15

Right of way fence, bears N. and S.

17.75

A. T. & S. Fe R. R. tracks bears N. and S.

18.85

Telephone line, bears N. and S.

19.25

Right of way fence, bears N. and S.

26.95

Spur, slopes S.; desc. 34 ft. over W. slope.

28.75

Wash, 40 lks. wide, course S.

31.95

Spur, slopes SW.; desc. over NW. slope.

36.25

Wash, 20 lks. wide, course SW.

39.96

The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, which is monumented with a granite stone, 13x10x4 ins., firmly set in the ground, marked $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 26

$\frac{1}{4}$

S 35

1904

1952

Rebuild the mound of stone, 2 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor. and bury the original corner stone alongside the iron post.

Dependent Resurvey, Portion of Bdrs. of Section 35, T. 10 N., R. 6 W.

Chains	<p>S. 89° 56' W., beginning new measurement.</p> <p>3.000 Wash, 40 lks. wide, course SE.; asc. 47 ft. over E. slope.</p> <p>11.200 Top of ascent, bears N. and S.</p> <p>13.800 Wash, 10 lks. wide, course SE.</p> <p>20.036 Point for the W, 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 26</p> <p>W 1/16</p> <p>S 35</p> <p>1952</p> </div> <p>20.840 Center of graded road, bears N. 19° 30' W. to Congress Mine and S. 19° 30' E. to Congress Junction.</p> <p>30.054 Point for the W W 1/64 sec. cor. of secs. 26 and 35.</p> <p>Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.</p> <p>31.700 Wash, 15 lks. wide, course S.</p> <p>38.100 Intersection of old roads, which bear N. and S. and E. and W.</p> <p>40.072 Cor. of secs. 26, 27, 34 and 35, which is monumented with a granite stone, 20x12x8 ins., firmly set in the ground; mkd. 1 notch on S. and 2 notches on E. edges.</p> <p>At the corner point.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 N R 6 W</p> <table border="1" style="margin: auto;"> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> <tr> <td>1904</td> <td></td> </tr> <tr> <td>1952</td> <td></td> </tr> </table> <p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of cor. and bury the original corner stone alongside the iron post.</p> </div> <p>Land, rolling. Soil, sandy. Timber, pale verde and catolaw; undergrowth, none.</p>	S 27	S 26	S 34	S 35	1904		1952	
S 27	S 26								
S 34	S 35								
1904									
1952									
	<p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp.</p> <p>N. 0° 02' W., bet. secs. 34 and 35.</p> <p>Over rolling land, through scattering timber.</p> <p>7.450 Right of way fence, bears N. 64½° E. and S. 64½° W.</p> <p>9.200 Center of State Highway No. 71, bears N. 64½° E. and S. 64½° W.</p> <p>10.850 Right of way fence, bears N. 64½° E. and S. 64½° W.</p> <p>36.650 Wash, 20 lks. wide, course SW.</p> <p>40.050 The ¼ sec. cor. of secs. 34 and 35, which is monumented with a granite stone, 20x18x18 ins., firmly set in the ground, mkd. ¼ on W. face.</p>								

Dependent Resurvey, Portion of Bdrs. of Section 35, T. 10 N., R. 6 W.

Chains	At the corner point. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S 34 S 35 1904 1952
	Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of cor. and bury the original corner stone alongside the iron post. N. 0° 04' W., beginning new measurement.
1.200	Wash, 10 lks. wide, course SW.
20.040	Point for the N 1/16 sec. cor. of secs. 34 and 35. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. N 1/16 S 34 S 35 1952
30.060	Point for the N N 1/64 sec. cor. of secs. 34 and 35. Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.
40.080	The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, sandy. Timber, sparse palo verde and catclaw; undergrowth, none.

Dependent Resurvey, Portion of Bdrs. of Section 26, T. 10 N., R. 6 W.

	From the cor. of secs. 25, 26, 35 and 36. N. 0° 05' W., bet. secs. 25 and 26. Over hilly and broken land, through scattering timber.
17.500	Wash, 30 lks. wide, course SE.; asc. 69 ft. over broken SW. slope.
25.500	Right of way fence, bears E. and W.
26.200	Center of A. T. and S. Fe. R. R. track, bears E. and W.
26.270	From this point a U. S. G. Survey bench mark, bears W. 19.5 links dist., and is marked by a brass tablet, seated in concrete, mkd. ELEVATION 3094.
27.900	Telephone line, bears E. and W.
29.000	Right of way fence, bears E. and W.
40.260	The ¼ sec. cor. of secs. 25 and 26, which is monumented with a granite stone, 18x14x8 ins., firmly set in the ground, mkd. ¼ on W. face. At the corner point. Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

Dependent Resurvey, Portion of Bdrs. of Section 26, T. 10 N., R. 6 W.

Chains

$\frac{1}{4}$
 S 26 | S 25
 1904
 1952

Bury the original corner stone alongside the iron post.

N. $0^{\circ} 08'$ W., beginning new measurement.

Over rocky SW. slope of mountain.

0.300 Wash, 15 lks. wide, course SW.; asc. 446 ft. over broken SW. slope.

1.700 Old road, bears NW. and SE.

40.030 The cor. of secs. 23, 24, 25 and 26, marked by a large X chiseled on the top of a granite rock, 5x4x4 ft. above ground, with 2 grooves S. and 1 groove E. of the X and a scattered mound of stone, 3 ft. W. of the cor.

At the X, marking the point for the corner.

Set a brass tablet, $3\frac{1}{4}$ in. diam., $3\frac{1}{2}$ in. stem, with top mkd.

T 10 N R 6 W
 S 23 | S 24
 ————
 S 26 | S 25
 1904
 1952

Rebuild the mound of stone, $2\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, S. $\frac{1}{2}$ hilly and broken; N. $\frac{1}{2}$ mountainous.

Soil, rocky and gravelly.

Timber, palo verde and catclaw; undergrowth, none.

S. $89^{\circ} 55'$ W., bet. secs. 23 and 26.

Over mountainous land, through scattering timber.

Descend 468 ft. over steep SW. slope of mountain.

5.500 Ravine, course S.

27.000 Enter gently rolling land, bears N. and S.

35.200 Wash, 20 lks. wide, course SE.

39.940 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate distance; the original corner stone, a sandstone, 18x14x4 ins., properly marked, was found lying on top of a mound of stone, 121 links E. and 89 links N. of this point. (record: pits and mound of earth)

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

S 23
 $\frac{1}{4}$ ————
 S 26
 1952

Dependent Resurvey, Portion of Bdrs., of Section 26, T. 10 N., R. 6 W.

Chains	<p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, N. of cor. and bury the original corner stone alongside the iron post.</p>												
49.100	Wash, 15 lks. wide, course S.												
57.900	Wash, 20 lks. wide, course S. 30° W.												
70.900	Wash, 40 lks. wide, course S.												
78.000	Graded road, bears N. to Congress Mine and S. to Congress Junction.												
79.880	<p>The cor. of secs. 22, 23, 26 and 27, which is monumented with a granite stone, 24x14x8 ins., firmly set in the ground, mkd. 2 notches S. and E. edges.</p>												
	At the corner point												
	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T 10 N R 6 W</td> </tr> <tr> <td style="text-align: center;">S 22</td> <td style="text-align: center;">S 23</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 27</td> <td style="text-align: center;">S 26</td> </tr> <tr> <td colspan="2" style="text-align: center;">1904</td> </tr> <tr> <td colspan="2" style="text-align: center;">1952</td> </tr> </table>	T 10 N R 6 W		S 22	S 23	-----		S 27	S 26	1904		1952	
T 10 N R 6 W													
S 22	S 23												

S 27	S 26												
1904													
1952													
	<p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of cor. and bury the original corner stone alongside the iron post.</p>												
	<p>Land, E. 27 chs., mountainous; remainder, gently rolling. Soil, E. 27 chs., rocky; remainder, sandy and gravelly. Timber, pale verde and catclaw; undergrowth, none.</p>												
	From the cor. of secs. 26, 27, 34 and 35.												
	N. 0° 01' W., bet. secs. 26 and 27.												
	Over gently rolling land, through scattering timber.												
10.010	Point for the S S 1/64 sec. cor. of secs. 26 and 27.												
	<p>Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.</p>												
11.300	Wash, 15 lks. wide, course SW.												
20.020	Point for the S 1/16 sec. cor. of secs. 26 and 27												
	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">S 1/16</td> </tr> <tr> <td style="text-align: center;">S 27</td> <td style="text-align: center;">S 26</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">1952</td> </tr> </table>	S 1/16		S 27	S 26	-----		1952					
S 1/16													
S 27	S 26												

1952													
30.030	Point for the N S 1/64 sec. cor. of secs. 26 and 27.												
	<p>Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.</p>												
33.700	Spur, slopes S. 80° E.; desc. along E. slope.												
35.410	Intersect line 1-2 Sur. No. 3156 Gold Dollar No. 3 lode patented mining claim.												
	At point of intersection												

Dependent Resurvey, Portion of Bars. of Section 26, T. 10 N., R. 6 W.

Chains

Set a wooden post, 3 ft. long, 2 ins. sq., 16 ins. in the ground to solid rock, and in a mound of stone to top, mkd. C C.

From point of intersection, Cor. No. 1, bears S. 47° 00' E., 1.08 chs. dist., marked by a granite stone in place, 6x3x1 ft. above ground, mkd. and witnessed as described in the official record.

From the same point, Cor. No. 2, bears N. 47° 00' W., 21.608 chs. dist., marked by a granite boulder, 4x3x2 ft. above ground, mkd. and witnessed as described in the official record. This corner is identical with the SE. end center of Gold Dollar No. 2.

Thence over patented land.

40.040 The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, which is marked by a granite stone, 22x12x10 ins., firmly set, mkd. and witnessed as described in the official record.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

S 27 | S 26

1904

1952

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor. and bury the original corner stone alongside the iron post.

47.350 Graded road, bears NW. to Congress Mine and SE. to Congress Junction.

47.800 Intersect line 3-4 Sur. No. 3156 Gold Dollar No. 3 lode patented mining claim at a point from which Cor. No. 4, bears S. 47° 02' E., 9.181 chs. dist., marked by a granite stone, 10x8x10 ins. above ground, firmly set, mkd. and witnessed as described in the official record, and Cor. No. 3, bears N. 47° 02' W., 13.486 chs. dist., and is marked by a granite stone, 12x7x8 ins. above ground, firmly set, marked and witnessed as described in the official record.

Leave patented land.

50.540 Wash, 15 lks. wide, course SE.

66.950 Graded road, bears N. 20° E. to Congress Mine and S. 20° W. to Congress Junction.

80.130 The cor. of secs. 22, 23, 26 and 27.

Land, S. 20 chs., and N. 30 chs. of line, gently rolling; remainder, mountainous.

Soil, S. 20 chs., and N. 30 chs. of line, sandy; remainder, rocky. Timber, pale verde and catclaw; undergrowth, none.

Subdivision of Sections, T. 10 N., R. 6 W.

From the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.

N. 0° 06' W., on the N. and S. center line of sec. 26.

Over rolling land, through scattering timber.

Ascend gradual SW. slope.

Subdivisions of Sections, T. 10 N., R. 6 W.

Chains	
15.150	Low spur, slopes SE.; desc. 15 ft. over NE. slope.
20.056	Point for the C S 1/16 sec. cor. of sec. 26. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
25.950	Wash, 20 lks. wide, course SE.; asc. 23 ft. along top of spur, slopes S.
40.112	Point for the C 1/4 sec. cor. of sec. 26, at the intersection with the E. and W. center line. Set an iron post, 3 ft. long, 2 ins. sq., 28 ins. in the ground, with brass cap mkd.
9.900	W. 0° 06' W., beginning new measurement. Leave spur, slopes S. from N. 20° W.; thence along E. slope.
15.850	Right bank of wash, bears NW. and SE.; thence along bottom of wash.
17.550	Right bank of wash, bears NE. and SW.
23.050	Old road, bears NW. and SE.
23.750	Center of same wash, 20 lks. wide, course SE. for 3 chs. then S.
40.040	The 1/4 sec. cor. of secs. 23 and 26. Land, rolling. Soil, sandy and gravelly. Timber, palo verde and catclaw; undergrowth, none.
	From the 1/4 sec. cor. of secs. 25 and 26. S. 89° 51' W., on the E. and W. center line of sec. 26. Over rolling land, through scattering timber.
5.250	Wash, 15 lks. wide, course S. 60° W.
29.050	Wash, 20 lks. wide, course SW.
37.450	Wash, 30 lks. wide, course SW.
39.350	Low spur, slopes SE.
39.968	The C 1/4 sec. cor. of sec. 26.
	S. 89° 51' W.; beginning new measurement.
10.300	Wash, 20 lks; wide, course SW.
20.004	Point for the C W 1/16 sec. cor. of sec. 26. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

Subdivision of Sections, T. 10 N., R. 6 W.

Chains

W 1/16

C ————— C

S 26
1952

- 22.400 Low spur, slopes S.
- 26.800 Wash, 20 lks. wide, course SW.
- 30.006 Point for the C W W 1/64 sec. cor. of sec. 26.
Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.
- 31.700 Wash, 40 lks. wide, course S. 30° E.
- 34.578 Intersect line L-4 of Sur. No. 3156 Gold Dollar No. 3 lode patented mining claim.
At point of intersection
Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. C C.
From point of intersection, Cor. No. 1 of Gold Dollar No. 3 lode patented mining claim, bears S. 40° 47' W., 7.11 chs. dist., and Cor. No. 4, bears N. 40° 47' E., 1.978 chs. dist.
Thence, over patented land.
- 36.200 Graded road, bears NW. to Congress Mine and SE. to Congress Junction; ascend 45 ft. over E. slope.
- 40.008 The 1/4 sec. cor. of secs. 26 and 27.
Land, rolling.
Soil, sandy and gravelly.
Timber, palo verde and catclaw; undergrowth, none.
- From the W 1/16 sec. cor. of secs. 26 and 35.
N. 0° 02' W., on the N. and S. center line of the SW 1/4 of sec. 26.
- 10.020 Point for the C S SW 1/64 sec. cor. of sec. 26.
Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.
- 20.040 Point for the SW 1/16 sec. cor. of sec. 26, at the intersection with the E. and W. center lines.
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.
- SW 1/16
S 26
1952
- 24.850 Wash, 40 lks. wide, course SE.
- 30.048 Point for the C N SW 1/64 sec. cor. of sec. 26.
Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.
Ascend along top of low spur, slopes S.

Subdivision of Sections, T. 10 N., R. 6 W.

Chains 40.056	The C W 1/16 sec. cor. of sec. 26.
	From the C S 1/16 sec. cor. of sec. 26.
	S. 89° 54' W., on the E. and W. center line of the SW 1/4 of sec. 26.
10.000	Wash, 30 lks. wide, course SW.
14.000	Low spur, slopes S.
16.750	Wash, 40 lks. wide, course S. 30° E.; asc. 40 ft. over E. slope.
20.026	The SW 1/16 sec. cor. of sec. 26.
20.850	Top of ascent, bears NW. and SE.; thence over gently rolling, grassy land.
27.950	Graded road, bears N. 19° 30' W. to Congress Mine and S. 19° 30' E., to Congress Junction.
30.039	Point for the C W SW 1/64 sec. cor. of sec. 26.
	Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.
40.052	The S 1/16 sec. cor. of secs. 26 and 27.
	From the W W 1/64 sec. cor. of secs. 26 and 35.
	N. 0° 01' W., on the N. and S. center line of the SW 1/4 SW 1/4 of sec. 26.
10.010	Point for the SW SW 1/64 sec. cor. of sec. 26, at the intersection with the E. and W. center line.
	Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.
12.726	Wire fence bears E. and W.
15.620	Road, bears E. to graded road and W. to farm house.
15.826	An earth dam, bears E. and W.
17.026	Wire fence, bears E. and W.
20.026	The C W SW 1/64 sec. cor. of sec. 26.
	From the C S SW 1/64 sec. cor. of sec. 26.
	S. 89° 55' W., on the E. and W. center line of SW 1/4 SW 1/4 sec. 26.
4.350	Graded road, bears N. 19° 30' W. to Congress Mine and S. 19° 30' E. to Congress Junction.
5.650	Old road, bears N. and S.
10.016	The SW SW 1/64 sec. cor. of sec. 26.
18.500	Old road, bears N. and S.
20.032	The S S 1/64 sec. cor. of secs. 26 and 27.

Subdivision-of-Sections, T. 10 N., R. 6 W.

Chains	From the C W SW 1/64 sec. cor. of sec. 26.
	N. 0° 01' W., on the N. and S. center line of the NW 1/4 SW 1/4 sec. 26.
5.900	Graded road, bears N. 19° 30' W., to Congress Mine and S. 19° 30' E. Congress Junction.
10.008	Point for the NW SW 1/64 sec. cor. of sec. 26, at the intersection with the E. and W. center line.
	Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.
19.950	Wash, 20 lks. wide, course SE.
20.016	The C W W 1/64 sec. cor. of sec. 26.
	From the C N SW 1/64 sec. cor. of sec. 26.
	S. 89° 53' W., on the E. and W. center line of the NW 1/4 SW 1/4 sec. 26.
	Descend W. slope of spur.
5.900	Wash, 40 lks. wide, course S. 30° E.; asc. NE. slope.
10.007	The NW SW 1/64 sec. cor. of sec. 26.
11.475	Graded road, on a curve concave to the SW.; asc. gradually along S. slope of spur.
20.014	The N S 1/64 sec. cor. of secs. 26 and 27.
	From the 1/4 sec. cor. of secs. 2 and 35 on the S. bdy. of the Tp. NORTH, on the N. and S. center line of sec. 35.
	Over gently rolling grassy land; along a wire fence.
19.800	Fence corner, fences extend N., S. and E.
23.800	Fence corner, fences extend S. and E.
25.270	Center of State Highway No. 71, bears E. to U. S. Highway No. 89 and W. to Aguila.
28.400	Fence, bears E. and W.
38.000	An earth dam, bears E., 50 lks. dist.
40.020	Point for the C 1/4 sec. cor. of sec. 35, at the intersection with the E. and W. center line.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	C 1/4
	S 35
	1952
	NORTH, beginning new measurement.
5.000	Fence, bears NW. and SE.
6.500	Graded road, bears NW. to Congress Mine and SE. to Congress Junction.

Subdivision-of-Sections, T. 10 N., R. 6 W.

Chains 20.048	Point for the C N 1/16 sec. cor. of sec. 35. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
21.300	Descend 34 ft. over NE. slope.
32.200	Wash, 40 lks. wide, course SE.; asc. gradual SW. slope.
40.096	The ¼ sec. cor. of secs. 26 and 35. Land, rolling. Soil, sandy. Timber, sparse palo verde and catclaw.
	From the ¼ sec. cor. of secs. 35 and 36. S. 89° 59' W., on the E. and W. center line of sec. 35. Over hilly land, through scattering timber.
0.200	Wash, 15 lks. wide, course NE.; asc. 30 ft. over E. slope.
6.000	Top of small knoll; desc. W. slope.
8.200	Ravine, course S.; asc. 52 ft. over E. slope.
13.200	Top of ascent, bears N. and S.; thence over gently rolling, grassy land.
17.300	Right of way fence, bears N. and S.
18.920	A. T. and S. Fe R. R. track, bears N. and S.
19.500	Telephone line, bears N. and S.
20.400	Right of way fence, bears N. and S.
35.400	Graded road, bears NW. to Congress Mine and SE. to Congress Junction.
36.400	Fence corner, fences extend NE., SW., and W.; thence along fence.
40.020	The C ¼ sec. cor. of sec. 35. S. 89° 59' W., beginning new measurement.
20.017	Point for the C W 1/16 sec. cor. of sec. 35. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
30.230	Wash, 15 lks. wide, course SW.
40.014	Fence corner, from which fences extend N., S., and E.

Subdivision of Sections, T. 10 N., R. 6 W.

Chains 40.034	<p>The $\frac{1}{4}$ sec. cor. of secs. 34 and 35.</p> <p>Land, E. 13 chs. hilly; remainder, gently rolling. Soil, E. 13 chs., rocky and gravelly; remainder, sandy. Timber, sparse palo verde and catclaw; undergrowth, none.</p> <hr/> <p>From the C W $\frac{1}{16}$ sec. cor. of sec. 35.</p> <p>N. $0^{\circ} 02'$ W., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 35.</p>
19.900	Fence, bears E. and W.
20.040	<p>Point for the NW $\frac{1}{16}$ sec. cor. of sec. 35, at the intersection with the E. and W. center line, which falls in the center of an old road, bearing irregularly E. and W.</p> <p>Set a granite stone, 16x8x4 ins., 12 ins. below the surface of the road, mkd. X on top, from which</p> <p>An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground for a reference monument, bears N. 45° E., 70.7 lks. dist., with brass cap mkd. NW $\frac{1}{16}$ S 35 RM 1952, and an arrow pointing to the corner.</p> <p>An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground for a reference monument, bears N. 45° W., 70.7 lks. dist., with brass cap mkd. NW $\frac{1}{16}$ S 35 R M 1952, and an arrow pointing to the corner.</p>
30.060	<p>Point for the C N NW $\frac{1}{64}$ sec. cor. of sec. 35.</p> <p>Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. $\frac{1}{64}$.</p>
37.700	Graded road, bears N. $19^{\circ} 30'$ W. to Congress Mine and S. $19^{\circ} 30'$ E. to Congress Junction.
40.080	<p>The W $\frac{1}{16}$ sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the C N $\frac{1}{16}$ sec. cor. of sec. 35.</p> <p>S. $89^{\circ} 58'$ W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 35.</p>
9.700	Graded road, bears NW. to Congress Mine and SE. to Congress Junction.
10.500	Old road, bears NW. and SE. at a junction with a road from the W.; thence along road.
11.000	Fence corner, bears S., 25 lks. dist., from which fences extend SE. and W.
20.027	The NW $\frac{1}{16}$ sec. cor. of sec. 35.
28.950	Wash, 15 lks. wide, course SW.
30.037	<p>Point for the C W NW $\frac{1}{64}$ sec. cor. of sec. 35, which falls in the center of a road, bearing E. and W.</p> <p>Set a granite stone, 10x8x4 ins., 12 ins. below the surface of the road, mkd. X on top.</p>
30.650	Leave road, which bears NW.
31.037	Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, for witness corner monument, mkd. W C $\frac{1}{64}$.

Subdivision of Sections, T. 10 N., R. 6 W.

Chains
40.047

The N 1/16 sec. cor. of secs. 34 and 35.

From the true point for the C W NW 1/64 sec. cor. of sec. 35.

N. 0° 03' W., on the N. and S. center line of the NW 1/4 NW 1/4 sec. 35.

5.640 Wash, 15 lks. wide, course SE.

10.020 Point for the NW NW 1/64 sec. cor. of sec. 35, at the intersection with the E. and W. center line.

Set a wooden post, 3 ft. long, 2 ins. sq., 24 ins. in the ground, mkd. 1/64.

20.040 The W W 1/64 sec. cor. of secs. 26 and 35.

From the C N NW 1/64 sec. cor. of sec. 35.

S. 89° 57' W., on the E. and W. center line of the NW 1/4 NW 1/4 sec. 35.

6.110 Wash, 15 lks. wide, course SW.

10.014 The NW NW 1/64 sec. cor. of sec. 35.

12.428 Wash, 15 lks. wide, course SE.

16.628 Old road, bears NW. and SE.

18.250 Wash, 15 lks. wide, course SW.

20.028 The N N 1/64 sec. cor. of secs. 34 and 35.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Fred R. Chappell	Cartographic Survey Aid.
Robert D. Stevens	" " "
Jesse A. Livesay	" " "
Martin G. Roeben	Surveying and Cartographic Aid
William H. Derendor	" " " "
Carl P. Lyons	" " " "

CERTIFICATE OF CADASTRAL ENGINEER

I, Ty White, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of February, 1950, I have surveyed executed a dependent resurvey of the Boundaries and a survey of Subdivision-of-Section Lines of Sections 26 and 35, Township 10 North, Range 6 West

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Albuquerque, New Mexico
June 6, 1952

Ty White
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., JAN 23 1953, 19

The foregoing field notes of the survey of dependent resurvey of the Boundaries and survey of the Subdivision-of-Section Lines of Sections 26 and 35, Township 10 North, Range 6 West of the Gila and Salt River Meridian, in the State of Arizona

executed by Ty White

having been critically examined and found correct, are hereby approved.

Donald B. Clement
Assistant Chief, Division of Cadastral Engineering.

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above described surveys in is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.