

Original

4412

indexed ✓

4-679
(September 1948)

BOOK 4412

RECEIVED
BUREAU OF LAND MANAGEMENT

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1953 AUG 18 AM 9:07

REGION V
PHOENIX, ARIZONA

FIELD NOTES

of the

Dependent Resurvey of the Boundaries,

and

Survey of the Subdivision of Sections 10 and 14,

of

Township 15 South, Range 12 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Clarence E. Bilbray, Cadastral Engineer

Under special instructions dated October 29 and November 19, 1952, which provided for the surveys included under Group No. 286, approved November 18, 1952 and assignment instructions dated November 26, 1952 and assignment instructions dated December 1, 1952

Survey commenced March 13, 1953

Survey completed March 26, 1953

4412

4412

119

BOOK 4412

INDEX DIAGRAM

Township _____, Range _____

| | | | | | | | |
|----|----|----|----|----|----|----|--|
| 6 | 5 | 4 | 3 | 2 | 1 | | |
| 7 | 8 | 9 | 5 | 5 | 11 | | |
| | | | 8 | 10 | | 4 | |
| | | | 10 | 10 | | 10 | |
| 18 | 17 | 16 | 7 | 9 | 13 | | |
| | | | 6 | 6 | | 4 | |
| | | | 2 | 2 | | 2 | |
| 19 | 20 | 21 | 22 | 3 | 22 | 1 | |
| | | | | 23 | 14 | 22 | |
| | | | | 3 | 21 | 1 | |
| 30 | 29 | 28 | 27 | 3 | 3 | 24 | |
| | | | | | | | |
| | | | | | | | |
| 31 | 32 | 33 | 34 | 35 | 36 | | |

16-56770-1

Subdivision SE $\frac{1}{4}$ Sec. 10 - Pages 11 to 14
 Subdivision SW $\frac{1}{4}$ Sec. 10 - Pages 14 to 16
 Subdivision NE $\frac{1}{4}$ Sec. 10 - Pages 16 to 19
 Subdivision NW $\frac{1}{4}$ Sec. 10 - Pages 19 to 21
 Subdivision NE $\frac{1}{4}$ Sec. 14 - Pages 23 to 24

The dependent resurvey of the boundaries and survey of the subdivisinal lines of sections 10 and 14, T. 15 S., R. 12 E., of the Gila and Salt River Meridian, Arizona. All the boundaries and subdivisinal lines in the north $\frac{2}{3}$ of this township were surveyed by J. F. Hesse, U. S. Surveyor, in 1915. The west five miles of the north boundary was retraced by W. H. Thorn, U. S. Cadastral Engineer, in 1924.

This survey was executed with a light mountain solar transit made by W. and L. E. Gurley, Serial No. 371540, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition and having been placed in satisfactory adjustment prior to the beginning of the survey, was tested and found free from appreciable error.

The measurements were made with a narrow steel tape, 5 chains in length, graduated to tenths of a link for the first ten links, every link for the remainder of the first 100 links, and at each 10 link interval for the remaining 400 links. The tape was tested by comparison with a standard 1 chain steel tape and found correct. The measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The directions of all lines were determined by transit method, with azimuth obtained from U. S. Coast and Geodetic Survey triangulation station "Snyder's Hill", which is located in the NW $\frac{1}{4}$ of section 3, T. 15 S., R. 12 E. All bearings were adjusted for differences in longitude between stations.

The geographic position of the southeast corner of section 14, T. 15 S., R. 12 E., as computed from tie to U. S. Coast and Geodetic Survey triangulation station "Snyder's Hill", made at the northwest corner of sec. 10, is Latitude $32^{\circ} 07' 07.7''$ N., Longitude $111^{\circ} 04' 46.8''$ W.

Chains

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 12 E.

(Restoring the survey made by J. F. Hesse in 1915)

Beginning at the corner of secs. 13, 14, 23, and 24, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.

N. $0^{\circ} 03'$ W., bet. secs. 13 and 14.

Over nearly level land, through undergrowth.


- | | |
|-------|---|
| 2.40 | Wash, 10 lks. wide, 1 ft. deep, drains NNW. |
| 10.10 | Wash, 5 lks. wide, 1 ft. deep, drains NW. |
| 27.30 | Old road, bears E. and W. |
| 36.60 | Wash, 5 lks. wide, 1 ft. deep, drains W. |
| 38.60 | Wash, 5 lks. wide, $1\frac{1}{2}$ ft. deep, drains NW. |
| 39.50 | Wash, 10 lks. wide, $1\frac{1}{2}$ ft. deep, drains WNW. |
| 40.04 | The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record. |
| ----- | |
| | N. $0^{\circ} 02'$ W., beginning new measurement. |
| 1.65 | Wash, 6 lks. wide, 2 ft. deep, drains W. |

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 12 E.

Chains

20.025 Point for the N 1/16 sec. cor. of secs. 13 and 14, at proportionate distance.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/4 ins. in the ground, with brass cap mkd.



Bury a stone mkd. X alongside the iron post.

40.05 The corner of secs. 11, 12, 13, and 14, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.

Land, nearly level.
Soil, sandy loam.
No timber; undergrowth, mesquite, greasewood and cacti.

S. 89° 48' W., bet. secs. 11 and 14.


Over nearly level land, through undergrowth.

14.80 Wash, 20 lks. wide, 1 1/2 ft. deep, drains SW.

19.00 Wash, 15 lks. wide, 1 ft. deep, drains SW.

20.082 Point for the E 1/16 sec. cor. of secs. 11 and 14, at proportionate distance.

Set an iron post, 28 ins. long, 2 1/2 ins diam., 2 1/4 ins. in the ground, with brass cap mkd.



Deposit a stone mkd. X alongside the iron post.

20.75 Wash, 15 lks. wide, 1 1/2 ft. deep, drains NW.

22.95 Same wash, drains SW.

30.123 Point for the WE 1/64 sec. cor. of secs. 11 and 14, at proportionate distance.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 2 and 3.

39.65 Shallow wash, drains S.

40.164 The 1/4 sec. cor. of secs. 11 and 14, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

S. 89° 52' W., beginning new measurement.

22.80 Wash, 10 lks. wide, 1 ft. deep, drains NW.

26.00 Shallow wash, 5 lks. wide, drains WNW.

33.15 Wash, 15 lks. wide, 1 ft. deep, drains NW.

40.155 The corner of secs. 10, 11, 14, and 15, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 12 E.

| Chains | |
|--------|--|
| | Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood, mesquite and cacti. |
| | From the corner of secs. 13, 14, 23, and 24. S. 89° 51' W., bet. secs. 14 and 23. Over nearly level land, through undergrowth. |
| 2.20 | Wash, 6 lks. wide, 1½ ft. deep, drains NNE. |
| 9.90 | Wash, 10 lks. wide, 1 ft. deep, drains N. |
| 14.80 | Shallow wash, 10 lks. wide, drains NNE. |
| 33.30 | Wash, 10 lks. wide, 1 ft. deep, drains N. |
| 36.30 | Wash, 20 lks. wide, 1 ft. deep, drains NW. |
| 39.20 | Wash, 10 lks. wide, 1 ft. deep, drains N. |
| 40.16 | The ¼ sec. cor. of secs. 14 and 23, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record. |
| | S. 89° 51' W., beginning new measurement. |
| 4.15 | Wash, 5 lks. wide, 1 ft. deep, drains NE. |
| 11.65 | Shallow wash, drains NNW. |
| 16.05 | Wash, 5 lks. wide, 1 ft. deep, drains NNE. |
| 19.85 | Wash, 10 lks. wide, 2 ft. deep, drains N. |
| 26.35 | Old road, bears NE. and SW. |
| 40.16 | The corner of secs. 14, 15, 22, and 23, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record. |
| | Land, nearly level. Soil, sandy loam. No timber; undergrowth, mesquite and cacti. |
| | N. 0° 02' W., bet. secs. 14 and 15. Over nearly level land, through scattering undergrowth. |
| 5.50 | Dirt dam, bears E. and W. |
| 29.30 | Wash, 5 lks. wide, 1 ft. deep, drains WSW. |
| 40.04 | The ¼ sec. cor. of secs. 14 and 15, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record. |
| | N. 0° 04' W., beginning new measurement. |
| 20.65 | Wash, 20 lks. wide, 2 ft. deep, drains W. |
| 35.25 | Wash, 20 lks. wide, 3 ft. deep, drains WNW. |
| 36.05 | Wash, 20 lks. wide, 3 ft. deep, drains W. |
| 40.04 | The corner of secs. 10, 11, 14, and 15, heretofore described. |

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 12 E.

| Chains | |
|--------|---|
| | Land, nearly level. Soil, sandy. No timber, undergrowth, mesquite and cacti. |
| | N. 0° 02' W., bet. secs. 10 and 11. Over nearly level land, through undergrowth. |
| 7.65 | Wash, 20 lks. wide, 1½ ft. deep, drains WNW. |
| 10.019 | Point for the SS 1/64 sec. cor. of secs. 10 and 11, at proportionate distance. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 97 and 128. |
| 12.25 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 20.038 | Point for the S 1/16 sec. cor. of secs. 10 and 11, at proportionate distance. Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd. S 1/16 S10 S11 1953 Deposit a stone mkd. X at base of iron post. |
| 30.057 | Point for the NS 1/64 sec. cor. of secs. 10 and 11, at proportionate distance. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 65 and 96. |
| 40.076 | The ¼ sec. cor. of secs. 10 and 11, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record. N. 0° 02' W., beginning new measurement. |
| 10.015 | Point for the SN 1/64 sec. cor. of secs. 10 and 11, at proportionate distance. Set wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 33 and 64. |
| 20.03 | Point for the N 1/16 sec. cor. of secs. 10 and 11, at proportionate distance. Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd. N 1/16 S10 S11 1953 Deposit a stone mkd. X at base of iron post. |
| 25.31 | El Paso Natural Gas line, bears N. 53° 35' W. and S. 53° 35' E. |
| 30.045 | Point for the NN 1/64 sec. cor. of secs. 10 and 11, at proportionate distance. |

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 12 E.

Chains

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 1 and 32.

40.06 The corner of secs. 2, 3, 10, and 11, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.

Land, nearly level.
Soil, sandy loam.
No timber; undergrowth, greasewood and mesquite.

S. 89° 48' W., bet. secs. 3 and 10.

Over nearly level land, through undergrowth.

10.038 Point for the EE 1/64 sec. cor. of secs. 3 and 10, at proportionate distance.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 2 and 3.

20.00 El Paso Natural Gas line, bears N. 53° 35' W. and S. 53° 35' E.

20.076 Point for the E 1/16 sec. cor. of secs. 3 and 10, at proportionate distance.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 3}{S\ 10}$
1953

Deposit a stone mkd. X at base of iron post.

30.114 Point for the WE 1/64 sec. cor. of secs. 3 and 10, at proportionate distance.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 6 and 7.

40.152 The 1/4 sec. cor. of secs. 3 and 10, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

S. 89° 48' W., beginning new measurement.

10.031 Point for the EW 1/64 sec. cor. of secs. 3 and 10, at proportionate distance.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 10 and 11.

20.062 Point for the W 1/16 sec. cor. of secs. 3 and 10, at proportionate distance.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 3}{S\ 10}$
1953

Deposit broken glass at base of iron post.

30.093 Point for the WW 1/64 sec. cor. of secs. 3 and 10, at proportionate distance.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 14 and 15

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 12 E.

- Chains
33.80 Wash, 8 lks. wide, 1 ft. deep, drains SW.
- 40.124 The corner of secs. 3, 4, 9, and 10, which is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.
Land, nearly level.
Soil, sandy loam.
No timber; undergrowth, greasewood, mesquite and cacti.
-
- From the corner of secs. 10, 11, 14, and 15.
S. 89° 48' W., bet. secs. 10 and 15.
Over nearly level land, through undergrowth.
- 10.033 Point for the EE 1/64 sec. cor. of secs. 10 and 15, at proportionate distance.
Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 126 and 127.
- 11.95 Wash, 30 lks. wide, 3 ft. deep, drains WNW.
- 20.066 Point for the E 1/16 sec. cor. of secs. 10 and 15, at proportionate distance.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/4 ins. in the ground, with brass cap mkd.
$$E \frac{1}{16} \begin{array}{r} S 10 \\ S 15 \\ 1953 \end{array}$$
Deposit a stone mkd. X at base of iron post.
- 30.099 Point for the WE 1/64 sec. cor. of secs. 10 and 15, at proportionate distance.
Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 122 and 123.
- 40.132 The 1/4 sec. cor. of secs. 10 and 15, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

S. 89° 48' W., beginning new measurement.
- 1.75 Wash, 25 lks. wide, 2 ft. deep, drains NW.
- 10.038 Point for the EW 1/64 sec. cor. of secs. 10 and 15, at proportionate distance.
Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, mkd. for lots 118 and 119.
- 20.076 Point for the W 1/16 sec. cor. of secs. 10 and 15, at proportionate distance.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/4 ins. in the ground, with brass cap mkd.
$$W \frac{1}{16} \begin{array}{r} S 10 \\ S 15 \\ 1953 \end{array}$$
Deposit a stone mkd. X at base of iron post.

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 12 E.

| Chains | |
|--------|--|
| 29.65 | Wash, 30 lks. wide, 2 ft. deep, drains NW. |
| 30.114 | Point for the WW 1/64 sec. cor. of secs. 10 and 15, at proportionate distance. |
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 114 and 115. |
| 39.35 | Wash, 30 lks. wide, 2 ft. deep, drains WNW. |
| 40.152 | The corner of secs. 9, 10, 15, and 16, falls in N. and S. road, monumented with an iron post, 2 ins. diam., set 12 ins. below surface, marked as described in the official record. (Reset during road construction by the County) from which |
| | An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 60 lks. dist., mkd. T15S R12E S9 RM 1953 and an arrow pointing to the true corner. |
| | An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° E., 60 lks. dist., mkd. T15S R12E S15 RM 1953 and an arrow pointing to the true corner. |
| | Land, nearly level. Soil, sandy loam. No timber; undergrowth, mesquite and cacti. |
| | N. 0° 02' W., bet. secs. 9 and 10. |
| | Over nearly level land, along road. |
| 3.00 | Wash, 40 lks. wide, 1½ ft. deep, drains NW. |
| 10.018 | Point for the SS 1/64 sec. cor. of secs. 9 and 10, at proportionate distance, falls in road, set nail. |
| | from which |
| | A wooden post, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears East, 45 lks. dist., marked for lots 112 and 113. |
| 20.036 | Point for the S 1/16 sec. cor. of secs. 9 and 10, at proportionate distance, falls in road. |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, with brass cap mkd. |
| | <div style="text-align: center;"> <p>S 1/16</p> <p>S 9 S10</p> <p>1953</p> </div> |
| | from which |
| | An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 45 lks. dist., mkd. S 1/16 S10 RM 1953 and an arrow pointing to the true corner. |
| | An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears West, 45 lks. dist., mkd. S 1/16 S9 RM 1953 and an arrow pointing to the true corner. |

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 12 E.

Chains

30.054 Point for the NS $1/64$ sec. cor. of secs. 9 and 10, at proportionate distance, falls in road, set nail.

from which

A wooden post, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears East, 45 lks. dist., marked for lots 80 and 81.

36.10 Wash, 20 lks. wide, 2 ft. deep, drains NW.

37.50 Wash, 20 lks. wide, 1 ft. deep, drains NW.

40.072 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, falls on W. edge of road, monumented with an iron post, 1 in. diam., set and marked as described in the official record, reset old post, 3 ins. below the surface...

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 45 lks. dist., mkd. $\frac{1}{4}$ S10 RM 1953 and an arrow pointing to the true corner.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears West, 45 lks. dist., mkd. $\frac{1}{4}$ S9 RM 1953 and an arrow pointing to the true corner.

N. $0^{\circ} 03'$ W., beginning new measurement.

3.50 Wash, 20 lks. wide, 1 ft. deep, drains NW.

10.014 Point for the SN $1/64$ sec. cor. of secs. 9 and 10, at proportionate distance, falls in road, set nail.

from which

A wooden post, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears East, 45 lks. dist., marked for lots 48 and 49.

13.05 Wash, 15 lks. wide, 1 ft. deep, drains W.

17.75 Wash, 10 lks. wide, 1 ft. deep, drains WNW.

20.028 Point for the N $1/16$ sec. cor. of secs. 9 and 10, at proportionate distance, falls in road.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 34 ins. in the ground, with brass cap mkd.

N $1/16$
S 9 | S10
1953

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 45 lks. dist., mkd. N $1/16$ S10 RM 1953 and an arrow pointing to the true corner.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears West, 45 lks. dist., mkd. N $1/16$ S9 RM 1953 and an arrow pointing to the true corner.

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 12 E.

| | |
|---|--|
| Chains | |
| 20.95 | Wash, 10 lks. wide, 2 ft. deep, drains WNW. |
| 28.80 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 30.042 | Point for the NN $\frac{1}{64}$ sec. cor. of secs. 9 and 10, at proportionate distance, falls in road, set nail. from which A wooden post, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears East, 50 lks. dist., marked for lots 16 and 17. |
| 34.45 | Wash, 10 lks. wide, 1 ft. deep, drains SW. |
| 40.056 | The corner of secs. 3, 4, 9, and 10. From this corner U. S. Coast and Geodetic Survey station "Snyder's Hill", bears N. $2^{\circ} 15'$ E., 56.54 chs. dist. Land, nearly level. Soil, sandy loam. No timber; undergrowth, mesquite and cacti. |
| Subdivision of Section 10, T. 15 S., R. 12 E. | |
| | From the $\frac{1}{4}$ sec. cor. of secs. 10 and 15. N. $0^{\circ} 03'$ W., on the N. and S, center line of sec. 10. |
| 10.02 | Point for the CSS $\frac{1}{64}$ sec. cor. of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 104, 105, 120, and 121. |
| 10.80 | Wash, 10 lks. wide, 2 ft. deep, drains NW. |
| 12.60 | Wash, 25 lks. wide, 4 ft. deep, drains WNW. |
| 18.65 | Wash, 15 lks. wide, 1 ft. deep, drains WNW. |
| 20.04 | Point for the center S $\frac{1}{16}$ sec. cor. of sec. 10. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. C S $\frac{1}{16}$ S10 C 1953 Deposit a stone mkd. X at base of iron post. |
| 27.00 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 30.06 | Point for the CNS $\frac{1}{64}$ sec. cor. of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 72, 73, 88, and 89. |
| 33.45 | Wash, 10 lks. wide, 1 ft. deep, drains W. |
| 40.08 | Point for the C $\frac{1}{4}$ sec. cor. of sec. 10, at the intersection of the E. and W. center line. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. C $\frac{1}{4}$ S10 1953 |

Subdivision of Section 10, T. 15 S., R. 12 E.

Chains

Deposit a stone mkd. X at base of iron post.

42.10 Wash, 15 lks. wide, 2 ft. deep, drains WNW.

44.50 Wash, 5 lks. wide, $1\frac{1}{2}$ ft. deep, drains WNW.

50.097 Point for the CSN $1/64$ sec. cor. of sec. 10.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 40, 41, 56, and 57.

50.40 Wash, 10 lks. wide, 1 ft. deep, drains WNW.

60.114 Point for the CN $1/16$ sec. cor. of sec. 10.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad | \quad \text{S } 10 \\ \text{C} \\ 1953 \end{array}$$

Deposit stone mkd. X at base of iron post.

70.131 Point for the CNN $1/64$ sec. cor. of sec. 10.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 8, 9, 24, and 25.

80.148 The $\frac{1}{4}$ sec. cor. of secs. 3 and 10.

From the $\frac{1}{4}$ sec. cor. of secs. 10 and 11:

S. $89^{\circ} 47'$ W., on the E. and W. center line of sec. 10.

10.037 Point for the CEE $1/64$ sec. cor. of sec. 10.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 62, 63, 66, and 67.

20.074 Point for the CE $1/16$ sec. cor. of sec. 10.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{E } 1/16 \\ \text{C} \quad \text{---} \quad \text{C} \\ \text{S } 10 \\ 1953 \end{array}$$

Deposit a stone mkd. X at base of iron post.

27.25 Wash, 15 lks. wide, 2 ft. deep, drains WNW.

28.55 Wash, 10 lks. wide, 2 ft. deep, drains WNW.

30.111 Point for the CWE $1/64$ sec. cor. of sec. 10.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 58, 59, 70, and 71.

33.10 Wash, 6 lks. wide, 2 ft. deep, drains WNW.

36.70 Wash, 6 lks. wide, 1 ft. deep, drains WNW.

40.148 The C $\frac{1}{4}$ sec. cor. of sec. 10.

45.50 Wash, 10 lks. wide, 1 ft. deep, drains WNW.

BOOK 1412

Subdivision of Section 10, T. 15 S., R. 12 E.

Chains

- 50.182 Point for the CEW $1/64$ sec. cor. of sec. 10.
Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 54, 55, 74, and 75.
- 56.60 Wash, 5 lks. wide, 1 ft. deep, drains NW.
- 60.216 Point for the CW $1/16$ sec. cor. of sec. 10.
Set an iron post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, with brass cap mkd.
- W $1/16$
C ——— C
S 10
1953
- Deposit a stone mkd. X at base of iron post.
- 70.250 Point for the CWW $1/64$ sec. cor. of sec. 10.
Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 50, 51, 78, and 79.
- 76.70 Wash, 10 lks. wide, 1 ft. deep, drains NW.
- 78.50 Wash, 10 lks. wide, 1 ft. deep, drains NW.
- 80.20 Road, bears N. and S.
- 80.284 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
-
- Subdivision of the SE $\frac{1}{4}$
- From the E $1/16$ sec. cor. of secs. 10 and 15.
N. $0^{\circ} 02' 30''$ W., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 10.
- 3.10 Wash, 30 lks. wide, 3 ft. deep, drains WNW.
- 10.017 Point for the CSSE $1/64$ sec. cor. of sec. 10.
Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 100, 101, 124, and 125.
- 20.034 Point for the SE $1/16$ sec. cor. of sec. 10, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- SE $1/16$ S10
1953
- Deposit a stone mkd. X at base of iron post.
- 30.050 Point for the CN SE $1/64$ sec. cor. of sec. 10.
Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 68, 69, 92, and 93.
- 32.00 Wash, drains WNW.
- 33.30 Wash, 15 lks. wide, 2 ft. deep, drains WNW.
- 35.50 Wash, 10 lks. wide, 1 ft. deep, drains NW.
- 40.066 The CE $1/16$ sec. cor. of sec. 10.

Subdivision of Section 10, T. 15 S., R. 12 E.

| Chains | |
|--------|---|
| | Subdivision of the SE $\frac{1}{4}$ |
| | From the S 1/16 sec. cor. of secs. 10 and 11. |
| | S. 89° 48' W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 10. |
| 4.80 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 5.80 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 6.85 | Wash, 10 lks. wide, 1 $\frac{1}{2}$ ft. deep, drains NW. |
| 10.035 | Point for the CE SE 1/64 sec. cor. of sec. 10. |
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 94, 95, 98, and 99. |
| 20.070 | The SE 1/16 sec. cor. of sec. 10. |
| 30.105 | Point for the CWSE 1/64 sec. cor. of sec. 10. |
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 90, 91, 102, and 103. |
| 30.55 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 40.140 | The CS 1/16 sec. cor. of sec. 10. |
| | Subdivision of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ |
| | From the CESE 1/64 sec. cor. of sec. 10. |
| | N. 0° 02' W., on the N. and S. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. |
| 1.65 | Wash, 10 lks. wide, 1 $\frac{1}{2}$ ft. deep, drains NW. |
| 7.20 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 9.85 | Wash, 5 lks. wide, 1 ft. deep, drains W. |
| 10.02 | Point for the NESE 1/64 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ |
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 66, 67, 94, and 95. |
| 20.038 | The CEE 1/64 sec. cor. of sec. 10. |
| | From the NS 1/64 sec. cor. of secs. 10 and 11. |
| | S. 89° 47' W., on the E. and W. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. |
| 10.037 | The NESE 1/64 sec. cor. of sec. 10. |
| 12.05 | Wash, 10 lks. wide 1 ft. deep, drains NW. |
| 15.10 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 15.70 | Wash, 15 lks. wide, 1 ft. deep, drains NW. |
| 20.072 | The CNSE 1/64 sec. cor. of sec. 10. |
| | Subdivision of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ |
| | From the CW-SE 1/64 sec. cor. of sec. 10 |

BOOK 4412

Subdivision of Section 10, T. 15 S., R. 12 E.

| Chains | N. 0° 03' W., on the N. and S. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. |
|--|---|
| 10.022 | Point for the NW-SE 1/64 sec. cor. of sec. 10; at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 70, 71, 90, and 91. |
| 19.40 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 20.04 | The C-W-E 1/64 sec. cor. of sec. 10. |
| From the C-N-SE 1/64 sec. cor. of sec. 10. | |
| S. 89° 47' W., on the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. | |
| 10.033 | The NW-SE 1/64 sec. cor. of sec. 10. |
| 13.30 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 20.066 | The C-N-S 1/64 sec. cor. of sec. 10. |
| Subdivision of the SE $\frac{1}{4}$ SE $\frac{1}{4}$. | |
| From the E-E 1/64 sec. cor. of secs. 10 and 15. | |
| N. 0° 02' W., on the N. and S. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. | |
| 10.02 | Point for the SE-SE 1/64 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 98, 99, 126, and 127. |
| 20.04 | The C-E-SE 1/64 sec. cor. of sec. 10. |
| From the S-S 1/64 sec. cor. of secs. 10 and 11. | |
| S. 89° 47' W., on the E. and W. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. | |
| 1.80 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 10.034 | The SE-SE 1/64 sec. cor. of sec. 10. |
| 20.072 | The C-S-SE 1/64 sec. cor. of sec. 10. |
| Subdivision of the SW $\frac{1}{4}$ SE $\frac{1}{4}$. | |
| From the W-E 1/64 sec. cor. of secs. 10 and 15. | |
| N. 0° 03' W., on the N. and S. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. | |
| 7.70 | Wash, 25 lks. wide, 4 ft. deep, drains WNW. |
| 10.016 | Point for the SW-SE 1/64 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 102, 103, 122, and 123. |
| 12.60 | Shallow wash, drains WNW. |
| 20.035 | The C-W-SE 1/64 sec. cor. of sec. 10. |
| From the C-S-SE 1/64 sec. cor. of sec. 10. | |

Subdivision of Section 10, T. 15 S., R. 12 E.

| | |
|---|--|
| Chains | S. 89° 47' W., on the E. and W. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 10. |
| 5.05 | Wash, 7 lks. wide, 1 ft. deep, drains NW. |
| 10.034 | The SW-SE 1/64 sec. cor. of sec. 10. |
| 12.30 | Wash, 10 lks. wide, 2 ft. deep, drains WNW. |
| 16.25 | Wash, 25 lks. wide, 4 ft. deep, drains WNW. |
| 20.068 | The C-S-S 1/64 sec. cor. of sec. 10. |
| Subdivision of the SW $\frac{1}{4}$. | |
| From the W 1/16 sec. cor. of secs, 10 and 15. | |
| N. 0° 03' W., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 10. | |
| 2.00 | Shallow wash, drains NW. |
| 10.02 | Point for the C-S-SW 1/64 sec. cor. of sec. 10. |
| Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 108, 109, 116, and 117. | |
| 17.30 | Wash, 30 lks. wide, 4 ft. deep, drains WNW. |
| 20.04 | Point for the SW 1/16 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the SW $\frac{1}{4}$ of sec. 10. |
| Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. | |
| SW 1/16 S10 | |
| 1953 | |
| Deposit a stone mkd. X at base of iron post. | |
| 22.65 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 25.35 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 30.057 | Point for the C-N-SW 1/64 sec. cor. of sec. 10. |
| Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 76, 77, 84, and 85. | |
| 31.85 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 38.35 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 40.074 | The C-W 1/16 sec. cor. of sec. 10. |
| From the C-S 1/16 sec. cor. of sec. 10. | |
| S. 89° 48' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 10. | |
| 9.00 | Wash, 20 lks. wide, 1 ft. deep, drains WNW. |
| 10.034 | Point for the C-E-SW 1/64 sec. cor. of sec. 10. |
| Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 86, 87, 106, and 107. | |
| 20.068 | The SW 1/16 sec. cor. of sec. 10. |

Subdivision of Section 10, T. 15 S., R. 12 E.

| Chains | |
|--|---|
| 29.70 | Wash, 30 lks. wide, 5 ft. deep, drains NW. |
| 30.104 | Point for the C-W-SW $1/64$ sec. cor. of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 82, 83, 110, and 111. |
| 40.14 | The S $1/16$ sec. cor. of secs. 9 and 10. |
| Subdivision of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ | |
| | From the C-E-SW $1/64$ sec. cor. of sec. 10. N. 0° 03' W., on the N. and S. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 10. |
| 3.25 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 8.15 | Wash, 15 lks. wide, 1 ft. deep, drains NW. |
| 10.02 | Point for the ^{NE} SW $1/64$ sec. cor. of sec 10, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 74, 75, 86, and 87. |
| 16.90 | Wash, 15 lks. wide, 1 ft. deep, drains W. |
| 19.55 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 20.04 | The C-E-W $1/64$ sec. cor. of sec. 10. |
| From the C-N-S $1/64$ sec. cor. of sec. 10. S. 89° 47' W., on the E. and W. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 10. | |
| 2.05 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 10.036 | The NE-SW $1/64$ sec. cor. of sec. 10. |
| 17.05 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 20.065 | The C-N-SW $1/64$ sec. cor. of sec. 10. |
| Subdivision of the NW $\frac{1}{4}$ SW $\frac{1}{4}$ | |
| | From the C-W-SW $1/64$ sec. cor. of sec. 10. N. 0° 02' W., on the N. and S. center line of the NW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 10: |
| 2.75 | Wash, 20 lks. wide, 4 ft. deep, drains NW. |
| 5.35 | Wash, 15 lks. wide, 2 ft. deep, drains NW. |
| 10.017 | Point for the NW-SW $1/64$ sec. cor. of sec. 10, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 78, 80, 81, and 83. |
| 20.04 | The C-W-W $1/64$ sec. cor. of sec. 10. |
| From the C-N-SW $1/64$ sec. cor. of sec. 10. S. 89° 47' W., on the E. and W. center line of the NW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 10. | |
| 10.038 | The NW-SW $1/64$ sec. cor. of sec. 10. |

Subdivision of Section 10, T. 15 S., R. 12 E.

Chains

10.80 Wash, 10 lks. wide, 2 ft. deep, drains WNW.

12.50 Wash, 20 lks. wide, $1\frac{1}{2}$ ft. deep, drains WNW.

14.00 Wash, 15 lks. wide, 1 ft. deep, drains NW.

20.073 The N-S $\frac{1}{64}$ sec. cor. of secs. 9 and 10.Subdivision of the $SE\frac{1}{4}$ $SW\frac{1}{4}$.From the E-W $\frac{1}{64}$ sec. cor. of secs. 10 and 15.N. $0^{\circ} 03'$ W., on the N. and S. center line of the $SE\frac{1}{4}$ $SW\frac{1}{4}$ of sec. 10.10.018 Point for the SE-SW $\frac{1}{64}$ sec. cor. of sec. 10, at the intersection of the E. and W. center line of the $SE\frac{1}{4}$ $SW\frac{1}{4}$ of sec. 10.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 106, 107, 118, and 119.

15.85- Wash, 25 lks. wide, 4 ft. deep, drains WNW.

20.038 The C-E-SW $\frac{1}{64}$ sec. cor. of sec. 10.From the C-S-S $\frac{1}{64}$ sec. cor. of sec. 10.S. $89^{\circ} 47'$ W., on the E. and W. center line of the $SE\frac{1}{4}$ $SW\frac{1}{4}$ of sec. 10.10.038 The SE-SW $\frac{1}{64}$ sec. cor. of sec. 10.20.069 The C-S-SW $\frac{1}{64}$ sec. cor. of sec. 10.Subdivision of the $SW\frac{1}{4}$ $SW\frac{1}{4}$.From the W-W $\frac{1}{64}$ sec. cor. of sec. 10, and 15.N. $0^{\circ} 02'$ W., on the N. and S. center line of the $SW\frac{1}{4}$ $SW\frac{1}{4}$ of sec. 10.

0.05 Wash, 30 lks. wide, 2 ft. deep, drains WNW.

10.02 Point for the SW-SW $\frac{1}{64}$ sec. cor. of sec. 10, at the intersection of the E. and W. center line of the $SW\frac{1}{4}$ $SW\frac{1}{4}$ sec. 10.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 110, 112, 113, and 115.

20.04 The C-W-SW $\frac{1}{64}$ sec. cor. of sec. 10.From the C-S-SW $\frac{1}{64}$ sec. cor. of sec. 10.S. $89^{\circ} 47'$ W., on the E. and W. center line of the $SW\frac{1}{4}$ $SW\frac{1}{4}$ of sec. 10.10.038 The SW-SW $\frac{1}{64}$ sec. cor. of sec. 10.20.073 The S-S $\frac{1}{64}$ sec. cor. of secs. 9 and 10.Subdivision of the $NE\frac{1}{4}$.From the C-E $\frac{1}{16}$ sec. cor. of sec. 10.N. $0^{\circ} 02' 30''$ W., on the N. and S. center line of the $NE\frac{1}{4}$ of sec. 10.10.016 Point for the C-S-NE $\frac{1}{64}$ sec. cor. of sec. 10.

Subdivision of Section 10, T, 15 S., R. 12 E.

| Chains | |
|--------|--|
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 36, 37, 60, and 61. |
| 20.032 | <p>Point for the NE 1/16 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the NE 1/4 of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/2 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S10 1953</p> <p>Deposit a stone mkd. X at base of iron post.</p> |
| 30.047 | <p>Point for the C-N-NE 1/64 sec. cor. of sec. 10.</p> <p>Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 4, 5, 28, and 29.</p> |
| 40.062 | The E 1/16 sec. cor. of secs. 3 and 10. |
| 10.037 | <p>From the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>S. 89° 48' W., on the E. and W. center line of the NE 1/4 of sec. 10.</p> <p>Point for the C-E-NE 1/64 sec. cor. of sec. 10.</p> <p>Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 30, 31, 34, and 35.</p> |
| 20.074 | The NE 1/16 sec. cor. of sec. 10. |
| 30.111 | <p>Point for the C-W-NE 1/64 sec. cor. of sec. 10.</p> <p>Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 26, 27, 38, and 39.</p> |
| 40.148 | The C-N 1/16 sec. cor. of sec. 10. |
| 10.015 | <p style="text-align: center;">Subdivision of the NE 1/4 NE 1/4.</p> <p>From the C-E-NE 1/64 sec. cor. of sec. 10.</p> <p>N. 0° 02' W., on the N. and S. center line of the NE 1/4 NE 1/4 of sec. 10.</p> <p>Point for the NE-NE 1/64 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the NE 1/4 NE 1/4 of sec. 10.</p> <p>Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 2, 3, 30, and 31.</p> |
| 12.68 | El Paso Natural Gas line, bears N. 53° 35' W. and S. 53° 35' E. |
| 20.03 | The E-E 1/64 sec. cor. of secs. 3 and 10. |
| 6.40 | <p>From the N-N 1/64 sec. cor. of secs. 10 and 11.</p> <p>S. 89° 48' W., on the E. and W. center line of the NE 1/4 NE 1/4 of sec. 10.</p> <p>El Paso Natural Gas line, bears N. 53° 35' W. and S. 53° 35' E.</p> |
| 10.041 | The NE-NE 1/64 sec. cor. of sec. 10. |
| 20.075 | The C-N-NE 1/64 sec. cor. of sec. 10. |

Subdivision of Section 10, T. 15 S., R. 12 E.

| Chains | Subdivision of the NW $\frac{1}{4}$ NE $\frac{1}{4}$. |
|--------|---|
| | From the C-W-NE 1/64 sec. cor. of sec. 10. N. 0° 02' 30" W., on the N. and S. center line of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 10. |
| 10.016 | Point for the NW-NE 1/64 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 6, and 7, 26, and 27. |
| 20.031 | The W-E 1/64 sec. cor. of secs. 3 and 10. |
| | From the C-N-NE 1/64 sec. cor. of sec. 10. S. 89° 48' W., on the E. and W. center line of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 10. |
| 10.037 | The NW-NE 1/64 sec. cor. of sec. 10. |
| 13.50 | Wash, 10 lks. wide, 1 ft. deep, drains WSW. |
| 20.073 | The C-N-N 1/64 sec. cor. of sec. 10. |
| | Subdivision of the SE $\frac{1}{4}$ NE $\frac{1}{4}$. |
| | From the C-E-E 1/64 sec. cor. of sec. 10. N. 0° 02' W., on the N. and S. center line of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 10. |
| 10.015 | Point for the SE-NE 1/64 sec. cor. of secs. 10, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 34, 35, 62, and 63. |
| 20.03 | The C-E-NE 1/64 sec. cor. of sec. 10. |
| | From the S-N 1/64 sec. cor. of secs. 10 and 11. S. 89° 47' W., on the E. and W. center line of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 10. |
| 10.038 | The SE-NE 1/64 sec. cor. of sec. 10. |
| 20.073 | The C-S-NE 1/64 sec. cor. of sec. 10. |
| | Subdivision of the SW $\frac{1}{4}$ NE $\frac{1}{4}$. |
| | From the C-W-E 1/64 sec. cor. of sec. 10. N. 0° 02' 30" W., on the N. and S. center line of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 10. |
| 0.25 | Wash, 7 lks. wide, 1 ft. deep, drains W. |
| 2.30 | Wash, 10 lks. wide, 1 ft. deep; drains NW. |
| 10.017 | Point for the SW-NE 1/64 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 38, 39, 58, and 59. |
| 20.033 | The C-W-NE 1/64 sec. cor. of sec. 10. |

Subdivision of Section 10, T. 15 S., R. 12 E.

| | |
|-------------------------------|---|
| Chains | From the C-S-NE $1/64$ sec. cor. of sec. 10. S. $89^{\circ} 47'$ W., on the E. and W. center line of the SW $1/4$ NE $1/4$ of sec. 10. |
| 10.036 | The SW-NE $1/64$ sec. cor. of sec. 10. |
| 19.60 | Wash, 5 lks. wide, 1 ft. deep, drains WNW. |
| 20.070 | The C-S-N $1/64$ sec. cor. of sec. 10. |
| Subdivision of the NW $1/4$. | |
| | From the C-W $1/16$ sec. cor. of sec. 10. N. $0^{\circ} 03'$ W., on the N. and S. center line of the NW $1/4$ of sec. 10. |
| 4.50 | Shallow wash, drains WNW. |
| 9.50 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 10.017 | Point for the C-S-NW $1/64$ sec. cor. of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 44, 45, 52, and 53. |
| 10.50 | Wash, 10 lks. wide, 1 ft. deep, drains W. |
| 20.034 | Point for the NW $1/16$ sec. cor. of sec. 10, at the intersection of the E. and W. center line of the NW $1/4$ of sec. 10. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. |
| NW $1/16$ S10 1953 | |
| | Deposit a stone mkd. X at base of iron post. |
| 20.30 | Wash, 10 lks. wide, 2 ft. deep, drains W. |
| 30.049 | Point for the C-N-NW $1/64$ sec. cor. of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 12, 13, 20, and 21. |
| 38.10 | Wash, 10 lks. wide, 1 ft. deep, drains SW. |
| 40.064 | The W $1/16$ sec. cor. of secs. 3 and 10. |
| | From the C-N $1/16$ sec. cor. of sec. 10. S. $89^{\circ} 48'$ W., on the E. and W. center line of the NW $1/4$ of sec. 10. |
| 10.033 | Point for the C-E-NW $1/64$ sec. cor. of sec. 10. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 22, 23, 42, and 43. |
| 11.80 | Wash, 5 lks. wide, 1 ft. deep, drains SW. |
| 15.70 | Same wash, drains WNW. |
| 20.066 | The NW $1/16$ sec. cor. of sec. 10. |
| 21.85 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 30.099 | Point for the C-W-NW $1/64$ sec. cor. of sec. 10. |

Subdivision of Section 10, T. 15 S., R. 12 E.

| | |
|-----------------------------------|--|
| Chains | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 18, 19, 46, and 47. |
| 39.80 | Wash, 15 lks. wide, 1 ft. deep, drains WNW. |
| 40.00 | Road, bears N. and S. |
| 40.132 | The N 1/16 sec. cor. of secs. 9 and 10. |
| Subdivision of the NE 1/4 NW 1/4. | |
| | From the C-E-NW 1/64 sec. cor. of sec. 10. |
| | N. 0° 03' W., on the N. and S. center line of the NE 1/4 NW 1/4 of sec. 10. |
| 0.95 | Wash, 5 lks. wide, 1 ft. deep, drains W. |
| 10.015 | Point for the NE-NW 1/64 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the NE 1/4 NW 1/4 of sec. 10. |
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 10, 11, 22, and 23. |
| 20.03 | The E-W 1/64 sec. cor. of secs. 3 and 10. |
| Subdivision of the NE 1/4 NW 1/4. | |
| | From the C-N-N 1/64 sec. cor. of sec. 10. |
| | S. 89° 48' W., on the E. and W. center line of the NE 1/4 NW 1/4 of sec. 10. |
| 2.40 | Shallow wash, drains SW. |
| 10.032 | The NE-NW 1/64 sec. cor. of sec. 10. |
| 12.75 | Wash, 10 lks. wide, 1 ft. deep, drains WSW. |
| 20.064 | The C-N-NW 1/64 sec. cor. of sec. 10. |
| Subdivision of the NW 1/4 NW 1/4. | |
| | From the C-W-NW 1/64 sec. cor. of sec. 10. |
| | N. 0° 03' W., on the N. and S. center line of the NW 1/4 NW 1/4 of sec. 10. |
| 2.05 | Wash, 10 lks. wide, 2 ft. deep, drains W. |
| 10.015 | Point for the NW-NW 1/64 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the NW 1/4 NW 1/4 of sec. 10. |
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 14, 16, 17, and 19. |
| 18.50 | Wash, 10 lks. wide, 1 ft. deep, drains W. |
| 20.03 | The W-W 1/64 sec. cor. of secs. 3 and 10. |
| Subdivision of the NW 1/4 NW 1/4. | |
| | From the C-N-NW 1/64 sec. cor. of sec. 10. |
| | S. 89° 48' W., on the E. and W. center line of the NW 1/4 NW 1/4 of sec. 10. |
| 2.70 | Wash, 10 lks. wide, 1 ft. deep, drains WSW. |
| 10.03 | The NW-NW 1/64 sec. cor. of sec. 10. |
| 10.35 | Wash, 7 lks. wide, 1 ft. deep, drains WSW. |
| 20.06 | The N-N 1/64 sec. cor. of secs. 9 and 10. |

Subdivision of Section 10, T. 15 S., R. 12 E.

| Chains | Subdivision of the SE $\frac{1}{4}$ NW $\frac{1}{4}$. |
|--------|--|
| | From the C-E-W 1/64 sec. cor. of sec. 10. |
| | N. 0° 03' W., on the N. and S. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 10. |
| 7.20 | Wash, 15 lks. wide, 1 ft. deep, drains WNW. |
| 10.015 | Point for the SE-NW 1/64 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 10. |
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 42, 43, 54, and 55. |
| 18.70 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 20.03 | The C-E-NW 1/64 sec. cor. of sec. 10. |
| | From the C-S-N 1/64 sec. cor. of sec. 10. |
| | S. 89° 47' W., on the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 10. |
| 6.35 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 10.035 | The SE-NW 1/64 sec. cor. of sec. 10. |
| 20.063 | The C-S-NW 1/64 sec. cor. of sec. 10. |
| | Subdivision of the SW $\frac{1}{4}$ NW $\frac{1}{4}$. |
| | From the C-W-W 1/64 sec. cor. of sec. 10. |
| | N. 0° 03' W., on the N. and S. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 10. |
| 4.20 | Wash, 6 lks. wide, 1 ft. deep, drains WNW. |
| 10.016 | Point for the SW-NW 1/64 sec. cor. of sec. 10, at the intersection of the E. and W. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 10. |
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 46, 48, 49, and 51. |
| 19.45 | Wash, 6 lks. wide, 1 ft. deep, drains WNW. |
| 12.50 | Wash, drains NW. |
| 20.033 | The C-W-NW 1/64 sec. cor. of sec. 10. |
| | From the C-S-NW 1/64 sec. cor. of sec. 10. |
| | S. 89° 47' W., on the E. and W. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 10. |
| 2.30 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 7.65 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 8.90 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 10.034 | The SW-NW 1/64 sec. cor. of sec. 10. |
| 19.95 | Road, bears N. and S. |
| 20.067 | The S-N 1/64 sec. cor. of secs. 9 and 10. |
| | Subdivision of Section 14, T. 15 S., R. 12 E. |
| | From the $\frac{1}{4}$ sec. cor. of secs. 14 and 23. |
| | N. 0° 04' W., on the N. and S. center line of sec. 14. |

BOOK 4412

Subdivision of Section 14, T. 15 S., R. 12 E.

| | |
|--------|---|
| Chains | |
| 14.30 | Old road, bears E. and W. |
| 17.30 | Wash, 10 lks. wide, 1 ft. deep, drains WSW. |
| 24.25 | Wash 15 lks. wide, 1 ft. deep, drains NW. |
| 32.25 | Wash, 10 lks. wide, 1 ft. deep, drains SW. |
| 40.04 | Point for the C $\frac{1}{4}$ sec. cor. of sec. 14, at the intersection of the E. and W. center line. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. C $\frac{1}{4}$ S14 1953 Deposit a stone mkd. X at base of iron post. |
| 49.55 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 55.40 | Wash, 20 lks. wide, 4 ft. deep, drains WNW. |
| 57.20 | Wash, 6 lks. wide, 1 ft. deep, drains WNW. |
| 60.05 | Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 14. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. C N $\frac{1}{16}$ S14 C 1953 Deposit a stone mkd. X at base of iron post. |
| 70.055 | Point for the C-N-N $\frac{1}{64}$ sec. cor. of sec, 14. Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 4 and 5. |
| 80.06 | The $\frac{1}{4}$ sec. cor. of secs. 11 and 14. From the $\frac{1}{4}$ sec. cor. of secs. 13 and 14. S. 89° 50' W., on the E. and W. center line of sec. 14. |
| 1.60 | Wash, 10 lks. wide, 1 ft. deep, drains WNW. |
| 7.10 | Wash, 7 lks. wide, $1\frac{1}{2}$ ft. deep, drains WNW. |
| 8.60 | Wash, 5 lks. wide, $1\frac{1}{2}$ ft. deep, drains NW. |
| 17.70 | Wash, 10 lks. wide, 1 ft. deep, drains N. |
| 19.75 | Wash, 10 lks. wide, 1 ft. deep, drains NNW. |
| 20.074 | Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 14. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. E $\frac{1}{16}$ C ——— C S 14 1953 Deposit a stone mkd. X at base of iron post. |

BOOK 4412

Subdivision of Section 14, T. 15 S., R. 12 E.

| | |
|---|--|
| Chains | |
| 23.90 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 26.20 | Wash, 10 lks. wide, 1 ft. deep, drains N. |
| 37.00 | Wash, 10 lks. wide, 1 ft. deep, drains NW. |
| 40.148 | The C $\frac{1}{4}$ sec. cor. of sec. 14. |
| 44.60 | Wash, 15 lks. wide, 1 ft. deep, drains NNW. |
| 51.70 | Wash, 10 lks. wide, 1 ft. deep, drains NNE. |
| 60.00 | Wash, 10 lks. wide, 1 ft. deep, drains N. |
| 71.50 | Wash, 10 lks. wide, 1 ft. deep, drains NE. |
| 80.29 | The $\frac{1}{4}$ sec. cor. of secs. 14 and 15. |
| Subdivision of the NE $\frac{1}{4}$. | |
| From the C-E 1/16 sec. cor. of sec. 14. | |
| N. 0° 03' W., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 14. | |
| 1.65 | Shallow wash, drains NW. |
| 3.30 | Wash, 10 lks. wide, 1 ft. deep, drains W. |
| 8.00 | Wash, 25 lks. wide, 4 ft. deep, drains WNW. |
| 20.016 | Point for the NE 1/16 sec. cor. of sec. 14, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ of sec. 14. |
| | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. |
| NE 1/16 S14 | |
| 1953 | |
| Deposit a stone mkd. X at base of iron post. | |
| 21.15 | Shallow wash, 10 lks. wide, drains W. |
| 30.026 | Point for the C-N-NE 1/64 sec. cor. of sec. 14. |
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 1 and 8. |
| 31.45 | Shallow wash, 7 lks. wide, drains WSW. |
| 39.85 | Wash, 10 lks. wide, drains W. |
| 40.036 | The E 1/16 sec. cor. of secs. 11 and 14. |
| From the N 1/16 sec. cor. of secs. 13 and 14. | |
| S. 89° 50' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 14. | |
| 20.085 | The NE 1/16 sec. cor. of sec. 14. |
| 25.00 | Shallow wash, 6 lks. wide, drains WSW. |
| 30.125 | Point for the C-W-NE 1/64 sec. cor. of sec. 14. |
| | Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 6 and 7. |
| 38.70 | Shallow wash, 5 lks. wide, drains WNW. |

Subdivision of Section 14, T. 15 S., R. 12 E.

Chains

40.165 The C-N 1/16 sec. cor. of sec. 14.

Subdivision of the NW $\frac{1}{4}$ NE $\frac{1}{4}$.

From the C-W-NE 1/64 sec. cor. of sec. 14.

N. 0° 03' W., on the N. and S. center line of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 14.10.006 Point for the NW-NE 1/64 sec. cor. of sec. 14, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 14.

Set a wooden post, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 2, 3, 6, and 7.

11.45 Wash, 10 lks. wide, 1 ft. deep, drains W.

19.15 Shallow wash, 5 lks. wide, drains W.

20.015 The W-E 1/64 sec. cor. of secs. 11 and 14.

From the C-N-NE 1/64 sec. cor. of sec. 14

S. 89° 49' W., on the E. and W. center line of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 14.

3.50 A shallow wash, 5 lks. wide, drains SW.

5.40 A shallow wash, 7 lks. wide, drains SW.

10.042 The NW-NE 1/64 sec. cor. of sec. 14.

20.084 The C-N-N 1/64 sec. cor. of sec. 14.

General Description

The surface of sections 10 and 14 is nearly level and is covered with an undergrowth of greasewood, mesquite and cacti. The soil is a sandy loam. The general drainage is to the west and northwest through a number of shallow washes. There is a bladed road along the west boundary of section 10. The El Paso Natural Gas line enters section 10 on the east boundary of the NE $\frac{1}{4}$ NE $\frac{1}{4}$ and leaves on the north boundary at the east 1/16 corner. There is no improvements in either of the sections.

25

BOOK 4412

4-680
(Feb., 1960)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| NAMES | CAPACITY |
|------------------|--------------------------------|
| Charles C. Doak | Cartographic Survey Aid |
| Jesse A Livesay | " " |
| Paul O. Heath | Surveying and Cartographic Aid |
| Pasqual Martinez | " " |
| Oscar M. Ybarra | " " |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

24

BOOK 4412

CERTIFICATE OF CADASTRAL ENGINEER


I, Clarence E. Bilbray, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 29th October 1952
19th day of November, 1952

I have ~~surveyed~~ independently resurveyed the boundaries, and surveyed the subdivision
of sections 10 and 14, T. 15 S., R. 12 E.

of the Gila & Salt River Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Albuquerque, New Mexico

May 15, 1953



Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., AUG 11 1953, 19

The foregoing field notes of the ~~survey of~~ independent resurvey of the boundaries, and
survey of the subdivision of sections 10 and 14, T. 15 S., R. 12 E., of the Gila and
Salt River Meridian, Arizona

executed by Clarence E. Bilbray

having been critically examined and found correct, are hereby approved.



Assistant Chief, Division of Cadastral Engineering.

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in~~

~~, is a true copy of the original field notes.~~

~~Chief, Division of Cadastral Engineering.~~