

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BOOK 4415

FIELD NOTES

of the

Dependent Resurvey of the Boundaries

and

Survey of Subdivisional Lines of Sections 34 and 35,

Township 14 South, Range 12 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Clarence E. Bilbray, Cadastral Engineer

Under special instructions dated October 29th 52
November 19th, 1952, which provided
for the surveys included under Group No. 286, approved November 18, 1952
November 26, 1952
and assignment instructions dated December 1, 1952

Survey commenced February 20, 19 53.

Survey completed March 6, 19 53.

4415

4415

BOOK 4415

INDEX DIAGRAM

Township 14 S, Range 12 E

6	5	4	3	2	1																				
7	8	9	10	11	12																				
18	17	16	15	14	13																				
19	20	21	22	23	24																				
30	29	28	27	26	25																				
31	32	33	<table border="1"> <tr> <td>10</td> <td>9</td> <td>9</td> <td>7</td> </tr> <tr> <td>5</td> <td>21</td> <td>11</td> <td>12</td> </tr> <tr> <td>22</td> <td>21</td> <td>13</td> <td>12</td> </tr> <tr> <td>5</td> <td>20</td> <td>10</td> <td>11</td> </tr> <tr> <td>4</td> <td>3</td> <td>2</td> <td>1</td> </tr> </table>	10	9	9	7	5	21	11	12	22	21	13	12	5	20	10	11	4	3	2	1	6	36
10	9	9	7																						
5	21	11	12																						
22	21	13	12																						
5	20	10	11																						
4	3	2	1																						

- Subdivision NE $\frac{1}{4}$ Sec. 35 ----- 13
- Subdivision NE $\frac{1}{4}$ NE $\frac{1}{4}$ Sec. 35 ----- 14
- Subdivision NW $\frac{1}{4}$ NE $\frac{1}{4}$ Sec. 35 ----- 14
- Subdivision SW $\frac{1}{4}$ NE $\frac{1}{4}$ Sec. 35 ----- 15
- Subdivision SE $\frac{1}{4}$ NE $\frac{1}{4}$ Sec. 35 ----- 15
- Subdivision SE $\frac{1}{4}$ Sec. 35 ----- 16
- Subdivision NE $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 35 ----- 17
- Subdivision NW $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 35 ----- 18
- Subdivision SW $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 35 ----- 19
- Subdivision SE $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 35 ----- 20
- Subdivision SE $\frac{1}{4}$ Sec. 34 ----- 23
- Subdivision NW $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 34 ----- 24
- Subdivision SW $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 34 ----- 25
- Subdivision SE $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 34 ----- 26
- Subdivision SW $\frac{1}{4}$ Sec. 34 ----- 26
- Subdivision NE $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 34 ----- 28
- Subdivision NW $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 34 ----- 28
- Subdivision SW $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 34 ----- 29
- Subdivision SE $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 34 ----- 29

T. 14 S., R. 12 E.

The south boundary of T. 14 S., R. 12 E. was originally surveyed by J. F. Hesse in 1915. The west 5 miles of the south boundary was retraced by W. H. Thorn and O. O. Gould in 1925-1926. The subdivisional lines was surveyed by Thorn and Gould in 1926. Thorn and Gould also resurveyed the north, east and west boundaries of the township.

The survey was executed with a light mountain solar transit made by W. and L. E. Gurley, Serial No, 371540, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition and having been placed in satisfactory adjustment prior to the beginning of the survey, was tested and found free from appreciable error.

The measurements were made with a narrow steel tape, 5 chains in length, graduated to tenths of a link for the first ten links, every link for the remainder of the first 100 links, and at each 10 link interval for the remaining 400 links. The tape was tested by comparison with a standard 1 chain steel tape and found correct. The measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The directions of all lines were determined by transit method, with azimuth obtained from U. S. Coast and Geodetic survey triangulation station "Snyder's Hill" which is located in the NW $\frac{1}{4}$ of section 3, T. 15 S., R. 12 E. All bearings were adjusted for differences in longitude between stations.

The geographic position of the southeast corner of section 35, T. 14 S., R. 12 E., as computed from a tie to U. S. Coast and Geodetic survey triangulation station "Snyder's Hill", is Latitude 32° 09' 45" N., Longitude 111° 04' 45" W.

Dependent Resurvey Portion of South Boundary, T. 14 S., R. 12 E.

(Reestablishment of the Survey Executed by)
(J. F. Hesse, Cadastral Engineer, in 1915)

Beginning at the corner of secs. 35 and 36, T. 14 S., R. 12 E. which is monumented with an iron post, 3 ins. diam., 12 ins. above ground, (in newly constructed road) marked as described in the official record.

Reset the iron post, 6 ins. below surface of road.

from which

An iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 75 lks. dist., with brass cap mkd. T14S R12E S36 RM 1953 and an arrow pointing to the true corner.

An iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 75 lks. dist., with brass cap mkd. T14S R12E S35 RM 1953 and an arrow pointing to the true corner.

S. 89° 39' W., on the S. bdy. of sec. 35, T. 14 S., R. 12 E.

Over nearly level land, along N. side of road.

2.085 The closing corner of secs. 1 and 2, T. 15 S., R. 12 E.

5.006 Point for the E-E-E 1/256 sec. cor. of sec. 35, T. 14 S., R. 12 E., falls on N. side of road, set. nail for cor. lots 69 and 70

Dependent Resurvey Portion of South Boundary, T. 14 S., R. 12 E.

Chains	from which
	A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears N. 0° 08' E., 30 lks. dist., marked for lots 69 and 70.
10.012	Point for the E-E 1/64 sec. cor. of sec. 35, T. 14 S., R. 12 E., falls on N. side of road, set nail.
	from which
	A wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, bears N. 0° 08' E., 30 lks. dist., marked for lots 68 and 69.
15.018	Point for the W-E-E 1/256 sec. cor. of sec. 35, T. 14 S., R. 12 E., falls on N. side of road, set nail.
	from which
	A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears N. 0° 07' E., 30 lks. dist., marked for lots 67 and 68.
20.024	Point for the E 1/16 sec. cor. of sec. 35, T. 14 S., R. 12 E., falls on N. side of road.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<u>E 1/16 S35</u> 1953
	Deposit a stone, mkd. X at base of iron post.
22.07	Intersection of roads, which bear N., S., E. and W.
25.03	Point for the E-W-E 1/256 sec. cor. of sec. 35, T. 14 S., R. 12 E., falls on N. side of road, set nail. Set a wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, marked for lots 65 and 66.
30.036	Point for the W-E 1/64 sec. cor. of sec. 35, T. 14 S., R. 12 E., falls on N. side of road, set nail
	from which
	A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears N. 0° 07' E., 30 lks. dist., marked for lots 64 and 65.
35.042	Point for the W-W-E 1/256 sec. cor. of sec. 35, T. 14 S., R. 12 E., falls on N. side of road, set nail.
	from which
	A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears N. 0° 07' E., 30 lks. dist., marked for lots 63 and 64.
40.048	The $\frac{1}{4}$ sec. cor. of sec. 35, T. 14 S., R. 12 E., which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.
	—————
	S. 89° 41' W., beginning new measurement.
2.10	Intersection of roads, which bear N., S., E. and W.

Dependent Resurvey Portion of South Boundary, T. 14 S., R. 12 E.

Chains	
4.60	Wash, 10 lks. wide, 2 ft. deep, drains SW.
12.65	Wash, 10 lks. wide, 2 ft. deep, drains SW.
22.10	Intersection of roads, which bear N., E. and W.
39.80	Intersection of roads, which bear N., E. and W.
40.05	The corner of secs. 34 and 35, T. 14 S., R. 12 E., which is monumented with an iron post, 3 ins. diam., set and marked as described in the official record.
	Land, nearly level. Soil, sandy. No timber; undergrowth, greasewood, mesquite and cacti.
	S. 89° 41' W., on the S. bdy. of sec. 34.
	Over nearly level land, along N. side of road.
2.00	Road, bears S. and E.
2.278	The closing corner of secs. 2 and 3, T. 15 S., R. 12 E.
5.007	Point for the E-E-E 1/256 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked E-E-E 1/256.
9.20	Wash, 10 lks. wide, 1 ft. deep, drains WSW.
10.014	Point for the E-E 1/64 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked E-E 1/64
11.90	Telephone line, bears ENE. and WSW.
13.555	Center line of Ajo Highway, on curve, set nail ^{for} cor. lots 66 and 68.
15.021	Point for the W-E-E 1/256 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 65 and 66.
16.90	Wash, 30 lks. wide, 4 ft. deep, drains SW.
20.028	Point for the E 1/16 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. E 1/16 S34 1953 Bury a stone mkd. X at base of iron post.
24.90	Wash, 10 lks. wide, 2 ft. deep, drains SW.
25.035	Point for the E-W-E 1/256 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 63 and 64.
30.042	Point for the W-E 1/64 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 62 and 63.

Dependent Resurvey Portion of South Boundary, T. 14 S., R. 12 E.

Chains	
34.90	Phone line, bears N. and S.
35.049	Point for the W-W-E 1/256 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 61 and 62.
39.25	Bladed road, bears N. and S.
40.056	The $\frac{1}{4}$ sec. cor. of sec. 34, T. 14 S., R. 12 E., which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

	S. 89° 41' W., beginning new measurement.
0.30	Wash, 10 lks. wide, 3 ft. deep, drains WSW.
2.369	Point for the $\frac{1}{4}$ sec. cor. of sec. 3, T. 15 S., R. 12 E., at proportionate distance. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

	$\frac{1}{4}$ S 3 1953
5.009	Point for the E-E-W 1/256 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 59 and 60.
10.018	Point for the E-W 1/64 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 58 and 59.
15.027	Point for the W-E-W 1/256 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 57 and 58.
17.80	Power line, bears NE. and SW.
20.036	Point for the W 1/16 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

	W 1/16 S34 1953
	Deposit a stone 3x3x4 ins., mkd. X alongside the iron post.
25.045	Point for the E-W-W 1/256 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 55 and 56.
30.054	Point for the W-W 1/64 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 54 and 55.
35.063	Point for the W-W-W 1/256 sec. cor. of sec. 34, T. 14 S., R. 12 E. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 53 and 54.
40.072	The corner of secs. 33 and 34, T. 14 S., R. 12 E., which is monumented with an iron post, 3 ins. diam., marked and witnessed as

Dependent Resurvey Portion of South Boundary, T. 14 S., R. 12 E.

Chains

described in the official record.

From this corner U. S. Coast and Geodetic survey triangulation station "Snyder's Hill", bears S. 0° 26' W., 24.34 chs. dist.

Land, nearly level.

Soil, sandy.

Undergrowth, greasewood, mesquite and cacti.

Dependent Resurvey of a Portion of Subdivision, T. 14 S., R. 12 E.

(Reestablishment of the Survey Executed by
(W. H. Thorn and O. O. Gould in 1926)

From the corner of secs. 33 and 34, on the S. bdy of the Tp.

North, bet. secs. 33 and 34.

Over nearly level land, through undergrowth.


11.111 Point for the S-S 1/64 sec. cor. of secs. 33 and 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 52 and 53.

15.80 Wash, 15 lks. wide, 2 ft. deep, drains SW.

21.103 Point for the S 1/16 sec. cor. of secs. 33 and 34, at proportionate distance.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a stone, mkd. X at base of iron post.

30.00 Shallow wash, drains SW.

31.095 Point for the N-S 1/64 sec. cor. of secs. 33 and 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 20 and 21.

34.10 Shallow wash, drains SSW.

41.087 The 1/4 sec. cor. of secs. 33 and 34, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

N. 0° 04' E., beginning new measurement.

1.40 Old road, bears NE. and SW.

6.90 Same road, bears SE. and N. along line.

17.70 Wash, 10 lks. wide, 1 ft. deep, drains SW.

19.60 Wash, 20 lks. wide, 1-ft. deep, drains SW.

26.80 Wash, 5 lks. wide, 2 ft. deep, drains SW.

39.25 Wash, 20 lks. wide, 3 ft. deep, drains WSW.

39.982 The corner of secs. 27, 28, 33, and 34, (falls in road) which is monumented with an iron post, 2 ins. diam., 12 ins. below surface of road, (Reset by County during road construction) marked as described in the official record.

Dependent Resurvey of a Portion of Subdivision, T. 14 S., R. 12 E.

Chains	from which
	<p>An iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 75 lks. dist., with brass cap mkd. T14S R12E S27 RM 1953 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° W., 75 lks. dist., with brass cap mkd. T14S R12E S33 RM 1953 and an arrow pointing to the true corner.</p> <p>Land, nearly level. Soil, sandy. No timber; undergrowth, greasewood, mesquite and cacti.</p>
	<p>From the corner of secs. 35 and 36, on the S. bdy. of the Tp. N. $0^{\circ} 08'$ E., bet. secs. 35 and 36. Over nearly level land, through undergrowth.</p>
0.50	Power line, bears E. and W.
10.184	Point for the S-S $1/64$ sec. cor. of secs. 35 and 36. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 55 and 70.
13.65	Power line, bears NE. and SW.
20.17	Point for the S $1/16$ sec. cor. of secs. 35 and 36, at proportionate distance. Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	Deposit a stone, mkd. X at base of iron post.
22.60	Wash, 10 lks. wide, 2 ft. deep, drains SW.
23.70	Wash, 15 lks. wide, 2 ft. deep, drains SW.
30.156	Point for the N-S $1/64$ sec. cor. of secs. 35 and 36. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked N-S $1/64$.
33.70	Telephone line, bears N. 72° E. and S. 72° W.
33.73	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lot 54.
34.73	Center line of Ajo Highway, bears N. $72^{\circ} 02'$ E. and S. $72^{\circ} 02'$ W., cor. lots 37 and 54, set nail.
35.73	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lot 37.
40.142	The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, which is monumented with an iron post, $\frac{1}{4}$ in. diam., set and marked as described in the official record. N. $0^{\circ} 08'$ E., beginning new measurement.

Dependent Resurvey of a Portion of Subdivision, T. 14 S., R. 12 E.

Chains	
10.049	<p>Point for the S-N 1/64 sec. cor. of secs. 35 and 36.</p> <p>Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 21 and 36.</p>
20.098	<p>Point for the N 1/16 sec. cor. of secs. 35 and 36, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <p>S35 S36</p> <p>1953</p> </div> <p>Deposit a stone, mkd. X at base of iron post.</p>
30.147	<p>Point for the N-N 1/64 sec. cor. of secs. 35 and 36.</p> <p>Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 5 and 20.</p>
34.65	<p>Wash, 10 lks. wide. 1 ft. deep; drains SSW.</p>
36.90	<p>Wash, 15 lks. wide, 1 ft. deep, drains SSW.</p>
40.196	<p>The corner of secs. 25, 26, 35; and 36, (falls in road) which is monumented with an iron post, 2 ins. diam., 12 ins. below surface of road, (reset by the County during road construction) marked as described in the official record.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins in the ground, for a reference monument, bears N. 45° E., 75 lks. dist., with brass cap mkd. T14S R12E S25 RM 1953 and an arrow pointing to the true corner.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° W., 75 lks. dist., with brass cap mkd. T14S R12E S35 RM 1953 and an arrow pointing to the true corner.</p> <p>Land, nearly level. Soil, sandy. No timber; undergrowth; greasewood, mesquite and cacti.</p>
	<p>S. 89° 59' W., bet. secs. 26 and 35.</p> <p>Along a newly constructed road.</p>
5.011	<p>Point for the E-E-E 1/256 sec. cor. of secs. 26 and 35, falls in road, set nail.</p> <p>from which</p> <p style="padding-left: 40px;">A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears S. 0° 08' W., 45 lks. dist., marked for lots 5 and 6.</p>
10.022	<p>Point for the E-E 1/64 sec. cor. of secs. 26 and 35, falls in road, set nail</p> <p>from which</p> <p style="padding-left: 40px;">A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears S. 0° 08' W., 45 lks. dist., marked for lots 6 and 7.</p>

Dependent Resurvey of a Portion of Subdivision, T. 14 S., R. 12 E.

Chains 15.033	Point for the W-E-E 1/256 sec. cor. of secs. 26 and 35, falls in road, set nail. from which A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins in the ground, for a reference, bears S. 0° 08' W., 45 lks. dist., marked for lots 7 and 8.						
20.044	Point for the E 1/16 sec. cor. of secs. 26 and 35, falls in road. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 34 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">E 1/16</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 26</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">S 35</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">1953</td> </tr> </table> </div> from which An iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 50 lks. dist., with brass cap mkd. E 1/16 S26 RM 1953 and an arrow pointing to the true corner. An iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., set 24 ins in the ground, for a reference monument, bears South, 50 lks. dist., with brass cap mkd. E 1/16 S35 RM 1953 and an arrow pointing to the true corner.	E 1/16	S 26		S 35		1953
E 1/16	S 26						
	S 35						
	1953						
24.70	Power line, bears NE. and SW.						
25.055	Point for the E-W-E 1/256 sec. cor. of secs. 26 and 35, falls in road, set nail. from which A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears S. 0° 07' W., 45 lks. dist., marked for lots 9 and 10.						
30.066	Point for the W-E 1/64 sec. cor. of secs. 26 and 35, falls in road, set nail. from which A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears S. 0° 07' W., 45 lks. dist., marked for lots 10 and 11.						
35.077	Point for the W-W-E 1/256 sec. cor. of secs. 26 and 35, falls in road, set nail. from which A wooden stake, 2 ft. long, 2 ins. sq., set 12 ins. in the ground, for a reference, bears S. 0° 07' W., 45 lks. dist., marked for lots 11 and 12.						
40.088	The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, (falls in road) which is monumented with an iron post, 1 in. diam., 12 ins. below surface of road, (reset by the County during road construction) marked as described in the official record. from which An iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., set 24 ins in the ground, for a reference monument, bears North, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S26 RM 1953 and an arrow pointing to the true corner						

Dependent Resurvey of a Portion of Subdivision, T. 14 S., R. 12 E.

Chains	<p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears South, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S35 RM 1953 and an arrow pointing to the true corner.</p>
	<p>S. 89° 59' W., beginning new measurement.</p>
9.70	Wash, 10 lks. wide, 3 ft. deep, drains SSW.
17.30	Wash, 20 lks. wide, 2 ft. deep, drains SSW.
18.70	Old road, bears NE. and SW.
20.00	Wash, 10 lks. wide, 1 ft. deep, drains SSW.
24.50	Wash, 20 lks. wide, 1 ft. deep, drains S.
38.30	Wash, 10 lks. wide, 1 ft. deep, drains SSW.
40.11	<p>The corner of secs. 26, 27, 34, and 35, (falls in road) which is monumented with an iron post, 2 ins. diam., 12 ins. below the surface of the road, (reset by the County during road construction) marked as described in the official record.</p> <p>from which</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 75 lks. dist., with brass cap mkd. T14S R12E S26 RM 1953 and an arrow pointing to the true corner.</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° W., 75 lks. dist., with brass cap mkd. T14S R12E S34 RM 1953 and an arrow pointing to the true corner.</p> <p>Land, nearly level. Soil, sandy. No timber; undergrowth, greasewood, mesquite and cacti.</p>
	<p>S. 89° 54' W., bet. secs. 27 and 34.</p> <p>Along a newly constructed road.</p>
8.25	Wash, 20 lks. wide, 2 ft. deep, drains SW.
13.65	Wash, 20 lks. wide, 2 ft. deep, drains S.
15.60	Old road, bears NE. and SW.
20.10	Wash, 10 lks. wide, 1 ft. deep, drains SSE.
26.00	Wash, 10 lks. wide, 1 ft. deep, drains SSW.
34.20	Wash, 20 lks. wide, 2 ft. deep, drains SW.
38.20	Wash, 10 lks. wide, 2 ft. deep, drains SW.
40.08	<p>The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, (falls in road) which is monumented with an iron post, 1 in. diam., 12 ins. below the surface of the road, (reset by the County during road construction) marked as described in the official record.</p> <p>From which</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S27 RM 1953 and an arrow pointing to the true corner.</p>

Dependent Resurvey of a Portion of Subdivision, T. 14 S., R. 12 E.

Chains	
	<p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears South, 50 lks. dist., with brass cap mkd. $\frac{1}{4}$ S34 RM 1953 and an arrow pointing to the true corner.</p>
	<p>S. $89^{\circ} 56'$ W., beginning new measurement.</p>
7.20	Wash, 20 lks. wide, 4 ft. deep, drains SSW.
25.10	Wash, 20 lks. wide, 3 ft. deep, drains SW.
31.40	Wash, 10 lks. wide, 2 ft. deep, drains SW.
40.08	The corner of secs. 27, 28, 33, and 34.
	<p>Land, nearly level . Soil, sandy. No timber; undergrowth, greasewood, mesquite and cacti.</p>
	<p>From the corner of secs. 34 and 35, on the S. bdy. of the Tp. N. $0^{\circ} 07'$ E., bet. secs. 34 and 35. Over nearly level land, through undergrowth.</p>
2.10	Wash, 10 lks. wide, 1 ft. deep, drains W.
7.442	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lot 68.
7.60	Telephone line, bears NE. and SW.
8.442	Center line of Ajo Highway, bears N. $63^{\circ} 49'$ E. and S. $60^{\circ} 02'$ W., cor. lots 68 and 69, set nail.
9.442	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lot 69.
10.832	Point for the S-S $1/64$ sec. cor. of secs. 34 and 35.
	<p>Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 37 and 69.</p>
11.35	Wash, 30 lks. wide, 2 ft. deep, drains W.
20.826	Point for the S $1/16$ sec. cor. of secs. 34 and 35, at proportionate distance.
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S $1/16$ S34 S35 1953</p>
	<p>Deposit a stone, mkd. X at base of iron post.</p>
30.82	Point for the N-S $1/64$ sec. cor. of secs. 34 and 35.
	<p>Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 5 and 36.</p>
40.10	Wash, 10 lks. wide, 2 ft. deep, drains WSW.
40.814	The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record,

Dependent Resurvey of a Portion of Subdivision, T. 14 S., R. 12 E.

Chains

N. 0° 01' E., beginning new measurement.

0.25 Power line, bears NE. and SW.

30.00 Shallow wash, drains WSW.

39.962 The corner of secs. 26, 27, 34, and 35.

Land, nearly level.

Soil, sandy.

No timber; undergrowth, greasewood, mesquite and cacti.

Subdivision of Section 35, T. 14 S., R. 12 E.

From the $\frac{1}{4}$ sec. cor. of sec. 35, on the S. bdy. of the Tp.

N. 0° 07' E., on the N. and S. center line of sec. 35.

Over nearly level land, through undergrowth.


5.00 Wash, 10 lks. wide, 1 ft. deep, drains SW.

8.05 Shallow wash, drains SW.

10.51 Point for the C-S-S $1/64$ sec. cor. of sec. 35.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 62 and 63.

15.40 Shallow wash, drains SW.

20.502 Point for the C-S $1/16$ sec. cor. of sec. 35.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Deposit a stone, mkd. X at base of iron post.

21.00 Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lot 47.

21.25 Telephone line, bears N. 72° E., and S. 72° W.

22.00 Center line of Ajo Highway, bears N. 72° 02' E. and S. 72° 02' W., cor. lots 45 and 47, set nail.

23.00 Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lot 45.

23.90 Wash, 10 lks. wide, 3 ft. deep, drains S. 70° W.

30.494 Point for the C-N-S $1/64$ sec. cor. of sec. 35.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 44 and 45.

40.486 Point for the C $\frac{1}{4}$ sec. cor. of sec. 35, at the intersection of the E. and W. center line of sec. 35.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.C $\frac{1}{4}$ S35
1953

Subdivision of Section 35, T. 14 S., R. 12 E.

Chains

- Deposit a stone, mkd. X at base of iron post.
- 50.508 Point for the C-S-N $1/64$ sec. cor. of sec. 35.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 28 and 29.
- 60.53 Point for the C-N $1/16$ sec. cor. of sec. 35.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- C
N 1/16 S 35
C
1953
- Deposit a stone, mkd. X at base of iron post.
- 70.552 Point for the C-N-N $1/64$ sec. cor. of sec. 35.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 12 and 13.
- 80.574 The $\frac{1}{4}$ sec. cor. of secs. 26 and 35.
-
- From the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.
N. 89° 51' W., on the E. and W. center line of sec. 35.
Over nearly level land, through undergrowth.
- 5.008 Point for the C-E-E-E $1/256$ sec. cor. of sec. 35.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 35, 36, 37, and 38.
- 10.016 Point for the C-E-E $1/64$ sec. cor. of sec. 35.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 34, 35, 38, and 39.
- 15.024 Point for the C-W-E-E $1/256$ sec. cor. of sec. 35.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 33, 34, 39, and 40.
- 20.032 Point for the C-E $1/16$ sec. cor. of sec. 35.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- E 1/16
C ——— C
S 35
1953
- Deposit a stone, mkd. X at base of iron post.
- 25.04 Point for the C-E-W-E $1/256$ sec. cor. of sec. 35.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 31, 32, 41, and 42.
- 30.048 Point for the C-W-E $1/64$ sec. cor. of sec. 35.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 30, 31, 42, and 43.

Subdivision of Section 35, T. 14 S., R. 12 E.

Chains	
35.056	Point for the C-W-W-E 1/256 sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 29, 30, 43, and 44.
40.064	The C $\frac{1}{4}$ sec. cor. of sec. 35.
80.11	The $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
Subdivision of the NE $\frac{1}{4}$.	
	From the C-E 1/16 sec. cor. of sec. 35. N. 0° 07' E., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 35.
10.035	Point for the C-S-NE 1/64 sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 24, 25, 32, and 33.
13.60	Shallow wash, drains WSW.
20.07	Point for the NE 1/16 sec. cor. of sec. 35, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ of sec. 35. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.. NE 1/16 S35 1953
23.25	Wash, 5 lks. wide, 1 ft. deep, drains WSW.
30.105	Point for the C-N-NE 1/64 sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 8, 9, 16, and 17.
40.14	The E 1/16 sec. cor. of secs. 26 and 35.
	From the N 1/16 sec. cor. of secs. 35 and 36. N. 89° 56' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 35.
4.70	Wash, 10 lks. wide, 1 ft. deep, drains SW.
5.009	Point for the C-E-E-NE 1/256 sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 19, 20, 21, and 22.
10.018	Point for the C-E-NE 1/64 sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 18, 19, 22, and 23,
13.40	Wash, 10 lks. wide, 1 ft. deep, drains SSW.
15.027	Point for the C-W-E-NE 1/256 sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 17, 18, 24, and 23.
20.036	The NE 1/16 sec. cor. of sec. 35.
24.70	Wash, 5 lks. wide, 1 ft. deep, drains SW.
25.045	Point for the C-E-W-NE 1/256 sec. cor. of sec. 35.

Subdivision of Section 35, T. 14 S., R. 12 E.

Chains

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 15, 16, 25, and 26.

30.054 Point for the C-W-NE $1/64$ sec. cor. of sec. 35.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 14, 15, 26, and 27.

35.063 Point for the C-W-W-NE $1/256$ sec. cor of sec. 35.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 13, 14, 27, and 28.

40.072 The C-N $1/16$ sec. cor. of sec. 35.

Subdivision of the NE $1/4$ NE $1/4$

From the C-E-NE $1/64$ sec. cor. of sec. 35.

N. $0^{\circ} 08'$ E., on the N. and S. center line of the NE $1/4$ NE $1/4$ of sec. 35.

4.95 Wash, 15 lks. wide, 1 ft. deep, drains SW.

10.036 Point for the NE-NE $1/64$ sec. cor. of sec. 35, at the intersection of the E. and W. center line of the NE $1/4$ NE $1/4$ of sec. 35.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 6, 7, 18, and 19.

20.083 The E-E $1/64$ sec. cor. of secs. 26 and 35.

From the N-N $1/64$ sec. cor. of secs. 35 and 36.

N. $89^{\circ} 57'$ W., on the E. and W. center line of the NE $1/4$ NE $1/4$ of sec. 35.

3.10 Wash, 15 lks. wide. 1 ft. deep, drains SW.

5.012 Point for the C-E-NE-NE $1/256$ sec. cor. of sec. 35.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 5, 6, 19, and 20.

5.35 Wash, 10 lks. wide, 1 ft. deep, drains SW.

10.024 The NE-NE $1/64$ sec. cor. of sec. 35.

11.75 Wash, 10 lks. wide, 1 ft. deep, drains SSW.

15.033 Point for the C-W-NE-NE $1/256$ sec. cor. of sec. 35.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 7, 8, 17, and 18.

16.25 Wash, 15 lks. wide, 1 ft. deep, drains SSW.

20.042 The C-N-NE $1/64$ sec. cor. of sec. 35.

Subdivision of the NW $1/4$ NE $1/4$

From the C-W-NE $1/64$ sec. cor. of sec. 35.

N. $0^{\circ} 07'$ E., on the N. and S. center line of the NW $1/4$ NE $1/4$ of sec. 35.

10.026 Point for the NW-NE $1/64$ sec. cor. of sec. 35, at the intersection of the E. and W. center line of the NW $1/4$ NE $1/4$ of sec. 35.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 10, 11, 14 and 15.

Subdivision of Section 35, T. 14 S., R. 12 E.

Chains	
20.057	The W-E $1/64$ sec. cor. of secs. 26 and 35.
	From the C-N-NE $1/64$ sec. cor. of sec. 35.
	N. $89^{\circ} 57'$ W., on the E. and W. center line of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 35.
5.012	Point for the C-E-NW-NE $1/256$ sec. cor. of sec. 35.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 9, 10, 15, and 16.
5.65	Wash, 10 lks. wide, 1 ft. deep, drains SSE.
10.025	The NW-NE $1/64$ sec. cor. of sec. 35.
14.40	Wash, 10 lks. wide, 1 ft. deep, drains SW.
15.034	Point for the C-W-NW-NE $1/256$ sec. cor. of sec. 35.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 11, 12, 13, and 14.
20.043	The C-N-N $1/64$ sec. cor. of sec. 35.
	Subdivision of the SW $\frac{1}{4}$ NE $\frac{1}{4}$.
	From the C-W-E $1/64$ sec. cor. of sec. 35.
	N. $0^{\circ} 07'$ E., on the N. and S. center line of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 35.
10.03	Point for the SW-NE $1/64$ sec. cor. of sec. 35, at the intersection of the E. and W. center line of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 35.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 26, 27, 30, and 31.
20.06	The C-W-NE $1/64$ sec. cor. of sec. 35.
	From the C-S-NE $1/64$ sec. cor. of sec. 35.
	N. $89^{\circ} 54'$ W., on the E. and W. center line of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 35.
5.009	Point for the C-E-SW-NE $1/256$ sec. cor. of sec. 35.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 25, 26, 31, and 32.
6.40	Wash, 10 lks. wide, 1 ft. deep, drains SSE.
10.016	The SW-NE $1/64$ sec. cor. of sec. 35.
15.027	Point for the C-W-SW-NE $1/256$ sec. cor. of sec. 35.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 27, 28, 29, and 30.
17.20	Wash, 10 lks. wide, 1 ft. deep, drains SW.
20.035	The C-S-N $1/64$ sec. cor. of sec. 35.
	Subdivision of the SE $\frac{1}{4}$ NE $\frac{1}{4}$.
	From the C-E-E $1/64$ sec. cor. of sec. 35.
	N. $0^{\circ} 08'$ E., on the N. and S. center line of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 35.

Subdivision of Section 35, T. 14 S., R. 12 E.

Chains	
10.043	Point for the SE-NE $\frac{1}{64}$ sec. cor. of sec. 35, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 35. Set a wooden stake, .2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 22, 23, 34, and 35.
14.85	Wash, 10 lks. wide, 1 ft. deep, drains SW.
18.75	Wash, 10 lks. wide, 1 ft. deep, drains SW.
20.082	The C-E-NE $\frac{1}{64}$ sec. cor. of sec. 35. From the S-N $\frac{1}{64}$ sec. cor. of secs. 35 and 36. N. 89° 54' W., on the E. and W. center line of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 35.
5.009	Point for the C-E-SE-NE $\frac{1}{256}$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 21, 22, 35, and 36.
9.50	Wash, 10 lks. wide, 1 ft. deep, drains SW.
10.018	The SE-NE $\frac{1}{64}$ sec. cor. of sec. 35.
11.90	Wash, 10 lks. wide, 1 ft. deep, drains SSW.
15.027	Point for the C-W-SE-NE $\frac{1}{256}$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 23, 24, 33, and 34.
15.30	Wash, 10 lks. wide, 1 ft. deep, drains SW.
20.036	The C-S-NE $\frac{1}{64}$ sec. cor. of sec. 35. Subdivision of the SE $\frac{1}{4}$. From the E $\frac{1}{16}$ sec. cor. of sec. 35, on the S. bdy. of the Tp. N. 0° 07' E., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 35.
8.10	Wash, 5 lks. wide, 3 ft. deep, drains SW.
10.348	Point for the C-S-SE $\frac{1}{64}$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 58, 59, 66, and 67.
15.85	Wash, 10 lks. wide, 1 ft. deep, drains WSW.
17.60	Wash, 10 lks. wide, 1 ft. deep, drains WSW.
20.336	Point for the SE $\frac{1}{16}$ sec. cor. of sec. 35, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$ of sec. 35. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. SE $\frac{1}{16}$ S35 1953 Deposit a stone, mkd. X at base of iron post.
27.36	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lots 50 and 51.
28.36	Center line of Ajo Highway, bears N. 72° 02' E. and S. 72° 02' W., cor. lots 40, 48, 50, and 51, set nail.

BOOK 4415

Subdivision of Section 35, T. 14 S., R. 12 E.

Chains	
29.36	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lots 40 and 48.
30.324	Point for the C-N-SE $1/64$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 40, 41, and 48.
31.00	Wash, 10 lks. wide, 3 ft. deep, drains WSW.
40.312	The C-E $1/16$ sec. cor. of sec. 35.
From the S $1/16$ sec. cor. of secs. 35 and 36. N. $89^{\circ} 52'$ W., on the E. and W. center line of the SE $1/4$ of sec. 35.	
5.007	Point for the C-E-E-SE $1/256$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 53, 54, 55, and 56.
10.013	Point for the C-E-SE $1/64$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 52, 53, 56, and 57.
14.10	Wash, 10 lks. wide, 1 ft. deep, drains SW.
15.02	Point for the C-W-E-SE $1/256$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 51, 52, 57, and 58.
20.026	The SE $1/16$ sec. cor. of sec. 35.
22.15	Road, bears N. and S.
25.032	Point for the C-E-W-SE $1/256$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 49, 50, 59, and 60.
25.60	Wash, 10 lks. wide, 1 ft. deep, drains SW.
30.039	Point for the C-W-SE $1/64$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 47, 49, 60, and 61.
34.35	Old road, bears NE. and SW.
35.045	Point for the C-W-W-SE $1/256$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 47, 61, and 62.
40.052	The C-S $1/16$ sec. cor. of sec. 35.
Subdivision of the NE $1/4$ SE $1/4$.	
From the C-E-SE $1/64$ sec. cor. of sec. 35. N. $0^{\circ} 08'$ E., on the N. and S. center line of the NE $1/4$ SE $1/4$ of sec. 35.	
2.10	Wash, 20 lks. wide, 2 ft. deep, drains SW.
9.988	Point for the NE-SE $1/64$ sec. cor. of sec. 35, at the intersection of the E. and W. center line of the NE $1/4$ SE $1/4$ of sec. 35 Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground,

Subdivision of Section 35, T. 14 S., R. 12 E.

Chains	
	marked NE-SE $1/64$, on line bet. lots 52 and 53.
10.294	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lots 52 and 53.
10.56	Telephone line, bears N. 72° E. and S. 72° W.
11.294	Center line of Ajo Highway, bears N. $72^{\circ} 02'$ E. and S. $72^{\circ} 02'$ W., cor. lots 38, 39, 52, and 53, set nail.
12.294	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lots 38 and 39.
13.95	Wash, 10 lks. wide, 2 ft. deep, drains WSW.
19.973	The C-E-E $1/64$ sec. cor. of sec. 35.
	From the N-S $1/64$ sec. cor. of sec. 35 and 36.
	N. $89^{\circ} 51'$ W., on the E. and W. center line of the NE-SE $1/4$ of sec. 35.
2.30	Road, bears N. and S.
5.007	Point for the C-E-NE-SE $1/256$ sec. cor. of sec. 35.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-E-NE-SE $1/256$, on line bet. lots 53 and 54.
10.015	The NE-SE $1/64$ sec. cor. of sec. 35.
11.70	Telephone line, bears N. 72° E. and S. 72° W.
14.012	Center line of Ajo Highway, bears N. $72^{\circ} 02'$ E. and S. $72^{\circ} 02'$ W., set nail.
15.022	Point for the C-W-NE-SE $1/256$ sec. cor. of sec. 35.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked C-W-NE-SE $1/256$, on line bet. lots 39 and 40.
20.028	The C-N-SE $1/64$ sec. cor. of sec. 35.
	Subdivision of the NW-SE $1/4$.
	From the C-W-SE $1/64$ sec. cor. of sec. 35.
	N. $0^{\circ} 07'$ E., on the N. and S. center line of the NW-SE $1/4$ of sec. 35.
3.767	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lots 47 and 49.
4.02	Telephone line, bears N. 72° E. and S. 72° W.
4.767	Center line of Ajo Highway, bears N. $72^{\circ} 02'$ E. and S. $72^{\circ} 02'$ W., cor. lots 46, 47, 48, and 49, set nail.
5.767	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lots 46 and 48.
7.35	Wash, 10 lks. wide, 2 ft. deep, drains WSW.
9.989	Point for the NW-SE $1/64$ sec. cor. of sec. 35, at the intersection of the E. and W. center line of the NW-SE $1/4$ of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 42, 43, 46, and 48.
12.75	Wash, 10 lks. wide, 1 ft. deep, drains WSW.
19.978	The C-W-E $1/64$ sec. cor. of sec. 35.

Subdivision of Section 35, T. 14 S., R. 12 E.

Chains	
	From the C-N-SE $1/64$ sec. cor. of sec. 35.
	N. $89^{\circ} 52'$ W., on the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 35.
1.90	Wash, 20 lks. wide, 3 ft. deep, drains WSW.
5.008	Point for the C-E-NW-SE $1/256$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 41, 42, and 48.
6.30	Wash, 5 lks. wide, 2 ft. deep, drains SSE.
10.016	The NW-SE $1/64$ sec. cor. of sec. 35.
12.50	Wash, 10 lks. wide, 2 ft. deep, drains SW.
15.023	Point for the C-W-NW-SE $1/256$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 43, 44, 45, and 46.
20.03	The C-N-S $1/64$ sec. cor. of sec. 35.
Subdivision of the SW $\frac{1}{4}$ SE $\frac{1}{4}$.	
	From the W-E $1/64$ sec. cor. of sec. 35, on the S. bdy. of the Tp. N. $0^{\circ} 07'$ E., on the N. and S. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 35.
10.429	Point for the SW-SE $1/64$ sec. cor. of sec. 35, at the intersection of the E. and W. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 60, 61, 64, and 65.
11.20	Wash, 10 lks. wide, 1 ft. deep, drains WSW.
12.30	Wash, 15 lks. wide, 2 ft. deep, drains WSW.
20.417	The C-W-SE $1/64$ sec. cor. of sec. 35.
From the C-S-SE $1/64$ sec. cor. of sec. 35.	
	N. $89^{\circ} 52'$ W., on the E. and W. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 35.
2.00	Road, bears N. and S.
5.006	Point for the C-E-SW-SE $1/256$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 59, 60, 65, and 66.
8.05	Wash, 10 lks. wide, 1 ft. deep, drains SW.
10.012	The SW-SE $1/64$ sec. cor. of sec. 35.
13.75	Wash, 20 lks. wide, 1 ft. deep, drains SW.
14.75	Wash, 10 lks. wide, 1 ft. deep, drains SW.
15.019	Point for the C-W-SW-SE $1/256$ sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 61, 62, 63, and 64.
16.75	Wash, 10 lks. wide, 1 ft. deep, drains SW.
20.026	The C-S-S $1/64$ sec. cor. of sec. 35.

Subdivision of Section 35, T. 14 S., R. 12 E.

Chains	
	Subdivision of the SE $\frac{1}{4}$ SE $\frac{1}{4}$.
	From the E-E 1/64 sec. cor. of sec. 35, on the S. bdy. of the Tp. N. 0° 08' E., on the N. and S. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 35.
10.265	Point for the SE-SE 1/64 sec. cor. of sec. 35, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 56, 57, 68, and 69.
14.65	Wash, 5 lks. wide, 2 ft. deep, drains WSW.
18.05	Wash, 5 lks. wide, 2 ft. deep, drains WSW.
20.254	The C-E-SE 1/64 sec. cor. of sec. 35. From the S-S 1/64 sec. cor. of secs. 35 and 36. N. 89° 52' W., on the E. and W. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 35.
0.45	Power line, bears N. and S.
2.35	Road, bears N. and S.
5.007	Point for the C-E-SE-SE 1/256 sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 55, 56, 69, and 70.
10.014	The SE-SE 1/64 sec. cor. of sec. 35.
15.02	Point for the C-W-SE-SE 1/256 sec. cor. of sec. 35. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 57, 58, 67, and 68.
15.75	Shallow wash, drains SW.
20.026	The C-S-SE 1/64 sec. cor. of sec. 35.
	Subdivision of Section 34, T. 14 S., R. 12 E.
	From the $\frac{1}{4}$ sec. cor. of sec. 34, on the S. bdy of the Tp. N. 0° 01' E., on the N. and S. center line of sec. 34. Over nearly level land.
0.25	Wash, 15 lks. wide, 2 ft. deep, drains WSW.
6.20	Bladed road, bears NNW. and SSE.
10.978	Point for the C-S-S 1/64 sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 44, 45, 60, and 61.
12.61	Power line, bears NE. and SW.
20.976	Point for the C-S 1/16 sec. cor. of sec. 34, at proportionate distance. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 34, T. 14 S., R. 12 E.

Chains

C
S 1/16 S34
C
1953

Deposit a stone, mkd. X at base of iron post.

24.70 Wash, 15 lks. wide, 1 ft. deep, drains SW.

30.70 Wash, 10 lks. wide 1 ft. deep, drains SW.

30.974 Point for the C-N-S 1/64 sec. cor. of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 12, 13, 28, and 29.

40.972 Point for the C 1/4 sec. cor. of sec. 34, at the intersection of the E. and W. center line of Sec. 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C 1/4 S34
1953

Deposit a stone, mkd. X at base of iron post.

51.90 Shallow wash, drains SW.

60.60 Wash, 10 lks. wide, 2 ft. deep, drains SW.

70.85 Wash, 10 lks. wide 1 ft. deep, drains SW.

77.90 Wash, 10 lks. wide, 1 ft. deep, drains SW.

80.92 The 1/4 sec. cor. of secs. 27 and 34.

From the 1/4 sec. cor. of secs. 34 and 35.

S. 89° 54' W., on the E. and W. center line of sec. 34.

0.30 Power line, bears NE. and SW.

5.013 Point for the C-E-E-E 1/256 sec. cor. of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 5 and 6.

6.45 Wash, 5 lks. wide, 2 ft. deep, drains SW.

10.026 Point for the C-E-E 1/64 sec. cor. of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 6 and 7.

10.55 Wash, 10 lks. wide, 2 ft. deep, drains SW.

15.039 Point for the C-W-E-E 1/256 sec. cor. of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 7 and 8.

20.052 Point for the C-E 1/16 sec. cor. of sec. 34,

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16
C S34 C

1953

Subdivision of Section 34, T. 14 S., R. 12 E.

Chains	
	Deposit a stone, mkd. X at base of iron post.
25.065	Point for the C-E-W-E 1/256 sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 9 and 10.
30.078	Point for the C-W-E 1/64 sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 10 and 11.
31.30	Wash, 10 lks. wide, 2 ft. deep, drains SW.
35.091	Point for the C-W-W-E 1/256 sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 11 and 12.
37.10	Telephone line, bears N. and S.
40.104	The C $\frac{1}{4}$ sec. cor. of sec. 34.
41.65	Bladed road, bears NNW. and SSE.
45.115	Point for the C-E-E-W 1/256 sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 13 and 14.
50.126	Point for the C-E-W 1/64 sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 14 and 15.
55.137	Point for the C-W-E-W 1/256 sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 15 and 16.
60.148	Point for the C-W 1/16 sec. cor. of sec. 34. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \hline \text{C} \\ \text{S } 34 \\ 1953 \end{array}$ </div>
	Deposit a stone, mkd. X at base of iron post.
61.65	Wash, 10 lks. wide, 1 ft. deep, drains SW.
65.159	Point for the C-E-W-W 1/256 sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 17 and 18.
70.17	Point for the C-W-W 1/64 sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 18 and 19.
73.35	Wash, 5 lks. wide, 1 ft. deep, drains SSW.
75.181	Point for the C-W-W-W 1/256 sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 19 and 20.

Subdivision of Section 34, T. 14 S., R. 12 E.

Chains	
78.80	Wash, 10 lks. wide, 1 ft. deep, drains S.
80.192	The $\frac{1}{4}$ sec. cor. of secs. 33 and 34.
Subdivision of the $SE\frac{1}{4}$.	
	From the E $1/16$ sec. cor. of sec. 34, on the S. bdy. of the Tp. N. $0^{\circ} 04'$ E., on the N. and S. center-line of the $SE\frac{1}{4}$ of sec. 34.
0.70	Wash, 5 lks. wide, 1 ft. deep, drains WSW.
5.35	Wash, 10 lks. wide, 3 ft. deep, drains WSW.
10.905	Point for the C-S-SE $1/64$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 40, 41, 64, and 65.
20.90	Point for the SE $1/16$ sec. cor. of sec. 34, at the intersection of the E. and W. center line of the $SE\frac{1}{4}$ of sec. 34. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. SE $1/16$ S34 1953 Deposit a stone, mkd. X at base of iron post.
26.85	Power line, bears NE. and SW.
30.897	Point for the C-N-SE $1/64$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 8, 9, 32, and 33.
33.95	Old road, bears NW. and SE.
40.894	The C-E $1/16$ sec. cor. of sec. 34.
	From the S $1/16$ sec. cor. of secs. 34 and 35. S. $89^{\circ} 52'$ W., on the E. and W. center line of the $SE\frac{1}{4}$ of sec. 34.
5.011	Point for the C-E-E-SE $1/256$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 35, 36, 37, and 38.
10.023	Point for the C-E-SE $1/64$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 34, 35, 38, and 39.
15.034	Point for the C-W-E-SE $1/256$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 33, 34, 39, and 40.
19.00	Wash, 10 lks. wide, 1 ft. deep, drains SW.
20.046	The SE $1/16$ sec. cor. of sec. 34.
25.056	Point for the C-E-W-SE $1/256$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 31, 32, 41, and 42.

Subdivision of Section 34, T. 14 S., R. 12 E.

Chains	
28.30	Power line, bears NE. and SW.
29.70	Wash, 5 lks. wide, 1 ft. deep, drains SW.
30.066	Point for the C-W-SE $1/64$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 30, 31, 42, and 43.
35.075	Point for the C-W-W-SE $1/256$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 29, 30, 43, and 44.
36.00	Telephone line, bears N. and S.
40.085	The C-S $1/16$ sec. cor. of sec. 34.
Subdivision of the $NE\frac{1}{4}SE\frac{1}{4}$.	
	From the C-E-SE $1/64$ sec. cor. of sec. 34. N. $0^{\circ} 05'$ E., on the N. and S. center line of the $NE\frac{1}{4}SE\frac{1}{4}$ of sec. 34.
9.994	Point for the NE-SE $1/64$ sec. cor. of sec. 34, at the intersection of the E. and W. center line of the $NE\frac{1}{4}SE\frac{1}{4}$ of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 6, 7, 34, and 35.
13.10	Power line, bears NE. and SW.
19.989	The C-E-E $1/64$ sec. cor. of sec. 34. From the N-S $1/64$ sec. cor. of sec. 34 and 35. S. $89^{\circ} 53'$ W., on the E. and W. center line of the $NE\frac{1}{4}SE\frac{1}{4}$ of sec. 34.
5.012	Point for the C-E-NE-SE $1/256$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 5, 6, 35, and 36.
8.10	Shallow wash, drains SW.
10.024	The NE-SE $1/64$ sec. cor. of sec. 34,
14.30	Power line, bears NE. and SW.
15.036	Point for the C-W-NE-SE $1/256$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 7, 8, 33, and 34.
20.049	The C-N-SE $1/64$ sec. cor. of sec. 34.
Subdivision of the $NW\frac{1}{4}SE\frac{1}{4}$.	
	From the C-W-SE $1/64$ sec. cor. of sec. 34. N. $0^{\circ} 04'$ E., on the N. and S. center line of the $NW\frac{1}{4}SE\frac{1}{4}$ of sec. 34.
9.997	Point for the NW-SE $1/64$ sec. cor. of sec. 34, at the intersection of the E. and W. center line of the $NW\frac{1}{4}SE\frac{1}{4}$ of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 10, 11, 30, and 31.

BOOK 4415

Subdivision of Section 34, T. 14 S., R. 12 E.

Chains	
13.50	Wash, 5 lks. wide, 2 ft. deep, drains SSW.
16.30	Same wash, drains SSE.
17.60	Same wash, drains SSW.
19.993	The C-W-E $1/64$ sec. cor. of sec. 34.

	From the C-N-SE $1/64$ sec. cor. of sec. 34.
	S. $89^{\circ} 54'$ W., on the E. and W. center line of the NW-SE $1/4$ of sec. 34.
5.010	Point for the C-E-NW-SE $1/256$ sec. cor. of sec. 34.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 9, 10, 31, and 32.
10.021	The NW-SE $1/64$ sec. cor. of sec. 34.
14.50	Wash, 10 lks. wide, 3 ft. deep, drains SW.
15.031	Point for the C-W-NW-SE $1/256$ sec. cor. of sec. 34.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 11, 12, 29, and 30.
16.50	Telephone line, bears N. and S.
19.75	Wash, 10 lks. wide, 2 ft. deep, drains SW.
20.041	The C-N-S $1/64$ sec. cor. of sec. 34.

	Subdivision of the SW-SE $1/4$
	From the W-E $1/64$ sec. cor. of sec. 34, on the S. bdy. of the Tp.
	N. $0^{\circ} 02'$ E., on the N. and S. center line of the SW-SE $1/4$ of sec. 34.
9.05	Wash, 20 lks. wide, 3 ft. deep, drains WSW.
10.75	Wash, 8 lks. wide, 1 ft. deep, drains WSW.
10.943	Point for the SW-SE $1/64$ sec. cor. of sec. 34, at the intersection of the E. and W. center line of the SW-SE $1/4$ of sec. 34.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 42, 43, 62, and 63.
19.75	Power line, bears NE. and SW.
20.94	The C-W-SE $1/64$ sec. cor. of sec. 34.

	From the C-S-SE $1/64$ sec. cor. of sec. 34.
	S. $89^{\circ} 52'$ W., on the E. and W. center line of the SW-SE $1/4$ of sec. 34.
5.007	Point for the C-E-SW-SE $1/256$ sec. cor. of sec. 34.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 41, 42, 63, and 64.
10.015	The SW-SE $1/64$ sec. cor. of sec. 34.
12.95	Wash, 5 lks. wide, 1 ft. deep, drains SW.
15.024	Point for the C-W-SW-SE $1/256$ sec. cor. of sec. 34.

Subdivision of Section 34, T. 14 S., R. 12 E.

Chains

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 43, 44, 61, and 62.

15.45 Telephone line, bears N. and S.

16.45 Wash, 5 lks. wide, 1 ft. deep, drains SSW.

20.033 The C-S-S $1/64$ sec. cor. of sec. 34.

Subdivision of the $SE\frac{1}{4}SE\frac{1}{4}$.

From the E-E $1/64$ sec. cor. of sec. 34, on the S. bdy. of the Tp.

N. $0^{\circ} 05'$ E., on the N. and S. center line of the $SE\frac{1}{4}SE\frac{1}{4}$ of sec. 34.

0.865 Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lot 68.

1.00 Telephone line, bears NE. and SW.

1.865 Center line of Ajo Highway, on curve, bears N. $57^{\circ} 29'$ E. and S. $60^{\circ} 38'$ W., cor. lots 66, 67 and 68, set nail.

2.865 Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, for a reference, marked for lots 67 and 69.

3.20 Wash, 15 lks. wide, 2 ft. deep, drains WSW.

4.50 Wash, 15 lks. wide, 2 ft. deep, drains WSW.

10.87 Point for the SE-SE $1/64$ sec. cor. of sec. 34, at the intersection of the E. and W. center line of the $SE\frac{1}{4}SE\frac{1}{4}$ of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 38, 39, 66, and 67.

20.865 The C-E-SE $1/64$ sec. cor. of sec. 34.

From the S-S $1/64$ sec. cor. of secs. 34 and 35.

S. $89^{\circ} 52'$ W., on the E. and W. center line of the $SE\frac{1}{4}SE\frac{1}{4}$ of sec. 34.

1.45 Wash, 30 lks. wide, 2 ft. deep, drains WSW.

5.009 Point for the C-E-SE-SE $1/256$ sec. cor. of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 37, 38, 67, and 69.

10.018 The SE-SE $1/64$ sec. cor. of sec. 34.

15.028 Point for the C-W-SE-SE $1/256$ sec. cor. of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 39, 40, 65, and 66.

18.05 Wash, 5 lks. wide, 1 ft. deep, drains SSW.

20.038 The C-S-SE $1/64$ sec. cor. of sec. 34.

Subdivision of the $SW\frac{1}{4}$.

From the W $1/16$ sec. cor. of sec. 34, on the S. bdy. of the Tp.

N. $0^{\circ} 02'$ E., on the N. and S. center line of the $SW\frac{1}{4}$ of sec. 34.

9.45 Wash, 20 lks. wide, 1 ft. deep, drains WSW.

Subdivision of Section 34, T. 14 S., R. 12 E.

Chains 11.05	Point for the C-S-SW $1/64$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 48, 49, 56, and 57.
21.049	Point for the SW $1/16$ sec. cor. of sec. 34, at the intersection of the E. and W. center line of the SW $1/4$ of sec. 34. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. SW $1/16$ S34 1953 Deposit a stone, mkd. X at base of iron post.
31.04	Point for the C-N-SW $1/64$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 16, 17, 24, and 25.
41.031	The C-W $1/16$ sec. cor. of sec. 34.
	From the C-S $1/16$ sec. cor. of sec. 34. S. $89^{\circ} 52'$ W., on the E. and W. center line of the SW $1/4$ of sec. 34.
1.70	Bladed road, bears NNW. and SSE.
5.011	Point for the C-E-E-SW $1/256$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 27, 28, 45, and 46.
10.023	Point for the C-E-SW $1/64$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 26, 27, 46, and 47.
15.034	Point for the C-W-E-SW $1/256$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 25, 26, 47, and 48.
16.60	Wash, 5 lks. wide, 1 ft. deep, drains SW.
20.046	The SW $1/16$ sec. cor. of sec. 34.
25.054	Point for the C-E-W-SW $1/256$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 23, 24, 49, and 50.
30.062	Point for the C-W-SW $1/64$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 22, 23, 50, and 51.
35.070	Point for the C-W-W-SW $1/256$ sec. cor. of sec. 34. Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 21, 22, 51, and 52.
37.10	Wash, 10 lks. wide, 1 ft. deep, drains SW.
40.078	The S $1/16$ sec. cor. of secs. 33 and 34.

Subdivision of Section 34, T. 14 S., R. 12 E.

Chains	Subdivision of the NE $\frac{1}{4}$ SW $\frac{1}{4}$.
	From the C-E-SW 1/64 sec. cor. of sec. 34.
	N. 0° 02' E., on the N. and S. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 34.
2.20	Wash, 10 lks. wide, 1 ft. dep, drains WSW.
9.997	Point for the NE-SW 1/64 sec. cor. of sec. 34, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 34.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 14, 15, 26, and 27.
19.987	The C-E-W 1/64 sec. cor. of sec. 34.
	From the C-N-S 1/64 sec. cor. of sec. 34.
	S. 89° 53' W., on the E. and W. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 34.
1.85	Bladed road, bears NNW, and SSE.
5.010	Point for the C-E-NE-SW 1/256 sec. cor. of sec. 34.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 13, 14, 27, and 28.
10.021	The NE-SW 1/64 sec. cor. of sec. 34.
15.032	Point for the C-W-NE-SW 1/256 sec. cor. of sec. 34.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 15, 16, 25, and 26.
20.043	The C-N-SW 1/64 sec. cor. of sec. 34.
	Subdivision of the NW $\frac{1}{4}$ SW $\frac{1}{4}$.
	From the C-W-SW 1/64 sec. cor. of sec. 34.
	N. 0° 01' E., on the N. and S. center line of the NW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 34.
6.25	Wash, 10 lks. wide, 1 ft. deep, drains SW.
9.30	Wash, 10 lks. wide, 1 ft. deep, drains SW.
9.991	Point for the NW-SW 1/64 sec. cor. of sec. 34, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 34.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 18, 19, 22, and 23.
10.25	Wash, 5 lks. wide, 1 ft. deep, drains SW.
19.985	The C-W-W 1/64 sec. cor. of sec. 34.
	From the C-N-SW 1/64 sec. cor. of sec. 34.
	S. 89° 53' W., on the E. and W. center line of the NW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 34.
5.011	Point for the C-E-NW-SW 1/256 sec. cor. of sec. 34.
	Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 17, 18, 23, and 24.
9.20	Wash, 5 lks. wide, 1 ft. deep, drains SW.
10.022	The NW-SW 1/64 sec. cor. of sec. 34.
15.033	Point for the C-W-NW-SW 1/256 sec. cor. of sec. 34.

Subdivision of Section 34, T. 14 S., R. 12 E.

Chains.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 19, 20, 21, and 22.

19.45 Wash, 5 lks. wide, 1 ft. deep, drains SW.

20.044 The N-S $1/64$ sec. cor. of secs. 33 and 34.

Subdivision of the $SW\frac{1}{4}SW\frac{1}{4}$.

From the W-W $1/64$ sec. cor. of sec. 34, on the S. bdy. of the tp.

North, on the N. and S. center line of the $SW\frac{1}{4}SW\frac{1}{4}$ of sec. 34.

4.50 Wash, 15 lks. wide, 1 ft. deep, drains SW.

11.075 Point for the SW-SW $1/64$ sec. cor. of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 50, 51, 54, and 55.

13.50 Wash, 10 lks. wide, 1 ft. deep, drains SW.

18.30 Wash, 10 lks. wide, 1 ft. deep, drains W.

21.072 The C-W-SW $1/64$ sec. cor. of sec. 34.

From the C-S-SW $1/64$ sec. cor. of sec. 34.

S. $89^{\circ} 53' W.$, on the E. and W. center line of the $SW\frac{1}{4}SW\frac{1}{4}$ of sec. 34.

5.005 Point for the C-E-SW-SW $1/256$ sec. cor. of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 49, 50, 55, and 56.

10.011 The SW-SW $1/64$ sec. cor. of sec. 34.

15.018 Point for the C-W-SW-SW $1/256$ sec. cor. of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 51, 52, 53, and 54.

20.025 The S-S $1/64$ sec. cor. of secs. 33 and 34.

Subdivision of the $SE\frac{1}{4}SW\frac{1}{4}$

From the E-W $1/64$ sec. cor. of sec. 34.

N. $0^{\circ} 01' E.$, on the N. and S. center line of the $SE\frac{1}{4}SW\frac{1}{4}$ of sec. 34.

5.45 Power line, bears NE. and SW.

11.009 Point for the SE-SW $1/64$ sec. cor. of sec. 34, at the intersection of the E. and W. center line of the $SE\frac{1}{4}SW\frac{1}{4}$ of sec. 34.

Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 46, 47, 58, and 59.

15.15 Wash, 15 lks. wide, 1 ft. deep, drains SW.

21.008 The C-E-SW $1/64$ sec. cor. of sec. 34.

From the C-S-S $1/64$ sec. cor. of sec. 34.

S. $89^{\circ} 52' W.$, on the E. and W. center line of the $SE\frac{1}{4}SW\frac{1}{4}$ of sec. 34.

Subdivision of Section 34, T. 14 S., R. 12 E.

Chains.

- 0.55 Bladed road, bears NNW. and SSE.
- 2.25 Power line, bears NE. and SW.
- 5.011 Point for the C-E-SE-SW $1/256$ sec. cor. of sec. 34.
Set a wooden stake, 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 45, 46, 59, and 60.
- 10.022 The SE-SW $1/64$ sec. cor. of sec. 34.
- 14.05 Wash, 5 lks. wide, 1 ft. deep, drains SW.
- 15.035 Point for the C-W-SE-SW $1/256$ sec. cor. of sec. 34.
Set a wooden stake 2 ft. long, 2 ins. sq., 12 ins. in the ground, marked for lots 47, 48, 57, and 58.
- 20.049 The C-S-SW $1/64$ sec. cor. of sec. 34.

General Description.

The surface of sections 34 and 35 is nearly level. The general drainage is to the southwest through a number of shallow washes. The sections are covered with an undergrowth of greasewood, mesquite, and cacti. The Ajo Highway enters section 35 on the east boundary near the $\frac{1}{4}$ section corner, and leaves section 34 on the south boundary of the $SE\frac{1}{4}SW\frac{1}{4}$. A power line enters section 35 near the E $1/6$ sec. cor. of secs. 26 and 35, and leaves on the south boundary of section 34 near the W $1/16$ sec. cor.

3

CERTIFICATE OF CADASTRAL ENGINEER

I, Clarence E. Bilbray, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 29th October, 1952
19th day of November, 1952,
I have ~~surveyed~~ independently resurveyed the boundaries and surveyed the subdivisio-
nal lines of sections 34 and 35, in T. 14 S., R. 12 E.

of the Gila & Salt River Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Albuquerque, New Mexico

September 17, 1953

Clarence E. Bilbray
Clarence E. Bilbray
Cadastral Engineer.

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., FEB 11 1954, 19

The foregoing field notes of the ~~survey~~ of dependent resurvey of the boundaries and survey
of the subdivisio-
nal lines of sections 34 and 35, in T. 14 S., R. 12 E., of the
Gila and Salt River Meridian, in the State of Arizona.

executed by Clarence E. Bilbray

having been critically examined and found correct, are hereby approved.

Donald B. Clement
Chief, Branch of Engineering and Construction.
Assistant Chief, Division
of Cadastral Engineering

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in~~
~~is a true copy of the original field notes.~~

~~Chief, Branch of Engineering and Construction.~~