

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Dependent Resurvey South, East and West Boundaries

and

Subdivisional Lines of Township 11 South, Range 29 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Clarence E. Bilbray, Cadastral Engineer


Under special instructions dated March 10, 1952, which provided  
for the surveys included under Group No. 281, approved March 14, 1952  
and assignment instructions dated March 20, 1952

Survey commenced April 11, 1952

Survey completed May 27, 1952

4417

4417



BOOK 4417

# INDEX DIAGRAM

Township 11 S, Range 29 E

	41	41	34	28	23	18						
11	6	41	5	33	4	28	8	22	2	17	1	5
	40	40	33	27	22	17						
11	7	39	8	32	9	27	10	21	11	16	12	4
	39	38	32	26	21	16						
10	18	38	17	31	16	26	15	21	14	15	18	4
	38	37	31	26	19	15						
10	19	37	20	30	21	25	22	19	23	14	24	3
	36	36	30	25	18	14						
9	30	35	29	29	28	24	27	18	26	13	25	3
	35	35	29	24	18	13						
8	31	34	32	28	33	23	34	18	35	12	36	2
	8	7	7	6	6	5						

## T. 11 S., R. 29 E.

## Chains.

The north boundary of Township 11 South, Range 29 East (2d. Standard Parallel South) was originally surveyed by T. F. White in 1882, and resurveyed by Horace M. Muscott in 1936. The south, east, and west boundaries were surveyed by Lewis Wolfley in 1885. The subdivisional lines were surveyed by John C. Smith in 1885.

The resurvey was made at the request of the Branch of Soil and Moisture of the Division of Land Management.

Preliminary to the resurvey the lines of the original survey are retraced and search is made for all corners and other calls of the record. Identified corners are remonumented in their original positions. Lost corners are re-established and remonumented at proportionate positions based on the original record. The retracement data are thoroughly verified and only the true line notes are given herein.

The survey is executed with light mountain transits, manufactured by W. & L. E. Gurley, serial numbers 371540 and 38124, both of which are the property of the Bureau of Land Management, and constructed in accordance with its specifications.

The measurements are made with steel tapes, 5 chains in length, manufactured by Lallie, graduated at each link interval for the first 100 links, and at each 10 link interval for the remaining 400 links. The tapes were tested by comparison with a Lufkin steel tape, kept for testing purposes, and found correct. The measurements are made on the slope, and the vertical angle of each slope interval ascertained by a clinometer in adjustment. The distances entered in the field note record are summations of the horizontal equivalents.

The directions of all lines were determined by transit methods, from azimuth given by the U. S. Coast & Geodetic Survey at triangulation station "Posey", corrected to refer to the mean meridian through the lines, and checked by altitude observations on the sun.

The geographic position of the southeast corner of the township, as computed from the tie to U. S. Coast & Geodetic Survey triangulation station "Posey", is Latitude  $32^{\circ} 25' 50.3''$  N., Longitude  $109^{\circ} 19' 46.2''$  W.

Dependent Resurvey of East Boundary of T. 11 S., R. 29 E.  
(Restoring the survey made by Lewis Wolfley in 1885)

The cor. of Ts. 11 and 12 S., Rs. 29 and 30 E., determined by proportionate measurement.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11S	
R29E	R30E
S36'	S31
-----	
S1	S6
T12S	
1952	

From this corner the corner of secs. 1, 6, 7, and 12, Ts. 12 S., Rs. 29 and 30 E., determined by the corner of fences bearing N., E., and W., with old stake lying loose on ground alongside, bears S.  $0^{\circ} 40'$  E., 80.84 chs. dist. This corner is now remonumented.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

## Dependent Resurvey of East Boundary of T. 11 S., R. 29 E.

Chains.

T12S	
R29E	R30E
S1	S6
S12	S7
1952	

Also, from the cor. of Ts. 11 and 12 S., Rs. 29 and 30 E., the  $\frac{1}{4}$  sec. cor. of secs. 3 and 34, Ts. 11 and 12 S., R. 30 E., marked by the original monument, a volcanic stone, firmly set in the ground, and witnessed by a mound of stone, bears S.  $89^{\circ} 16'$  E., 277.41 chs. dist. This  $\frac{1}{4}$  sec. cor. is now remonumented.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 34	
$\frac{1}{4}$	S 3
1952	

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of cor., and bury the old corner stone alongside the iron post.

From the corner of Ts. 11 and 12 S., Rs. 29 and 30 E.

N.  $0^{\circ} 09'$  E., bet. secs. 31 and 36.

Over gently rolling land, through scattering undergrowth.

26.90 Bladed road, bears N.  $75^{\circ} 45'$  W. and S.  $75^{\circ} 45'$  E.

40.00 Wash, 50 lks. wide, 3 ft. deep, drains WNW.

40.42 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	
S36	S31
1952	

44.50 Shallow wash, drains WNW.

45.00 Over rolling sand dunes.

80.84 Point for the cor. of secs. 25, 30, 31, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11S	
R29E	R30E
S25	S30
S36	S31
1952	

Land, gently rolling.

Soil, sandy.

No timber; undergrowth greasewood and mesquite.

## Dependent Resurvey of East Boundary, T. 11 S., R. 29 E.

Chains

N. 0° 09' E., bet. secs. 25 and 30

Over gently rolling land, through undergrowth.

40.42

Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ | \\ S25 \quad | \quad S30 \\ 1952 \end{array}$$

61.70

Wash, 60 lks. wide, 3 ft. deep, drains W.

80.84

Point for the corner of secs. 19, 24, 25, and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.
$$\begin{array}{c} T11S \\ R29E \quad | \quad R30E \\ S24 \quad | \quad S19 \\ \hline S25 \quad | \quad S30 \\ 1952 \end{array}$$

Land, gently rolling.

Soil, sandy.

No timber; undergrowth, mesquite.

N. 0° 09' E., bet. secs. 19 and 24.

Over rolling land, through undergrowth.

17.50

Shallow wash, drains W.

40.42

Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ | \\ S24 \quad | \quad S19 \\ 1952 \end{array}$$

54.40

Wash, 20 lks. wide, 2 ft. deep, drains SW.

77.30

Old road, bears E. and W.

80.84

Point for the corner of secs. 13, 18, 19, and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground, with brass cap mkd.
$$\begin{array}{c} T11S \\ R29E \quad | \quad R30E \\ S13 \quad | \quad S18 \\ \hline S24 \quad | \quad S19 \\ 1952 \end{array}$$

## Dependent Resurvey of East Boundary, T. 11 S., R. 29 E.

Chains	<p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy. No timber; undergrowth, greasewood and mesquite.</p>										
	<p>N. 0° 09' E., bet. secs. 13 and 18.</p> <p>Over rolling land, through undergrowth.</p>										
4.40	Wash, 30 lks. wide, 3 ft. deep, drains W.										
40.42	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>  <table style="margin: auto;"> <tr> <td>S13</td> <td> </td> <td>S18</td> </tr> <tr> <td colspan="3">1952</td> </tr> </table> </div>	S13		S18	1952						
S13		S18									
1952											
	<p>raise a mound of stone, 2 ft. base, <math>1\frac{1}{2}</math> ft. high, W. of cor.</p>										
47.00	Shallow wash, drains WNW.										
80.84	<p>Point for the corner of secs. 7, 12, 13, and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam.; 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T11S</td> </tr> <tr> <td>R29E</td> <td>R30E</td> </tr> <tr> <td>S12</td> <td>S 7</td> </tr> <tr> <td>S13</td> <td>S18</td> </tr> <tr> <td colspan="2">1952</td> </tr> </table> </div>	T11S		R29E	R30E	S12	S 7	S13	S18	1952	
T11S											
R29E	R30E										
S12	S 7										
S13	S18										
1952											
	<p>Land, rolling. Soil, sandy. No timber; undergrowth, greasewood and mesquite.</p>										
	<p>N. 0° 09' E., bet. secs. 7 and 12.</p> <p>Over rolling land, through undergrowth.</p>										
40.42	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>  <table style="margin: auto;"> <tr> <td>S12</td> <td> </td> <td>S 7</td> </tr> <tr> <td colspan="3">1952</td> </tr> </table> </div>	S12		S 7	1952						
S12		S 7									
1952											
80.84	<p>Point for the corner of secs. 1, 6, 7, and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

FOOT 4417

## Dependent Resurvey of East Boundary, T. 11 S., R. 29 E.

Chains

T11S	
R29E	R30E
S 1	S 6
S12	S 7

1952

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly.

No timber; undergrowth, greasewood and mesquite.

N. 0° 09' E., bet. secs. 1 and 6.

Over rolling land, through undergrowth.

26.50 Shallow wash, 100 lks. wide, drains W.

40.42 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post 28 ins. long,  $2\frac{1}{2}$  ins. diam. 24 ins. in the ground over a deposit of broken glass  $\frac{1}{4}$  with brass cap mkd.

S 1	S 6
-----	-----

1952

Over rolling sand dunes.

75.28 The closing corner of Ts. 11 S., Rs. 29 and 30 E., which is an iron post, 3 ins. diam., set, marked and witnessed as described in the 1936 resurvey record of the 2nd Standard Parallel South, through Range 29 E.

From this corner the standard  $\frac{1}{4}$  sec. cor. of sec. 36, bears N. 89° 58' W., 3.22 chs. dist.

Land, rolling.

Soil, sand...

No timber; undergrowth, mesquite.

## Dependent Resurvey of South Boundary, T. 11 S., R. 29 E.

(Restoring the survey made by Lewis Wolfley in 1885)

From the corner of Ts. 11 and 12 S., Rs. 29 and 30 E.

N. 88° 51' W., bet. secs. 1 and 36.

Over level land.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post 28 ins. long  $2\frac{1}{2}$  ins. diam. 24 ins. in the ground over a deposit of broken glass with brass cap mkd.

$\frac{1}{4}$ S. 36
S 1

1952

59.00 Road, bears NW. and SE.

80.01 Point for the corner of secs. 1, 2, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

## Dependent Resurvey of South Boundary, T.11 S., R. 29 E.

Chains

T11SR29E	
S35	S36
S 2	S 1

T12S  
1952

Land, nearly level.  
Soil, sandy loam.  
No timber; undergrowth, scattering mesquite.

N. 88° 51' W., bet. secs. 2 and 35.

Over level land, through scattering undergrowth.

10.00 San Simon wash, drains N.

30.00 Road, bears ENE. and W. along line.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 2 and 35, at proportionate distance; on N. side of road; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 28 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$ S 35
S 2
1952

Set redwood stake,  $1\frac{1}{4}$  ins.  $4\frac{1}{4}$  ft. long, 24 ins. in the ground, alongside the iron post.

Continue along and near N. side of road.

80.01 Point for the corner of secs. 2, 3, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11SR29E	
S34	S35
S 3	S 2

T12S  
1952

Land, east-half, level; west-half, rolling.  
Soil, sandy loam.  
No timber; undergrowth, greasewood and mesquite.

N. 88° 51' W., bet. secs. 3 and 34.

Over gently rolling land, through undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 34, at proportionate distance, on N. side of road ditch; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$ S 34
S 3
1952



BOOK 4411

## Dependent Resurvey of South Boundary, T. 11 S., R. 29 E.

Chains	Set redwood post, 4x4 ins. sq. 4 ft. long, 2 1/4 ins. in the ground, alongside the iron post,  Continue along N. side road.												
48.00	Leave road; bears N. 87° 00' W. and S. 87° 00' E.; thence through undergrowth.												
76.00	Shallow wash; drains ENE.												
80.01	Point for the corner of secs. 3, 4, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2 1/8 ins. diam., 2 1/4 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T11SR29E</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T12S</td></tr> <tr><td colspan="2">1952</td></tr> </table> Land, gently rolling. Soil, sandy. No timber; undergrowth, greasewood and mesquite.	T11SR29E		S 33	S 34	<hr/>		S 4	S 3	T12S		1952	
T11SR29E													
S 33	S 34												
<hr/>													
S 4	S 3												
T12S													
1952													
	N. 88° 51' W., bet. secs. 4 and 33.  Over gently rolling land, through undergrowth.												
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/4 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <table style="margin-left: auto; margin-right: auto;"> <tr><td>1/4 S 33</td></tr> <tr><td><hr/></td></tr> <tr><td>1/4 S 4</td></tr> <tr><td>1952</td></tr> </table>	1/4 S 33	<hr/>	1/4 S 4	1952								
1/4 S 33													
<hr/>													
1/4 S 4													
1952													
80.01	Point for the corner of secs. 4, 5, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/4 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T11SR29E</td></tr> <tr><td>S 32</td><td>S 33</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2">T12S</td></tr> <tr><td colspan="2">1952</td></tr> </table> Land, gently rolling. Soil, sandy. No timber; undergrowth, greasewood and mesquite.	T11SR29E		S 32	S 33	<hr/>		S 5	S 4	T12S		1952	
T11SR29E													
S 32	S 33												
<hr/>													
S 5	S 4												
T12S													
1952													
	N. 88° 51' W., bet. secs. 5 and 32.  Over nearly level land, through undergrowth.												
16.00	Graded road, bears NE. and SW.												
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 2 1/4 ins. in the ground over a deposit of broken glass, with brass cap mkd.												

## Dependent Resurvey of South Boundary, T. 11 S., R. 29 E.

Chains

$$\begin{array}{r} \frac{1}{4} \text{ S } 32 \\ \hline \text{S } 5 \\ 1952 \end{array}$$

80.01 Point for the corner of secs. 5, 6, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11SR29E	
S31	S32
S 6	S 5

T12S  
1952

Land, nearly level.

Soil, sandy.

No timber; undergrowth, greasewood and mesquite.

N. 88° 51' W., bet. secs. 6 and 31.

Over nearly level land, through undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 31 \\ \hline \text{S } 6 \\ 1952 \end{array}$$

64.00 Shallow wash, drains NNE.

76.41 The corner of Ts. 11 and 12 S., Rs. 28 and 29 E., determined by cor. of fences bearing S., E. and W., from which Mt. Dos Cabezas, bears S. 36° 43' W. (record). Mt. Graham, bears N. 53° 20' W. (record).

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11S	
R28E	R29E
S36	S31
S 1	S 6

T12S  
1952

Land, nearly level.

Soil, sandy.

No timber; undergrowth, greasewood, mesquite and yucca.

## Dependent Resurvey of West Boundary, T. 11 S., R. 29 E.

(Restoring the survey made by Lewis Wolfley in 1885)

N. 0° 20' E., bet. secs. 31 and 36.

Over nearly level land, through undergrowth.

0.40 Road, bears E. and W.

## Dependent Resurvey of West Boundary, T. 11 S., R. 29 E.

Chains  
40.19

Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S36} \quad | \quad \text{S31} \\ \hline 1952 \end{array}$$

55.30 Wash, 10 lks. wide, 2 ft. deep, drains ENE.

69.50 Old road, bears NE. and SW.

80.39 The corner of secs. 25, 30, 31, and 36, marked by a 2x2 in. redwood stake and the original stake lying loose alongside.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \text{T11S} \\ \text{R28E} \quad | \quad \text{R29E} \\ \text{S25} \quad | \quad \text{S30} \\ \hline \text{S36} \quad | \quad \text{S31} \end{array}$$

1952

Reset old stake alongside the iron post.

Land, nearly level.

Soil, sandy.

No timber, undergrowth, greasewood, mesquite and yucca.

N. 0° 19' W., bet. secs. 25 and 30.

Over nearly level land, through undergrowth.

40.25

Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S25} \quad | \quad \text{S30} \\ \hline 1952 \end{array}$$

61.00 Shallow wash, drains NNE.

69.50 Shallow wash, drains E.

80.51 Point for the corner of secs. 19, 24, 25, and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \text{T11S} \\ \text{R28E} \quad | \quad \text{R29E} \\ \text{S24} \quad | \quad \text{S19} \\ \hline \text{S25} \quad | \quad \text{S30} \end{array}$$

1952

## Dependent Resurvey of West Boundary, T. 11 S., R. 29 E.

Chains

Land, nearly level.  
Soil, sandy.  
No timber; undergrowth, greasewood, mesquite and yucca.

N. 0° 19' W., bet. secs. 19 and 24,

Over nearly level land, through undergrowth.

40.25 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S24} \quad | \quad \text{S19} \\ \hline 1952 \end{array}$$

80.51 Point for the corner of secs. 13, 18, 19, and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \text{T11S} \\ \text{R28E} \quad | \quad \text{R29E} \\ \text{S13} \quad | \quad \text{S18} \\ \hline \text{S24} \quad | \quad \text{S19} \\ \hline 1952 \end{array}$$

Land, nearly level.  
Soil, sandy and gravelly.  
No timber; undergrowth, greasewood.

N. 0° 19' W., bet. secs. 13 and 18.

Over rolling land, through undergrowth.

5.50 Shallow wash, drains NW.

40.25 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S13} \quad | \quad \text{S18} \\ \hline 1952 \end{array}$$

80.51 Point for the corner of secs. 7, 12, 13, and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T11S} \\ \text{R28E} \quad | \quad \text{R29E} \\ \text{S12} \quad | \quad \text{S 7} \\ \hline \text{S13} \quad | \quad \text{S18} \\ \hline 1952 \end{array}$$

## Dependent Resurvey of West Boundary, T. 11 S., R. 29 E.

## Chains

Set redwood post,  $4 \times 4$  ins. 6 ft. long,  $2 \frac{1}{4}$  ins. in the ground, alongside the iron post.

Land, rolling.

Soil, sandy and gravelly.

No timber; undergrowth, greasewood.

N.  $0^{\circ} 19'$  W., bet. secs. 7 and 12.

Over rolling land, through undergrowth.

40.25 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, at proportionate distance, there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2 \frac{1}{2}$  ins. diam.,  $2 \frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S12 \quad | \quad S7 \\ | \\ 1952 \end{array}$$

79.01 Point for the witness corner of secs. 1, 6, 7, and 12.

Set an iron post, 28 ins. long,  $2 \frac{1}{2}$  ins. diam.,  $2 \frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} WC \\ T11S \\ \hline R28E \quad | \quad R29E \\ S1 \quad | \quad S6 \\ \hline S12 \quad | \quad S7 \\ 1952 \end{array}$$

80.00 Left bank of San Simon wash, 10 ft. deep, drains WNW.

80.51 True point for the corner of secs. 1, 6, 7, and 12, at proportionate distance, falls in San Simon wash; there is no remaining evidence of the original corner.

Land, rolling.

Soil, sandy and gravelly.

No timber; undergrowth, greasewood.

N.  $0^{\circ} 19'$  W., bet. secs. 1 and 6.

Over bottom of wash.

1.50 Right bank of San Simon wash; thence over rolling sand dunes, through scattering undergrowth.

40.25 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2 \frac{1}{2}$  ins. diam.,  $2 \frac{1}{4}$  ins. in the ground, over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S1 \quad | \quad S6 \\ | \\ 1952 \end{array}$$

67.93 Intersect the 2nd Standard Parallel South, point for the closing corner of Ts. 11 S., Rs. 28 and 29 E., at proportionate distance;

Dependent Resurvey of West Boundary, T. 11 S., R. 29 E.

Chains

there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T10SR28E

S36

S 1 | S 6

R28E | R29E

T11S

CC

1952

Bury a lavastone  $4\frac{1}{2} \times 3$  ins., mkd. X alongside the iron post.

From this cor. the standard cor. of Ts. 10 S., Rs. 28 and 29 E., which is an iron post, 3 ins. diam., set, marked and witnessed as described in the 1936 resurvey record of the 2nd Standard Parallel South, through Range 29 E., bears N.  $89^{\circ} 58'$  E., 34.57 chs. dist.

From this same cor. the standard  $\frac{1}{4}$  sec. cor. of sec. 36, T. 10 S., R. 28 E., marked by an old rotted stake with three other old stakes lying loose on ground alongside, bears S.  $89^{\circ} 58'$  W., 6.22 chs. dist.

At the corner point .

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

SC

$\frac{1}{4}$  S 36

1952

Land. rolling

Soil, sand.

No timber; undergrowth, scattering mesquite.

Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

(Restoring the survey made by John C. Smith in 1885)

From the corner of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp. N.  $0^{\circ} 17'$  E., bet. secs. 35 and 36.

Over nearly level land, through scattering undergrowth.

15.00

Road, bears NE. and SW.

37.00

Earth dike, bears NW. and E.

38.80

Northwest cor. of reservoir, bears E. 50 lks. dist.

40.37

Point for the  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$

S35 | S36

1952

U.S. Coast and Geodetic Survey triangulation station "Posey" bears S.  $21^{\circ} 46'$  E., 27.28 chs. dist.

67.40

South end of reservoir.

70.60

North end of reservoir.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains  
80.74

Point for the corner of secs. 25, 26, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T11SR29E	
S26	S25
S35	S36

1952

Set redwood post, 4x4 ins. 6 ft. long, 24 ins. in the ground alongside the iron post.

Land, nearly level.

Soil, clay loam.

No timber; undergrowth, scattering mesquite.

---

From the corner of secs. 25, 30, 31, and 36, on the E. bdy of the Tp. N. 88° 57' W., bet. secs. 25 and 36.

Over rolling sand dunes, through undergrowth.

35.00 Leave sand dunes; enter nearly level land.

39.90 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	S 25
	S 36
1952	

73.10 Bladed road, bears N. and S.

75.40 Enter open pasture, bears N. and S.

79.80 The corner of secs. 25, 26, 35, and 36.

Land, east-half, rolling; west-half nearly level.

Soil, clay loam, and sandy.

No timber; undergrowth, mesquite and sage.

---

N. 0° 20' E., bet. secs. 25 and 26.

Over nearly level land, through open pasture.

13.75 Leave pasture, bears E. and W.; thence through undergrowth.

40.37 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	
	S26
	S25

1952

46.70 Shallow wash, 50 lks. wide, drains W.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

80.74

Point for the corner of secs. 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11SR29E	
S23	S24
S26	S25

1952

Land, nearly level.  
Soil, clay loam, and sandy.  
No timber; undergrowth, mesquite and sage.

From the corner of secs, 19, 24, 25, and 30, on the E. bdy. of the Tp.

N. 89° 01' W., bet. secs. 24 and 25.

Over rolling sand dunes, through undergrowth.

39.74

Point for the  $\frac{1}{4}$  sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	S 24
	S 25
	1952

79.30

Bladed road, bears N. and S.

79.49

The corner of secs. 23, 24, 25, and 26.

Land, rolling sand dunes.  
Soil, sandy.  
No timber, undergrowth, mesquite and sage.

N. 0° 08' E., bet. secs. 23 and 24.

Over gently rolling land, through undergrowth.

40.37

Point for the  $\frac{1}{4}$  sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	
S23	S24

1952

71.20

South bank of arroyo, 10 ft. deep, drains WSW.

72.70

North bank of same.

80.74

The corner of secs. 13, 14, 23, and 24, marked by the original monument, a malpais stone, 12x8x6 ins., loosely set, marked 3 grooves S. and 1 groove E. faces.

At the corner point



## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

## Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T11SR29E	
S14	S13
S23	S24

1952

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor., and bury the old corner stone alongside the iron post.

Land, gently rolling.

Soil, sandy.

No timber; undergrowth, mesquite and sage.

From the corner of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp. N.  $89^{\circ} 07'$  W., bet. secs. 13 and 24.

Over rolling land, through undergrowth.

39.73 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	S 13
S 14	S 24
1952	

47.20 Wash, 50 lks. wide, 6 ft. deep, drains WSW.

77.90 Bladed road, bears N. and S.

79.47 The corner of secs. 13, 14, 23, and 24.

Land, rolling.

Soil, sandy and gravelly.

No timber; undergrowth, greasewood, mesquite and sage.

N.  $0^{\circ} 25'$  W., bet. secs. 13 and 14.

Over rolling land, through undergrowth.

20.50 Shallow wash, drains WSW.

40.48 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	
S14	S13
1952	

55.30 Wash, 10 lks. wide, 2 ft. deep, drains W.

65.50 Road, bears NW. and SE.

80.96 Point for the corner of secs. 11, 12, 13, and 14, at proportionate distance; there is no remaining evidence of the original corner.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11SR29E	
S11	S12
<hr/>	
S14	S13

1952

Land, gently rolling.

Soil, sandy.

No timber; undergrowth, greasewood and mesquite.

From the corner of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp. N.  $89^{\circ} 04'$  W.; bet. secs. 12 and 13.

Over rolling sand dunes, through undergrowth.

40.09 Point for the  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	S 12
$\frac{1}{4}$	S 13
<hr/>	
1952	

71.30 Bladed road, bears N.  $15^{\circ}$  E. and S.  $15^{\circ}$  W.

80.19 The corner of secs. 11, 12, 13, and 14.

Land, gently rolling.

Soil, sandy.

No timber; undergrowth, mesquite.

N.  $0^{\circ} 05'$  E., bet. secs. 11 and 12.

Over, gently rolling land, through scattering undergrowth.

13.90 Road, bears NW. and SE.

40.48 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	
S11	S12
<hr/>	
1952	

1952

80.96 Point for the corner of secs. 1, 2, 11, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11SR29E	
S 2	S 1
<hr/>	
S11	S12

1952

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains	Land, gently rolling. Soil, sandy. No timber; undergrowth, mesquite
	From the corner of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp. N. 89° 02' W., bet secs. 1 and 12.
	Over rolling land, through undergrowth.
32.45	Bladed road, bears SSW. and NNE. turning W. to ranch house.
40.12	Point for the $\frac{1}{4}$ -sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \text{ S } 1 \\ \hline \frac{1}{4} \text{ S } 12 \\ 1952 \end{array}$
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
42.80	Flowing water well, bears N. 59° 15' W., 2.20 chs. dist.
51.00	Ranch house, bears N. approximately 6.00 chs. dist.
80.25	The corner of secs. 1, 2, 11, and 12.  Land, east-half, rolling; west-half, nearly level. Soil, sandy and gravelly. No timber; undergrowth, greasewood, mesquite and sage.
	N. 0° 23' E., bet. secs. 1 and 2.
	Over rolling sand dunes, through undergrowth.
22.50	Bladed road, bears E. and W.
40.48	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 2 $\frac{1}{2}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S } 2 \quad   \quad \text{S } 1 \\ \hline 1952 \end{array}$
74.01	The closing corner of secs. 1 and 2, T. 11 S., R. 29 E., which is an iron post, 2 ins. diam., set, and marked as described in the 1936 resurvey record of the 2nd Standard Parallel South, through Range 29 E.
	From this corner the standard $\frac{1}{4}$ sec. cor. of sec. 35, bears N. 89° 58' W., 3.21 chs. dist. and the standard cor. of secs. 35 and 36 bears S. 89° 58' E. 36.79 chs. dist. Land, rolling sand dunes. Soil, sandy. No timber; undergrowth, mesquite and yucca.

North Boundary Sec. 1

Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

At a point on the 2nd Standard Parallel South, midway between the closing corner of Ts. 11 S., Rs. 29 and 30 E., and the closing corner of secs. 1 and 2. The point for the  $\frac{1}{4}$  sec. cor. of sec. 1.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$  S 1  
1952

From this corner the standard corner of secs. 35 and 36, T. 10 S., R. 29 E., bears N.  $89^{\circ} 58'$  W., 3.21 chs. dist. and the standard  $\frac{1}{4}$  sec. cor. of secs. 36 bears S.  $89^{\circ} 58'$  E. 36.78 chs. dist.

From the corner of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp. N.  $0^{\circ} 11'$  E., bet. secs. 34 and 35.

Over gently rolling land, through undergrowth.

10.00 Wash, 10 lks. wide, 2 ft. deep, drains ENE.

40.37 Point for the  $\frac{1}{4}$  sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post; 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$   
S34 | S35  
1952

56.00 Shallow wash, drains ENE.

80.74 Point for the corner of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11SR29E  
S27 | S26  
S34 | S35  
1952

Land, gently rolling.

Soil, sandy.

No timber; undergrowth, greasewood and mesquite.

From the corner of secs. 25, 26, 35, and 36.

N.  $88^{\circ} 49'$  W., bet. secs. 26 and 35.

Over nearly level land, through open pasture.

19.50 Leave pasture; thence through undergrowth.

21.30 Ditch, 7 lks. wide, 3 ft. deep, drains NW.

40.07 Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

BOOK 4417

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains	
	$\frac{1}{4}$ — S 26 — S 35 1952
54.60	Wash, 10 lks. wide, 3 ft. deep, drains NW.
68.20	Dirt dike, brs. NE. and SW.
80.15	The cor. of secs. 26, 27, 34 and 35.  Land nearly level. Soil, clay loam. No timber; undergrowth, mesquite.
	N. 0° 21' E., bet. secs. 26 and 27. Over gently rolling land, through scattering undergrowth.
23.20	Left bank of San Simon wash, 10 ft. deep, drains NW.
24.00	Right bank of same wash.
40.37	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original cor.  Set an iron post 28 ins. long, $2\frac{1}{2}$ ins. diam. 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <div style="text-align: center;"> <math>\frac{1}{4}</math>            S27   S26            1952         </div>
67.75	An arroyo, 30 lks. wide, 8 ft. deep, drains NW.; thense over grassy flat.
80.74	Point for the corner of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post 28 ins. long 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <div style="text-align: center;">           T11SR29E            S22   S23            S27   S26            1952         </div>
	Land, nearly level. Soil clay loam. No timber; undergrowth, scattering mesquite.
	From the corner of secs. 23, 24, 25 and 26. N. 87° 19' W., bet. secs. 23 and 26.  Over nearly level land, through scattering undergrowth.
39.97	The $\frac{1}{4}$ cor. of secs. 23 and 26, which is marked by an iron post, 2 ins. diam., set 12 ins. in the ground, at cor of fences, bearing S. and W., with original monument, a sandstone 10x10x10 ins., lying loose on ground alongside.  At the cor. point  Set an iron post 28 ins. long, $2\frac{1}{2}$ ins. diam, 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <div style="text-align: center;">           S 23   <math>\frac{1}{4}</math> — S 26 —             1952         </div>
	Bury the old corner stone alongside the ironpost.

## Dependent Resurvey of Subdivision, T. 11 S. R. 29 E.

Chains	S. 89° 44' W., beginning new measurement.
16.70	Wash, 20 lks. wide, 5 feet deep, drains N.
30.00	Enter grassy flat.
40.18	The corner of secs. 22, 23, 26 and 27. Land, nearly level. Soil, sandy and gravelly. No timber; mesquite and salt cedar along the San Simon wash.
	N. 0° 05' W., bet. secs. 22 and 23. Over nearly level grassy flat.
10.00	Earth tank, bears E. approximately 1.50 chs. dist.
39.50	Wash, drains west.
40.37	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins in the ground over a deposit of broken glass, with brass cap marked $\frac{1}{4}$ $\begin{array}{c} \text{S22} \mid \text{S23} \\ \hline 1952 \end{array}$
80.74	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post 28 ins. long, $2\frac{1}{2}$ ins. diam. 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. $\begin{array}{c} \text{T11SR29E} \\ \text{S15} \mid \text{S14} \\ \hline \text{S22} \mid \text{S23} \\ \hline 1952 \end{array}$ Land, nearly level. Soil, sandy. No timber; undergrowth, sage and grass.
40.17	From the corner of secs. 13, 14, 23 and 24. N. 88° 47' W., bet. secs. 14 and 23. Over gently rolling land, through undergrowth. Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. $\frac{1}{4} \begin{array}{c} \text{S 14} \\ \hline \text{S 23} \end{array}$ 1952

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

80.35

The corner of secs. 14, 15, 22, and 23.

Land, gently rolling.

Soil, sandy.

No timber; undergrowth, greasewood and mesquite.

N. 0° 17' W., bet. secs. 14 and 15.

Over gently rolling land, through undergrowth.

40.37

Point for the  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ | \\ S15 \quad | \quad S14 \\ 1952 \end{array}$$

41.60

Wash, 10 lks. wide, 2 ft. deep, drains W.

80.74

Point for the  $\frac{1}{4}$  sec. cor. of secs. 10, 11, 14, and 15, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.
$$\begin{array}{c} T11SR29E \\ S10 \quad | \quad S11 \\ \hline S15 \quad | \quad S14 \\ 1952 \end{array}$$

Land, gently rolling.

Soil, sandy.

No timber; undergrowth, mesquite and sage.

From the corner of secs. 11, 12, 13, and 14.

N. 88° 57' W., bet. secs. 11 and 14.

Over gently rolling land, through scattering undergrowth.

40.08

Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \quad S \quad 11 \\ | \\ S \quad 14 \\ 1952 \end{array}$$

40.20

Shallow wash, drains N.

80.17

The corner of secs. 10, 11, 14, and 15.

Land, gently rolling sand dunes.

Soil, sand.

No timber; undergrowth, scattering mesquite and sage.

N. 0° 07' W., bet. secs. 10 and 11.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains	Over gently rolling land, through scattering undergrowth.
14.50	Shallow wash, drains W.
40.37	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <div style="text-align: center;"> <math>\frac{1}{4}</math>            S10   S11            1952         </div>
60.00	Shallow wash, drains SW.
68.70	Old road, bears E. and W.
80.74	Point for the corner of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <div style="text-align: center;">           T11SR29E            S 3   S 2            S10   S11            1952         </div> <p>Land, gently rolling. Soil, sandy. No timber, undergrowth, mesquite, yucca and sage.</p>
	From the corner of secs. 1, 2, 11, and 12,  N. 89° 05' W., bet. secs. 2 and 11.  Over gently rolling sand dunes, through scattering undergrowth.
40.21	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <div style="text-align: center;"> <math>\frac{1}{4}</math> S 2            S 11            1952         </div>
47.00	Shallow wash, drains WSW.
80.43	The corner of secs. 2, 3, 10, and 11.  Land, gently rolling sand dunes. Soil, sandy. No timber; undergrowth, mesquite and sage.
	N. 0° 45' E., bet. secs. 2 and 3.  Over gently rolling sand dunes, through scattering undergrowth.
6.00	Shallow wash, drains SW.
10.00	Ascend 18 ft.



## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains 20.00	Top of ascent; thence over rolling sand dunes.
40.37	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  $\begin{array}{c} \frac{1}{4} \\   \\ S\ 3 \quad   \quad S\ 2 \\   \\ 1952 \end{array}$
72.77	The closing corner of secs. 2 and 3, T. 11 S., R. 29 E., which is an iron post, 2 ins. diam., set, and marked as described in the 1936 resurvey record of the 2nd Standard Parallel South, through Range 29 E.  From this corner the standard $\frac{1}{4}$ sec. cor. of sec. 34, bears N. $89^{\circ} 58'$ W., 3.20 chs. dist. and the standard cor. of secs. 34 and 35 bears S. $89^{\circ} 58'$ E., 36.80 chs. dist. Land, rolling sand dunes. Soil, sandy. No timber; undergrowth, mesquite and sage.
North Boundary Sec. 2	
	At a point on the 2nd Standard Parallel South, midway between the closing corners of secs. 1 and 2, and secs. 2 and 3, on N. bdy of sec. 2. The point for the $\frac{1}{4}$ sec. cor. of sec. 2.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  $\begin{array}{c} \frac{1}{4} \text{ S } 2 \\   \\ 1952 \end{array}$
	From this corner the standard corner of secs. 34 and 35, T. 10 S., R. 29 E., bears N. $89^{\circ} 58'$ W., 3.22 chs. dist. and the standard $\frac{1}{4}$ cor. of sec. 35 bears S. $89^{\circ} 58'$ E., 36.81 chs. dist.
	From the corner of secs. 3, 4, 33, and 34, on the S. bdy of the Tp. N. $0^{\circ} 12'$ E., bet. secs. 33 and 34.  Over gently rolling land, through undergrowth.
2.80	Bladed road, bears E. and W.
3.60	Wire fence, bears E. and W.
40.32	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  $\begin{array}{c} \frac{1}{4} \\   \\ S33 \quad   \quad S34 \\   \\ 1952 \end{array}$
80.64	Point for the corner of secs. 27, 28, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

T11SR29E	
S28	S27
S33	S34

1952

Land, gently rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood.

From the corner of secs. 26, 27, 34, and 35.  
N. 88° 54' W., bet. secs. 27 and 34.  
Over gently rolling land, through undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	S 27
	S 34
	1952

79.99 The corner of secs. 27, 28, 33, and 34.

Land, gently rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood and mesquite.

N. Q° 10' E., bet. secs. 27 and 28.

Over gently rolling land, through undergrowth.

19.50 Shallow wash, drains ENE.

40.32 Point for the  $\frac{1}{4}$  sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	
S28	S27
	1952

50.00 Descend gradually into flat.

65.00 Foot of descent; thence over flat.

80.64 Point for the corner of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11SR29E	
S21	S22
S28	S27

1952

Land, gently rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains	From the corner of secs. 22, 23, 26, and 27. N. 88° 59' W., bet. secs. 22 and 27. Over nearly level land, through undergrowth.
9.70	Wash, 30 lks. wide, 10 ft. deep, drains NW.
21.80	San Simon wash, 20 lks. wide, 10 ft. deep, drains NW.
30.00	Ascend slightly over gently rolling land.
40.10	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \frac{1}{4} \text{ S } 22 \\ \hline \frac{1}{4} \text{ S } 27 \\ 1952 \end{array}$
80.20	The corner of secs. 21, 22, 27, and 28. Land, east-half, nearly level; west-half, gently rolling. Soil, east-half, clay loam; west-half, sandy. No timber; undergrowth, mesquite, with salt cedar along the washes.
	N. 0° 09' W., bet. secs. 21 and 22. Over grassy flat.
24.80	San Simon wash, 30 lks. wide, 7 ft. deep, drains NW.
33.40	Wash, 10 lks. wide, 4 ft. deep, drains WNW.
40.32	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \hline \text{S21} \quad   \quad \text{S22} \\ \hline 1952 \end{array}$
80.64	Thence over gently rolling land, through scattering undergrowth. Point for the corner of secs. 15, 16, 21, and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. $\begin{array}{c} \text{T11SR29E} \\ \hline \text{S16} \quad   \quad \text{S15} \\ \hline \text{S21} \quad   \quad \text{S22} \\ \hline 1952 \end{array}$ Land, south-half, level; north-half, gently rolling. Soil, sandy clay. No timber; undergrowth, mesquite and sage, with salt cedar along wash.

Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

From the corner of secs. 14, 15, 22, and 23.

N. 89° 05' W., bet. secs. 15 and 22.

Over gently rolling land, through scattering undergrowth.

40.12

Point for the  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$  S 15  
 S 22  
 1952

41.60

Right bank of wash, 10 ft. deep, drains N.

43.10

Left bank same wash.

80.25

The corner of secs. 15, 16, 21, and 22.

Land, nearly level.

Soil, sandy clay.

No timber; undergrowth, scattering mesquite and sage.

N. 0° 24' W., bet. secs. 15 and 16.

Over nearly level flat, through scattering undergrowth.

40.32

Point for the  $\frac{1}{4}$  sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$   
 S16 | S15  
 1952

76.30

Wash, 30 lks. wide, 10 ft. deep, drains NW.

80.64

Point for the corner of secs. 9, 10, 15, and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11SR29E  
 S 9 | S10  
 S16 | S15  
 1952

Land, nearly level.

Soil, sandy clay.

No timber; undergrowth, scattering mesquite and sage.

From the corner of secs. 10, 11, 14, and 15.

N. 89° 09' W., bet. secs. 10 and 15.

Over gently rolling land, through undergrowth.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

40.18

Point for the  $\frac{1}{4}$  sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \hline S 10 \\ S 15 \\ 1952 \end{array}$$

52.00

Wash, 20 lks. wide, 2 ft. deep, drains SW.

62.30

Wash, 100 lks. wide, 4 ft. deep, drains WNW.

80.37

The corner of secs. 9, 10, 15, and 16.

Land, gently rolling.

Soil, sandy.

No timber; undergrowth, scattering mesquite and sage.

N. 0° 09' W., bet. secs. 9 and 10.

Over gently rolling land, through scattering mesquite and sage.

4.50

Wash, drains WNW.

40.32

Point for the  $\frac{1}{4}$  sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S 9 \quad | \quad S 10 \\ \hline 1952 \end{array}$$

47.10

Wash, 30 lks. wide, 7 ft. deep, drains W.

72.90

Old road, bears ENE. and SW.

80.64

Point for the corner of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} T11SR29E \\ S 4 \quad | \quad S 3 \\ \hline S 9 \quad | \quad S 10 \\ \hline 1952 \end{array}$$

Land, gently rolling.

Soil, sandy.

No timber; undergrowth, scattering mesquite and sage.

From the corner of secs. 2, 3, 10, and 11.

N. 89° 13' W., bet. secs. 3 and 10.

Over rolling sand dunes, through scattering undergrowth.

5.15

Wash, 10 lks. wide, 4 ft. deep, drains SW.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

40.20

Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 3 \\ \hline \text{S } 10 \\ 1952 \end{array}$$

80.40

The corner of secs. 3, 4, 9, and 10.

Land, rolling sand dunes.

Soil, sand.

No timber; undergrowth, mesquite and sage.

N.  $0^{\circ} 54'$  E., bet. secs. 3 and 4.

Over rolling sand dunes, through undergrowth.

8.45

Dirt dyke, bears ESE. and WNW.

40.32

Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ \hline \text{S } 4 \quad | \quad \text{S } 3 \\ 1952 \end{array}$$

71.72

The closing corner of secs. 3 and 4, T. 11 S., R. 29 E., which is an iron post, 2 ins. diam., set, and marked as described in the 1936 resurvey record of the 2nd Standard Parallel South, through Range 29 E.

From this corner the standard  $\frac{1}{4}$  sec. cor. of sec. 33, bears N.  $89^{\circ} 58'$  W., 2.94 chs. dist. and the standard cor. of secs. 33 and 34 bears S.  $89^{\circ} 58'$  E., 37.06 chs. dist.

Land, rolling sand dunes.

Soil, sand.

No timber; undergrowth, mesquite and sage.

## North Boundary Sec. 3

At a point on the 2nd Standard Parallel South, midway between the closing corners of secs. 2 and 3, and secs. 3 and 4, on N. bdy. of sec. 3. The point for the  $\frac{1}{4}$  sec. cor. of sec. 3.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 3 \\ \hline 1952 \end{array}$$

From this corner the standard corner of secs. 33 and 34, T. 10 S., R. 29 E., bears N.  $89^{\circ} 58'$  W., 3.08 chs. dist. and the standard  $\frac{1}{4}$  sec. cor. of sec. 34 bears S.  $89^{\circ} 58'$  E., 36.94 chs. dist.

From the corner of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp.

N.  $0^{\circ} 11'$  E., bet. secs. 32 and 33.

Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.


Chains

Over gently rolling land, through undergrowth.

1.90  
2.60  
40.31

Bladed road, bears E. and W.  
Wire fence, bears E. and W.  
Point for the  $\frac{1}{4}$  sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.


Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.



80.62

Point for the corner of secs. 28, 29, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.



Land, gently rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood and mesquite.

From the corner of secs. 27, 28, 33, and 34,  
N. 88° 53' W., bet. secs. 28 and 33.  
Over gently rolling land, through undergrowth.


39.00

Shallow wash, drains NE.

40.02

Point for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.



80.05

The corner of secs. 28, 29, 32, and 33.

Land, gently rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood and scattering mesquite.

N. 0° 03' W., bet. secs. 28 and 29.

Over gently rolling land, through undergrowth.

38.50

Shallow wash, drains NE.


40.31

Point for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.


Chains



65.00 Shallow wash, drains ENE.

80.62 Point for the corner of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.



Land, gently rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood and mesquite.


From the corner of secs. 21, 22, 27, and 28.

N. 88° 54' W., bet. secs. 21 and 28.

Over gently rolling land, through undergrowth.

40.16 Point for the  $\frac{1}{4}$  sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.



51.15 Dirt dyke, bears NNE. and S.

80.32 The corner of secs. 20, 21, 28, and 29.

Land, gently rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood and mesquite.


N. 0° 07' W., bet. secs. 20 and 21.

Over gently rolling land, through undergrowth.

13.50 Wash, 10 lks. wide, 6 ft. deep, drains NE.

40.31 Point for the  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.;  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.



67.00 Wash, 80 lks. wide, 4 ft. deep, drains NE.



## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

80.62

Point for the corner of secs. 16, 17, 20, and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11SR29E	
S17	S16
S20	S21

1952

Land, rolling.

Soil, sandy.

No timber; undergrowth; greasewood.

---

From the corner of secs. 15, 16, 21, and 22.

N.  $88^{\circ} 56'$  W., bet. secs. 16 and 21.

Over level flat, through scattering undergrowth.

24.00

Right bank of San Simon wash, 15 ft. deep, drains NNW.

25.50

Left bank of wash.

39.00

Leave flat; thence over gently rolling land.

40.13

Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	S 16
$\frac{1}{4}$	S 21
1952	

80.27

The corner of secs. 16, 17, 20, and 21.

Land, east-half, level; west-half, gently rolling.

Soil, sandy.

No timber; undergrowth, greasewood, mesquite and yucca.

---

N.  $0^{\circ} 26'$  W., bet. secs. 16 and 17.

Over rolling land, through undergrowth.

26.20

Wash, 8 lks. wide, 1 ft. deep, drains E.

35.80

Wash, 7 lks. wide, 2 ft. deep, drains E.

40.31

Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam.,  $2\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$	
S17	S16
1952	

65.40

Wash, 15 lks. wide, 3 ft. deep, drains ENE.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.


Chains 80.62	<p>Point for the corner of secs. 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 2<math>\frac{1}{4}</math> ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T11SR29E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S17</td><td>S16</td></tr> </table> <p style="text-align: center;">1952</p> <p>Land, rolling. Soil, sandy. No timber; undergrowth, greasewood.</p>	T11SR29E		S 8	S 9	<hr/>		S17	S16
T11SR29E									
S 8	S 9								
<hr/>									
S17	S16								
<p>2.60</p> <p>5.60</p> <p>13.20</p> <p>18.30</p> <p>20.90</p> <p>40.14</p> <p>50.00</p> <p>70.00</p> <p>80.29</p>	<p>From the corner of secs. 9, 10, 15, and 16.</p> <p>N. 88° 59' W., bet. secs. 9 and 16.</p> <p>Over level flat, through scattering undergrowth.</p> <p>Right bank of wash, 8 ft. high, bears NW. and SE., drains NW.</p> <p>Left bank of wash.</p> <p>Wash, 40 lks. wide, 6 ft. deep, drains N.</p> <p>Right bank of San Simon wash, 10 ft. deep, drains N.</p> <p>Left bank of wash.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 2<math>\frac{1}{4}</math> ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2"><math>\frac{1}{4}</math> S 9</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">S 16</td></tr> </table> <p style="text-align: center;">1952</p> <p>Wash, 100 lks. wide, 4 ft. deep, drains NNE.</p> <p>Leave flat; thence over gently rolling land.</p> <p>The corner of secs. 8, 9, 16, and 17.</p> <p>Land, east 70 chs. flat; west 10 chs. gently rolling Soil, sandy. No timber; undergrowth, scattering mesquite and sage.</p>	$\frac{1}{4}$ S 9		<hr/>		S 16			
$\frac{1}{4}$ S 9									
<hr/>									
S 16									
40.31	<p>N. 0° 15' W., bet. secs. 8 and 9.</p> <p>Over gently rolling land, through undergrowth.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 2<math>\frac{1}{4}</math> ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2"><math>\frac{1}{4}</math></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p style="text-align: center;">1952</p>	$\frac{1}{4}$		<hr/>		S 8	S 9		
$\frac{1}{4}$									
<hr/>									
S 8	S 9								

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains	
43.30	Left bank of San Simon wash, 10 ft. deep, drains WNW.
46.60	Right bank of wash.
66.10	Old road, bears NW. and SE.
80.62	Point for the corner of secs. 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <div style="text-align: center;">           T11SR29E            S 5   S 4            S 8   S 9            1952         </div>
	Land, gently rolling. Soil, sandy. No timber; undergrowth, greasewood, mesquite, with salt cedar along San Simon wash.
	From the corner of secs. 3, 4, 9, and 10. N. 88° 59' W., bet. secs. 4 and 9. Over gently rolling sand dunes, through undergrowth.
3.70	Wash, 5 lks. wide, 2 ft. deep, drains S.
7.70	Wash, 10 lks. wide, 2 ft. deep, drains S.
13.50	Ascend gradually.
17.00	Top of low ridge; descend gradually.
22.00	Foot of slope; thence over gently rolling land.
40.21	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.  <div style="text-align: center;"> <math>\frac{1}{4}</math> S 4  <math>\frac{1}{4}</math> S 9            1952         </div>
45.00	Shallow wash, drains SSW.
57.90	Wash, 10 lks. wide, 3 ft. deep, drains S.
80.43	The corner of secs. 4, 5, 8, and 9.  Land, gently rolling sand dunes. Soil, sandy and gravelly. No timber; undergrowth, mesquite and sage.
	N. 0° 40' E.; bet. secs. 4 and 5. Over rolling sand dunes, through undergrowth.
40.31	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains



70.40

The closing corner of secs. 4 and 5, T. 11 S., R. 29 E., which is an iron post, 2 ins. diam., set, and marked as described in the 1936 resurvey record of the 2nd Standard Parallel South, through Range 29 E.

From this corner the standard  $\frac{1}{4}$  sec. cor. of sec. 32, bears N.  $89^{\circ} 58'$  W., 2.13 chs. dist. and the standard cor. of secs. 32 and 33 bears S.  $89^{\circ} 58'$  E., 37.83 chs. dist.  
Land, rolling sand dunes.  
Soil, sandy.  
No timber; undergrowth, mesquite and sage.

North Boundary Sec. 4

At a point on the 2nd Standard Parallel South, midway between the closing corners of secs. 3 and 4, and secs. 4 and 5, on N. bdy. of sec. 4. The point for the  $\frac{1}{4}$  sec. cor. of secs. 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.



From this corner the standard corner of secs. 32 and 33, T. 10 S., R. 29 E., bears N.  $89^{\circ} 58'$  W., 2.57 chs. dist. and the standard  $\frac{1}{4}$  cor. of sec. 33 bears S.  $89^{\circ} 58'$  E., 37.46 chs. dist.

From the corner of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp. N.  $0^{\circ} 11'$  E., bet. secs. 31 and 32.


Over gently rolling land, through undergrowth.

1.40 Wire fence, bears E. and W.

3.70 Bladed road, bears E. and W.


40.28 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.



80.57 Point for the corner of secs. 29, 30, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.



## Dependent Resurvey of Subdivision, T, 11 S., R. 29 E.

## Chains.

Land, gently rolling.  
Soil, sandy clay.  
No timber; undergrowth, greasewood.

From the corner of secs. 28, 29, 32, and 33.

N. 88° 52' W., bet. secs. 29 and 32.

Over gently rolling land, through undergrowth.

40.00

Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 29 \\ \hline \frac{1}{4} \text{ S } 32 \\ 1952 \end{array}$$

50.50

Shallow wash, drains NNE.

79.99

The corner of secs. 29, 30, 31, and 32.

Land, gently rolling.  
Soil, sandy and gravelly.  
No timber; undergrowth, greasewood.

N. 88° 57' W., bet. secs. 30 and 31.

Over gently rolling land, through undergrowth.

39.95

Point for the  $\frac{1}{4}$  sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 30 \\ \hline \frac{1}{4} \text{ S } 31 \\ 1952 \end{array}$$

46.60

Shallow wash, drains NE.

69.60

Old road, bears NNE. and SSW.

76.16

The corner of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp.

Land, gently rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood, mesquite and yucca.

From the corner of secs. 29, 30, 31, and 32.

N. 0° 16' W., bet. secs. 29 and 30.

Over gently rolling land, through undergrowth.

40.28

Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground over a deposit of broken glass, with brass cap mkd.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

$$\begin{array}{c} \frac{1}{4} \\ | \\ S30 \quad | \quad S29 \\ | \\ 1952 \end{array}$$

62.60 Draw, drains NE.

80.57 Point for the corner of secs, 19; 20, 29, and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.
$$\begin{array}{c} T11SR29E \\ \hline S19 \quad | \quad S20 \\ \hline S30 \quad | \quad S29 \\ | \\ 1952 \end{array}$$

Land, gently rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood.

From the corner of secs. 20, 21, 28, and 29.

N. 88° 56' W., bet. secs. 20 and 29.

Over gently rolling land, through undergrowth.

0.75 Wire fence, bears N. and S.

15.50 Shallow wash, drains NE.

40.13 Point for the  $\frac{1}{4}$  sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.
$$\begin{array}{c} S 20 \\ \hline \frac{1}{4} S 29 \\ 1952 \end{array}$$

66.00 Wash, 30 lks. wide, 5 ft. deep, drains NNE.

80.26 The corner of secs. 19, 20, 29, and 30.

Land, gently rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood and mesquite.

N. 88° 57' W., bet. secs. 19 and 30.

Over gently rolling land, through undergrowth.

18.95 Old road, bears NW. and SE.

40.10 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.
$$\begin{array}{c} S 19 \\ \hline \frac{1}{4} S 30 \\ 1952 \end{array}$$

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains	
59.75	Old road, bears N. and S.
66.50	Shallow wash, drains NE.
76.27	The corner of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp. Land, gently rolling. Soil, sandy. No timber; undergrowth, greasewood.
	From the corner of secs. 19, 20, 29, and 30. N. 0° 16' W., bet. secs. 19 and 20. Over gently rolling land, through undergrowth.
40.28	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\   \\ S19 \quad S20 \\   \\ 1952 \end{array}$
80.57	Point for the corner of secs. 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. $\begin{array}{c} T11SR29E \\ S18 \quad S17 \\ \hline S19 \quad S20 \\   \\ 1952 \end{array}$ Land, gently rolling. Soil, sandy. No timber; undergrowth, greasewood and mesquite.
	From the corner of secs. 16, 17, 20, and 21. N. 88° 58' W., bet. secs. 17 and 20. Over gently rolling land, through undergrowth.
38.10	Shallow wash, drains NNE.
40.18	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd. $\begin{array}{c} S 17 \\ \hline S 20 \\   \\ 1952 \end{array}$
80.37	The corner of secs. 17, 18, 19, and 20. Land, gently rolling. Soil, sandy. No timber; undergrowth, greasewood and mesquite.

Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains

N. 88° 58' W., bet. secs. 18 and 19.

Over gently rolling land, through undergrowth.

3.60 Shallow wash, drains NE.

40.13 Point for the  $\frac{1}{4}$  sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$  S 18  
S 19  
1952

70.10 Shallow wash, drains NW.

76.24 The corner of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp.

Land, gently rolling.  
Soil, sandy and gravelly.  
No timber, undergrowth, greasewood and mesquite.

From the corner of secs. 17, 18, 19, and 20.

N. 0° 24' W., bet. secs. 17 and 18.

Over rolling land, through undergrowth.

4.40 Wash, 8 lks. wide, 4 ft. deep, drains NE.

40.28 Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$\frac{1}{4}$   
S18 | S17  
1952

80.57 Point for the corner of secs. 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

T11SR29E  
S 7 | S 8  
S18 | S17  
1952

Land, rolling.  
Soil, sandy.  
No timber; undergrowth, greasewood, mesquite and sage.

From the corner of secs. 8, 9, 16, and 17.

N. 89° 03' W., bet. secs. 8 and 17.

Over gently rolling land, through undergrowth.

40.14 Point for the  $\frac{1}{4}$  sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.



## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

## Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 8 \\ \hline \text{S } 17 \\ 1952 \end{array}$$

69.70 Shallow wash, drains NNE.

80.29 The corner of secs. 7, 8, 17, and 18.

Land, gently rolling.

Soil, sandy.

No timber; undergrowth, greasewood and mesquite.

N.  $89^{\circ} 03'$  W., bet. secs. 7 and 18.

Over rolling land, through undergrowth.

7.80 Wash, 10 lks. wide, 2 ft. deep, drains NNW.

40.13 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \text{S } 7 \\ \hline \frac{1}{4} \text{ S } 18 \\ 1952 \end{array}$$

60.00 Ascend gradually.

70.00 Top of ascent; thence over gently rolling land.

76.17 The corner of secs. 7, 12, 13, and 18.

Land, rolling.

Soil, sandy and gravelly.

No timber; undergrowth, greasewood, mesquite and sage.

From the corner of secs. 7, 8, 17, and 18.

N.  $0^{\circ} 24'$  W., bet. secs. 7 and 8.

Over rolling land, through undergrowth.

40.28 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ \hline \text{S } 7 \quad | \quad \text{S } 8 \\ 1952 \end{array}$$

49.50 Left bank of San Simon wash, 10 ft. deep, drains WNW.

52.00 Right bank of wash.

58.50 Old road, bears E. and W.

71.10 Wire fence, bears E. and W.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

Chains	
72.00	Thence over rolling sand dunes.
80.57	Point for the corner of secs. 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.  $\begin{array}{c} T11SR29E \\ \hline S 6 \quad   \quad S 5 \\ \hline S 7 \quad   \quad S 8 \end{array}$ <p style="text-align: center;">1952</p> Land, rolling. Soil, sandy. No timber; undergrowth, mesquite and sage.
	From the corner of secs. 4, 5, 8, and 9. N. $89^{\circ} 04'$ W., bet. secs. 5 and 8. Over rolling land, through undergrowth.
34.60	Wash, 20 lks. wide, 2 ft. deep, drains S.
40.23	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.  $\begin{array}{c} S 5 \\ \hline \frac{1}{4} S 8 \\ 1952 \end{array}$
80.47	The corner of secs. 5, 6, 7, and 8.  Land, rolling sand dunes. Soil, sandy. No timber; undergrowth, mesquite and sage.
	N. $89^{\circ} 04'$ W., bet. secs. 6 and 7. Over rolling sand dunes, through undergrowth.
40.17	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground over a deposit of broken glass, with brass cap mkd.  $\begin{array}{c} S 6 \\ \hline \frac{1}{4} S 7 \\ 1952 \end{array}$
60.00	old road, bears NW. and SE.
76.01	The corner of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp.  Land, rolling sand dunes. Soil, sand. No timber; undergrowth, mesquite and sage.

## Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

## Chains

From the corner of secs. 5, 6, 7, and 8

N.  $0^{\circ} 45'$  E., bet, secs. 5 and 6

Over rolling sand dunes, through undergrowth.

40.29

Point for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 6 \ | \ S\ 5 \\ | \\ 1952 \end{array}$$

69.16

The closing corner of secs. 5 and 6, T. 11 S., R. 29 E., which is an iron post, 2 ins. diam., set, and marked as described in the 1936 resurvey record of the 2nd Standard Parallel South, through Range 29 E.

From this corner the standard  $\frac{1}{4}$  sec. cor. of sec. 31, bears N.  $89^{\circ} 58'$  W., 1.70 chs. dist. and the standard cor. of secs. 31 and 32 bears S.  $89^{\circ} 58'$  E., 38.37 chs. dist.

Land, rolling sand dunes.

Soil, sandy.

No timber; undergrowth, mesquite and sage.

## North Boundary Sec. 5

At a point on the 2nd Standard Parallel South, midway between the closing corners of secs. 4 and 5, and secs. 5 and 6, on N. bdy. of sec. 5. The point for the  $\frac{1}{4}$  sec. cor. of sec. 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \ S \ 5 \\ \hline 1952 \end{array}$$

From this corner the standard corner of secs. 31 and 32, T. 11 S., R. 29 E., bears N.  $89^{\circ} 58'$  W., 1.85 chs. dist. and the standard  $\frac{1}{4}$  cor. of sec. 32 bears S.  $89^{\circ} 58'$  E., 38.09 chs. dist.

## North Boundary Sec. 6

At a point on the 2nd Standard Parallel South, at proportionate distance, between the closing corner of secs. 5 and 6, and the closing corner of Ts. 11 S., Rs. 28 and 29 E. The point for the  $\frac{1}{4}$  sec. cor. of sec. 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \ S \ 6 \\ \hline 1952 \end{array}$$

From this corner the standard corner of Ts. 10 S., Rs. 28 and 29 E., bears N.  $89^{\circ} 58'$  W., 2.415 chs. dist. and the standard  $\frac{1}{4}$  cor. of sec. 31 bears S.  $89^{\circ} 58'$  E., 38.66 chs. dist.

Dependent Resurvey of Subdivision, T. 11 S., R. 29 E.

General Description

The land within the boundaries of this township is gently rolling to rolling, except for a broad level flat along San Simon wash. The north and east tiers of sections is mostly sand dunes. The drainage in the north and east portions of the township is to the south and west, and in the south and west portions to the northeast into San Simon wash which drains northwest. This wash enters the township on the south boundary of sec. 35, and leaves the township the west boundary at the corner of secs. 1, 6, 7, and 12.

The soil is sandy except along and near San Simon wash which is a silt and sandy clay. There is no timber in the township, undergrowth consist of greasewood, mesquite and sage. There are four flowing water wells within the township, two of which are located in sec. 36, one in sec. 14 and one in sec. 1. There are several dirt dams and tanks in the township. There is approximately 13 miles of bladed roads in the township.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

BOOK 4417

FIELD ASSISTANTS

NAMES	CAPACITY
Jesse A Livesay	Cartographic Survey Aid
O. Charles Harper	Cartographic Survey Aid
Charles A. Neal	Cartographic Survey Aid
Earl G. McKean	Cartographic Survey Aid
Max Lester	Cartographic Survey Aid
Kenneth L Nelson	Cartographic Survey Aid

CERTIFICATE OF CADASTRAL ENGINEER

I, Clarence E. Bilbray, HEREBY CERTIFY upon honor that, in  
pursuance of special instructions bearing date of the 10th day of March, 1952,  
I have ~~surveyed~~ independently resurveyed south, east and west boundaries and  
subdivisional lines, T. 11 S., R. 29 E.

Gila and Salt River  
of the \_\_\_\_\_ Meridian, in the State of Arizona, which are  
represented in the foregoing field notes as having been executed by me and under my direction; and that  
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the  
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing  
field notes.

Albuquerque, New Mexico  
August 22, 1952

Clarence E. Bilbray  
Clarence E. Bilbray  
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., JAN 25 1954, 19\_\_\_\_

re-  
The foregoing field notes of the survey of the south, east and west boundaries and  
subdivisional lines of T. 11 S., R. 29 E., of the Gila and Salt River Meridian,  
in the State of Arizona.

executed by Clarence E. Bilbray, Cadastral Engineer  
having been critically examined and found correct, are hereby approved.

James B. Ciment  
Assistant Chief, Division of Cadastral Engineering.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 11 S.,  
R. 29 E., G. & S.R.M. Ariz is a true copy of the original field notes.

\_\_\_\_\_  
Chief, Division of Cadastral Engineering.