

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

①

4439

FIELD NOTES

of the

Dependent Resurvey of the South Boundary,

the Independent Resurvey of the East Boundary

and the

Survey of the North Boundary and Subdivisional Lines

of

Township 5 North, Range 18 West.

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Ty White, Cadastral Engineer

Under special instructions dated October 9, 1952, which provided
for the surveys included under Group No. 285, approved October 21, 1952
and assignment instructions dated November 7, 1952

Survey commenced November 17, 1952

Survey completed December 30, 1952

4439

4439

(1A)

BOOK 4439

INDEX DIAGRAM

Township 5 North, Range 18 West.
14 14 14 13 12 11

6	47 5	39 4	34 3	28 2	22 1	10
46	46	39	33	27	21	
7	45 8	38 9	33 10	27 11	20 12	9
45	44	38	32	26	19	
18	44 17	37 16	32 15	26 14	18 13	9
44	43	36	31	25	18	
19	42 20	36 21	31 22	25 23	17 24	8
42	42	36	30	24	17	
30	41 29	35 28	30 27	23 26	16 25	7
41	40	35	29	23	16	
31	39 32	34 33	29 34	22 35	15 36	6
1	2	3	4	5	6	

(B)

T. 5 N., R. 18 W.

BOOK 4439

The west boundary of T. 5 N., R. 18 W. was surveyed by Ty White and Claude F. Warner, Cadastral Engineers, in 1950. The south boundary which is the First Standard Parallel North was surveyed by John F. Hesse, Deputy Surveyor, in 1909, and resurveyed by Woodbury Abbey, Surveyor, Roy J. Gill and Hans D. Voigt, Transitmen, in 1915. This boundary was retraced and the east boundary surveyed by Charles E. Hunter, Transitman, in 1927. The following field notes describe the dependent resurvey of the south boundary, the independent resurvey of the east boundary and the survey of the north boundary and subdivisional lines of T. 5 N., R. 18 W.

The survey was executed with light mountain solar transits made by Buff and Buff, serial No. 26066 and W. and L. E. Gurley, serial No. 461263, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instruments were in good condition and having been placed in satisfactory adjustment prior to the beginning of the survey were tested and found free from appreciable error.

The direction of the lines were determined by the solar transit method. The measurements were made with a Lufkin steel tape, 5 chains in length, graduated to tenths of a link for the first ten links, every link for the balance of the first 100 links and the remainder at intervals of 10 links. The tape was tested by comparison with a standard steel tape and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents only are entered in this field note record. Lines connecting previously established corners were run by the random and true method but the random lines are omitted from the field notes.

The data furnished with the special instructions give the geographic position of the southeast corner of the township as latitude $33^{\circ} 43' 28''$ N. and longitude $114^{\circ} 09' 07''$ W. Elevation approximately 750 ft.

November 16, 1952; at camp in section 31, T. 5 N., R. 18 W., G. and S. R. Meridian, Arizona, in approximate latitude $33^{\circ} 43' 30''$ N. and longitude $114^{\circ} 09' 43''$ W. I make an hour angle observation on Polaris east of the meridian for azimuth and latitude, making four observations, two each with the telescope in direct and reversed positions, observing simultaneously the vertical angle to Polaris and the horizontal angle from the east edge of a tree on the sky-line approximately 4 miles N., W. to Polaris. My watch reads correct Mountain Standard Time as checked with radio time signals.

Mean watch time of observation	5h 28m 42s p.m.
Watch fast of l.m.t.	0h 36m 36s
Mean horizontal deflection angle	25° 50' 52"
Azimuth of Polaris	1° 07' 36"
Bearing of reference point	N: 26° 58' 28" E.
Mean observed vertical angle	33° 55' 31"
Reduced latitude	33° 43' 42" N.

Every 30m from 8 to 10:30 a.m. and from 1:30 to 4 p.m., we make proper settings on the arcs of the solar attachments and ascertain that the resulting orientations of the instruments, when compared with the meridian established by Polaris observation, have a maximum error of less than $1' 30''$.

We repeat the tests of the arcs daily by noon observation and verify the meridional indications at frequent intervals throughout the survey.

The mean observed magnetic declination is $14\frac{1}{2}^{\circ}$ E.

Dependent Resurvey, 1st Stan. Par. N.
S. Bdy. T. 5 N., R. 18 W.

Reestablishment of the Survey executed by John F. Hesse, Deputy Surveyor, in 1909 and the Resurvey by Woodbury Abbey, Surveyor, Roy J. Gill and Hans D. Voigt, Transitmen, in 1915.

Dependent Resurvey, 1st Stan. Par. N.
S. Bdy. T. 5 N., R. 18 W.

Chains	
	<p>From the standard cor. of Tps. 5 N., Rs. 18 and 19 W., which is monumented with an iron post, 3 ins. diam., firmly set in the ground, marked and witnessed as described in the official record.</p> <p>EAST, along the S. bdy. of sec. 31.</p> <p>Over gently rolling land, through scattering timber.</p>
2.80	Wash, 30 lks. wide, course NW.
27.60	Wash, 50 lks. wide, course NW.
40.03	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented by a sandstone, 16x16x12 ins. firmly set in the ground, mkd. S C $\frac{1}{4}$ on N. face and witnessed with a mound of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C <u>$\frac{1}{4}$ S 31</u> 1952</p> </div> <p>Bury the original corner stone alongside the iron post.</p>
	<p>N. 89° 55' E., beginning new measurement.</p>
8.90	State Highway No. 95, bears N. and S.
10.50	Wash, 20 lks. wide, course NW.
31.71	The closing corner of Tps. 4 N., Rs. 18 and 19 W. is 4 lks. S. of line and is monumented with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.
40.03	<p>The standard corner of secs. 31 and 32, monumented with a malpais stone, 16x12x10 ins., firmly set, mkd. and witnessed as described in the official record.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div style="text-align: center;"> <p>S C T 5 N R 18 W <u>S 31 S 32</u> 1952</p> </div> <p>Bury the original corner stone alongside the iron post.</p> <p>Land, gently rolling. Soil, gravelly and rocky. Timber, ironwood and palo verde; und. greasewood.</p>
	<p>N. 89° 57' E., along the S. bdy. of sec. 32.</p> <p>Over gently rolling land, through scattering timber.</p>
2.90	Wash, 20 lks. wide, course NW.
15.50	Left bank of wash, bears NW. and SE.

Dependent Resurvey, 1st Stan. Par. N.
S. Bdy. T. 5 N., R. 18 W.

BOOK 4439

Chains											
29.00	Right bank of wash, bears NW. and SE.										
36.50	Wash, 40 lks. wide, course N. 70° W.										
40.06	The standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented with a malpais stone, 10x12x8 ins., firmly set, marked and witnessed as described in the official record.										
	At the corner point										
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground with brass cap mkd.										
	<table style="margin: auto;"> <tr><td>S</td><td>C</td></tr> <tr><td>$\frac{1}{4}$</td><td>S 32</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1952</td></tr> </table>	S	C	$\frac{1}{4}$	S 32	<hr/>		1952			
S	C										
$\frac{1}{4}$	S 32										
<hr/>											
1952											
	Bury the original corner stone alongside the iron post.										
	N. 89° 50' E., beginning new measurement.										
8.50	Wash, 40 lks. wide, course SW.										
12.00	Recess wash, 40 lks. wide, course NW.										
30.63	The closing corner of secs. 5 and 6, T. 4 N., R. 18 W., monumented by an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.										
39.91	The standard corner of secs. 32 and 33, monumented by a malpais stone, 16x10x8 ins., firmly set in the ground, marked and witnessed as described in the official record.										
	At the corner point										
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.										
	<table style="margin: auto;"> <tr><td>S</td><td>C</td></tr> <tr><td>T 5 N</td><td>R 18 W</td></tr> <tr><td>S 32</td><td>S 33</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1952</td></tr> </table>	S	C	T 5 N	R 18 W	S 32	S 33	<hr/>		1952	
S	C										
T 5 N	R 18 W										
S 32	S 33										
<hr/>											
1952											
	Bury the original corner stone alongside the iron post.										
	Land, rolling. Soil, rocky and gravelly. Timber, ironwood and palo verde; undergrowth, greasewood.										
	S. 89° 57' E., along the S. bdy. of sec. 33.										
	Over gently rolling land, through scattering timber.										
6.40	Wash, 20 lks. wide, course N. 60° W.										
23.10	Wash, 20 lks. wide, course NW.										
39.82	The standard $\frac{1}{4}$ sec. cor. of sec. 33, monumented by a malpais stone, 16x8x8 ins., firmly set in the ground, marked and witnessed as described in the official record.										
	At the corner point										
	Set an iron post, 28 ins. long; $2\frac{1}{2}$ ins. diam., 26 ins. in the ground with brass cap mkd.										

BOOK 4439

Dependent Resurvey, 1st Stan. Par. N.
S. Bdy. T. 5 N., R. 18 W.

Chains

S O

 $\frac{1}{4}$ S 33

1952

Bury the original corner stone alongside the iron post.

N. 89° 59' E., beginning new measurement.

18.50 Wash, 20 lks. wide, course NW.

30.82 The closing corner of secs. 4 and 5, T. 4 N., R. 18 W. monumented by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

40.11 The standard corner of secs. 33 and 34, monumented by a malpais stone, 18x12x8 ins., firmly set in the ground, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

S O

T 5 N R 18 W

 $\frac{1}{4}$ S 33 | S 34

1952

Bury the original corner stone alongside the iron post.

Land, rolling.

Soil, rocky and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

S. 89° 56' E., along the S. bdy. of sec. 34.

Over rolling land, through scattering timber.

3.30 Wash, 20 lks. wide, course NW.

10.50 Wash, 30 lks. wide, course N. 60° W.

40.00 The standard $\frac{1}{4}$ sec. cor. of sec. 34, monumented by a malpais stone, 14x10x10 ins., firmly set in the ground, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground with brass cap mkd.

S O

 $\frac{1}{4}$ S 34

1952

Bury the original corner stone alongside the iron post.

S. 89° 50' E., beginning new measurement.

12.50 Old road, bears SE. and NW.

15.50 Wash, 40 lks. wide, course N. 60° W.

Dependent Resurvey, 1st Stan. Par. N.
S. Bdy. T. 5 N., R. 18 W.

BOOK 4439

Chains	
31.18	The closing corner of secs. 3 and 4, T. 4 N., R. 18 W., monumented by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.
32.20	Wash, 40 lks. wide, course N. 60° W.
34.50	Recross wash, 40 lks. wide, course SW.
39.98	The standard corner of secs. 34 and 35, monumented by an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.
	Land, rolling. Soil, rocky and gravelly. Timber, ironwood and palo verde; undergrowth, greasewood.
	S. 89° 17' E., along the S. bdy. of sec. 35.
	Over mountainous land, through scattering timber.
5.00	Enter mountainous land, bears NE. and SW.; asc. 736 ft. over broken NW. slope.
19.00	Spur, slopes N.; 5 chs. to toe; continue ascent along a general N. slope.
28.70	Top of sharp rocky peak, 75 ft. high.
39.79	The witness standard $\frac{1}{4}$ sec. cor. of sec. 35, monumented by an iron post, 1 in. diam., firmly set in a mound of stone, marked and witnessed as described in the official record.
40.04	The true point for the standard $\frac{1}{4}$ sec. cor. of sec. 35 which falls in a ravine, course N.
	From the true point for the standard $\frac{1}{4}$ sec. cor. of sec. 35. N. 89° 02' E., beginning new measurement. Continue ascent over W. slope.
6.00	Top of high ridge, bears N. and S.; desc. 400 ft. over cliffs, general NE. slope.
13.25	Ravine, course SE.; asc. 443 ft. over SW. slope.
31.20	The closing corner of secs. 2 and 3, T. 4 N., R. 18 W. is 14 lks. S. of line and is monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, marked and witnessed as described in the official record.
40.13	The standard corner of secs. 35 and 36, monumented by an iron post, 3 ins. diam., firmly set in a mound of stone, marked and witnessed as described in the official record.
	Land, mountainous. Soil, rocky. Timber, ironwood and palo verde; undergrowth, greasewood.
	EAST, along the S. bdy. of sec. 36.
	Over mountainous land, through scattering timber.
	Ascend 80 ft. over cliff, facing W.

BOOK 4439

Dependent Resurvey, 1st Stan. Par. N.,
S. Rdy. T. 5 N., R. 18 W.

Chains	
1.20	Ridge spur, slopes S.; desc. 744 ft. over E. slope.
(Approx)	Thence by triangulation 33.78 chs.
11.00	Ravine, course SE.
(Approx)	
12.00	Spur, slopes SE.
(Approx)	
14.00	Ravine, course S.
(Approx)	
16.00	Wash, in bottom of canyon, course S. for 10 chains then W.; asc. 500 ft. over W. slope.
39.99	True point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance, which falls on slide rock. Impracticable to monument.
	From the true point for the standard $\frac{1}{4}$ sec. cor. of sec. 36.
	N. $89^{\circ} 52'$ E., beginning new measurement.
	Continue over precipitous ascent.
2.95	The witness standard $\frac{1}{4}$ sec. cor. of sec. 36., which is monumented by an iron post, 1 in. diam., firmly set in a mound of stone, mkd. as described in the official record. No accessories.
15.82	Ridge, bears N. and S.; desc. 350 ft. over E. slope. Thence by triangulation 19.97 chs.
(Approx)	
24.00	Ravine, course N.; asc. 500 ft. over W. slope.
31.15	Find no evidence of the closing corner of secs. 1 and 2, T. 4 N., R. 18 W.
35.80	Top of Haystack Mountain; descend over bluff, bears N. and S.
39.99	The standard corner of Tps. 5 N., Rs. 17 and 18 W., monumented by an iron post, 3 ins. diam., firmly set in a mound of stone, marked and witnessed as described in the official record.
	Land, mountainous. Soil, rocky. Timber, palo verde and ironwood; undergrowth, greasewood.
Independent Resurvey, of Range Line, T. 5 N., Bet. Rs. 17 and 18 W.	
Independent Resurvey, superseding the Survey executed by Charles E. Hunter, Transitman, in 1927.	
Preliminary to the subdivision of T. 5 N., R. 18 W. the east boundary was retraced and found to be out of limits for measurement. As the townships to the east and west of the line had not been subdivided, the line was subject to rectification, therefore the line was resurveyed and all evidence of the orig- inal corners destroyed as follows:	
	From the standard corner of Tps. 5 N., Rs. 17 and 18 W.
	N. $0^{\circ} 02'$ W., bet. secs. 31 and 36.
	Over mountainous land, through scattering timber.
	Descend 816 ft. over NE. slope. of Haystack Mountain.
39.84	The orig. $\frac{1}{4}$ sec. cor. of secs. 31 and 36, bears EAST, 9 lks. dist., monumented by an iron post, 1 in. diam., firmly set in a mound of stone, mkd. and witnessed as described in the official record.


Independent Resurvey of Range Line,
T. 5 N., Bet. Rs. 17 and 18 W.

ECCOK 4439

Chains

40.00

Destroy all evidence of this corner.
Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.
Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.



Enter small valley; desc. gradually 58 ft. over NE. slope.

54.40

Wash, 50 lks. wide, course NW.; asc. 75 ft. over S. slope.

66.55


Detached spur, bears E. and W.; desc. 68 ft. along top of a spur, slopes N.

79.78

The orig. cor. of secs. 25, 30, 31 and 36, bears EAST, 8 lks. dist., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, mkd. and witnessed as described in the official record.
Destroy all evidence of this corner.

80.00

Point for the cor. of secs. 25, 30, 31 and 36.
Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.



Land, mountainous.
Soil, rocky and gravelly.
Timber, ironwood and palo verde; undergrowth, greasewood.

N. 0° 02' W., bet. secs. 25 and 30.

Over rolling land, through scattering timber.

5.00

Descend 46 ft. along point of spur, slopes N.

35.00


Wash, 50 lks. wide, course N. 60° W.

39.79

The orig. $\frac{1}{4}$ sec. cor. of secs. 25 and 30, bears EAST, 7 lks. dist., monumented by an iron post, 1 in. diam., firmly set in a mound of stone, mkd. and witnessed as described in the official record.
Destroy all evidence of this corner.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.
Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.



51.30

Ascend S. slope.

57.80

Old road, bears N. 70° W. and S. 70° E.

62.00

Spur, slopes W.; desc. N. slope.

70.50

Wash, 20 lks. wide, course NW.

79.73

The orig. corner of secs. 19, 24, 25 and 30, bears EAST, 3 lks. dist., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, mkd. and witnessed as described in the official record.
Destroy all evidence of this corner.

Independent Resurvey, of Range Line
T. 5 N., Bet. Rs. 17 and 18 W.

Chains

79.90 Wash, 30 lks. wide, course SW.

80.00 Point for the cor. of secs. 19, 24, 25 and 30 falls in wash.
Impracticable to monument the corner.

Land, rolling.


Soil, rocky and gravelly.

Timber, ironwood and palo verde; undergrowth, greasewood.

N. 0° 02' W., bet. secs. 19 and 24.

Over broken land, through scattering timber.

0.50 Point for the witness cor. of secs. 19, 24, 25, and 30.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground
to solid rock and in a mound of stone to top, with brass cap mkd.


Ascend 46 ft. over S. slope.

12.20 Spur, slopes W.; desc. 29 ft. over N. slope.

24.00 Wash, 20 lks. wide, course NW.; asc. 51 ft. over S. slope.

28.80 Spur, slopes W.; desc. 68 ft. over N. slope.

36.70 Wash, 20 lks. wide, course W.


39.56 The orig. $\frac{1}{4}$ sec. cor. of secs. 19 and 24, bears EAST, 3 lks. dist.,
monumented by an iron post, 1 in. diam., firmly set in the ground,
mkd. and witnessed as described in the official record. Destroy
all evidence of this corner.40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24.Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground
and in a mound of stone to top, with brass cap mkd.

62.80 Wash, 20 lks. wide, course W.; asc. 34 ft. over S. slope.

66.30 Top of rocky knoll; desc. 34 ft. over N. slope.

79.49 The original cor. of secs. 13, 18, 19 and 24, monumented by an iron
post, 2 ins. diam., firmly set in the ground, mkd. and witnessed
as described in the official record. Destroy all evidence of this
corner.

80.00 Point for the cor. of secs. 13, 18, 19, and 24.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground
with brass cap mkd.

Independent Resurvey, of Range Line,
T. 5 N., Bet. Rs. 17 and 18 W.

BOOK 4439

Chains

Land, broken.
Soil, rocky and gravelly.
Timber, ironwood and palo verde; undergrowth, greasewood.

- N. 0° 02' W., bet. secs. 13 and 18.
Over mountainous land, through scattering timber.
3.00 Wash, 20 lks. wide, course SW.; asc. 323 ft. over S. slope.
18.70 Ridge, bears E. and W.; desc. 289 ft. over N. slope.
38.71 The orig. $\frac{1}{4}$ sec. cor. of secs. 13 and 18, monumented by an iron post, 1 in. diam., firmly set in a mound of stone, mkd. and witnessed as described in the official record. Destroy all evidence of this cor.
40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18.
Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$
 S 13 | S 18
 1952

- 57.00 Wash, 30 lks. wide, course NW.
76.70 Wash, 20 lks. wide, course NW.
79.39 The orig. cor. of secs. 7, 12, 13 and 18, bears WEST, 3 lks. dist. and is monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, mkd. and witnessed as described in the official record. Destroy all evidence of this corner.
80.00 Point for the corner of secs. 7, 12, 13 and 18.
Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

T 5 N
 R 18 W | R 17 W
 S 12 | S 7
 S 13 | S 18
 1952

Land, mountainous.
Soil, rocky and gravelly.
Timber, ironwood and palo verde; undergrowth, greasewood.

- N. 0° 02' W., bet. secs. 7 and 12.
Over mountainous land, through scattering timber and undergrowth.
7.50 Wash, 20 lks. wide, course W.
9.10 Old road, bears E. and W.
11.00 Wash, 40 lks. wide, course SW.
32.90 Begin ascent of 74 ft. over S. slope.
36.50 Spur, slopes E.; desc. 49 ft. over N. slope.
39.33 The orig. $\frac{1}{4}$ sec. cor. of secs. 7 and 12, bears WEST, 1 lk. dist. and is monumented by an iron post, 1 in. diam., firmly set in the ground, mkd. and witnessed as described in the official record. Destroy all evidence of this corner.

Independent Resurvey of Range Line,
T. 5 N., Bet. Rs. 17 and 18 W.

Chains 40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S 12 S 7 1952 </div> <p>Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p>
54.50	Wash, 20 lks. wide, course SW.
58.60	Begin ascent of 140 ft. over SW. slope.
79.30	The orig. cor of secs. 1, 6, 7 and 12, bears WEST, 2 lks. dist. and is monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, mkd. and witnessed as described in the official record. Destroy all evidence of this corner.
80.00	Point for the cor. of secs. 1, 6, 7 and 12 falls in a small drain, course SW. Impracticable to monument the corner.
	<p>Land, mountainous. Soil, rocky and gravelly. Timber, ironwood and palo verde; undergrowth, greasewood.</p>
	<p>N. $0^{\circ} 02'$ W., bet. secs. 1 and 6.</p> <p>Over mountainous land, through scattering timber.</p> <p>Continue ascent of 156 ft. over SW. slope.</p>
0.50	<p>Point for the witness corner of secs. 1, 6, 7 and 12.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.</p> <div style="text-align: center;"> T 5 N R 18 W R 17 W S 1 S 6 ----- S 12 S 7 WC 1952 </div>
10.90	Ridge, bears SE. and W.; desc. 50 ft. over NW. slope.
14.00	Drain, course NE.; asc. 41 ft. over S. slope.
17.40	Spur, slopes E.; desc. 21 ft. over N. slope.
18.50	Drain, course E.; asc. 91 ft. over S. slope.
23.80	Spur, slopes N. 70° E.; desc. 132 ft. over N. slope.
32.80	Drain, course E.; asc. 26 ft. over SE. slope.
37.60	Spur, slopes N. 70° E.; desc. 75 ft. over NW. slope.
39.10	The orig. $\frac{1}{4}$ sec. cor. of secs. 1 and 6, bears WEST, 3 lks. dist. and is monumented by an iron post, 1 in. diam., firmly set in a mound of stone, mkd. and witnessed as described in the official record. Destroy all evidence of this corner.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6.

Independent Resurvey, of Range Line,
T. 5 N., Bet. Rs. 17 and 18 W.

BOOK 4439

Chains

Set an iron post, 3 ft. long, 1 1/2 in. diam., 14 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

$\frac{1}{2}$
 S 1 | S 6
 1952

Continue descent over NW. slope.

45.00 Wash, 30 lks. wide, course N. 70° E.; asc. 141 ft. over SE. slope.

54.40 Spur, slopes N. 70° E.; desc. 234 ft. over NW. slope.

65.00 Wash, 30 lks. wide, course NE.

74.00 Point for the cor. of Tps. 5 and 6 N., R. 18 W., established at point East of the cor. of Tps. 5 and 6 N., Rs. 18 and 19 W.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N	
R 18 W	
S 36	T 5 N
<hr/>	
S 1	R 17 W
T 5 N	S 6

1952

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of corner.

81.83 The cor. of Tps. 5 and 6 N., Rs. 17 and 18 W. which is monumented by an iron post, 3 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record. As this corner now refers to the sections of Tps. 5 and 6 N., R. 17 W. only the markings on the brass cap are changed to read.

	T 6 N	
	R 17 W	
T 6 N	S 31	
R 18 W	<hr/>	
S 36	S 6	
	T 5 N	

1952

1927

Rebuild the mound of stone, 3 ft. base, 2 1/2 ft. high, E. of cor. Land, mountainous.

Soil, rocky and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

North Boundary of T. 5 N., R. 18 W.

From the corner of Tps. 5 and 6 N., R. 18 W.

WEST, bet. secs. 1 and 36.

Over mountainous land, through scattering timber and undergrowth.

Ascend 21 ft. over E. slope.

3.00 Spur, slopes N.; desc. 29 ft. over W. slope.


7.90 Drain, course N.; asc. 38 ft. over E. slope.

14.30 Spur, slopes N.; desc. 40 ft. over W. slope.


17.90 Wash, 40 lks. wide, course NE.: ASC. 126 ft. over SE. slope.

Chains

- 20.95 State Highway No. 95, bears NE. and SW.
 - 39.60 Spur, slopes NE.; desc. 20 ft. over NW. slope.
 - 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.



- Descend 106 ft. over NW. slope.
 - 45.90 Drain, course N.; asc. 28 ft. along N. slope.
 - 47.90 Point of a spur, slopes N.; desc. 32 ft. along N. slope.
 - 53.00 Right bank of wash, bears N. 70° E. and S. 70° W.
 - 58.50 Left bank of wash, bears N. 70° E. and S. 70° W.; asc. 46 ft. over E. slope.
 - 64.70 Spur, slopes N.; desc. 52 ft. over W. slope.
 - 72.30 Wash, 20 lks. wide, course N.
 - 73.00 Old road, bears N. 20° E. and S. 20° W.
 - 80.00 Point for the cor. of secs. 1, 2, 35 and 36.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.




Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous.
Soil, rocky and gravelly.
Timber, palo verde and ironwood; undergrowth, greasewood.

WEST, bet. secs. 2 and 35.

Over mountainous land, through scattering timber.

- 4.30 Ascend 139 ft. over NE. slope.
 - 14.40 Ridge, bears NW. and SE.; desc. 251 ft. over SW. slope.
 - 29.00 Wash, 30 lks. wide, course SW.; asc. 237 ft. over E. slope.
 - 38.85 Spur, slopes S.; desc. 152 ft. over W. slope.
 - 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.



North Boundary of T. 5 N., R. 18 W.

Chains

Continue descent over cliffs.


45.00 Ravine, course SW.; asc. 42 ft. over E. slope.

59.60 Spur, slopes S.; desc. 280 ft. over W. slope.

67.00 Foot of descent, bears N. and S.

80.00 Point for the cor. of secs. 2, 3, 34 and 35.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, mountainous.
 Soil, rocky and gravelly.
 Timber, ironwood and palo verde; undergrowth, greasewood.

WEST, bet. secs. 3 and 34.

Over rolling land, through scattering timber and undergrowth.

2.30 Detached spur, bears N. and S.

5.00 Wash, 20 lks. wide, course SW.


9.00 Recross wash, 20 lks. wide, course NW.

14.00 Detached spur, bears NW. and SE.

18.80 Foot of descent, bears N. and S.; enter valley.

40.00 Point for the ¼ sec. cor. of secs. 3 and 34.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.




Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

55.50 Wash, 30 lks. wide, course SW.

80.00 Point for the cor. of secs. 3, 4, 33 and 34.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling.
 Soil, gravelly.
 Timber, ironwood and palo verde; undergrowth, greasewood.


North Boundary of T. 5 N., R. 18 W.

Chains

WEST, bet. secs. 4, and 33.
Over rolling land, through scattering timber and undergrowth.

40.00 Point for the 1/4 sec. cor. of secs. 4 and 33.


Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.

80.00 Point for the cor. of secs. 4, 5, 32 and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.




Raise a mound of stone 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.
Soil, sandy and gravelly.
Timber, palo verde and ironwood; undergrowth, greasewood.

WEST, bet. secs. 5 and 32.
Over rolling land, through scattering timber and undergrowth.


40.00 Point for the 1/4 sec. cor. of secs. 5 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



80.00 Point for the cor. of secs. 5, 6, 31 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.
Soil, sandy loam.
Timber, palo verde and ironwood; undergrowth, greasewood.

WEST, bet. secs. 6 and 31.
Over rolling land, through scattering timber and undergrowth.

North Boundary of T. 5 N., R. 18 W.

Chains
0.25 Top of sand ridge, bears N. and S.
40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 31}{S\ 6}$
1952

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
79.38 The cor. of Tps. 5 and 6 N., Rs. 18 and 19 W., monumented by an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.

Land, rolling.
Soil, sandy loam.
Timber, paloverde and ironwood; undergrowth, greasewood.

Subdivision of T. 5 N., R. 18 W.

From the standard cor. of secs. 35 and 36 on the S. bdy. of the Tp. N. $0^{\circ} 03' W.$, bet. secs. 35 and 36.
Over mountainous land, through scattering timber and undergrowth.
2.00 Spur, course S. $10^{\circ} E.$
12.75 Spur, course SW.
17.00 Ravine, course W.
31.25 Ravine, course W.
40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$
S 35 | S 36
1952

46.00 Ravine, course W.; asc. 102 ft. over SE. slope.
57.00 Top of sharp peak; desc. 328 ft. over N. slope.
71.70 Ravine, course NW.; asc. 52 ft. over S. slope.
80.00 Point for the cor. of secs. 25, 26, 35 and 36.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.

T 5 N R 18 W
S 26 | S 25
S 35 | S 36
1952

Land, mountainous.
Soil, rocky.
Timber, paloverde and ironwood; undergrowth, greasewood.

Subdivision of T. 5 N., R. 18 W.

Chains	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp. N. 89° 55' W., bet. secs. 25 and 36. Over mountainous land, through scattering timber. Descend 26 ft. over W. slope.
3.35	Foot of descent, bears N. and S.
12.15	Wash, 50 lks. wide, course NW.
32.35	Wash, 50 lks. wide, course N.
39.92	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd. $\frac{1}{4}$ S 25 S 36 1952
40.85	Begin ascent of 726 ft. over E. slope.
64.60	Ridge, bears N. 15° W. and S. 15° E.; desc. 406 ft. over W. slope.
76.65	Ravine, course NW.
77.00	Spur, slopes N. 60° W.; desc. 98 ft. over SW. slope.
79.84	The cor. of secs. 25, 26, 35 and 36. Land mountainous. Soil, rocky. Timber, paloverde and ironwood; undergrowth, greasewood.
	N. 0° 03' W., bet. secs. 25 and 26. Over mountainous land, through scattering timber and undergrowth.
0.50	Spur, slopes NW.
1.10	Ravine, course NW.; asc. approx. 300 ft. over SW. slope.
18.96	Ridge spur, slopes NW.; desc. approx. 300 ft. over NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd. $\frac{1}{4}$ S 26 S 25 1952
	Leave mountainous, enter rolling land, bears NW. and SE.
40.50	Wash, 25 lks. wide, course NW.
61.50	Wash, 20 lks. wide, course NW.
75.80	Wash, 5 lks. wide, course NW.
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd. T 5 N R 18 W S 23 S 24 S 26 S 25 1952

Subdivision of T. 5 N., R. 18 W.

Chains

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, S. ½, mountainous; N. ½, rolling.
Soil, rocky and gravelly.
Timber, palo verde and ironwood; undergrowth, greasewood.

From the true point for the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp.

S. 89° 58' W., bet. secs. 24 and 25.

Over rolling land, through scattering timber and undergrowth.


3.40 Wash, 20 lks. wide, course SW.; asc. 166 ft. over E. slope.

8.90 Spur, slopes S.; desc. 83 ft. over W. slope.

34.80 Wash, 25 lks. wide, course NW.

39.95 Point for the ¼ sec. cor. of secs. 24 and 25.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

58.50 Old road, bears N. 80° W. and S. 80° E.

79.90 The cor. of secs. 23, 24, 25 and 26.

Land, rolling.
Soil, rocky and gravelly.
Timber, palo verde, and ironwood; undergrowth, greasewood.

N. 0° 03' W., bet. secs. 23 and 24.

Over rolling land, through scattering timber and undergrowth.


5.60 Old road, bears N. 60° W. and S. 60° E.

15.68 Dim road, bears NW. and SE.

36.00 Wash, course NW.

40.00 Point for the ¼ sec. cor. of secs. 23 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of cor.

40.70 Wash, 20 lks. wide, course NW.; asc. 6 ft. over S. slope.

46.40 Detached spur, bears N. 70° W. and S. 70° E.; desc. 23 ft. over N. slope.

49.00 Wash, 50 lks. wide, course N, 60° W.

68.50 Wash, 25 lks. wide, course W.

Subdivision of T. 5 N., R. 18 W.

<p>Chains 80.00</p>	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 5 N</td> <td>R 18 W</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td colspan="2">1952</td> </tr> </table> </div> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>Land, rolling. Soil, gravelly. Timber, ironwood and palo verde; undergrowth, greasewood.</p>	T 5 N	R 18 W	S 14	S 13	S 23	S 24	1952	
T 5 N	R 18 W								
S 14	S 13								
S 23	S 24								
1952									
<p>4.90 10.95 14.60 25.20 32.90 39.96</p>	<p>From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp. S. 89° 57' W., bet. secs. 13 and 24.</p> <p>Over mountainous land, through scattering timber and undergrowth.</p> <p>Wash, 20 lks. wide, course S. 20° W.; asc. 73 ft. over E. slope.</p> <p>Spur, slopes S.; desc. 74 ft. over W. slope.</p> <p>Wash, 20 lks. wide, course S.; asc. 275 ft. over E. slope.</p> <p>Spur, slopes S. 10° W.</p> <p>Ravine, course S.</p> <p>Point for the ¼ sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>S 13</td> </tr> <tr> <td>¼</td> </tr> <tr> <td>S 24</td> </tr> <tr> <td>1952</td> </tr> </table> </div> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.</p> <p>Descend 293 ft. over W. slope.</p>	S 13	¼	S 24	1952				
S 13									
¼									
S 24									
1952									
<p>41.00 45.20 79.92</p>	<p>Leave mountainous, enter rolling land, bears NW. and SE.</p> <p>Wash, 20 lks. wide, course SW.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, E. ½, mountainous; W. ½, rolling. Soil, rocky and gravelly. Timber, palo verde and ironwood; undergrowth, greasewood.</p>								
<p>8.20 35.00 40.00</p>	<p>N. 0° 03' W., bet. secs. 13 and 14.</p> <p>Over rolling land, through scattering timber and undergrowth.</p> <p>Wash, 20 lks. wide, course W.</p> <p>Begin ascent of 52 ft. over S. slope.</p> <p>Point for the ¼ sec. cor. of secs. 13 and 14.</p>								

Subdivision of T. 5 N., R. 18 W.

Chains

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground and in a mound of stone to top with brass cap mkd.



Continue ascent over S. slope.

40.80 Spur, slopes W.; desc. 122 ft. over N. slope.

50.50 Wash, 40 lks, wide, course W.

55.80 Road, bears E. and W.


73.30 Wash, 20 lks. wide, course N. 60° W.; asc. 81 ft. over SE. slope.

77.20 Spur, slopes SW.; desc. 31 ft. over NW. slope.

79.70 Drain, course NW.

80.00 Point for the cor. of secs. 11, 12, 13 and 14.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



08
Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp.

S. 89° 56' W., bet. secs. 12 and 13.

Over rolling land, through scattering timber and undergrowth.

2.40 Wash, 20 lks. wide, course NW.


13.10 Road, bears NE. and SW.

27.50 Recross road, bears NW. and SE.

32.10 Road, bears NE. and SW.

39.95 Point for the 1/4 sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.

Enter mountainous land, bears N. and S. ; asc. 23 ft. over E. slope.

44.00 Low spur, slopes N.; desc. 23 ft. over W. slope.

Subdivision of T. 5 N., R. 18 W.

Chains	
45.00	Wash, 10 lks. wide, course SW.; asc. 152 ft. over NE. slope.
60.30	Spur, slopes SE.; desc. 141 ft. over SW. slope.
71.90	Drain, course SW.; asc. 20 ft. over E. slope.
76.90	Spur, slopes S. for 1 ch., then SW.; desc. 39 ft. over W. slope.
79.90	The cor. of secs. 11, 12, 13 and 14.
	Land, E. $\frac{1}{2}$, rolling; W. $\frac{1}{2}$, mountainous. Soil, rocky and gravelly. Timber, palo verde and ironwood; undergrowth, greasewood.
	N. $0^{\circ} 03'$ W., bet. secs. 11 and 12.
	Over mountainous land, through scattering timber and undergrowth. Ascend 121 ft. over S. slope.
7.90	Spur, slopes W.; desc. 143 ft. over N. slope.
14.00	Drain, course W.; asc. 50 ft. over S. slope.
18.80	Detached spur, bears E. and W.; desc. 63 ft. over N. slope.
23.70	Wash, 50 lks. wide, course W.
24.90	State Highway No. 95, bears N. 30° E. and S. 30° W.
25.30	Wash, 50 lks. wide, course S. 80° W.
31.20	Ascend 20 ft. over S. slope.
34.75	Spur, slopes W.; desc. 20 ft. over N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
	$\frac{1}{4}$ S 11 S 12 1952
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
55.80	Wash, 40 lks. wide, course SW.
68.80	Wash, 30 lks. wide, course SW.; asc. 77 ft. over SE. slope.
74.20	Spur, slopes SW. from N. 10° E., continue ascent along W. slope.
78.30	Recross spur, slopes S. 10° E., thence along a SE. slope.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
	T 5 N R 18 W S 2 S 1 S 11 S 12 1952
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Subdivision of T. 5 N., R. 18 W.

Chains

Land, mountainous.
Soil, rocky.
Timber, palo verde and ironwood; undergrowth, greasewood.

From the true point for the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.

S. 89° 58' W., bet. ~~secs.~~ secs. 1 and 12.

Over mountainous land, through scattering timber and undergrowth.

- 3.75 Drain, course SW.; asc. E. slope.
- 6.45 Point of a spur, slopes S.; desc. 14 ft. over W. slope.
- 9.95 Drain, course SW.; asc. 25 ft. over E. slope.
- 12.65 Spur, slopes S.; desc. 25 ft. over W. slope.
- 17.75 Wash, 20 lks. wide, course SW.; asc. 34 ft. over E. slope.
- 21.15 Point of a spur, slopes S.; desc. 84 ft. over SW. slope.
- 23.75 Wash, 20 lks. wide, course S.; asc. 14 ft. over E. slope.
- 28.25 Spur, slopes S.; desc. 39 ft. over W. slope.
- 31.55 Foot of descent, bears N. and S.
- 38.45 Wash, 40 lks. wide, course SW.
- 39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
- S 1

—

S 12

1952
- Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
- Ascend 23 ft. over E. slope.
- 44.60 Spur, slopes S.; asc. 8 ft. over E. slope.
- 47.95 Wash, 40 lks. wide, course SW.
- 50.65 Spur, slopes S.; desc. 13 ft. over W. slope.
- 53.95 Foot of descent, bears N. and S.
- 58.05 State Highway No. 95, bears N. 20° E. and S. 20° W.
- 59.95 Wash, 30 lks. wide, course SW.; asc. 23 ft. over E. slope.
- 61.15 Spur, slopes S.; desc. 23 ft. over W. slope.
- 64.95 Wash, 20 lks. wide, course S.; asc. 52 ft. over E. slope.
- 70.05 Spur, slopes S.; desc. 52 ft. over W. slope.
- 75.55 Wash, 30 lks. wide, course SW.; asc. 40 ft. over SE. slope.
- 79.94 The cor. of secs. 1, 2, 11 and 12.
Land, mountainous.
Soil, rocky.
Timber, palo verde; undergrowth, greasewood.

Chains	
	<p>N. 0° 03' W., bet. secs. 1 and 2.</p> <p>Over mountainous land, through scattering timber and undergrowth.</p> <p>Ascend 272 ft. along SE. slope of spur.</p>
17.70	Cross top of spur, slopes S. 20° W. from N. 20° E., continue ascent along W. slope.
30.90	Top of ascent; desc. 115 ft. along NW. slope.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 2 S 1 1952 </p>
	Continue descent along NW. slope.
44.00	Ravine, course W.; asc. 185 ft. over S. slope.
55.40	Ridge spur, slopes SW.; desc. 196 ft. over N. slope.
74.11	<p>Intersect the N. bdy. of the Tp. at the cor. of secs. 1, 2, 35 and 36.</p> <p>Land, mountainous. Soil, rocky. Timber, palo verde; undergrowth, greasewood.</p>
	<p>From the standard cor. of secs. 34 and 35 on the E. bdy. of the Tp.</p> <p>N. 0° 03' W., bet. secs. 34 and 35.</p> <p>Over mountainous land, through scattering timber and undergrowth.</p>
1.50	Wash, 40 lks. wide, course W.
12.00	Begin ascent of 105 ft. over S. slope.
19.80	Spur, slopes W.; desc. 149 ft. over N. slope.
38.00	Foot of descent, bears E. and W.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 34 S 35 1952 </p>
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
43.20	Wash, 50 lks. wide, course W.
66.00	Wash, 20 lks. wide, course W.
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p>

Subdivision of T. 5 N., R. 18 W.

Chains

T 5 N	R 18 W
S 27	S 26
S 34	S 35
1952	

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, S. $\frac{1}{2}$, mountainous; N. $\frac{1}{2}$, rolling.

Soil, rocky and sandy.

Timber, ironwood and palo verde; undergrowth, greasewood.

From the cor. of secs. 25, 26, 35 and 36.

S. $89^{\circ} 41'$ W., bet. secs. 26 and 35.

Over mountainous land, through scattering timber and undergrowth.

Ascend 26 ft. over E. slope.

2.50 Top of a small peak on a spur, slopes NW. for 10 chs.; desc. 270 ft. over cliffs, facing W.

10.50 Wash, 30 lks. wide, course NW.; asc. 141 ft. over cliffs, facing NE.

24.20 Spur, slopes NW.; desc. 351 ft. over cliffs facing SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.

Set an iron post, 28 ins. long; $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid ground and in a mound of stone to top with brass cap mkl.

S 26

S 35

1952

Over rolling land.

41.90 Wash, course S. 10° E.; enter valley, bears N. and S.

47.00 Begin ascent of 18 ft. over E. slope.

52.60 Detached spur, bears N. and S.; desc. 58 ft. over W. slope.

58.60 Foot of descent, bears N. and S.

74.60 Right bank of wash, bears NW. and SE.

78.00 Left bank of wash, bears NW. and SE.

80.16 The cor. of secs. 26, 27, 34 and 35.

Land, E. $\frac{1}{2}$, mountainous; W. $\frac{1}{2}$, rolling.

Soil, E. $\frac{1}{2}$, rocky; W. $\frac{1}{2}$, sandy.

Timber, ironwood and palo verde; undergrowth, greasewood.

N. $0^{\circ} 03'$ W., bet. secs. 26 and 27.

Over rolling land, through scattering timber and undergrowth.


2.00 Left bank of wash, bears NW. and SE.

4.90 Right bank of wash, bears NW. and SE.


20.00 A small knoll, bears E., 5 chs. dist.

Subdivision of T. 5 N., R. 18 W.

Chains
 28.80 Old road, bears N. 10° E. and S. 10° W.
 35.00 Recross road, bears N. 10° W. and S. 10° E.
 38.00 Wash, 20 lks. wide, course W.
 39.90 Recross road, bears N. 30° E. and S. 30° W.
 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.




79.00 Wash, 50 lks. wide, course W.
 80.00 Point for the cor. of secs. 22, 23, 26 and 27.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.
 Soil, gravelly.
 Timber, palo verde and ironwood; undergrowth, greasewood.

From the cor. of secs. 23, 24, 25 and 26.
 S. 89° 49' W., bet. secs. 23 and 26.
 Over rolling land, through scattering timber and undergrowth.
 12.10 Wash, 40 lks. wide, course NW.
 25.10 Wash, 50 lks. wide, course NW.
 40.04 True point for $\frac{1}{4}$ sec. cor. of secs. 23 and 26 falls in a wash, 30 lks. wide, course NW.; impracticable to monument the corner.
 42.54 Point for the witness $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd,



Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

48.40 Recross wash, 40 lks. wide, course SW.
 62.40 Recross wash, 40 lks. wide, course NW.
 65.10 Old road, bears N. 30° E. and S. 30° W.
 75.10 Wash, 50 lks. wide, course S. 60° W.

Subdivision of T. 5 N., R. 18 W.

Chains

79.60

Wash, 25 lks. wide, course SW.

80.08

The cor. of secs. 22, 23, 26 and 27.

Land, rolling.

Soil, gravelly.

Timber, ironwood and paloverde; undergrowth, greasewood.

N. 0° 03' W., bet. secs. 22 and 23.

Over rolling land, through scattering timber and undergrowth.

5.00

Wash, 50 lks. wide, course SW.


27.90

Old road, bears NW. and SE.

40.00

Point for the 1/4 sec. cor. of secs. 22 and 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

54.00

Wash, 20 lks. wide, course NW.

66.00

Wash, 20 lks. wide, course NW.


75.00

Wash, course W.

80.00

Point for the cor. of secs. 14, 15, 22 and 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly.

Timber, paloverde and ironwood; undergrowth, greasewood.

From the cor. of secs. 13, 14, 23 and 24.

S. 89° 51' W., bet. secs. 14 and 23.

Over rolling land, through scattering timber and undergrowth.


29.35

Old road, bears N. 20° E. and S. 20° W.

40.02

Point for the 1/4 sec. cor. of secs. 14 and 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N. of cor.


41.05

Wash, 50 lks. wide, course NW.

Subdivision of T. 5 N., R. 18 W.

Chains 80.04	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, gravelly. Timber, paloverde and ironwood; undergrowth, greasewood.</p>									
	<p>N. 0° 03' W., bet. secs. 14 and 15.</p> <p>Over rolling land, through scattering timber and undergrowth.</p>									
10.90	Wash, 50 lks. wide, course SW.									
30.00	Wash, 30 lks. wide, course SW.									
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.									
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>S 15</td> <td> </td> <td>S 14</td> </tr> <tr> <td colspan="3" style="text-align: center;">1952</td> </tr> </table> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p>	S 15		S 14	1952					
S 15		S 14								
1952										
55.40	Old road, bears E. and W.									
66.15	State Highway No. 95, bears NE. and SW.									
71.00	Wash, 40 lks. wide, course NW.									
80.00	Point for the cor. of secs. 10, 11, 14 and 15.									
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T. 5 N. R. 18 W.</td> </tr> <tr> <td>S 10</td> <td> S 11</td> </tr> <tr> <td>S 15</td> <td> S 14</td> </tr> <tr> <td colspan="2" style="text-align: center;">1952</td> </tr> </table> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land, rolling. Soil, gravelly. Timber, paloverde and ironwood; undergrowth, greasewood.</p>	T. 5 N. R. 18 W.		S 10	S 11	S 15	S 14	1952		
T. 5 N. R. 18 W.										
S 10	S 11									
S 15	S 14									
1952										
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89° 50' W., bet. secs. 11 and 14.</p> <p>Over mountainous land, through scattering timber and undergrowth.</p>									
7.00	Ravine, in bend, course SW. from SE.									
21.35	State Highway No. 95, bears NE. and SW.									
24.10	Wash, 30 lks. wide, course S. 60° W.; asc. 23 ft. over SE. slope.									
29.00	Spur, slopes SW.; desc. 19 ft. over NW. slope.									
35.00	Drain, course SW.									
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.									
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>$\frac{1}{4}$</td> <td> </td> <td>S 11</td> </tr> <tr> <td></td> <td> </td> <td>S 14</td> </tr> <tr> <td colspan="3" style="text-align: center;">1952</td> </tr> </table>	$\frac{1}{4}$		S 11			S 14	1952		
$\frac{1}{4}$		S 11								
		S 14								
1952										

Subdivision of T. 5 N., R. 18 W.

Chains	
40.30	Spur, slopes SW.; desc. 46 ft. over NW. slope.
47.10	Foot of descent, bears NE. and SW.; enter rolling land.
68.50	Left bank of wash, bears NE. and SW.; thence along bottom of wash.
71.50	Left bank of wash, bears NW. and SE.
80.00	The cor. of secs. 10, 11, 14 and 15. Land, W. $\frac{1}{2}$, rolling; E. $\frac{1}{2}$, mountainous. Soil, W. $\frac{1}{2}$, gravelly; E. $\frac{1}{2}$, rocky. Timber, palo verde and ironwood; undergrowth, greasewood.
	N. 0° 03' W., bet. secs. 10 and 11. Over rolling land, through scattering timber and undergrowth.
5.00	Wash, 30 lks. wide, course W. ; asc. 72 ft. over S. slope.
8.65	Spur, slopes W.; desc. 40 ft. over N. slope.
30.90	Wash, 50 lks. wide, course S. 60° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd, <div style="text-align: center;">  </div>
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
64.70	Wash, 30 lks. wide, course S. 40° W.
80.00	Point for the cor. of secs. 2, 3, 10 and 11 falls in a drain, course SW. Impracticable to monument the corner at this point. Land, rolling. Soil, gravelly and rocky. Timber, palo verde and ironwood; undergrowth, greasewood.
	From the cor. of secs. 1, 2, 11 and 12. S. 89° 50' W., bet. secs. 2 and 11. Over mountainous land, through scattering timber and undergrowth. Ascend 45 ft. over E. slope.
1.90	Spur, slopes S. 10° E.; desc. 106 ft. over W. slope.
11.20	Wash, 30 lks. wide, course S. 40° W.; asc. 44 ft. over E. slope.
15.00	Point of a spur, slopes S.; desc. 51 ft. over W. slope.
39.40	Wash, 20 lks. wide, course S.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

Subdivision of T. 5 N., R. 18 W.

Chains	
	<p style="text-align: center;"> S 2 $\frac{1}{4}$ ————— S 11 1952 </p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.</p>
44.85	Spur, slopes S.; desc. 15 ft. over W. slope.
48.50	Wash, 20 lks. wide, course S.; asc. 24 ft. over E. slope.
51.40	Spur, slopes S.; desc. W. slope.
53.30	Wash, 30 lks. wide, course SW.
80.00	<p>True point for the cor. of secs. 2, 3, 10 and 11, Land, mountainous. Soil, rocky. Timber, palo verde; undergrowth, greasewood.</p>
	<p>From the true point for the cor. of secs. 2, 3, 10 and 11. N. 0° 06' W., bet. secs. 2 and 3. Over mountainous land, through scattering timber and undergrowth.</p>
0.50	<p>Point for the witness cor. of secs. 2, 3, 10 and 11. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;"> T 5 N R 18 W S 3 S 2 ———— S 10 S 11 ↓ WC 1952 </p> <p>Raise a mound of stone 2½ ft. base, 2½ ft. high, W. of cor.</p>
22.30	Wash, 50 lks. wide, course SW.
34.20	Point of a spur, slopes W.
39.00	Drain, course W.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 3 S 2 1952 </p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p>
42.20	Sand ridge, bears E. and W.
52.20	Wash, 50 lks. wide, course W.; asc. 173 ft. over SE. slope.
65.90	Top of spur, slopes SW.; desc. 145 ft. over NW. slope.
74.24	<p>Intersect the N. bdy. of the Tp. at the cor. of secs. 2, 3, 34 and 35. Land, S. $\frac{1}{4}$, rolling; N. $\frac{1}{4}$, mountainous. Soil, S. $\frac{1}{4}$, gravelly; N. $\frac{1}{4}$, rocky. Timber, palo verde and ironwood; undergrowth, greasewood.</p>

Subdivision of T. 5 N., R. 18 W.

Chains

From the standard cor. of secs. 33 and 34 on the S. bdy. of the Tp.
N. 0° 04' W., bet. secs. 33 and 34.

Over rolling land, through scattering timber and undergrowth.


8.60 Wash, 25 lks. wide, course NW.

13.70 Wash, 50 lks. wide, course N. 60° W.

36.80 Wash, 40 lks. wide, course NW.

40.00 Point for the 1/4 sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.




Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

44.00 Wash, 30 lks. wide, course SW.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.
Soil, gravelly.
Timber, palo verde and ironwood; undergrowth, greasewood.

From the cor. of secs. 26, 27, 34 and 35.


N. 89° 54' W., bet. secs. 27 and 34.

Over rolling land, through scattering timber and undergrowth.

10.00 Old road, bears N. 30° E. and S. 30° W.

39.99 Point for the 1/4 sec. cor. of secs. 27 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N. of cor.

79.98 The cor. of secs. 27, 28, 33 and 34.

Land, rolling.
Soil, gravelly.
Timber, ironwood and palo verde; undergrowth, greasewood.

Subdivision of T. 5 N., R. 18 W.

Chains

N. 0° 04' W., bet. secs. 27 and 28.


Over rolling land, through scattering timber and undergrowth.

5.70 Wash, 40 lks. wide, course W.

31.50 Wash, 50 lks. wide, course SW.

40.00 Point for the 1/4 sec. cor. of secs. 27 and 28.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.




Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

65.00 Wash, 20 lks. wide, course SW.

79.00 Wash, course SW.

80.00 Point for the cor. of secs. 21, 22, 27 and 28.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the cor. of secs. 22, 23, 26 and 27.


N. 89° 54' W., bet. secs. 22 and 27.

Over rolling land, through scattering timber and undergrowth.

0.85 Wash, 50 lks. wide, course SW.

39.98 Point for the 1/4 sec. cor. of secs. 22 and 27.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N. of cor.

79.25 Wash, 20 lks. wide, course SW.

79.96 The cor. of secs. 21, 22, 27 and 28.

Land, rolling.

Soil, gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

Subdivision of T. 5 N., R. 18 W.

Chains


N. 0° 04' W., bet. secs. 21 and 22.

Over rolling land, through scattering timber and undergrowth.

22.40 Wash, 40 lks. wide, course S. 50° W.

40.00 Point for the 1/4 sec. cor. of secs. 21 and 22.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.


51.00 Wash, 20 lks. wide, course S. 50° W.

54.40 Old road, bears N. 40° W. and S. 40° E.

62.00 Wash, 60 lks. wide, course W.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the cor. of secs. 14, 15, 22 and 23.

N. 89° 54' W., bet. secs. 15 and 22.


Over rolling land, through scattering timber and undergrowth.

9.45 Wash, 50 lks. wide, course SW.

37.25 Wash, 20 lks. wide, course S. 10° W.

39.98 Point for the 1/4 sec. cor. of secs. 15 and 22.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.



79.96 The cor. of secs. 15, 16, 21 and 22.

Land, rolling.

Soil, sandy and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

Subdivision of T. 5 N., R. 18 W.

Chains

N. $0^{\circ} 04'$ W., bet. secs. 15 and 16.

Over rolling land, through scattering timber and undergrowth.

19.80 Wash, 40 lks. wide, course SW.

32.70 State Highway No. 95, bears NE. and SW.

34.00 Old road, bears E. and W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 16 \quad | \quad \text{S } 15 \\ \hline 1952 \end{array}$$
Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.57.00 Wash, 30 lks. wide, course S. 50° W.

80.00 Point for the cor. of secs. 9, 10, 15 and 16.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} \text{T } 5 \text{ N } \text{ R } 18 \text{ W} \\ \text{S } 9 \quad | \quad \text{S } 10 \\ \hline \text{S } 16 \quad | \quad \text{S } 15 \\ \hline 1952 \end{array}$$
Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, gravelly and sandy.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the cor. of secs. 10, 11, 14 and 15.

N. $89^{\circ} 54'$ W., bet. secs. 10 and 15.

Over rolling land, through scattering timber and undergrowth.

17.75 Right bank of wash, bears SE. and N. 70° W.24.95 Left bank of wash, bears NW. and S. 70° E.39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} \text{S } 10 \\ \hline \frac{1}{4} \\ \hline \text{S } 15 \\ \hline 1952 \end{array}$$
Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

79.96 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.

Soil, sandy and gravelly.

Timber, ironwood and palo verde; undergrowth, greasewood.

Subdivision of T. 5 N., R. 18 W.

Chains

N. 0° 04' W., bet. secs. 9 and 10.

Over rolling land, through scattering timber and undergrowth.


0.40 Left bank of wash, bears S. 60° W. and N. 60° E.

4.00 Right bank of wash, bears S. 60° W. and N. 60° E.

28.00 Wash, 50 lks, wide, course W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.




Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

50.10 Wash, 30 lks. wide, course W.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the true point for the cor. of secs. 2, 3, 10 and 11.


N. 89° 53' W., bet. secs. 3 and 10.

Over rolling land, through scattering timber and undergrowth.

21.95 Wash, 50 lks. wide, course S. 30° W.

39.98 The point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.

65.95 Wash, 30 lks. wide, course S. 30° W.

79.96 The cor. of secs. ^{EE}3, ^{SE}4, 9 and 10.

Land, rolling.

Soil, sandy and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

Chains


N. 0° 08' W., bet. secs. 3 and 4.

Over rolling land, through scattering timber and undergrowth.

5.00 Wash, 30 lks. wide, course W.

40.00 Point for the 1/4 sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

60.00 Wash, 50 lks. wide, course W.

74.00 Intersect the N. bdy. of the Tp. at the cor. of secs. 3, 4, 33 and 34.

Land, rolling.

Soil, sandy and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the standard cor. of secs. 32 and 33 on the S. bdy. of the Tp.

N. 0° 04' W., bet. secs. 32 and 33.


Over rolling land, through scattering timber and undergrowth.

7.60 Wash, 50 lks. wide, course N. 60° W.

25.50 Wash, 40 lks. wide, course W.

40.00 Point for the 1/4 sec. cor. of secs. 32 and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.


52.20 Wash, 30 lks. wide, course N. 20° W.

60.00 Wash, 60 lks. wide, course W.

73.30 Wash, 50 lks. wide, course S. 60° W.

80.00 Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone 3 ft. base, 2 1/2 ft. high, W. of cor.

Subdivision of T. 5 N., R. 18 W.

Chains

Land, rolling.
Soil, gravelly.
Timber, ironwood and palo verde; undergrowth, greasewood.


From the cor. of secs. 27, 28, 33 and 34.

WEST, bet. secs. 28 and 33.

Over rolling land, through scattering timber and undergrowth.

39.97 Point for the 1/4 sec. cor. of secs. 28 and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.

52.95 Wash, 50 lks. wide, course SW.

60.65 Wash, 30 lks. wide, course S. 20° W.

79.94 The cor. of secs. 28, 29, 32 and 33.

Land, rolling.
Soil, gravelly.
Timber, palo verde and ironwood; undergrowth, greasewood.

N. 0° 04' W., bet. secs. 28 and 29.

Over rolling land, through scattering timber and undergrowth.

21.00 Wash, 30 lks. wide, course S. 30° W.

40.00 Point for the 1/4 sec. cor. of secs. 28 and 29.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.




Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

49.60 Wash, 30 lks. wide, course S. 50° W.

60.00 Wash, 30 lks. wide, course SW.

80.00 Point for the cor. of secs. 20, 21, 28 and 29.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.




Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

Chains	
	<p>Land, rolling. Soil, sandy and gravelly. Timber, palo verde and ironwood; undergrowth, greasewood.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28. S. 89° 58' W., bet. secs. 21 and 28. Over rolling land, through scattering timber and undergrowth.</p> <p>39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.</p> <div style="text-align: center;"> <p>S 21</p> <p>-----</p> <p>$\frac{1}{4}$</p> <p>S 28</p> <p>1952</p> </div>
	<p>79.96 The cor. of secs. 20, 21, 28 and 29. Land, rolling. Soil, sandy and gravelly. Timber, palo verde and ironwood; undergrowth, greasewood.</p>
	<p>N. 0° 04' W., bet. secs. 20 and 21. Over rolling land, through scattering timber and undergrowth.</p> <p>12.00 Wash, 30 lks. wide, course S. 60° W.</p> <p>27.40 Wash, 50 lks. wide, course S. 60° W.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div style="text-align: center;"> <p>$\frac{1}{4}$</p> <p>S 20 S 21</p> <p>1952</p> </div> <p>Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p> <p>44.60 Wash, 50 lks. wide, course SW.</p> <p>53.60 State Highway No. 95, bears N. 20° E. and S. 20° W.</p> <p>79.10 Left bank of wash, bears E. and W.</p> <p>80.00 Point for the cor. of secs. 16, 17, 20 and 21 falls in wash where it is impracticable to monument the corner. Land, rolling. Soil, sandy and gravelly. Timber, palo verde and ironwood; undergrowth, greasewood.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22. S. 89° 58' W., bet. secs. 16 and 21. Over rolling land, through scattering timber and undergrowth.</p>

Chains
39.97

Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

55.45 State Highway No. 95, bears N. 30° E. and S. 30° W.

58.45 Wash, 40 lks. wide, course S. 40° W.

64.95 Right bank of wash, bears N. 80° W. and S. 80° E. , thence across bed of wash.

79.94 The true point for the cor. of secs. 16, 17, 20 and 21.

Land, rolling.

Soil, gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the true point for the cor. of secs. 16, 17, 20 and 21.

N. 0° 04' W.; bet. secs. 16 and 17.


Over rolling land, through scattering timber and undergrowth.

Across bed of wash.

0.30 Right bank of wash, bears E. and W.

1.00 Point for the witness cor. of secs. 16, 17, 20 and 21.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.




Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft high, W. of cor.

27.80 Old road, bears NE. and SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

45.00 Wash, 50 lks. wide, course N. 60° W.


73.00 Wash, 30 lks. wide, course N. 60° W.

80.00 Point for the cor. of secs. 8, 9, 16 and 17.

Subdivision of T. 5 N., R. 18 W.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling.

Soil, gravelly.

Timber, ironwood and palo verde; undergrowth, greasewood.

From the cor. of secs. 9, 10, 15 and 16.

N. 89° 57' W. bet. secs. 9 and 16.


Over rolling land, through scattering timber and undergrowth.

1.00 Left bank of wash, bears N. 80° E. and S. 80° W.

13.00 Right bank of wash, bears N. 80° E. and S. 80° W.

40.00 Point for the ¼ sec. cor. of secs. 9 and 16.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

69.50 Wash, 30 lks. wide, course S. 60° W.

80.00 The cor. of secs. 8, 9, 16 and 17.

Land, rolling.

Soil, sandy.

Timber, palo verde and ironwood; undergrowth, greasewood.

N. 0° 04' W., bet. secs. 8 and 9.

Over rolling land, through scattering timber and undergrowth.

26.50 Wash, 20 lks. wide, course S. 70° W.

40.00 Point for the ¼ sec. cor. of secs. 8 and 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, W. of cor.

59.10 Wash, 50 lks. wide, course S. 70° W.

80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

Chains

T 5	N	R 18	W
S 5		S 4	
S 8		S 9	
1952			

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy.

Timber, ironwood and palo verde; undergrowth, greasewood.

From the cor. of secs. 3, 4, 9 and 10.

N. $89^{\circ} 59'$ W., bet. secs. 4 and 9.

Over rolling land, through scattering timber and undergrowth.

15.90 Wash, 30 lks. wide, course SW.

40.04 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

	S 4	
$\frac{1}{4}$	—	
	S 9	
	1952	

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

80.08 The cor. of secs. 4, 5, 8 and 9.

Land, rolling.

Soil, sandy.

Timber, palo verde and ironwood; undergrowth, greasewood.

N. $0^{\circ} 05'$ E., bet. secs. 4 and 5.

Over rolling land, through scattering timber and undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

	$\frac{1}{4}$	
S 5		S 4
	1952	

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

74.00 Intersect the N. bdy. of the Tp. at the cor. of secs. 4, 5, 32 and 33.

Land, rolling.

Soil, sandy loam.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the standard cor. of secs. 31 and 32 on the S. bdy. of the Tp.

N. $0^{\circ} 05'$ W., bet. secs. 31 and 32.

Subdivision of T. 5 N., R. 18 W.

Chains

Over rolling land, through scattering timber and undergrowth.

7.50

Wash, drains NW.


12.50

Wash, 50 lks. wide, course W.

40.00

Point for the 1/4 sec. cor. of secs. 31 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

43.60

Wash, 50 lks. wide, course S. 50° W.


64.50

Wash, 30 lks. wide, course W.

80.00

Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the cor. of secs. 28, 29, 32 and 33.


S. 89° 56' W., bet. secs. 29 and 32.

Over rolling land, through scattering timber and undergrowth.

39.00

Point for the witness 1/4 sec. cor. of secs. 29 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.

40.00

True point for the 1/4 sec. cor. of secs. 29 and 32 which falls in a wash; 30 lks. wide, course NW.

53.60

Wash, 60 lks. wide, course N. 70° W.

80.00

The cor. of secs. 29, 30, 31 and 32.

Land, rolling.

Soil, gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

Chains


WEST, bet. secs. 30 and 31.

Over rolling land, through scattering timber and undergrowth.

16.65 State Highway No. 95, bears N. 20° E. and S. 20° W.

40.00 Point for the 1/4 sec. cor. of secs. 30 and 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.

63.00 Wash, 30 lks. wide, course NW.

70.00 Recross same wash, 30 lks. wide, course S. 60° W.

79.94 Intersect the W. bdy. of the Tp. at the cor. of secs. 25, 30, 31 and 36.

Land, rolling.

Soil, sandy and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the cor. of secs. 29, 30, 31 and 32.


N. 0° 05' W., bet. secs. 29 and 30.

Over rolling land, through scattering timber and undergrowth.

16.60 Wash, 50 lks. wide, course N. 70° W.

40.00 Point for the 1/4 sec. cor. of secs. 29 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.




Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

48.80 Wash, 30 lks. wide, course SW.

51.25 State Highway, No. 95, bears NE. and SW.

80.00 Point for the cor. of secs. 19, 20, 29 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.



Raise a mound of stone 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, rolling.

Soil, sandy.

Timber, palo verde and ironwood; undergrowth, greasewood.


Subdivision of T. 5 N., R. 18 W.

Chains	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89° 56' W., bet. secs. 20 and 29.</p> <p>Over rolling land, through scattering timber and undergrowth.</p> <p>40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{\text{S } 20}{\text{S } 29}$ 1952 </p> <p>Raise a mound of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, N. of cor.</p> <p>64.20 State Highway No. 95, bears N. 20° E. and S. 20° W.</p> <p>80.04 The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling. Soil, sandy. Timber, palo verde and ironwood; undergrowth, greasewood.</p>
	<p>S. 89° 59' W., bet. secs. 19 and 30.</p> <p>Over rolling land, through scattering timber and undergrowth.</p> <p>30.00 Wash, 50 lks. wide, course S. 60° W.</p> <p>38.60 Recross same wash, 50 lks. wide, course N. 60° W.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{\text{S } 19}{\text{S } 30}$ 1952 </p> <p>Raise a mound of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, N. of cor.</p> <p>43.80 Recross wash, 50 lks. wide, course S. 70° W.</p> <p>52.20 Recross wash, 50 lks. wide, course N. 60° W.</p> <p>65.00 Recross wash, 50 lks. wide, course S. 60° W.</p> <p>79.78 Intersect the W. bdy. of the Tp. at the cor. of secs. 19, 24, 25 and 30.</p> <p>Land, rolling. Soil, sandy. Timber, palo verde and ironwood; undergrowth, greasewood.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 05' W., bet. secs. 19 and 20.</p> <p>Over rolling land, through scattering timber and undergrowth.</p> <p>8.00 Wash, 50 lks. wide, course S. 50° W.</p>

Subdivision of T. 5 N., R. 18 W.

Chains

38.50 Wash, 20 lks. wide, course S. 60° W.


40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

58.40 Enter wash land, bears E, and W.; drains W.

65.50 Leave wash land, bears E. and W.

79.70 Road, bears S. 70° W. and N. 70° E.

80.00 Point for the cor. of secs. 17, 18, 19 and 20.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone to top with brass cap mkd.

Land, rolling.

Soil, sandy loam.

Timber, ironwood and palo verde; undergrowth, greasewood.


From the true point for the cor. of secs. 16, 17, 20 and 21.

S. 89° 57' W., bet. secs. 17 and 20.

Over rolling land, through scattering timber and undergrowth.

Across bed of wash,

20.00 Right bank of wash, bears S. 60° W. and N. 70° E.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

44.50 Recross wash, 50 lks. wide, course N. 50° W.

51.10 Recross wash, 50 lks. wide, course S. 30° W.

79.00 Old road, bears N. 40° E. and S. 40° W.

80.02 The cor. of secs. 17, 18, 19 and 20.

Land, rolling.

Soil, sandy and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

Subdivision of T. 5 N., R. 18 W.

Chains

WEST, bet. secs. 18 and 19.

Over rolling land, through scattering timber and undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

S 18

 $\frac{1}{4}$

S 19

1952

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

79.64 Intersect the W. bdy. of the Tp. at the cor. of secs. 13, 18, 19 and 24.

Land, rolling.

Soil, sandy and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the cor. of secs. 17, 18, 19 and 20.

N. $0^{\circ} 05'$ W., bet. secs. 17 and 18.

Over rolling land, through scattering timber and undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

S 18 | S 17

1952

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.65.80 Wash, 50 lks. wide, course N. 60° W.

80.00 Point for the cor. of secs. 7, 8, 17 and 18.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

T 5 N R 18 W

S 7 | S 8

S 18 | S 17

1952

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, sandy.

Timber, palo verde and ironwood; undergrowth, greasewood.

From the cor. of secs. 8, 9, 16 and 17.

WEST, bet. secs. 8 and 17.

Over rolling land, through scattering timber and undergrowth.

Subdivision of T. 5 N., R. 18 W.

Chains
39.98Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} \text{S 8} \\ \frac{1}{4} \text{ ---} \\ \text{S 17} \\ 1952 \end{array}$$
Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

79.96 The cor. of secs. 7, 8, 17 and 18.

Land, rolling.

Soil, sandy and gravelly.

Timber, palo verde and ironwood; undergrowth, greasewood.

N. $89^{\circ} 58'$ W., bet. secs. 7 and 18.

Over rolling land, through scattering timber and undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} \text{S 7} \\ \frac{1}{4} \text{ ---} \\ \text{S 18} \\ 1952 \end{array}$$
Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.62.00 Left bank of wash, bears NE. and S. 80° W.; thence across bed of wash.68.50 Left bank of wash, bears NW. and S. 80° E.

79.49 Intersect W. bdy. of Tp. at the cor. of secs. 7, 12, 13 and 18.

Land, rolling.

Soil, sandy and gravelly.

Timber, ironwood and palo verde; undergrowth, greasewood.

From the cor. of secs. 7, 8, 17 and 18.

N. $0^{\circ} 05'$ W., bet. secs. 7 and 8.

Over rolling land, through scattering timber and undergrowth.

20.50 Wash, 40 lks. wide, course S. 70° W.40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S 7} \text{ ---} \text{S 8} \\ 1952 \end{array}$$
Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Subdivision of T. 5 N., R. 18 W.

Chains
41.20 Wash, 20 lks. wide, course S. 70° W.
80.00 Point for the cor. of secs. 5, 6, 7 and 8.
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T 5 N.	R 18 W
S 6	S 5
S 7	S 8
1952	

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
Land, rolling.
Soil, sandy loam.
Timber, ironwood and palo verde; undergrowth, greasewood.

From the cor. of secs. 4, 5, 8 and 9.
S. 89° 59' W., bet. secs. 5 and 8.
Over rolling land, through scattering timber and undergrowth.
39.98 Point for the ¼ sec. cor. of secs. 5 and 8.
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

S 5	
¼	
S 8	
1952	

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

79.96 The cor. of secs. 5, 6, 7 and 8.
Land, rolling.
Soil, sandy loam.
Timber, palo verde and ironwood; undergrowth, greasewood.

N. 89° 57' W., bet. secs. 6 and 7.
Over rolling land, through scattering timber and undergrowth.
40.00 Point for the ¼ sec. cor. of secs. 6 and 7.
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

S 6	
¼	
S 7	
1952	

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

79.38 Intersect the W. bdy. of the Tp. at the cor. of secs. 1, 6, 7 and 12.
Land, rolling.
Soil, sandy loam.
Timber, ironwood and palo verde; undergrowth, greasewood.

Chains

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 02' E., bet. secs. 5 and 6.

Over rolling land, through scattering timber and undergrowth.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

$\frac{1}{4}$
 S 6 | S 5
 1952

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

74.01

Intersect the N. bdy. of the Tp. at the cor. of secs. 5, 6, 31 and 32.

Land, rolling.

Soil, sandy loam.

Timber, palo verde and ironwood; undergrowth, greasewood.

Test of Solar Orientation

At camp in sec. 31, T. 5 N., R. 18 W., every 30m from 8 a.m. to 10:30 a.m. and from 1:30 to 4 p.m., we make proper settings on the arcs of the solar attachments and ascertain that the resulting orientations of the instruments, when compared with the meridian established by Polaris observation, have a maximum error of less than 1' 30".

January 4, 1953.

General Description of T. 5 N., R. 18 W.

The east two tiers of sections of T. 5 N., R. 18 W. are for the most part mountainous, the remainder of the township is of rolling land. The elevation of the township ranges from approximately 900 to 2000 ft. above sea level. The highest point in the township being Haystack Mountain a portion of which is located in section 36. The rock formation of the mountainous area is volcanic and the soil in most of the rolling area is rocky and gravelly with sandy loam in the extreme northwest portion of the township.

The general direction of the drainage in the township is west and is furnished by washes which are dry except during rainy periods.

There are no settlers within the township and no mining activity at this time. A sparse growth of native grass furnishes grazing for a few head of cattle. There is a dense growth of ironwood and palo verde timber along the washes and a heavy undergrowth of greasewood throughout the township.

State Highway No. 95, a graded and gravel surfaced road, enters the township on the south boundary of section 31 and traverses through sections 31, 30, 29, 20, 21, 16, 15, 14, 11, 12 and 1, leaving the township on the north boundary of section 1, near the northeast township corner.

49

BOOK 4439

4-680
(Feb., 1950)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Fred R. Chappell	Cartographic Survey Aid
Robert D. Stevens	" " "
William H. Derendor	Surveying and Cartographic Aid
Paul O. Heath	" " " "
Abenicio Crespín	" " " "
Fernando D. Chavez	" " " "
Deciderio Baca	" " " "

50

BOOK 4439

CERTIFICATE OF CADASTRAL ENGINEER

I, Ty White, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of October, 1952, I have ~~re-surveyed~~ resurveyed the south and east boundaries and surveyed the north boundary and subdivisio[nal] lines of Township 5 North, Range 18 West

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Albuquerque, New Mexico,
April 22, 1953.

Ty White
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., APR 5 1955, 19

The foregoing field notes of the ~~re-survey~~ resurvey of the south and east boundaries and the survey of the north boundary and subdivisio[nal] lines of Township 5 North, Range 18 West

executed by Ty White

having been critically examined and found correct, are hereby approved.

Earl G. Harrington
Chief, Division of Cadastral Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Chief, Division of Cadastral Engineering