

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Dependent Resurvey

of a

Portion of the South Boundary and the

Survey of

A Portion of the Subdivisional Lines

Completing the Survey of

Township 6 North, Range 20 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Ty White, Cadastral Engineer

Under special instructions dated October 9, 1952, which provided
for the surveys included under Group No. 285, approved October 21, 1952
and assignment instructions dated November 7, 1952

Survey commenced February 10, 1953

Survey completed February 17, 1953

4442

4442

4442

1A

BOOK 4442

INDEX DIAGRAM

Township 6 North, Range 20 West

6	5	4	3	2	8	1
				15	7	
7	8	9	10	11	7	12
				14	6	
18	17	16	15	14	6	13
				13	5	
19	20	21	22	12	23	6
				12	11	4
30	29	28	27	11	26	4
			10	9	3	
31	32	33	34	9	35	3
			2	1	1	

T. 6 N., R. 20 W.

Chains

The following notes describe the resurvey of a portion of the south boundary and the survey of a portion of the subdivisional lines of Township 6 North, Range 20 West, Gila and Salt River Meridian.

The description of the instruments and methods is contained in the survey notes of T. 7 N., R. 18 W., surveyed concurrently with this township under the same group.

The geographic position of the southeast corner of the township, as determined from ties to U. S. C. & G. S. triangulation station POSA, is: Latitude, $33^{\circ} 48' 37''$ N.; and Longitude, $114^{\circ} 17' 02.5''$ W.

Dependent Resurvey of Portion of S. Bdy.

This resurvey of a portion of the south boundary is made for the purpose of establishing corners for T. 6 N., R. 20 W., and altering the marks on the existing monuments to refer to T. 5 N., R. 20 W., only. Reference is made to the 1950 survey of this line for topography and descriptions of land and vegetation.

From the cor. of Ts. 6 N., Rs. 19 and 20 W., which is an iron post, set, mkd. and witnessed as described in the survey record of T. 6 N., R. 19 W.

West, along the south bdy. of sec. 36.

- 6.27 The $\frac{1}{4}$ sec. cor. originally established for secs. 1 and 36, marked by an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record. This cor. now functions for sec. 1 only. I alter the marks thereon to read:

$$\frac{1}{4} \text{ S } 1$$

1950

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 36.

Set an iron post, $2\frac{1}{2}$ ins. diam., 30 ins. long, 24 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \text{ S } 36$$

1951

Bury broken glass alongside the iron post.

- 46.27 The cor. originally established for secs. 1, 2, 35 and 36, marked by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions for secs. 1 and 2, T. 5 N., R. 20 W., only. I alter the monument marks to read:

$$\begin{array}{c} \text{T6N R20W} \\ \hline \text{S2 | S1} \\ \hline \text{T5N R20W} \end{array}$$

1950

- 80.00 Point for the cor. of secs. 35 and 36.

Set an iron post, $2\frac{1}{2}$ ins. diam., 30 ins. long, 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T6N R20W} \\ \hline \text{S35 | S36} \\ \hline \text{T5NR20WS2} \end{array}$$

1953

Bury broken glass alongside the iron post.

West, along S. bdy. of sec. 35.

Resurvey of Portion of S. Bdy., T. 6 N., R. 20 W.

Chains

6.27

The $\frac{1}{4}$ sec. cor. originally established for secs. 2 and 35, an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record. This $\frac{1}{4}$ sec. cor. now functions for sec. 2 only. I alter the monument marks to read:

 $\frac{1}{4}$ S 2

1950

40.00

Point for the $\frac{1}{4}$ sec. cor. of sec. 35.

Set an iron post, $2\frac{1}{2}$ ins. diam., 30 ins. long, 24 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$ S 35

1953

Bury broken glass alongside the iron post.

46.27

The cor. originally established for secs. 2, 3, 34 and 35, marked by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions for secs. 2 and 3, T. 5 N., R. 20 W., only. I alter the monument marks to read:

T6N R20W S35

S3 S2

T5N R20W

1950

80.00

Point for the cor. of secs. 34 and 35.

Set an iron post, $2\frac{1}{2}$ ins. diam., 30 ins. long, 24 ins. in the ground, with brass cap mkd.

T6N R20W

S34 S35

T5N R20W S3

1953

West, along the S. bdy. of sec. 34.

6.27

The $\frac{1}{4}$ sec. cor. originally established for secs. 3 and 34, marked by and iron post, 1 in. diam., set, mkd. and witnessed as described in the official record. This $\frac{1}{4}$ sec. cor. now functions for sec. 3 only. I alter the monument marks to read:

 $\frac{1}{4}$ S 3

1950

40.00

Point for the $\frac{1}{4}$ sec. cor. of sec. 34.

Set an iron post, $2\frac{1}{2}$ ins. diam., 30 ins. long, 24 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$ S 34

1953

Bury broken glass alongside the iron post.

46.27

The cor. originally established for secs. 3, 4, 33 and 34, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions for secs. 3 and 4, T. 5 N., R. 20 W., only. I alter the monument marks to read:

Resurvey of Portion of S. Bdy., T. 6 N., R. 20 W.

Chains

T6N R20W S34
 S4 | S3
 T5N | R20W
 1953

78.47

The closing cor. of Ts. 5 and 6 N., R. 20 W., on the Colorado River Indian Reservation Bdy., marked by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the closing cor. of secs. 4, 33, and 34. I alter the monument marks to read:

CC
 T6N
 S33 | S34
 T5N | S4 CC
 R20W | PL
 S4
 1913 | 1950

Subdivision of T. 6 N., R. 20 W.

From the cor. of secs. 35 and 36 on the S. bdy. of the Tp., which is monumented with an iron post, marked and witnessed as described in the field notes of T. 6 N., R. 19 W.

N. 0° 01' W., bet. secs. 35 and 36.

Over rolling land, through scattering undergrowth.

40.00

Point for the 1/4 cor. of secs. 35 and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4
 S 35 | S 36
 1953

Deposit a broken glass bottle alongside iron post.

80.00

Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N | R 20 W
 S 26 | S 25
 S 35 | S 36
 1953

Deposit a broken glass bottle alongside iron post.

Land, rolling.

Soil, gravelly.

Timber, palo verde.

Undergrowth, scattering greasewood.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., which is monumented with an iron post, marked and witnessed as described in the official record.

N. 89° 59' W., bet. secs. 25 and 36.

Over rolling land, through scattering undergrowth.

24.00

Drain, course S.

40.00

Point for the 1/4 cor. of secs. 25 and 36.

Subdivision of T. 6 N., R. 20 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 25
 ———
 S 36
 1953

Deposit a broken glass bottle alongside iron post.

80.00 The cor. of secs. 25, 26, 35 and 36.

Land, rolling.
 Soil, gravelly.
 Timber, palo verde.
 Undergrowth, scattering greasewood.

N. 0° $01'$ W., bet. secs. 25 and 26.

Over rolling land, through scattering undergrowth.

40.00 Point for the $\frac{1}{4}$ cor. of secs. 25 and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 26 | S 25
 1953

Deposit a broken glass bottle alongside iron post.

80.00 Point for the cor. of secs. 23, 24, 25 and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T. 6 N. R. 20 W.
 S 23 | S 24
 S 26 | S 25

1953

Deposit a broken glass bottle alongside iron post.

Land, rolling.
 Soil, gravelly.
 Timber, palo verde.
 Undergrowth, scattering greasewood.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., which is monumented with an iron post, marked and witnessed as described in the official record.

West, bet. secs. 24 and 25.

Over rolling land, through scattering undergrowth.

24.50 Drain, course S.

39.00 Drain, course S.

BOOK 4442

Subdivision of T. 6 N., R. 20 W.

Chains

40.00 Point for the $\frac{1}{4}$ cor. of secs. 24 and 25.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 24
 $\frac{1}{4}$ ———
S 25
1953

Deposit a broken glass bottle alongside iron post.

76.00 Drain, course S. 60° E.

80.00 The cor. of secs. 23, 24, 25 and 26.

Land, rolling.
Soil, sandy.
Timber, palo verde.
Undergrowth, scattering greasewood.

N. 0° 01' W., bet. secs. 23 and 24.

Over rolling land, through scattering undergrowth.

35.00 Drain, course S. 60° E.

40.00 Point for the $\frac{1}{4}$ cor. of secs. 23 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 23 | S 24
1953

Deposit a broken glass bottle alongside iron post.

80.00 Point for the cor. of secs. 13, 14, 23 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N R 20 W
S 14 | S 13
———
S 23 | S 24
1953

Deposit a broken glass bottle alongside iron post.

Land, rolling.
Soil, gravelly.
Timber, palo verde and ironwood.
Undergrowth, scattering greasewood.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., which is monumented with an iron post, marked and witnessed as described in the official record.

S. 89° 59' W., bet. secs. 13 and 24.

Chains

Over gently rolling land, through scattering undergrowth.

40.02 Point for the $\frac{1}{4}$ cor. of secs. 13 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} S 13 \\ \frac{1}{4} \text{ ---} \\ S 24 \\ 1953 \end{array}$$

80.04 Deposit a broken glass bottle alongside iron post.

The cor. of secs. 13, 14, 23 and 24.

Land, gently rolling.
Soil, sandy.
Timber, none.
Undergrowth, scattering greasewood.

N. $0^{\circ} 01'$ W., bet. secs. 13 and 14.

Over gently rolling land, through scattering undergrowth.

40.00 Point for the $\frac{1}{4}$ cor. of secs. 13 and 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S 14 \quad | \quad S 13 \\ 1953 \end{array}$$

80.00 Deposit a broken glass bottle alongside iron post.

Point for the cor. of secs. 11, 12, 13 and 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T 6 N \quad R 20 W \\ S 11 \quad | \quad S 12 \\ \text{---} \quad | \quad \text{---} \\ S 14 \quad | \quad S 13 \\ 1953 \end{array}$$

Deposit a broken glass hottle alongside iron post.

Land, gently rolling.
Soil, sandy.
Timber, none.
Undergrowth, scattering greasewood.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., which is monumented with an iron post, marked and witnessed as described in the official record.

WEST, bet. secs. 12 and 13.

Chains

Over gently rolling land, through scattering undergrowth.

40.04

Point for the $\frac{1}{4}$ cor. of secs. 12 and 13.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 12

 $\frac{1}{4}$ ———

S 13

1953

Deposit a broken glass bottle alongside iron post.

80.08

The cor. of secs. 11, 12, 13 and 14.

Land, gently rolling.

Soil, sandy.

Timber, none.

Undergrowth, scattering greasewood.

N. 0° 01' W., bet. secs. 11 and 12.

Over rolling land, through scattering undergrowth.

40.00

Point for the $\frac{1}{4}$ cor. of secs. 11 and 12.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$

S 11 | S 12

1953

Deposit a broken glass bottle alongside iron post.

80.00

Point for the cor. of secs. 1, 2, 11 and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 N R 20 W

S 2 | S 1

S 11 | S 12

1953

Deposit a broken glass bottle alongside iron post.

Land, rolling.

Soil, sandy.

Timber, none.

Undergrowth, scattering greasewood.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., which is monumented with an iron post, marked and witnessed as described in the official record.

Subdivision of T. 6 N., R. 20 W.

Chains


S. 89° 58' W., bet. secs. 1 and 12.

Over gently rolling land, through scattering undergrowth.

40.04

Point for the $\frac{1}{4}$ cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a broken glass bottle alongside iron post.

80.08

The cor. of secs. 1, 2, 11 and 12.

Land, gently rolling.

Soil, sandy.

Timber, none.

Undergrowth, scattering greasewood.

N. 0° 01' W., bet. secs. 1 and 2.

Over rolling land, through scattering undergrowth.

40.00

Point for the $\frac{1}{4}$ cor. of secs. 1 and 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a broken glass bottle alongside iron post.

76.57

Intersect the E. bdy. of the Colorado River Indian Reservation.

Point for the closing cor. of secs. 1 and 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a broken glass bottle alongside iron post.

From this point; the closing cor. of secs. 2 and 35, from the W, bears N. 18° 21' E., 3.55 chs. dist., and is monumented with an iron post, marked and witnessed as described in the official record; The reservation boundary Mile Post No. 30, bears, N. 18° 21' E., 11.61 chs. dist., and is monumented with an iron post, marked and witnessed as described in the official record.

Chains

Land, rolling.
Soil, sandy.
Timber, none.
Undergrowth, scattering greasewood.

From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., which is monumented with an iron post, marked and witnessed as described in the official record.


N. 0° 01' W., bet. secs. 34 and 35.

Over rolling land, through scattering undergrowth.

10.70 Wash, 20 lks. wide, course SW.

40.00 Point for the $\frac{1}{4}$ cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a broken glass bottle alongside iron post.

76.80 Drain, course SE.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a broken glass bottle alongside iron post.

Land, rolling.
Soil, sandy.
Timber, palo verde.
Undergrowth, scattering greasewood.

From the cor. of secs. 25, 26, 35 and 36.

WEST, bet. secs. 26 and 35.

Over broken land, through scattering timber and undergrowth.

26.56 Drain, course S.

39.98 Point for the $\frac{1}{4}$ cor. of secs. 26 and 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of T. 6 N., R. 20 W.

Chains

S 26

 $\frac{1}{4}$

S 35

1953

Deposit a broken glass bottle alongside iron post.

58.96 Drain, course S.

76.56 Top of low spur, slopes S.

79.96 The cor. of secs. 26, 27, 34 and 35.

Land, broken.

Soil, gravelly.

Timber, palo verde.

Undergrowth, scattering greasewood.

WEST, bet. secs. 27 and 34.

Over broken land, through scattering undergrowth.

1.50 Drain, course SE.

7.67 Top of low spur, slopes S.

9.00 Drain, course S.

15.50 Top of low spur, slopes S.

26.60 Wash, 20 lks. wide, course S. 20° W.

37.00 Wash, 50 lks. wide, course S.

40.00 Point for the $\frac{1}{4}$ cor. of secs. 27 and 34.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 27

 $\frac{1}{4}$

S 34

1953

Deposit a broken glass bottle alongside iron post.

51.60 Drain, course S.

51.82 Intersect the E. bdy. of the Colorado River Indian Reservation.

Point for the closing cor. of secs. 27 and 34.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

R

T 6 N.

I

S 27. C C

R

S 34

C

R 20 W

1953

From this point; the closing cor. of secs. 28 and 33, from the W., bears S. 18° 20' W., 14 lks. dist., and is monumented with an

Chains

iron post, marked and witnessed as described in the official record.

Land, broken.

Soil, sandy and gravelly.

Timber, palo verde.

Undergrowth, scattering greasewood.

From the cor. of secs. 26, 27, 34 and 35.

N. 0° 01' W., bet. secs. 26 and 27.

Over broken land, through scattering undergrowth.

20.00 Drain, course SE.

40.00 Point for the $\frac{1}{4}$ cor. of secs. 26 and 27.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd..

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 27 \quad | \quad \text{S } 26 \\ \hline 1953 \end{array}$$

Deposit a broken glass bottle alongside iron post.

80.00 Point for the cor. of secs. 22, 23, 26 and 27.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd..

$$\begin{array}{c} \text{T } 6 \text{ N } \text{ R } 20 \text{ W} \\ \text{S } 22 \quad | \quad \text{S } 23 \\ \hline \text{S } 27 \quad | \quad \text{S } 26 \\ \hline 1953 \end{array}$$

Deposit a broken glass bottle alongside iron post.

Land, broken.

Soil, gravelly.

Timber, palo verde.

Undergrowth, scattering greasewood.

From the cor. of secs. 23, 24, 25 and 26.

WEST, bet. secs. 23 and 26.

Over rolling land, through scattering undergrowth.

39.98 Point for the $\frac{1}{4}$ cor. of secs. 23 and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd..

$$\begin{array}{c} \text{S } 23 \\ \hline \frac{1}{4} \quad | \\ \hline \text{S } 26 \\ \hline 1953 \end{array}$$

Deposit a broken glass bottle alongside iron post.

Subdivision of T. 6 N., R. 20 W.

Chains

58.46 Wash, 20 lks. wide, course SE.

79.96 The cor. of secs. 22, 23, 26 and 27.

Land, rolling.
Soil, sandy and gravelly.
Timber, palo verde.
Undergrowth, scattering greasewood.


WEST, bet. secs. 22 and 27.

Over rolling land, through scattering undergrowth.

25.18 Intersect the E. bdy. of the Colorado River Indian Reservation.

Point for the closing cor. of secs. 22 and 27.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd..



Deposit a broken glass bottle alongside iron post.

From this point; the closing cor. of secs. 22 and 27, from the W., bears S. 18° 20' W., 9 lks. dist., and is monumented with an iron post, marked and witnessed as described in the official record; the reservation boundary Mile Post No. 26, bears N. 18° 20' E., 25.26 chs. dist., and is monumented with an iron post, marked and witnessed as described in the official record.

Land, rolling.
Soil, sandy.
Timber, none.
Undergrowth, scattering greasewood.

From the cor. of secs. 22, 23, 26 and 27.

N. 0° 01' W., bet. secs. 22 and 23.

Over rolling hilly land, through scattering timber.


9.40 Wash, 20 lks. wide, course SE.

11.88 Top of low spur, slopes SE.

15.00 Drain, course S. 20° E.

40.00 Point for the ¼ cor. of secs. 22 and 23.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd..



Deposit a broken glass bottle alongside iron post.

BOOK 4442

Subdivision of T. 6 N., R. 20 W.

Chains

45.00 Ascend 43 ft. over SW. slope.

47.61 Top of ridge, bears N. 80° W. and S. 80° E.; desc. 40 ft. over NE. slope.

57.00 Drain, course E.; asc. 30 ft. over S. slope.


58.77 Top of spur, slopes E.; desc. 50 ft. over N. slope.

71.70 Drain, course W.

75.59 Intersect E. bdy. of the Colorado River Indian Reservation.

Point for the closing cor. of secs. 22 and 23.

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, and mound to top with stone, with brass cap mkd.



From this point, the closing cor. of secs. 15 and 22, from the W., bears N. 18° 20' E., 4.36 chs. dist., and is monumented with an iron post, marked and witnessed as described in the official record.

Land, hilly.
Soil, gravelly.
Timber, palo verde.
Undergrowth, scattering greasewood.

From the cor. of secs. 13, 14, 23 and 24.

WEST, bet. secs. 14 and 23.

Over rolling hilly land, through scattering timber and undergrowth.

25.00 Ascend 35 ft. over E. slope.


29.40 Top of spur, slopes N.; desc. 34 ft. over W. slope.

34.30 Drain, course N.; asc. 24 ft. over E. slope.

37.30 Top of spur, slopes N.; desc. 23 ft. over W. slope.

40.00 Point for the ¼ cor. of secs. 14 and 23.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and mound to top with stone, with brass cap mkd.



67.00 Drain, course N.

Subdivision of T. 6 N., R. 20 W.

Chains

72.30


Ascend 29 ft. over E. slope.

78.46

Intersect E. bdy. of the Colorado River Indian Reservation.

Point for the closing cor. of secs. 14 and 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



From this point; the closing cor. of secs. 15 and 22, from the W., bears S. 18° 20' W., 24 lks. dist., and is monumented with an iron post, marked and witnessed as described in the official record; the reservation boundary Mile Post No. 27, bears N. 18° 20' E., 20.91 chs. dist., and is monumented with an iron post, marked and witnessed as described in the official record.

Land, hilly.
Soil, gravelly.
Timber, palo verde.
Undergrowth, scattering greasewood.

From the cor. of secs. 11, 12, 13 and 14.


WEST., bet. secs. 11 and 14.

Over rolling land, through scattering undergrowth.

40.00

Point for the 1/4 cor. of secs. 11 and 14.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a broken glass bottle alongside iron post.

51.92

Intersect the E. bdy. of the Colorado River Indian Reservation.

Point for the closing cor. of secs. 11 and 14.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a broken glass bottle alongside iron post.

Subdivision of T. 6 N., R. 20 W.

Chains

From this point; the closing cor. for secs. 10 and 15, from the W., bears S. 18° 21' W., 11 lks. dist., and is monumented with an iron post, marked and witnessed as described in the official record; the reservation boundary Mile Post No. 28, bears N. 18° 21' E., 16.58 chs. dist., monumented with an iron post marked and witnessed as described in the official record. This iron post is in a bad state of repair with the top portion rusted off.

At point for reservation boundary Mile Post No. 28.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

R M P
I 28 / P L
R 1912
C 1953

Deposit a broken glass bottle and the original iron post alongside iron post.

Land, rolling.

Soil, sandy.

Timber, none.

Undergrowth, scattering greasewood.

From the cor. of secs. 1, 2, 11 and 12.

WEST, bet. secs. 2 and 11.

Over gently rolling land, through scattering undergrowth.

25.39

Intersect the E. bdy. of the Colorado River Indian Reservation.

Point for the closing cor. of secs. 2 and 11.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

R T 6 N
I S 2 C C
R S 11
C R 20 W
1953

Deposit a broken glass bottle alongside iron post.

From this point; the closing cor. of secs. 2 and 11, from the W., bears S. 18° 21' W., 7 lks. dist., and is monumented with an iron post, marked and witnessed as described in the official record; the reservation boundary Mile Post No. 29, bears N. 18° 21' E., 12.30 chs. dist., and is monumented with an iron post, marked and witnessed as described in the official record.

Land, rolling.

Soil, sandy.

Timber, none.

Undergrowth, scattering greasewood.

BOOK 4442

T. 6 N., R. 20 W.

Chains

General Description

This portion of Township 6 North, Range 20 West lies east of and adjacent to the Colorado River Indian Reservation. It is located on the La Pesa Plain with a variation in elevation of from 750 ft. to 900 ft. above sea level. The drainage is in a generally south direction. The soil is all sandy and gravelly and supports a scattering growth of greasewood with occasional small stands of palo verde timber. There are no traveled roads or improvements within the township.

4-680
(Feb., 1960)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Fred R. Chappell	Cartographic Survey Aid
Jack Hammett	Surveying and Cartographic Aid
Ernest S. Barela	" "
Amarante Lovato	" "
O. Charles Harper	" "
Paul O. Heath	" "

CERTIFICATE OF CADASTRAL ENGINEER

I, Ty White, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9 th. day of October, 1952

I have surveyed Portions of the south boundary and subdivisional lines of Township 6 North, Range 20 West.

Gila and of the Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing

field notes.
Calver City, Calif.
January 29, 1954

Ty White
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., APR 5 1955, 1955

The foregoing field notes of the survey of Portions of the south boundary and subdivisional lines of Township 6 North, Range 20 West.

executed by Ty White

having been critically examined and found correct, are hereby approved.

Earl G. Harrington
Chief, Division of Cadastral Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.~~

~~_____
Chief, Division of Cadastral Engineering.~~