

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Dependent Resurvey of a Portion of the West Boundary

and

Portion of Subdivision, and Survey of the Subdivisional Lines

of

Sections 6, 7, 18, and 19,

and

Mineral Segregation Survey of the Margarita Mineral Claim

in Section 7,

Township 15 South, Range 13 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Clarence E. Bilbray, Cartographer (Cadastral)

Under special instructions dated January 9  
December 7, 1953, which provided  
for the surveys included under Group No. 286, approved January 22, 1953  
December 7, 1953  
and assignment instructions dated December 1, 1952

Survey commenced January 7, 1954

Survey completed February 8, 1954

4452

4452

4452

1A

BOOK 4452

# INDEX DIAGRAM

Township 15 South, Range 13 East

15	15 14 15	5	4	3	2	1
13	14 13 12					
20	19 11 19	8	9	10	11	12
9	18 10 8					
3	26 8 26	17	16	15	14	13
3	25 7 6					
2	32 5 32	20	21	22	23	24
1	31 5 4					
30		29	28	27	26	25
31		32	33	34	35	36

- Subdivision SE  $\frac{1}{4}$  Sec. 6 ----- Page 16
- Subdivision SW  $\frac{1}{4}$  Sec. 6 ----- Page 17
- Subdivision NE  $\frac{1}{4}$  Sec. 7 ----- Page 20
- Subdivision NW  $\frac{1}{4}$  Sec. 7 ----- Page 21
- Subdivision SE  $\frac{1}{4}$  Sec. 7 ----- Page 22
- Mineral Segregation Survey Sec. 7 ----- Page 24
- Subdivision NE  $\frac{1}{4}$  Sec. 18 ----- Page 28
- Subdivision NW  $\frac{1}{4}$  Sec. 18 ----- Page 29
- Subdivision SW  $\frac{1}{4}$  Sec. 18 ----- Page 30
- Subdivision NE  $\frac{1}{4}$  Sec. 19 ----- Page 33
- Subdivision NW  $\frac{1}{4}$  Sec. 19 ----- Page 34
- Subdivision SW  $\frac{1}{4}$  Sec. 19 ----- Page 35

## T. 15 S., R. 13 E.

## Chains

The township boundaries and subdivisional lines were originally surveyed by S. W. Foreman in 1871. A portion of the boundaries and subdivisional lines were resurveyed by L. D. Chillson in 1888. The W.  $3\frac{1}{2}$  miles of the north boundary of the township were retraced by W. E. Hiester in 1931 at which time iron post monuments were set at the quarter section corner of sections 3 and 34, and at the corner of sections 5, 6, 31, and 32. Retracements and partial resurveys of the township exteriors were made by C. M. Leedy in 1915, but no corners were reestablished on the north boundary. In the same year Leedy also made extensive resurveys of subdivisional lines. The north  $\frac{1}{4}$  miles of the west boundary were resurveyed and a double set of corners established by J. F. Hesse in 1915.

The following field notes are those of the dependent resurvey of a portion of the west boundary and portion of the subdivision, and survey of the subdivisional lines of sections 6, 7, 18, and 19, T. 15 S., R. 13 E., of the Gila and Salt River Meridian, Arizona.

The survey was executed with a light mountain solar transit made by W. & L. E. Gurley, serial number 371540, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition, and having been placed in satisfactory adjustment prior to the beginning of the survey, was tested and found free from appreciable error.

The measurements were made with a narrow steel tape, 5 chains in length, graduated to tenths of a link for the first 10 links, every link for the following 90 links, and at each 10 link interval for the remaining 400 links. The tape was tested by comparison with a standard 1-chain steel tape and found correct. The measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents are entered in the field note record.

The directions of all lines were determined by transit method, with azimuth obtained from U. S. Coast & Geodetic Survey triangulation station "CAT MOUNTAIN", which is located in the NW $\frac{1}{4}$  of section 30, T. 14 S., R. 13 E. All bearings were adjusted for differences in longitude between stations.

The geographic position of the southeast corner of section 19, T. 15 S., R. 13 E., as computed through the tie made to triangulation station CAT MOUNTAIN, is:

Latitude,  $32^{\circ} 06' 16.4''$  N. Longitude,  $111^{\circ} 02' 43.4''$  W.

Dependent Resurvey, Portion of West Boundary, T. 15 S., R. 13 E.

(Reestablishment of the survey executed by J. F. Hesse in 1915)

Beginning at the corner of secs. 19, 24, 25, and 30, T. 15 S., R. 12 and 13 E., which is monumented with an iron post, 3 ins. diam., set and marked as described in the official record.

N.  $0^{\circ} 28'$  E., on west boundary of section 19.

Over nearly level land, through undergrowth.

10.11 Point for the S-S  $\frac{1}{64}$  sec. cor. of sec. 19.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

SS1/64

S 19

1954

## Dependent Resurvey, Portion of West Boundary, T. 15 S., R. 13 E.

Chains 20.22	<p>Point for the S 1/16 sec. cor. of sec. 19.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 2<math>\frac{1}{4}</math> ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 19 1954</p>
30.33	<p>Point for the N-S 1/64 sec. cor. of sec. 19.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 2<math>\frac{1}{4}</math> ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">N-S 1/64 S 19 1954</p>
40.02	<p>The <math>\frac{1}{4}</math> sec. cor. of sec. 24, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.</p>
40.44	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 19, at record distance from the <math>\frac{1}{4}</math> sec. cor. of sec. 24. There is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 2<math>\frac{1}{4}</math> ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S19 1954</p>
60.66	<p>Point for the N 1/16 sec. cor. of sec. 19.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 2<math>\frac{1}{4}</math> ins. in the ground over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S19 1954</p>
76.65	<p>Old road, bears NW. and SE.</p>
80.07	<p>The corner of secs. 13 and 24, T. 15 S., R. 12 E., which is monumented with an iron post, 3 ins. diam., set and marked as described in the official record.</p> <p>Remark the brass cap</p> <p style="text-align: center;">T15S R12E   R13E S13   S19 S24   1954 1915</p>
80.88	<p>Point for the corner of secs. 18 and 19, at record distance from the corner of secs. 13 and 24. There is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 2<math>\frac{1}{4}</math> ins. in the ground over a deposit of broken glass, with brass cap mkd.</p>

## Dependent Resurvey, Portion of West Boundary, T. 15 S., R. 13 E.

Chains

T15S	T15S
S13	S18
R12E	S19
	R13E
	1954

Land, nearly level.  
Soil, sandy.  
No timber; undergrowth, greasewood and mesquite.

N. 0° 25' E., on west boundary of section 18.

Over nearly level land, through undergrowth.

10.105 Point for the S-S 1/64 sec. cor. of sec. 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S-S	S-S
1/64	1/64
S18	S18
	1954

20.21 Point for the S 1/16 sec. cor. of sec. 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 1/16	S 1/16
S18	S18
	1954

21.40 Road, bears ENE. and WSW.

26.60 Wash, 12 lks. wide, 1 ft. deep, drains W.

39.25 The ¼ sec. cor. of sec. 13, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.

40.42 Point for the ¼ sec. cor. of sec. 18, at record distance from the ¼ sec. cor. of sec. 13. There is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

¼	¼
S18	S18
	1954

N. 0° 28' E., beginning new measurement.

10.105 Point for the S-N 1/64 sec. cor. of sec. 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S-N	S-N
1/64	1/64
S18	S18
	1954

## Dependent Resurvey, Portion of West Boundary, T. 15 S., R. 13 E.

Chains 20.21	Point for the N 1/16 sec. cor. of sec. 18.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  N 1/16 S18 1954
31.70	El Paso Natural Gas line, bears N. 75° 35' W. and S. 75° 35' E.
38.90	The corner of secs. 12 and 13, T. 15 S., R. 12 E., which is monumented with an iron post, 3 ins. diam., set and marked as described in the 1953 resurvey record of sec. 12, T. 15 S., R. 12 E.
40.42	The corner of secs. 7 and 18, which is monumented with an iron post, $2\frac{1}{2}$ ins. diam., set and marked as described in the 1953 resurvey record of sec. 12, T. 15 S., R. 12 E.  Land, nearly level. Soil, sandy. No timber; undergrowth, greasewood and mesquite.
Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.  Reestablishment of the surveys executed by S. W. Foreman in 1871, and resurvey by C. M. Leedy in 1915.  Beginning at the corner of secs. 19, 20, 29, and 30, which is monumented with an iron post, 3 ins. diam., set and marked as described in the official record.  S. 89° 53' W., bet. secs. 19 and 30.  Over nearly level land, through undergrowth.	
19.87	The E 1/16 sec. cor. of secs. 19 and 30, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.
39.79	The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, which is monumented with an iron post, 1 in. diam., set and marked as described in the official record.  S. 88° 15' W., beginning new measurement.
10.209	Point for the E-W 1/64 sec. cor. of secs. 19 and 30.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  E-W 1/64 $\frac{S 19}{S 30}$ 1954
16.10	Wash, 10 lks. wide, 1 ft. deep, drains ENE.
20.418	The W 1/16 sec. cor. of secs 19 and 30, which is monumented with an iron post, 1 in. diam., set and marked as described in the official recbrd.  S. 87° 58' W., beginning new measurement.
10.188	Point for the W-W 1/64 sec. cor. of secs. 19 and 30.

## Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.

Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{S 19} \\ \text{W-W } 1/64 \text{ } \\ \hline \text{S 30} \\ 1954 \end{array}$$

16.65 Wash, 7 lks. wide, 1 ft. deep, drains NNE.

19.95 Wash, 7 lks. wide, 1 ft. deep, drains NNE.

20.275 The corner of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp.

Land, nearly level.

Soil, sandy.

No timber; undergrowth, greasewood and mesquite.

From the corner of secs. 19, 20, 29, and 30.

N.  $0^{\circ}$  31' E., bet. secs. 19 and 20.

Over nearly level land, through undergrowth,

36.60 Wash. 10 lks. wide, 2 ft. deep, drains E.

40.15 The  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, which is marked by a 2 in. iron pipe, accepted as the best existing evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \uparrow \\ \text{S19} \mid \text{S20} \\ \downarrow \\ 1954 \end{array}$$

Bury the old iron pipe alongside the iron post.

N.  $0^{\circ}$  28' E., beginning new measurement.

10.053 Point for the S-N  $1/64$  sec. cor. of secs. 19 and 20.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \text{S-N } 1/64 \\ \text{S19} \mid \text{S20} \\ \downarrow \\ 1954 \end{array}$$

20.106 Point for the N  $1/16$  sec. cor. of secs. 19 and 20.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \text{N } 1/16 \\ \text{S19} \mid \text{S20} \\ \downarrow \\ 1954 \end{array}$$

22.10 Old road, bears E. and W.

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.

Chains 26.90	Old road, bears NNW. and SSE.								
28.60	Wash, 10 lks. wide, 1 ft. deep, drains SE.								
30.159	Point for the N-N 1/64 sec. cor. of secs. 19 and 20.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">N-N 1/64</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2">1954</td></tr> </table> </div>	N-N 1/64		S19	S20	1954			
N-N 1/64									
S19	S20								
1954									
40.212	The corner of secs. 17, 18, 19, and 20, which is marked by an iron pipe, 2 ins. diam., accepted as the best existing evidence of the position of the original corner.  At the corner point  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.  <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T15SRL3E</td></tr> <tr><td>S18</td><td>S17</td></tr> <tr><td>S19</td><td>S20</td></tr> <tr><td colspan="2">1954</td></tr> </table> </div> <p>Land, nearly level. Soil, sandy. No timber; undergrowth, greasewood, mesquite and cacti.</p>	T15SRL3E		S18	S17	S19	S20	1954	
T15SRL3E									
S18	S17								
S19	S20								
1954									
	S. 89° 22' W., bet. secs. 18 and 19.  Ascend 90 ft. over SE. slope, through undergrowth.								
10.094	Point for the E-E 1/64 sec. cor. of secs. 18 and 19.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.  <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">E-E 1/64</td></tr> <tr><td colspan="2">S 18</td></tr> <tr><td colspan="2">S 19</td></tr> <tr><td colspan="2">1954</td></tr> </table> </div>	E-E 1/64		S 18		S 19		1954	
E-E 1/64									
S 18									
S 19									
1954									
20.188	Point for the E 1/16 sec. cor. of secs. 18 and 19.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">E 1/16</td></tr> <tr><td colspan="2">S 18</td></tr> <tr><td colspan="2">S 19</td></tr> <tr><td colspan="2">1954</td></tr> </table> </div>	E 1/16		S 18		S 19		1954	
E 1/16									
S 18									
S 19									
1954									
22.20	Top of ascent; desc. 50 ft.								
30.282	Point for the W-E 1/64 sec. cor. of secs. 18 and 19.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.  <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">W-E 1/64</td></tr> <tr><td colspan="2">S 18</td></tr> <tr><td colspan="2">S 19</td></tr> <tr><td colspan="2">1954</td></tr> </table> </div>	W-E 1/64		S 18		S 19		1954	
W-E 1/64									
S 18									
S 19									
1954									



## Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.

Chains 32.00	Wash, 10 lks. wide, 2 ft. deep, drains S.; asc. 30 ft.
37.85	Top of ascent; desc. 90 ft. over rocky W. slope.
40.376	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining-evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.  $\frac{1}{4}$ S 18 S 19 1954
50.40	Foot of descent. Thence over nearly level land.
50.47	Point for the E-W $\frac{1}{64}$ sec. cor. of secs. 18 and 19.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  E-W $\frac{1}{64}$ S 18 S 19 1954  Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
60.564	Point for the W- $\frac{1}{16}$ sec. cor. of secs. 18 and 19.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  W $\frac{1}{16}$ S 18 S 19 1954
70.658	Point for the W-W $\frac{1}{64}$ sec. cor. of secs. 18 and 19.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  W-W $\frac{1}{64}$ S 18 S 19 1954
80.50	The corner of secs. 18 and 19, on the W. bdy. of the Tp.  Land, rolling; western part nearly level. Soil, sandy and rocky. No timber; undergrowth, greasewood, mesquite and cacti.
	From the corner of secs. 17, 18, 19, and 20. N. $0^{\circ}$ 06' E., bet. secs. 17 and 18.  Over rolling land, through undergrowth.
32.00	Top of ridge, bears E. and W.
40.048	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.  $\frac{1}{4}$ S 18   S 17 1954

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.

Chains  
50.06

Point for the S-N 1/64 sec. cor. of secs. 17 and 18.

Set an iron post, 28 ins. long; 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S-N 1/64  
S 18 | S 17  
1954

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

50.75

El Paso Natural Gas line, bears N. 75° 30' W. and S. 75° 30' E.

54.80

Road, bears E. and W.

60.072

Point for the N 1/16 sec. cor. of secs. 17 and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

N 1/16  
S 18 | S 17  
1954

62.00

Top of ridge, bears E. and W.; descend over gradual N. slope.

69.00

Wash, 20 lks. wide, 3 ft. deep, drains W.; asc. gradually over S. slope.

70.084

Point for the N-N 1/64 sec. cor. of secs. 17 and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N-N 1/64  
S 18 | S 17  
1954

80.096

Point for the corner of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

T15S R13E  
S 7 | S 8  
S 18 | S 17  
1954

From this cor., the 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 3 ins. diam., firmly set and with brass cap mkd. as described in the official record, bears N. 89° 44' E., 120.53 chs. dist.

Land, rolling.  
Soil, sandy and rocky.  
No timber; undergrowth, greasewood, mesquite, paloverde and cacti.

S. 89° 54' W., bet. secs. 7 and 18.

Over rolling land, through undergrowth.

## Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.

Chains	
8.90	Wash, 10 lks. wide, 1 ft. deep, drains SW.
10.027	Point for the E-E 1/64 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd. $\begin{array}{r} \text{S } 7 \\ \text{E-E } 1/64 \text{ ---} \\ \text{S18} \\ 1954 \end{array}$
20.054	Point for the E 1/16 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \text{S } 7 \\ \text{E } 1/16 \text{ ---} \\ \text{S18} \\ 1954 \end{array}$
30.081	Point for the W-E 1/64 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \text{S } 7 \\ \text{W-E } 1/64 \text{ ---} \\ \text{S18} \\ 1954 \end{array}$
33.60	Wash, 6 lks. wide, 2 ft. deep, drains SE.
34.45	Wash, 6 lks. wide, 1 ft. deep, drains S.
40.108	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd. $\begin{array}{r} \text{S } 7 \\ \text{¼ ---} \\ \text{S18} \\ 1954 \end{array}$
40.85	Wash, 10 lks. wide, 3 ft. deep, drains S.
45.95	Wash, 10 lks. wide, 3 ft. deep, drains S.
50.135	Point for the E-W 1/64 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd. $\begin{array}{r} \text{S } 7 \\ \text{E-W } 1/64 \text{ ---} \\ \text{S18} \\ 1954 \end{array}$
60.162	Point for the W 1/16 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{r} \text{S } 7 \\ \text{W } 1/16 \text{ ---} \\ \text{S18} \\ 1954 \end{array}$

## Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.

Chains

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

74.70 Wash, 5 lks. wide, 1 ft. deep, drains S.

76.40 Road, bears NW. and SE.

79.994 The corner of secs. 7 and 18, on the W. bdy. of the Tp.

Land, rolling.

Soil, sandy and rocky.

No timber; undergrowth, greasewood, mesquite, paloverde and cacti.

From the corner of secs. 7, 8, 17, and 18.

N. 0° 38' E., bet. secs. 7 and 8.

Over rolling land, through undergrowth.

10.025 Point for the S-S 1/64 sec. cor. of secs. 7 and 8.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd.

S-S 1/64

S 7 | S 8

1954

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

20.05 Point for the S 1/16 sec. cor. of secs. 7 and 8.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd.

S 1/16

S 7 | S 8

1954

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

30.075 Point for the N-S 1/64 sec. cor. of secs. 7 and 8.

Set an iron post; 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd.

N-S 1/64

S 7 | S 8

1954

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

36.35 Wash, 15 lks. wide, 2 ft. deep, drains SSE.

39.10 Old road, bears E. and W.

40.10 The ¼ sec. cor. of secs. 7 and 8, monumented with an iron pipe, 1½ ins. diam., this corner has been used in subdivisional surveys in sec. 8, accepted as the best existing evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

## Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.

Chains

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 7 \quad | \quad \text{S } 8 \\ | \\ 1954 \end{array}$$

N.  $1^{\circ} 39'$  E., beginning new measurement.

- 0.30 Intersection of newly constructed roads, bears N., E., and W.  
Thence along or near W. side of road.
- 5.00 Ascend a gradual S. slope.
- 10.152 Point for the S-N  $1/64$  sec. cor. of secs. 7 and 8.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{S-N } 1/64 \\ | \\ \text{S } 7 \quad | \quad \text{S } 8 \\ | \\ 1954 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

- 20.00 End of road.
- 20.304 Point for the N  $1/16$  sec. cor. of secs. 7 and 8.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{N } 1/16 \\ | \\ \text{S } 7 \quad | \quad \text{S } 8 \\ | \\ 1954 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

- 30.456 Point for the N-N  $1/64$  sec. cor. of secs. 7 and 8.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{N-N } 1/64 \\ | \\ \text{S } 7 \quad | \quad \text{S } 8 \\ | \\ 1954 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Ascend 230 ft. over a steep rocky S. slope.

- 38.00 Top of ridge, bears E. and W., desc. 105 ft. over a steep N. slope to cor.

- 40.608 The corner of secs. 5, 6, 7, and 8, which is monumented with a 2 in. iron pipe, this point has long been recognized as the corner by adjacent land owners, and has been used for subdivisional surveys in sec. 8, and is accepted as the best existing evidence of the position of the original corner

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.

Chains

T15SR13E

S 6 | S 5

S 7 | S 8

1954

Land, rolling and hilly.

Soil, sandy and rocky

No timber; undergrowth, greasewood, mesquite, paloverde and cacti.

S. 89° 36' W., bet. secs. 6 and 7.

Descend 60 ft. over broken NW. slope, through undergrowth.

6.90 Wash, 10 lks. wide, 3 ft. deep, drains N., ascend 20 ft.

10.107 Point for the E-E 1/64 sec. cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

S 6
E-E 1/64 ———
S 7
1954

11.50 Top of ascent, desc. 110 ft. over W. slope.

20.214 Point for the E 1/16 sec. cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

S 6

S 7

1954

21.00 Thence overrolling land.

25.30 Fall 40 lks. N. of road intersection from which roads, bears S. and W.

30.321 Point for the W-E 1/64 sec. cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 6
W-E 1/64 ———
S 7
1954

From this point center line of road, bears S. 35 lks. dist.

35.00 Fall 30 lks. N. of intersection of roads, which bear S. and E.

40.428 Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

S 6

S 7

Ascend 75 ft. over broken SE. slope.

46.50 Wash, 6 lks. wide, 1 ft. deep, drains ESE.

## BOOK 4452

Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.

## Chains

- 50.535 Point for the E-W 1/64 sec. cor. of secs. 6 and 7.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- E-W 1/64  $\frac{S\ 6}{S\ 7}$   
1954
- Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
- 60.642 Point for the W 1/16 sec. cor. of secs. 6 and 7.  
Set an iron post, 28 ins. long, 2½ ins. diam., over a chiseled X on bedrock, and in a mound of stone to top, with brass cap mkd.
- W 1/16  $\frac{S\ 6}{S\ 7}$   
1954
- 61.50 Top of ascent; desc. 80 ft. over W. and SW. slope.
- 70.50 Wash, 8 lks. wide, 1 ft. deep, drains SSW.; asc. 120 ft. over SE. s slope.
- 70.749 Point for the W-W 1/64 sec. cor. of secs. 6 and 7.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- (constant bearing)  $\frac{S\ 6}{S\ 7}$   
W-W 1/64  $\frac{S\ 6}{S\ 7}$   
1954
- Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
- 80.533 The corner of secs. 6 and 7, which is monumented with an iron post, 2½ ins. diam., set, marked and witnessed as described in the 1953 resurvey record of sec. 1.  
Land, rolling and hilly.  
Soil, sandy and rocky  
No timber; undergrowth, greasewood, mesquite, paloverde and cacti.
- 
- From the corner of secs. 5, 6, 7, and 8.  
N. 0° 54' W., bet. secs. 5 and 6.  
Descend 118 ft. over steep N. slope.
- 8.15 Old road, bears E. and W.
- 9.75 Foot of descent; asc. 60 ft.
- 9.935 Point for the S-S 1/64 sec. cor. of secs. 5 and 6.  
Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
- S-S 1/64  
S 6 | S 5  
1954
- 17.45 Top of ascent; desc. 20 ft.

## Dependent Resurvey, Portion of Subdivision, T. 15 S., R. 13 E.

Chains

19.70 Wash, 10 lks. wide, 1 ft. deep, drains SW.

19.87 Point for the S 1/16 sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} \text{S } 1/16 \\ | \\ \text{S } 6 \quad | \quad \text{S } 5 \\ | \\ 1954 \end{array}$$

22.75 Wash, 7 lks. wide, 3 ft. deep, drains SW.; asc 400 ft. over steep S. and SW. slope.

39.59 Point for the witness ¼ sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{WC} \\ | \\ \frac{1}{4} \\ | \\ \text{S } 6 \quad | \quad \text{S } 5 \\ | \\ 1954 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

39.74 True point for the ¼ sec. cor. of secs. 5 and 6, falls on rock cliff, 20 ft. high. (at proportionate distance)

51.00 Top of ridge; 50 lks. W. of saddle, bears E. and W.; desc. approximately 350 ft. over steep, N. slope.

65.00 Thence over gently rolling land.

80.077 The corner of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp. is monumented with an iron post, 2 ins. diam., set and marked as described in the official record.

Land, mountainous.

Soil, rocky clay.

No timber; undergrowth, greasewood, mesquite, paloverde and cacti.

## Subdivision of Section 6, T. 15 S., R. 13 E.

From the ¼ sec. cor. of secs. 6 and 7.

N. 0° 39' W., on the N. and S. center line of sec. 6.

Over rolling land, through undergrowth.

9.94 Point for the C-S-S 1/64 sec. cor. of sec. 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} \text{C} \\ | \\ \text{S-S } 1/64 \quad | \quad \text{S } 6 \\ | \\ \text{C} \\ | \\ 1954 \end{array}$$

11.95 Old road, bears NW. and SE.

19.88 Point for the C-S 1/16 sec. cor. of sec. 6.



## BOOK 4452

Subdivision of Section 6, T. 15 S., R. 13 E.

## Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C \\ | \\ S \ 1/16 \quad | \quad S \ 6 \\ | \\ C \\ 1954 \end{array}$$

22.60 Wash, 15 lks. wide, 2 ft. deep, drains SW.

39.76 Point for the C  $\frac{1}{4}$  sec. cor. of sec. 6, at the intersection of the E. and W. center line of sec. 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} C \ \frac{1}{4} \ S \ 6 \\ 1954 \end{array}$$

65.60 Shallow wash, drains NE.

78.60 Shallow wash, drains NE.

79.99 Intersect the N. bdy. of the Tp., at the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, which is monumented with an iron post,  $2\frac{1}{2}$  ins. diam., set and marked as described in the official record.

Land, rolling.

Soil, sandy and rocky.

No timber; undergrowth, greasewood, mesquite, paloverde and cacti.

From the true point for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 6.

S.  $89^{\circ} 37'$  W., on the E. and W. center line of sec. 6.

Descend 225 ft. over a broken W. slope.

20.124 Point for the C-E  $1/16$  sec. cor. of sec. 6.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 13 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} E \ 1/16 \\ C \ \text{---} \ C \\ | \\ S \ 6 \\ 1954 \end{array}$$

Thence over rolling land.

20.65 Old road, bears NE. and SW

28.85 Wash, 15 lks. wide, 2 ft. deep, drains NE.

40.248 The C  $\frac{1}{4}$  sec. cor. of sec. 6.

60.353 Point for the C-W  $1/16$  sec. cor. of sec. 6, falls on bedrock.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., over a chiseled X on bedrock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} W \ 1/16 \\ C \ \text{---} \ C \\ | \\ S \ 6 \end{array}$$

1954

80.045 The  $\frac{1}{4}$  sec. cor. of sec. 6, which is monumented with an iron post,  $2\frac{1}{2}$  ins. diam., set, marked and witnessed as described in the 1953 resurvey record of sec. 1, T. 15 S., R. 12 E.

## Subdivision of Section 6, T. 15 S., R. 13 E.

## Chains

Land, rolling.  
Soil, sandy and rocky.  
No timber; undergrowth, greasewood, mesquite, paloverde and cacti.

Subdivision of the SE $\frac{1}{4}$ .

From the E 1/16 sec. cor. of secs. 6 and 7.

N. 0° 48' W., on the N. and S. center line of the SE $\frac{1}{4}$  of sec. 6.

Over gently rolling land.

9.942 Point for the C-S-SE 1/64 sec. cor. of sec. 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 6  
C-S-SE  
1/64  
1954

15.30 Old road, bears NW. and SE.

19.884 Point for the SE 1/16 sec. cor. of sec. 6, at the intersection of the E. and W. center line of the SE $\frac{1}{4}$  of sec. 6.

SE 1/16 S 6

1954

37.55 Shallow wash; 10 lks. wide, drains NE.

39.763 The C-E 1/16 sec. cor. of sec. 6.

From the S 1/16 sec. cor. of secs. 5 and 6.

S. 89° 36' W., on the E. and W. center line of the SE $\frac{1}{4}$  of sec. 6.

Over gently rolling land.

10.084 Point for the C-E-SE 1/64 sec. cor. of sec. 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 6  
C-E-SE  
1/64  
1954

20.168 The SE 1/16 sec. cor. of sec. 6.

25.25 Old road, bears NE. and SW.

30.253 Point for the C-W-SE 1/64 sec. cor. of sec. 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 2 $\frac{1}{4}$  ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 6  
C-W-SE  
1/64  
1954

## BOOK 4452

Subdivision of Section 6, T. 15 S., R. 13 E.

Chains

40.338

The C-S 1/16 sec. cor. of sec. 6.

Subdivision of the SW $\frac{1}{4}$ .

From the W 1/16 sec. cor. of secs. 6 and 7:

N. 0° 31' W.; on the N. and S. center line of the SW $\frac{1}{4}$  of sec. 6.

Ascend 35 ft. over S. slope.

1.75 Top of ascent; desc. 63 ft. over N. slope.

5.85 Wash, 15 lks. wide, 2 ft. deep, drains SW.; asc. 30 ft. over S. slope.

9.936 Point for the C-S-SW 1/64 sec. cor. of sec. 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 3 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd:

S 6  
C-S-SW  
1/64  
1954

10.35 Top of ascent; desc. 100 ft. over N. slope.

19.872 Point for the SW 1/16 sec. cor. of sec. 6, at the intersection of the E. and W. center line of the SW $\frac{1}{4}$  of sec. 6.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

SW 1/16 S 6  
1954

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

20.00 Thence over rolling land.

22.35 Wash, 20 lks. wide, 2 ft. deep, drains WNW.

39.754 The C-W 1/16 sec. cor. of sec. 6.

From the C-S 1/16 sec. cor. of sec. 6.

S. 89° 35' W., on the E. and W. center line of the SW $\frac{1}{4}$  of sec. 6.

Over broken land.

5.65 Old road, bears NW. and SE.

10.08 Point for the C-E-SW 1/64 sec. cor. of sec. 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 6  
C-E-SW  
1/64  
1954

20.16 The SW 1/16 sec. cor. of sec. 6.

30.242 Point for the C-W-SW 1/64 sec. cor. of sec. 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

## Subdivision of Section 6, T. 15 S., R. 13 E.

Chains

S 6  
C-W-SW  
1/64  
1954

39.956 The S 1/16 sec. cor. of sec. 6, on the W. bdy. of the Tp., which is monumented with an iron post, 2½ ins. diam., set and marked as described in the 1953 resurvey record of sec. 1, T. 15 S., R. 12 E.

## Subdivision of Section 7, T. 15 S., R. 13 E.

From the ¼ sec. cor. of secs. 7 and 18.

N. 0° 53' E., on the N. and S. center line of sec. 7.

Over rolling and broken land.

10.036 Point for the C-S-S 1/64 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

C  
S-S 1/64 | S 7  
C  
1954

20.072 Point for the C-S 1/16 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

C  
S 1/16 | S 7  
C  
1954

30.108 Point for the C-N-S 1/64 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, over a deposit of broken glass, with brass cap mkd.

C  
N-S 1/64 | S 7  
C  
1954

40.144 Point for the C ¼ sec. cor. of sec. 7, at the intersection of the E. and W. center line of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

C ¼ S 7  
1954

40.35 Bladed road, (W. end) bears E.

46.10 Wash, 10 lks. wide, 2 ft. deep, drains E.

50.10 Bladed road, (W. end) bears E.

## BOOK 4452

Subdivision of Section 7, T. 15 S., R. 12 E.

## Chains

- 60.313 Point for the C-N  $1/16$  sec. cor. of sec. 7.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.
- $$\begin{array}{c} C \\ | \\ N\ 1/16 \quad | \quad S\ 7 \\ | \\ C \\ 1954 \end{array}$$
- 66.50 Old road, bears E. and W.
- 67.90 Wash, 10 lks. wide, 4 ft. deep, drains SE.
- 70.398 Point for the C-N-N  $1/64$  sec. cor. of sec. 7.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
- $$\begin{array}{c} C \\ | \\ N-N\ 1/64 \quad | \quad S\ 7 \\ | \\ C \\ 1954 \end{array}$$
- 72.85 Wash, 10 lks. wide, 3 ft. deep, drains E.
- 80.483 The  $\frac{1}{4}$  sec. cor. of secs. 6 and 7.  
Land, broken and rolling.  
Soil, sandy and rocky.  
No timber; undergrowth, mesquite, paloverde and cacti.
- From the  $\frac{1}{4}$  sec. cor. of secs. 7 and 8.  
N.  $89^{\circ} 59'$  W., on the E. and W. center line of sec. 7.  
Over rolling land, along S. side of road.
- 9.973 Point for the C-E-E  $1/64$  sec. cor. of sec. 7.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
- $$\begin{array}{c} E-E\ 1/64 \\ \hline C \quad \quad \quad C \\ S\ 7 \\ 1954 \end{array}$$
- 11.35 Wash, 12 lks. wide, 2 ft. deep, drains SE.
- 13.45 Wash, 12 lks. wide, 2 ft. deep, drains SE.
- 19.946 Point for the C-E  $1/16$  sec. cor. of sec. 7.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
- $$\begin{array}{c} E\ 1/16 \\ \hline C \quad \quad \quad C \\ S\ 7 \\ 1954 \end{array}$$
- 29.919 Point for the C-W-E  $1/64$  sec. cor. of sec. 7.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Subdivision of Section 7, T. 15 S., R. 13 E.

Chains	
	<p style="text-align: center;"> <math display="block">\begin{array}{c} \text{W-E } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 7 \\ 1954 \end{array}</math> </p>
39.892	The C $\frac{1}{4}$ sec. cor. of sec. 7.
60.093	Point for the C-W $1/16$ sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
	<p style="text-align: center;"> <math display="block">\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 7 \\ 1954 \end{array}</math> </p>
67.65	Wash, 8 lks. wide, .1 ft. deep, drains NW.
80.022	<p>The <math>\frac{1}{4}</math> sec. cor. of sec. 7, which is monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., set, marked and witnessed as described in the 1953 resurvey record of sec. 12, T. 15 S., R. 12 E.</p> <p>Land, rolling and hilly. Soil, sandy and rocky. No timber; undergrowth, greasewood, mesquite, paloverde and cacti.</p>
Subdivision of the NE $\frac{1}{4}$ .	
From the C-E $1/16$ sec. cor. of sec. 7, on a bearing of N. $1^{\circ} 18'$ E., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 7.	
Over rolling land.	
0.30	Bladed road, bears E. and W.
8.55	Wash, 15 lks. wide, 2 ft. deep, drains SE.
10.118	Point for the C-S-NE $1/64$ sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 7 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
	<p style="text-align: center;"> <math display="block">\begin{array}{c} \text{S } 7 \\ \text{C-S-NE} \\ 1/64 \\ 1954 \end{array}</math> </p>
16.85	Old road, bears NW. and SE.
20.236	Point for the NE $1/16$ sec. cor. of sec. 7, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$ of sec. 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
	<p style="text-align: center;"> <math display="block">\begin{array}{c} \text{NE } 1/16 \text{ S } 7 \\ 1954 \end{array}</math> </p>
25.15	Bladed road, bears E. and W.
30.355	Point for the C-N-NE $1/64$ sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

## BOOK 4452

## Subdivision of Section 7, T. 15 S., R. 13 E.

## Chains

- S 7  
C-N-NE  
1/64  
1954
- 40.474 The E 1/16 sec. cor. of secs. 6 and 7.
- 
- From the N 1/16 sec. cor. of secs. 7 and 8.  
S. 89° 48' W., on the E. and W. center line of the NE 1/4 of sec. 7.  
Over rolling land.
- 10.035 Point for the C-E-NE 1/64 sec. cor. of sec. 7.  
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- S 7  
C-E-NE  
1/64  
1954
- 12.60 Road, bears N. and S.
- 15.60 Road, bears NE. and SW.
- 20.07 The NE 1/16 sec. cor. of sec. 7, at the intersection of the
- 25.30 Old road, bears N. and S.
- 31.10 Wash, 10 lks. wide, 2 ft. deep, drains SE.
- 35.30 Bladed road, bears N. and S.
- 39.20 Old road, bears NW. and SE.
- 40.145 The C-N 1/16 sec. cor. of sec. 7.

## Subdivision of the NW 1/4.

- From the C-W 1/16 sec. cor. of sec. 7.  
N. 0° 55' E., on the N. and S. center line of the NW 1/4 of sec. 7.  
Ascend 200 ft. over steep S. slope.
- 10.00 Top of ascent; descend 235 ft. over steep N. slope.
- 20.093 Point for the NW 1/16 sec. cor. of sec. 7, at the intersection of the E. and W. center line of the NW 1/4 of sec. 7.  
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- NW 1/16 S 7  
1954
- Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  
Thence over rolling and broken land.
- 27.90 Old road, bears E. and W.
- 30.143 Point for the C-N-NW 1/64 sec. cor. of sec. 7.  
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

## Subdivision of Section 7, T. 15 S., R. 13 E.

Chains

S 7  
C-N-NW  
1/64  
1954

31.60 Wash, 10 lks. wide, 1 ft. deep, drains WSW.

35.00 Ascend 55 ft. over S. slope.

40.193 The W 1/16 sec. cor. of secs. 6 and 7.

From the C-N 1/16 sec. cor. of sec. 7.

S. 89° 49' W., on the E. and W. center line of the NW $\frac{1}{4}$  of sec. 7.

Ascend 100 ft. over E. slope.

10.099 Point for the C-E-NW 1/64 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

S 7  
C-E-NW  
1/64  
1954

11.00 Top of ascent; descend 100 ft. over W. slope.

20.198 The NW 1/16 sec. cor. of sec. 7.

28.05 Wash, 12 lks. wide, 2 ft. deep, drains WSW. Thence over rolling land.

30.302 Point for the C-W-NW 1/64 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S 7  
C-W-NW  
1/64  
1954

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

40.108 The N 1/16 sec. cor. of sec. 7, on the W. bdy. of the Tp., which is monumented with an iron post, 2 $\frac{1}{2}$  ins. diam., set, marked and witnessed as described in the 1953 resurvey record of sec. 12, T. 15 S., R. 12 E.Subdivision of the SE $\frac{1}{4}$ .

From the E 1/16 sec. cor. of secs. 7 and 18.

N. 0° 44' E., on the N. and S. center line of the SE $\frac{1}{4}$  of sec. 7.

Over gently rolling land.

10.029 Point for the C-S-SE 1/64 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

S 7  
C-S-SE  
1/64  
1954



## BOOK 4452

## Subdivision of Section 7, T. 15 S., R. 13 E.

Chains	
11.10	Wash, 10 lks. wide, 1 ft. deep, drains ENE.
15.80	Wash, 10 lks. wide, 3 ft. deep, drains ESE.
18.30	Wash, 15 lks. wide, 2 ft. deep, drains ESE.
20.058	Point for the SE 1/16 sec. cor. of sec. 7, at the intersection of the E. and W. center line of the SE 1/4 of sec. 7.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.  SE 1/16 S 7  1954
29.605	Intersect the S. bdy. of the Margarita lode. (Unsurveyed)  Set a 1 in. T-iron stake, 24 ins. long, 18 ins. in the ground, with cap mkd. PI.  From point of intersection AP No. 2 of the Margarita lode, bears S. 85° 45' E., 8.511 chs. dist.  From the same point AP No. 3 of the Margarita lode, bears N. 85° 45' W., 13.348 chs. dist.
30.088	Point for the C-N-SE 1/64 sec. cor. of sec. 7.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  S 7 C-N-SE 1/64 1954
38.715	Intersect the N. bdy. of the Margarita lode. (Unsurveyed)  Set a 1 in. T-iron stake, 24 ins. long, 18 ins. in the ground, with cap mkd. PI.  From point of intersection AP No. 4 of the Margarita lode, bears N. 85° 45' W., 12.788 chs. dist.  From the same point AP No. 1 of the Margarita lode, bears S. 85° 45' E., 9.063 chs. dist.
40.118	The C-E 1/16 sec. cor. of sec. 7.  From the S 1/16 sec. cor. of secs. 7 and 8.  S. 89° 58' W., on the E. and W. center line of the SE 1/4 of sec. 7.  Over rolling land.
4.00	Wash, 10 lks. wide, 1 ft. deep, drains SE.
10.002	Point for the C-E-SE 1/64 sec. cor. of sec. 7.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  S 7 C-E-SE 1/64 1954
20.004	The SE 1/16 sec. cor. of sec. 7.

## Subdivision of Section 7, T. 15 S., R. 13 E.

Chains  
30.007

Point the C-W-SE 1/64 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd.

S 7  
C-W-SE  
1/64  
1954

40.01

The C-S 1/16 sec. cor. of sec. 7.

Segregation Survey of the Margarita Lode in Sec. 7, T. 15 S., R. 13 E.

At the location monument, which is a mound of stone, 4 ft. base, 3 ft. high, pointed out by the claimant Cipriano Ortiz, Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd.

M  
AP 1

1954

Raise a mound of stone, 3 ft. base, 2 ft. high, SW. of AP..

Thence

S. 4° 17' W., along the E. end line.

Over rolling land.

9.091 Angle point No. 2.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd.

M  
AP 2

1954

From this point the location monument, which is a mound of stone, 4 ft. base, 3 ft. high, (pointed out by the claimant Cipriano Ortiz) bears S. 48° 50' E., 3 lks. dist.

Thence

N. 85° 45' W., along the S. side line.

Over rolling land.

8.511 Intersect the E 1/16 line of sec. 7.

21.859

The location monument, which is a mound of stone, 4 ft. base, 3 ft. high, pointed out by the claimant. Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground, with brass cap mkd.

M  
AP 3




1954

Raise a mound of stone, 3 ft. base, 2 ft. high, NE. of AP.

Thence

N. 4° 17' E., on the W. end line.

## Segregation Survey of the Margarita Lode in Sec. 7, T. 15 S., R. 13 E.

Chains	Ascend 60 ft. over rocky S. slope.
3.15	Top of ascent; descend 60 ft. over rocky N. slope.
9.091	Angle point No. 4. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	
	From this angle point the location monument, which is a mound of stone, 4 ft. base, 3 ft. high, pointed out by the claimant, bears N. $85^{\circ} 39'$ W., 5 lks. dist.
	From this same point the $\frac{1}{4}$ sec. cor. of sec. 7, bears N. $86^{\circ} 20'$ W., 7.19 chs. dist.
	Thence
	S. $85^{\circ} 45'$ E.; on the N. side line.
	Over gently rolling land.
12.788	Intersect the E $1/16$ sec. line of sec. 7.
21.851	Angle point No. 1 and point of beginning. From this angle point the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, bears N. $79^{\circ} 16'$ E., 11.11 chs. dist.
Subdivision of Section 18, T. 15 S., R. 13 E.	
	From the $\frac{1}{4}$ sec. cor. of secs: 18 and 19.
	N. $0^{\circ} 17'$ E.; on the N. and S. center line of sec. 18.
	Ascend 200 ft. Over steep S. slope.
8.00	Top of ascent; descend 220 ft. over a N. and NW. slope.
10.06	Point for the C-S-S $1/64$ sec. cor. of sec. 18. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
	
20.12	Point for the C-S $1/16$ sec. cor. of sec. 18. Set an iron post, 28 ins. long, $2\frac{3}{4}$ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
	
40.24	Point for the C $1/4$ sec. cor. of sec. 18, at the intersection of the E. and W. center line of sec. 18.

## Subdivision of Section 18, T. 15 S., R. 13 E.

Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

C  $\frac{1}{4}$  S 18

1954

Thence over gently rolling land.

48.25 Road, bears ENE. and WSW.

50.30 Point for the C-S-N  $1/64$  sec. cor. of sec. 18.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

C  
S-N  $1/64$  | S 18

C  
1954

60.36 Point for the C-N  $1/16$  sec. cor. of sec. 18.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

C  
N  $1/16$  | S 18

C  
1954

61.65 El Paso Natural Gas line, bears N.  $75^{\circ} 30'$  W. and S.  $75^{\circ} 30'$  E.

70.42 Point for the C-N-N  $1/64$  sec. cor. of sec. 18.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground over a deposit of broken glass, with brass cap mkd.

C  
N-N  $1/64$  | S 18

C  
1954

70.80 Wash, 7 lks. wide, 3 ft. deep, drains E.

79.10 Wash, 10 lks. wide, 4 ft. deep, drains SE.

80.48 The  $\frac{1}{4}$  sec. cor. of secs. 7 and 18.

Land, rolling and hilly.

Soil, sandy and rocky.

No timber; undergrowth, greasewood, mesquite, paloverde and cacti.

From the  $\frac{1}{4}$  sec. cor. of secs. 17 and 18.

S.  $89^{\circ} 39'$  W., on the E. and W. center line of sec. 18.

Over gently rolling land, through undergrowth.

10.06 Point for the C-E-E  $1/64$  sec. cor. of sec. 18.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

## Subdivision of Section 18, T. 15 S., R. 13 E.

Chains	
	$\begin{array}{c} \text{E-E } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 18 \\ 1954 \end{array}$
20.12	<p>Point for the C-E 1/16 sec. cor. of sec. 18 .</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 18 \\ 1954 \end{array}$
30.18	<p>Point for the C-W-E 1/64 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} \text{W-E } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 18 \\ 1954 \end{array}$
40.24	The C $\frac{1}{4}$ sec. cor. of sec. 18.
50.305	<p>Point for the C-E-W 1/64 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} \text{E-W } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 18 \\ 1954 \end{array}$
60.37	<p>Point for the C-W 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 18 \\ 1954 \end{array}$
62.45	Road, bears ENE. and WSW.
64.75	Wash, 8 lks. wide, 2 ft. deep, drains W.
70.435	<p>Point for the C-W-W 1/64 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
	$\begin{array}{c} \text{W-W } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 18 \\ 1954 \end{array}$
80.264	<p>The <math>\frac{1}{4}</math> sec. cor. of sec. 18, on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, sandy. No timber; undergrowth, greasewood, mesquite and cacti.</p>

## Subdivision of Section 18, T. 15 S., R. 13 E.

Chains

Subdivision of the NE $\frac{1}{4}$ .

From the C-E 1/16 sec. cor. of sec. 18.

N. 0° 11' E., on the N. and S. center line of the NE $\frac{1}{4}$  of sec. 18.

Over rolling land, through undergrowth.

10.034 Point for the C-S-NE 1/64 sec. cor. of sec. 18.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.S 18  
C-S-NE  
1/64  
1954

13.85 Road, bears ENE. and WSW.

16.12 El Paso Natural Gas line, bears N. 75° 30' W. and S. 75° 30' E.

20.068 Point for the NE 1/16 sec. cor. of sec. 18, at the intersection of the E. and W. center line of the NE $\frac{1}{4}$  of sec. 18.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

NE 1/16 S 18

1954

21.80 Wash, 10 lks. wide, 1 ft. deep, drains E.

30.103 Point for the C-N-NE 1/64 sec. cor. of sec. 18.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.S 18  
C-N-NE  
1/64  
1954

34.40 Old road, bears NE. and SW.

40.138 The E 1/16 sec. cor. of secs. 7 and 18.

From the N 1/16 sec. cor. of secs. 17 and 18.

S. 89° 48' W., on the E. and W. center line of the NE $\frac{1}{4}$  of sec. 18.

Over rolling land, through undergrowth.

10.042 Point for the C-E-NE 1/64 sec. cor. of sec. 18.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.S 18  
C-E-NE  
1/64  
1954

20.084 The NE 1/16 sec. cor. of sec. 18.

22.90 Wash, 8 lks. wide, 2 ft. deep, drains E.

30.128 Point for the C-W-NE 1/64 sec. cor. of sec. 18.

## BOOK 4452

## Subdivision of Section 18, T. 15 S., R. 13 E.

<p>Chains</p> <p>35.40</p> <p>40.172</p>	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p> <p style="text-align: center;">S 18 C-W-NE 1/64 1954</p> <p>El Paso Natural Gas line, bears N. 75° 30' W. and S. 75° 30' E.</p> <p>The C-N 1/16 sec. cor. of sec. 18.</p>
Subdivision of the NW $\frac{1}{4}$ .	
<p>.80</p> <p>10.082</p>	<p>From the C-W 1/16 sec. cor. of sec, 18.</p> <p>N. 0° 22' E., on the N. and S. center line of the NW<math>\frac{1}{4}</math> of sec. 18.</p> <p>Over gently rolling land.</p> <p>Road, bears E. and W.</p> <p>Point for the C-S-NW 1/64 sec. cor. of sec. 18.</p>
<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>	
<p>20.164</p>	<p style="text-align: center;">S 18 C-S-NW 1/64 1954</p> <p>Point for the NW 1/16 sec. cor. of sec. 18, at the intersection of the E. and W. center line of the NW<math>\frac{1}{4}</math> of sec. 18.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>
NW 1/16 S 18	
1954	
<p>26.66</p>	<p>El Paso Natural Gas line, bears N. 75° 30' W. and S. 75° 30' E.</p>
<p>30.25</p>	<p>Point for the C-N-NW 1/64 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
S 18	
C-N-NW	
1/64	
1954	
Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.	
<p>40.336</p>	<p>The W 1/16 sec. cor. of secs. 7 and 18.</p>
From the C-N 1/16 sec. cor. of sec. 18.	
S. 89° 47' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 18.	
Over gently rolling land.	
<p>10.047</p>	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.</p>

## Subdivision of Section 18, T. 15 S., R. 13 E.

Chains

S 18  
C-E-NW  
1/64  
1954

12.55 Old road, bears NW. and SE.

20.094 The NW 1/16 sec. cor. of sec. 18.

30.141 Point for the C-W-NW 1/64 sec. cor. of sec. 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground,  
over a deposit of broken glass, with brass cap mkd.

S 18  
C-W-NW  
1/64  
1954

39.958 The N 1/16 sec. cor. of sec. 18., on the W. bdy. of the Tp.

## Subdivision of the SW¼.

From the W 1/16 sec. cor. of secs. 18 and 19.

N. 0° 21' E., on the N. and S. center line of the SW¼ of sec. 18.

Over nearly level land.

10.081 Point for the C-S-SW 1/64 sec. cor. of sec. 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground,  
over a deposit of broken glass, with brass cap mkd.

S 18  
C-S-SW  
1/64  
1954

20.162 Point for the SW 1/16 sec. cor. of sec. 18, at the intersection of the E. and W. center line of the SW¼ of sec. 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground,  
over a deposit of broken glass, with brass cap mkd.

SW 1/16 S 18

1954

40.328 The C-W 1/16 sec. cor. of sec. 18.

From the C-S 1/16 sec. cor. of sec. 18.

S. 89° 31' W., on the E. and W. center line of the SW¼ of sec. 18.

Descend 80 ft. over rocky W. slope.

10.00 Foot of descent; thence over gently rolling land.

10.08 Point for the C-E-SW 1/64 sec. cor. of sec. 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 2¼ ins. in the ground,  
with brass cap mkd.

S 18  
C-E-SW  
1/64  
1954



## Subdivision of Section 18, T. 15 S., R. 13 E.

Chains

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor..

20.16 The SW  $1/16$  sec. cor. of sec. 18.30.241 Point for the C-W-SW  $1/64$  sec. cor. of sec. 18.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

S 18  
C-W-SW  
 $1/64$   
1954

40.077 The S  $1/16$  sec. cor. of sec. 18, on the W. bdy. of the Tp.

## Subdivision of Section 19, T. 15 S., R. 13 E.

From the  $\frac{1}{4}$  sec. cor. of secs. 19 and 30.N.  $0^{\circ} 03'$  E., on the N. and S. center line of sec. 19.

Over nearly level land, along and near W. side of road.

9.914 Point for the C-S-S  $1/64$  sec. cor. of sec. 19.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

C  
S-S  $1/64$  | S 19  
C  
1954

19.828 Point for the C-S  $1/16$  sec. cor. of sec. 19.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

O  
S  $1/16$  | S 19  
C  
1954

29.742 Point for the C-N-S  $1/64$  sec. cor. of sec. 19.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

C  
N-S  $1/64$  | S 19  
C  
1954

39.40 Fall 25 lks. W. of intersection of roads, bears S. and E.

39.656 Point for the C  $\frac{1}{4}$  sec. cor. of sec. 19, at the intersection of the E. and W. center line of sec. 19.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass; with brass cap mkd.

C  $\frac{1}{4}$  S 19  
1954

## Subdivision of Section 19, T. 15 S., R. 13 E.

Chains

49.742 Point for the C-S-N 1/64 sec. cor. of sec. 19.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \text{C} \\ | \\ \text{S-N } 1/64 \quad | \quad \text{S } 19 \\ | \\ \text{C} \\ 1954 \end{array}$$

52.05 Road, bears NE. and SW.

59.828 Point for the C-N 1/16 sec. cor. of sec. 19.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \text{C} \\ | \\ \text{N-1/16} \quad | \quad \text{S } 19 \\ | \\ \text{C} \\ 1954 \end{array}$$

61.90 Road, bears E. and W.

69.914 Point for the C-N-N 1/64 sec. cor. of sec. 19.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground; over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \text{C} \\ | \\ \text{N-N } 1/64 \quad | \quad \text{S } 19 \\ | \\ \text{C} \\ 1954 \end{array}$$
80.00 The  $\frac{1}{4}$  sec. cor. of secs. 18 and 19.

Land, nearly level.

Soil, sandy.

No timber; undergrowth, greasewood, mesquite and cacti.

From the  $\frac{1}{4}$  sec. cor. of secs. 19 and 20.S.  $89^{\circ} 11'$  W., on the E. and W. center line of sec. 19.

Over nearly level land, along N. side of road.

2.40 Wash, 5 lks. wide, 1 ft. deep, drains SE.

10.022 Point for the C-E-E 1/64 sec. cor. of sec. 19.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

$$\begin{array}{c} \text{E-E } 1/64 \\ \text{C} \quad \text{---} \quad \text{C} \\ | \\ \text{S } 19 \\ | \\ \text{C} \\ 1954 \end{array}$$

17.00 Wash, 5 lks. wide, 1 ft. deep, drains NE.

20.044 Point for the C-E 1/16 sec. cor. of sec. 19.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

## Subdivision of Section 19, T. 15 S., R. 13 E.

Chains	
	$\begin{array}{c} \text{E } 1/16 \\ \hline \text{C} \quad \text{C} \\ \text{S } 19 \\ 1954 \end{array}$
30.066	Point for the C-W-E 1/64 sec. cor. of sec. 19. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{c} \text{C } \text{W-E } 1/64 \text{ C} \\ \hline \text{S } 19 \\ 1954 \end{array}$
39.85	Fall 25 lks. N. of intersection of roads, bears S. and E.
40.088	The C ¼ sec. cor. of sec. 19.
50.23	Point for the C-E-W 1/64 sec. cor. of sec. 19. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{c} \text{C } \text{E-W } 1/64 \text{ C} \\ \hline \text{S } 19 \\ 1954 \end{array}$
60.372	Point for the C-W 1/16 sec. cor. of sec. 19. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{c} \text{C } \text{W } 1/16 \text{ C} \\ \hline \text{S } 19 \\ 1954 \end{array}$
70.514	Point for the C-W-W 1/64 sec. cor. of sec. 19. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.
	$\begin{array}{c} \text{C } \text{W-W } 1/64 \text{ C} \\ \hline \text{S } 19 \\ 1954 \end{array}$
80.479	The ¼ sec. cor. of sec. 19, on the W. bdy. of the Tp. Land, nearly level. Soil, sandy. No timber; undergrowth, greasewood, mesquite and cacti.
Subdivision of the NE ¼	
	From the C-E 1/16 sec. cor. of sec. 19.
	N. 0° 15' E., on the N. and S. center line of the NE ¼ of sec. 19.
	Over gently rolling land.
1.10	Wash, 10 lks. wide, 2 ft. deep, drains SE.
10.069	Point for the C-S-NE 1/64 sec. cor. of sec. 19. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.

Subdivision of Section 19, T. 15 S., R. 13 E.

Chains		meters
	S. 19 C-S-NE 1/64 1954	
20.00	Old road, bears E. and W.	880.00
20.138	Point for the NE 1/16 sec. cor. of sec. 19, at the intersection of the E. and W. center line of the NE 1/4 of sec. 19.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.  NE 1/16 S 19  1954	880.00
30.209	Point for the C-N-NE 1/64 sec. cor. of sec. 19.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.  S 19 C-N-NE 1/64 1954	880.00
	Ascend 80 ft. over S. slope.	
40.28	The E 1/16 sec. cor. of secs. 18 and 19.  From the N 1/16 sec. cor. of secs. 19 and 20.  S. 89° 17' W., on the E. and W. center line of the NE 1/4 of sec. 19  Over gently rolling land.	880.00
5.25	Wash, 7 lks. wide, 2 ft. deep, drains SE.	
10.058	Point for the C-E-NE 1/64 sec. cor. of sec. 19.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 19 C-E-NE 1/64 1954	880.00
19.25	Road, bears ESE. and WNW.	
20.116	The NE 1/16 sec. cor. of sec. 19.	
30.175	Point for the C-W-NE 1/64 sec. cor. of sec. 19.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.  S 19 C-W-NE 1/64 1954	
32.75	Road, bears ESE. and WSW.	
36.75	Road, bears NE. and SW.	
40.234	The C-N 1/16 sec. cor. of sec. 19.  Subdivision of the NW 1/4  From the C-W 1/16 sec. cor. of sec. 19.	

## Subdivision of Section 19, T. 15 S., R. 13 E.

Chains	N. 0° 14' E., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 19. Over nearly level land.
10.099	Point for the C-S-NW 1/64 sec. cor. of sec. 19. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 19 C-S-NW 1/64 1954
19.80	Old road, bears NW. and SE.
20.198	Point for the NW 1/16 sec. cor. of sec. 19, at the intersection of the E. and W. center line of the NW $\frac{1}{4}$ of sec. 19. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  NW 1/16 S 19  1954
40.393	The W 1/16 sec. cor. of secs. 18 and 19.  From the C-N 1/16 sec. cor. of sec. 19. S. 89° 17' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 19. Over nearly level land.
1.25	Wash, 5 lks. wide, 2 ft. deep, drains S.
10.12	Point for the C-E-NW 1/64 sec. cor. of sec. 19. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 19 C-E-NW 1/64 1954
20.24	The NW 1/16 sec. cor. of sec. 19.
21.00	Old road, bears NW. and SE.
30.358	Point for the C-W-NW 1/64 sec. cor. of sec. 19. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 19 C-W-NW 1/64 1954
40.26	The N 1/16 sec. cor. of sec. 19, on the W. bdy. of the Tp.  Subdivision of the SW $\frac{1}{4}$ . From the W. 1/16 sec. cor. of secs. 19 and 30. N. 0° 15' E., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 19 Over nearly level land.

## Subdivision of Section 19, T. 15 S., R. 13 E.

Chains 10.00	Point for the C-S-SW $1/64$ sec. cor. of sec. 19.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 19 C-S-SW $1/64$ 1954
20.00	Point for the SW $1/16$ sec. cor. of sec. 19, at the intersection of the E. and W. center line of the SW $1/4$ of sec. 19.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, over a deposit of broken glass; with brass cap mkd.  SW $1/16$ S 19  1954
30.012	Point for the C-N-SW $1/64$ sec. cor. of sec. 19.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 19 C-N-SW $1/64$ 1954
40.024	The C-W $1/16$ sec. cor. of sec. 19.  From the C-S $1/16$ sec. cor. of sec. 19.  S. $88^{\circ}$ 41' W., on the E. and W. center line of the SW $1/4$ of sec. 19.  Over nearly level land.
10.178	Point for the C-E-SW $1/64$ sec. cor. of sec. 19.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 19 C-E-SW $1/64$ 1954
20.356	The SW $1/16$ sec. cor. of sec. 19.
22.25	Wash, 6 lks. wide, 1 ft. deep, drains NE.
30.52	Point for the C-W-SW $1/64$ sec. cor. of sec. 19.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, over a deposit of broken glass, with brass cap mkd.  S 19 C-W-SW $1/64$ 1954
40.543	The S $1/16$ sec. cor. of sec. 19, on the W. bdy. of the Tp.

## BOOK 4452

## General Description

The greater portion of sections 6, 7 and 18 is rolling and hilly; section 19 is nearly level. The soil is a sandy loam except in the hilly portions which is a rocky clay. The sections are covered with an undergrowth of greasewood, mesquite, paloverde and cacti. The general drainage is to the south and east except the north portion of section 6 which is to the northwest. The El Paso Natural Gas line enters section 18 on the east boundary approximately 10.00 chs. north of the  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, and leaves the section on west boundary of the NW $\frac{1}{4}$ . The Margarita mining claim is located in the NE $\frac{1}{4}$  of sec. 7.

4-690  
(Feb., 1950)

BOOK 4452

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Stephen Schmidt, Jr.	Cartographer (Cadastral)
Jesse A. Livesay	Cartographic Survey Aid
Robert D. Stevens	" "
Adan Lovato	Surveying and Cartographic Aid
Deciderio Baca	" "



39

BOOK 4452

### CERTIFICATE OF CADASTRAL ENGINEER

I, Clarence E. Bilbray, ~~HEREBY~~ CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th ~~9th~~ day of December ~~January~~, 1953, 1953,

I have ~~surveyed~~ ~~independently~~ resurveyed a portion of the west boundary and portion of the subdivision, and surveyed the subdivisional lines of sections 6, 7, 18, and 19, and segregation survey of the Margarita Mineral Claim in section 7, Township 15 South, Range 13 East.

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Albuquerque, New Mexico

June 1, 1954

*Clarence E. Bilbray*  
Clarence E. Bilbray  
Cartographer (Cadastral)

### CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., AUG 30 1955, 19

The foregoing field notes of the ~~survey of~~ ~~dependent~~ resurvey of a portion of the west boundary and portion of the subdivision, and survey of the subdivisional lines of sections 6, 7, 18, and 19, and segregation survey of the Margarita Mineral Claim in sec. 7, Township 15 South, Range 13 East of the Gila and Salt River Meridian, Arizona.

executed by Clarence E. Bilbray

having been critically examined and found correct, are hereby approved.

*Earl G. Harrington*  
Chief, Division of Cadastral Engineering  
Cadastral Engineering Staff Officer

### ~~CERTIFICATE OF TRANSCRIPT~~

~~Whereby that the foregoing transcript of the field notes of the above-described surveys in~~

is a true copy of the original field notes.

~~Chief, Division of Cadastral Engineering~~