

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

BOOK 4467

Original

# FIELD NOTES

of the Survey of

Partial Subdivision

of

Township 40 North, Range 3 West

Of the Gila and Salt River Meridian,

In the State of Arizona

### EXECUTED BY

Donald E. Harding - Cadastral Engineer

Under special instructions dated August 16, 1954, which provided  
for the surveys included under Group No. 294, approved August 20, 1954  
and assignment instructions dated October 4, 1954.

Survey commenced October 27, 1954

Survey completed October 27, 1954

4467

4467

4467

BOOK 4467

# INDEX DIAGRAM

Township 40 North, Range 3 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	2 1 32	1 33	34	35	36

Partial Subdivision of T. 40 N., R. 3 W.

Chains

The north, south, and west boundaries were surveyed by J. C. Thoma in 1914. The east boundary was provided for under the survey of T. 40 N., R. 2 W.

For the test of the instruments and methods used see notes for the survey of T. 40 N., R. 1 W.

The geographic position of the southeast corner of T. 40 N., R. 3 W. is latitude 36°49'00" N., longitude 112°33'59" W. The magnetic declination is 16°00' E.


From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the township, set and marked as described in the official record.

N. 0° 02' W., bet. secs. 32 and 33.

Over rolling land, through scattered sagebrush and sparse grass.

40.00 Point for the 1/4 sec. cor. of secs. 32 and 33.


Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

80.00 Point for the cor. of secs. 28, 29, 32, and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

Land, low and rolling.

Soil, sandy clay.

Timber, none.

Undergrowth, sagebrush and sparse grass.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the township, set and marked as described in the official record.

N. 0° 03' W., bet. secs. 31 and 32.

Over low rolling land, through scattered sagebrush and sparse grass.

Desc. 46 ft. over N. slope.

5.00 Wash, 30 lks. wide, 3 ft. deep, course W.; asc. 45 ft. over S. slope.

37.00 Small wash, course SW.

Partial Subdivision of T. 40 N., R. 3 W.

Chains

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 32.  
 Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
 S 31 | S 32  
 1954

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

43.35 Small wash, course SW.

80.00 Point for the cor. of secs. 29, 30, 31, and 32.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T40NR3W  
 S30 | S29  
 S31 | S32  
 1954

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.  
 Soil, sandy clay.  
 Timber, none.  
 Undergrowth, sagebrush and sparse grass.

From the cor. of secs. 28, 29, 32, and 33.

S. 89° 59' W., bet. secs. 29 and 32.

Over low rolling land, through scattered sagebrush and sparse grass.

40.06 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 32.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S. 29  
 —————  
 S 32  
 1954

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of cor.

40.30 Road, track, bears N. and S.

80.12 The cor. of secs. 29, 30, 31, and 32.

Land, low and rolling.  
 Soil, sandy clay.  
 Timber, none.  
 Undergrowth, sagebrush and sparse grass.

## Partial Subdivision of T. 40 N., R. 3 W.

## General Description

The soil in T. 40 N., R. 3 W. is sandy clay, third rate. Portions of the township have fair to good grass. There is no timber in the township. The only permanent water is Kanab Wash which bisects the township from north to south, near the east boundary. No one is living within the township. Its only value is grazing purposes.



CERTIFICATE OF CADASTRAL ENGINEER

BOOK 4461

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of August, 1954, I have surveyed part of the subdivision of T. 40 N., R. 3 W.

of the G & S R Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

June 8, 1955

Donald E. Harding

Donald E. Harding

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., OCT 25 1955, 19

The foregoing field notes of the survey of part of the subdivision of T. 40 N., R. 3 W., G & S R Meridian of Arizona

executed by Donald E. Harding

having been critically examined and found correct, are hereby approved.

George G. Harrington, Chief, Division of Cadastral Engineering, Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above described surveys in is a true copy of the original field notes.

Chief, Division of Cadastral Engineering