

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

# FIELD NOTES

of the

Survey of a Portion of the East Boundary,

Dependent Resurvey of the South Boundary,

and

Survey of a Portion of the Subdivisional Lines

in

Township 6 South, Range 29 East

Of the Gila and Salt River Meridian,

In the State of Arizona

### EXECUTED BY

Horace G. Parker, Cartographer Cadastral

Under special instructions dated November 16, 1954, which provided  
for the surveys included under Group No. 299, approved November 16, 1954  
and assignment instructions dated December 16, 1954

Survey commenced March 2, 1955

Survey completed April 27, 1955

4488

4488

4488

1A

BOOK 4488

# INDEX DIAGRAM

Township 6 South, Range 29 East

|    |    |          |             |          |      |
|----|----|----------|-------------|----------|------|
|    |    |          | 23          | 22       | 21   |
| 6  | 5  | 4        | 17 3        | 21 2     | 20 1 |
| 7  | 8  | 9        | 18<br>16 10 | 19<br>11 | 12 5 |
| 18 | 17 | 24<br>16 | 16 15       | 14       | 13 4 |
| 19 | 20 | 23<br>21 | 15 22       | 23       | 24 3 |
| 30 | 29 | 28       | 14 27       | 26       | 25 2 |
| 31 | 32 | 33       | 13 34       | 35       | 36 1 |
| 12 | 10 | 9        | 8           | 7        | 6    |

Survey of a Portion of the East Boundary, Reestablishment of the Survey of the South Boundary, and Survey of a Portion of the Subdivisional Lines in Township 6 South, Range 29 East.

## Chains

The north boundary, First Standard Parallel South, was surveyed by Philip Contzen in 1895. Portions of this line were resurveyed by W. H. Kimmel in 1914, as represented on the plat of T. 5 S., R. 29 E., approved June 19, 1915. A portion of the east boundary was surveyed by D. Drummond in 1891, as represented on the plat approved September 29, 1891. The south boundary was surveyed by C. E. Hunter in 1933, as represented on the plat approved February 27, 1934.

The following field notes are those of the survey of the east boundary of T. 6 S., R. 29 E., the survey of the south boundary, remarking original corner monuments to function for T. 7 S., R. 29 E. and establishing new corners for T. 6 S., R. 29 E. at regular intervals of departure, and the survey of a portion of the subdivisional lines of T. 6 S., R. 29 E.

The survey was initiated on the official request of the Arizona State Land Department, Phoenix, Arizona.

For the description of instruments and methods of measurement used, refer to the field notes of T. 6 S., R. 28 E., executed under this same group.

The directions of the lines of survey were determined from the azimuth of the U.S.C.&G.S. triangulation station Guthrie and by sustained angulation carried forward and supplemented by altitude observations on the sun for azimuth taken throughout the work.

The geographic position of the southeast corner of the township, computed from a direct tie to the U.S.C.&G.S. triangulation station Guthrie, is latitude  $32^{\circ} 51' 28''$  N., longitude  $109^{\circ} 18' 26''$  W. The observed magnetic declination is  $13^{\circ} 45'$  E.

---

Survey of a Portion of the East Boundary, T. 6 S., R. 29 E.

---

The point for the corner of Ts. 6 S., Rs. 29 and 30 E., established on the north boundary of section 6, T. 7 S., R. 30 E., at a point south of the corner of sections 1, 6, 7 and 12, Ts. 6 S., Rs. 29 and 30 E.

Set an iron post, 36 ins. long, 3 ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 6 S  
R 29 E   R 30 E  
  S 36 | S 31  
T 7 S   R 30 E   S 6  
1955

raise a mound of stone, 5 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

From this corner, the corner originally established for the cor. of Ts. 6 and 7 S., Rs. 29 and 30 E., monumented with an iron post, 3 ins. diam., firmly set in the ground with top of post projecting slightly above the mound of stone, marked and witnessed as described in the official record, bears S.  $89^{\circ} 59'$  W., 2.78 chs. dist. This corner now functions for Ts. 7 S., Rs. 29 and 30 E. only. I remark the monument to read

T 6 S   R 29 E   S 36  
  S 1 | S 6  
R 29 E   R 30 E  
  T 7 S  
  1933  
  1955

## Survey of a Portion of the East Boundary of T. 6 S., R. 29 E.

## Chains

I rebuild the mound of stone around the corner and raise a mound of stone, 5 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

From this same corner, the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., firmly set in the ground, marked and witnessed as described in the official record, bears N.  $89^{\circ} 59'$  E., 36.22 chs. dist.

Thence North, between secs. 31 and 36.

Over mountainous land, through scattering undergrowth; desc. 37 ft. over N. slope.

6.80 Small draw, 5 lks. wide, 1 ft. deep, drains W.; asc. 16 ft. along W. slope.

14.60 Top of ascent, slopes W.; desc. 46 ft. over WNW. slope.

22.80 Enter wash from N., 80 lks. wide, 6 ft. deep, drains SW.

25.48 Leave same wash from NE., 120 lks. wide, 6 ft. deep, drains S.; asc. 351 ft. over ESE. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 5 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$

188

188 S 36 | S 31

1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Continue ascent over mountainous land, through scattering timber and undergrowth; asc. 562 ft. over steep SE. slope.

56.50 Fence, 4 strand barbed wire with steel posts, bears NE. and SW.

56.80 Top of spur from ridge, slopes SW.; desc. 62 ft. over NW. slope.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 6 S

R 29 E R 30 E

S 25 | S 30

S 36 | S 31

1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, mountainous.

Soil, gravelly and rocky, 4th rate.

Timber, scattering juniper.

Undergrowth, ocotillo, catclaw and cacti.

North, between secs. 25 and 30.

Over rough mountainous land, through scattering timber and undergrowth; desc. 210 ft. over WNW. slope.

24.80 Small hillside draw, 10 lks. wide, 2 ft. deep, drains W.

## Survey of a Portion of the East Boundary of T. 6 S., R. 29 E.

## Chains

33.30 Wash, 1 ch. wide, 6 ft. deep, drains SW.; asc. 198 ft. over SE. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 30.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$   
S 25 | S 30  
1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Continue over mountainous land; asc. 728 ft. over steep rocky SE. slope.

62.00 Enter scattering timber.

72.37 Fence, 4 strand barbed wire with steel posts, bears E. and W.

72.80 Top of ridge, bears E. and W.; desc. 211 ft. over steep rocky N. slope.

80.00 Point for the cor. of secs. 19, 24, 25, and 30.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 6 S  
R 29 E | R 30 E  
S 24 | S 19  
S 25 | S 30  
1955

No suitable bearing trees available.

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, rough mountainous.

Soil, gravelly and rocky, 4th rate.

Timber, scattering juniper and oak.

Undergrowth, ocotillo, catclaw, sagebrush and cacti.

North, between secs. 19 and 24.

Over rough mountainous land, through scattering timber and undergrowth; desc. 959 ft. over steep rocky N. slope.

39.00 Wash, 1 ch. wide, 10 ft. deep, drains NW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$   
S 24 | S 19  
1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

No suitable bearing trees available within limits.

## Survey of a Portion of the East Boundary of T. 6 S., R. 29 E.

|        |  |       |  |        |        |      |      |      |      |
|--------|--|-------|--|--------|--------|------|------|------|------|
| Chains | Continue over rough mountainous land, through scattering timber and undergrowth; asc. 46 ft. over S. slope.  |       |  |        |        |      |      |      |      |
| 42.68  | Top of ascent, slopes SW.; continue ascent along W. slope.   |       |  |        |        |      |      |      |      |
| 46.67  | Hillside gulch, drains SW.   |       |  |        |        |      |      |      |      |
| 54.30  | Top of spur from ridge, slopes W.; desc. 398 ft. over N. slope.  |       |  |        |        |      |      |      |      |
| 71.80  | Wash, 30 lks. wide, 6 ft. deep, drains NW.; asc. 11 ft. over SW. slope.  |       |  |        |        |      |      |      |      |
| 76.80  | Top of spur from ridge, slopes W.; desc. 25 ft. over NNE. slope.   |       |  |        |        |      |      |      |      |
| 80.00  | Point for the cor. of secs. 13, 18, 19 and 24.<br>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock; and in a mound of stone to top, with brass cap mkd.                                |       |  |        |        |      |      |      |      |
|        | <table border="1"> <tbody> <tr> <td colspan="2">T 6 S</td> </tr> <tr> <td>R 29 E</td> <td>R 30 E</td> </tr> <tr> <td>S 13</td> <td>S 18</td> </tr> <tr> <td>S 24</td> <td>S 19</td> </tr> </tbody> </table><br>1955      | T 6 S |  | R 29 E | R 30 E | S 13 | S 18 | S 24 | S 19 |
| T 6 S  |  |       |  |        |        |      |      |      |      |
| R 29 E | R 30 E   |       |  |        |        |      |      |      |      |
| S 13   | S 18   |       |  |        |        |      |      |      |      |
| S 24   | S 19   |       |  |        |        |      |      |      |      |
|        | raise a mound of stone, 5 ft. base, 2½ ft. high, W. of corner.<br>Land, rough mountainous.<br>Soil, gravelly and rocky, 4th rate.<br>Timber, scattering juniper.<br>Undergrowth, ocotillo, catalaw, sagebrush and cacti. |       |  |        |        |      |      |      |      |
|        | North, between secs. 13 and 18.<br>Over rough mountainous land, through scattering timber and undergrowth; desc. 135 ft. over steep rocky N. slope.  |       |  |        |        |      |      |      |      |
| 26.80  | Wash, 30 lks. wide, 10 ft. deep, drains W.; asc. 454 ft. over steep rocky SW. slope.   |       |  |        |        |      |      |      |      |
| 27.50  | Top of spur from ridge, slopes N. 20° W.; desc. 275 ft. over NE. slope.  |       |  |        |        |      |      |      |      |
| 40.00  | Point for the ¼ sec. cor. of secs. 13 and 18.<br>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.                                 |       |  |        |        |      |      |      |      |
|        | <table border="1"> <tbody> <tr> <td colspan="2">¼</td> </tr> <tr> <td>S 13</td> <td>S 18</td> </tr> </tbody> </table><br>1955  | ¼     |  | S 13   | S 18   |      |      |      |      |
| ¼      |  |       |  |        |        |      |      |      |      |
| S 13   | S 18   |       |  |        |        |      |      |      |      |
|        | raise a mound of stone, 5 ft. base, 2½ ft. high, W. of corner.<br>Continue over rough mountainous land, through scattering timber and undergrowth; desc. 562 ft. over steep rocky NNE. slope.                            |       |  |        |        |      |      |      |      |
| 80.00  | Point for the cor. of secs. 7, 12, 13 and 18.<br>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.                                 |       |  |        |        |      |      |      |      |

## Survey of a Portion of the East Boundary of T. 6 S., R. 29 E.

Chains

|        |        |
|--------|--------|
| T 6 S  |        |
| R 29 E | R 30 E |
| S 12   | S 7    |
| S 13   | S 18   |
| 1955   |        |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, rough mountainous.

Soil, gravelly and rocky, 4th rate.

Timber, scattering juniper.

Undergrowth, ocotillo, catclaw, sagebrush and cacti.

North, between secs. 7 and 12.

Over rough mountainous land; through scattering timber and undergrowth; desc. 163 ft. over steep rocky NE. slope.

2.80 Fence, 4 strand barbed wire, bears ENE. and WSW.

10.80 Wash, 40 lks. wide, 6 ft. deep, drains NW.; asc. 370 ft. over steep rocky SW. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|               |     |
|---------------|-----|
| $\frac{1}{4}$ |     |
| S 12          | S 7 |
| 1955          |     |

raise a mound of stone, 5 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Continue over rough mountainous land, through scattering timber and undergrowth.

40.30 Top of spur from ridge, slopes NNW.; desc. 277 ft. over steep rocky NE. slope.

55.30 Leave scattering timber.

60.00 Bottom of NE. slope, slope changes to E.; desc. 177 ft. over E. slope.

79.80 The original cor. of secs. 1, 6, 7 and 12, monumented with a volcanic stone, 10x9x7 ins. above ground, firmly set, marked and witnessed as described in the official record. Alongside the old stone

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

|        |        |
|--------|--------|
| T 6 S  |        |
| R 29 E | R 30 E |
| S 1    | S 6    |
| S 12   | S 7    |
| 1955   |        |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, mountainous.

Soil, gravelly and rocky, 4th rate.

Timber, scattering juniper.

Undergrowth, ocotillo, catclaw, cacti, sagebrush and Spanish dagger.

Dependent Resurvey of the South Boundary of T. 6 S., R. 29 E.

## Chains

Although originally surveyed as a common boundary, the corners established by C. E. Hunter, described in the official returns of the 1933 survey, will no longer serve for the corners of sections in T. 6 S., R. 29 E. Therefore, the established corners are altered to refer to sections in T. 7 S., R. 29 E. only, and new corners are established at intervals of 40.00 and 80.00 chains to refer to sections of T. 6 S., R. 29 E. only.

From the corner of Ts. 6 S., Rs. 29 and 30 E., hereinbefore described.

S. 89° 55' W., along the S. bdy. of sec. 36, T. 6 S., R. 29 E.

Over mountainous land, through scattering undergrowth; desc. 240 ft. over rocky W. slope.

2.78 The cor. of Ts. 7 S., Rs. 29 and 30 E., hereinbefore described.

Thence West, continuing measurement.

14.54 Wash, 40 lks. wide, 10 ft. deep, drains S. 30° W. Thence along S. slope.

18.00 Wash, 5 lks. wide, 1 ft. deep, drains SE.; asc. 218 ft. over general E. slope.

28.72 Wash, 20 lks. wide, 4 ft. deep, drains SE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 36.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S 36

1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

No suitable bearing trees available.

42.78 The original corner established for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set in the ground, marked and witnessed as described in the official record. This corner now functions as the  $\frac{1}{4}$  sec. cor. of sec. 1 only. I alter the markings on the corner monument to read

$\frac{1}{4}$  S 1

1933  
1955

rebuild the mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

Continue ascent, asc. 398 ft. over precipitous E. slope.

47.20 Top of cliff, approximately 100 ft. high, edge bears S. 70° E. and N. 70° W. Continue ascent, asc. 121 ft. over SE. slope. Enter scattering timber.

66.50 Top of rocky spur from ridge, slopes S.; desc. 174 ft. along base of cliff over SW. slope.



## Independent Resurvey of the South Boundary of T. 6 S., R. 29 E.

Chains

78.00

Bottom of descent on SW. slope, continue over S. slope.

80.00

Point for the cor. of secs. 35 and 36, T. 6 S., R. 29 E.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 6 S    R 29 E  
 S 35 | S 36

1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

Land, rough mountainous.

Soil, gravelly and rocky, 4th rate.

Timber, scattering juniper.

Undergrowth, catclaw, ocotillo, sagebrush and cacti.

West, along the S. bdy. of sec. 35, T. 6 S., R. 29 E.

Over mountainous land, through scattering undergrowth; asc. 40 ft. over SSW. slope.

3.00

Fence, 4 strand barbed wire with steel posts, bears N. and S.

3.13

The original corner established as the corner of secs. 1, 2, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record. This corner now functions as the cor. of secs. 1 and 2, T. 7 S., R. 29 E. only. I alter the markings on the corner monument to read

T 6 S    R 29 E    S 35

S 2 | S 1

T 7 S    R 29 E

1933

1955

rebuild the mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

8.79

Top of spur from ridge, slopes S.  $60^\circ$  W.; desc. 367 ft. over NW. slope.

40.00

Point for the  $\frac{1}{4}$  sec. cor. of sec. 35.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S 35

1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

43.30

The original corner established for the  $\frac{1}{4}$  sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set in the ground, marked and witnessed as described in the official record. This corner now functions as the  $\frac{1}{4}$  sec. cor. of sec. 2 only. I alter the markings on the corner monument to read

$\frac{1}{4}$  S 2

1933

1955

## Dependent Resurvey of the South Boundary of T. 6 S., R. 29 E.

|        |  |
|--------|--|
| Chains | rebuild the mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, S. of corner.   |
| 62.00  | Wash, 70 lks. wide, 20 ft. deep, drains S. $70^\circ$ W.   |
| 73.00  | Ravine, course S. $30^\circ$ E.; asc. 69 ft. over E. slope.  |
| 80.00  | True point for the cor. of secs. 34 and 35, T. 6 S., R. 29 E.<br>This point falls in a crevice of a sandstone cliff, approximately 20 ft. high; not monumented.  |
|        | Land, rough mountainous.<br>Soil, gravelly and rocky, 4th rate.<br>No timber.<br>Undergrowth, oakbrush, catclaw, ocotillo, sagebrush and cacti.  |
|        | West, along the S. bdy. of sec. 34.<br>Over mountainous land, through scattering undergrowth.  |
| 2.00   | Point selected for the witness corner of secs. 34 and 35, on S. slope near the top of a small hill sloping S.<br><br>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.<br><br><div style="text-align: center;">           T 6 S    R 29 E<br/> <u>  S 34   S 35</u>    WC<br/>           1955         </div>   |
| 3.40   | raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.<br><br>Original corner established for the cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record. This corner now functions as the corner of secs. 2 and 3 only. I alter the markings on the corner monument to read<br><br><div style="text-align: center;"> <u>  T 6 S    R 29 E    S 34</u><br/>           S 3   S 2<br/>           T 7 S    R 29 E<br/>           1933<br/>           1955         </div> |
|        | rebuild the mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, S. of corner.<br>Desc. 171 ft. over rocky SW. slope.  |
| 24.20  | Wash, 30 lks. wide, 4 ft. deep, drains N. $30^\circ$ W. Road in wash, bears NW. and SE.; asc. 218 ft. over NE. slope.  |
| 28.54  | Fence, 4 strand barbed wire with steel and cedar posts, bears NW. and SE.  |
| 38.79  | Top of spur from ridge, slopes NW.; desc. 9 ft. over SW. slope.  |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of sec. 34.<br><br>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.<br><br><div style="text-align: center;"> <u>  <math>\frac{1}{4}</math> S 34</u><br/>           1955         </div>   |

## Dependent Resurvey of the South Boundary of T. 6 S., R. 29 E.

Chains

- raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.
- 43.43 The original corner established for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set in the ground, marked and witnessed as described in the official record. This corner now functions as the  $\frac{1}{4}$  sec. cor. of sec. 3 only. I alter the markings on the corner monument to read
- $\frac{1}{4}$  S 3  
 1933  
 1955
- rebuild the mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.  
Asc. 110 ft. over E. slope.
- 55.60 Top of spur from ridge, slopes N.; desc. 109 ft. over W. slope.
- 63.00 Wash, 30 lks. wide, 4 ft. deep, drains N.; asc. 102 ft. over E. slope.
- 69.87 Top of spur from ridge, slopes NW.; desc. 202 ft. over W. slope.
- 80.00 Point for the cor. of secs. 33 and 34.
- Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 5 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.
- T 6 S R 29 E  
S 33 | S 34  
 1955
- raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.
- Land, rough mountainous.  
Soil, gravelly and rocky, 4th rate.  
No timber.  
Undergrowth, catclaw, oakbrush, ocotillo, sagebrush and cacti.
- 
- West, along the S. bdy. of sec. 33.
- Over mountainous land, through sparse timber and scattering undergrowth; desc. 124 ft. over rocky W. slope.
- 3.45 The original corner established for the cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record. This corner now functions as the cor. of secs. 3 and 4 only. I alter the markings on the corner monument to read
- T 6 S R 29 E S 33  
 S 4 | S 3  
 T 7 S R 29 E  
 1933  
 1955
- rebuild the mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.
- 4.25 Wash, 20 lks. wide, 3 ft. deep, drains N.  $70^\circ$  W.; asc. 13 ft. over NE. slope.
- 11.50 End of spur from ridge, slopes NW.; desc. 80 ft. over W. slope.

## Dependent Resurvey of the South Boundary of T. 6 S., R. 29 E.

## Chains

- 22.08 Wash, 40 lks. wide, 4 ft. deep, drains N.; asc. 294 ft. over NE. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 33.  
Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.  
$$\frac{1}{4} \text{ S } 33$$
  
1955  
raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.  
Continue ascent, asc. 94 ft. over NE. slope.
- 43.46 The original corner established for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set in the ground, marked and witnessed as described in the official record. This corner now functions as the  $\frac{1}{4}$  sec. cor. of sec. 4 only. I alter the markings on the corner monument to read  
$$\frac{1}{4} \text{ S } 4$$
  
1933  
1955  
rebuild the mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.
- 43.83 Top of high rocky spur from ridge, slopes N.; desc. 641 ft. over general W. slope.
- 80.00 Point for the cor. of secs. 32 and 33.  
Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.  
$$\begin{array}{cc} \text{T 6 S} & \text{R 29 E} \\ \text{S 32} & | \text{S 33} \end{array}$$
  
1955  
raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.  
Land, rough mountainous.  
Soil, gravelly and rocky, 4th rate.  
Timber, sparse juniper.  
Undergrowth, sagebrush, ocotillo, catclaw, oakbrush and cacti.
- 3.89 West, along the S. bdy. of sec. 32.  
Over gradual W. slope, through scattering undergrowth.  
The original corner established for the cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record. This corner now functions as the cor. of secs. 4 and 5 only. I alter the markings on the corner monument to read

Dependent Resurvey of the South Boundary of T. 6 S., R. 29 E.

| Chains |  |
|--------|--|
|        | <p><u>T 6 S R 29 E S 32</u><br/>                     S 5   S 4<br/>                     T 7 S R 29 E<br/>                     1933<br/>                     1955</p>   |
|        | rebuild the mound of stone, 4 ft. base, 2½ ft. high, S. of corner.   |
|        | Continue descent, desc. 97 ft. over gradual W. slope.  |
| 19.75  | Road to Gillespie's ranch, bears SW. and N.  |
| 37.10  | Wash, 30 lks. wide, 4 ft. deep, drains SW. Thence over gradual E. slope.   |
| 40.00  | Point for the ¼ sec. cor. of sec. 32.  |
|        | Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.  |
|        | <p><u>¼ S 32</u><br/>                     1955</p>   |
|        | raise a mound of stone, 4 ft. base, 2½ ft. high, N. of corner.   |
| 44.00  | The original corner established for the ¼ sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set in the ground, marked and witnessed as described in the official record. This corner now functions as the ¼ sec. cor. of sec. 5 only. I alter the markings on the corner monument to read |
|        | <p><u>¼ S 5</u><br/>                     1933<br/>                     1955</p>  |
|        | rebuild the mound of stone, 4 ft. base, 2½ ft. high, S. of corner.   |
| 44.10  | Begin descent, desc. 17 ft. over gradual W. slope.   |
| 47.00  | Bottom of descent; thence over nearly level land.  |
| 52.00  | Old road to Gillespie's ranch, bears N. 70° W. and S. 70° E.   |
| 67.00  | Wash, 40 lks. wide, 5 ft. deep, drains WSW.  |
| 72.00  | Wash, 1 ch. wide, 12 ft. deep, drains S. Begin ascent, asc. 43 ft. over E. slope.  |
| 74.00  | Telephone line, bears N. 15° E. and S. 15° W.  |
| 80.00  | Point for the cor. of secs. 31 and 32.   |
|        | Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.  |
|        | <p><u>T 6 S R 29 E</u><br/>                     S 31   S 32<br/>                     1955</p>  |
|        | raise a mound of stone, 4 ft. base, 2½ ft. high, N. of corner.   |

## Dependent Resurvey of the South Boundary of T. 6 S., R. 29 E.

Chains

Land, nearly level.  
Soil, gravelly and rocky, 4th rate.  
No timber.  
Undergrowth, sagebrush, ocotillo, catclaw and cacti.

West, along the S. bdy. of sec. 31.

Continue ascent, asc. 32 ft. over E. slope, through heavy undergrowth.

3.97 The original corner established for the cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone with the top of post projecting slightly above the mound of stone, marked and witnessed as described in the official record. This corner now functions as the cor. of secs. 5 and 6 only. I alter the markings on the corner monument to read

$$\begin{array}{c} \underline{T\ 6\ S\ R\ 29\ E\ S\ 31} \\ S\ 6\ | \ S\ 5 \\ T\ 7\ S\ R\ 29\ E \\ 1933 \\ 1955 \end{array}$$

rebuild the mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

Top of ascent; continue across nearly level mesa, through heavy undergrowth.

6.20 Old graded highway, No. 71, bears N.  $30^\circ$  E. and S.  $30^\circ$  W.

33.00 Begin descent, desc. 72 ft. over NW. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 31.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} \underline{\frac{1}{4}\ S\ 31} \\ 1955 \end{array}$$

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

Continue descent, desc. 66 ft. over NW. slope.

43.77 The original corner established for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., firmly set in the ground, marked and witnessed as described in the official record. This corner now functions as the  $\frac{1}{4}$  sec. cor. of sec. 6 only. I alter the markings on the corner monument to read

$$\begin{array}{c} \underline{\frac{1}{4}\ S\ 6} \\ 1933 \\ 1955 \end{array}$$

rebuild the mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

43.96 Wash, 90 lks. wide, 7 ft. deep, drains SW.; asc. 96 ft. over SE. slope.

52.65 Top of spur from ridge, slopes SW.; desc. 86 ft. over NW. slope.

56.20 Wash, 30 lks. wide, 4 ft. deep, drains SW.; asc. 58 ft. over SSE. slope.

## Dependent Resurvey of the South Boundary of T. 6 S., R. 29 E.

| Chains   |   |
|--|---|
| 82.40  | Begin descent; desc. 104 ft. over W. slope to corner.   |
| 84.98  | <p>The original closing corner established for the cor. of Ts. 6 and 7 S., R. 29 E., monumented with an iron post, 3 ins. diam., firmly set in the ground, marked and witnessed as described in the official record. I rebuild a mound of stone around the corner, and raise a mound of stone, 5 ft. base, 2½ ft. high, E. of corner.</p> <p>From this corner, the SE. cor. of T. 6 S., R. 28 E., monumented with an iron post, 3 ins. diam., firmly set in the ground, marked and witnessed as described in the official record, bears S., 6.80 chs. dist.</p> <p>From this same corner, the ¼ sec. cor. of sec. 36, T. 6 S., R. 28 E., monumented with an iron post, 2½ ins. diam., firmly set in the ground and in a mound of stone to top, bears N., 33.20 chs. dist.</p> <p>Land, nearly level and gently rolling.<br/>Soil, gravelly and rocky, 4th rate.<br/>No timber.<br/>Undergrowth, chaparral, ocotillo, sagebrush and cacti.</p> |
| Survey of a Portion of the Subdivisional Lines of T. 6 S., R. 29 E.  |   |
| Beginning the subdivisional survey at the cor. of secs. 33 and 34, on the S. bdy. of the township, hereinbefore described. |   |
| N. 0° 02' W., bet. secs. 33 and 34.  |   |
| Over rough mountainous land, through scattering undergrowth; asc. 101 ft. over S. slope through sparse timber.             |   |
| 9.94   | Top of spur from ridge, slopes WNW.; desc. 364 ft. over N. slope.   |
| 26.30  | Fence, 4 strand barbed wire, bears E. and W. Wash, 50 lks. wide, 1½ ft. deep, drains WSW. approximately 10 chs., thence NNW.; asc. 191 ft. over steep rocky S. slope.   |
| 27.10  | Road, bears E. and W.   |
| 40.00  | <p>Point for the ¼ sec. cor. of secs. 33 and 34.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.</p>   |
| $\frac{1}{4}$<br>S 33   S 34<br>. 1955   |   |
| raise a mound of stone, 4 ft. base, 2½ ft. high, W. of corner.   |   |
| Continue ascent, asc. 298 ft. over steep S. slope.   |   |
| 51.90  | Top of spur from ridge, slopes W.; desc. 212 ft. over N. slope.   |
| 56.00  | Trail, bears E. and W.  |
| 61.30  | Wash, 30 lks. wide, 10 ft. deep, drains WSW.; asc. 506 ft. over steep rocky S. slope.   |

## Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

## Chains

77.20 Top of spur from ridge, slopes WNW.; desc. 17 ft. over N. slope.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|       |        |
|-------|--------|
| T 6 S | R 29 E |
| S 28  | S 27   |
| S 33  | S 34   |
| 1955  |        |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, rough mountainous.

Soil, gravelly and rocky, 4th rate.

Timber, sparse juniper.

Undergrowth, sagebrush, ocotillo, catclaw and cacti.

N.  $0^{\circ} 02'$  W., bet. secs. 27 and 28.

Over rough mountainous land; desc. 40 ft. over N. slope.

4.50 Gulch, drains W.; asc. 40 ft. over S. slope.

9.92 Top of ridge, bears E. and W.; desc. 257 ft. over N. slope.

14.40 Fence, 4 strand barbed wire, bears E. and W.

29.93 Wash, 1 ch. wide, 6 ft. deep, drains W.; asc. 92 ft. over S. slope. A cement water tank, 6x6 ft. with small corral, bears W., 50 lks. dist.

35.38 Top of spur from ridge, slopes WSW.; desc. 55 ft. over N. slope.

39.00 An old house, bears E., 10 chs. dist.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 27 and 28.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|               |
|---------------|
| $\frac{1}{4}$ |
| S 28   S 27   |
| 1955          |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Continue over rough mountainous land, through scattering undergrowth; desc. 11 ft. over N. slope.

42.50 Fence, 4 strand barbed wire, bears NE. and SW.

43.70 Old graded road, No. 71, bears NE. and SW.

45.30 Wash, 30 lks. wide, 6 ft. deep, drains SW.; asc. 160 ft. over rocky S. slope.

55.00 Top of spur from ridge, slopes W.; desc. 97 ft. over N. slope.

69.50 Wash, 20 lks. wide, 4 ft. deep, drains W.; thence over nearly level land.



## Survey of a Portion of the Subdivisional Lines of T. 6 S., R. 29 E.

## Chains

80.00

Point for the cor. of secs. 21, 22, 27 and 28.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|       |        |
|-------|--------|
| T 6 S | R 29 E |
| S 21  | S 22   |
| S 28  | S 27   |
| 1955  |        |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, mountainous.

Soil, gravelly and rocky, 4th rate.

No timber.

Undergrowth, ocotillo, catclaw and cacti.

N.  $0^{\circ}$  02' W., bet. secs. 21 and 22.

Over mountainous land through scattering undergrowth; desc. 209 ft. over WNW. slope.

13.00

Wash, 150 lks. wide, 12 ft. deep, drains W. 1 ch., thence NW.; asc. 287 ft. over SW. slope.

39.50

Top of spur from ridge, slopes NW. approximately 5 shs., thence N.

40.00

Point for the  $\frac{1}{4}$  sec. cor. of secs. 21 and 22.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|               |  |
|---------------|--|
| $\frac{1}{4}$ |  |
| S 21   S 22   |  |
| 1955          |  |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Continue over mountainous land, through scattering undergrowth; desc. 189 ft. along NNE. slope.

55.00

Bottom of NNE. slope; continue descent, desc. 40 ft. along E. slope.

80.00

Point for the corner of secs. 15, 16, 21 and 22.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|       |        |
|-------|--------|
| T 6 S | R 29 E |
| S 16  | S 15   |
| S 21  | S 22   |
| 1955  |        |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, mountainous.

Soil, gravelly and rocky, 4th rate.

No timber.

Undergrowth, catclaw, ocotillo, sagebrush and cacti.

Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

|        |  |
|--------|--|
| Chains | <p>N. 0° 02' W., bet. secs. 15 and 16.</p> <p>Over mountainous land, through scattering undergrowth. Continue along E. slope, through sparse timber.</p>   |
| 10.00  | <p>Leave sparse timber; begin descent, desc. 240 ft. over steep rocky N. slope.</p>  |
| 15.60  | <p>Wash, 15 lks. wide, 4 ft. deep, drains NE.</p>  |
| 35.00  | <p>Wash, 150 lks. wide, 10 ft. deep, drains NNW.; asc. 11 ft. over SW. slope.</p>  |
| 37.00  | <p>Top of ascent, slopes W.; desc. 7 ft. over NW. slope to corner.</p>   |
| 40.00  | <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 15 and 16.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, to top, with brass cap mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math><br/>             S 16   S 15<br/>             1955         </div> <p>raise a mound of stone, 4 ft. base, <math>2\frac{1}{2}</math> ft. high, W. of corner.</p> <p>Continue over mountainous land, through scattering undergrowth; desc. 23 ft. along W. slope.</p>   |
| 45.00  | <p>Bottom of descent; begin ascent, asc. 173 ft. along W. slope.</p>   |
| 57.30  | <p>Fence, 4 strand barbed wire with steel posts, bears NE. and SW.</p>   |
| 64.00  | <p>Top of ascent, slopes WNW.; desc. 52 ft. over N. slope.</p>   |
| 79.95  | <p>Top of spur from ridge, slopes N.</p>   |
| 80.00  | <p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;">             T 6 S R 29 E.<br/>             S 9   S 10<br/>             S 16   S 15<br/>             1955         </div> <p>raise a mound of stone, 4 ft. base, <math>2\frac{1}{2}</math> ft. high, W. of corner.</p> <p>Land, mountainous.<br/>             Soil, gravelly and rocky, 4th rate.<br/>             Timber, sparse juniper.<br/>             Undergrowth, sagebrush, ocotillo, catclaw and cacti.</p> |
|        | <p>N. 0° 02' W., bet. secs. 9 and 10.</p> <p>Over mountainous land, through scattering undergrowth. Continue descent along top of spur from ridge, desc. 57 ft. over N. slope.</p>   |
| 10.00  | <p>Bottom of descent, bears E. and W. Continue over nearly level land.</p>   |
| 25.00  | <p>Begin descent, desc. 188 ft. over steep rocky N. slope.</p>   |

## Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

## Chains

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 9 and 10.  
Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$   
S 9 | S 10  
1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Continue descent, desc. 29 ft. over N. slope.

46.07 Wash, 40 lks. wide, 5 ft. deep, drains NW.; asc. 198 ft. over WSW. slope.

60.30 Top of ascent, slopes W.

64.00 Begin descent, desc. 159 ft. over WNW. slope.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 6 S R 29 E  
S 4 | S 3  
S 9 | S 10  
1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, mountainous.

Soil, gravelly and rocky, 4th rate.

No timber.

Undergrowth, sagebrush, ocotillo, catclaw and cacti.

N.  $0^{\circ} 02'$  W., bet. secs. 3 and 4.

Over mountainous land, through scattering undergrowth; desc. 339 ft. over WNW. slope.

25.00 Wash, 60 lks. wide, 4 ft. deep, drains NE.; asc. 339 ft. over steep rocky S. slope.

35.00 Top of spur from ridge, slopes NE.; desc. 48 ft. over N. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 4.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 4 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$   
S 4 | S 3  
1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Continue descent, desc. 291 ft. over N. slope.

## Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

## Chains

- 51.50 Wash, 20 lks. wide, 20 ft. deep, drains NE.; asc. 266 ft. over S. slope.
- 61.00 Old road, bears NE. and SW.
- 65.00 Top of spur from ridge, slopes NE.; desc. 52 ft. over N. slope.
- 71.32 Intersect the First Standard Parallel South. Point for the closing cor. of secs. 3 and 4.
- Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 5 S. R 29 E S 33

S 4 | S 3  
T 6 S R 29 E  
- C O  
1955

raise a mound of stone, 4 ft. base, 2½ ft. high, W. of corner.

From this corner, the standard ¼ sec. cor. of sec. 33, T. 5 S., R. 29 E., monumented with a malpais stone, 12x8x6 ins. above ground, firmly set, marked and witnessed as described in the official record, bears W., 6.18 chs. dist.

From this same corner, the witness standard corner of secs. 33 and 34, T. 5 S., R. 29 E., monumented with a malpais stone, 8x8x4 ins. above ground, firmly set, marked and witnessed as described in the official record, bears E., 46.82 chs. dist.

Land, mountainous.  
Soil, gravelly and rocky, 4th rate.  
No timber.  
Undergrowth, sagebrush, ocotillo, catclaw and cacti.

From the corner of secs. 3, 4, 9 and 10, hereinbefore described.  
East, between secs: 3 and 10.

- 3.80 Top of spur from ridge, slopes N.; desc. 41 ft. over E. slope through scattering timber.
- 12.25 Wash, 30 lks. wide, 4 ft. deep, drains N.; asc. 97 ft. over W. slope.
- 18.40 Top of spur from ridge, slopes N.; desc. 309 ft. over steep rocky E. slope. Leave scattering timber.
- 32.50 Wash, 20 lks. wide, 4 ft. deep, drains NNW. 2 chs., thence NW.
- 36.85 Point selected for the witness ¼ sec. cor. of secs. 3 and 10.
- Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

¼  $\frac{S 3}{S 10}$  W C  
1955

raise a mound of stone, 4 ft. base, 2½ ft. high, N. of corner.

Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

Chains

Continue over mountainous land, through scattering undergrowth, along N. slope of end of spur.

39.50 Wash, 40 lks. wide, 4 ft. deep, drains NW.; asc. 47 ft. over malpais rock slide SW. slope.

40.00 True point for the 1/4 sec. cor. of secs. 3 and 10 falls in malpais rock slide, not monumented.

Continue ascent, asc. 252 ft. over rocky W. slope.

49.90 Top of spur from ridge, slopes N.; desc. 310 ft. over E. slope.

73.20 Wash, 40 lks. wide, 6 ft. deep, drains N.; asc. 83 ft. over W. slope.

80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|       |        |
|-------|--------|
| T 6 S | R 29 E |
| S 3   | S 2    |
| S 10  | S 11   |
| 1955  |        |

raise a mound of stone, 4 ft. base, 2 1/2 ft. high, W. of corner.

Land, mountainous.

Soil, gravelly and rocky, 4th rate.

Timber, scattering juniper.

Undergrowth, sagebrush, ocotillo, catclaw and cacti.

East, between secs. 2 and 11.

Over rolling land, through scattering undergrowth; desc. 123 ft. over ESE. slope.

21.45 Wash, 30 lks. wide, 5 ft. deep, drains NE.

28.60 Wash, 50 lks. wide, 6 ft. deep, drains N.; asc. 93 ft. over W. slope.

34.90 Top of low flat spur from ridge, slopes N.; desc. 71 ft. over E. slope.

40.00 Point for the 1/4 sec. cor. of secs. 2 and 11.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|         |
|---------|
| 1/4 S 2 |
| S 11    |
| 1955    |

raise a mound of stone, 4 ft. base, 2 1/2 ft. high, N. of corner.

Continue over gently rolling land, through scattering undergrowth; desc. 57 ft. over E. slope.

46.00 Wash, 17 lks. wide, 4 ft. deep, drains NW.; asc. 17 ft. over W. slope.

50.00 Top of ascent, slopes N.

## Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

## Chains

56.80 Wash, 50 lks. wide, 10 ft. deep, drains NW.; asc. 144 ft. over W. slope.

71.00 Road, bears NW. and SE. Continue over nearly level land.

80.00 Point for the cor. of secs. 1, 2, 11 and 12.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|       |        |
|-------|--------|
| T 6 S | R 29 E |
| S 2   | S 1    |
| S 11  | S 12   |
| 1955  |        |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, west-half, rolling; east-half, gently rolling.

Soil, gravelly and rocky, 4th rate.

No timber.

Undergrowth, sagebrush, ocotillo, catclaw and cacti.

N.  $0^{\circ}$  01' W., bet. secs. 1 and 2.

Over gently rolling land, through scattering undergrowth; desc. 143 ft. over NNW. slope.

1.20 Road, bears NW. and SE.

6.35 Fence, 4 strand barbed wire, bears E. and W.

30.00 Desc. 115 ft. over steep N. slope.

38.20 Wash, 20 lks. wide, 6 ft. deep, drains W.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 2.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|               |
|---------------|
| $\frac{1}{4}$ |
| S 2   S 1     |
| 1955          |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Continue over nearly level land, through scattering undergrowth.

65.00 Begin descent, desc. 131 ft. over N. slope.

71.23 Intersect the First Standard Parallel South. Point for the closing corner of secs. 1 and 2.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

|       |        |      |
|-------|--------|------|
| T 5 S | R 29 E | S 35 |
| S 2   | S 1    |      |
| T 6 S | R 29 E |      |
| C C   |        |      |
| 1955  |        |      |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

Chains

From this corner, the standard  $\frac{1}{4}$  sec. cor. of sec. 35, T. 5 S., R. 29 E., monumented with an iron post, 1 in. diam., firmly set in the ground with top of post projecting slightly above the mound of stone, marked and witnessed as described in the official record, bears W., 6.21 chs. dist.

From this same corner, the standard corner of secs. 35 and 36, T. 5 S., R. 29 E., monumented with an iron post, 2 ins. diam., firmly set in the ground with top of post projecting slightly above the mound of stone, marked and witnessed as described in the official record, bears E., 33.82 chs. dist.

Land, south-half, gently rolling; north-half, nearly level.  
Soil, gravelly and rocky, 4th rate.  
No timber.  
Undergrowth, sagebrush, ocotillo, catclaw and cacti.

The point for the  $\frac{1}{4}$  sec. cor. of sec. 1, on the N. bdy. of the township, is at midpoint between the reestablished standard closing cor. of Ts. 5 and 6 S., R. 29 E., monumented with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record and the closing cor. of secs. 1 and 2, T. 6 S., R. 29 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., hereinbefore described.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S 1  
1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

From this corner, the standard cor. of secs. 35 and 36, T. 5 S., R. 29 E., monumented with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record, bears W., 6.16 chs. dist.

From this same corner, the standard  $\frac{1}{4}$  sec. cor. of sec. 36, T. 5 S., R. 29 E., monumented with an iron post, 1 in. diam., firmly set in the ground, marked and witnessed as described in the official record, bears E., 33.85 chs. dist.

From the corner of secs. 2, 3, 10 and 11.

N.  $0^{\circ}$  01' W., bet. secs. 2 and 3.

Over nearly level land, through scattering undergrowth; desc. 126 ft. over gradual N. slope.

25.00 Desc. 98 ft. over abrupt NW. slope.

32.30 Wash, 25 lks. wide, 6 ft. deep, drains NE.; asc. 77 ft. over steep rocky SE. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 2 and 3.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
S 3 | S 2  
1955

## Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

## Chains

- raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.  
 Continue over nearly level land, through scattering undergrowth.
- 55.00 Begin descent, desc. 48 ft. over N. slope.
- 60.60 Wash, 20 lks. wide, 4 ft. deep, drains E.; asc. 34 ft. over S. slope.
- 65.00 Top of ascent, slopes E. Continue over nearly level land.
- 71.31 Intersect the First Standard Parallel South. Point for the closing corner of secs. 2 and 3.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 5 S. R. 29 E. S 34

S 3 | S 2

T 6 S. R. 29 E.

C C

1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

From this corner, the standard  $\frac{1}{4}$  sec. cor. of sec. 34, T. 5 S., R. 29 E., monumented with a malpais stone, 10x8x4 ins. above ground, firmly set in the ground, marked and witnessed as described in the official record, bears W., 6.13 chs. dist.

From this same corner, the witness standard corner of secs. 34 and 35, T. 5 S., R. 29 E., monumented with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record, bears E., 32.81 chs. dist.

Land, nearly level.

Soil, gravelly and rocky, 4th rate.

No timber.

Undergrowth, sagebrush, ocotillo, catclaw and cacti.

The point for the  $\frac{1}{4}$  sec. cor. of sec. 2, on the N. bdy. of the township is at midpoint between the closing cor. of secs. 1 and 2 and the closing cor. of secs. 2 and 3, hereinbefore described.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S 2

1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

From this corner, the witness standard corner of secs. 34 and 35, T. 5 S., R. 29 E., monumented with a malpais stone, 10x8x4 ins. above ground, firmly set, marked and witnessed as described in the official record, bears W., 7.19 chs. dist., and the true point for that cor. bears W., 6.19 chs. dist.

From this same corner, the reestablished standard  $\frac{1}{4}$  sec. cor. of sec. 35, T. 5 S., R. 29 E., monumented with an iron post, 1 in. diam., firmly set in the ground, marked and witnessed as described in the official record, bears E., 33.79 chs. dist.



## Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

## Chains

The true point for the  $\frac{1}{4}$  sec. cor. of sec. 3, on the N. bdy. of the township, at midpoint between the closing corners of secs. 2 and 3 and secs. 3 and 4, T. 6 S., R. 29 E., hereinbefore described falls in the bottom of a deep wash and is deemed unsafe for the corner, not monumented. From this point, the true point for the stan. cor. of secs. 33 and 34, T. 5 S., R. 29 E., bears W., 6.22 chs. dist. At a point 6.18 chs. E. of the true point for the  $\frac{1}{4}$  sec. cor. of sec. 3 and 60 lks. W. of the witness standard corner of secs. 33 and 34, T. 5 S., R. 29 E.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

WC  $\frac{1}{4}$  S 3  
1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of corner.

From this <sup>witness</sup> corner, the true point for the standard corner of secs. 33 and 34, T. 5 S., R. 29 E., not monumented, bears W., 12.40 chs. dist.

From the corner of secs. 15, 16, 21 and 22, hereinbefore described.

West on true line bet. secs. 16 and 21.

Over heavily rolling land, through scattering undergrowth; asc. 122 ft. over E. slope.

16.58 Top of ridge, bears N. and S.; desc. 312 ft. over W. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 21.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S 16  
S 21  
1955

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

Continue descent, desc. 200 ft. over W. slope through scattering undergrowth.

53.20 Wash, 40 lks. wide, 6 ft. deep, drains NNW.; asc. 52 ft. over E. slope.

54.60 Road, bears NW. and SE.

56.70 Telephone line, bears N. and S.

57.70 Top of low spur from ridge, slopes N.; desc. 12 ft. over W. slope.

60.90 Wash, 30 lks. wide, 4 ft. deep, drains NW.; asc. 223 ft. over ENE. slope.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

## Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

Chains

|       |        |
|-------|--------|
| T 6 S | R 29 E |
| S 17  | S 16   |
| S 20  | S 21   |
| 1955  |        |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, heavily rolling.

Soil, gravelly and rocky, 4th rate.

No timber.

Undergrowth, ocotillo, sagebrush, catclaw and cacti.

N.  $0^{\circ} 02'$  W., bet. secs. 16 and 17.

Over heavily rolling land, through scattering undergrowth; desc. 269 ft. over steep NE. slope.

21.00 Wash, 40 lks. wide, 6 ft. deep, drains NW.; asc. 259 ft. over S. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 17.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|               |  |
|---------------|--|
| $\frac{1}{4}$ |  |
| S 17   S 16   |  |
| 1955          |  |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Continue ascent, asc. 29 ft. over gradual S. slope, through scattering undergrowth.

50.50 Top of spur from ridge, slopes NNW. Road, bears NW. and SE. Continue over nearly level land.

71.30 Road, bears NE. and SW.

75.00 Begin descent, desc. 12 ft. over gradual N. slope.

80.00 Point for the cor. of secs. 8, 9, 16 and 17.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

|       |        |
|-------|--------|
| T 6 S | R 29 E |
| S 8   | S 9    |
| S 17  | S 16   |
| 1955  |        |

raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of corner.

Land, south-half, heavily rolling; north-half, nearly level.

Soil, gravelly and rocky, 4th rate.

No timber.

Undergrowth, sagebrush, ocotillo, catclaw, sotol and cacti.

N.  $89^{\circ} 59'$  E., bet. secs. 9 and 16.

Over rolling land, through scattering undergrowth.

1.80 Curve on road, bears NW. and S.

Survey of a Portion of the Subdivisional Lines in T. 6 S., R. 29 E.

| Chains |  |
|--------|--|
| 4.80   | Road, bears NNE. and SSW.; desc. 69 ft. over E. slope.   |
| 6.70   | Telephone line, bears NE. and SW.  |
| 16.40  | Wash, 20 lks. wide, 1½ ft. deep, drains N. Continue over gently rolling land.  |
| 29.00  | Wash, 30 lks. wide, 4 ft. deep, drains NW.; asc. 75 ft. over SSW. slope.   |
| 39.98  | <p>Point for the ¼ sec. cor. of secs. 9 and 16.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.</p> |
|        | $\frac{1}{4} \frac{S 9}{S 16}$ <p>1955</p>   |
|        | raise a mound of stone, 4 ft. base, 2½ ft. high, N. of corner.   |
|        | Continue ascent, asc. 17 ft. over gradual W. slope, through scattering undergrowth.  |
| 50.00  | Top of ridge, bears NNW. and SSE.; desc. 115 ft. over E. slope.  |
| 64.80  | Wash, 40 lks. wide, 6 ft. deep, drains NNW.; asc. 115 ft. over W. slope.   |
| 79.96  | The corner of secs. 9, 10, 15 and 16.  |
|        | <p>Land, gently rolling.</p> <p>Soil, gravelly and rocky, 4th rate.</p> <p>No timber.</p> <p>Undergrowth, sagebrush, ocotillo, catclaw, sotol and cacti.</p>                                       |

General Description

The general elevation of the township ranges from about 4100 to 5500 ft. above sea level. The eastern half of the township is rough broken mountainous land, and the western half is rolling and rough mountainous. The soil is very shallow, being gravelly and stony, 4th rate, as the entire township is covered with rocks.

The eastern half of the township is covered with sparse timber along the main spurs and ridges, and the entire township is covered with scattering undergrowth.

There is a rancher living in section 33. There is some stock grazing in the southern half and west-central portion of the township. Stock water reservoirs have been developed in sections 24 and 28. Grazing is limited, as the area is too rough and rocky and there is not sufficient rainfall to produce a good stand and growth of native grasses. There is no cultivated land within the township.

4-680  
(Feb., 1960)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| NAMES                    | CAPACITY    |
|--------------------------|-------------|
| Clarence J. Curtis       | Note-keeper |
| Darwin P. Russell        | Chainman    |
| Maurice L. Hinton        | Flagman     |
| Angel G. Montez          | Cornerman   |
| Gregorio E. Ornelas, Jr. | Cornerman   |
| Francisco M. Peru        | Cornerman   |
|                          |             |
|                          |             |
|                          |             |
|                          |             |
|                          |             |
|                          |             |
|                          |             |
|                          |             |
|                          |             |
|                          |             |
|                          |             |
|                          |             |
|                          |             |
|                          |             |

27

CERTIFICATE OF CADASTRAL ENGINEER

I, Horace G. Parker, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of November, 1954, I have surveyed a portion of the east boundary, independently resurveyed the south boundary, and surveyed a portion of the subdivisional lines in Township 6 South, Range 29 East

of the G & S R Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah

September 2, 1955

Horace G. Parker  
Horace G. Parker  
Cartographer Cadastral

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., JAN 30 1956, 19

The foregoing field notes of the survey of a portion of the east boundary, independent resurvey of the south boundary, and survey of a portion of the subdivisional lines in Township 6 South, Range 29 East, Gila and Salt River Meridian, Arizona

executed by Horace G. Parker

having been critically examined and found correct, are hereby approved.

Earl G. Harrington  
Chief, Division of Cadastral Engineering  
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.

\_\_\_\_\_  
Chief, Division of Cadastral Engineering