

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of

the survey

of

the North Boundary

and

subdivision

of

partial

Township 8 North, Range 19 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Fred R. Chappell-Cartographic Aid

Under special instructions dated Oct. 9, 19 52, which provided
for the surveys included under Group No. 285, approved Oct. 21, 1955
and assignment instructions dated Feb. 2, 19 53

Survey commenced Jan. 26, 19 54

Survey completed Feb. 12, 19 54

4492

4492

1A

BOOK 4492

INDEX DIAGRAM

Township 8 N., Range 19 W.

				21		14		8	
6	5	4	20	3	13	2	7	1	
		20		19		13		7	
7	8	9	19	10	12	11	6	12	
		18		18		12		6	
18	17	16	17	15	11	14	5	13	
		17		16		11		5	
19	20	24	21	16	22	10	23	5	24
	24		23		15		10		4
30	29	23	28	15	27	9	26	4	25
	22		22		14		9		3
31	32	21	33	14	34	8	35	3	36

2nd Stand. Par. N., S. Bdy., T. 9 N., R. 19 W.

Chains

The instructions for the survey of T. 8 N., R. 19 W. are included in Group 285, Arizona. The south boundary of T. 8 N., R. 19 W. was surveyed by Ty White and Donald E. Harding in 1953. The survey of the east boundary is contained in T. 8 N., R. 18 W.

The Colorado River Indian Reservation boundary, which was resurveyed by Guy P. Harrington in 1912, forms the west boundary of this fractional township.

For the check of instruments and tapes see the notes for T. 8 N., R. 17 W. The latitude of the SE. cor. of the township is $33^{\circ}59'04''$ N., long. is $114^{\circ}10'47''$ W. Magnetic declination is $14\frac{1}{2}^{\circ}$ E.

From the standard township corner of T. 9 N., Rs. 18 and 19 W.

West, with the establishment of the Second Standard Parallel North, along the S. bdy. of sec. 36, T. 9 N., R. 19 W., on a transit line describing the tangent.

Over low rolling sand dunes.

40.00

Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, on the parallel.

Set an iron post, 36 ins. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

S C

 $\frac{1}{4}$ S 36

1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the standard cor. of secs. 35 and 36, N. 1 lk. from the tangent.

Set an iron post, 36 ins. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

S C

T 9 N R 19 W

S 35 | S 36

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

West, continuing the tangent on the S. bdy. of sec. 35, which bears, S. $89^{\circ}58.8'$ W.

Over low rolling sand dunes.

19.25

Transmission line and road, bears N. 8° E. and S. 8° W.

40.00

Point for the standard $\frac{1}{4}$ sec. cor. of sec. 35, N. 2 lks. from the tangent.

Set an iron post, 36 ins. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

S C

 $\frac{1}{4}$ S 35

1954

BOOK 4492

2nd Stan. Par. N., S. Bdy., T. 9 N., R. 18 W.

Chains

deposit broken glass alongside the iron post, for witness.

80.00

Point for the standard cor. of secs. 34 and 35, N. 5 lks. from the tangent.

Set an iron post, 36 ins. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

S C

T 9 N R 19 W

S 34 | S 35

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

West, continuing the tangent on the S. bdy. of sec. 34, which bears S. 89° 58.2' W.

Over low rolling sand dunes.

40.00

Point for the standard $\frac{1}{4}$ sec. cor. of sec. 34, N. 4 lks. from the tangent.

Set an iron post, 36 ins. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

S C

 $\frac{1}{4}$ S 34


1954

deposit broken glass alongside the iron post, for witness.

62.50

Intersect the Colorado River Indian Reservation boundary.

Point for the closing standard cor. of sec. 34, N. 5 lks. from the tangent.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

deposit broken glass alongside the iron post, for witness.

From the above intersection point, the standard ^{closing} cor. of sec. 34, T. 9 N., R. 19 W., for the Colorado River Indian Reservation, set and marked as described in the official record, bears N. 18° 23' E., 1.80 chs. dist.

From the same point, the 43rd mile cor. of the Colorado River Indian Reservation bdy., set and marked as described in the official record, bears N. 18° 23' E., 38.83 chs. dist.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

Subdivision of T. 8 N., R. 19 W.

Chains

Beginning the subdivisional survey at the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the township.

N. 0° 01' W., bet. secs. 35 and 36.

Over low gravel ridges.

15.00

Leave gravel ridges.

26.60

Enter overflow bottom of Bouse wash, bears E. and W., thence across a series of channels, some scattered ironwood and palo verde.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S 35 | S 36

1954

deposit broken glass alongside the iron post, for witness.

44.93

Leave overflow bottom of Bouse wash, bears E. and W.

47.50

State Highway No. 72, Bouse to Parker, bears E. and W.

49.40

Enter gravel ridges.

59.10

Powerline, bears E. and W.

68.30

Telephone line, bears E. and W.

68.85

Railroad, bears E. and W.

80.00

Point for the cor. of secs. 25, 26, 35, and 36.

Set an iron post, 36 ins. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 8 N R 19 W

S 26 | S 25

S 35 | S 36

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and gravel ridges.

Soil, sandy clay.

Timber, scattered; underbrush, ocotillo and cacti.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the township.

N. 89° 58' W., bet. secs. 25 and 36.

Over low gravel ridges.

40.02

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

Set an iron post, 36 ins. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

BOOK 4492

Subdivision of T. 8 N., R. 19 W.

Chains

S 25

 $\frac{1}{4}$

S 36

1954

deposit broken glass alongside the iron post, for witness.

80.04

The cor. of secs. 25, 26, 35, and 36.

Land, low rolling gravel ridges.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 25 and 26.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$

S 26 | S 25

1954

deposit broken glass alongside the iron post, for witness.

80.00

Set an iron post, 36 ins. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 8 N R 19 W

S 23 | S 24

S 26 | S 25

1954

deposit broken glass alongside the iron post, for witness.

Land, low sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 19, 24, 25, and 30.

N. 89° 57' E., bet. secs. 24 and 25.

Over low gravel ridges.

19.99

Enter sand hills.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.

Set an iron post, 36 ins. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

S 24

 $\frac{1}{4}$

S 25

1954

deposit broken glass alongside the iron post, for witness.

80.00

The cor. of secs. 23, 24, 25, and 26.

BOOK 4492

Subdivision of T. 8 N., R. 19 W.

Chains

Land, low gravel ridges.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 23 and 24.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\frac{1}{4}$$

S 23		S 24
1954		

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 13, 14, 23, and 24.

Set an iron post, 36 ins. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 8 N R 19 W	
S 14	S 13
S 23	S 24
1954	

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp.

West, bet. secs. 13 and 24.

Over gravel flats.

39.99

Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.

Set an iron post, 36 ins. long., 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$$\frac{1}{4}$$

S 13
S 24
1954

deposit broken glass alongside the iron post, for witness.

79.98

The cor. of secs. 13, 14, 23, and 24.

Land, low gravel flats.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 14 and 13.

Over low rolling sand dunes.

Subdivision of T. 8 N., R. 19 W.

Chains

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\frac{1}{4}$$

S 14		S 13
------	--	------

1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 11, 12, 13, and 14.

Set an iron post, 36 ins. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 8 N R 19 W

S 11		S 12
------	--	------

S 14		S 13
------	--	------

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 7, 12, 13, and 18.

West, bet. secs. 12 and 13.

Over low rolling sand dunes.

39.99

Point for the $\frac{1}{4}$ cor. sec. of secs. 12 and 13.

Set an iron post, 36 ins. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$$\frac{1}{4}$$

S 12

S 13

1954

deposit broken glass alongside the iron post, for witness.

79.98

The cor. of secs. 11, 12, 13, and 14.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0°01' W., bet. secs. 11 and 12.

Over low rolling sand dunes.

10.60

Enter gravel flats.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of T. 8 N., R. 19 W.

Chains

$$\frac{1}{4}$$

S 11	S 12
1954	

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 1, 2, 11, and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 19 W	
S 2	S 1
S 11	S 12
1954	

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and gravel flats.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.

S. $89^{\circ} 59'$ W., bet. secs. 1 and 12.

Over low rolling sand dunes.

40.03

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\frac{1}{4} \frac{S 1}{S 12}$$

1954

deposit broken glass alongside the iron post, for witness.

80.06

The cor. of secs. 1, 2, 11, and 12.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. $0^{\circ} 01'$ W., bet. secs. 1 and 2.

Over low rolling sand dunes and scattered brush.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\frac{1}{4}$$

S 2	S 1
1954	

deposit broken glass alongside the iron post, for witness.

69.60

Intersect the second standard parallel north.

Subdivision of T. 8 N., R. 19 W.

Chains

Point for the closing cor. of secs. 1 and 2, T. 8 N., R. 19 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N R 19 W

S 36

S 2 | S 1

GC

T 8 N R 19 W

1954

deposit broken glass alongside the iron post, for witness.

From this intersection point the standard cor. of secs. 35 and 36, T. 9 N., R. 19 W., heretofore described, bears West, 17.36 chs. dist.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

At a point midway between the closing cors. of secs. 1 and 6, T. 8 N., Rs. 18 and 19 W., and of secs. 1 and 2, T. 8 N., R. 19 W., point for the $\frac{1}{4}$ sec. cor. of sec. 1.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 1

1954

deposit broken glass alongside the iron post, for witness.

From the above point, the standard $\frac{1}{4}$ sec. cor. of sec. 36, bears West 17.385 chs. dist.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp.

N. $0^{\circ} 01'$ W., bet. secs. 34 and 35.

Over low rolling sand dunes.

16.50 S. bank of Bouse wash, course W., enter scattered timber along the wash, bears E. and W.

22.64 N. bank of Bouse wash, leave timber; enter gravel flats, bears E. and W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 34 | S 35

1954

deposit broken glass alongside the iron post, for witness.

46.30 State Highway No. 72, Bouse to Parker, bears E. and W.

BOOK 4492

Subdivision of T. 8 N., R. 19 W.

Chains

50.00

Enter gravel ridges.

61.50

Powerline, bears E. and W.

80.00

Point for the cor. of secs. 26, 27, 34, and 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 19 W

S 27 | S 26

S 34 | S 35

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 25, 26, 35, and 36.

West, bet. secs. 26 and 35.

Over low rolling sand dunes.

39.96

Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 26

 $\frac{1}{4}$

S 36

1954

deposit broken glass alongside the iron post, for witness.

72.70

Railroad, bears NW. and SE.

74.50

Telephone line, bears NW. and SE.

79.92

The cor. of secs. 26, 27, 34, and 35.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. $0^{\circ} 01'$ W., bet. secs. 26 and 27.

Over low rolling sand dunes.

1.60

Telephone line, bears NW. and SE.

2.20

A.T. and S.F. railroad, bears NW. and SE.

36.59

Transmission line and road, bears N. 8° E. and S. 8° W.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.

Set an iron post, 36 ins. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S 27 | S 26

1954

Subdivision of T. 8 N., R. 19 W.


Chains

80.00

deposit broken glass alongside the iron post, for witness.

Point for the cor. of secs. 22, 23, 26, and 27.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.
Soil, sandy clay, and gravel.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 23, 24, 25, and 26.


West, bet. secs. 23 and 26.

Over low rolling sand dunes.

39.95

Point for the 1/4 sec. cor. of secs. 23 and 26.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



1954

deposit broken glass alongside the iron post, for witness.

73.50

The cor. of secs. 22, 23, 26, and 27.

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 22 and 23.

Over low rolling sand dunes.

40.00

Point for the 1/4 sec. cor. of secs. 22 and 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 14, 15, 22, and 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

BOOK 4492

Subdivision of T. 8 N., R. 19 W.

Chains

T 8 N R 19 W
 S 15 | S 14
 S 22 | S 23
 1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.
 Soil, sandy clay.
 Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 13, 14, 23, and 24.

N. 89° 59' W., bet. secs. 14 and 23.

Over low rolling sand dunes and gravel flats.

39.94 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.

Set an iron post, 36 ins. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

S 14
 $\frac{1}{4}$
 S 23
 1954

deposit broken glass alongside the iron post, for witness.

62.38 Power line, N. 8° E., S. 8° W.

62.78 Road, bears N. 8° E., S. 8° W.

79.88 The cor. of secs. 14, 15, 22, and 23.

Land, low rolling sand dunes.
 Soil, sandy clay.
 Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 14 and 15.

Over low rolling sand dunes, gravel flats.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 15 | S 14
 1954

deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 10, 11, 14, and 15.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 19 W
 S 10 | S 11
 S 15 | S 14
 1954

.Subdivision of T. 8 N., R. 19 W.

Chains

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and gravel flats.
Soil, gravel and sandy clay.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 11, 12, 13, and 14.

West, bet. secs. 11 and 14.

Over low rolling sand dunes and gravel flats.

39.97

Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 11

$\frac{1}{4}$

S 14

1954

deposit broken glass alongside the iron post, for witness.

51.30

Transmission line, bears N. 8° E. and S. 8° W.

51.80

Road, bears N 8° E & S 8° W

60.00

Leave sand hills, enter gravel flats, bears N. and S.

79.94

The cor. of secs. 10, 11, 14, and 15.

Land, low rolling sand dunes and gravel flats.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

N. 0° $01'$ W., bet. secs. 10 and 11.

Over low rolling sand dunes and gravel flats.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 10 | S 11

1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 2, 3, 10, and 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 19 W

S 3 | S 2

S 10 | S 11

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and gravel flats.
Soil, sandy clay and gravel.
Timber, none; underbrush, ocotillo and cacti.

BOOK 4492

Subdivision of T. 8 N., R. 19 W.

Chains

From the cor. of secs. 1, 2, 11, and 12.

West, bet. secs. 2 and 11.

Over low rolling sand dunes, gravel flats and scattered brush.

39.94 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{r} S 2 \\ \frac{1}{4} \\ \hline S 11 \\ 1954 \end{array}$$

deposit broken glass alongside the iron post, for witness.

40.00 Transmission line, bears N. 8° E. and S. 8° W.40.50 Road, bears N. 8° E. and S. 8° W.

79.88 The cor. of secs. 2, 3, 10, and 11.

Land, low rolling sand dunes and gravel flats.
Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. $0^{\circ} 01'$ W., bet. secs. 2 and 3.

Over low rolling sand dunes and gravel flats.

35.00 Enter sand dunes, leave gravel flats.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
$$\begin{array}{r} \frac{1}{4} \\ S 3 \quad | \quad S 2 \\ 1954 \end{array}$$

deposit broken glass alongside the iron post, for witness.

69.55 Intersect the 2nd standard parallel north.

Point for the closing cor. of secs. 2 and 3, T. 8 N., R. 19 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{r} T 9 N R 19 W \\ S 35 \\ \hline S 3 | S 2 \\ CC \\ T 8 N R 19 W \\ 1954 \end{array}$$

deposit broken glass alongside the iron post, for witness.

From this cor. the standard cor. of secs. 34 and 35, T. 9 N., R. 19 W., heretofore described, bears west, 17.50 chs. dist.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

Subdivision of T. 8 N., R. 19 W.

Chains

At a point midway between the closing cor. of secs. 1 and 2; and secs. 2 and 3, T. 8 N., R. 19 W.; point for the $\frac{1}{4}$ sec. cor. of sec. 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 2
1954

deposit broken glass alongside the iron post, for witness.

From the above $\frac{1}{4}$ sec. cor. point, the standard $\frac{1}{4}$ sec. cor. of sec. 35, bears West 17.45 chs. dist.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the township.

N. $0^{\circ} 02' W.$, bet. secs. 33 and 34.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S 33 | S 34

1954

deposit broken glass alongside the iron post, for witness.

42.50

Gravel ridge, bears E. and W.

54.00

S. bank of Bouse wash, bears E. and W.

73.00

N. bank of Bouse wash, bears E. and W.

78.00

Leave gravel ridges, enter sand dunes, bears E. and W.

80.00

Point for the cor. of secs. 27, 28, 33, and 34.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 19 W

S 28 | S 27

S 33 | S 34

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 26, 27, 34, and 35.

West, bet. secs. 27 and 34.

Over low rolling sand dunes.

Subdivision of T. 8 N., R. 19 W.

Chains

5.00	Transmission line, S. and N. 8° E., with road.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{r} S 27 \\ \frac{1}{4} \text{ ---} \\ S 34 \\ 1954 \end{array}$ deposit broken glass alongside the iron post, for witness.
66.30	Power line, bears NW. and SE.
66.79	State Highway No. 72, Bouse to Parker, bears NW. and SE.
79.98	The cor. of secs. 27, 28, 33, and 34. Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.
	N. 0° 02' W., bet. secs. 27 and 28. Over low rolling sand dunes and gravel ridges.
10.49	State Highway No. 72 Bouse to Parker, bears NW. and SE.
10.89	Powerline, NW. and SE.
26.44	Telephone line, NW. and SE.
27.00	A.T. and S.F. railroad, bears NW. and SE.
29.90	Wash, 30 lks wide, 2 ft. deep, course SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{r} \frac{1}{4} \\ S 28 \mid S 27 \\ 1954 \end{array}$ deposit broken glass alongside the iron post, for witness.
80.00	Point for the cor. secs. 21, 22, 27, and 28. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\begin{array}{r} T 8 N R 19 W \\ S 21 \mid S 22 \\ \text{---} \\ S 28 \mid S 27 \\ 1954 \end{array}$ deposit broken glass alongside the iron post, for witness. Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.
	From the cor. of secs. 22, 23, 26, and 27. West, bet. secs. 22 and 27.

Subdivision of T. 8 N., R. 19 W.

Chains

Over low rolling sand dunes.

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 22
$\frac{1}{4}$ ———
S 27
1954

deposit broken glass alongside the iron post, for witness.

79.98 The cor. of secs. 21, 22, 27, and 28.

Land, low rolling sand dunes and gravel ridges.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

N. 0° 02' W., bet. secs. 21 and 22.

Over gravel ridges and flats.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
' S 21 S 22
1954

deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 15, 16, 21, and 22.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 19 W
S 16 S 15
—————
S 21 S 22
1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling gravel flats.
Soil, gravel sandy clay.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 14, 15, 22, and 23.

N. 89° 58' W., bet. secs. 15 and 22.

Over low rolling gravel ridges and flats.

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

BOOK 4492

Subdivision of T. 8 N., R. 19 W.

Chains

$$\begin{array}{r} S 15 \\ \frac{1}{4} \text{---} \\ S 22 \end{array}$$

1954

deposit broken glass alongside the iron post, for witness.

79.96

The cor. of secs. 15, 16, 21, and 22.

Land, low rolling gravel ridges and flats.
Soil, sandy and gravel.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 15, 16, 21, and 22.

West, bet. secs. 16 and 21.

Over gravel flats.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{r} S 16 \\ \frac{1}{4} \text{---} \\ S 21 \end{array}$$

1954

deposit broken glass alongside the iron post, for witness.

76.40

Intersect Colorado River Indian Reservation bdy.

Point for the closing cor. of secs. 16 and 21.

Set an iron post, 36 ins. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T 8 N \\ R 19 W \\ \hline S 16 \quad CC \\ S 21 \end{array}$$

1954

deposit broken glass alongside the iron post, for witness.

From above intersection point, the closing cor. for secs. 17 and 20, T. 8 N., R. 19 W., C.R.I.R. subdivision, set and marked as described in the official record, bears S. $18^{\circ} 23' W.$, 9.12 chs. dist.

Land, low rolling gravel ridges and flats.
Soil, sandy and gravel.
Timber, none; underbrush, ocotillo and cacti.

N. $0^{\circ} 02' W.$, bet. secs. 15 and 16.

Over gravel flats.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} \\ S 16 \quad | \quad S 15 \end{array}$$


1954

Subdivision of T. 8 N., R. 19 W.

Chains	deposit broken glass alongside the iron post, for witness.
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	$\begin{array}{r} T\ 8\ N\ R\ 19\ W \\ S\ 9\ \ S\ 10 \\ \hline S\ 16\ \ S\ 15 \\ .1954 \end{array}$
	deposit broken glass alongside the iron post, for witness.
	<p>Land, low gravel flats.</p> <p>Soil, sandy and gravel.</p> <p>Timber, none; underbrush, ocotillo and cacti.</p>
	From the cor. of secs. 10, 11, 14, and 15.
	West, bet. secs. 10 and 15.
	Over low rolling gravel flats.
39.98	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	$\begin{array}{r} S\ 10 \\ \frac{1}{4} \text{---} \\ S\ 15 \\ .1954 \end{array}$
	deposit broken glass alongside the iron post, for witness.
50.00	Enter gravel ridges.
79.96	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, low rolling gravel flats and gravel ridges.</p> <p>Soil, sandy and gravel.</p> <p>Timber, none; underbrush, ocotillo and cacti.</p>
	From the cor. of secs. 9, 10, 15, and 16.
	West, bet. secs. 9 and 16.
40.00	<p>Point for the $\frac{1}{4}$ cor. of secs. 9 and 16.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	$\begin{array}{r} S\ 9 \\ \frac{1}{4} \text{---} \\ S\ 16 \\ .1954 \end{array}$
	deposit broken glass alongside the iron post, for witness.
49.78	<p>Intersect the Colorado River Indian Reservation bdy.</p> <p>Point for the closing cor. of secs. 9 and 16.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of T. 8 N., R. 19 W.

Chains



deposit broken glass alongside the iron post, for witness.

From the above intersection point, the closing cor. of secs. 8 and 17 on the E. bdy. of the Colorado Indian Reservation, marked and set as described in the official record, bears S. 18° 23' W., 9.18 chs. dist.

From this same point, the 40 mile cor. on the Colorado River Indian Reservation bdy., marked and set as described in the official record, bears S. 18° 23' W., 43.74 chs. dist.

Land, low rolling gravel ridges.
Soil, sandy clay and gravel.
Timber, none; underbrush, ocotillo and cacti.

N. 0° 02' W., bet. secs. 9 and 10.

Over low rolling sand dunes.

40.00

Point for the 1/4 sec. cor. of secs. 9 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 3, 4, 9, and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes and gravel ridges.
Soil, sand and gravel.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 2, 3, 10, and 11.

S. 89° 58' W., bet. secs. 3 and 10.

Over gravel valley and sand dunes.

39.97

Point for the 1/4 sec. cor. of secs. 3 and 10.

Subdivision of T. 8 N., R. 19 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 3

 S 10
 1954

deposit broken glass alongside the iron post, for witness.

79.94 The cor. of secs. 3, 4, 9, and 10.

Land, low rolling sand dunes and gravel valley.

Soil, sandy clay and gravel.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 3, 4, 9, and 10.

West, bet. secs. 4 and 9.

Over low rolling sand dunes and gravel ridges.

23.16 Intersect the Colorado River Indian Reservation bdy.

Point for the closing cor. of secs. 4 and 9.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 19 W
 S 4
 S 9
 1954

deposit broken glass alongside the iron post, for witness.

From this cor. the closing cor. of secs. 4 and 9 of the Colorado River Indian Reservation, marked and set as described in the official record, bears S. $18^{\circ} 23'$ W., 9.17 Chs. dist.

From this same cor. the 41 mile cor. on the Colorado River Indian Reservation bdy, marked and set as described in the official record, bears S. $18^{\circ} 23'$ W., 48.03 chs. dist.

Land, low rolling sand dunes and ridges.

Soil, sandy and gravel.

Timber, none; underbrush, ocotillo and cacti.

N. $0^{\circ} 02'$ W., bet. secs. 3 and 4.

Over low rolling sand dunes.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 4 | S 3
 1954

deposit broken glass alongside the iron post, for witness.

BOOK 4492

Subdivision of T. 8 N., R. 19 W.

Chains

69.45

Intersect the second standard parallel north.

Point for the closing cor. of secs. 3 and 4, T. 8 N., R. 19 W.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 9 N	R 19 W
S 34	

S 4	S 3
CC	

T 8 N	R 19 W
-------	--------

1954

deposit broken glass alongside the iron post, for witness.

From this cor. the standard closing cor. of sec. 34, T. 9 N., R. 19 W., on the Colorado River Indian Reservation bdy., heretofore described, bears West .07 lks. dist.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

At a point midway between the closing cors. of secs. 2 and 3, and secs. 3 and 4, T. 8 N., R. 19 W., point for the $\frac{1}{4}$ sec. cor. of sec. 3.Set an iron post 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 3

1954

deposit broken glass alongside the iron post, for witness.

From the above $\frac{1}{4}$ sec. cor. point, the standard $\frac{1}{4}$ sec. cor. of sec. 34, bears West 17.535 chs. dist.

Beginning at the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the township.

N. 0° 02' W., bet. secs. 32 and 33.

Over gravel flats and gravel ridges:

30.00

Enter gravel ridges.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 32 S 33

1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 28, 29, 32, and 33.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N	R 19 W
S 29	S 28
S 32	S 33

1954

Subdivision of T. 8 N., R. 19 W.

Chains	<p>deposit broken glass alongside the iron post, for witness.</p> <p>Land, gravel flats and gravel ridges. Soil, sandy and gravel. Timber, none; underbrush, ocotillo and cacti.</p>
11.00	<p>From the cor. of secs. 27, 28, 33, and 34. West, bet. secs. 28 and 33. Over low gravel ridges and gravel flats. End of gravel ridges.</p>
14.60	NE. bank of Bouse wash, bears WNW.
39.00	<p>Point for the witness $\frac{1}{4}$ sec. cor. of secs. 28 and 33. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \frac{1}{4} \text{ W } \text{ S } 28 \\ \hline \text{C } \text{ S } 33 \\ 1954 \end{array}$
40.00	<p>deposit broken glass alongside the iron post, for witness. True point for $\frac{1}{4}$ sec. cor. of secs. 28 and 33 falls in main channel of Bouse wash.</p>
58.30	W. bank of wash, bears ESE. and WNW.
80.00	<p>The cor. of secs. 28, 29, 32, and 33. Land, low gravel ridges and gravel flats. Soil, sandy clay. Timber, none; underbrush, ocotillo and cacti.</p>
8.40	Wash, 30 lks. wide, 4 ft. deep, course N.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{S } 29. \\ \hline \frac{1}{4} \\ \text{S } 32 \\ 1954 \end{array}$
49.70	<p>deposit broken glass alongside the iron post, for witness. Intersect the Colorado River Indian Reservation bdy. Point for the closing cor. of secs. 29 and 32. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T } 8 \text{ N} \\ \text{C} / \text{R } 19 \text{ W} \\ \text{R} / \text{S } 29 \\ \text{I} / \text{S } 32 \\ \text{R} / 1954 \end{array} \text{CC}$
	<p>deposit broken glass alongside the iron post, for witness.</p>

BOOK 4492

Subdivision of T. 8 N., R. 19 W.

Chains

From above intersection the closing cor. of secs. 30 and 31, on the E. bdy. of the Colorado River Indian Reservation, marked and set as described in the official record, bears S. 18° 22' W., 8.82 chs. dist.

From this same point the 37 mile cor. on the E. bdy. of the Colorado River Indian Reservation, marked and set as described in the official record, bears S. 18° 22' W., 30.70 chs. dist.

Land, low gravel ridges.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 02' W., bet. secs. 28 and 29.

Over low rolling gravel ridges.

8.30 Top of spur, bears NE.

10.00 End of gravel ridges.

22.30 S. bank of Bouse wash, course W., enter scattered timber.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 29 | S 28

1954

deposit broken glass alongside the iron post, for witness.

44.80 N. bank of Bouse wash, bears W.

45.00 Enter gravel flats.

64.99 Enter low gravel ridges.

80.00 Point for the cor. of secs. 20, 21, 28, and 29.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 19 W

S 20 | S 21

S 29 | S 28

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling gravel ridges and flats.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 21, 22, 27, and 28.

S. 89° 57' W., bet. secs. 21 and 28.

Over gravel ridges.

39.99 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.

Subdivision of T. 8 N., R. 19 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 21

$\frac{1}{4}$ ———
S 28

1954

deposit broken glass alongside the iron post, for witness.

57.43

A.T. and S.F. railroad, bears NW. and SE.

58.10

Telephone line, bears NW. and SE.

61.80

State Highway No. 72 Bouse to Parker, bears NW. and SE.

65.80

Power line, NW. and SE.

79.98

The cor. of secs. 20, 21, 28, and 29.

Land, low rolling gravel ridges.

Soil, gravel and sand.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 20, 21, 28, and 29.

West, bet. secs. 20 and 29.


Over low gravel ridges.

23.04

Intersect the Colorado River Indian Reservation bdy.

Point for the closing cor. of secs. 20 and 29.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

From above intersection the closing cor. of secs. 20 and 29, on the E. bdy. of the Colorado River Indian Reservation, marked and set as described in the official record, bears S. $18^{\circ} 22'$ W., 9.08 chs. dist.

From this same point the 36 mile cor. on the E. bdy. of the Colorado River Indian Reservation marked and set as described in the official record, bears S. $18^{\circ} 22'$ W., 35.17 chs. dist.

Land, low rolling gravel ridges.

Soil, sandy and gravel.

Timber, none; underbrush, ocotillo and cacti.

N. $0^{\circ} 02'$ W., bet. secs. 20 and 21.

Over low rolling gravel ridges.

12.60

Wash, 30 lks wide, 2 ft. deep, course SW.

22.99

Power line, bears NW. and SE.

Subdivision of T. 8 N., R. 19 W.

Chains


29.69 State Highway No. 72, Bouse to Parker, bears NW. and SE.

33.59 Telephone line, bears NW. and SE.

35.69 A.T. and S.F. railroad, bears NW. and SE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.




deposit broken glass alongside the iron post, for witness.

69.29 Intersect the Colorado River Indian Reservation.

Point for the closing cor. of secs. 20 and 21.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

From above intersection the closing cor. of secs. 17 and 20, on the E. bdy., marked and set as described in the official record, bears N. $18^{\circ} 23'$ E., 2.22 chs. dist.

From this same point the 39 mile cor. on the E. bdy. of the Colorado River Indian Reservation, marked and set as described in the official record, bears S. $23'$ W., 28.09 chs. dist.

Land, low rolling gravel ridges.

Soil, sandy clay and gravel.

Timber, none; underbrush, ocotillo and cacti.

General Description

This fractional township consists of rolling gravel ridges and benches, with scattered sand dunes, bisected by numerous dry sand washes. There is scattered paloverde along some of the washes. The other vegetation is cacti, greasewood and very sparse grass. The township is bisected by the A. T. & S. F. Railroad and State Highway No. 72.

No one is living within the township boundaries.

BOOK 4492

CERTIFICATE OF CADASTRAL ENGINEER

I, Fred R. Chappell, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of Oct., 1952, I have surveyed the North Boundary and completed the subdivision of T. 8 N., R. 19 W.

of the G & S R Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

May 24, 1955

Fred R. Chappell
Fred R. Chappell
Cartographic Aid

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., MAY 2 1956, 19

The foregoing field notes of the survey of the North Boundary and the completion of the subdivision of T. 8 N., R. 19 W. of the Gila and Salt River Meridian of Arizona.

executed by Fred R. Chappell

having been critically examined and found correct, are hereby approved.

Carl G. Harrington
Chief, Division of Cadastral Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.