

(1)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of

the survey

of

the West Boundary

and

a portion of the subdivision

of

T. 9 N., R. 17 W.

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Fred R. Chappell- Cartographic Aid

Under special instructions dated Oct. 9, 1952, which provided
for the surveys included under Group No. 285, approved Oct. 21, 1952.
and assignment instructions dated Feb. 2, 1953.

Survey commenced Jan. 12, 1954

Survey completed Feb. 2, 1954

4493

3
3
4
4

BOOK 4493

INDEX DIAGRAM

Township 9 N., Range 17 W.

4	6	5	4	9	3	13	2	12	1	
						14				
3	7	8	9	8	10		11		12	
			12							
3	18	17	11	16	7	15	14		13	
			11							
2	19	20	21	7	22		23		24	
1	30	29	28	6	27		26		25	
		10							5	
1	31	10	32	9	33	6	34	35	5	36

16

T. 9 N., R. 17 W.

Chains

The north and east boundaries of the township were surveyed by Harris in 1915 and 1916. The field notes of the survey of the 2nd Standard Parallel North, south boundary of T. 9 N., R. 17 W., are contained in the notes of the survey of T. 8 N., R. 17 W., heretofore written under Group 285.

For the test on the instruments and chains, see the notes for T. 8 N., R. 17 W. The geographic position of the southeast cor. of T. 9 N., R. 17 W. is Latitude $34^{\circ}04'12''$ N. and Longitude $113^{\circ}58'30''$ W.

West Boundary of T. 9 N., R. 17 W.

From the standard cor. of Ts. 9 N., Rs. 17 and 18 W.

N. $0^{\circ}02'$ E., bet. secs. 31 and 36.

Over low rolling sand dunes.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36:

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 36 | S 31

1954

deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N	
R 18 W	R 17 W
S 25	S 30
S 36	S 31

1954

deposit broken glass alongside the iron post, for witness.

Land, sand dunes.

Soil, sandy clay.

Timber, none: underbrush, ocotillo, cacti and greasewood.

N. $0^{\circ}02'$ E., bet. secs. 25 and 30.

Over low rolling sand dunes.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 25 | S 30

1954


deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 19, 24, 25 and 30.

West Boundary of T. 9 N., R. 17 W.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo, cacti and greasewood.

N. 0° 02' E., bet. secs. 19 and 24.

Over low rolling sand dunes.


35.00 Leave sand dunes; enter gravel valley

38.30 Wash, 76 lks. wide, 2 ft. deep, drains NW.; enter scattering paloverde and ironwood trees.

40.00 True point for the ¼ sec. cor. falls in a wash, 33 lks. wide, 3 ft. deep, drains W.

40.50 Point for the witness ¼ sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

50.00 Enter ironwood trees.

51.90 Left bank of wash, drains W.


55.90 Right bank of wash.

64.30 Wash, drains SW., 10 lks. wide, 1 ft. deep.

65.50 Enter gravel flats, leave ironwood trees.

80.00 Point for the cor. of secs. 13, 18, 19 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



1954

deposit broken glass alongside the iron post, for witness.

West Boundary of T. 9 N., R. 17 W.

Chains

Land, sand dunes and gravel valleys and ridges.
 Soil, sandy gravel
 Timber, ironwood and paloverde; underbrush, ocotillo, cacti and greasewood.

N. 0° 02' E., bet. secs. 13 and 18.

Over gravel flats.

15.00 Enter ironwood trees.

16.60 Left bank of wash, drains W.

20.90 Right bank of wash.

38.80 Wash, drains W., 20 lks. wide, 2 ft. deep.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top with brass cap mkd.

$\frac{1}{4}$

S 13 | S 18

1954

43.50 Road, bears S. 45° W. and N. 45° E.

70.00 Begin ascent, asc. 46 ft. to cor.

80.00 Point for the cor. of secs. 7, 12, 13 and 18.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top with brass cap mkd.

T 9 N

R 18 W | R 17 W

S 12 | S 7

S 13 | S 18

1954

Land, gravel flats and rocky hills.
 Soil, sandy gravel, and stony.
 Timber, paloverde and ironwood; underbrush, ocotillo, cacti and greasewood.

N. 0° 02' E., bet. secs. 7 and 12.

Over rocky and mountainous slope.

10.00 Ascend 115 ft. over S. slope.

31.47 Top of ascent.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top with brass cap mkd.

$\frac{1}{4}$

S 12 | S 7

1954

West Boundary of T. 9 N., R. 17 W.

Chains									
45.00	Continue ascent, asc. 200 ft. over S. slope.								
69.64	Top of ridge, bears E. and W.; desc. 20 ft. over N. slope.								
72.52	Bottom of descent; asc. 19 ft. over S. slope.								
76.61	Top of ascent; desc. 43 ft. to cor.								
80.00	Point for the cor. of secs. 1, 6, 7 and 12.								
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top with brass cap mkd.								
	<table border="1"> <tr><td colspan="2">T 9 N</td></tr> <tr><td>R 18 W</td><td>R 17 W</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td>S 12</td><td>S 7</td></tr> </table> <p>1954</p>	T 9 N		R 18 W	R 17 W	S 1	S 6	S 12	S 7
T 9 N									
R 18 W	R 17 W								
S 1	S 6								
S 12	S 7								
	Land, rocky and mountainous. Soil, stony. Timber, none; underbrush, scattering cacti.								
	N. 0° 02' E., bet. secs. 1 and 6.								
	Over rocky ridge.								
	Descend 268 ft. over N. slope.								
17.59	Wash, 10 lks. wide, 3 ft. deep, drains E.								
20.17	Bottom of descent; asc. 166 ft. over S. slope.								
38.87	Top of ascent. Thence along E. slope.								
40.00	Point for the ¼ sec. cor. of secs. 1 and 36.								
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table border="1"> <tr><td colspan="2">¼</td></tr> <tr><td>S 1</td><td>S 6</td></tr> </table> <p>1954</p>	¼		S 1	S 6				
¼									
S 1	S 6								
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.								
75.30	Begin ascent, asc. 21 ft. over S. slope.								
77.57	Top of ascent; desc. 20 ft. to cor.								
80.11	The cor. of Ts. 9 and 10 N., Rs. 17 and 18 W., which is monumented with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in official record.								
	Land, rocky and mountainous. Soil, stony. Timber, none; underbrush, scattering cacti.								

Partial Subdivision of T. 9 N., R. 17 W.

Chains

Beginning the subdivisional survey at the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., previously described.

N. 0° 01' W., bet. secs. 35 and 36.

Over sand dunes.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 35 | S 36
1954

deposit broken glass alongside the iron post, for witness.

60.00 Leave sand dunes; enter gravel flats.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N R 17 W
S 26 | S 25
S 35 | S 36
1954

deposit broken glass alongside the iron post, for witness.

Land, sand dunes and gravel flats.

Soil, rocky loam.

Timber, none; underbrush, ocotillo, cacti and greasewood.

From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., which is monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as described in official record.

N. 89° 59' W., bet. secs. 25 and 36.

Over sand dunes.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 25
S 36

deposit broken glass alongside the iron post, for witness.

80.00 The cor. of secs. 25, 26, 35 and 36.

Land, sand dunes.

Soil, rocky loam.

Timber, none; underbrush, ocotillo, cacti and greasewood.

Partial Subdivision of T. 9 N., R. 17 W.

Chains	From the standard cor. of secs. 33 and 34 on the S. bdy. of the Tp., previously described.
	N. 0° 02' W., bet. secs. 33 and 34.
	Over sand hills.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$
	S 33 S 34
	1954
	deposit broken glass alongside the iron post, for witness.
70.00	Leave sand dunes; enter gravel flats.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 N R 17 W
	S 28 S 27
	S 33 S 34
	1954
	deposit broken glass alongside the iron post, for witness.
	Land, sand hills and gravel flats.
	Soil, rocky loam.
	Timber, none; underbrush, ocotillo, cacti and greasewood.
	N. 0° 02' W., bet. secs. 27 and 28.
	Over gravel flats, through scattering ironwood trees.
14.50	Wash, drains W., 20 lks. wide, 1 ft. deep.
22.30	Left bank of wash, 1.40 chs. wide, 3 ft. deep, drains W.
23.70	Right bank of wash.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$
	S 28 S 27
	1954
	deposit broken glass alongside the iron post, for witness.
70.90	Wash, drains W., 50 lks. wide, 2 ft. deep.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Partial Subdivision of T. 9 N., R. 17 W.

Chains

T 9 N R 17 W

S 21	S 22
S 28	S 27

1954

deposit broken glass alongside the iron post, for witness.

Land, gravel flats.

Soil, rocky loam.

Timber, ironwood; underbrush, ocotillo, cacti and greasewood.

N. 0° 02' W., bet. secs. 21 and 22.

Over gravel flats, through scattering ironwood trees.

2.10 Wash, drains W., 15 lks. wide, 1 ft. deep.

38.00 Leave gravel flats; enter small rolling sand hills.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$

S 21 | S 22

1954

deposit broken glass alongside the iron post, for witness.

48.00 Leave sand hills; enter gravel flats.

70.64 Road, bears E. and W.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 9 N R 17 W

S 16	S 15
S 21	S 22

1954

Land, sand hills and gravel flats.

Soil, rocky loam.

Timber, ironwood; underbrush, ocotillo, cacti and greasewood.

N. 0° 02' W., bet. secs. 15 and 16.

Over gravel flats, through scattering ironwood trees.

27.20 Wash, drains SW., 20 lks. wide, 3 ft. deep.

30.00 Leave gravel flats; enter gravel ridges.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Partial Subdivision of T. 9 N., R. 17 W.

Chains

$$\frac{1}{4}$$

S 16		S 15
------	--	------

1954

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

53.00 Wash, drains SW., 30 lks. wide, 2 ft. deep.

80.00 Point for the cor. of secs. 9, 10, 15 and 16.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N	R 17 W
-------	--------

S 9		S 10
-----	--	------

S 16		S 15
------	--	------

1954

deposit a sandstone 3 x 4 x 1 ins., mkd. X alongside the iron post, for witness.

Land, gravel flats and ridges.

Soil, rocky loam.

Timber, ironwood; underbrush, ocotillo, cacti and greasewood.

N. $0^{\circ} 02'$ W., bet. secs. 9 and 10.

Over gravel ridges.

7.10 Wash, drains SW., 20 lks. wide, 2 ft. deep.

31.70 Road, bears SW. and NE.

38.30 Wash, drains SW., 30 lks. wide, 1 ft. deep.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.
$$\frac{1}{4}$$

S 9		S 10
-----	--	------

1954

46.40 Wash, drains SW., 10 lks. wide, 2 ft. deep.

58.20 Road and transmission line, bears NW. and SE.

59.80 Transmission line and telephone line, bears NW. and SE.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N	R 17 W
-------	--------

S 4		S 3
-----	--	-----

S 9		S 10
-----	--	------

1954

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Partial Subdivision of T. 9 N., R. 17 W.

Chains

Land, gravel ridges.
Soil, rocky loam.
Timber, none; underbrush, ocotillo, cacti and greasewood.

N. 0° 12' E., bet. secs. 3 and 4.

Over gravel ridges.

17.60 Begin descent, desc. 29 ft. over N. slope.

22.58 Bottom of descent; asc. 112 ft. over S. slope.

40.00 Point for the 1/4 sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top with brass cap mkd.

1/4

S 4 | S 3

1954

41.88 Top of ridge; bears E. and W.; desc. 103 ft. over N. slope.

51.15 Bottom of descent; asc. 26 ft. over S. slope.

54.83 Top of ascent; desc. 17 ft. over N. slope.

59.82 Bottom of descent, asc. 37 ft. over S. slope.

62.05 Top of ascent, desc. 40 ft. over N. slope.

67.01 Bottom of descent.

68.51 Wash, drains W., 10 lks. wide, 2 ft. deep.

71.71 Ascend 35 ft. over S. slope.

80.15 The cor. of secs. 3, 4, 33 and 34, Ts. 9 and 10 N., R. 17 W., which is monumented with an iron post, 2 1/2 ins. diam., firmly set, marked and witnessed as described in official record.

Land, gravel ridges.
Soil, rocky loam.
Timber, none; underbrush, ocotillo, cacti and greasewood.

From the standard cor. of secs. 32 and 33 on the S. bdy. of the Tp., previously described.

N. 0° 02' W., bet. secs. 32 and 33.

Over low rolling sand dunes, through scattering brush and cacti.

40.00 Point for the 1/4 sec. cor. of secs. 32 and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4

S 32 | S 33

1954

deposit broken glass alongside the iron post, for witness.

Partial Subdivision of T. 9 N., R. 17 W.

Chains
80.00

Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N	R 17 W
S 29	S 28
S 32	S 33
1954	

deposit broken glass alongside the iron post, for witness.

Land, sand dunes.

Soil, rocky loam.

Timber, none; underbrush, ocotillo, cacti and greasewood.

From the standard cor. of secs. 31 and 32 on the S. bdy. of the Tp., previously described.

N. $0^{\circ} 03'$ W., bet. secs. 31 and 32.

Over low rolling sand dunes, through scattering brush and cacti.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 31 S 32
1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N	R 17 W
S 30	S 29
S 31	S 32
1954	

deposit broken glass alongside the iron post, for witness.

Land, sand dunes.

Soil, rocky loam.

Timber, none; underbrush, ocotillo, cacti and greasewood.

From the cor. of secs. 28, 29, 32 and 33.

N. $89^{\circ} 59'$ W., bet. secs. 29 and 32.

Over low rolling sand dunes.

39.99

Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$	S 29
	S 32

Partial Subdivision of T. 9 N., R. 17 W.

Chains

deposit broken glass alongside the iron post, for witness.

79.98 The cor. of secs. 29, 30, 31 and 32.

Land, sand dunes.

Soil, rocky loam.

Timber, none; underbrush, ocotillo, cacti and greasewood.

From the cor. of secs. 15, 16, 21 and 22.

West, bet. secs. 16 and 21.

Over gravel ridges.

15.00 Leave gravel ridges, enter gravel flats.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S 16} \\ \hline \text{S 21} \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

74.30 Road, bears N. and S.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{ccc} \text{T 9 N} & & \text{R 17 W} \\ \text{S 17} & | & \text{S 16} \\ \hline \text{S 20} & | & \text{S 21} \end{array}$$

$$\begin{array}{ccc} \text{S 17} & | & \text{S 16} \\ \hline \text{S 20} & | & \text{S 21} \end{array}$$

1954

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Land, gravel flats and ridges.

Soil, rocky loam.

Timber, none; underbrush, ocotillo, cacti and greasewood.

N. 0° 02' W., bet. secs. 16 and 17.

Over gravel flats.

.70 Wash, drains W., 50 lks. wide; 3 ft. deep.

5.00 Road, bears NW. and SE.

14.20 Wash, drains SW., 20 lks. wide, 2 ft. deep.

32.80 Wash, drains SW., 10 lks. wide, 2 ft. deep.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S 17} \\ \hline \text{S 16} \end{array}$$

1954

Partial Subdivision of T. 9 N., R. 17 W.

Chains
 45.00 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
 Leave gravel flats; asc. 12 ft. over gravel ridges.
 53.39 Wash, drains SSW., 10 lks. wide, 1 ft. deep.
 55.55 Road, bears SSW. and NNE.
 71.50 Continue ascent, asc. 28 ft. over S. slope of ridge.
 74.96 Top of ascent.
 80.00 Point for the cor. of secs. 8, 9, 16 and 17.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T 9 N . R 17 W

S 8	S 9
S 17	S 16

1954

Land, gravel flats and ridges.
 Soil, rocky loam.
 Timber, none; underbrush, ocotillo, cacti and greasewood.

From the cor. of secs. 9, 10, 15 and 16.
 West, bet. secs. 9 and 16.
 Over gravel ridges, through scattering trees.
 23.20 Wash, drains S., 20 lks. wide, 2 ft. deep.
 35.00 Left bank of wash, course SW.
 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 9
S 16

50.00 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
 Right bank of wash.
 75.00 Begin ascent, asc. 37 ft. over E. slope.
 78.15 Top of gravel ridge; descend 26 ft. to cor.
 80.00 The cor. of secs. 8, 9, 16 and 17.
 Land, gravel ridges.
 Soil, rocky loam.
 Timber, paloverde and ironwood; underbrush, ocotillo, cacti and greasewood.

From the cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the Tp., which is monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as described in official record.

S. 00 01' E., bet. secs. 1 and 2.

Partial Subdivision of T. 9 N., R. 17 W.

Chains

- Over mountain ridges.
- 40.05 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at the computed position, if the Tp. was completely subdivided.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, and in a mound of stone to top with brass cap mkd.
- $\frac{1}{4}$
S 2 | S 1
1954
- From the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, desc. 178 ft. over broken S. slope to wash.
- 67.05 Wash, drains SW.; desc. 17 ft. to cor.
- 80.05 Point for the cor. of secs. 1, 2, 11 and 12, at the computed position, if the Tp. was completely subdivided.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top with brass cap mkd.
- T 9 N R 17 W
S 2 | S 1
S 11 | S 12
1954
- Land, mountainous.
Soil, rocky.
Timber, none; underbrush, scattering cacti.
- From the cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the Tp., which is monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as described in official record.
- S. 0° 01' E., bet. secs. 2 and 3.
- Ascend 464 ft. over N. slope of ridge to top of spur.
- 19.73 Top of spur, slopes NW.; desc. 173 ft. over S. slope of ridge.
- 20.72 Top of spur, slopes SW.
- 28.61 Ascend 39 ft. over N. slope of spur.
- 34.28 Top of spur, slopes SW.; desc. 31 ft. to cor.
- 40.10 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at the computed position, if the Tp. was completely subdivided.
- Set an iron post, 36 ins. long, 1 in. diam., 6 ins. in the ground to solid rock, and in a mound of stone to top with brass cap mkd.
- $\frac{1}{4}$
S 3 | S 2
1954
- 40.60 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
- 40.60 Descend 349 ft. over S. slope to cor.

Partial Subdivision of T. 9 N., R. 17 W.

Chains
80.10

Point for the cor. of secs. 2, 3, 10 and 11, at the computed position, if the Tp. was completely subdivided.

Set an iron post, 36 ins. long, 1 in. diam., 16 ins. in the ground to solid rock, and in a mound of stone to top with brass cap mkd..

T 9 N R 17 W

S 3	S 2
S 10	S 11

1954

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, mountainous.

Soil, rocky

Timber, none; underbrush, scattering cacti.

From the cor. of secs. 1, 2, 11 and 12.

West, bet. secs. 2 and 11.

Descend 20 ft. over W. slope of mountain to wash.

6.90 Wash, 4 chs. wide, 4 ft. deep, drains S.; asc. 213 ft. over broken slope to top of spur.

35.30 Top of spur, slopes N.; desc. 98 ft.

35.30 Top of spur, slopes N.; desc. 98 ft. over broken slope to cor.

40.05 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, and in a mound of stone to top with brass cap mkd.

S 2

 $\frac{1}{4}$ S 11

1954

From the $\frac{1}{4}$ sec. cor., asc. 49 ft. over broken slope to ridge.

43.10 Ridge, bears N. and S.; desc. 290 ft. over W. slope to wash.

60.00 Wash, 60 lks. wide, 20 ft. deep; asc. 124 ft. to top of spur.

73.25 Top of spur, slopes S.; desc. 93 ft. over W. slope to cor.

80.10 The cor. of secs. 2, 3, 10 and 11.

Land, mountainous

Soil, rocky

Timber, none; underbrush, scattering cacti.

General Description

Most of the land and soil found in the northern portion of T. 9 N., R. 17 W. is rocky shale peaks. The soil in the southern portion of the township is almost straight sand. There is cacti, ocotillo, and greasewood throughout most of the township. There is scattered paloverde and ironwood along the banks of washes in portions of the township. The lack of water and rainfall prohibits the use of the land to any extent. Occasionally there is sufficient rain in the fall and winter to establish feed for livestock. There is a road, power line and wash crossing E. and W. through the township. There is no one living within the boundaries of the township. The magnetic declination is $14\frac{1}{2}^{\circ}$ E.

15

BOOK 4493

4-680
(Feb., 1960)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Earl Paddock	Notes
Ray Garcia	Flagman
Abencio Crespín	Chainman
Fernando Chavez	Truckdriver

16-68505-2

16

BOOK 4493

CERTIFICATE OF CADASTRAL ENGINEER

I, Fred R. Chappell, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th. day of Oct., 52,

I have surveyed the West Boundary and a portion of the subdivision of
T. 9 N., R. 17 W.

of the G & S R Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

May 24, 1955

Fred R. Chappell
Fred R. Chappell
Cartographic Aid

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., MAY 2 1956, 19

The foregoing field notes of the survey of the West Boundary and a portion of the
subdivision of T. 9 N., R. 17 W., of the Gila and Salt River Meridian of Arizona

executed by Fred R. Chappell

having been critically examined and found correct, are hereby approved.

Earl G. Harrington
Chief, Division of Cadastral Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.