

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original
FIELD NOTES

of

the survey

of

the East Boundary

and

completion of the subdivision

of

Township 9 North, Range 19 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald E. Harding-Cadastral Engineer

Under special instructions dated Oct. 9, 1952, which provided

for the surveys included under Group No. 285, approved Oct. 21, 1952

and assignment instructions dated Feb. 2, 1953

Survey commenced Jan. 15, 1954

Survey completed Feb. 1, 1954

4495

1A

BOOK 4495

INDEX DIAGRAM

Township 9 N., Range 19 W.

				17	17	13		
6	5	4	3	17	2	12	1	4
					12		11	
7	8	9	10		11	10	12	3
					10		9	
18	17	16	15		14	8	13	2
					8		7	
19	20	21	22		23	6	24	2
				16				
				16			6	
30	29	28	27	15	26	5	25	1
				14			5	
31	32	33	34	14	35	5	36	1

T. 9 N., R. 19 W.

Chains

The north boundary of the township is the south boundary of T. 10 N., R. 19 W., which was resurveyed by Harris in 1915.
The east boundary of the Colorado River Indian Reservation was resurveyed by Guy P. Harrington in 1912.
The south boundary or the 2nd Standard Parallel North is contained in the notes for T. 8 N., R. 19 W. The lat. of the SE. cor. of the township is $34^{\circ}04'12''$ N., long. is $114^{\circ}10'58''$ W. Mag. decl. $14\frac{1}{2}^{\circ}$ E.

East Boundary of T. 9 N., R. 19 W.

From the standard township corner of T. 9 N., Rs. 18 and 19 W. North, bet. secs. 31 and 36.
Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 36 and 31.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S. 36 | S 31

1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 25, 30, 31, and 36.

Set an iron post 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N

R 19 W | R 18 W

S 25 | S 30

S 36 | S 31

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

North, bet. secs. 25 and 30.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ cor. of secs. 25 and 30.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$

S 25 | S 30

1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 19, 24, 25, and 30.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

BOOK 4495

E. Bdy., T. 9 N., R. 19 W.

Chains	
	<p style="text-align: center;">T 9 N R 19 W R 18 W S 24 S 19 S 25 S 30 1954</p> <p>deposit broken glass along side the iron post, for witness.</p>
	<p>Land, low rolling sand dunes. Soil, sandy clay. Timber, none; underbrush, ocotille and cacti.</p>
	<p>North, bet. secs. 19 and 24. Over low rolling sand dunes.</p>
3.40	Descend 34 ft. from a sand dune, bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 19. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <p style="text-align: center;">$\frac{1}{4}$ S 24 S 19 1954</p> <p>deposit broken glass alongside the iron post, for witness.</p>
42.20	Leave sand dunes; enter gravel ridges, bears E. and W.
53.01	Wash, 22 lks. wide, 5 ft. deep, course SW.
67.17	Over rough rocky ridges, scattered brush and paloverde.
79.47	Wash, 22 lks. wide, 4 ft. deep, course S. 80° W.
80.00	Point for the cor. of secs. 13, 18, 19, and 24. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 9 N R 19 W R 18 W S 13 S 18 S 24 S 19 1954</p> <p>Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land, low rolling sand dunes and gravel ridges. Soil, sandy clay and gravel. Timber, none; underbrush, ocotille and cacti.</p>
40.00	<p>North, bet. secs. 13 and 18. Asc. 161 ft. over S. slope of a lava covered mountain. Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, in a mound of stone to top, with brass cap mkd.</p>

. E. Bdy., T. 9. N., R. 19 W.

Chains

$$\frac{1}{4}$$

S 13	S 18
------	------

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Ascend 459 ft. over rocky SW. slope.

73.80

Rocky ridge, bears NW. and SE.; desc. 99 ft. over NE. slope under cliff.

80.00

Point for the cor. of secs. 7, 12, 13, and 18.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a mound of stone to the top, with brass cap mkd.

T 9 N	
R 19 W	R 18 W
S 12	S 7
S 13	S 18

1954

A cross (X), 6 ins. long, 1 in. deep, on E. face of cliff, bears West 8 lks. dist.

Land, rocky covered ridges.

Soil, rocky clay.

Timber, none; underbrush, cacti, sparse grass.

North, bet. secs. 7 and 12.

Desc. 650 ft. over broken NE. slope to the cor.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
$$\frac{1}{4}$$

S 12	S 7
------	-----

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Across level bench.

52.20

Road, NW. and SE.

54.60

Left bank of flat wash, course NW.

58.60

Osborne Wash, drains NW.

62.60

Right bank of flat wash,

80.00

Point for the cor. of secs. 1, 6, 7, and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N	
R 19 W	R 18 W
S 1	S 6
S 12	S 7

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

E. Bdy., T. 9.N., R. 19 W.

Chains

Land, mountainous.
Soil, gravel and rocky clay.
Timber, none; underbrush, ocotillo and cacti.

North, bet. secs. 1 and 6.

Over low rolling ridges.

19.40 Crossing deep, rough draws, draining W.

27.19 Bottom of wash, 30 lks. wide, 4 ft. deep, bears NW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$

S 1 | S 6

1954

Raise a mound of stone 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.44.40 Wash, 10 lks. wide, 4 ft. deep, course S. 80° W.

55.59 Wash, 22 lks. wide, 5 ft. deep, course W.

65.91 Wash, 20 lks. wide, 3 ft. deep, course W.

70.05 Wash, 75 lks. wide, 2 ft. deep, course W.

81.58 Intersect the S. bdy. of T. 10 N., R. 19 W.

Point for the closing cor. of Ts. 9 N., Rs. 18 and 19 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a mound of stone to the top, with brass cap mkd.

T 10 N R 19 W

S 36

S 1 | S 6

CC

T 9 N R 19 W

1954

From this point the cor. for Ts. 9 and 10 N., Rs. 18 and 19 W., bears E. 15.58 chs. dist. and is monumented by an iron post, 3 ins. diam., firmly set, and marked as described in the official record.

This cor. will now refer to Ts. 10 N., Rs. 18 and 19 W. only, therefore

I delete the markings and remark the iron post.

T 10 N

R 19 W | R 18 W

S 36 | S 31

S 1

T 9 N R 19 W

1954

Land, rocky ridges.
Soil, rocky clay.
Timber, none; underbrush, ocotillo and cacti.

Subdivision of T. 9 N., R. 19 W.

Chains

Beginning the subdivisional survey at the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp.

N. 0° 01' W., bet. secs. 35 and 36.

Over low sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 35 | S 36
1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 25, 26, 35, and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N R 19 W
S 26 | S 25
S 35 | S 36
1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp.

S. 89° 58' W., between secs. 25 and 36.

Over low rolling sand dunes.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 25
S 36
1954

deposit broken glass alongside the iron post, for witness.

80.00

The cor. of secs. 25, 26, 35, and 36.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 25 and 26.

Over low rolling sand dunes.

10.30

Transmission line, bears N. 8° E., S. 8° W., and road.


Subdivision of T. 9 N., R. 19 W.

Chains

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.




deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 23, 24, 25, and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.


From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of Tp. N. 89° 59' W., bet. secs. 24 and 25.

Over low rolling sand dunes.

40.01

Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

70.25

Transmission line and road, bears N. 8° E. and S. 8° W.

80.02

The cor. of secs. 23, 24, 25, and 26.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 23 and 24.

Over low rolling sand dunes, through scattered brush.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

absor bus ..

Subdivision of T. 9 N., R. 19 W.

Chains

$\frac{1}{4}$
 S 23 | S 24

1954

deposit broken glass alongside the iron post, for witness.

58.70 Road, bears E. and W.

64.80 Base of mountain, bears E. and W.; asc. 218 ft. over SE. slope.

80.00 Point for the cor. of secs. 13, 14, 23, and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N R 19 W

S 14 | S 13

S 23 | S 24

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp. N. $89^{\circ} 58'$ W., bet. secs. 13 and 24.

Over rocky ridges and spurs sloping S.; asc. 29 ft. over SE. slope.

15.88 Top of spur, bears S.; desc. 32 ft. over W. slope.

33.06 Wash, bears SW.; 10 lks. wide, 2 ft. deep.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 13

$\frac{1}{4}$
S 24

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

44.00 Wash, 75 lks. wide, 8 ft. deep, course S. 10° W.

47.50 Road, bears NE. and SW.; asc. 101 ft. over SSE. slope.

58.98 Power line, bears N. 8° E. and S. 8° W.

64.79 Top of sandrock spur, slopes S.; thence across series of spurs.

68.27 Top of spur, slopes S.

70.96 Top of spur, slopes S.; desc. 30 ft. over W. slope.

72.96 Bottom of wash, 10 lks wide, 2 ft. deep, course S.; asc. 116 ft. over ESE. slope.

80.00 The cor. of secs. 13, 14, 23, and 24.

Subdivision of T. 9 N., R. 19 W.

Chains

Land, low rolling sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 13, 14, 23, and 24.

West, bet. secs. 14 and 23.

Asc. 99 ft. over SE. slope of lava covered mountains.

13.46 Top of spur, slopes S. from the mountain; asc. 94 ft. over S. slope of mountain.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, in a mound of stone to top, with brass cap mkd.

$$\begin{array}{r} S 14 \\ \frac{1}{4} \text{ ---} \\ S 23 \\ 1954 \end{array}$$


Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Desc. 357 ft. over SW. slope of mountain.

62.60 Intersect the Colorado River Indian Reservation bdy.

Point for the closing cor. of secs. 14 and 23.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, E. of cor.

From the point of intersection, the closing cor. of secs. 14 and 23 from the west, on the E. bdy. of the Colorado River Indian Reservation, established by Guy Harrington during the subdivision of that Indian reservation in 1912, bears N. $18^{\circ} 23'$ E., 1.46 chs. dist.

From the same point, the 46 mile cor. on the Colorado River Indian Reservation bdy., set and marked as described in the official record, bears N. $18^{\circ} 23'$ E., 25.46 chs. dist.

Land, mountainous, rocky.
Soil, rocky clay.
Timber, none; underbrush, ocotillo and cacti.

N. $0^{\circ} 01'$ W., bet. secs. 13 and 14.

Asc. 205 ft. over rocky SE. slope of mountain.

14.60 Spur, slopes ENE., desc. 177 ft. over N. slope.

26.23 Rocky gully, course East; asc. 141 ft. over SE. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.

BOOK 4495

Subdivision of T. 9 N., R. 19 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

S 14 S 13

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Asc. 39 ft. over E. slope.

45.00 Slope changes to NE., desc.

45.50 Top of cliff, 30 ft. high, bears NW. and SE.; desc. 125 ft. over NE. slope.

59.40 Wash, in bottom of rocky gorge, course NE.; desc. 152 ft. over NE. slope.

80.00 Point for the cor. of secs. 11, 12, 13, and 14.

Set an iron post 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T 9 N R 19 W

S 11 | S 12

S 14 | S 13

1954

Land, mountainous.

Soil, rocky clay.

Timber, none; underbrush, cootille and cacti.

From the sec. cor. of secs. 7, 12, 13, and 18, on the E. bdy.

N. $89^{\circ} 58'$ W., bet. secs. 12 and 13.

Over top of mountain with rocky ledges; asc. 99 ft. over ledges and cliffs.

3.30 Ridge, bears NW. and SE.; desc. 650 ft. over rocky WSW. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a mound of stone to the top, with brass cap mkd.

S 12

S 13

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Desc. 33 ft. over W. slope.

61.67 Wash, 3 ft. deep, 35 lks. wide, course NNW.; asc. 56 ft. over E. slope.

65.27 Transmission line and road, bears NNW. and SSE.

69.10 Rocky gully, bears N.; asc. 10 ft. to the cor.

80.00 The cor. of secs. 11, 12, 13, and 14.

Subdivision of T. 9 N., R. 19 W.

Chains

Land, mountainous.
Soil, rocky clay.
Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 11, 12, 13, and 14

West, bet. secs. 11 and 14.

Over broken N. slope of mountain.

12.83 Wash, 15 lks. wide, 6 ft. deep, course N.; asc. 109 ft. over N. slope.

34.72 Wash, shallow, course N.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 11

S 14

1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Asc. 51 ft. over NE. slope.

45.60 Spur, slopes N., desc. 50 ft. over W. slope.

50.24 Intersect the Colorado River Indian Reservation bdy.

Point for the closing cor. of secs. 11 and 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 N

R 19 W

S 11

S 14

1954

deposit broken glass alongside the iron post, for witness.

From the point of intersection, the closing cor. of secs. 11 and 14 from the west on the E. bdy. of the Colorado River Indian Reservation, established by Guy Harrington, during the subdivision of that Indian reservation in 1912, bears S. 13°03' E., 1.46 chs. dist.

From this same point, the 47 mile cor. on the Colorado River Indian Reservation bdy., mkd. and set as described in the official record, bears N. 13°03' W., 21.59 chs. dist.

Land, rocky ledges and sand dunes.
Soil, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

N. 0°01' W., bet. secs. 11 and 12.

Desc. 79 ft. over gravel bench into rocky draw.

35.81 Wash, 35 lks. wide, 2 ft. deep, course NW.

BOOK 4495

Subdivision of T. 9 N., R. 19 W.

Chains

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- $\frac{1}{4}$
S 11 | S 12
1954
- Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
- 47.18 Transmission line and road, bears NNW. and SSE.
- 80.00 Point for the cor. of secs. 1, 2, 11, and 12.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 9 N R 19 W
S 2 | S 1

S 11 | S 12
1954
- Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
Land, gravel benches.
Soil, rocky loam.
Timber, paloverde; underbrush, ocotillo and cacti.
-
- From the cor. of secs. 1, 6, 7, and 12, on the E. bdy.
N. $89^{\circ}58'$ W., bet. secs. 1 and 12.
Over low gravel ridges and washes.
- 4.80 Road, graded, bears NW. and SE.
- 6.00 Enter Osborne draw, course N. 12° W.
- 20.00 Main channel of Osborne wash.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- $\frac{1}{4}$ S 1

S 12
1954
- Raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.
- 40.20 Asc. 54 ft., leave Osborne draw.
- 46.80 Wash, 30 lks. wide, 5 ft. deep, course N.
- 51.30 Wash, 25 lks. wide, 4 ft. deep, course N.
- 59.20 Wash, 10 lks. wide, 8 ft. deep, course N.
- 80.00 The cor. of secs. 1, 2, 11, and 12.

Subdivision of T. 9 N., R. 19 W.

Chains

Land, low gravel ridges.
Soil, gravel, sandy clay.
Timber, none; underbrush, ocotillo and cacti.

West, bet. secs. 2 and 11.


Over gravel bench, through scattered brush.

12.00 Transmission line, bears NNW. and SSE.

36.50 Road, bears SE. and NW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.




deposit broken glass alongside the iron post, for witness.

68.80 Intersect the Colorado River Indian Reservation bdy.

Point for the closing cor. of secs. 2 and 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

From the point of intersection, the closing cor. of secs. 2 and 11 from the west, on the E. bdy. of the Colorado River Indian Reservation, established by Guy Harrington, during the subdivision of that Indian reservation in 1912, bears S. $13^{\circ} 03' E.$, 1.55 chs. dist.

From this same point the 48 mile cor. on the Colorado River Indian Reservation bdy. marked and set as described in the official record, bears N. $13^{\circ} 03' W.$, 19.37 chs. dist.

Land, level bench.
Soil, sandy and gravelly clay.
Timber, none; underbrush, ocotillo and cacti.


N. $0^{\circ} 01' W.$, bet. secs. 1 and 2.

Over gravel bench.

8.50 Road, graded, bears E. and W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



BOOK 4495

Subdivision of T. 9 N., R. 19 W.

Chains

deposit broken glass alongside the iron post, for witness.

44.40 Edge of breaks, bears N. 70° W. and S. 70° E.; desc. 63 ft. into Osborne draw.

47.10 South bank of Osborne Wash.

58.92 Wash, center of main channel, 6 ft. deep, 50 lks. wide, course N. 70° W. N. 70° W.

69.82 N. bank of wash, bears WNW. and ESE.; asc. 62 ft.

72.26 Top of breaks, N. of Osborne draw, bears WNW. and ESE.

81.60 Intersect the S. bdy. of T. 10 N., R. 19 W.

Point for the closing cor. of ~~secs. 1 and 2~~, T. 9 N., R. 19 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 N R 19 W

S 35

S 2 | S 1

C C

R 9 N R 19 W

1954

Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of cor.

From this point, the cor. of secs. 1, 2, 35, and 36, Ts. 9 and 10 N., R. 19 W., bears East, 15.57 chs. dist. and is monumented with an iron post, 3 ins. in diam., firmly set and marked as described in the official record.

This cor. will now refer to secs. 35 and 36; T. 10 N., R. 19 W., only, therefore

I delete the markings and remark the iron post.

T 10 N R 19 W

S 35 | S 36

S 1

T 9 N R 19 W

1915

Land, gravel benches and washes.

Soil, sandy and rocky.

Timber, none; underbrush, cootillo and cacti, sparse grass.

At a point mid-way between the closing cor. of secs. 1 and 2, and the closing Tp. cor. of secs. 1 and 6, T. 9 N., Rs. 18 and 19 W.; point for the ¼ sec. cor. of sec. 1

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼

S 1

1954

deposit broken glass alongside the iron post, for witness.

From this point the ¼ sec. cor. of sec. 36, bears East, 15.57 chs. dist.

Subdivision of T. 9 N., R. 19 W.

Chains

N. 0° 01' W., bet. secs. 34 and 35.

Over low rolling sand dunes, through scattered brush.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.


Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground; with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.00 Point for the cor. of secs. 26, 27, 34, and 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 25, 26, 35, and 36.


N. 89° 59' W., bet. secs. 26 and 35.

Over low rolling sand dunes.

1.50 Transmission line and road, bears N. 8° E. and S. 8° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

80.00 The cor. of secs. 26, 27, 34, and 35.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 26, 27, 34, and 35.

West, bet. secs. 27 and 34.

Over low rolling sand dunes.


Subdivision of T. 9 N., R. 19 W.

Chains

35.82

Intersect the Colorado River Indian Reservation bdy.

Point for the closing cor. of secs. 27 and 34.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

1954

deposit broken glass alongside the iron post, for witness.

From the point of intersection, the closing cor. of secs. 27 and 34 from the west, on the E. bdy. of the Colorado River Indian Reservation, established by Guy Harrington, during the subdivision of that Indian reservation in 1912, bears N. 18° 23' E., 1.69 chs. dist.

From this same point the 44 mile cor. on the Colorado River Indian Reservation bdy., marked and set as described in the official record, bears N. 18° 23' E., 34.32 chs. dist.

Land, low rolling sand dunes.


Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 26 and 27.

Over low rolling sand dunes.

40.00


Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

1954

deposit broken glass alongside the iron post, for witness.

80.00

Point for the cor. of secs. 22, 23, 26, and 27.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

1954

deposit broken glass alongside the iron post, for witness.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs., 23, 24, 25, and 26.

Subdivision of T. 9 N., R. 19 W.

Chains

N. 89° 57' W., bet. secs. 23 and 26.

Over low rolling sand dunes.

39.99 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 23
 $\frac{1}{4}$ —————
 S 26
 1954

deposit broken glass alongside the iron post, for witness.

79.98 The cor. of secs. 22, 23, 26, and 27.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

From the cor. of secs. 22, 23, 26, and 27.


West, bet. secs. 22 and 27.

Over low rolling sand dunes.

9.19 Intersect the Colorado River Indian Reservation bdy.

Point for the closing cor. of secs. 22 and 27.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

From the point of intersection, the closing cor. of secs. 22 and 27, from the west, on the E. bdy. of the Colorado River Indian Reservation, established by Guy Harrington, during the subdivision of that Indian reservation in 1912, bears N. 18° 23' E., 1.60 chs. dist.

From this same point the 45 mile cor. on the Colorado River Indian Reservation, marked and set as described in the official record, bears N. 18° 23' E., 29.92 chs. dist.

Land, low rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

N. 0° 01' W., bet. secs. 22 and 23.

Over low rolling sand dunes.


27.62 Intersect the Colorado River Indian Reservation bdy.

Point for the closing cor. of secs. 22 and 23.

Subdivision of T. 9 N., R. 19 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



deposit broken glass alongside the iron post, for witness.

From the point of intersection, the 45th mile cor. of the Colorado River Indian Reservation bdy., bears N. $18^{\circ} 23'$ E., 80 lks. dist.

Land, rolling sand dunes.

Soil, sandy clay.

Timber, none; underbrush, ocotillo and cacti.

At a point 40 chs. West in longitude of the closing cor. of secs. 1 and 2, T. 9 N., R. 19 W.

Point for the $\frac{1}{4}$ sec. cor. of sec. 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 2
1954

Raise a mound of stone 3 ft. base, $2\frac{1}{2}$ ft. high, S. of cor.

From this point the $\frac{1}{4}$ sec. cor. of sec. 35 bears East 15.57 chs. dist.

At a point 80 chs. West in longitude of the closing cor. of secs. 1 and 2.

Point for the closing cor. of secs. 2 and 3.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

T 10 N R 19 W
S 34

S 3 | S 2
CC
T 9 N R 19 W
1954

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, S. of cor.

From the above point the cor. of secs. 34 and 35, T. 10 N., R. 19 W., bears East, 15.57 chs. dist.

From the closing cor. of secs. 2 and 3.

S. $0^{\circ} 01'$ E., bet. secs. 2 and 3.

Over bottom of Osborne draw.

15.50 Leave draw, over gravel bench, bears N. 70° W. and S. 70° E.


35.51 Intersect Colorado River Indian Reservation bdy.

Subdivision of T. 9 N., R. 19 W.

Chains

Point for the closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

From above intersection point the 48th mile cor. of the Colorado River Indian Reservation bdy., bears S. $13^{\circ} 03'$ E., 30 chs. dist.

Land, gravel benches.

Soil, sandy and gravel.

Timber, none; underbrush, ocotillo and cacti.

General Description

The south half on this partial township is covered with sand dunes with cacti and ocotillo and very sparse grass. It is bisected with a transmission line from north to south and a track road under the line.

The south part of the north half is high lava covered mountains without vegetation. The extreme north part is bisected by the Osborne draw and wash and a graded road which is maintained. There is no water within the boundaries nor is there anyone living within this township.

20

BOOK 4495

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in
 pursuance of special instructions bearing date of the 9th. day of Oct., 1952,
 I have surveyed the East Boundary and a portion of the subdivision of T. 9 N., R. 19 W.

of the G & S R Meridian, in the State of Arizona, which are
 represented in the foregoing field notes as having been executed by me and under my direction; and that
 said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
 Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
 field notes.

May 25, 1955

Donald E. Harding
 Donald E. Harding
 Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
 Washington, D. C., MAY 2 1956, 19

The foregoing field notes of the survey of the East Boundary and a portion of the
subdivision of T. 9 N., R. 19 W. of the Gila and Salt River Meridian of Arizona.

executed by Donald E. Harding
 having been critically examined and found correct, are hereby approved.

Earl G. Harrington
 Chief, Division of Cadastral Engineering
 Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.