

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Dep. Resurvey of a Portion of the East Boundary

and a

Portion of the Subdivision

and

Survey of a Portion of the Subdivision

of

Township 16 North, Range 2 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald E. Harding, Cartographer

Leslie H. Godwin, Cartographer-Cadastral

Phil D. Smith, Cartographic Survey Aid

Under special instructions dated February 15 and March 20, 1956, which provided  
for the surveys included under Group No. 309, approved February 15 and March 20,  
1956  
and assignment instructions dated February 24, 1956

Survey commenced March 7, 1956

Survey completed April 5, 1956

4499

4499

112

BOOK 4499

# INDEX DIAGRAM

Township 16 North, Range 2 East

		33	25 24	14	10
6	5	32 4	24 8 24	13 2	9 1 3
		31			
7	8	31 9	22 10 23	12 11	8 12 2
		30	21	11	7
18	17	29 16	20 15 21	10 14	6 13 1
		29	18	5	
19	20	28 21	17 22 4 19	23	24
		27	17		
30	29	27 28	16 27	26	25
		26	15		
31	32	25 33	14 34	35	36

## Township 16 North, Range 2 East

Chains

The north boundary of the township, Fourth Standard Parallel North, was surveyed by J. B. McLaughlin in 1883. A dependent resurvey of the Fourth Standard Parallel North through Range 3 East, which includes a portion of the north boundary of section 1 of this township was executed by J. B. Wright in 1907-08. The few McLaughlin corners found were destroyed. A dependent resurvey of the south boundary of section 31, T. 17 N., R. 3 E., which constitutes a portion of the north boundary of section 1, T. 16 N., R. 2 E., and an independent resurvey of the Fourth Standard Parallel North through Range 2 East, was made by Donald E. Harding in 1956, under Group 310, Arizona. A portion of the east boundary was surveyed by J. B. Wright in 1907 and resurveyed by S. E. Blout in 1913. The south boundary, a portion of the east, and secs. 23, 24, 25, 26, 35 and 36 were surveyed by S. E. Blout in 1913.

This survey was requested by Mr. William A. Evans, Attorney at Law, 807 Title & Trust Building, Phoenix, Arizona, to accommodate applications for patent to approximately 200 placer mining claims.

The following notes are those of the dependent resurvey of the north three miles of the east boundary, the north and west boundary of section 23, and the survey of a portion of the subdivision.

The survey was executed with W. and L. E. Gurley transits, serial numbers 541329 and 541332, constructed in accordance with standard instrumental specifications of the Bureau of Land Management. The instruments were in good condition, placed in proper adjustment prior to the beginning of the survey.

The directions of all lines were determined by stellar observations and augmented by direct solars, and the measurements made by Inlufin steel tapes, 5 chains in length, graduated 1/10 link for the first 10 links, every link for the next 90 links and every 10 links for the balance. Tapes were tested by comparison with a standard tape and found correct. Measurements were made on the slope; the vertical angle of each interval was ascertained by clinometers in good adjustment. The horizontal equivalents only are entered in this field note record.

The geographic position of the southeast corner of this survey is latitude  $33^{\circ} 43' 15''$  N. and longitude  $112^{\circ} 06' 46''$  W., as determined from data shown on the official plat, approved July 27, 1914. The mean magnetic declination is  $16^{\circ} 30'$  E.

---

 Dependent Resurvey of the North Half of the East Boundary, T. 16 N., R. 2 E.
 

---

From the cor. of secs. 13 and 24, which is monumented with a 2 in. iron post, set, mkd. and witnessed, as described in the official record.

N.  $0^{\circ} 01'$  W., on the E. bdy. of sec. 13.

Over rolling grassy ridges.

Asc. 20 ft. over SE. slope.

4.10 Fence, bears E. and W.

4.80 U. S. Highway No. 89A, bears ENE. and SW.

5.20 Ridge, bears ENE. and SW.; desc. 162 ft. over NNW. slope.

6.50 Road, graded, bears N.  $80^{\circ}$  E. and S.  $80^{\circ}$  W.

13.00 Road, graded, bears E. and W.

## BOOK 4499

Dependent Resurvey, N.  $\frac{1}{2}$  of E. Bdy., T. 16 N., R. 2 E.

Chains	
13.14	Record distance for the cor. of secs. 19 and 30, T. 16 N., R. 3 E., falls in roadway. No remaining evidence of the original cor.
20.00	Wash, 20 lks. wide, 8 ft. deep, drains E.; asc. 30 ft. over S. slope.
25.45	Telephone line, bears NE. and SW.
27.00	Spur, low, slopes E.; desc. 65 ft. over N. slope.
33.00	Fence, bears E. and W.
40.00	The $\frac{1}{4}$ sec. cor. of sec. 13, which is monumented with a 1 in. I. P., set, mkd. and witnessed as described in the official record. Desc. 50 ft. over N. slope.
43.10	Wash, 40 lks. wide, 5 ft. deep, with stream of water, 3 ft. wide, 10 ins. deep, drains E.; asc. 105 ft. over S. slope.
46.50	Spur, slopes E.; desc. 55 ft. over NNE. slope.
53.13	The $\frac{1}{4}$ sec. cor. of sec. 19, monumented with a limestone, set, mkd., and witnessed as described in the official record.
62.50	Wash, drains NE.
73.50	Road, graded, bears ESE. and WNW.
80.00	The cor. of secs. 12 and 13, which is monumented with a 2 in. I. P., set, mkd. and witnessed as described in the official record. Land, rolling. Soil, sandy and gravelly. Vegetation, scattered greasewood, cacti, century plants and dense grass.
	N. 0° 01' W., on the E. bdy. of sec. 12. Over rolling grassy ridges. Desc. 100 ft. over NE. slope.
4.30	Railroad, bears E. and W., abandoned.
13.38	The cor. of secs. 18 and 19, T. 16 N., R. 3 E., which is monumented with a granite stone, set, mkd. and witnessed as described in the official record.
27.60	Wash, 40 lks. wide, 5 ft. deep, with a stream of water, 3 ft. wide, 6 ins. deep, drains E.
40.00	The $\frac{1}{4}$ sec. cor. of sec. 12, which is monumented with a 1 in. I. P., set, mkd., and witnessed as described in the official record.
49.60	Wash, 40 lks. wide, 10 ft. deep, drains E.; asc. 280 ft. over S. slope.
53.28	The $\frac{1}{4}$ sec. cor. of sec. 18, T. 16 N., R. 3 E., monumented with a limestone, set, mkd. and witnessed as described in the official record.
80.00	The cor. of secs. 1 and 12, which is monumented with a 2 in. I. P., set, mkd. and witnessed as described in the official record.

Dep. Resurvey, N.  $\frac{1}{2}$  of E. bdy., T. 16 N., R. 2 E.

Chains

Land, rolling.  
Soil, sandy and gravelly.  
Vegetation, scattered greasewood, cacti, century plants, and dense grass.

N. 0° 08' E., on the E. bdy. of sec. 1.

Over rolling grassy ridges.

Asc. 200 ft. over SSW. slope.

12.97

The cor. of secs. 7 and 18, T. 16 N., R. 3 E., monumented with a limestone, set, mkd. and witnessed as described in the official record.

23.50

Road, bladed. bears E. and W.

24.50

S. edge of flat-topped ridge.

40.00

The  $\frac{1}{4}$  sec. cor. of sec. 1, which is monumented with the stub of a 1 in. iron post, the broken part of the post lying alongside.

At the cor. point.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S1

1956

Raise a mound of stone,  $3\frac{1}{2}$  ft. base, 3 ft. high, W. of cor.

Asc. 80 ft. over S. slope.

52.50

Road, track, bears E. and W.

53.02

Record distance for the  $\frac{1}{4}$  sec. cor. of sec. 7, T. 16 N., R. 3 E.; no remaining evidence of the cor.

56.90

Ridge, bears ESE. and WNW.; desc. 70 ft. over N. slope.

70.30

S. rim of canyon, bears E. and W.; desc. 250 ft. over N. slope.

78.70

Wash, in canyon, 15 lks. wide, drains E.; asc. 40 ft. over S. slope.

80.00

Point for the N.  $\frac{1}{16}$  cor. of sec. 1.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

N  $\frac{1}{16}$

S 1

80

1956

Asc. 165 ft. over S. slope.

86.20

The closing cor. of Ts. 16 N., Rs. 2 and 3 E., which is monumented with a limestone, 24 x 12 x 3 ins., firmly set in a mound of stone, mkd. and witnessed as described in the official record.

At the cor. point.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

Dep. Resurvey, N. 1/2 of E. Bdy., T. 16 N., R. 2 E.

Chains

T17N R3E  
 S31  
 S 1 | S 7  
 R2E | R3E  
 C C  
 T16N  
 1956

Place the original cor. alongside the iron post.

Raise a mound of stone, 3 ft. base, 3 ft. high, S. of cor.

From above cor. point, the standard cor. of secs. 31 and 32, T. 17 N., R. 3 E., bears S. 89° 53' E., 13.36 chs. dist., mkd. with a 2 1/2 in. I.P., set, mkd. and witnessed as described in field notes of Land, rolling. T. 17 N., R. 3 E.  
 Soil, sandy and gravelly.  
 Vegetation, scattered greasewood, cacti, century plants and dense grass.

Dep. Resurvey of a Portion of the Subdivision, T. 16 N., R. 2 E.

The cor. of secs. 22, 23, 26 and 27 was destroyed in the construction of U. S. Highway No. 89A; therefore I reestablish the cor. in its true position from the record tie given in the mineral survey No. 3471, of Lode Claim No. 5 Fraction.

At the cor. point.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T16N R2E  
 S22 | S23  
 S27 | S26  
 1956

From the cor. point, cor. No. 1 of Lode Claim No. 5 Fraction bears S. 21° 49' W., 3.913 chs. dist.

Thence

N. 0° 10' W., bet. secs. 22 and 23.

0.60 U. S. Highway No. 89A, bears S. 60° W. and N. 10° E.; asc. 130 ft. over E. slope.

10.00 Enter outskirts of Jerome, Arizona.

11.35 Top of ridge; desc. 110 ft. over NE. slope.

19.40 Intersect end of street, bears N. 45° W.; desc. 35 ft. over NE. slope.

21.20 Recross U. S. Highway No. 89A, bears N. 70° W. and S. 70° E.; desc. 45 ft. over NE. slope.

24.00 Intersect end of street, bears N. 15° W.; desc. 25 ft. over NE. slope.

28.80 Street, bears N. 75° W.; desc. 5 ft.

Dep. Resurvey of a Portion of the Subdivision, T. 16 N., R. 2 E.

Chains						
31.40	Recross U. S. Highway No. 89A, bears S. 30° E. and N. 35° W.; desc. 20 ft. over NE. slope.					
32.65	Street, bears N. 40° W. and S. 40° E.; desc. 30 ft.					
39.50	Street, bears N. 65° W. and 200 ft. S. 65° E. to end.					
39.95	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of sec. 23, at proportionate distance; no remaining evidence of the original I. P.                      Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td style="border-right: 1px solid black; padding-right: 5px;"><math>\frac{1}{4}</math></td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S23</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">1956</td></tr> </table> </div> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.                      Desc. 140 ft. over N. slope.</p>	$\frac{1}{4}$	S23	1956		
$\frac{1}{4}$						
S23						
1956						
42.80	Telephone line, bears E. and W.					
44.40	Road, graded, bears E. and W.					
48.10	Wash, 20 lks. wide, 3 ft. deep, drains NE.; asc. 370 ft. over SE. slope.					
50.90	Road, graded, bears E. and W.					
53.00	Same road, bears E. and W.					
54.90	N. edge of Jerome, Arizona.					
60.60	Railroad, bears NE. and SW., abandoned.					
71.90	Spur, slopes N. 60° E.; desc. 170 ft. over rocky NW. slope.					
79.90	<p>The cor. of secs. 14, 15, 22 and 23, which is monumented with a 2 in. I.P.; set, mkd. and witnessed as described in the official record. As this cor. now functions for secs. 14 and 23 only, I remark the iron post</p> <div style="text-align: center;"> <table border="0"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">T16N R2E</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S22</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"><u>S14</u></td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S23</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">1956</td></tr> </table> </div> <p>Land, mountainous.                      Soil, rocky clay.                      Vegetation, scattered greasewood, cacti, century plants and grass.</p>	T16N R2E	S22	<u>S14</u>	S23	1956
T16N R2E						
S22						
<u>S14</u>						
S23						
1956						
	<p>From the cor. of secs. 13, 14, 23 and 24, which is monumented with a 2 in. I.P., set, mkd. and witnessed as described in the official record.</p>					
	S. 89° 47' W., bet. secs. 14 and 23.					
	Desc. 100 ft. over WNW. slope.					
7.00	Wash, 10 lks. wide, 4 ft. deep, drains N.; asc. 50 ft. over E. slope.					
14.40	Spur, slopes N. 30° E.; desc. 90 ft. over W. slope.					

## BOOK 4499

## Dep. Resurvey of a Portion of the Subdivision, T. 16 N., R. 2 E.

## Chains

- 26.50 Wash, 20 lks. wide, 4 ft. deep; drains NE.; asc. 250 ft. over E. slope.
- 39.98 The  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, which is monumented with an iron post, set, mkd. and witnessed as described in the official record.  
Asc. 240 ft. over E. slope.
- 48.70 Spur, slopes S.  $10^{\circ}$  E.; desc. 60 ft. over S. slope.
- 59.00 Head of draw, course S.  $70^{\circ}$  E.; asc. 295 ft. over SE. slope.
- 71.90 Railroad, bears N. and S., abandoned; asc. 100 ft. over E. slope.
- 75.10 Spur, slopes N.  $10^{\circ}$  E.; desc. 70 ft. over WNW. slope.
- 79.90 The cor. of secs. 14 and 23.  
Land, high rolling ridges.  
Soil, rocky and sandy clay.  
Vegetation, scattered greasewood, cacti, century plants and dense grass.

## Survey of a Portion of the Subdivision, T. 16 N., R. 2 E.

- From the cor. of secs. 13, 14, 23 and 24, which is monumented with a 2 in. I. P., set, mkd. and witnessed as described in the official record.
- N.  $0^{\circ} 01'$  E., bet. secs. 13 and 14.  
Desc. 220 ft. over NW. slope.
- 13.80 Wash, 20 lks. wide, 6 ft. deep, drains N.  $40^{\circ}$  E.
- 14.10 Road, graded, bears N.  $70^{\circ}$  E. and N.  $45^{\circ}$  W.; desc. 140 ft. over NW. slope.
- 20.30 Wash, 40 lks. wide, 8 ft. deep, drains N.  $75^{\circ}$  E.; asc. 70 ft. over S. slope.
- 25.30 Road, bladed, bears N.  $80^{\circ}$  E. and N.  $40^{\circ}$  W.; asc. 65 ft. over SE. slope.
- 26.70 Railroad, bears E. and W., abandoned.
- 38.00 Spur, slopes E.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 14.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$   
S14 | S13  
1956

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.  
From this cor., cor. No. 5 of Lode Claim Meadow Wash, Survey No. 3436, bears S.  $62^{\circ} 12'$  W., 1.25 chs. dist.



## Subdivision, T. 16 N., R. 2 E.

## Chains

Desc. over gentle ENE. slope.

41.50 Wash, 150 lks. wide, 12 ft. deep, drains N. 75° E.

48.40 Road, bladed, bears E. and W.; asc. 65 ft. over SE. slope.

69.20 Spur, slopes NE.; desc. 150 ft. over NW. slope.

74.60 Wash, 10 lks. wide, 4 ft. deep, drains NE.; asc. 105 ft. over SE. slope.

80.00 Point for the cor. of secs. 11, 12, 13 and 14.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T16N R2E

S11 | S12

S14 | S13

1956

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From this cor., cor. No. 4 of Lode Claim No. Thirty-three, Mineral Survey No. 3436, bears S. 0° 23' W., 17.63 chs. dist.

Land, high rolling.

Soil, sandy and rocky clay.

Vegetation, scattered greasewood, cacti, century plants and dense grass.

From the cor. of secs. 12 and 13, on the E. bdy. of the Tp.

N. 89° 54' W., bet. secs. 12 and 13.

Asc. over gentle E. slope.

7.80 Road, bladed, bears S. 25° E. and N. 25° W.

12.00 Wash, 1 ch. wide, 8 ft. deep, drains N. 10° E.

38.00 Railroad, bears NW. and S., abandoned.

40.11 Point for the ¼ sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

¼  $\frac{S12}{S13}$

1956

From this cor., cor. No. 4 of Lode Claim No. 11, identical to cor. No. 2 of Lode Claim No. 9, Mineral Survey No. 3436, bears N. 86° 03' E., 17.42 chs. dist.

Cor. No. 13 of Exchange Survey No. 666 bears S. 80° 18' W., 5.27 chs. dist.

50.40 Wash, 25 lks. wide, 6 ft. deep, drains N. 10° E.

56.80 Wash, 20 lks. wide, 4 ft. deep, drains N. 30° E.; asc. 220 ft. over SE. slope.

80.22 The cor. of secs. 11, 12, 13 and 14.

Subdivision, T. 16 N., R. 2 E.

## Chains

Land, rolling.  
Soil, sandy and rocky clay.  
Vegetation, scattered greasewood, cacti, century plants and dense grass.

N. 0° 01' E., bet. secs. 11 and 12.

Over rolling general E. slope.

.50 Spur, low, slopes NE.; desc. 230 ft. over NE. slope.

22.40 Road, bladed, bears N. 55° E. and S. 25° W.

27.40 Wash, 20 lks. wide, 1 ft. deep, drains N. 50° E.

33.30 Road, bladed, bears NE. and SW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 12.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S11 | S12 \\ | \\ 1956 \end{array}$$

Raise a mound of stone,  $3\frac{1}{2}$  ft. base, 3 ft. high, W. of cor.

Desc. 100 ft. over NE. slope.

58.00 Wash, 15 lks. wide, 4 ft. deep, drains NE.; asc. 180 ft. over SE. slope.

76.00 Spur, slopes E.; desc. 80 ft. over NE. slope.

80.00 Point for the cor. of secs. 1, 2, 11 and 12.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} T16N R2E \\ S 2 | S 1 \\ \hline S11 | S12 \\ 1956 \end{array}$$

Raise a mound of stone,  $3\frac{1}{2}$  ft. base, 3 ft. high, W. of cor.

Land, rolling.  
Soil, sandy and rocky clay.  
Vegetation, scattered greasewood, cacti, century plants and dense grass.

From the cor. of secs. 1 and 12 on the E. bdy. of the Tp.

N. 89° 56' W., bet. secs. 1 and 12.

Desc. 95 ft. over SW. slope.

15.90 Road, bladed, bears N. 70° W. and S. 70° E.

## Subdivision, T. 16 N., R. 2 E.

Chains

33.00

Road, bladed, bears NW. and SE.

34.20

Wash, 20 lks. wide, 6 ft. deep, drains SE.; asc. 50 ft. over E. slope.

40.06

Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 12.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} \text{ S } 1 \\ \hline \text{S } 12 \end{array}$$

1956

Asc. 260 ft. over NNE. slope.

80.12

The cor. of secs. 1, 2, 11, and 12.

Land, rolling.

Soil, sandy and gravelly clay.

Vegetation, scattered greasewood, cacti, century plants and dense grass.

N.  $0^{\circ} 01'$  E., bet, secs, 1 and 2.

Over rolling E. slope.

34.35

Road, bladed, bears N.  $60^{\circ}$  E. and S.  $60^{\circ}$  W.; also wash, 50 lks. wide, 6 ft. deep, drains N,  $70^{\circ}$  E.

40.00

Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 2.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} \\ \hline \text{S } 2 \text{ S } 1 \end{array}$$

1956

43.40

Wash, 25 lks. wide, 8 ft. deep, drains S.  $60^{\circ}$  E.

56.90

Road, bladed, bears N.  $30^{\circ}$  W. and S.  $30^{\circ}$  E.

57.80

Wash, 15 lks. wide, 4 ft. deep, drains S.  $80^{\circ}$  E.; asc. 100 ft. over ESE. slope.

80.00

Point for the N.  $1/16$  cor. of secs. 1 and 2.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 4 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
$$\begin{array}{r} \text{N } 1/16 \\ \hline \text{S } 2 \text{ S } 1 \end{array}$$

80

1956

86.33

Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 1 and 2, T. 16 N., R. 2 E.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
$$\begin{array}{r} \text{T17N R2E} \\ \text{S36} \\ \hline \text{S } 2 \text{ S } 1 \end{array}$$

C C

T16N R2E

1956

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, S. of cor.

## Subdivision, T. 16 N., R. 2 E.

## Chains

From this cor., the standard cor. of Ts. 17 N., Rs. 2 and 3 E., bears East 13.84 chs. dist., mkd. with a  $2\frac{1}{2}$  in. I.P., set, mkd. and witnessed as described in field notes of T. 17 N., R. 2 E.

Land, rolling.

Soil, sandy and gravelly clay.

Vegetation, scattered greasewood, cacti, century plants and dense grass.

At a point midway between the closing cor. of Ts. 16 N., Rs. 2 and 3 E. and the closing cor. of secs. 1 and 2, T. 16 N., R. 2 E.

Point for the  $\frac{1}{4}$  sec. cor. of sec. 1

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd:

$\frac{1}{4}$  S 1

1956

Raise a mound of stone,  $3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, S. of cor.

From above cor. point, the standard  $\frac{1}{4}$  sec. cor. of sec. 31, T. 17 N., R. 3 E., bears East, 13.61 chs. dist., mkd. with a  $2\frac{1}{2}$  in. I.P., set, mkd. and witnessed as described in field notes of T. 17 N., R. 3 E.

From the cor. of secs. 14 and 23.

N.  $0^{\circ} 01'$  E., on the W. bdy. of sec. 14.

Desc. 320 ft. over NNW. slope:

- 2.80 Railroad, bears NE. and SW., abandoned.
  - 8.60 Road, oiled, bears E. and W.
  - 9.40 Road, oiled, bears SE. and NW.
  - 18.40 Wash, 15 lks. wide, 3 ft. deep, with a small stream of water, drains NE.
  - 22.50 Spur, short, slopes NE.; desc. 200 ft. over N. slope.
  - 24.60 Wash, in canyon, drains E.; asc. 200 ft. over S. slope.
  - 27.60 N. rim of canyon; asc. 230 ft. over SE. slope.
  - 27.70 Railroad, bears NE. and SW., abandoned.
  - 39.50 Spur, slopes E.
  - 40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 14.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
- |  $\frac{1}{4}$   
| S 14
- 1956
- From this cor., the N C E of Lode Claim Republic, Mineral Survey No. 2811, bears S.  $80^{\circ} 15'$  E., 7.79 chs. dist.
- Desc. 150 ft. over ENE. slope.
  - 61.00 Head of draw, drains NE.; desc. 85 ft. over E. slope.
  - 70.00 Slope changes to N.; desc. 180 ft. over N. slope.
  - 75.00 Wash, 20 lks. wide, in canyon, drains NE.; asc. 170 ft. over S. slope.
  - 80.00 Point for the cor. of secs. 11 and 14.

## Subdivision, T. 16 N., R. 2 E.

## Chains

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T16N R2E

S15  $\frac{S11}{S14}$

1956

From this cor., cor. No. 12 of Exchange Survey No. 666, bears S.  $84^{\circ}$  E., 7.50 chs. dist.

Land, rolling.

Soil, sandy and gravelly clay.

Vegetation, scattered greasewood, cacti, century plants and dense grass.

From the cor. of secs. 11, 12, 13 and 14.

S.  $89^{\circ}$  48' W., bet. secs. 11 and 14.

3.00 Spur, slopes ENE., thence across N. slope.

4.80 Fence, bears N.  $70^{\circ}$  E. and S.  $70^{\circ}$  W.

12.10 Draw, drains NE.; asc. 150 ft. over SE. slope.

17.10 Spur, slopes NE.; desc. 70 ft. over NNW. slope.

26.70 Draw, drains NE.; asc. 240 ft. over ESE. slope.

37.60 Spur, slopes NNE.

39.94 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 14.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$   $\frac{S11}{S14}$

1956

From this cor., cor. No. 3 of Lode Claim Mary, Mineral Survey No. 3525, bears S.  $31^{\circ}$  52' W., 2.47 chs. dist.

Desc. 90 ft. over NW. slope.

47.70 Draw, drains N.  $10^{\circ}$  E.; asc. 190 ft. over E. slope.

55.30 Spur, slopes NE.; desc. 160 ft. over NW. slope.

65.90 Wash, 30 lks. wide, 10 ft. deep, drains NE.; asc. 370 ft. over ESE. slope.

79.88 The cor. of secs. 11 and 14.

Land, rolling.

Soil, sandy and gravelly clay.

Vegetation, scattered greasewood, cacti, century plants and dense grass.

## Subdivision, T. 16 N., R. 2 E.

## Chains

N. 0° 01' E., on the W. bdy. of sec. 11.

Asc. 20 ft. over SE. slope.

.90 Spur, slopes NE.; desc. 250 ft. over N. slope.

12.10 Wash, 10 lks. wide, in canyon, drains N. 80° E.; asc. 110 ft. over S. slope.

20.00 Spur, slopes E.; desc. 150 ft. over NNW. slope.

29.20 Wash, 20 lks. wide, 8 ft. deep, drains E.; asc. 250 ft. over S. slope.

37.20 Spur, slopes N. 70° E.; desc. 60 ft. over N. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 11.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

|  $\frac{1}{4}$   
S11  
1956

Raise a mound of stone,  $3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, E. of cor.

41.00 Wash, 10 lks. wide, 3 ft. deep, drains N. 70° E.; asc. 90 ft. over S. slope.

44.20 Road, track, bears NE. and SW.

50.00 Spur, slopes SE.; desc. 220 ft. over NE. slope.

56.70 Road, bears NE. and SW.

62.70 Wash, 10 lks. wide, 3 ft. deep, drains N. 60° E.; asc. 120 ft. over S. slope.

71.30 Spur, slopes NE.

73.50 Road, bears NE. and SW.; desc. 100 ft. over N. slope.

80.00 Point for the cor. of secs. 2 and 11.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T16N R2E  
S10 | S 2  
     | S11  
1956

Land, rolling.

Soil, sandy and gravelly clay.

Vegetation, scattered greasewood, cacti, century plants and dense grass.

From the cor. of secs. 1, 2, 11 and 12.

S. 89° 52' W., bet. secs. 2 and 11.

Asc. 230 ft. over general SE. slope.

## Subdivision, T. 16 N., R. 2 E.

## Chains

- 26.90 Spur, slopes SE.; desc. 110 ft. over S. slope.
- 39.98 Point for the  $\frac{1}{4}$  sec. cor. of secs. 2 and 11.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.  
$$\begin{array}{c} \frac{1}{4} \text{ S } 2 \\ \text{S } 11 \\ 1956 \end{array}$$
- Asc. 160 ft. over E. slope.
- 51.20 Ridge, low, bears ENE. and WSW.; desc. 70 ft. over NW. slope.
- 60.80 Wash, 30 lks. wide, 8 ft. deep, drains N. 35° E.
- 64.30 Same wash, drains S. 50° E. from NW.; asc. 230 ft. over NE. slope.
- 78.00 Spur, slopes NE.
- 79.96 The cor. of secs. 2 and 11.  
Land, rolling.  
Soil, sandy and gravelly clay.  
Vegetation, scattered greasewood, cacti, century plants and dense grass.
- 
- N. 0° 01' E. on the W. bdy. of sec. 2.  
Desc. 110 ft. over NNW. slope.
- 3.20 Curve in road, bears NW. and SW.
- 6.30 Wash, 15 lks. wide, 2 ft. deep, drains NE.
- 9.30 Wash, 25 lks. wide, 2 ft. deep, drains NE.
- 12.80 Road, bears NNE. and SSW.; asc. 432 ft. over S. slope.
- 24.60 Spur, slopes NE.; desc. 175 ft. across general E. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 2.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.  
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 2 \\ 1956 \end{array}$$
- 52.00 Wash, 30 lks. wide, 3 ft. deep, drains SE.; asc. 480 ft. over S. slope.
- 80.00 Point for the N. 1/16 cor. of sec. 2.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., over X cut in solid rock, and in a mound of stone to top, with brass cap mkd.  
$$\begin{array}{c} \text{N } 1/16 \\ \text{S } 2 \\ 80 \\ 1956 \end{array}$$
- 84.00 Ridge, bears NW. and SE.; desc. 15 ft. over NE. slope.
- 86.29 Intersect Fourth Standard Parallel North,  
Point for the closing cor. of secs. 2 and 3, T. 16 N., R. 2 E.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

Subdivision, T. 16 N., R. 2 E.

Chains

T17N R2E

S35

S 3 | S 2

C C

R16N R2E

1956

From above cor. point, the standard cor. of secs. 35 and 36 bears East, 13.78 chs. dist., mkd. with a 2 1/2 in. I. P., set, mkd. and witnessed as described in field notes of T. 17 N., R. 2 E.

Land, high and rolling.

Soil, sandy and gravelly clay.

Vegetation, scattered greasewood, cacti, century plants and dense grass.

At a point midway between the closing cors. of secs. 1 and 2 and 2 and 3, T. 16 N., R. 2 E.

Point for the 1/4 sec. cor. of sec. 2.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

1/4 S 2

1956

From above cor. point, the standard 1/4 sec. cor. of sec. 36, T. 17 N., R. 2 E., bears East 13.80 chs. dist., mkd. with a 2 1/2 in. I.P., set, mkd. and witnessed as described in field notes of T17N, R2E.

From the cor. of secs. 3, 4, 33, and 34, on the south boundary of the township, which is monumented with a 2 in. I.P., set, marked, and witnessed as described in the official record.

N. 0° 02' W.; bet. secs. 33 and 34.

Desc. 670 ft. over broken N. slope, through timber and dense undergrowth.

37.80

Road, graded, bears E. and W.

40.00

Point for the 1/4 sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., over X cut in solid rock, and in a mound of stone to top, with brass cap mkd.

1/4

S 33 | S 34

1956

from which

A ponderosa pine, 8 ins. diam., bears S. 44° E., 63 lks. dist., mkd. 1/4 S34 BT.

A ponderosa pine, 12 ins. diam., bears S. 79 1/4° W., 35 lks. dist., mkd. 1/4 S33 BT.

From above cor. point, cor. No. 3 of Three Sisters lode claim, Mineral Survey No. 1415, bears N. 41° 50' E., 7.40 chs. dist.

Desc. 59 ft. over N. slope.

43.50

Wash, 30 lks. wide, 2 ft. deep, course NE.; desc. 80 ft. over NE. slope.



## Subdivision, T. 16 N., R. 2 E.

## Chains

- 50.70 Wash, 20 lks. wide, 4 ft. deep, course NE.; asc. 30 ft. over S. slope.  
 57.10 Spur, low, slopes NE.; desc. 105 ft. over N. slope.  
 59.70 Road, graded, bears E, and W.  
 65.70 Same road, bears SE. and NW.  
 67.00 Corral and old buildings, bear East, 5 chs. dist.

68.00 Wash, in Mescal Gulch, 20 lks. wide, 6 ft. deep, course SE.; asc. 120 ft. over S. slope.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., over X cut in solid rock, and in a mound of stone to top, with brass cap mkd.

T16N R2E  
 S28|S27  
 S33|S34  
 1956

Land, mountainous.

Soil, clay loam.

Timber, ponderosa pine, red pine, pinon, and juniper.

Undergrowth, dense scrub oak, locus brush, buck brush, manzanite, and grass.

From the true point for the cor. of secs. 26, 27, 34 and 35, which is witnessed S.  $0^{\circ} 01'$  E., 0.20 lks. dist. by a 2 in. I.P., as described in the official record.

N.  $89^{\circ} 49'$  W., bet. secs. 27 and 34.

Over mountainous land, through timber and undergrowth.

5.70 Mescal Gulch, 30 lks. wide, 3 ft. deep, with stream 2 ft. wide and 6 ins. deep, drains NE.; asc. 840 ft. over E. slope.

12.00 Road, graded, bears NE. and SW.

26.80 Slope changes to S.

39.90 Point for the  $\frac{1}{4}$  sec. cor. of secs. 27 and 34.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$  S27  
 S34  
 1956

From above cor. point, cor. No. 4 of the Lone Pine lode claim, Mineral Survey No. 1615, bears N.  $86^{\circ} 15'$  W., 3166 chs. dist.; asc. 55 ft. over S. slope.

45.50 Spur, slopes S.; desc. 140 ft. over SW. slope.

53.60 Wash, 10 lks. wide, 2 ft. deep, course SW.; asc. 240 ft. over SE. slope.

65.00 Spur, slopes S.; desc. 105 ft. over SSW. slope.

73.20 Fence, bears N. and S.

## Subdivision, T. 16 N., R. 2 E.

Chains	
79.80	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, mountainous. Soil, clay loam. Timber, ponderosa pine, red pine, piñon, and juniper. Undergrowth, dense scrub oak, locus brush, buck brush, manzanite, and grass.</p>
	<p>N. 0° 02' W., bet. secs. 27 and 28. Asc. 340 ft. over S. slope, through dense undergrowth.</p>
14.10	Ridge, bears E. and W.; desc. 670 ft. over steep N. slope.
37.70	Telephone line, bears NE. and SW.
38.60	Power line, bears E. and W.
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 27 and 28.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p>
	S28   S27
	1956
	<p>From above cor. point, cor. No. 4 of the Red Jacket lode claim, Mineral Survey No. 1271, bears N. 57° 41' W., 3173 chs. dist.</p>
	Desc. 135 ft. over N. slope.
51.50	Wash, in Hull Canyon, 40 lks. wide, 10 ft. deep, course SE.; asc. 200 ft. over SSE. slope.
56.40	Telephone line, bears NE. and SW.
63.00	U. S. Highway No. 89A, bears SE. and NW.; asc. 105 ft. over S. slope.
72.50	Spur, slopes W.; desc. 80 ft. over NW. slope.
75.90	Road, graded, bears NE. and SW.
79.20	Wash, 10 lks. wide, 2 ft. deep, course SW.
80.00	<p>Point for the cor. of secs. 21, 22, 27 and 28.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p>
	T16N R2E
	S21   S22
	S28   S27
	1956
	<p>From above cor. point, cor. No. 4 of the Victory lode claim, Mineral Survey No. 3240, bears N. 10° 23' E., 14.14 chs. dist.</p>

BOOK 4489

## Subdivision, T. 16 N., R. 2 E

## Chains

Land, mountainous.  
 Soil, rocky clay.  
 Timber, scattered pinon and pine.  
 Undergrowth, dense scrub oak, manzanite, buck brush, cacti, and grass.

From the cor. of secs. 22, 23, 26, and 27.

N. 89° 40' W., bet. secs. 22 and 27.

.30 U. S. Highway 89A, bears NNE. and SW. 5 chs.; thence W.; asc. 120 ft. over rocky ledges and loose boulders on SE. slope.

5.00 Spur, slopes SE.; asc. 220 ft. over rough broken S. slope.

39.38 Point for the  $\frac{1}{4}$  sec. cor. of secs. 22 and 27.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$$\frac{1}{4} \frac{S 22}{S 27}$$

1956

From the above cor. point, cor. No. 3 of the Lucky Boy lode claim, identical with cor. No. 2 of the Lucky Boy Extension lode claim, Mineral Survey No. 1350, bears S. 84° 21' E., 21.71 chs. dist.

Asc. 340 ft. over E. slope.

56.60 Spur, slopes SE.; thence across S. slope.

60.00 Asc. 140 ft. over SSE. slope.

67.40 Ridge, bears NE. and SW.; desc. 330 ft. over WNW. slope.

73.90 Road, graded, bears NE. and SW.

79.76 The cor. of secs. 21, 22, 27, and 28.

Land, mountainous.  
 Soil, rocky clay.  
 Timber, scattered pine and pinon.  
 Undergrowth, manzanite, buck brush, cacti, and grass.

N. 0° 02' W., bet. secs. 21 and 22.

2.60 Wash, 30 lks. wide, 5 ft. deep, course SW.; asc. 330 ft. over broken W. slope through dense undergrowth.

14.90 Road, graded, bears NW. and SE.

18.38 U.S.G.L.O. B.M., bears West, 3.09 chs. dist., mkd.

Elevation  
 Above Sea Level  
 6269  
 DATUM PRSCT  
 G.L.O.

Subdivision, T. 16 N., R. 2 E.

Chains					
18.90	Ridge, bears NE. and WNW.; desc. 500 ft. over broken N. slope.				
32.50	Wash, 20 lks. wide, 4 ft. deep, course NE.; thence across E. slope.				
39.10	Point for the witness $\frac{1}{4}$ sec. cor. of secs. 21 and 22.				
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone to top, with brass cap mkd.				
	$\frac{1}{4}$ <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">W</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> </table> 1956	W	C	S 21	S 22
W	C				
S 21	S 22				
40.00	True point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22 falls on a slide rock slope, unsafe to set cor.; desc. 240 ft. over broken NE. slope.				
55.60	Road, graded, bears NE. and SW.				
61.80	Same road, bears NW. and SE.				
64.30	Same road, bears E. and SW.				
67.40	Wash, 20 lks. wide, 3 ft. deep, course E.				
71.00	Wash, 10 lks. wide, 3 ft. deep, course S. 80° E.; asc. 190 ft. over S. slope.				
77.20	Road, graded, bears E. and W.				
80.00	Point for the cor. of secs. 15, 16, 21, and 22.				
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.				
	T16N R2E <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S16</td> <td style="padding: 0 5px;">S15</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S21</td> <td style="padding: 0 5px;">S22</td> </tr> </table> 1956	S16	S15	S21	S22
S16	S15				
S21	S22				
	From above cor. point, cor. No. 3 of the Victor lode claim, Mineral Survey No. 1349, bears N. 77° 28' W.; 4.45 chs. dist.				
	Land, mountainous. Soil, rocky clay. Timber, none. Undergrowth, manzanite, buck brush, cacti, and grass.				
	East, bet. secs. 15 and 22. Desc. 200 ft. over broken E. slope, through scattered undergrowth.				
6.80	Road, graded, bears WSW. and NE. 2 chs.; thence ESE.				
23.20	Same road, bears WNW. and SW.				
27.20	Top E. edge of slag dump; desc. 300 ft. over E. slope of dump.				
34.00	Bottom edge of slag dump; desc. 160 ft. over NE. slope.				


Subdivision, T. 16 N., R. 2 E.

Chains

39.79

Point for the 1/4 sec. cor. of secs. 15 and 22.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



1956

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.

From above cor. point, the north center end of Mountain Boy lode claim, Mineral Survey 2811, bears N. 49° 23' E., 15.19 chs. dist.

Across gentle N. slope.

40.20

S. wall of brick building on line.

53.00

Wash, 30 lks wide, 1 ft. deep, with water 1 ft. wide, 3 ins. deep, drains N.

64.20

Road, oiled, bears NE. and SW.

66.20

Road, oiled, bears SE. and NW.

68.10


House on line.

79.58

Intersect the west boundary of sec. 14.

Point for the closing cor. of secs. 15 and 22.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.



1956

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

From above cor. point, the cor. of secs. 14 and 23, bears S. 0°01' W., 68 lks. dist.

Land, mountainous.

Soil, gravelly clay.

Timber, none.

Undergrowth, scattered greasewood, cacti, and grass.

At a point 40 chs. S. 0° 10' E. in latitude, from the closing cor. of secs. 15 and 22.

Point for the 1/4 sec. cor. of sec. 22.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap marked



1956

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

Subdivision, T. 16 N., R. 2 E.

Chains

From above cor. point, the  $\frac{1}{4}$  sec. cor. of sec. 23 bears S.  $0^{\circ} 10' E.$ , 63 lks. dist.

From the cor. of secs. 15, 16, 21, and 22.

North, bet. secs. 15 and 16.

Over rolling land, through scattered undergrowth.

Desc. 90 ft. over broken NE. slope.

15.00

Spur, slopes NE.; desc. 240 ft. over N. slope.

21.00

Wash, 40 lks. wide, 6 ft. deep, course E.; asc. 70 ft. over S. slope.

30.00

Spur, slopes E.; desc. 70 ft. over N. slope.

34.70

Wash, 40 lks. wide, 4 ft. deep, course E.; asc. 140 ft. over SE. slope.

40.00

Point for the  $\frac{1}{4}$  sec. cor. of secs. 15 and 16.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$

S 16 | S 15

1956

From above cor. point, cor. No. 2 Barnett lodeclaim, Mineral Survey No. 3348, bears N.  $55^{\circ} W.$ , 4.40 chs. dist.

42.20

Spur, slopes E; thence over broken E. slope.

59.80

Road, graded, bears NW. and SE. on spur sloping E.; desc. 420 ft. over NE. slope.

76.40

Wash, 20 lks. wide, 3 ft. deep, course E.; asc. 30 ft. over S. slope.

80.00

Point for the cor. of secs. 9, 10, 15, and 16.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with brass cap mkd.

T16N R2E

S9 | S10

S16 | S15

1956

Raise a mound of stone,  $3\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

Land, high and rolling.

Soil, rocky clay.

Vegetation, Spanish bayonet, century plant, cat claw, and heavy grass.

Subdivision, T. 16 N., R. 2 E.

Chains

East, bet. secs. 10 and 15.

Desc. 130 ft. over SE. slope.

5.20 Wash, 20 lks. wide, 3 ft. deep, course NE.

5.90 Road, graded, bears N. 80° E. and S. 80° W.; thence over N. slope.

19.60 Road, graded, bears N. 80° W. and SW.; asc. 230 ft. over NNW. slope.

39.80 Point for the 1/4 sec. cor. of secs. 10 and 15.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

1/4 S 10 / S 15

1956

From above cor. point, cor. No. 4 of the Maid of Erin lode claim, Mineral Survey 3348, bears N. 16° 30' E., 8 chs. dist.

Asc. 120 ft. over NW. slope.

47.50 Spur, slopes NE.; desc. 540 ft. over broken ESE. slope.

79.60 Intersect the west boundary of sec. 11.

Point for the closing cor. for secs. 10 and 15.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T16N R2E  
C S10 | S11  
C S15 |

1956

From above cor. point, the cor. of secs. 11 and 14 bears S. 0° 01' W., 64 lks. dist.

Land, high and rolling.

Soil, rocky clay.

Vegetation, Spanish bayonet, century plant, cat claw, and heavy grass.

At a point midway between the closing cors. of secs. 10 and 15 and 15 and 22.

Point for the 1/4 sec. cor. of sec. 15.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

1/4

S 15

1956

From above cor. point, the 1/4 sec. cor. of sec. 14, bears S. 0° 01' W., 66 lks. dist.

Subdivision, T. 16 N., R. 2 E.

Chains

From the cor. of secs. 9, 10, 15, and 16.

North, bet. secs. 9 and 10.

Over rolling hills, through scattered undergrowth; asc. 35 ft. over SE. slope.

3.30 Spur, short, slopes E.; desc. 140 ft. over NE. slope.

13.10 Wash, 15 lks. wide, 2 ft. deep, course E.; desc. 75 ft. over broken E. slope.

22.80 Road, graded, bears NE. and N. 15° W.

27.50 Wash, 15 lks. wide, 2 ft. deep, course E.

28.90 Same road, bears NNE. and SSW.

39.60 Same road, bears NW. and SSE.

40.00 Point for the 1/4 sec. cor. of secs. 9 and 10 falls in a meandering wash, .20 lks wide, 3 ft. deep, course S. 60° E.

42.10 Point for the witness 1/4 sec. cor. of secs. 9 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.

1/4

S 9 | S 10

W | C

1956

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Asc. 260 ft. over grassy SW. slope.

56.50 Spur, slopes SE.; desc. 255 ft. over NE. slope.

67.70 Wash, 20 lks. wide, 2 ft. deep, course N. 80° E.; asc. 115 ft. over S. slope.

75.90 Spur, slopes ENE.; desc. 100 ft. over N. slope.

80.00 Point for the cor. of secs. 3, 4, 9, and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T16N R2 E

S4 | S3

S9 | S10

1956

Land, high and rolling. Soil, rocky clay. Vegetation, Spanish bayonet, century plant, cat claw, and heavy grass.

East, bet. secs. 3 and 10.

Over rolling hills, through scattered undergrowth.



Subdivision, T. 16 N., R. 2 E.

Chains

Desc. 250 ft. over SE. slope.

16.00

Wash, 20 lks. wide, 2 ft. deep, course S. 60° E.; thence over broken S. slope.

39.80

Point for the 1/4 sec. cor. of secs. 3 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

1/4 S 3 / S 10

1956

Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, N. of cor.

Over broken S. slope.

48.40

Slope changes to SE.; desc. 320 ft.

61.00

Road, bladed, bears N. and S. 1 ch. to road bearing E. and W.

75.50

Road, bears N. 30° E. and S. 30° W.

75.80

Wash, 30 lks. wide, 2 ft. base, course N. 30° E.; asc. 60 ft. over NW. slope.

79.60

Intersect the west boundary of sec. 2.

Point for the closing cor. of secs. 3 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.

T16N R2E

C S 3 / S 10 S2

1956

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

From above cor. point, the cor. of secs. 2 and 11, bears S. 0° 01' W. 47 lks. dist.

Land, high and rolling.

Soil, rocky clay.

Vegetation, Spanish bayonet, century plant, cat claw, and heavy grass.

At a point midway between the closing cor. of secs. 3 and 10 and 10 and 15.

Point for the 1/4 sec. cor. of sec. 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

1/4

S10

1956

From above cor. point, the 1/4 sec. cor. of sec. 11, bears S. 0° 01' W., 55 1/2 lks. dist.

Subdivisión, T. 16 N., R. 2 E.

Chains

From a point N. 0° 01' E.; 40 chs. in latitude, from the closing cor. of secs. 3 and 10.

Point for the 1/4 sec. cor. of sec. 3.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

1/4

S 3

1956

From the above cor. point, the 1/4 sec. cor. of sec. 2, bears S. 0° 01' W., 47 lks. dist.

At a point N. 0° 01' E., 80 chs. dist. in latitude, from the closing cor. of secs. 3 and 10.

Point for the N. 1/16 cor. of sec. 3.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

N 1/16

S 3

80

1956

From the above cor. point, the N. 1/16 cor. of sec. 2, bears S. 0° 01' W., 47 lks. dist.

From the cor. of secs. 3, 4, 9, and 10.

North, between secs. 3 and 4.

Over rolling hills, through scattered undergrowth.

2.50 Wash, 10 lks. wide, 3 ft. deep, course N. 80° E.

7.00 Wash, 25 lks. wide, 2 ft. deep, course ESE.; asc. 100 ft. over S. slope.

12.40 Spur, slopes SE.; asc. 20 ft. over NE. slope.

23.70 Wash, 20 lks. wide, 3 ft. deep, course SE.; asc. 150 ft. over SW. slope.

33.00 Spur, slopes SE.; desc. 130 ft. over NE. slope.

38.00 Wash, 20 lks. wide, 2 ft. deep, course NE.

40.00 Point for the 1/4 sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

1/4

S 4 | S 3

1956

BOOK 4499

Subdivision, T. 16 N., R. 2 E.

Chains

Asc. 60 ft. over SE. slope.

52.50 Spur, short, slopes E.; desc. 230 ft. over NE. slope.


61.70 Fence, bears NNE. and SSW.

67.50 Wash, 20 lks. wide, 2 ft. deep, course E.

69.50 Wash, 15 lks. wide, 2 ft. deep, course E.; asc. 35 ft. over S. slope.

80.00 Point for the N. 1/16 cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.




Asc. 95 ft. over S. slope.

85.88 Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 3 and 4, T. 16 N., R. 2 E.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.



From above cor. point, the standard cor. for secs. 34 and 35, T. 17 N., R. 2 E., bears East, 13.43 chs. dist., mkd. with a 2 1/2 in. I. P., set, mkd. and witnessed as described in field notes of T. 17 N., R. 2 E.

Land, high and rolling.

Soil, rocky clay.

Vegetation, Spanish bayonet, century plant, catclaw, and heavy grass.

At a point midway between the closing cors. of secs. 2 and 3 and 3 and 4, T. 16 N., R. 2 E.

Point for the 1/4 sec. cor. of sec. 3.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.



From above cor. point, the standard 1/4 sec. cor. of sec. 35, T. 17 N., R. 2 E., bears East 13.60 chs. dist., mkd. with a 2 1/2 in. I. P., set, mkd. and witnessed as described in field notes of T. 17 N., R. 2 E.

From the true point for the cor. of secs. 4, 5, 32 and 33, on the south boundary of the township, whose witness cor. bears West 2 chs. dist., and is monumented with a 2 in. I. P., set, mkd. and witnessed as described in the official record.

N. 0° 02' W., bet. secs. 32 and 33.

## Subdivision, T. 16 N., R. 2 E.

Chains	Desc. 260 ft. over NE. slope, through scattered undergrowth.
9.70	Wash, 30 lks. wide, 10 ft. deep, course ENE.; asc. 210 ft. over SE. slope.
17.40	Spur, slopes ENE.; desc. 420 ft. over N. slope.
32.50	Wash, 25 lks. wide, 2 ft. deep, course ENE.; asc. 250 ft. over S. slope.
35.40	U. S. Highway No. 89A, bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd. $\frac{1}{4}$ S32   S33 1956
41.50	Power line, bears NE. and SW.
41.70	Telephone line, bears NE. and SW.; asc. 90 ft. over S. slope.
47.00	Spur, slopes E.; desc. 110 ft. over E. slope.
58.00	Spur, short, slopes NE.; desc. 220 ft. over NNE. slope.
79.60	Point for the witness cor. of secs. 28, 29, 32 and 33. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd. T16N R2E W   C S29   S28 S32   S33 1956
80.00	True point for the cor. of secs. 28, 29, 32 and 33 falls in wash, 25 lks. wide, 3 ft. deep, course N. $80^{\circ}$ E. Land, mountainous. Soil, rocky clay. Timber, scattered pine. Undergrowth, oak brush, cedar brush, cacti, and grass.
	From the cor. of secs. 27, 28, 33 and 34. N. $89^{\circ} 57'$ W., bet. secs. 28 and 33. Desc. 100 ft. over S. slope, through scattered undergrowth.
22.00	Wash, 20 lks. wide, 2 ft. deep, course SE.; asc. 60 ft. over N. slope.
30:00	Road, bladed, bears SE. and NW.
37.70	Telephone line, bears NE. and SW. and wash, 30 lks. wide, 2 ft. deep, course ENE.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S28 S33 1956

## Subdivision, T. 16 N., R. 2 E.

Chains

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of cor.

Asc. 40 ft. over S. slope.

45.30 U. S. Highway 89A, bears N. and S.

47.00 Power line, bears NE. and SW.; asc. 500 ft. over E. slope.

61.90 Spur, slopes ESE.; desc. 150 ft. over broken S. slope.

77.25 Wash, 40 lks. wide, 2 ft. deep, course SE.

80.02 The cor. of secs. 28, 29, 32 and 33.

Land, mountainous.

Soil, rocky clay.

Timber, scattered pine.

Undergrowth, oak brush, cedar brush, cacti, and grass.

N.  $0^{\circ} 02'$  W., bet. secs. 28 and 29.

Desc. 80 ft. over NE. slope, through scattered undergrowth.

5.90 Wash, 15 lks. wide, 2 ft. deep, course SE.; asc. 290 ft. over SW. slope.

22:60 Spur, slopes SE.; desc. 260 ft. over ENE. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 29.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd. $\frac{1}{4}$ 

S29 | S28

1956

Desc. 260 ft. over NE. slope.

57.00 Wash, in Hull Canyon, 50 lks. wide, 2 ft. deep, course ESE.; asc. 280 ft. over S. slope.

72.50 Spur, slopes ESE.; desc. 100 ft. over NE. slope.

76.30 Road, bladed, bears NW. and SE.

80.00 Point for the cor. of secs. 20, 21, 28 and 29.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T16N R2E

S20 | S21

S29 | S28

1956

Land, mountainous.

Soil, rocky clay.

Timber, scattered pine.

Undergrowth, oak brush, cedar brush, cacti, and grass.

From the cor. of secs. 21, 22, 27 and 28.

N.  $89^{\circ} 52'$  W., bet. secs. 21 and 28.

Subdivision, T. 16 N.; R. 2 E.

Chains	
	Over rolling hills, through scattered undergrowth.
3.00	Wash, 10 lks. wide, 2 ft. deep, course S.; asc. 445 ft. over ESE. slope.
24.40	Spur, slopes S.; desc. 340 ft. over WSW. slope.
36.50	Wash, 20 lks. wide, 2 ft. deep, course SE.; asc. 65 ft. over SE. slope.
39.96	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ $\frac{S21}{S28}$ 1956
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor. Asc. 90 ft. over SE. slope.
52.00	Spur, slopes S.; desc. 30 ft. over W. slope.
57.30	Wash, 1 ch. wide, 3 ft. deep, course ESE.; asc. 20 ft. up the wash.
60.60	Leave wash, course E, from WNW.; asc. 320 ft. over NE. slope.
79.92	The cor. of secs. 20, 21, 28 and 29. Land, high and rolling. Soil, rocky clay. Vegetation, scattered brush, greasewood, cacti, and grass.
	N. $0^{\circ} 02'$ W., bet. secs. 20 and 21. Desc. 50 ft. over NE. slope, through scattered undergrowth.
3.90	Wash, 90 lks. wide, 3 ft. deep, course S. $75^{\circ}$ E.; asc. 105 ft. over S. slope.
12.50	Road, bears NE. and SW. on spur sloping SSE.; asc. 280 ft. over E. slope.
22.70	Top of ascent; desc. 60 ft. over E. slope.
29.10	Wash, 30 lks. wide, 2 ft. deep, course SE.; asc. 270 ft. over S. slope.
38.40	Ridge, bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone to top, with brass cap mkd. $\frac{1}{4}$ $\frac{S20}{S21}$ 1956
	Desc. 200 ft. over broken N. slope.

Subdivision, T. 16 N., R. 2 E.

Chains

- 55.80 Road, bears E. and NW.; desc. 125 ft. over NE. slope.
- 74.00 Wash, 5 lks. wide, 1 ft. deep, course E.; asc. 20 ft. over S. slope.
- 80.00 Point for the cor. of secs. 16, 17, 20, and 21, on high spur sloping ENE.

Set and iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T16N R2E

S17 | S16

S20 | S21

1956

Land, high and rolling.  
Soil, rocky clay.  
Vegetation, scattered cedar brush, greasewood, cacti, and grass.

From the cor. of secs. 15, 16, 21, and 22.

N. 89° 52' W., bet. secs. 16 and 21.

Asc. 30 ft. over E. slope, through scattered undergrowth.

- 10.80 Road, graded, bears NW. and SE.; asc. 230 ft. over NE. slope.

- 28.00 Spur, slopes NE.; desc. 180 ft. over NW. slope.

- 38.00 Wash, 20 lks. wide, 3 ft. deep, course N, 80° E.

- 39.95 Point for the 1/4 sec. cor. of secs. 16 and 21.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

S 16

1/4 S 21

1956

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.

Asc. 580 ft. over broken SE. slope.

- 79.90 The cor. of secs. 16, 17, 20, and 21.

Land, high and rolling.  
Soil, rocky clay.  
Vegetation, scattered brush, greasewood, cacti, and grass.

North, between secs. 16 and 17.

Desc. 230 ft. over NW. slope, through scattered undergrowth.

- 8.00 Wash in canyon, 30 lks. wide, 3 ft. deep, course NE.; asc. 540 ft. over SE. slope.

- 36.00 Ridge, bears NNE. and SW.; desc. 60 ft. over NW. slope.

- 38.20 Fence, bears E. and W.

- 40.00 Point for the 1/4 sec. cor. of secs. 16 and 17.

Subdivision, T. 16 N., R. 2 E.

Chains

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

1/4  
S 17 | S 16

1956

Desc. 380 ft. over WNW. slope.

51.50 Draw, course NW.; asc. 130 ft. over SW. slope.

65.00 Spur, slopes W.; desc. 350 ft. over NW. slope.

80.00 Point for the cor. of secs. 8, 9, 16, and 17.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T16N R2E

S8 | S9

S17 | S16

1956

Land, high and rolling.

Soil, rocky clay.

Vegetation, oak brush, mountain mahogany, cacti, and heavy grass.

From the cor. of secs. 9, 10, 15, and 16.

N. 89° 50' W., bet. secs. 9 and 16.

Asc. 480 ft. over broken E. slope, through scattered undergrowth.

37.10 Road, graded, bears NE. and SW.

39.925 Point for the 1/4 sec. cor. of secs. 9 and 16.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

1/4 S 9  
S 16

1956

Asc. 460 ft. over E. slope.

44.00 Road, graded, bears N. and S.

52.30 Spur, slopes NNE.; desc. 95 ft. over NW. slope.

57.40 Same road, bears NE. and SW.

58.60 Draw, course N. 20° E.; asc. 170 ft. over NE. slope.

66.90 Spur, slopes NE.; desc. 270 ft. over NW. slope.

79.85 The cor. of secs. 8, 9, 16, and 17.

Land, high and rolling.

Soil, rocky clay.

Vegetation, oak brush, mountain mahogany, cacti, and heavy grass.



BOOK 4499

Subdivision, T. 16 N., R. 2 E.

Chains

North, bet. secs. 8 and 9.

Desc. 280 ft. over NW. slope, through scattered undergrowth.

9.60 Road, graded, bears NE. and SW. 2 chs., thence N.

19.00 Draw, course NE.

25.00 Power line, bears E. and W.; asc. 240 ft. over SE. slope.

28.90 Road, graded, bears SW. and NE.

34.85 Spur, short, slopes E.; desc. 100 ft. over ENE. slope.

38.90 Road, graded, bears NW. and SE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 8 and 9.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
$$\frac{1}{4}$$

S 8		S 9
-----	--	-----

1956

Desc. 215 ft. over NE. slope.

54.60 Draw, course E.; asc. 200 ft. over SE. slope.

65.20 Spur, slopes E.; desc. 230 ft. over NE. slope.

80.00 Point for the cor. of secs. 4, 5, 8, and 9.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T16N R2 E	
S5	S4
S8	S9

1956

Land, high and rolling.

Soil, rocky clay.

Vegetation oak brush, mountain mahogany, cacti, and heavy grass.

From the cor. of secs. 3, 4, 9, and 10.

N. 89° 51' W., bet. secs. 4 and 9.

Asc. 350 ft. over broken SE. slope, through scattered undergrowth.

16.15 Spur, slopes NE.; desc. 40 ft. over NW. slope.

30.60 Draw, course NE.; asc. 460 ft. over broken E. slope.

39.91 Point for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 9.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
$$\frac{1}{4} \frac{S 4}{S 9}$$

1956

Subdivision, T. 16 N., R. 2 E.

Chains  
40.00

Fence, bears N. and S.  
Asc. 85 ft. over E. slope.

47.40

Ridge, bears NW. and SE.; desc. 480 ft. over WSW. slope.

67.20

Wash, 20 lks. wide, 10 ft. deep, course N.; asc. 210 ft. over NE. slope.

79.82

The cor. of secs. 4, 5, 8, and 9.

Land, high and rolling.  
Soil, rocky clay.  
Vegetation, oak brush, mountain mahogany, cacti, and heavy grass.

40.00

North, bet. secs. 4 and 5.

Desc. 300 ft. over NE. slope, through scattered undergrowth.

Point for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$

S 5 | S 4

1956

Desc. 65 ft. over NE. slope.

58.20

Wash, 50 lks. wide, 15 ft. deep, course N. 20° W.; desc. 110 ft. over W. slope.

64.50

Fence, bears NW. and SE.

80.00

Point for the N.  $\frac{1}{16}$  cor. of secs. 4 and 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., over X cut in solid rock, and in a mound of stone to top, with brass cap mkd.

N  $\frac{1}{16}$

S 5 | S 4

80

1956

85.67

Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 4 and 5.

T17N R2E

S33

S 5 | S 4

.C | C

T16N R2E

1956

From above point the standard cor. of secs. 33 and 34, T. 17. N., R. 2 E., bears East, 13.23 chs. dist.

Land, high and rolling.  
Soil, rocky clay.  
Vegetation, oak brush, mountain mahogany, cacti, and heavy grass.

## Subdivision, T. 16 N., R. 2 E.

## Chains

At a point midway between the closing cors. of secs. 3 and 4 and 4 and 5, T. 16 N., R. 2 E.

Point for the  $\frac{1}{4}$  sec. cor. of sec. 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

—  
 $\frac{1}{4}$  S 4

1956

From above point, the standard  $\frac{1}{4}$  sec. cor. of sec. 34, T. 17 N., R. 2 E., bears East, 13.33 chs. dist., mkd. with a  $2\frac{1}{2}$  in. I.P., set, mkd. and witnessed as described in field notes of T. 17 N., R. 2 E.

## General Description

The south half of the portion surveyed is high and rough, covered with scattered pine, cedar brush, mountain mahogany, scrub oak, cacti, and grass. The major portion of this part of the township is taken up by patented lode mining claims. The almost abandoned town of Jerome, Arizona, lies mostly in sec. 22, partly in 23.

The north half of the portion surveyed is high, rolling grass covered ridges, with no timber and very scattered brush. Several of the canyons have small streams of water.

There is very limited mining activity at present. There is evidence of extensive mining in the past of copper with some gold and silver.

The portion of the township surveyed is a limestone formation, used both for making cement and in processing copper ore.

The northwest portion of this township is known as the Black Hills.

4-680  
(Feb., 1950)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Dean J. Allen	Notekeeper
Alburn D. Griffin	Notekeeper
Paul G. Bauer	Chairman
Freddy H. Jones	Chairman
Charley Avants	Flagman
Samuel E. Hardin	Flagman
Robert R. Mitchell	Truck Driver and cornerman
Andrew M. Nelson	Truck Driver and cornerman
Clarence A. Wambacher	Axeman



37

BOOK 4499

### CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, ~~STATE OF~~ Utah, HEREBY CERTIFY upon honor that, in  
pursuance of special instructions bearing dates of the 15 February 1956  
20 day of March, 1956

I have ~~surveyed~~ supervised the resurvey of a portion of the east boundary, and a  
portion of the subdivision, and survey of a portion of the subdivision of T. 16 N.,  
R. 2 E.

of the G. & S. R. Meridian, in the State of Arizona, which are  
represented in the foregoing field notes as having been executed ~~by me and~~ under my direction; and that  
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the  
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing  
field notes.

Salt Lake City, Utah  
July 13, 1956

Donald E. Harding  
Donald E. Harding  
Cartographer

### CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., AUG 14 1956, 19

The foregoing field notes of the ~~survey of~~ resurvey of a portion of the east boundary, and  
a portion of the subdivision, and survey of a portion of the subdivision of T. 16 N.,  
R. 2 E., Gila and Salt River, Meridian, Arizona.

executed by Donald E. Harding

having been critically examined and found correct, are hereby approved.

Earl G. Harrington  
Chief, Division of Cadastral Engineering  
Cadastral Engineering Staff Officer

### CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in  
, is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.