

ORIGINAL
BOOK 4511

4511
indexed ✓

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BOOK 4511

FIELD NOTES

of the

Survey of the West and North Boundary of

T. 37 N., R. 15 W.

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

George M. Boofer Cartographer (Cadastral)

Under special instructions dated September 22, 1954, which provided
for the surveys included under Group No. 295, approved September 27, 1954
and assignment instructions dated November 8, 1955.

Survey commenced November 25, 1955

Survey completed December 6, 1955

4511

4511

2
1A

BOOK 4511

INDEX DIAGRAM

Township 37 N., Range 15 W.

	9	9	8	7	6	6
5	6	5	4	3	2	1
4	7	8	9	10	11	12
3	18	17	16	15	14	13
2	19	20	21	22	23	24
2	30	29	28	27	26	25
1	31	32	33	34	35	36

T. 37 N., R. 15 W.

Chains

The east and south boundaries were surveyed by D. R. Averill in 1929.

The following field notes are those of the west and north boundaries of T. 37 N., R. 15 W.

The geographic position of the southwest cor. of the township is, latitude 36°33'26.815" N., longitude 113°57'27.543" W., as determined from a direct tie to station MOSBY, U.S.C. & G.S. The magnetic declination is 16° E.

Survey of the West Boundary of T. 37 N., R. 15 W.

Beginning at the ^{*} cor. of Ts. 36 and 37 N., Rs. 15 and 16 W., an iron post, 3 ins. diam., set, marked and described in the official record.

From this cor., station U.S.C. & G.S. MOSBY, bears N. 32° 05' W., at a dist. of 42.02 chs., latitude, 36°33'50.049" N., longitude, 113°57'45.599" W.

Thence

North, bet. secs. 31 and 36, along the west boundary of T. 37 N., R. 15 W.

Over rolling land, through scattered timber and undergrowth; desc. 25 ft. over gradual N. slope.

11.30 Wash, 50 lks. wide, 2 ft. deep, drains SE.; asc. 115 ft. over SE. moderate slope.

23.90 Spur, slopes SE.; desc. 30 ft. over gradual NE. slope.

40.00 Point for the ¼ sec. cor. of secs. 31 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap marked

¼
S36|S31
1956

Continue descent of 35 ft. over broken N. slope.

45.10 Wash, 50 lks. wide, 6 ft. deep, drains SE.; asc. 70 ft. over SW. slope.

79.05 Small spur, slopes SW.; desc. 125 ft. over NW. slope.

80.00 Point for the cor. of secs. 25, 30, 31, and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T37N
R16W|R15W
S25|S30
S36|S31
1956

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

* Stan. Cor. of Ts. 37 N., Rs. 15 and 16 W.

Survey of the West Boundary of T. 37 N., R. 15 W.

Chains	<p>Land, rolling. Soil, sandy, gravelly and rocky. Timber, Joshua trees; undergrowth, blackbrush, sage, and cacti.</p>
	<p>North, bet. secs. 25 and 30. Over rolling land, through scattered timber and undergrowth.</p>
10.30	Wash, 15 lks. wide, 3 ft. deep, drains NW. out of ridge.
17.65	Point of ridge, jutting NW.; desc. 160 ft. over NW. slope.
20.55	Wash, 1 ch. wide, 4 ft. deep, drains NW.
30.65	Wash, 30 lks. wide, 8 ft. deep, drains NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. firmly in the ground, and in a mound of stone to top, with brass cap marked <div style="text-align: center;"> $\frac{1}{4}$ S25 S30 1956 </div>
	<p>Desc. 20 ft. over N. slope.</p>
50.00	Wash, 20 lks. wide, 3 ft. deep, drains NE.
59.00	Wash, 30 lks. wide, 4 ft. deep, drains E.
63.20	Wash, 1 ch. wide, 4 ft. deep, drains E.
71.50	Wash, 10 lks. wide, 2 ft. deep; drains E.; asc. 65 ft. over E. slope.
80.00	Point for the cor. of secs. 19, 24, 25, and 30. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap marked <div style="text-align: center;"> T37N R16W R15W S24 S19 S25 S30 1956 </div>
	<p>Land, rolling. Soil, sandy, gravelly and rocky. Timber, Joshua trees; undergrowth, blackbrush, sage and cacti.</p>
	<p>North, bet. secs. 19 and 24. Over rolling land, through scattered timber and undergrowth; desc. 25 ft. over gradual N. slope.</p>
10.40	S. rim of canyon, bears E. and W.; desc. 85 ft. over broken N. slope.
16.10	Bottom of canyon; asc. 175 ft. over S. slope.
23.60	N. rim of canyon; desc. 85 ft. over gradual NW. slope.
34.20	Wash, 25 lks. wide, 2 ft. deep, drains NE.
39.65	Wash, 50 lks. wide, 2 ft. deep, drains SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24.

Survey of the West Boundary, T. 37 N., R. 15 W.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap marked

¼
S24|S19
1956

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Asc. 80 ft. over S. slope of ledge rock.

52.80 Spur, slopes SE.; desc. over NE. slope.

55.65 Wash, 20 lks. wide, 3 ft. deep, drains E.

64.70 Spur, slopes E.; desc. 20 ft. over N. slope.

68.40 Wash, 25 lks. wide, 8 ft. deep, drains E.

72.45 Spur, slopes E.; desc. 40 ft. over N. slope.

80.00 Point for the cor. of secs. 13, 18, 19, and 24.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap marked

T37N
R16W|R15W
S13|S18
S24|S19
1956

Land, rolling.

Soil, very rocky, (ledge rock).

Timber, none; undergrowth, scattered sagebrush, cacti and grass.

North, bet. secs. 13 and 18.

Over rocky, rolling land, through scattered undergrowth.

9.50 Small wash, 15 lks. wide, 2 ft. deep, drains E. out of ridge.

19.05 Spur, slopes E.; desc. 100 ft. over NE. slope.

21.45 Wash, 10 lks. wide, 4 ft. deep, drains E.; asc. 175 ft. over SE. slope.

24.00 Main ridge, bears N. 20° E. and S. 20° W., slopes SW.; desc. 425 ft. over NW. slope.

37.90 Jacobs Dugout road, bears NE. and SW.

39.45 Wash, 10 lks. wide, 2 ft. deep, drains NE.

40.00 Point for the ¼ sec. cor. of secs. 13 and 18.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone to top, with brass cap marked

¼
S13|S18
1956

Asc. 50 ft. over E. slope of dirt bank.

Survey of the West Boundary, T. 37 N., R. 15 W.

Chains											
52.00	Fence, 4 strand barbed wire, bears N. 15° E. and S. 15° W.										
54.95	Wash, 30 lks. wide, 6 ft. deep, drains SE.										
55.85	Track road, bears NE. and SW.										
58.60	Wash, 10 lks. wide, 8 ft. deep, drains SE.										
63.50	Knoll, slopes E.; desc. 10 ft. over NE. slope.										
68.85	Wash, 20 lks. wide, 8 ft. deep, drains SE.										
80.00	Point for the cor. of secs. 7, 12, 13, and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked										
	<table border="1"> <tr><td colspan="2">T37N</td></tr> <tr><td>R16W</td><td>R15W</td></tr> <tr><td>S12</td><td>S7</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2">1956</td></tr> </table>	T37N		R16W	R15W	S12	S7	S13	S18	1956	
T37N											
R16W	R15W										
S12	S7										
S13	S18										
1956											
	raise a mound of stone, 3 ft. base 2½ ft. high, W. of cor. Land, rolling. Soil, sandy and gravelly. Timber, Joshua, cedar and pinon trees; undergrowth, black brush, creosote brush, Brigham tea, and cacti, some grass.										
	North, between secs. 7 and 12. Over rolling land, through medium growth of timber and undergrowth.										
2.50	Wash, 10 lks. wide, 3 ft. deep, drains SE.										
8.20	Wash, 10 lks. wide, 4 ft. deep, drains SE.; asc. 60 ft. SE. slope.										
17.95	Small spur, slopes SE.; desc. 40 ft. over NE. slope.										
22.70	Wash, 40 lks. wide, 9 ft. deep, drains E.										
38.40	Wash, 30 lks. wide, 4 ft. deep, drains E.										
40.00	Point for the ¼ sec. cor. of secs. 7 and 12. Set an iron post, 30 ins. long, 2½ ins. diam, 20 ins. in the ground, with brass cap marked										
	<table border="1"> <tr><td colspan="2">¼</td></tr> <tr><td>S12</td><td>S7</td></tr> <tr><td colspan="2">1956</td></tr> </table>	¼		S12	S7	1956					
¼											
S12	S7										
1956											
	raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.										
50.05	Wash, 20 lks. wide, 6 ft. deep, drains SE.										
58.15	Wash, 50 lks. wide, 20 ft. deep, drains ESE.										
80.00	Point for the cor. of secs. 1, 6, 7, and 12. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked										

Survey of the West Boundary, T. 37 N., R. 15 W.

Chains

T37N	
R16W	R15W
S1	S6
S12	S7
1956	

raise a mound of stone, 3 ft. base, 2½ ft. high W. of cor.

Land, gently rolling.

Soil, sandy, gravelly and rocky.

Timber, cedar and pinon trees; undergrowth, black brush, greasewood, Spanish dagger, cacti, and medium grass.

North, bet. secs. 1 and 6.

Over rolling land, sloping E., through scattered timber and undergrowth.

1.20 Small wash, 10 lks. wide, 3 ft. deep, drains E.

12.50 Wash, 15 lks. wide, 8 ft. deep, drains SE.

16.10 Wash, 50 lks. wide, 20 ft. deep, drains SE.; asc. 35 ft. over gradual E. slope.

39.42 Point for the witness ¼ sec. cor. of secs. 1 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap marked

WC	
¼	
S1	S6
1956	

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

40.00 True point for the ¼ sec. cor. of secs. 1 and 6 falls on insecure ground in bottom of wash; 60 lks. wide, 2 ft. deep, drains E.; asc. 19 ft. over S. slope.

43.70 Small spur, slopes E.

54.90 Wash, 20 lks. wide, 7 ft. deep, drains ESE.

71.00 Wash, 20 lks. wide, 20 ft. deep, drains ESE.

75.15 Wash, 5 lks. wide, 3 ft. deep, drains SE.

80.00 Point for the cor. of Ts. 37 and 38 N., Rs. 15 and 16 W.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap marked

T38N	
R16W	R15W
S36	S31
S1	S6
T37N	
1956	

A sandstone boulder, 18x14x8 ft. above ground, bears S. 28° W., at 40 lks. dist., marked X - BR S-1.

Survey of the West Boundary, T. 37 N., R. 15 W.

Chains	<p>Land, rolling. Soil, sandy, gravelly and rocky. Timber, pinon, cedar; undergrowth, blackbrush, cacti, scrub oak, and cacti.</p>					
	<p>Survey of the North Boundary, T. 37 N., R. 15 W.</p>					
	<p>Beginning at the cor. of Ts. 37 and 38 N., Rs. 14 and 15 W., an iron post, 3 ins. diam., set, marked and described in the official record</p> <p>S. 89° 56' W., bet. secs. 1 and 36.</p> <p>Over mountainous land, through medium growth of timbers and undergrowth.</p> <p>From SW. slope of ridge, desc. 135 ft.</p>					
14.05	Wash, 20 lks. wide, 4 ft. deep, drains NW. to main wash.					
29.85	Wash, 10 lks. wide, 6 ft. deep, drains N.; asc. E. slope of canyon wall, west side.					
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36.					
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to cap, with brass cap marked</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="text-align: center;">S36</td></tr> <tr><td style="text-align: center;">S1</td></tr> <tr><td style="text-align: center;">1956</td></tr> </table>	S36	S1	1956		
S36						
S1						
1956						
	Continue ascent 420 ft. over E. slope.					
58.95	Canyon rim, bears N. 10° E. and S. 10° W.; desc. 125 ft. W. slope.					
80.00	Point for the cor. of secs. 1, 2, 35, and 36.					
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in ground, on an outcropping, and in a mound of stone to top, with brass cap marked</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="text-align: center;">T38N R15W</td></tr> <tr><td style="text-align: center;">S35 S36</td></tr> <tr><td style="text-align: center;">S2 S1</td></tr> <tr><td style="text-align: center;">T37N</td></tr> <tr><td style="text-align: center;">1956</td></tr> </table>	T38N R15W	S35 S36	S2 S1	T37N	1956
T38N R15W						
S35 S36						
S2 S1						
T37N						
1956						
	<p>Land, mountainous. Soil, rocky. Timber, cedar and pinon; undergrowth, blackbrush, greasewood, cacti, and creosote brush.</p>					
	<p>S. 89° 56' W., bet. secs. 2 and 35.</p> <p>Over mountainous land, through scattered timber and undergrowth.</p> <p>Desc. 390 ft. over NW. slope of ridge point.</p>					
18.95	Wash, 50 lks. wide, 6 ft. deep, drains N.; asc. 105 ft. over E. slope.					
30.00	Low spur, projects NW.; desc. NW. slope.					

Survey of the North Boundary, T. 37 N., R. 15 W.

Chains	
37.20	Wash, 10 lks. wide, 2 ft. deep, drains NW. out of ridge.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, with X marked at base of post, and in a mound of stone to top, with brass cap marked $\frac{1}{4} \frac{S35}{S2}$ 1956
42.40	Point of E. rim of canyon, bears NE. and SW.; desc. 455 ft. over W. slope.
59.10	Wash, 25 lks. wide, 4 ft. deep, drains W. to main wash.
65.10	Wash, 30 lks. wide, 8 ft. deep, drains NW.
71.60	Wash, 50 lks. wide, 6 ft. deep, drains SW.; also bottom of canyon. asc. 200 ft. over E. slope.
80.00	Point for the cor. of secs. 2, 3, 34, and 35. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap marked $\begin{array}{c} T38N R15W \\ S34 S35 \\ S3 S2 \\ T37N \\ 1956 \end{array}$ Land, mountainous. Soil, very rocky. Timber, Cedar, oak, Joshua trees; undergrowth, blackbrush, cacti, and Spanish dagger.
	S. $89^{\circ} 56'$ W., bet. secs. 3 and 34. Over mountainous land, through scattered timber and undergrowth. Continue ascent 240 ft. over E. slope.
5.60	W. rim of canyon, bears NE. and SW. slopes S.
7.50	Wash, 10 lks. wide, 4 ft. deep, drains S.
13.65	Wash, 1 ch. wide, 5 ft. deep, drains SE.; asc. 150 ft. gradual E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to cap, with brass cap marked $\frac{1}{4} \frac{S34}{S3}$ 1956
42.60	Top of ascent, slopes SE.; desc. 65 ft. over W. slope of small knoll.
66.50	Wash, 30 lks. wide, 3 ft. deep, drains S.; thence across level mesa.

Survey of the North Boundary, T. 37 N., R. 15 W.

Chains	
80.00	<p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground and in a mound of stone to top, with brass cap marked</p> <p style="text-align: center;">T38N R15W S33 S34 S4 S3 T37N 1956</p> <p>Land, rolling, and high mesa. Soil, sandy, gravelly and rocky. Timber, Joshua trees; undergrowth, blackbrush, sagebrush, creosote and Spanish dagger.</p>
	<p>S. 89° 56' W., bet. secs. 4 and 33.</p>
	<p>Over high mesa land, through timber and undergrowth.</p>
13.95	<p>E. rim of Cottonwood canyon, bears N. and S.; desc. 395 ft. over W. slope.</p>
27.50	<p>Bottom of Cottonwood canyon and wash, 50 lks. wide, 9 ft. deep, drains S.</p>
29.50	<p>Mud Mountain and Cain Springs Road, bears N. and S.; asc. 220 ft. over E. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 4 and 33.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap marked</p> <p style="text-align: center;">¼ <u>S33</u> S4 1956</p> <p>Continue ascent 270 ft. over E. slope.</p>
53.80	<p>W. rim of Cottonwood Canyon, bears N. 15° E. and S. 15° W.; desc. 80 ft. over W. slope.</p>
70.25	<p>Spur, jutting out of rim, slopes SW.; continue descent 290 ft. over W. slope.</p>
80.00	<p>Bottom of small canyon, bears N. and S.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 32, and 33.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap marked</p> <p style="text-align: center;">T38N R15W S32 S33 S5 S4 T37N 1956</p> <p>Land, rolling. Soil, gravelly and rocky. Timber, Joshua trees; undergrowth, blackbrush, greasewood, cacti, and Spanish dagger.</p>

Survey of the North Boundary, T. 37 N., R. 15 W.

Chains

S. 89° 56' W., bet. secs. 5 and 32.

Over heavily rolling land, through scattered timber and undergrowth.

2.00 Wash, 25 lks. wide, 4 ft. deep, drains S.; asc. 100 ft. over E. slope.

7.35 Spur, slopes SE.

10.60 Wash, 40 lks. wide, 6 ft. deep, drains SE.; continue ascent of 145 ft. over E. slope.

30.60 Ridge, bears N. and S.; slopes S.; desc. 305 ft. over W. slope.

40.00 Point for the sec. cor. of secs. 5 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to cap, with brass cap marked

S32
S5
1956

Continue descent of 90 ft. over W. slope.

47.75 Rim rock, bears N. and S.; continue descent of 25 ft. over W. slope.

55.00 Round knob, slopes S.; desc. 40 ft. over W. slope.

58.65 Wash, 20 lks. wide, 3 ft. deep, drains SSW.

80.00 Point for the cor. of secs. 5, 6, 31, and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap marked

T38N R15W
S31 | S32
S6 | S5
T37N
1956

Land, rolling.
Soil, gravelly and rocky.
Timber, Joshua trees; undergrowth, blackbrush, cacti, creosote, and Spanish dagger. (large area surrounding here is burned off).

S. 89° 56' W., bet. secs. 6 and 31.

Over rolling land, through scattered timber and medium undergrowth.

.30 Wash, 20 lks. wide, 3 ft. deep, drains SSE.

13.20 Wash, 25 lks. wide, 4 ft. deep, drains S.

22.00 Wash, 10 lks. wide, 2 ft. deep, drains S.

22.90 Track road, bears N. and S.

37.70 Wash, 15 lks. wide, 4 ft. deep, drains SSE.

Survey of the North Boundary, T. 37 N., R. 15 W.

Chains

40.00

Point for the 1/4 sec. cor. of secs. 6 and 31.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap marked

1/4 S31
S6
1956

Asc. 60 ft. over gradual E. slope.

63.60

Spur, slopes S; desc. 70 ft. over SW. slope.

72.20

Top of ascent; desc. 35 ft. over W. slope.

81.18

The cor. of Ts. 37 and 38 N., Rs. 15 and 16 W. is on rolling land.

Soil, gravelly and rocky.

Timber, Joshua trees; undergrowth, blackbrush, cacti, creosote and Spanish dagger.

General Description

The land is very rolling with canyons and rocky outcroppings. It is covered with Joshua palms, cedar and pinon trees. Undergrowth consists of blackbrush, cacti, greasewood, and scattered grass. The Jacobs ranch lies approximately 2 miles west of the south boundary corner and there is also a well and windmill approximately 1/2 mile east of the 1/4 sec. cor. of secs. 13 and 18. The land classification is generally poor and is used only for grazing purposes.

WATER MARK
1956
1956
1956

1956
1956
1956

1956
1956
1956

1956
1956
1956

1956
1956
1956

1956
1956
1956

1956
1956
1956

4-680
(Feb., 1960)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Arlo P. Lloyd	Ass't. instrument man
John R. Koger	Ass't. instrument man and notekeeper
Kenneth C. Pettingill	chainman
Bob Lee Brackenburg	axeman
Paul D. Barnes	truck driver and flagman
Eugene Owens	flagman

14
12


CERTIFICATE OF CADASTRAL ENGINEER

I, George M. Boofer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22 day of September 1954,

I have surveyed the west and north boundaries of township 37 N., range 15 W.

of the G.&.S.R. Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
May 20, 1956



George M. Boofer
Cartographer (Cadastral)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., NOV 26 1956, 19

The foregoing field notes of the survey of the west and north boundaries of township 37 N., range 15 W.; Gila and Salt River meridian.

executed by George M. Boofer having been critically examined and found correct, are hereby approved.


Carl G. Harrington
Chief, Division of Cadastral Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

Chief, Division of Cadastral Engineering