

(1)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE
Original

FIELD NOTES

of the Survey of a

Portion of the Subdivision

of

Township 5 North, Range 17 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Leslie H. Godwin, Cartographer(Cadastral)

Donald E. Harding, Cartographer

Under special instructions dated January 25, 1955, which provided
for the surveys included under Group No. 303, bearing the approval of the
Commissioner of the General Land Office under date of January 25, 1955
and assignment instructions dated January 3, 1956

Survey commenced January 18, 1956

Survey completed January 27, 1956

(1A)

BOOK 4518

INDEX DIAGRAM.

Township 5 North, Range 17 West

6	5	4	5 3	2	1
7	8	9	4 10	11	12
13	17	6 16	4 15	14	18
19	20	21	3 22	23	24
30	29	28	2 27	26	25
31	9 32	8 33	1 34	35	36

Township 5 North, Range 17 West

Chains

The South boundary (First Standard Parallel North) and the East boundary were originally surveyed by J. F. Hesse in 1909. The South boundary was resurveyed by C. E. Hunter in 1927, and the East boundary was resurveyed by W. H. Thorn in 1927. The South boundary of sec. 31 was also resurveyed by Abbey, Gill and Voight in 1915. The West boundary was surveyed by C. E. Hunter in 1927 and resurveyed under Group 285 by Fred R. Chappell in 1952. The North boundary was surveyed by Otis D. Gould in 1927.

The following field notes are those of the survey of a portion of the subdivision of T. 5 N., R. 17 W., as requested by the Arizona State Land Department.

For the test of the instruments and methods used, see the notes for the survey of T. 9 N., R. 16 W.

The Geographic position of the SE. cor. of the township is in latitude $33^{\circ} 43' 28''$ N. and longitude $113^{\circ} 58' 01''$ W., as computed from the plat of T. 5 N., R. 18 W., accepted April 5, 1955. The mean magnetic declination, as determined by taking readings in secs. 16 and 32, was observed to be $15^{\circ} 00'$ E.

 Portion of the Subdivision of T. 5 N., R. 17 W.

Beginning at the standard cor. of secs. 33 and 34, on the S. bdy. of the township; an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

N. $0^{\circ} 08'$ W., bet. secs. 33 and 34.

Over rocky, rolling land; through scattered undergrowth.

3.70 Spur, slopes S. 80° E.

8.70 Spur, slopes S. 60° E.

14.90 Wash, 10 lks. wide, 2 ft. deep, drains S. 50° E.

18.30 Spur, slopes S. 70° E.

23.20 Wash, 10 lks. wide, 1 ft. deep, drains S. 60° E.; asc. 140 ft. over broken SSW. slope to cor. point.

36.90 Spur, slopes W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone 4 ft. base to top, with brass cap mkd.

$\frac{1}{4}$

S33 | S34

1956

Asc. 40 ft. over S. slope.

44.50 Ridge, bears E. and W.; desc. 170 ft. over steep, rocky N. slope.

54.40 Wash, 70 lks. wide, 1 ft. deep, drains S. 80° E.; asc. 50 ft. over S. slope.

60.70 Spur, slopes S. 80° E.; desc. 25 ft. over N. slope.

Partial Subdivision, T. 5 N., R. 17 W.

Chains

67.00 Wash, 15 lks. wide, 1 ft. deep, drains S. 30° E.; asc. 30 ft. over broken S. slope to cor. point.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T5N	R17W
S28	S27
S33	S34

1956

Raise a mound of stone, 2½ ft. base, 3 ft. high, W. of cor.

Land, broken and mountainous.
Soil, rocky.
Vegetation, scattered palo verde, saguaro and other cacti, and greasewood and ironwood.

N. 0° 08' W., bet. secs. 27 and 28.

Over steep, rocky S. slope, through scattered undergrowth.

Asc. 210 ft.

14.00 Ridge, bears S 80° E. and W.; desc. 100 ft. over N. slope.

22.20 Asc. 280 ft. over steep rocky S. slope.

33.00 Spur, slopes W.; desc. 140 ft. over steep, rocky N. slope.

38.00 Wash, 20 lks. wide, 2½ ft. deep, drains W.

39.50 Begin ascent of steep, rocky S. slope; asc. 17 ft. to cor. point.

40.00 Point for the ¼ sec. cor. of secs. 27 and 28.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.

S28	S27
-----	-----

1956

Continue ascent; asc. 370 ft. over broken S. slope to top of ridge.

42.00 Rocky spur, slopes W.

45.20 Spur, slopes W.

52.40 Spur, slopes S. 80° E.

57.20 Ridge, bears S. 70° W. and E.; desc. 90 ft. over broken N. slope.

64.20 Asc. 370 ft. over broken S. slope.

74.00 Rocky ridge, bears E. and W.; desc. 110 ft. over N. slope to cor. point.

80.00 Point for the cor. of secs. 21, 22, 27 and 28.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the

Partial Subdivision, T. 5 N., R. 17 W.

Chains

ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T5N	R17W
S21	S22
S28	S27

1956

Land, steep and mountainous.

Soil, rocky.

Vegetation, scattered palo verde, saguaro and other cacti, and greasewood.

N. 0° 08' W., bet. secs. 21 and 22.

Over steep, rocky land, through scattered undergrowth.

Asc. 65 ft. over broken S. slope.

8.30 Ridge, bears N. 10° W. and S. 30° E.

12.00 Spur, slopes N. 50° E.; desc. 800 ft. over steep, rocky N. slope.

33.60 Wash, 50 lks. wide, 1 ft. deep, drains E.; asc. steep, rocky S. slope to cor. point.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.

$\frac{1}{4}$

S21	S22
-----	-----

1956

Continue ascent; asc. 200 ft. over S. slope.

45.10 Thence, desc. 350 ft. along broken E. slope.

66.80 Wash, $1\frac{1}{2}$ chs. wide, 2 ft. deep, drains E.; asc. 60 ft. over SE. slope.

75.70 Ridge, bears N. 80° E. and S. 80° W.; desc. 30 ft. along NW. slope to cor. point.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T5N	R17W
S16	S15
S21	S22

1956

Land, steep and mountainous

Soil, rocky.

Vegetation, scattered palo verde, saguaro and other cacti, and greasewood.

Partial Subdivision, T. 5 N., R. 17 W.

Chains	
	N. 0° 08' W., bet. secs. 15 and 16. Desc. 35 ft. over rocky E. slope, through scattered undergrowth.
3.90	Wash, 50 lks. wide, 3 ft. deep, drains E.
5.00	Wash, 40 lks. wide, 2 ft. deep, drains N. 80° E.; asc. 100 ft. over S. slope.
20.00	Bottom of nearly vertical cliff; asc. 350 ft. to top.
24.00	Top of cliff, on ridge bearing N. 80° E. and S. 80° W.; desc. 320 ft. over steep rocky N. slope to cor. point.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. 1/4 S16 S15 1956
	Continue descent; desc. 90 ft. over rocky N. slope.
44.80	Spur, slopes NW.; desc. 250 ft. over N. slope.
61.90	Bottom of slope; asc. 110 ft. over general broken S. slope.
66.90	Spur, slopes S. 80° E.
74.70	Rocky knoll, bears S. 60° E. and N. 60° W.; desc. 175 ft. over N. slope.
80.00	Bottom of hill. Point for the cor. of secs. 9, 10, 15 and 16. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. T5N R17W S9 S10 S16 S15 1956
	From the above cor. point, cor. No. 3, load claim Francesca, mineral survey No. 3185, bears N. 6° 27' E., 4.38 chs. dist. Land, mountainous. Soil, rocky. Vegetation, scattered palo verde, ironwood, greasewood, saguaro, and other cacti.
	N. 0° 08' W., bet. secs. 9 and 10. Over gently rolling and broken land, through scattered undergrowth.
3.40	Road, bladed, bears E. and W.; desc. 40 ft. over N. slope.
5.60	Wash, 20 lks. wide, 6 ft. deep, drains N. 40° E.
11.60	Wash, 15 lks. wide, 1 ft. deep, drains N. 30° E.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.

Partial Subdivision, T. 5 N., R. 17 W.

Chains

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

1/4

S9 | S10

1956

45.90 Wash, 15 lks. wide, 1 ft. deep, drains N. 40° E.

52.40 Road, bladed, bears N. 30° E. and S. 30° W.

73.10 Spur, low, slopes N. 30° W.

79.40 Wash, 10 lks. wide, 6 ins. deep, drains N. 30° E.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T5N R17W

S4 | S 3

S9 | S10

1956

Land, gently rolling and broken.

Soil, gravelly and rocky.

Vegetation, scattered palo verde, ironwood, greasewood, saguaro, and other cacti.

N. 0° 05' W., bet. secs. 3 and 4.

Over rolling land, through scattered undergrowth.

2.00 Wash, 15 lks. wide, 1 ft. deep, drains N. 35° E.

19.40 Spur, slopes S. 80° E.; desc. 50 ft. over N. slope.

34.30 Wash, 20 lks. wide, 1 ft. deep, drains N. 80° E.

40.00 Point for the 1/4 sec. cor. of secs. 3 and 4.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

1/4

S4 | S3

1956

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.

65.60 Wash, 30 lks. wide, 1 ft. deep, drains N. 80° E.

81.80 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the township; a 2 in. iron post, set, mkd. and witnessed, as described in the official record.

Land, gently rolling and broken.

Soil, gravelly and rocky.

Vegetation, scattered palo verde, ironwood, greasewood, saguaro, and other cacti.

Partial Subdivision, T. 5 N., R. 17 W.

Chains

From the cor. of secs. 15, 16, 21 and 22,
S. 89° 48' W., bet. secs. 16 and 21.

Over very steep mountainous land, through scattered undergrowth.
Over inaccessible peaks by triangulation and traverse.

Asc. app. 150 ft. over steep rocky E. slope.

18.00 Foot of inaccessible pyramid peak; asc. app. 700 ft. over nearly
vertical E. slope.

25.00 Top of peak; desc. app. 450 ft. over steep rocky, broken W. slope to
cor. point.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, falls on inaccessible
point.

40.25 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 16 and 21.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground,
and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S16 \searrow W \\ S21 \nearrow C \\ 1956 \end{array}$$

Continue descent; desc. 200 ft. over W. slope.

55.00 Bottom of slope; thence over rocky broken mountainous land.

62.70 Saddle, on spur sloping N. 80° W.; desc. 140 ft. over N. slope.

Thence along broken N. slope to cor. point.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground,
and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.

$$\begin{array}{l} T5N R17W \\ S17 | S16 \\ S20 | S21 \\ 1956 \end{array}$$

Land, steep and mountainous.

Soil, rocky.

Vegetation, palo verde, greasewood, saguaro, and other cacti.

N. 0° 08' W., bet. secs. 16 and 17.

Over steep mountainous land, through scattered undergrowth.

Desc. 125 ft. over N. slope.

8.00 Bottom of draw, drains W.; asc. 250 ft. over S. slope.

15.90 Ridge, bears N. 70° W. and S. 70° E.; desc. 340 ft. along steep,
broken general E. slope.

36.30 Spur, rocky, slopes N.; desc. 80 ft. over N. slope to cor. point.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground,
and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Partial Subdivision, T. 5 N., R. 17 W.

Chains

 $\frac{1}{4}$

S17 | S16

1956

Continue descent; desc. 110 ft. over broken N. slope.

69.60 Bottom of slope; asc. 75 ft. over SE. slope.

80.00 Point for the cor. of secs. 8, 9, 16 and 17.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T5N R17W
 S 8 | S 9
 S17 | S16
 1956

From the above cor. point, U. S. Mineral Monument, No. 3184, bears S. $69^{\circ} 56'$ E., 37.45 chs. dist.

Land, steep and mountainous.

Soil, rocky.

Vegetation, palo verde, greasewood, saguaro, and other cacti.

From the cor. of secs. 9, 10, 15 and 16.

S. $89^{\circ} 51'$ W., bet. secs. 9 and 16.

Over rocky rolling hills, through scattered undergrowth.

Asc. 110 ft. over E. slope.

4.30 Ridge, rocky, bears N. 40° E. and S. 40° W.; desc. 170 ft. over W. slope.

17.30 Bottom of slope.

25.90 Wash, 25 lks. wide, 1 ft. deep, drains S. 50° W.

33.90 Spur, slopes N.

40.08 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$ S 9
 S16
 1956

From the above cor. point, cor. No. 3, Copper King Load, Mineral Survey No. 3185, bears N. $83^{\circ} 24'$ W., 20.21 lks. dist.53.30 Road, bladed, bears N. 30° E. and S. 30° W.; asc. 30 ft. over E. slope.61.20 Spur, slopes N. 45° W.; desc. 15 ft. over W. slope.66.10 Road, bladed, bears S. 50° E. and N. 50° W.68.90 Wash, 15 lks. wide, 1 ft. deep, drains S. 60° E.69.30 Road, bladed, bears S. 40° E. and N. 40° W.

Partial Subdivision, T. 5 North, Range 17 West

Chains

- 76.30 Wash, 10 lks. wide, 6 ins. deep, drains S. 40° E.; asc. 50 ft. over SW. slope.
- 79.20 Ridge, rocky, bears N. 80° E. and S. 80° W.
- 80.16 The cor. of secs. 8, 9, 16 and 17, heretofore described.
- Land, rolling foothills.
Soil, rocky.
Vegetation, palo verde, greasewood, and cacti.
-
- From the standard cor. of secs. 32 and 33 on the S. bdy. of the township; a 2 in. iron post, set, mkd. and witnessed as described in the official record.
- N. 0° 08' W., bet. secs. 32 and 33.
- Over rolling hills, through scattered undergrowth.
- .70 Spur, slopes E.
- 10.70 Wash, 20 lks. wide, 1 ft. deep, drains S. 70° E.; desc. 65 ft. over S. slope.
- 20.10 Spur, slopes E.; desc. 40 ft. over broken E. slope.
- 25.10 Spur, slopes E.
- 29.40 Wash, 30 lks. wide, 2 ft. deep; drains S. 80° E.; asc. 20 ft. over S. slope.
- 35.10 Spur, slopes S. 10° W.
- 39.00 Wash, 10 lks. wide, 1 ft. deep, drains S. 60° W.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.
- $\frac{1}{4}$
- S32 | S33
- 1956
- Asc. 55 ft. over S. slope.
- 56.30 Spur, slopes E.; desc. 20 ft. over NE. slope.
- 59.70 Wash, 15 lks. wide, 1 ft. deep, drains S. 10° E.; asc. 80 ft. over SW. slope.
- 70.40 Spur, slopes SE.; asc. 100 ft. over broken S. slope.
- 80.00 Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T5N R17W

S29 | S28

S32 | S33

1956

Partial Subdivision, T. 5 N., R. 17 W.

Chains

Land, high rolling and broken.
Soil, rocky.
Vegetation, scattered palo verde, greasewood, saguaro, and other cacti.

From the standard cor. of secs. 31 and 32 on the S. bdy. of the township; a 2 in. iron post, set, mkd. and witnessed, as described in the official record.

N. 0° 09' W., bet. secs. 31 and 32.

Over rolling hills, through scattered undergrowth.

Desc. 30 ft. over N. slope.

4.70 Wash, 20 lks. wide, 1 ft. deep, drains N. 80° E.; asc. 40 ft. over S. slope.

10.00 Spur, slopes N. 80° E.; desc. 90 ft. over steep NW. slope.

16.00 Slope changes; desc. 120 ft. along W. slope.

31.00 Wash, 30 lks. wide, 1 ft. deep, drains NE.; desc. 45 ft. over S. slope.

35.20 Spur, rocky, slopes N. 80° E.; desc. 70 ft. over N. slope.

38.60 Wash, 10 lks. wide, 1 ft. deep, drains N. 80° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$

S31 | S32

1956

Asc. 190 ft. over S. slope.

50.80 Ridge, rocky, bears N. 80° W. and S. 80° E.; desc. 20 ft. along NW. slope.

56.50 Spur, slopes NW.; continue descent, desc. 230 ft. along NW. slope.

66.20 Bottom of slope.

70.80 Wash, 25 lks. wide, 2 ft. deep, drains N. 60° E.; asc. 25 ft. over S. slope.

80.00 Spur, slopes W.

Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T5N R17W

S30 | S29

S31 | S32

1956

Land, steep and rolling.

Soil, rocky.

Vegetation, scattered palo verde, greasewood, and cacti.

BOOK 4518

Partial Subdivision, T. 5 N., R. 17 W.

Chains

From the cor. of secs. 28, 29, 32 and 33,
S. 89° 51' W., bet. secs. 29 and 32.

Over steep broken land, through scattered undergrowth.

Asc. 65 ft. to top of very steep E. slope.

- 1.10 Ridge, bears N. and S.; desc. 180 ft. along broken S. slope.
- 10.60 Spur, slopes S. 60° W.; desc. 100 ft. over steep rocky W. slope.
- 15.40 Wash, 30 lks. wide, 1 ft. deep, drains S.; asc. 120 ft. over rocky E. slope.
- 21.00 Ridge, bears N. 20° W. and S. 20° E.; desc. 95 ft. along steep broken S. slope.
- 23.80 Spur, slopes S. 20° W.
- 26.50 Spur, slopes S.
- 29.50 Wash, 15 lks. wide, 2 ft. deep, drains S. 20° E.; asc. 60 ft. over SW. slope.
- 33.00 Spur, slopes S. 70° E.; asc. 105 ft. over broken E. slope to cor. point.
- 40.02 Point for the 1/4 sec. cor. of secs. 29 and 32.
Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mdk.

1/4	S29
	S32
	1956
- Continue ascent; asc. 60 ft. over E. slope.
- 44.50 Ridge, bears N. and S.; desc. 370 ft. over broken W. slope.
- 54.10 Spur, rocky, slopes S. 70° W.
- 57.10 Wash, 30 lks. wide, 2 ft. deep, drains NW.
- 63.90 Wash, 20 lks. wide, 1 ft. deep, drains S. 20° W.; asc. 80 ft. along S. slope.
- 70.10 Top of rocky knoll; desc. 110 ft. over rocky W. slope.
- 80.04 The cor. of secs. 29, 30, 31 and 32, heretofore described.

Land, steep and broken.

Soil, rocky.

Vegetation, scattered palo verde, greasewood, saguaro, and other cacti.

General Description, T. 5 N., R. 17 W.

The land included in this survey of a portion of the subdivision of T. 5 N., R. 17 W. varies from rolling land to high mountainous peaks and ridges. The soil varies from sandy to rocky. Vegetation consists of palo verde, greasewood, saguaro, and other cacti.

General Description, T. 5 N., R. 17 W.

Chains

With the exception of seasonal grazing of cattle and mining, there is no other value, there being no inhabitants in this area. There is no perennial water supply.

The general drainage pattern is in a north and easterly direction.

(14)

CERTIFICATE OF CADASTRAL ENGINEER

I, Leslie H. Godwin, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of January, 1955 I have surveyed a portion of the subdivision of Township 5 North, Range 17 West.

of the G & S R Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

August 10, 1956
Salt Lake City, Utah

Leslie H. Godwin
Leslie H. Godwin
Cartographer (Cadastral)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., 19

The foregoing field notes of the survey of
executed by
having been critically examined and found correct, are hereby approved.

Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes.

Cadastral Engineering Staff Officer.

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of January, 1955, I have supervised the survey of a portion of the subdivision, T. 5 N., R. 17 W.

of the G & S R Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

August 10, 1956
Salt Lake City, Utah

Donald E. Harding
Donald E. Harding
Cartographer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., JAN 15 1957, 19

The foregoing field notes of the survey of a portion of the subdivision of T. 5 N., R. 17 W., G & S R Meridian, Arizona.

supervised by Donald E. Harding

having been critically examined and found correct, are hereby approved.

Carl G. Harrington
Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.