

BOOK 4526
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Original

FIELD NOTES

of the Survey of the

East and North Boundaries

and a

Portion of the Subdivision

of

Township 9 North, Range 16 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Phil D. Smith, Cartographic Survey Aid

Donald E. Harding, Cartographer

Leslie H. Godwin, Cartographer-Cadastral

Under special instructions dated January 25, 1955, which provided
for the surveys included under Group No. 303, approved January 25, 1955
and assignment instructions dated January 3, 1956

Survey commenced January 9, 1956

Survey completed January 13, 1956

4526

2
1A

BOOK 4526
INDEX DIAGRAM

Township 9 North, Range 16 West

9 6	9 5	8 4	7 17 3	7 13 2	6 12 1 5
7	8	9	16 10	12 11	12 4
18	17	19 18 16	16 15	14	13 3
19	20	18 21	15 22	23	24 3
30	29	28	14 27	26	25 2
31	21 20 32	20 33	13 34	35	11 10 36 1

16-58770-1

- Leslie H. Godwin Cartographer(Cadastral)
- Phil D. Smith Cartographic Survey Aid

T. 9 N., R. 16 W.

Chains

The south boundary (Second Standard Parallel North) was surveyed by A. T. Harris in 1915. The west boundary was surveyed by A. T. Harris in 1915.

The following field notes are those of the survey of the east and north boundaries and a portion of the subdivision of T. 9 N., R. 16 W., to mark the boundaries of those sections that normally are considered State school sections, and which survey will be of benefit to the Division of Range and Forestry, Bureau of Land Management.

The survey was executed with W. and L. E. Gurley transits Nos. 541329 and 541332, constructed in accordance with standard instrumental specifications of the Bureau of Land Management. The instruments were maintained in precise adjustment throughout the progress of the survey.

The directions of all lines of this survey were determined by tie to U.S.C. & G.S. Triangulation Station Midway, augmented by direct solar observations and hour angle observations on Polaris from time to time as the survey was carried forward.

Corners on the east-west lines were set on the true latitudinal curve by use of the tangent method. Lines connecting previously established corners were run by random and true method, but for simplification of the record the random lines are omitted from the field notes. All subdivisional corners established are calculated to be at the positions they would occupy if the entire township were subdivided.

Measurements were made with a Lufkin steel tape, 5 chains in length, graduated every one-tenth link for the first 10 links, every link for the next 90 links, and every 10 links for the balance. The tape was tested by comparison with a one chain standard steel tape and found correct. All measurements were made on the slope and the vertical angle of each interval ascertained by a clinometer in good adjustment; the horizontal equivalents alone were entered in this field note record. The lengths of all lines were determined by chaining if possible; otherwise, by traverse or triangulation. The details of such traverses or triangulations have been thoroughly verified, and in order to simplify the record, the diagrams and reductions are omitted from these field notes.

The geographic position for the SE. cor. of this township is latitude $34^{\circ} 04' 15''$ N., and longitude $113^{\circ} 52' 10''$ W., as determined by traverse from U.S.C. & G.S. Triangulation Station Midway, situated in sec. 36, T. 9 N., R. 16 W. The magnetic declination was read at a number of stations throughout the township, and the average was found to be $14\frac{1}{2}^{\circ}$ E. Triangulation Station Midway bears N. $83^{\circ} 13'$ E., 21.73 chs. dist. from the standard corner of secs. 35 and 36, T. 9 N., R. 16 W., and is in latitude $34^{\circ} 04' 16.841''$ N., and longitude $113^{\circ} 52' 55.704''$ W.

Survey of the East Boundary, T. 9 N., R. 16 W.

Beginning at the standard township cor. of Ts. 9 N., Rs. 15 and 16 W., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the survey of the Second Standard Parallel North, through R. 16 W.

North, bet. secs. 31 and 36.

Over gently rolling land, through scattered undergrowth.

6.00

Wash, 21 lks. wide, 18 ins. deep, drains W.

E. Bdy., T. 9 N., R. 16 W.

Chains
40.00Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 36 \quad | \quad \text{S } 31 \\ 1956 \end{array}$$

Deposit a rock, 4 x 6 x 4 ins., mkd. with an X. Collar of stone laid around iron post.

No bearing trees available.

61.00 Wash, 1 ch. wide, 2 ft. deep, drains W.

63.00 Fork of same wash, 10 lks. wide, 3 ft. deep, drains S. 70° W.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
$$\begin{array}{c} \text{T9N} \\ \text{R16W } \text{R15W} \\ \text{S25 } | \text{ S30} \\ \text{S36 } | \text{ S31} \\ 1956 \end{array}$$

Raise a mound of stone, 2 ft. base, to top of iron post, and deposit a rock, 4 x 3 x 4 ins., mkd. with an X alongside iron post.

Land, slightly rolling.

Soil, sandy to sandy loam.

Vegetation, scattered palo verde and saguaro cactus, dense grease-wood and mesquite.

North, bet. secs. 25 and 30.

Over slightly rolling land, through undergrowth.

6.90 Road, bladed, bears N. 41° E. and S. 41° W.15.50 Wash, 1.20 chs. wide, 3 ft. deep, drains S. 30° W.40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 25 \quad | \quad \text{S } 30 \\ 1956 \end{array}$$

41.00 Top of sandhill, sloping W.

55.80 Wash, 12 lks. wide, 2 ft. deep, drains N. 80° W.79.10 Wash, 15 lks. wide, 2 ft. deep, drains S. 20° W.

80.00 True point for cor. of secs. 19, 24, 25 and 30 falls at side of wash, where a monument cannot be perpetuated.

Point selected for witness cor. bears North, 60 lks. distance.

East Bdy. of T. 9 N., R. 16 W.

Chains

Land, slightly rolling.
Soil, gravelly.
Vegetation, scattered palo verde, mesquite, medium dense greasewood,
and cholla and saguaro cactus.

North, bet. secs. 19 and 24.

Over gently rolling land, through medium dense undergrowth.

.60 Point selected for witness cor. of secs. 19, 24, 25 and 30.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T9N
R16W R15W
S24 | S19
S25 | S30
W C
1956

Deposit a stone, 4 x 3 x 3 ins., mkd. with an X, alongside the iron post.

26.00 Wash, 15 lks. wide, 10 ins. deep, drains S. 15° E.

40.00 Point for the ¼ sec. cor. of secs. 19 and 24.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.

¼
S 24 | S 19
1956

63.00 Wash, 20 lks. wide, 2 ft. deep, drains S. 50° W.

80.00 Point for the cor. of secs. 13, 18, 19 and 24.

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone 3 ft. base to top, with brass cap mkd.

T9N
R16W R15W
S13 | S18
S24 | S19
1956

Land, rolling.
Soil, gravelly.
Vegetation, scattered palo verde, greasewood, and cholla and saguaro cactus.

North, bet. secs. 13 and 18.

Over rolling land, through medium dense undergrowth.

26.00 Wash, 10 lks. wide, 8 ins. deep, drains W.

Asc. over S. slope of spur.

East Bdy. of T. 9 N., R. 16 W.

Chains 40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, on the S. slope of spur near top.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 13 S 18 1956</p>
41.30	Small spur, slopes S. 80° E.
46.00	Wash, 8 lks. wide, 6 ins. deep, drains S. 80° E.
48.20	Spur, slopes S. 55° E.
52.00	Draw, drains S. 55° E.
62.40	Top of rocky knoll.
79.50	Wash, 10 lks. wide, 6 ins. deep, drains West 2 chs.; thence NW.
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18, falls 48 lks. N. of wash draining W.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R16W R15W S12 S 7 S13 S18 1956</p> <p>Land, rolling. Soil, gravelly. Vegetation, scattered palo verde, greasewood, saguaro and cholla cactus.</p>
	North, bet. secs. 7 and 12.
	Over rolling land, through medium dense undergrowth.
4.70	Spur, slopes W.
22.00	Wash, 10 lks. wide, 8 ins. deep, drains N. 30° W.
31.90	Spur, slopes W.
39.80	Main wash, 15 lks. wide, 2 ft. deep, drains West 1 ch.; thence SW.
40.00	True point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12 falls at bottom of wash, 10 lks. wide, 1 ft. deep, which drains SW. 25 lks. into main wash.
40.50	<p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 7 and 12.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone 3 ft. base to top, with brass cap mkd.</p>

East Bdy. of T. 9 N., R. 16 W.

Chains

$$\frac{1}{2}$$

$$S' 12 \downarrow S' 7$$

$$W C$$

$$1956$$

- 52.50 Spur, slopes W.
- 63.20 Wash, 15 lks. wide, 18 ins. deep, drains S. 75° W.; asc. 28 ft. over SSE. slope to top of small ridge.
- 70.00 Ridge, bears E. and W.; desc. 45 ft. over NNW. slope.
- 79.00 Wash, 20 lks. wide, 1 ft. deep, drains N. 20° W. 2 chs. and empties into main wash.
- 80.00 Point for the cor. of secs. 1, 6, 7 and 12, falls on W. slope of wash.
- Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
- T9N
R16W R15W
S 1 | S 6
S12 | S 7
1956
- Land, rolling.
Soil, gravelly.
Vegetation, scattered palo verde, medium dense greasewood, saguaro and cholla cactus.

North, bet. secs. 1 and 6.

Over rolling land, through medium dense undergrowth.

- .85 Main wash, 20 lks. wide, 2 ft. deep, drains W.; asc. 50 ft. over S. slope.
- 11.40 Saddle in small ridge, bearing E. and W.; desc. 65 ft. over N. slope.
- 19.50 Wash, 25 lks. wide, 1 ft. deep, drains N. 20° W.; asc. 45 ft. over SSW. slope.
- 32.10 Spur, slopes W.; desc. 50 ft. over NNE. slope.
- 37.50 Small wash, drains N. 10° W.
- 40.00 Point for the ¼ sec. cor. of secs. 1 and 6.
- Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base to top; with brass cap mkd.
- $\frac{1}{4}$
S 1 | S 6
1956
- 51.90 Wash, 20 lks. wide, 6 ins. deep, drains N. 25° W.
- 65.64 Spur, slopes N. 85° W.

East Bdy. of T. 9 N., R. 16 W.

Chains

79.50

Wash, 15 lks. wide, 6 ins. deep, drains W.

80.00

Point for the cor. of Ts. 9 and 10 N., Rs. 15 and 16 W.

Set an iron post, 30 ins. long, 2½ ins. diam., over an X cut in solid rock, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T10N
R16W R15W
S36 | S31
S 1 | S 6
T9N
1956

Land, rolling.
Soil, gravelly.
Vegetation, scattered palo verde, medium dense greasewood, and cholla cactus.

Survey of the North Boundary, T. 9 N., R. 16 W.

From the cor. of Ts. 9 and 10 N., Rs. 15 and 16 W.

West, bet. secs. 1 and 36.

Over rolling land, through medium dense undergrowth.

.80

Wash, 15 lks. wide, 6 ins. deep, changing its course from W. to SW.

4.45

Spur, slopes N. 30° E.

12.00

Wash, 20 lks. wide, 10 ins. deep, drains SW. 1 ch.; thence NW.

15.20

Same wash, drains NW.

21.00

Road, bladed, bears S. 10° W. and N. 10° E.

30.00

Same wash, 50 lks. wide, 1 ft. deep, drains W. 2.50 chs.; thence NW.

40.00

Point for the ¼ sec. cor. of secs. 1 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

¼ S 36
S 1
1956

51.70

Spur, slopes N. 20° W.

72.00

Wash, 10 lks. wide, 6 ins. deep, drains N.

80.00

Point for the cor. of secs. 1, 2, 35 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T10N R16W
S35 | S36
S 2 | S 1
T9N
1956

North Bdy. of T. 9 N., R. 16 W.

Chains

Land, rolling.
Soil, gravelly.
Vegetation, scattered palo verde, saguaro and cholla cactus, and medium dense greasewood.

West, bet. secs. 2 and 35.

Over rolling land, through medium dense undergrowth.

Asc. 95 ft. over E. slope to top of spur.

10.90 Spur, slopes N.; desc. 100 ft. over W. slope into valley.

20.30 Enter valley.

29.20 Wash, 10 lks. wide, 5 ins. deep, drains N. 25° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on gentle S. slope.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 4½ ft. base to top, with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 35}{S\ 2}$
1956

56.70 Spur, slopes S.

66.50 Road, bladed, bears S. 20° E. and N. 20° W., then changes direction to W. 2 chs. further.

80.00 Point for the cor. of secs. 2, 3, 34 and 35, falls on small spur, sloping SW.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T10N R16W
 $\frac{S34\ S35}{S\ 3\ S\ 2}$
T9N
1956

Land, rolling.
Soil, gravelly.
Vegetation, scattered palo verde, ocotillo, medium dense greasewood, and saguaro and cholla cactus.

West, bet. secs. 3 and 34.

Over slightly rolling land, through scattered undergrowth.

18.50 Wash, 12 lks. wide, 2 ft. deep, drains S.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, falls on W. slope 1 ch. East of small wash, draining S. 10° W.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

North Bdy., T. 9 N., R. 16 W.

Chains

$$\frac{1}{2} \frac{S 34}{S 3}$$

1956

- 41.00 Wash, 10 lks. wide, 3 ft. deep, drains S. 10° W.
- 51.20 Road, bladed, bears N. and S.; 2 chs. further N. changes direction to NE.
- 76.80 Wash, 15 lks. wide, 1 ft. deep, drains South 1 ch.; thence SW.
- 80.00 Point for the cor. of secs. 3, 4, 33 and 34, falls on SE. slope.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T10N R16W

S33	S34
S 4	S 3

T9N

1956

Land, slightly rolling.
Soil, gravelly.
Vegetation, scattered palo verde, greasewood, ocotillo, cholla and rat tail cactus.

West, bet. secs. 4 and 33.

Over slightly rolling land, through scattered undergrowth.

- 21.00 Wash, 10 lks. wide, 6 ins. deep, drains SW.
- 24.40 Spur, slopes S. 20° W.
- 30.00 Wash, 15 lks. wide, 10 ins. deep, drains South 3 chs.; thence SW.
- 40.00 Point for the ¼ sec. cor. of secs. 4 and 33.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

$$\frac{1}{2} \frac{S 33}{S 4}$$

1956

- 52.70 Forks of wash, main wash 15 lks. wide, 1 ft. deep, drains S.
- 57.40 Road, bladed, bears N. and S.
- 66.20 Small spur, sloping S.
- 80.00 Point for the cor. of secs. 4, 5, 32 and 33, falls on E. edge of small wash.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T10N R16W

S32	S33
S 5	S 4

T9N

1956

North Bdy., T. 9 N., R. 16 W.

Chains

Land, slightly rolling.
Soil, gravelly.
Vegetation, scattered palo verde, greasewood, ocotillo, and cholla and rat tail cactus.

West, bet. secs. 5 and 32.

Over slightly rolling land, through scattered undergrowth.

35.40 Leave valley; begin ascent of E. slope of rocky spur.

37.30 Wash, 15 lks. wide; 20 ins. deep; drains S. 70° E.

40:00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32 falls 2 chs. South of deep wash, draining S. 70° E.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 32 \\ S 5 \end{array}$$

1956

Asc. 115 ft. over E. slope.

52.70 Spur, slopes N. 10° W.; desc. 75 ft. over W. slope.

61.50 Wash, 15 lks. wide, 1 ft. deep, drains North 1 ch. into main wash.

76.50 Wash, 10 lks. wide, 30 ins. deep, drains North 1 ch. into main wash.

79.70 Point selected for witness cor. of secs. 5, 6, 31 and 32.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

$$\begin{array}{c} T10N R16W \\ W \leftarrow \begin{array}{l} S31 | S32 \\ S 6 | S 5 \end{array} \\ C \\ T9N \\ 1956 \end{array}$$

80.00 True point for the cor. of secs. 5, 6, 31 and 32, falls on E. side of small wash where monument cannot be perpetuated.

Land, rolling.
Soil, gravelly.
Vegetation, scattered palo verde, ocotillo, greasewood, cholla and rat tail cactus.

West, bet. secs. 6 and 31.

Over broken land, through scattered undergrowth.

Asc. 420 ft. over E. slope.

39.00 East rim of canyon; desc. 40 ft. over steep SW. slope to cor. point.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31 falls on steep SW. slope.

North Bdy., T. 9 N., R. 16 W.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., over an X cut in solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

$$\frac{1}{2} \frac{S \ 31}{S \ 6}$$

1956

Continue descent; desc. 220 ft. over steep SW. slope.

50.60 Wash, at bottom of canyon, 25 lks. wide, 2 ft. deep, drains S. 70° E. for 2.50 chs.; thence S.; asc. 250 ft. over ENE. slope.

68.60 Rocky spur, slopes N. 15½° W.; desc. 75 ft. over WSW. slope.

73.70 Draw, drains NW.; asc. 135 ft. over ENE. slope to cor.

80.00 The cor. of Ts. 9 and 10 N., Rs. 16 and 17 W., an iron post, set, mkd. and witnessed as described in the official record.

Land, broken, projecting ledges.

Soil, rocky.

Vegetation, scattered palo verde, greasewood, ocotillo, and saguaro and cholla cactus.

Survey of a Portion of the Subdivision, T. 9 N., R. 16 W.

From the standard cor. of secs. 35 and 36, on the S. bdy. of the township, which is monumented with a 3 in. iron post, set, mkd. and witnessed as described in the official record.

N. 0° 01' W., bet. secs. 35 and 36.

Over slightly rolling land, across rocky washes, through scattered undergrowth.

1.60 Wash, 100 lks. wide, 8 ins. deep, drains S. 50° W.

6.60 Wash, 150 lks. wide, 5 ins. deep, drains SW.

8.80 Windmill, bears East, 10 lks. dist.

9.40 Wash, 130 lks. wide, 10 ins. deep, drains S. 50° W.

17.00 Road, bladed, bears N. 20° W. and S. 20° E.

20.00 Wash, 200 lks. wide, 18 ins. deep, drains S. 40° W.

22.70 Wash, 70 lks. wide, 12 ins. deep, drains S. 40° W.

25.50 Road, bladed, bears NW. and SE.

26.30 Power line, bears NW. and SE.

30.40 Wash, 40 lks. wide, 12 ins. deep, drains S. 40° W.

40.00 Point for the ¼ sec. cor. of secs. 35 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

Portion of Subdivision, T. 9 N., R. 16 W.

Chains

$\frac{1}{4}$
 S 35 | S 36
 1956

Raise a mound of stone, 2 ft. base, 18 ins. high, W. of cor.

43.50 Wash, 40 lks. wide, 10 ins. deep, drains S. 40° E.

77.00 Wash, 7 lks. wide, 10 ins. deep, drains SE.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T9N R16W

$\frac{S26}{S35}$ | $\frac{S25}{S36}$

1956

Raise a mound of stone, 2 ft. base, 18 ins. high, W. of cor.

Land, slightly rolling.

Soil, sandy.

Vegetation, scattered palo verde, greasewood, and ironwood.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the township.

S. 89° 59' W., bet. secs. 25 and 36.

Over nearly level land, through scattered undergrowth.

4.85 Road, bladed, bears NE. and SW.

6.05 Railroad bed, bears NE. and SW. (Abandoned).

13.05 Wash, 140 lks. wide, 14 ins. deep, drains S. 10° E.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{S 25}{S 36}$
 $\frac{1}{4}$
 1956

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

69.85 Wash, 70 lks. wide, 8 ins. deep, drains S. 10° E.

79.75 Road, Bouse to Alamo Crossing, Arizona, bladed, bears N. 40° W. and S. 40° E.

80.04 The cor. of secs. 25, 26, 35 and 36.

Land, gently rolling.

Soil, sand.

Vegetation, scattered palo verde, ironwood, saguaro, and greasewood.

Portion of Subdivision, T. 9 N., R. 16 W.

Chains	<p>From the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the township.</p> <p>S. 0° 01' E., bet. secs. 1 and 2.</p> <p>Over slightly rolling land, through medium dense undergrowth.</p> <p>9.71 Spur, slopes S. 80° E.</p> <p>26.60 Road, bladed, bears E. and W.</p> <p>29.00 Wash, 30 lks. wide, 2½ ft. deep, drains N. 80° W.</p> <p>40.06 Point for the ¼ sec. cor. of secs. 1 and 2.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">¼ S 2 S 1 1956</p> <p>80.06 Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R16W S 2 S 1 S11 S12. 1956</p> <p>Land, slightly rolling. Soil, gravelly. Vegetation, medium dense greasewood, scattered palo verde, catclaw, and cactus.</p>
40.00	<p>West, bet. secs. 2 and 11.</p> <p>Over rolling land, through medium dense undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 2 and 11.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">¼ S 2 S 11 1956</p> <p>58.50 Wash, 8 lks. wide, 3 ft. deep, drains S. 50° W.</p> <p>72.30 Wash, 10 lks. wide, 3½ ft. deep, drains S.</p> <p>80.00 Point for the cor. of secs. 2, 3, 10 and 11.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p>

Portion of Subdivision, T. 9 N., R. 16 W.

Chains

T9N R16W

S 3	S 2
S10	S11

1956

Land, slightly rolling.
Soil, gravelly.
Vegetation, medium dense greasewood and catclaw, scattered palo verde and ocotillo.

N. 0° 01' W., bet. secs. 2 and 3.

Over slightly rolling land, through medium dense undergrowth.

26.00 Wash, 8 lks. wide, 3 ft. deep, drains SE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, falls on gentle W. slope, 1.50 chs. E. of small wash draining S. 30° E.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone to top with 3½ ft. base, with brass cap mkd.

S 3	S 2
-----	-----

1956

80.03 The cor. of secs. 2, 3, 34 and 35, previously described.

Land, slightly rolling.
Soil, gravelly.
Vegetation, medium dense greasewood, cholla and saguaro cactus, scattered palo verde and Brigham tea.

From the standard cor. of secs. 33 and 34, on the S. bdy. of the township, which is monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the survey of the Second Standard Parallel North, through R. 16 W.

N. 0° 02' W., bet. secs. 33 and 34.

Over rolling sand hills, through scattered undergrowth.

28.30 Wash, 30 lks. wide, 18 ins. deep, drains SW.

33.00 Top of low sand hill, bears SW. and N. 60° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

S 33	S 34
------	------

1956

Deposit broken glass alongside the iron post for witness.

Portion of Subdivision, T. 9 N., R. 16 W.

Chains

60.00 Asc. 110 ft. over S. slope of rocky ridge.
 65.60 Rocky ridge, bears N. 50° E. and S. 70° W.; desc. 85 ft. over N. slope.
 70.50 Bottom of slope; continue over rolling sand hills.
 80.00 Point for the cor. of secs. 27, 28, 33 and 34.
 Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T9N R16W
 S28 | S27
 S33 | S34

1956

Deposit broken glass alongside iron post for witness.

Land, rolling.
 Soil, sand.
 Vegetation, scattered saguaro and other species of cactus, greasewood, short brush and grass.

N. 0° 02' W., bet. secs. 27 and 28.

Over rolling sand hills, through scattered undergrowth.

27.10 Road, bladed, bears NW. and SE.
 28.40 Power line, bears NW. and SE.
 28.60 Wash, 20 lks. wide, 14 ins. deep, drains NW.
 29.30 Power line, bears NW. and SE.
 35.10 Wash, 10 lks. wide, 18 ins. deep, course W.
 40.00 Point for the ¼ sec. cor. of secs. 27 and 28.
 Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone 3 ft. base to top, with brass cap mkd.

¼
 S 28 | S 27

1956

48.90 Wash, 20 lks. wide, 12 ins. deep, drains SE.; asc. 56 ft. over S. slope.
 60.00 Spur, slopes S. 70° W.; desc. N. slope of spur.
 65.00 Asc. 95 ft. over S. slope.
 69.80 Rocky ridge, bears E. and W.; desc. 75 ft. along E. slope of spur, top of which slopes N. 30° W.
 80.00 Point for the cor. of secs. 21, 22, 27 and 28, which falls at the bottom of E. slope.

Portion of the Subdivision, T. 9 N., R. 16 W.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T9N R16W
 S21 | S22
 S28 | S27

1956

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, steeply rolling hills.

Soil, sandy and rocky.

Vegetation, scattered saguaro and other cactus, palo verde, greasewood, and short brush.

N. 0° $02'$ W., bet. secs. 21 and 22.

Over rolling hills, through scattered undergrowth.

1.20 Wash, 20 lks. wide, 24 ins. deep, drains N. 70° W.

4.70 Wash, 50 lks. wide, 24 ins. deep, drains W.; asc. 165 ft. over W. slope, over spurs sloping SW. to W.

13.50 Spur, slopes SW.

18.50 Spur, slopes W.

23.40 Spur, slopes W.; desc. 26 ft. along W. slope.

26.40 Bottom of descent; asc. 138 ft. over S. slope.

35.95 Rocky ridge, bears N. 70° E. and S. 80° W.; desc. over N. to NW. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

$\frac{1}{4}$
 S 21 | S 22
 1956

Asc. 112 ft. over rocky W. slope.

49.50 Ridge, rocky, bears N. 70° W. and S. 70° E.; desc. 120 ft. over NNE. slope.

58.20 Wash, 20 lks. wide, 36 ins. deep, drains N. 70° E.; asc. 42 ft. over S. slope.

63.20 Spur, slopes E.; desc. 104 ft. over E. slope.

75.60 Bottom of slope; thence over rolling, rocky land.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Portion of Subdivision, T. 9 N., R. 16 W.

Chains

T9N R16W

S16 | S15

S21 | S22

1956

Land, steeply rolling hills.
Soil, rocky.
Vegetation, scattered saguaro and other cactus, palo verde, and greasewood.

N. 0° 02' W., bet. secs. 15 and 16.

Over rolling, rocky hills, through scattered undergrowth.

40.00 Point for the 1/4 sec. cor. of secs. 15 and 16.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4

S 16 | S 15

1956

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

44.00 Wash, 30 lks. wide, 18 ins. deep, drains N. 70° W.

56.30 Road, bladed, bears N. 20° W. and S. 20° E.

76.40 Wash, 30 lks. wide, 12 ins. deep, drains S. 80° W.

80.00 Point for the cor. of secs. 9, 10, 15 and 16.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T9N R16W

S 9 | S10

S16 | S15

1956

Land, rolling.
Soil, rocky.
Vegetation, scattered palo verde, saguaro and other species of cactus, and greasewood.

N. 0° 02' W., bet. secs. 9 and 10.

Over gradually rolling land, across scattered washes, through medium scattered undergrowth.

15.10 Wash, 40 lks. wide, 10 ins. deep, drains W.

18.40 Wash, 20 lks. wide, 12 ins. deep, drains SW.

22.40 Wash, 10 lks. wide, 12 ins. deep, drains SW.

29.00 Wash, 15 lks. wide, 14 ins. deep, drains S. 40° W.

40.00 Point for the 1/4 sec. cor. of secs. 9 and 10.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Portion of Subdivision, T. 9 N., R. 16 W.

Chains

$$\frac{1}{4}$$

S 9		S 10
-----	--	------

1956

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

76.19 Road, bladed, bears NE. and SW.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T9N R16W

S 4		S 3
-----	--	-----

S 9		S 10
-----	--	------

1956

Land, rolling.

Soil, sandy and rocky.

Vegetation, scattered saguaro and other species of cactus, palo verde, and greasewood.

N. 0° 09' E., bet. secs. 3 and 4.

Over rocky rolling hills, across scattered washes, through scattered undergrowth.

1.90 Wash, 20 lks. wide, 14 ins. deep, drains S. 60° W.

11.40 Wash, 10 lks. wide, 6 ins. deep, drains S. 30° W.

31.00 Wash, 10 lks. wide, 18 ins. deep, drains S. 30° W.

35.30 Wash, 10 lks. wide, 10 ins. deep, drains S. 20° W.

40.00 Point for the ¼ sec. cor. of secs. 3 and 4.

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone, 2½ ft. base to top, with brass cap mkd.

$$\frac{1}{4}$$

S 4		S 3
-----	--	-----

1956

53.00 Wash, 10 lks. wide, 10 ins. deep, drains S. 30° W.

75.30 Wash, 20 lks. wide, 14 ins. deep, drains S. 40° W.

80.17 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the township, an iron post, 2½ ins. diam., previously described.

Land, rolling.

Soil, sandy and rocky.

Vegetation, scattered palo verde, saguaro and other species of cactus, and greasewood.

Portion of Subdivision, T. 9 N., R. 16 W.

Chains

From the cor. of secs. 15, 16, 21 and 22, previously described.
West, bet. secs. 16 and 21.

Over rolling, rocky hills, through scattered undergrowth.

4.10 Wash, 15 lks. wide, 12 ins. deep, drains N.

7.20 Wash, 20 lks. wide, 8 ins. deep, drains N.

18.40 Wash, 20 lks. wide, 14 ins. deep, drains NW.

28.80 Begin ascent of E. slope; asc. 75 ft.

36.70 Rocky ridge, bears S. and N. 20° W.; desc. 45 ft. over N. slope to cor. point.

40.00 Point for the ¼ sec. cor. of secs. 16 and 21.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

¼ $\frac{S 16}{S 21}$
1956

Continue to desc. along N. slope; desc. 60 ft.; thence over nearly level land.

46.50 Wash, 12 lks. wide, 10 ins. deep, drains N. 20° W.

53.40 Wash, 10 lks. wide, 12 ins. deep, drains N.

62.90 Wash, 150 lks. wide, 12 ins. deep, drains N. 30° W.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R16W
S17 | S16
S20 | S21
1956

Deposit broken glass alongside iron post for witness.

Land, slightly rolling.

Soil, sandy.

Vegetation, palo verde, cacti, and greasewood.

N. 0° 02' W., bet. secs. 16 and 17.

Over slightly rolling land, across rocky washes, through scattered undergrowth.

7.40 Wash, 10 lks. wide, 16 ins. deep, drains W.

23.00 Wash, 10 lks. wide, 8 ins. deep, drains W.

27.90 Wash, 15 lks. wide, 13 ins. deep, drains S. 60° W.

30.00 Spur, small, slopes S. 60° W.

32.10 Wash, 40 lks. wide, 15 ins. deep, drains S. 70° W.

Portion of Subdivision, T. 9 N., R. 16 W.

Chains									
35.60	Wash, 130 lks. wide, 14 ins. deep, drains S. 70° W.								
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.								
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.								
	$\frac{1}{4}$ <table style="margin: auto;"> <tr> <td>S 17</td> <td> </td> <td>S 16</td> </tr> <tr> <td colspan="3" style="text-align: center;">1956</td> </tr> </table>	S 17		S 16	1956				
S 17		S 16							
1956									
	Raise a mound of stone, 2½ ft. base, 18 ins. high, W. of cor.								
46.50	Road, bladed, bears SW. and NE.								
60.00	Wash, 130 lks. wide, 16 ins. deep, drains SW.								
74.40	Wash, 10 lks. wide, 8 ins. deep, drains S. 10° W.								
80.00	Point for the cor. of secs. 8, 9, 16 and 17.								
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin: auto;"> <tr> <td colspan="2" style="text-align: center;">T9N R16W</td> </tr> <tr> <td style="text-align: center;">S 8</td> <td style="text-align: center;"> S 9</td> </tr> <tr> <td style="text-align: center;">S 17</td> <td style="text-align: center;"> S 16</td> </tr> <tr> <td colspan="2" style="text-align: center;">1956</td> </tr> </table>	T9N R16W		S 8	S 9	S 17	S 16	1956	
T9N R16W									
S 8	S 9								
S 17	S 16								
1956									
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.								
	Land, nearly level.								
	Soil, sandy and rocky.								
	Vegetation, scattered palo verde, cacti, and greasewood.								

	From the cor. of secs. 9, 10, 15 and 16.						
	West, bet. secs. 9 and 16.						
	Over nearly level land, through scattered undergrowth.						
11.40	Road, bladed, bears N. 10° W. and S. 10° E.						
22.00	Fork of same road, bears N. 80° W. and S. 80° E.						
23.80	Wash, 10 lks. wide, 24 ins. deep, drains S. 60° W.						
33.00	Wash, 2 chs. wide, 14 ins. deep, drains SW.						
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.						
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.						
	$\frac{1}{4}$ <table style="margin: auto;"> <tr> <td>S 9</td> <td style="text-align: center;"> </td> <td>S 16</td> </tr> <tr> <td colspan="3" style="text-align: center;">1956</td> </tr> </table>	S 9		S 16	1956		
S 9		S 16					
1956							
	Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.						

Portion of Subdivision, T. 19 N., R. 16 W.

Chains
40.50
62.00
63.80
75.70
80.00

Same road, bears N. 50° E. and S. 50° W.
Wash, 14 lks. wide, 12 ins. deep, drains S. 20° W.
Wash, 20 lks. wide, 6 ins. deep, drains S. 10° W.
Wash, 20 lks. wide, 10 ins. deep, drains S. 10° W.
The cor. of secs, 8, 9, 16 and 17.

Land, nearly level.
Soil, sandy and rocky.
Vegetation, scattered palo verde, cacti, and greasewood.

40.00

From the standard cor. of secs. 32 and 33, on the S. bdy. of the township, a 3 in. iron post, set, mkd. and witnessed as described in the official record.

N. 0° 02' W., bet. secs. 32 and 33.

Over rolling sand hills, through scattered undergrowth.

Point for the 1/4 sec. cor. of secs. 32 and 33.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




Build a collar of rock around the iron post.

Continue over rolling sand hills.

80.00

Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Build a collar of rock around the iron post.

Land, slightly rolling.

Soil, sand.

Vegetation, scattered saguaro and other species of cactus, and greasewood.

27.50

From the standard cor. of secs. 31 and 32, on the S. bdy. of the township, a 3 in. iron post, set, mkd. and witnessed as described in the official record.

N. 0° 03' W., bet. secs. 31 and 32.

Over rolling sand hills, through scattered undergrowth.

Wash, 7 lks. wide, 18 ins. deep, drains SW.

Portion of Subdivision, T. 9 N., R. 16 W.

Chains

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S 31 | S 32

1956

Build a collar of rock around the iron post.

80.00

Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T9N R16W

S30 | S29

S31 | S32

1956

Build a collar of stone around the iron post.

Land, rolling.

Soil, sand.

Vegetation, scattered saguaro and other species of cactus, and greasewood.

From the cor. of secs. 28, 29, 32 and 33.

West, bet. secs. 29 and 32.

Over rolling sand hills, through scattered undergrowth.

5.00

Wash, 10 lks. wide, 10 ins. deep, drains SW.

39.93

Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S 29

S 32

1956

Build a collar of rock around the iron post.

79.86

The cor. of secs. 29, 30, 31 and 32.

Land, rolling.

Soil, sand.

Vegetation, scattered saguaro and other species of cactus, and greasewood.

General Description

The land in Township 9 North, Range 16 West, is nearly level to rolling in most of the southern half. The northeast portion is rolling with a few low rocky spurs and hills. The northwest portion changes from rolling to mountainous going toward the northwest corner. The soil is predominantly sand, which changes to gravel mixed with sandy loam and clay in the vicinity of rocky hills and spurs, which are composed mostly of granite.

T. 9 N., R. 16 W.

Chains

Numerous shallow washes are in evidence throughout the township and the general drainage pattern is toward the southwest, with the exception of the northeast corner, where the drainage pattern is toward the north and northeast.

The Parker Dam - Phoenix power line crosses over the southwest corner of the township, entering the township on the west boundary near the southwest corner of section 18 and projecting through the township on a bearing of about S. 60° E. until it crosses the Second Standard Parallel North (south boundary of the township) near the standard section corner of section 36.

No hard surfaced roads are in this township, but two gravel roads enter it. One extends from State Highway 72 at Bouse and enters the township on the south boundary of section 36, proceeding in a general NNW. direction toward the north boundary. In section 9 it forks, one fork crossing the north boundary of the township on the north boundary of section 3, and the other on the north boundary of section 4. The other road extends out from State Highway 72 near Parker and enters this township approximately on the west boundary of section 18 and then proceeds in a general ENE. direction, where it junctions with the other road near the south boundary of section 9.

The only water noted in the township was the presence of a windmill on the west boundary of section 36.

The vegetation consists of saguaro, palo verde, ocotillo, greasewood, mesquite, iron wood, cacti, and some bunch grass.

The only apparent revenue derived from the land appeared to be seasonal grazing of cattle.

4-680
(Feb., 1950)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Alburn D. Griffin	Notekeeper
Steve Stanley Dailey, Jr.	Notekeeper
Deon Allen	Chainman
Henry C. Stanford	Chainman
John Trammel	Flagman
Freddy H. Jones	Flagman
Earl Morgan	Truck Driver
Andrew Nelson	Truck Driver, Cornerman

24 26

CERTIFICATE OF CADASTRAL ENGINEER

We ~~XX~~ Phil D. Smith and Leslie H. Godwin _____, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 25th day of January, 1955

We ~~X~~ have surveyed the East and North boundaries and a portion of the subdivision of
Township 9 North, Range 16 West.

of the G & S R Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by ~~me and under my direction~~ us
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

July 31, 1956
Salt Lake City, Utah

Phil D. Smith
Leslie H. Godwin
Phil D. Smith and Leslie H. Godwin
Cartographic Survey Aid - Cartographer-Cadastral

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., _____, 19____

The foregoing field notes of the survey of _____
executed by _____
having been critically examined and found correct, are hereby approved.

Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____
_____, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.

25
28

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 25th day of January, 1956,
I have ~~surveyed~~ supervised the survey of the East and North boundaries and a portion
of the subdivision of Township 9 North, Range 16 West.

of the G & S R Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

July 31, 1956
Salt Lake City, Utah

Donald E. Harding
Donald E. Harding
Cartographer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., JAN 15 1957, 19

The foregoing field notes of the survey of the East and North boundaries and a portion
of the subdivision of T. 9 N., R. 16 W., G & S R Meridian, Arizona.

supervised
~~executed~~ by Donald E. Harding

having been critically examined and found correct, are hereby approved.

Carl G. Harrington
Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____
_____, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.