

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

Original
FIELD NOTES

of the

Survey

of

The East and West Boundaries

and

Partial Subdivision

of

Township 12 North, Range 12 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Phil D. Smith, Cartographic Survey Aid

Donald E. Harding, Cartographer

Under special instructions dated January 25, 1955, which provided
for the surveys included under Group No. 303, bearing the approval of the
Commissioner of the General Land Office under date of January 25, 1955
and assignment instructions dated January 3, 1956

Survey commenced February 13, 1956

Survey completed March 2, 1956

4527

4527

BOOK 4527

INDEX DIAGRAM.

Township 12 North, Range 12 West

9 6	5	4	3	12 2	11 1 4
				12	10
8 7	8	9	10	11	12 4
7 18	17	16	15	14	13 3
7 19	20	21	22	23	24 2
6 30	29	28	27	26	25 2
5 31	32	33	34	35	36 1

Township 12 North, Range 12 West

Chains

The north boundary (Third Standard Parallel North) was surveyed by A. N. Oliver in 1911, and the south boundary by Hugo Price in 1917.

The following notes are those of the survey of the east and west boundaries and partial subdivision.

For the test of the instruments and methods used, see the notes for T. 9 N., R. 16 W. of this group.

The geographic position of the SE. cor. of the township is latitude $34^{\circ} 19' 52''$ N. and longitude $113^{\circ} 27' 22''$ W., as computed from the plat of T. 11 N., R. 12 W., approved January 28, 1919. The mean magnetic declination is 15° E.

The East Boundary of T. 12 N., R. 12 W.

From the cor. of Tps. 11 and 12 N., Rs. 11 and 12 W., which is monumented with an iron post, set, mkd. and witnessed as described in the official record.

North, bet. secs. 31 and 36.

Over high, rolling hills, through scattered undergrowth.

Asc. 325 ft. over SW. slope.

37.00 Spur, slopes SE.; desc. 30 ft. over NE. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam, 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S36 | S31

1956

raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Asc. 50 ft. over SE. slope.

42.50 Spur, slopes E.; desc. 260 ft. over rolling NNE. slope.

58.50 S. edge of wash, course W.

64.50 N. edge of same wash; asc. 160 ft. over S. slope.

75.80 Road, track, bears NE. and SW.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T12N

R12W | R11W

S25 | S30

S36 | S31

1956

Land, high and rolling.

Soil, rocky clay.

Undergrowth, scattered palo verde, catclaw, greasewood, saguaro, cholla and barrel cactus.

East Boundary, T. 12 N., R. 12 W.

Chains

North, bet. secs. 25 and 30.

Asc. 115 ft. over S. slope, through scattered undergrowth.

9.50 Spur, slopes W.; desc. 130 ft. over N. slope.

13.50 S. edge of wash, course W.

18.50 N. edge of same wash; asc. 60 ft. over broken SW. slope.

21.00 Wash, 60 lks. wide, 3 ft. deep, course SW.

35.20 Wash, 30 lks. wide, 5 ft. deep, course SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

S25 | S30

1956

raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Asc. 140 ft. over SE. slope.

57.40 Spur, slopes S. 70° W.; desc. 65 ft. over NNW. slope.

71.20 Wash, 15 lks. wide, 4 ft. deep, course SW.

80.00 Point for the cor. of secs. 19, 24, 25 and 30.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T12N

R12W R11W

S24 | S19

S25 | S30

1956

Land, high and rolling.

Soil, rocky clay.

Undergrowth, scattered palo verde, catclaw, greasewood, saguaro, cholla, and barrel cactus.

North, bet. secs. 19 and 24.

Over rolling land, through scattered undergrowth.

5.00 Wash, 20 lks. wide, 3 ft. deep, course W.; asc. 120 ft. over S. slope.

37.00 Spur, low, slopes W.

37.80 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$

W C

S24 | S19

1956

East Boundary, T. 12 N., R. 12 W.

Chains

raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

40.00

True point for the 1/4 sec. cor. of secs. 19 and 24 falls in center of a wash, 1 1/2 chs. wide, 5 ft. deep, course W.; asc. 140 ft. over S. slope.

50.50

Spur, slopes W.; desc. 30 ft. over N. slope.

63.20

Wash, 15 lks. wide, 4 ft. deep, course W.; asc. 70 ft. over SW. slope.

80.00

Point for the cor. of secs. 13, 18, 19 and 24.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T12N
R12W R11W
S13 | S18
S24 | S19
1956

Land, high and rolling.

Soil, rocky clay.

Undergrowth, scattered palo verde, catclaw, greasewood, saguaro, cholla, and barrel cactus.

North, bet. secs. 13 and 18.

Asc. 90 ft. over SW. slope, through scattered undergrowth.

8.00

Rocky knoll; asc. 90 ft. over WSW. slope.

29.30

Spur, slopes S. 10° W. from N. 20° E.; asc. 80 ft. over W. slope.

36.50

Small draw, course S. 20° W.; desc. 20 ft. over W. slope.

40.00

Point for the 1/4 sec. cor. of secs. 13 and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.

1/4
S13 | S18
1956

Asc. 160 ft. over broken WSW. slope.

80.00

Point for the cor. of secs. 7, 12, 13 and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T12N
R12W R11W
S12 | S7
S13 | S18
1956

Land, high and rolling.

Soil, rocky clay.

Undergrowth, scattered palo verde, catclaw, greasewood, saguaro, cholla, and barrel cactus.

East Boundary, T. 12 N., R. 12 W.

Chains	
	North, bet. secs. 7 and 12. Asc. 30 ft. over S. slope.
8.00	Spur, slopes W.; thence over bench.
21.15	S. rim of canyon, bears E. and W.; desc. 185 ft. over N. slope.
28.50	Wash, 2 chs. wide, 3 ft. deep, course W.; asc. 155 ft. over S. slope.
34.80	N. rim of canyon, bears E. and W.
37.80	Spur, slopes W.; desc. 30 ft. over N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S12 S7 1956
	raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of cor. Desc. 20 ft. over NE. slope.
46.60	Wash, 20 lks. wide, 3 ft. deep, course S. 10° W.; asc. 560 ft. over SW. slope.
75.00	Top of ascent, W. side of high rocky knoll; desc. 190 ft. over WNW. slope.
80.00	Point for the cor. of secs. 1, 6, 7 and 12. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in the ground, in a mound of stone to top, with brass cap mkd. T12N R12W R11W S 1 S 6 S12 S 7 1956
	Land, high and rolling. Soil, rocky clay. Undergrowth, scattered palo verde, catclaw, greasewood, saguaro, cholla, and barrel cactus.
	North, bet. secs. 1 and 6. Desc. 140 ft. over NW. slope.
6.00	Wash, 30 lks. wide, 4 ft. deep, course W.; asc. 70 ft. over SW. slope.
19.20	Spur, slopes NW.; desc. 155 ft. over NE. slope.
35.90	Wash, 20 lks. wide, 2 ft. deep, course NW.; asc. 20 ft. over S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6.

East Boundary, T. 12 N., R. 12 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., over an X cut in solid rock, in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$

S1 | S6

1956

Asc. 50 ft. over S. slope.

42.50 Spur, slopes W.; desc. 65 ft. over N. slope.

47.60 Wash, 15 lks wide, 3 ft. deep, course S. 70° W.; asc. 220 ft. over S. slope.

61.00 Intersect the Third Standard Parallel North.

Point for the closing cor. of Ts. 12 N., Rs. 11 and 12 W., falls on broken ledges facing E., impossible to monument cor.

At a point 55 lks. E. of the true point for the closing cor., point selected for the witness cor. closing cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., over an X cut in solid rock, in a mound of stone to top, with brass cap mkd.

T13N R11W

W ← S31.

C ← S1 | S6

C C

R12W R11W

T12N

1956

From the true point for the closing cor., the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 13 N., R. 11 W., bears East, 2.94 chs. dist., monumented as recorded.

Land, high and rolling.

Soil, rocky clay.

Undergrowth, scattered palo verde, catclaw, greasewood, saguaro, cholla, and barrel cactus.

The West Boundary of T. 12 N., R. 12 W.

From the cor. of Ts. 12 N., Rs. 12 and 13 W., on the N. bdy. of T. 11 N., R. 13 W., which is monumented with an iron post, set, mkd. and witnessed as described in the official record.

North, bet. secs. 31 and 36.

Over high rolling land, through scattered undergrowth.

Asc. 65 ft. over S. slope.

3.90 Ridge, bears E. and W.; desc. 530 ft. over N. slope.

39.40 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 31 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.

West Boundary, T. 12 N., R. 12 W.

Chains

	$\frac{1}{4}$ $W C$ $S36 \uparrow S31$ 1956
40.00	The true point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, falls in a wash, 40 lks. wide, 3 ft. deep, course N. 10° E. Desc. 120 ft. over broken NE. slope.
47.50	Wash, 30 lks. wide, 5 ft. deep, course N. 30° E.
56.00	Wash, 20 lks. wide, 2 ft. deep, course NE.
73.00	Wash, 1 ch. wide, 3 ft. deep, course E.; asc. 40 ft. over S. slope.
80.00	Point for the cor. of secs. 25, 30, 31 and 36. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.
	$T12N$ $R13W R12W$ $\frac{S25 S30}{S36 S31}$ 1956
	Land, high and rolling. Soil, gravel and rocky clay. Undergrowth, scattered palo verde, greasewood, catclaw, ocotillo, saguaro, and cholla cactus.
	North, bet. secs. 25 and 30. Asc. 80 ft. over broken E. slope.
31.30	S. rim of canyon, bears E. and W.; desc. 187 ft. over N. slope.
35.20	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 25 and 30. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ $W C$ $S25 \uparrow S30$ 1956
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
35.50	S. edge of wash, course SE.
40.00	The true point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, falls in center of wash.
44.00	N. edge of same wash; asc. 80 ft. over S. slope.
52.00	Spur, slopes E.; desc. 60 ft. over N. slope.
59.30	Wash, 10 lks. wide, 3 ft. deep, course E.; asc. 140 ft. over S. slope.
69.70	Spur, slopes S. 80° E.; desc. 135 ft. over N. slope.
80.00	Point for the cor. of secs. 19, 24, 25 and 30, falls in draw, course SE.

West Boundary, T. 12 N., R. 12 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T12N
R13W R12W
S24 | S19
S25 | S30
1956

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, high and rolling.

Soil, gravel and rocky clay.

Undergrowth, scattered palo verde, greasewood, catclaw, ocotillo, saguaro, and cholla cactus.

North, bet. secs. 19 and 24.

Asc. 165 ft. over broken S. slope.

16.50 Spur, slopes SE.; desc. 130 ft. over NE. slope.

34.60 Wash, 30 lks. wide, 5 ft. deep, course ENE; asc. 40 ft. over SE. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$

S24 | S19

1956

Asc. 80 ft. over SSE. slope.

45.60 Spur, slopes E.; desc. 90 ft. over N. slope.

56.50 Wash, 15 lks. wide, 3 ft. deep, course E.; asc. 70 ft. over S. slope.

62.00 Spur, slopes E.; desc. 70 ft. over N. slope.

71.80 Wash, 10 lks. wide, 3 ft. deep, course SE; asc. 105 ft. over S. slope.

80.00 Point for the cor. of secs. 13, 18, 19 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T12N
R13W R12W
S13 | S18
S24 | S19
1956

Land, high and rolling.

Soil, gravel and rocky clay.

Undergrowth, scattered palo verde, greasewood, catclaw, ocotillo, saguaro, and cholla cactus.

North, bet. secs. 13 and 18.

Asc. 25 ft. over S. slope, through scattered undergrowth.

West Boundary, T. 12 N., R. 12 W.

Chains	
1.40	Spur, slopes E.; desc. 60 ft. over N. slope.
6.00	Draw, course NE.; asc. 235 ft. over S. slope.
24.80	<p>Witness point on line bet. secs. 13 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over an X cut in solid rock, in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">W P S13 S18</p> <p style="text-align: center;">1956</p>
	This point falls on spur sloping SE. on top of rocky breaks into Big Sandy wash.
	Desc. 495 ft. over sloping solid rock ledge to Big Sandy wash.
39.00	Base of rock ledge; S. edge of Big Sandy wash, course SE.
40.00	True point for the ¼ sec. cor. of secs. 13 and 18, falls in the Big Sandy wash, impossible to monument.
60.00	N. bank of Big Sandy wash; asc. 85 ft. over rock slope.
71.60	<p>Point selected for witness point on line bet. secs. 13 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over an X cut in solid rock, in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">W P S13 S18</p> <p style="text-align: center;">1956</p>
	Asc. 95 ft. over S. slope.
80.00	<p>Point for the cor. of secs. 7, 12, 13 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;">T12N R13W R12W S12 S 7 S13 S18 1956</p>
	<p>Land, high and rolling.</p> <p>Soil, gravel and rocky clay.</p> <p>Undergrowth, scattered palo verde, greasewood, catclaw, ocotillo, saguaro, and cholla cactus.</p>
	North, bet. secs. 7 and 12.
	Asc. 115 ft. over S. slope, through scattered undergrowth.
9.20	Spur, slopes SW.
13.70	Head of draw, course SW.; asc. 385 ft. over SW. slope.
39.00	Spur, slopes SE.
40.00	<p>Point for the ¼ sec. cor. of secs. 7 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground,</p>

West Boundary, T. 12 N., R. 12 W.

Chains

in a mound of stone to top, with brass cap mkd.

 $\frac{1}{4}$

S12 | S7

1956

Asc. 280 ft. over broken S. slope.

71.10 Ridge, bears E. and SW.; desc. 60 ft. over NE. slope.

80.00 Point for the cor. of secs. 1, 6, 7 and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T12N

R13W R12W

S1 | S6

S7 | S12

1956

Land, high and rolling.

Soil, gravel and rocky clay.

Undergrowth, scattered palo verde, greasewood, catclaw, ocotillo, saguaro, and cholla cactus.

North, bet. secs. 1 and 6.

Desc. 380 ft. over N. slope, through scattered undergrowth.

24.00 Wash, 10 lks. wide, 2 ft. deep, course NE.; desc. 200 ft. over broken NE. slope.

35.60 S. edge of wash, bears N. 70° W.40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, falls in the middle of a wash, impossible to monument.

44.40 N. edge of same wash.

45.50 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 1 and 6.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd. $\frac{1}{4}$

S1 ↓ S6

W C

1956

Asc. 80 ft. over S. slope.

52.50 Spur, low, slopes W.; desc. 40 ft. into wash.

53.50 S. edge of wash, course W.

59.90 Junction of washes, one from N, one from E., course W.

60.46 Intersect the Third Standard Parallel North.

Point for the closing cor. of T. 12 N., Rs. 12 and 13 W., falls in the junction of these two washes; impossible to monument.

West Boundary, T. 12 N., R. 12 W.

Chains

At a point 64 lks. North of the true point for the closing cor. for T. 12 N., Rs. 12 and 13 W., point selected for the witness cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T13N R12W
 $\frac{S31}{S1 \quad S6}$
 R13W R12W
 WCCC
 T12N
 1956

From the true point for the closing cor., the true point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 13 N., R. 12 W., bears East, 2.56 chs. dist, whose witness cor. bears West of its true point 4.00 chs. dist., monumented with an iron post as recorded.

Land, high and rolling.

Soil, gravel and rocky clay.

Undergrowth, scattered palo verde, greasewood, catclaw, ocotillo, saguaro, and cholla cactus.

Partial Subdivision, T. 12 N., R. 12 W.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the township.

N. $89^{\circ} 58'$ W., bet. secs. 1 and 12.

Desc. 240 ft. over N. slope, through scattered undergrowth.

13.00 Wash, 20 lks. wide, 2 ft. deep, course SW.; asc. 20 ft. over SE. slope.

25.40 Spur, slopes S.; desc. 90 ft. over NW. slope.

32.00 Wash, 15 lks. wide, 4 ft. deep, course SW.; asc. 30 ft. over SE. slope.

35.50 Spur, slopes S.; desc. 45 ft. over W. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4} \frac{S1}{S12}$

1956

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Desc. 70 ft. over WNW. slope.

60.00 Wash, 25 lks. wide, 2 ft. deep, course SW.; asc. 100 ft. over SE. slope.

80.00 Point for the cor. of secs. 1, 2, 11 and 12.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, in a mound of stone to top, with brass cap mkd.

Partial Subdivision, T. 12 N., R. 12 W.

Chains

T12N R12W

S 2 | S 1

S11 | S12

1956

Land, high and rolling.
Soil, gravel and rocky clay.
Undergrowth, scattered palo verde, greasewood, catclaw, ocotillo,
saguaro, and cholla cactus.

N. 0° 01' W., bet. secs. 1 and 2.

Asc. 300 ft. over S. slope, through scattered undergrowth.

14.60 Ridge, bears E. and W.; desc. 555 ft. over N. slope.

36.40 Wash, 1 ch. wide, 3 ft. deep, course W.; asc. 110 ft. over S. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the
ground, in a mound of stone to top, with brass cap mkd.

 $\frac{1}{4}$

S 2 | S 1

1956

Asc. 675 ft. over broken S. slope.

60.99 Intersect the Third Standard Parallel North.

Point for the closing cor. of secs. 1 and 2, T. 12 N., R. 12 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., over an X cut in
solid rock, in a mound of stone to top, with brass cap mkd.

T13N R12W

S36

S 2 | S 1

C C

T12N R12W

1956

From above closing cor., the standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 13
N., R. 12 W., bears East, 2.98 chs. dist., monumented with an iron
post as recorded.

Land, high and rolling.
Soil, gravel and rocky clay.
Undergrowth, scattered palo verde, greasewood, catclaw, ocotillo,
saguaro, and cholla cactus.

At a point midway bet. the closing cor. of T. 12 N., Rs. 11 and 12
W. and the closing cor. of secs. 1 and 2, T. 12 N., R. 12 W., point
for the $\frac{1}{4}$ sec. cor. of sec. 1.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., over an X cut in
solid rock, in a mound of stone to top, with brass cap mkd.

 $\frac{1}{4}$ S 1

1956

Partial Subdivision, T. 12 N., R. 12 W.

Chains	
	From above cor. point, the standard township cor. of Ts. 13 N., Rs. 11 and 12 W., bears East, 2.96 chs. dist., monumented with an iron post as recorded.
	From the cor. of secs. 1, 2, 11 and 12. N. 89° 58' W., bet. secs. 2 and 11. Asc. 15 ft. over E. slope, through scattered undergrowth.
2.00	Spur, slopes S.; desc. 140 ft. over W. slope.
16.00	Head of draw, course SE.; asc. 30 ft. over E. slope.
21.80	Spur, slopes SSW.; desc. 150 ft. over W. slope.
39.80	Spur, slopes SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, in a mound of stone to top, with brass cap mkd. $\frac{1}{4} \begin{array}{c} S 2 \\ S 11 \end{array}$ 1956
	Desc. 285 ft. over NW. slope.
48.00	Wash, 50 lks. wide, 3 ft. deep, course SW.; asc. 430 ft. over ESE. slope.
68.50	Spur, slopes SW.; desc. 250 ft. over NW. slope.
80.00	Point for the cor. of secs. 2, 3, 10 and 11. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd. $\begin{array}{c} T12N R12W \\ \hline S 3 S 2 \\ S10 S11 \end{array}$ 1956
	Land, high and rolling. Soil, gravel and rocky clay. Undergrowth, scattered palo verde, greasewood, catclaw, ocotillo, saguaro, and cholla cactus.
	N. 0° 01' W., bet. secs. 2 and 3. Desc. 20 ft. over NW. slope, through scattered undergrowth.
1.50	Wash, 20 lks. wide, 2 ft. deep, course SW.; asc. 150 ft. over SE. slope.
6.00	Rocky knoll, on spur sloping SW.; desc. 123 ft. over NW. slope.
21.20	Wash, 20 lks. wide, 5 ft. deep, course SW.; asc. 80 ft. up this wash.
29.00	Leave wash from NE.; asc. 190 ft. over SSE. slope.

Partial Subdivision, T. 12 N., R. 12 W.

Chains

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$

S3 | S2

1956

Asc. 65 ft. over S. slope.

47.70

Spur, slopes W.; desc. 285 ft. over N. slope.

61.03

Intersect the Third Standard Parallel North.

Point for the closing cor. of secs. 2 and 3, T. 12 N., R. 12 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T13N R12W

S35

S3 | S2

C C

T12N R12W

1956

From above closing cor. point, the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 13 N., R. 12 W., bears East 3.26 chs. dist., monumented with an iron post as recorded.

Land, high and rolling.

Soil, gravel and rocky clay.

Undergrowth, scattered palo verde, greasewood, catclaw, ocotillo, saguaro, and cholla cactus.

At a point midway bet. the closing cors. of secs. 1 and 2 and secs. 2 and 3, T. 12 N., R. 12 W., point for the $\frac{1}{4}$ sec. cor. of sec. 2.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., over an X cut in solid rock, in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$ S2

1956

From above cor. point, the standard cor. of secs. 35 and 36, T. 13 N., R. 12 W., bears East, 3.12 chs. dist., monumented with an iron post as recorded.

General Description, T. 12 N., R. 12 W.

T. 12 N., R. 12 W. is high rolling land with some cliffs and is very cut up with deep, dry canyons. Big Sandy wash cuts across the SW. portion of the township and is a wide, mostly dry, very sandy wash. There is no timber; however, there is scattered to dense undergrowth. The only apparent revenue derived at present is from grazing. There is limited mining activity near this area.

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of January, 1955 I have surveyed supervised the survey of the east and west boundaries and partial subdivision of T. 12 N., R. 12 W.

of the G & S R Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

July 30, 1956
Salt Lake City, Utah

Donald E. Harding
Donald E. Harding
Cartographer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., JAN 15 1957, 19

The foregoing field notes of the survey of the east and west boundaries and partial subdivision of T. 12 N., R. 12 W., G. & S. R. Meridian, Arizona.

supervised by
executed by Donald E. Harding

having been critically examined and found correct, are hereby approved.

Carl G. Harrington
Chief, Division of Cadastral Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Chief, Division of Cadastral Engineering