

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of the

Dependent Resurvey of the South Boundary of Section 31

and

Dependent Resurvey of the Subdivision

of

Township 23 North, Range 18 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald B. Harding, Cadastral Engineer

Under special instructions dated October 19, 1955, which provided
for the surveys included under Group No. 308, approved October 19, 1955
and assignment instructions dated October 19, 1955

Survey commenced October 25, 1955

Survey completed November 16, 1955

BOOK 4533

INDEX DIAGRAM

Township 23 North, Range 18 West

6	46	5	35	4	27	3	19	2	10	1
45	45		34		27		18		10	
7	44	8	33	9	26	10	17	11	9	12
43	43		32		25		16		8	
18	42	17	32	16	24	15	15	14	7	13
41	40		31		23		15		6	
19	39	20	30	21	22	22	14	23	5	24
39	38		30		22		13		5	
30	37	29	29	28	21	27	12	26	4	25
37	36		29		20		12		3	
31	36	32	28	33	20	34	11	35	2	36
1										

Dependent Resurvey of Township 23 North, Range 18 West

Chains

The four boundaries and subdivisional lines of Township 23 North, Range 18 West, were surveyed by O. H. Case in 1872. The east half of the south boundary was resurveyed by Theo. O. Johnston and the west half by Edward O. Lyman in 1915, as represented on the plat of T. 22 N., R. 18 W., approved December 24, 1917. The south four miles of the west boundary (Fifth Guide Meridian West) were resurveyed by T. O. Johnston in 1915 and the north two miles were resurveyed by G. H. Richardson in 1916, as represented on the plat of T. 23 N., R. 19 W., approved December 24, 1917. The east boundary was resurveyed in 1916 by Hugo Price as represented on the plat of T. 23 N., R. 17 W., approved December 24, 1917. The north boundary was resurveyed by Richardson and Price in 1916 as represented on the plat of T. 24 N., R. 18 W., approved December 24, 1917.

This resurvey was requested by memorandums from the Bureau of Land Management, Range Manager, dated August 12, 1954, and October 10, 1955. He advised that there was extensive obliteration of the original survey monuments.

The survey was executed with a light mountain solar transit made by Buff and Buff, Serial No. 16724, and a W. and L. E. Gurley solar transit, Serial No. 541332, constructed in accordance with standard instrumental specifications of the Bureau of Land Management. Horizontal circle is $4\frac{1}{2}$ inches in diameter with two double opposite verniers reading to single minutes. Vertical circle is 4 inches in diameter with one double vernier reading to single minutes. The instrument is equipped with an improved telescopic solar attachment, radii of latitude arc 3 inches and of declination arc $3\frac{1}{2}$ inches with vernier reading to single minutes. The instruments were in good condition and were placed in proper adjustment prior to the beginning of the survey.

The direction of all lines was determined by the direct solar method, solar method, and from Coast and Geodetic Triangulation Stations, and the measurements made by a Lufkin steel tape, 5 chains in length, graduated one-tenth link for the first 10 links, every link for the next 90 links, and every 10 links for the balance. The tape was tested by comparison with a standard tape and found correct. Measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustment. The horizontal equivalents only are entered in this field note record.

The transits were checked from time to time on the camp meridian which was established from U.S.G.S. Triangulation Station "Highway" and the azimuth of the lines was checked by direct solar method as the survey progressed. The geographic position of the Southeast corner of the township is latitude $35^{\circ} 19' 45''$ N. and longitude $114^{\circ} 08' 56''$ W. The magnetic declination is 15° E.

No new ties were made to patented mining claims as all of the original survey corners to which the claims were tied were found in their original position.

Dependent Resurvey of the S. Bdy., Sec. 31

Reestablishment of the Survey made by Edward O. Lyman in 1915. The S. bdy. of sec. 31, T. 23 N., R. 18 W., was resurveyed for alignment only. The bearing in the official record is S. $89^{\circ} 41'$ W.

From the cor. of secs. 31 and 32, which is monumented with an iron post, set, mkd., and witnessed as described in the official record.

N. $89^{\circ} 41'$ W. on the S. bdy. of sec. 31.

Dependent Resurvey of the S. Bdy., Sec. 31

Chains

40.76 The $\frac{1}{4}$ sec. cor. of sec. 31, which is monumented with an iron post, set, mkd., and witnessed as described in the official record.

80.51 The cor. of Ts. 22 and 23 N., Rs. 18 and 19 W., which is monumented with an iron post, set, mkd., and witnessed as described in the official record.

Dependent Resurvey of the Subdivision, T. 23 N., R. 18 W.

Reestablishment of the Survey made by O. H. Case in 1872.

From the cor. of secs. 35 and 36 on the S. bdy. of the Tp., which is monumented with a granite stone, 20x8x5 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T23N R18W
S35|S36
S 2
T22N
1955

Thence

N. 0° 02' W. bet. secs. 35 and 36.

Over nearly level land.

4.50 Wash, 10 lks. wide, 2 ft. deep, drains S. 70° W.

11.70 Road, graded, bears NE. and SW.

18.60 Wash, 20 lks. wide, 4 ft. deep, drains S. 80° W.

34.50 Wash, 40 lks. wide, 3 ft. deep, drains N. 70° W.

39.81 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$
S35|S36
1955

43.90 Wash, 10 lks. wide, 3 ft. deep, drains S. 80° W.

69.60 Wash, 20 lks. wide, 5 ft. deep, drains S. 80° W.

74.50 Road, graded, bears NW. and SE.

79.62 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

T23N R18W
 $\frac{S26}{S35} | \frac{S25}{S36}$
 1955

Land, level.
 Soil, rocky clay.
 Timber, none; undergrowth, cacti, oak brush, greasewood and sparse grass.

From the cor. of secs. 25 and 36 on the E. bdy. of the Tp., which is monumented with an iron post, set, mkd. and witnessed as described in the official record.

S. 89° 32' W. bet. secs. 25 and 36.

Desc. 270 ft. over broken W. slope, through scattered brush.

32.10 Wash, 15 lks. wide, 4 ft. deep, drains S. 60° W.

39.90 Wash, 20 lks. wide, 6 ft. deep, drains S. 40° W.

43.58 The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented with a broken granite stone, 12x8x5 ins., lying in a mound of stone, properly mkd. and set as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone to cap, with brass cap mkd.

$\frac{1}{4} \frac{S25}{S36}$

1955

Bury the original cor. stone alongside the iron post.

S. 89° 39' W., beginning new measurement.

Over gentle W. slope.

2.40 Road, track, bears NE. and SW.

10.00 Desc. 125 ft. over SW. slope.

28.30 Wash, 10 lks. wide, 3 ft. deep, drains S. 50° W.

32.70 Road, track, bears NE. and SW.

33.60 Power line, bears NW. and SE.

39.65 The cor. of secs. 25, 26, 35 and 36.

Land, gently rolling.
 Soil, rocky clay.
 Timber, none; undergrowth, cacti, oak brush, greasewood and sparse grass.

Dependent Resurvey
Subdivision, T. 23 N., R. 18 W.

Chains	<p>N. 1° 03' W. bet. secs. 25 and 26.</p> <p>4.50 Wash, 15 lks. wide, 4 ft. deep, drains S. 60° W.</p> <p>7.40 Power line, bears NW. and SE.</p> <p>15.00 Road, track, bears NE. and SW.; asc. 100 ft. over S. slope.</p> <p>25.00 Ridge, bears E. and W.; desc. over gentle N. slope.</p> <p>28.60 Wash, 10 lks. wide, 4 ft. deep, drains N. 80° W.</p> <p>34.80 Wash, 5 lks. wide, 1 ft. deep, drains N. 80° W.</p> <p>39.82 The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with a granite stone, 20xl8xl2 ins., properly mkd. and set in a mound of stone, as described in the official record.</p> <p>At the cor. point.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\frac{1}{4}$ <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S26</td> <td style="padding: 0 5px;">S25</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1955</td> </tr> </table> </div> <p>Bury the original cor. stone at the base of the iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 21' E. beginning new measurement.</p> <p>Asc. 60 ft. over a SW. slope.</p> <p>6.90 Spur, slopes W.; desc. 20 ft. over N. slope.</p> <p>14.60 Wash, 40 lks. wide, 5 ft. deep, drains S. 60° W.</p> <p>16.00 Road, graded, bears NE. and SW.; asc. 220 ft. over SSW. slope.</p> <p>34.50 Spur, high and rocky, slopes W.; desc. 90 ft. over N. slope.</p> <p>40.72 The cor. of secs. 23, 24, 25 and 26, monumented with a rotted stake in a mound of stone, as described in the official record.</p> <p>At the cor. point.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 10px;">T23N R18W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S23</td> <td style="padding: 0 5px;">S24</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S26</td> <td style="padding: 0 5px;">S25</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1955</td> </tr> </table> </div> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.</p> <p>Land, high and rolling. Soil, rocky clay. Timber, none; undergrowth, cacti and sparse grass.</p>	S26	S25	1955		T23N R18W		S23	S24	S26	S25	1955	
S26	S25												
1955													
T23N R18W													
S23	S24												
S26	S25												
1955													

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

From the cor. of secs. 24 and 25 on the E. bdy. of the Tp., which is monumented with an iron post, set, mkd. and witnessed as described in the official record.

S. 89° 52' W. bet. secs. 24 and 25.

Over mountainous land, through scattered undergrowth.

3.30 Wash, 20 lks. wide, 6 ft. deep, drains S. 30° W.; asc. 400 ft. over rocky, broken E. slope.

23.70 Spur, slopes S.; desc. 240 ft. over W. slope.

33.80 Wash, 10 lks. wide, 4 ft. deep, drains S. 40° W.; asc. 30 ft. over SE. slope.

41.44 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over an X cut in solid rock, and in a mound of stone to top, with brass cap mkd.

$$\frac{1}{4} \frac{S24}{S25}$$

1955

Asc. 20 ft. over SE. slope.

44.40 Spur, slopes S.; desc. 230 ft. over W. slope.

53.70 Wash, 15 lks. wide, 2 ft. deep, drains S. 30° W.

55.60 Road, graded, bears NW. and SE.

62.30 Wash, 10 lks. wide, 3 ft. deep, drains S. 30° W.; asc. 130 ft. over E. slope.

64.30 Fence, bears NW. and SE.

71.80 Spur, slopes SSE.; desc. 210 ft. over W. slope.

82.88 The cor. of secs. 23, 24, 25 and 26.

Land, mountainous.

Soil, rocky clay.

Timber, scattered juniper; undergrowth, cat claw, cacti and sparse grass.

N. 5° 40' E. bet. secs. 23 and 24.

Desc. 40 ft. over NW. slope.

4.60 Road, graded, bears N. 80° E. and SW.

15.00 Wash, 1.50 chs. wide, 4 ft. deep, drains S. 45° W.

18.00 Power line, bears N. 75° E. and SW.; asc. 70 ft. over E. slope.

29.00 Wash, 20 lks. wide, 2 ft. deep, drains S. 40° E.

38.09 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; no remaining evidence of the original cor.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S23 | S24 \\ 1955 \end{array}$$

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Asc. 180 ft. over broken ESE. slope.

70.00 Spur, slopes E.; desc. 80 ft. over NE. slope.

75.60 Wash, 10 lks. wide, 2 ft. deep, drains S. 50° E.

76.18 The cor. of secs. 13, 14, 23 and 24, monumented with a volcanic stone, 26x18x6 ins., properly mkd. and firmly set in a mound of stone, as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} T23N R18W \\ \frac{S14 | S13}{S23 | S24} \\ 1955 \end{array}$$

Place the original cor. stone at the base of the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, scattered juniper; undergrowth, cat claw, cacti and sparse grass.

From the cor. of secs. 13 and 24 on the E. bdy. of the T_h, which is monumented with an iron post, set, mkd. and witnessed as described in the official record.

N. $89^{\circ} 56'$ W. bet. secs. 13 and 24.

Across broken S. slope, through dense juniper.

21.80 Road, track, bears NE. and SW.

27.10 Road, track, bears NE. and SW.

31.50 Road, graded, bears NE. and SW.; leave timber.

33.90 Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.

41.04 The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with a granite stone, 12x8x6 ins., properly mkd. and firmly set in a mound of stone, as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

$$\frac{1}{4} \frac{S13}{S24}$$

1955

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
and bury the original cor. stone alongside the iron post.

From the above cor. U. S. Mineral Monument No. 4020 bears S. 89°
 $34'$ E., 10.71 chs. dist.

S. $82^\circ 25'$ W. beginning new measurement.

- .20 Power line, bears NE. and SW.
- 12.50 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.
- 12.70 Road, track, bears NW. and SE.
- 19.50 Wash, 20 lks. wide, 2 ft. deep, drains S. 20° E.; asc. 135 ft.
over E. slope.
- 25.00 Spur, slopes S. 10° E.; desc. 120 ft. over W. slope.
- 30.50 Wash, 20 lks. wide, 6 ft. deep, drains S. 15° E.; asc. 40 ft. over
E. slope.
- 33.77 The cor. of secs. 13, 14, 23 and 24.

Land, rolling and broken.

Soil, rocky clay.

Timber, juniper; undergrowth, cacti, scattered greasewood and
sparse grass.

N. $4^\circ 30'$ W. bet. secs. 13 and 14.

Over mountainous land, through scattered timber.

Asc. 110 ft. over SW. slope.

- 4.20 Spur, short, slopes S. 20° E.; desc. 70 ft. over NE. slope.
- 9.60 Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E.; asc. 280 ft.
over S. slope.
- 21.00 Spur, slopes SW.; desc. 250 ft. over N. slope.
- 32.50 Wash, 12 lks. wide, 4 ft. deep, drains N. 60° W.; asc. 142 ft.
over S. slope.
- 42.38 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, at proportionate
distance; no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the
ground, and in a mound of stone to top, with brass cap mkd.

$$\frac{1}{4} \frac{S14}{S13}$$

1955

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	<p>Asc. 160 ft. over SE. slope.</p> <p>55.50 Spur, slopes SSW; desc. 210 ft. over NNW. slope.</p> <p>72.40 Wash, 10 lks. wide, 3 ft. deep, drains SW.</p> <p>75.00 Road, graded, bears NE. and SW.; asc. 205 ft. over S. slope.</p> <p>84.76 The cor. of secs. 11, 12, 13 and 14, monumented with a granite stone, 16x10x8 ins., properly mkd. and firmly set in a mound of stone, as described in the official record. At the cor. point.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23N R18W S11 S12 S14 S13 1955</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor. and bury the original cor. stone alongside the iron post.</p> <p>Land, mountainous. Soil, rocky clay. Timber, scattered juniper; undergrowth, cacti, scattered greasewood and sparse grass.</p>
19.90	<p>From the cor. of secs. 12 and 13 on the E. bdy. of the Tp., monumented with an iron post, set, mkd. and witnessed as described in the official record.</p> <p>N. 89° 42' W. bet. secs. 12 and 13.</p> <p>Desc. 260 ft. over broken S. slope.</p> <p>Through juniper and scattered underbrush.</p> <p>Toe of spur, slopes SW.</p>
27.90	<p>Wash, 15 lks. wide, 3 ft. deep, drains S.; over broken S. slope.</p>
36.50	<p>Wash, 10 lks. wide, 1 ft. deep, drains S. 25° W.</p>
39.635	<p>Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">¼ ——— S12 S13 1955</p> <p>Desc. 65 ft. over S. slope.</p>
43.30	<p>Wash, 15 lks. wide, 2 ft. deep, drains S. 40° W.; asc. 100 ft. over SE. slope.</p>
49.50	<p>Spur, slopes SSW.; desc. 280 ft. over W. slope.</p>
63.30	<p>Rocky gully, drains SW.; asc. 60 ft. over SE. slope.</p>

BOOK 4533

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
67.00	Spur, slopes SW.; desc. 130 ft. over W. slope.
70.20	Road, graded, bears NE. and SW.
72.70	Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.; asc. 160 ft. over SE. slope.
79.27	The cor. of secs. 11, 12, 13 and 14. Land, mountainous. Soil, rocky clay. Timber, scattered juniper; undergrowth, cacti, scattered greasewood and sparse grass.
	N. 1° 06' W. bet. secs. 11 and 12. Asc. 710 ft. over ESE. slope. Through scattered juniper and underbrush.
37.80	Ridge, bears NE. and SW.
40.18	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12, at proportionate distance; no remaining evidence of original cor. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S11 S12 1955 Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
44.50	Ridge, bears NW. and SE.; desc. 430 ft. over broken N. slope.
58.30	Wash, 30 lks. wide, 4 ft. deep, drains NW.; asc. 40 ft. over WSW. slope.
65.80	Road, graded, bears NW. and SE.
72.50	Spur, slopes NW.; desc. 190 ft. over NNE. slope.
77.50	Road, graded, bears NE. and SW.
80.36	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. T23N R18W S 2 S 1 S11 S12 1955 Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor. Land, mountainous. Soil, rocky clay. Timber, scattered juniper; undergrowth, cacti, scattered greasewood and sparse grass.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

From the cor. of secs. 1 and 12 on the E. bdy. of the Tp., which is monumented with an iron post, set, mkd. and witnessed as described in the official record.

N. 89° 50' W. bet. secs. 1 and 12.

Desc. 540 ft. over broken W. slope.

Through dense juniper and underbrush.

20.10 Road, graded, bears N. and S.

40.095 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$ $\frac{S 1}{S 12}$

1955

Asc. 100 ft. over E. slope of knoll.

56.00 Desc. 450 ft. over broken W. slope.

68.00 Road, graded, bears N. and S.

69.00 Slope changes to NE.; asc. 140 ft.

80.19 The cor. of secs. 1, 2, 11 and 12.

Land, mountainous.

Soil, rocky clay.

Timber, juniper; undergrowth, oak brush, scattered mountain mahogany, cacti and sparse grass.

N. 1° 46' E. bet. secs. 1 and 2.

Desc. 50 ft. over N. slope.

3.00 Wash, 10 lks. wide, 3 ft. deep, drains N. 70° W. from E.; asc. 70 ft. over W. slope.

5.80 Road, graded, bears NW. and SE.

13.70 Power line, bears NW. and SE.

18.00 Spur, low, slopes W.; desc. 40 ft. over N. slope.

20.90 Road, track, bears SW. and NE. 8 chs. to mine.

22.20 Wash, 10 lks. wide, 3 ft. deep, drains S. 30° W.

27.60 Road, track, bears NW. and SE.; asc. 150 ft. over SW. slope.

40.20 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$
S 2 | S 1

1955

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

Asc. 790 ft. over rocky SSW. slope.

66.70

Ridge, bears E. and W.; desc. 260 ft. over rocky N. slope.

80.65

The cor. of secs. 1, 2, 35 and 36, Ts. 23 and 24 N., R. 18 W., monumented with an iron post, set, mkd. and witnessed as described in the official record.

Land, mountainous.

Soil, rocky clay.

Timber, juniper; undergrowth, oak brush, scattered mountain mahogany, cacti and sparse grass.

From the cor. of secs. 34 and 35 on the S. bdy. of the Tp., which is monumented with an iron post, set, mkd. and witnessed as described in the official record.

N. 0° 24' W. bet. secs. 34 and 35.

Over low rolling grassy ridges and benches.

5.00

Wash, 30 lks. wide, 5 ft. deep, drains SW.

11.30

Wash, 30 lks. wide, 4 ft. deep, drains SW.

15.00

Road, track, bears NW. and SE.

30.60

Road, graded, bears NE. and SW.

38.50

Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.

39.60

Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \hline S34 | S35 \\ 1955 \end{array}$$

67.00

Wash, 20 lks. wide, 3 ft. deep, drains S. 60° W.

79.20

The cor. of secs. 26, 27, 34 and 35, monumented with a granite stone, 14x8x6 ins., properly mkd. and firmly set as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T23N R18W \\ \hline S27 | S26 \\ \hline S34 | S35 \\ 1955 \end{array}$$

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor. and bury the original cor. stone alongside the iron post.

Land, gently rolling.

Soil, sandy clay.

Timber, none; undergrowth, cacti, scattered greasewood and sparse grass.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

From the cor. of secs. 25, 26, 35 and 36.

N. 89° 39' W. bet. secs. 26 and 35.

Over low grassy ridges.

6.60 Wash, 30 lks. wide, 4 ft. deep, drains S. 60° W.

8.80 Road, graded, bears NW. and SE.

28.50 Wash, 15 lks. wide, 5 ft. deep, drains S. 60° W.

39.70 The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented with a granite stone, 8x6x5 ins., properly mkd. and set in a mound of stone, as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S26}{S35}$$

1955

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor. and bury the original cor. stone alongside the iron post.

S. 89° 03' W. beginning new measurement.

3.90 Wash, 10 lks. wide, 1 ft. deep, drains S. 70° W.

10.70 Road, graded, bears NE. and SW.

14.60 Wash, 20 lks. wide, 4 ft. deep, drains S. 40° W.

29.80 Road, track, bears NE. and SW.

39.43 The cor. of secs. 26, 27, 34 and 35.

Land, gently rolling.

Soil, sandy clay.

Timber, none; undergrowth, cacti, scattered greasewood and sparse grass.

N. 1° 50' W. bet. secs. 26 and 27.

Over gently rolling grassy ridges.

5.30 Wash, 20 lks. wide, 3 ft. deep, drains S. 40° W.

12.40 Road, track, bears NE. and SW.

14.60 Road, track, bears NW. and SE.

27.30 Wash, 40 lks. wide, 3 ft. deep, drains S. 45° W.

32.60 Road, track, bears NW. and SE.

38.40 Wash, 20 lks. wide, 2 ft. deep, drains S. 50° W.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

39.62 The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented with a granite stone, 18x16x14 ins., properly mkd. and firmly set in a mound of stone, as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \hline S27 | S26 \\ 1955 \end{array}$$

Bury the original cor. stone alongside the iron post.

N. 0° 11' E. beginning new measurement.

9.70 Wash, 20 lks. wide, 4 ft. deep, drains S. 70° W.

23.00 Wash, 15 lks. wide, 3 ft. deep, drains S. 80° W.

32.00 Road, track, bears NW. and SE.

35.10 Road, graded, bears N. 35° W. and S. 80° E.

39.10 The cor. of secs. 22, 23, 26 and 27, monumented with a rotted stake in a mound of stone, as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} T23N R18W \\ \hline S22 | S23 \\ \hline S27 | S26 \\ 1955 \end{array}$$

Land, gently rolling.

Soil, sandy clay.

Timber, none; undergrowth, cacti, scattered greasewood and sparse grass.

From the cor. of secs. 23, 24, 25 and 26.

S. 88° 20' W. bet. secs. 23 and 26.

Desc. 120 ft. over W. slope, through scattered brush.

5.60 Road, graded, bears NE. and SW.

14.70 Wash, 1.60 chs. wide, 4 ft. deep, drains S. 20° W.

22.90 Power line, bears NE. and SW.

39.93 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
	$\frac{1}{4} \frac{S23}{S26}$ 1955
	Desc. 100 ft. over SW. slope.
45.90	Wash, 6 lks. wide, 2 ft. deep, drains S. 20° W.
46.50	Power line, bears NW. and SE.
54.80	Wash, 12 lks. wide, 2 ft. deep, drains NW.
79.86	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling. Soil, rocky clay. Timber, none; undergrowth, cacti, greasewood and sparse grass.
	N. 0° 03' E. bet. secs. 22 and 23.
	Over rolling ridges, through scattered brush.
4.40	Road, track, bears NW. and SE.
6.90	Road, track, bears NW. and SE.
12.10	Wash, 15 lks. wide, 4 ft. deep, drains N. 60° W.
39.80	Wash, 20 lks. wide, 3 ft. deep, drains S. 70° W.
40.48	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	$\frac{1}{4}$ $S22 S23$ 1955
44.90	Wash, 15 lks. wide, 4 ft. deep, drains S. 60° W.
50.00	Wash, 10 lks. wide, 2 ft. deep, drains SW.
55.50	Wash, 10 lks. wide, 2 ft. deep, drains SW.
59.60	Wash, 15 lks. wide, 3 ft. deep, drains SW.
67.20	Wash, 30 lks. wide, 3 ft. deep, drains SW.
71.30	Road, track, bears NE. and SW.
72.80	Wash, 15 lks. wide, 3 ft. deep, drains S. 10° E.
74.50	Power line, bears NW. and SE.
80.96	The cor. of secs. 14, 15, 22 and 23, monumented with a granite stone, 16x12x10 ins., properly mkd. and firmly set in a mound of stone, as described in the official record.
	At the cor. point.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T23N R18W
S15 | S14
S22 | S23
1955

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor. and bury the original cor. stone alongside the iron post.

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, cacti, greasewood, and sparse grass.

From the cor. of secs. 13, 14, 23 and 24.

N. $88^{\circ} 04'$ W. bet. secs. 14 and 23.

.40 Wash, 10 lks. wide, 2 ft. deep, drains S. 50° E.; asc. 310 ft. over ENE. slope, through scattered juniper and underbrush.

12.40 Ridge, bearing N. and S. and N. foot of Nigger Head; desc. 190 ft. over N. slope.

39.70 Short, steep spur, slopes NNW.; desc. 110 ft. over W. slope.

43.70 Point for the $\frac{1}{4}$ sec. for. of secs. 14 and 23, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ $\frac{S14}{S23}$
1955

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Desc. 350 ft. over broken W. slope.

73.40 Wash, 15 lks. wide, 2 ft. deep, drains S. 25° W.

79.80 Wash, 12 lks. wide, 1 ft. deep, drains S. 30° W.

80.10 Road, track, bears NE. and SW.; asc. 25 ft. over E. slope.

83.20 Spur, slopes S.; desc. 40 ft. over W. slope.

87.40 The cor. of secs. 14, 15, 22 and 23.

Land, mountainous.

Soil, rocky clay.

Timber, scattered juniper; undergrowth, oakbrush, greasewood, cacti and sparse grass.

N. $1^{\circ} 44'$ W. bet. secs. 14 and 15.

Over rolling grassy ridges.

7.00 Wash, 10 lks. wide, 3 ft. deep, drains S. 10° W.; asc. 130 ft. over SSE. slope.

24.00 Spur, low, slopes SSW.

34.50 Wash, 30 lks. wide, 6 ft. deep, drains S. 40° W.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
41.20	<p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with a granite stone, 18x12x8 ins., properly mkd. and firmly set in a mound of stone, as described in the official record.</p> <p>At the cor. point.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S15 S14 1955</p> <p>Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor. and bury the original cor. stone alongside the iron post.</p>
	<p style="text-align: center;">N. 2° 35' E. beginning new measurement.</p>
13.70	<p>Wash, 10 lks. wide, 2 ft. deep, drains NW.</p>
25.00	<p>Road, graded, bears NW. and SE.</p>
27.10	<p>Same road, bears NE. and SW.</p>
28.90	<p>Wash, 30 lks. wide, 3 ft. deep, drains N. 60° W.</p>
31.00	<p>Same road, bears NW. and SE.</p>
41.28	<p>The cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 30x18x4 ins., properly mkd. and firmly set in a mound of stone, as described in the official record.</p> <p>At the cor. point.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T23N R18W S10 S11 S15 S14 1955</p> <p>Land, rolling ridges. Soil, rocky clay. Timber, none; undergrowth, greasewood, cacti, scrub oak and sparse grass.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p>
	<p>N. 89° 17' W. bet. secs. 11 and 14.</p>
	<p>Over broken S. slope, through scattered brush.</p>
4.20	<p>Rocky gulch, drains S.</p>
19.90	<p>Rocky gulch, drains SE.</p>
22.50	<p>Spur, slopes SW.; desc. 161 ft. over W. slope.</p>
29.90	<p>Spur, slopes SW.; desc. 60 ft. over N. slope.</p>
39.98	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, at proportionate distance; no remaining evidence of the original cor.</p>

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$$\frac{1}{4} \frac{S11}{S14}$$

1955

Desc. 530 ft. over WNW. slope.

72.50 Road, track, bears NW. and SE.

79.96 The cor. of secs. 10, 11, 14 and 15.

Land, mountainous.

Soil, rocky clay.

Timber, none; undergrowth, cacti, greasewood, oak brush and grass.

N. $2^{\circ} 20'$ W. bet. secs. 10 and 11.

Over grassy ridges, through scattered brush.

1.80 Wash, 15 lks. wide, 12 ft. deep, drains SW.

2.40 Road, graded, bears NW. and SE.

4.10 Wash, 10 lks. wide, 2 ft. deep, drains S. 70° W.; asc. 70 ft. over gentle S. slope.

14.20 Wash, 20 lks. wide, 3 ft. deep, drains S. 30° W.

20.20 Road, graded, bears NNE. and WSW.

25.60 Wash, 30 lks. wide, 4 ft. deep, drains W.

38.70 Wash, 15 lks. wide, 3 ft. deep, drains S. 50° W.; asc. 40 ft. over S. slope.

41.48 The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented with a granite stone, 18x14x5 ins., properly mkd. and firmly set in a mound of stone, as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S10 | S11}{1955}$$

1955

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor. and bury the original cor. stone alongside the iron post.

Cor. falls on prow of spur, sloping SSW.

N. $0^{\circ} 03'$ W. beginning new measurement.

Asc. 110 ft. over W. slope.



Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
16.00	Spur, slopes NW.; desc. 60 ft. over N. slope.
30.20	Wash, 40 lks. wide, 4 ft. deep, drains S. 60° W., with road in wash; asc. 90 ft. over S. slope.
37.00	Spur, slopes SW.; desc. 30 ft. over N. slope.
39.61	The cor. of secs. 2, 3, 10 and 11, monumented with a granite stone, 16x12x6 ins., properly mkd. and firmly set as described in the official record. At the cor. point. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T23N R18W S 3 S 2 S10 S11 1955</p> </div> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor. and bury the original cor. stone alongside the iron post.</p> <p>Land, rolling ridges. Soil, rocky clay. Timber, none; undergrowth, cacti, greasewood and grass.</p>
From the cor. of secs. 1, 2, 11 and 12. N. 88° 37' W. bet. secs. 2 and 11. Over high ridges, through scattered juniper and underbrush. Asc. 135 ft. over NE. slope.	
7.80	Spur, slopes NW.; desc. 135 ft. over W. slope.
13.40	Wash, 20 lks. wide, 4 ft. deep, drains NW.; asc. 140 ft. over ENE. slope.
20.10	Spur, slopes N.; desc. 290 ft. over W. slope.
32.50	Spur, slopes NW.; desc. over W. slope.
39.965	Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>¼ — S 2 S11 1955</p> </div> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor. Desc. 220 ft. over WSW. slope.</p>
53.10	Road, track, bears NW. and SE.
67.80	Spur, slopes SW.; desc. 175 ft. over WNW. slope.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
79.93	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, mountainous. Soil, rocky clay. Timber, scattered juniper; undergrowth, oak brush, mountain mahogany, greasewood, cacti and grass.</p>
	<p>N. 2° 39' E. bet. secs. 2 and 3.</p> <p>Over high ridges, through scattered brush.</p> <p>Desc. 40 ft. over NW. slope.</p>
5.70	<p>Wash, 12 lks. wide, 4 ft. deep, drains SW.; asc. 185 ft. over SW. slope.</p>
23.00	<p>Spur, slopes NNW.; desc. 90 ft. over N. slope.</p>
33.20	<p>Road, graded, bears E. and W.</p>
37.20	<p>Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.; asc. 65 ft. over S. slope.</p>
39.40	<p>The sec. cor. of secs. 2 and 3, monumented with a granite stone, 12x12x6 ins., properly mkd. and firmly set in a mound of stone, as described in the official record.</p> <p>At the cor. point.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">S 3 S 2 1955</p> <p>Bury the original cor. stone alongside the iron post.</p>
	<p>N. 0° 35' E. beginning new measurement.</p> <p>Asc. 40 ft. over S. slope.</p>
2.00	<p>Spur, slopes W.; desc. 90 ft. over NNW. slope.</p>
14.60	<p>Road, track, bears NE. and SW.</p>
21.10	<p>Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. 140 ft. over SSE. slope.</p>
31.50	<p>Spur, slopes SW.; desc. 130 ft. over W. slope.</p>
39.93	<p>The cor. of secs. 2, 3, 34 and 35, Ts. 23 and 24 N., R. 18 W., set, mkd. and witnessed as described in the official record.</p> <p>Land, mountainous. Soil, rocky clay. Timber, none; undergrowth, cacti, greasewood and grass.</p>

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
	<p>From the cor. of secs. 33 and 34 on the S. bdy. of the tp., which is monumented with an iron post, set, mkd. and witnessed as described in the official record.</p> <p>N. 1° 12' W. bet. secs. 33 and 34.</p> <p>Over nearly level grassy benches.</p>
7.20	Wash, 20 lks. wide, 2 ft. deep, drains S. 60° W.
13.80	Wash, 15 lks. wide, 2 ft. deep, drains S. 65° W.
26.10	Wash, 20 lks. wide, 1 ft. deep, drains S. 60° W.
28.50	Wash, 40 lks. wide, 4 ft. deep, drains S. 55° W.
40.21	<p>Point for the 1/2 sec. cor. of secs. 33 and 34, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>S33 S34 1955</p> </div> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p>
41.00	Wash, 20 lks. wide, 3 ft. deep, drains SW.
43.00	Road, graded, bears NE. and SW.
55.60	Wash, 20 lks. wide, 3 ft. deep, drains S. 60° W.
80.42	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a granite stone, 18x14x6 ins., properly mkd. and firmly set as described in the official record.</p> <p>At the cor. point.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T23N R18W S28 S27 S33 S34 1955</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor. and bury the original cor. stone alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay. Timber, none; undergrowth, cacti, greasewood and grass.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89° 09' W. bet. secs. 27 and 34.</p> <p>Desc. over gentle S. slope.</p>

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

- 1.60 Wash, 10 lks. wide, 1 ft. deep, drains S. 60° W.
- 8.00 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.
- 15.90 Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
- 21.70 Wash, 15 lks. wide, 2 ft. deep, drains SW.
- 31.90 Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.
- 39.96 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate distance; no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
- $$\frac{1}{4} \frac{S27}{S34}$$
- 1955
- Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
- 46.90 Road, graded, bears NNW. and SSE.
- 52.90 Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
- 79.92 The cor. of secs. 27, 28, 33 and 34.
- Land, nearly level.
Soil, sandy clay.
Timber, none; undergrowth, cacti, greasewood and grass.
-
- N. 1° 13' W. bet. secs. 27 and 28.
- Over nearly level grassy benches.
- 31.50 Wash, 20 lks. wide, 2 ft. deep, drains S. 70° W.
- 39.80 Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.
- 40.22 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance; no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
- $$\frac{1}{4} \begin{array}{c} S28 \\ | \\ S27 \end{array}$$
- 1955
- Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
- 48.40 Wash, 20 lks. wide, 3 ft. deep, drains SW.
- 52.00 Telephone line, bears SW. and NE.
- 56.20 Road, track, bears NE. and SW.
- 61.10 Wash, 10 lks. wide, 1 ft. deep, drains S. 60° W.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

63.50 Road, track, bears NW. and SE.

67.50 Road, graded, bears NNW. and SSE.

75.00 Wash, 30 lks. wide, 3 ft. deep, drains SW.

80.44 Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23N R18W
S21|S22
S28|S27
1955

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Land, nearly level.

Soil, sandy clay.

Timber, none; undergrowth, cacti, greasewood and grass.

From the cor. of secs. 22, 23, 26 and 27.

N. 87° 48' W. bet. secs. 22 and 27.

Desc. over gentle SW. slope.

3.00 Road, graded, bears N. 80° W. and S. 35° E.

34.40 Same road, bears WSW. and N. 80° E.

36.10 Telephone line, bears NE. and SW.

40.19 Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

¼ — S22
S27
1955

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

68.60 Wash, 40 lks. wide, 2 ft. deep, drains S. 60° W.

80.38 The cor. of secs. 21, 22, 27 and 28.

Land, nearly level.

Soil, sandy clay.

Timber, none; undergrowth, cacti, greasewood and grass.

N. 0° 05' W. bet. secs. 21 and 22.

Over nearly level grassy benches.

17.70 Wash, 20 lks. wide, 2 ft. deep, drains SW.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

- 21.90 Wash, 30 lks. wide, 3 ft. deep, drains S. 30° W.
- 26.30 Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.
- 40.21 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S21 | S22
 1955

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

- 48.50 Wash, 20 lks. wide, 4 ft. deep, drains SW.
- 52.40 Road, track, bears NE. and SW.
- 57.60 Wash, 20 lks. wide, 3 ft. deep, drains S. 30° W.
- 72.70 Wash, 20 lks. wide, 2 ft. deep, drains SW.
- 80.42 Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T23N R18W
 S16 | S15
 S21 | S22
 1955

Land, nearly level.
 Soil, sandy clay.
 Timber, none; undergrowth, cacti, greasewood and grass.

From the cor. of secs. 14, 15, 22 and 23.

N. 88° 11' W. bet. secs. 15 and 22.

Over rocky rolling ridges, through scattered brush.

- .50 Wash, 10 lks. wide, 2 ft. deep, drains S. 10° E.; asc. 50 ft. over E. slope.
- 3.50 Power line, bears NW. and SE.
- 5.60 Ridge, bears N. and S., with track road on top; desc. 30 ft. over W. slope.
- 8.10 Wash, 10 lks. wide, 1 ft. deep, drains S. 25° W.
- 16.90 Wash, 20 lks. wide, 4 ft. deep, drains S. 30° W.
- 24.80 Road, graded, bears NE. and SW.
- 29.70 Wash, 10 lks. wide, 1 ft. deep, drains S. 25° W.
- 35.60 Wash, 10 lks. wide, 2 ft. deep, drains S. 40° W.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
40.31	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4} \begin{array}{l} S15 \\ S22 \\ 1955 \end{array}$ </div> <p>Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p>
42.50	Spur, slopes SW.; desc. 50 ft. over NW. slope.
54.50	Wash, 10 lks. wide, 2 ft. deep, drains S. 60° W.
74.70	Wash, 15 lks. wide, 2 ft. deep, drains S. 30° W.
80.62	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, cacti and sparse grass.</p>
	<p>N. 0° 08' E. bet. secs. 15 and 16.</p> <p>Over rolling grassy ridges.</p>
18.60	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.
21.30	Wash, 15 lks. wide, 2 ft. deep, drains SW.
23.10	Wash, 20 lks. wide, 2 ft. deep, drains S. 70° W.
40.21	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4} \begin{array}{l} S16 S15 \\ 1955 \end{array}$ </div> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p>
47.20	Wash, 30 lks. wide, 4 ft. deep, drains S. 40° W.
54.20	Road, track, bears NW. and SE.
69.70	Road, track, bears NE. and SW.
71.80	Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.
80.42	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

T23N R18W
S 9 | S10
S16 | S15
1955

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, sandy clay.

Timber, none; undergrowth, scattered greasewood, cacti and grass.

From the cor. of secs. 10, 11, 14 and 15.

N. 89° 47' W. bet. secs. 10 and 15.

Desc. over gentle W. slope, through scattered brush.

1.40 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.

5.30 Road, track, bears NW. and SE.

9.20 Wash, 15 lks. wide, 1 ft. deep, drains SW.

25.00 Wash, 30 lks. wide, 3 ft. deep, drains S. 40° W.

26.70 Power line, bears NW. and SE.

37.10 Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.

41.67 The ¼ sec. cor. of secs. 10 and 15, monumented with a granite stone, 16x12x6 ins., set, mkd. and witnessed as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

¼ — S10
S15
1955

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor. and bury the original cor. stone alongside the iron post.

N. 89° 15' W. beginning new measurement.

1.70 Road, track, bears NE. and SW.

4.20 Wash, 5 lks. wide, 1 ft. deep, drains S. 10° W.; asc. 30 ft. over E. slope.

10.40 Top of low hill, bears N. 5 chs. and S. 5 chs.; desc. 40 ft. over W. slope.

16.80 Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.

31.40 Wash, 50 lks. wide, 2 ft. deep, drains S. 10° W.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
36.70	Road, track, bears NE. and SW.
39.45	The cor. of secs. 9, 10, 15 and 16. Land, rolling. Soil, sandy and rocky clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.
	N. 1° 11' W. bet. secs. 9 and 10. Over nearly level land.
11.90	Road, graded, bears N. 10° E. and S. 10° W.
21.40	Road, track, bears NE. and SW.
25.10	Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
31.90	Road, track, bears NW. and SE.
40.22	Point for the $\frac{1}{2}$ sec. cor. of secs. 9 and 10, at proportionate distance; no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \text{S } 9 \text{ S } 10 \\ 1955 \end{array}$ Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor. From above cor. U.S.C.&G.S. B.M. No. T116, dated 1935, bears N. 77° 39' E., 3.88 chs. dist.
48.00	Road, track, bears E. and W.
49.00	Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.
53.40	Road, track, bears NW. and SE.; enter dense greasewood.
59.00	Wash, 10 lks. wide, 2 ft. deep, drains SW.
71.00	The SE. bank of a wash, bears SW. and NE.; enter wash draining SW. from N.; thence along wash.
79.00	Leave wash, draining from N. 10° W.
80.44	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone to top, with brass cap mkd. $\begin{array}{c} \text{T23N R18W} \\ \text{S } 4 \text{ S } 3 \\ \text{S } 9 \text{ S } 10 \\ 1955 \end{array}$ Land, rolling. Soil, sandy and rocky clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.


Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89° 54' W. bet. secs. 3 and 10.
	Desc. 84 ft. over WNW. slope, through scattered brush.
14.30	Wash, 30 lks. wide, 2 ft. deep, drains S. 40° W.
22.50	Road, graded, bears NE. and SW.
28.50	Road, track, bears NE. and SW.
30.60	Wash, 15 lks. wide, 2 ft. deep, drains SW.
35.00	Wash, 15 lks. wide, 1 ft. deep, drains S. 15° W.
40.61	The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented with a granite stone, 18x16x8 ins., set, mkd. and witnessed as described in the official record.
	At the cor. point.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	$\frac{1}{4} \frac{S 3}{S 10}$ 1955
	Bury the original cor. stone alongside the iron post.

	S. 89° 55' W., beginning new measurement.
3.70	Wash, 15 lks. wide, 1 ft. deep, drains S. 40° W.
30.30	Road, graded, bears NNE. and SSW.
34.90	Wash, 40 lks. wide, 3 ft. deep, drains S. 10° W.
40.28	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling.
	Soil, sandy and rocky clay.
	Timber, none; undergrowth, scattered greasewood, cacti and grass.
	N. 1° 14' E. bet. secs. 3 and 4.
	Over rolling land, through scattered brush.
5.50	Wash, 30 lks. wide, 4 ft. deep, drains S. 10° W.
25.30	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° E.
38.00	Enter the S. side of the town of Chloride, Arizona.
40.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains



Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

60.10 Main street of Chloride, Arizona, bears N. 80° E. and S. 80° W.

66.30 Wash, 20 lks. wide, 4 ft. deep, drains S. 50° W.

80.44 The cor. of secs. 3 and 4, T. 23 N., R. 18 W., monumented with an iron post, set, mkd. and witnessed as described in the official record.

Land, rolling.

Soil, sandy clay.

Timber, none; undergrowth, greasewood, cacti and grass.

From the cor. of secs. 32 and 33 on the S. bdy. of the Tp., which is monumented with an iron post, set, mkd. and witnessed as described in the official record.


N. 1° 07' W. bet. secs. 32 and 33.

Over nearly level grassland.

30.00 Santa Claus, Arizona, bears E., 6 chs. dist.

40.40 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

42.00 Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.

44.70 U. S. Highway 93 and 466, bears N. 30° 28' W. and S. 30° 28' E.

47.80 Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.


50.00 Wash, 30 lks. wide, 3 ft. deep, drains S. 30° W.

55.00 Wash, 20 lks. wide, 2 ft. deep, drains S. 20° W.

72.70 Telephone line, bears NW. and SE.

80.80 Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.



Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, level.

Soil, sandy clay.

Timber, none; undergrowth, scattered greasewood, cacti and grass.

From the cor. of secs. 27, 28, 33 and 34.

S. $89^{\circ} 36'$ W. bet. secs. 28 and 33.

Over nearly level grassland.

29.19 Road, track, bears NE. and SW.

40.245 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S28}{S33}$$

1955

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.

45.80 Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.

57.80 Road, track, bears NW. and SE.

59.20 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.

66.10 Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.

72.30 Wash, 90 lks. wide, 3 ft. deep, drains S. 30° W.

80.49 The cor. of secs. 28, 29, 32 and 33.

Land, level.

Soil, sandy clay.

Timber, none; undergrowth, scattered greasewood, cacti and grass.

N. $1^{\circ} 04'$ W. bet. secs. 28 and 29.

Over nearly level grassland.

5.50 Telephone line, bears NE. and SW.

16.00 Wash, 20 lks. wide, 3 ft. deep, drains S. 60° W.

38.10 Road, track, bears NW. and SE.

40.40 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S29}{S28}$$

1955

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	<p>Deposit broken glass for witness.</p> <p>72.20 Wash, 40 lks. wide, 4 ft. deep, drains S. 45° W.</p> <p>80.80 Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T23N R18W S20 S21 S29 S28 1955</p> <p>Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89° 51' W. bet. secs. 21 and 28.</p> <p>2.40 Road, graded, bears NNW. and SSE.</p> <p>13.10 Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.</p> <p>29.50 Road, track, bears NE. and SW.</p> <p>34.50 Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.</p> <p>40.12 Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">¼ — S21 S28 1955</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>47.10 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.</p> <p>71.00 Wash, 90 lks. wide, 3 ft. deep, drains S. 40° W.</p> <p>80.24 The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.</p> <hr/> <p>N. 0° 20' W. bet. secs. 20 and 21.</p> <p>Over nearly level grassland.</p> <p>10.90 Wash, 20 lks. wide, 2 ft. deep, drains S. 40° W.</p> <p>27.10 Wash, 15 lks. wide, 1 ft. deep, drains S. 60° W.</p>
--------	---

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

40.39 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S20} | \text{S21} \\ | \\ 1955 \end{array}$$

43.20 Road, track, bears NW. and SE.

45.90 Wash, 20 lks. wide, 2 ft. deep, drains S. 60° W.

73.10 Wash, 30 lks. wide, 2 ft. deep, drains S. 60° W.

80.78 Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T23N R18W} \\ \hline \text{S17} | \text{S16} \\ \hline \text{S20} | \text{S21} \\ | \\ 1955 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, level.

Soil, sandy clay.

Timber, none; undergrowth, scattered greasewood, cacti and grass.

From the cor. of secs. 15, 16, 21 and 22.

N. $89^\circ 51'$ W. bet. secs. 16 and 21.

Over nearly level grassland.

6.80 Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.

11.60 Road, graded, bears N. and S.

28.10 Wash, 1.10 chs. wide, 3 ft. deep, drains S. 25° W.

40.29 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S16} \\ \hline \text{S21} \\ | \\ 1955 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

43.50 Wash, 20 lks. wide, 2 ft. deep, drains S. 10° W.

63.70 Wash, 15 lks. wide, 1 ft. deep, drains S. 30° W.

73.70 Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
80.58	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.</p>
	<p>N. 1° 15' E. bet. secs. 16 and 17.</p> <p>Over nearly level grassland.</p>
7.60	Wash, 1 ch. wide, 3 ft. deep, drains S. 45° W.
21.80	Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.
40.40	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \hline S17 S16 \\ \hline 1955 \end{array}$ </div> <p>Raise a mound of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, W. of cor.</p>
44.50	Wash, 20 lks. wide, 3 ft. deep, drains S. 60° W.
56.50	Fence, bears NW. and SE.
80.80	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a granite stone, 24x10x10 ins., set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T23N R18W \\ S 8 S 9 \\ \hline S17 S16 \\ \hline 1955 \end{array}$ </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. and bury the original cor. stone alongside the iron post.</p> <p>Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89° 37' W. bet. secs. 9 and 16.</p> <p>Over nearly level grassland.</p>
1.50	Road, graded, bears N. 10° E. and S. 10° W.
9.40	Wash, 5 lks. wide, 1 ft. deep, drains S. 20° W.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
27.70	Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.
34.00	Wash, 40 lks. wide, 3 ft. deep, drains S. 20° W.
37.00	Wash, 30 lks. wide, 2 ft. deep, drains S.
39.50	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance; falls on unsafe ground.
39.70	Point for the witness $\frac{1}{4}$ sec. cor. of secs. 9 and 16. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \hline \begin{array}{ccc} S & 9 & W \\ \hline & 316 & \rightarrow C \end{array} \\ 1955 \end{array}$ <p>Raise a mound of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, N. of cor.</p>
47.90	Fence, bears NNE. and SSW.
62.20	Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
79.00	The cor. of secs. 8, 9, 16 and 17. Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.
	N. 2° 15' W. bet. secs. 8 and 9. Over nearly level grassland.
6.90	Road, track, bears NE. and SW.
9.00	Wash, 30 lks. wide, 2 ft. deep, drains S. 65° W.
23.20	Wash, 10 lks. wide, 2 ft. deep, drains S. 40° W.
23.70	Telephone line, bears NE. and SW.
38.50	Road, track, bears NE. and SW.
40.17	The point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \hline S \ 8 \ \ S \ 9 \\ 1955 \end{array}$
45.00	Wash, 40 lks. wide, 4 ft. deep, drains S. 30° W.
48.60	Road, track, bears NW. and SE.
50.60	Fence, bears NE. and SW.
52.50	Road, track, bears NE. and SW.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

- 64.90 Wash, 15 lks. wide, 2 ft. deep, drains S. 45° W.
- 68.80 Wash, 20 lks. wide, 2 ft. deep, drains S. 60° W.
- 80.34 The cor. of secs. 4, 5, 8 and 9, monumented with a granite stone, 12x10x6 ins., lying in a mound of stone, mkd. and witnessed as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23N R18W
S 5 | S 4
S 8 | S 9
1955

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor. and bury the original cor. stone alongside the iron post.

Land, level.

Soil, sandy clay.

Timber none; undergrowth, scattered greasewood, cacti and grass.

From the cor. of secs. 3, 4, 9 and 10.

N. 89° 45' W. bet. secs. 4 and 9.

Over rolling ridges.

- .70 Wash, 30 lks. wide, 4 ft. deep, drains S. 10° E.; asc. 115 ft. over E. slope.
- 6.30 Top of hill, which extends 30 chs. N. and 10 chs. S.; desc. 125 ft. over W. slope.
- 24.10 Road, graded, bears N. and S.
- 28.30 Road, graded, bears NNE. and SSW.
- 30.50 Power line, bears NNE. and SSW., 15 chs. to a ranch house.
- 33.70 Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.
- 35.20 Road, graded, bears NNE. and S., 15 chs. to ranch house.
- 37.80 Telephone line, bears NE. and SW.
- 39.30 Wash, 20 lks. wide, 2 ft. deep, drains S. 20° W.
- 40.28 Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

¼ — S 4
S 9
1955

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
46.50	Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
64.70	Wash, 25 lks. wide, 2 ft. deep, drains S. 20° W.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
79.93	The cor. of secs. 2, 3, 10 and 11. Land, mountainous. Soil, rocky clay. Timber, scattered juniper; undergrowth, oak brush, mountain mahogany, greasewood, cacti and grass.
	N. 2° 39' E. bet. secs. 2 and 3. Over high ridges, through scattered brush. Desc. 40 ft. over NW. slope.
5.70	Wash, 12 lks. wide, 4 ft. deep, drains SW.; asc. 185 ft. over SW. slope.
23.00	Spur, slopes NNW.; desc. 90 ft. over N. slope.
33.20	Road, graded, bears E. and W.
37.20	Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.; asc. 65 ft. over S. slope.
39.40	The sec. cor. of secs. 2 and 3, monumented with a granite stone, 14x8x6 ins., properly mkd. and firmly set in a mound of stone, as described in the official record. At the cor. point. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd. S 3 S 2 1955 Bury the original cor. stone alongside the iron post.
	N. 0° 35' E. beginning new measurement. Asc. 40 ft. over S. slope.
2.00	Spur, slopes W.; desc. 90 ft. over NNW. slope.
14.60	Road, track, bears NE. and SW.
21.10	Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. 140 ft. over SSE. slope.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
	<p>From the cor. of secs. 31 and 32 on the S. bdy. of the Tp., which is monumented with an iron post, set mkd. and witnessed as described in the official record.</p> <p>N. 0° 54' W. bet. secs. 31 and 32.</p> <p>Over nearly level grassland.</p>
5.00	Wash, 30 lks. wide, 3 ft. deep, drains S. 30° W.
40.52	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 31 and 32, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S31 S32 1955 </div> <p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p>
61.60	Road, track, bears NE. and SW.
67.80	Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.
81.04	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T23N R18W S30 S29 S31 S32 1955 </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.</p>
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89° 30' W. bet. secs. 29 and 32.</p> <p>Over nearly level grassland.</p>
2.90	Telephone line, bears NW. and SE.
8.90	Wash, 10 lks. wide, 1 ft. deep, drains S. 45° W.
18.20	Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.
20.00	U. S. Highway 93 and 466, bears N. 30° 28' W. and S. 30° 28' E.
21.90	Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.
25.30	Power line, bears N. 30° 28' W. and S. 30° 28' E.
29.40	Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
40.145	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> $\frac{1}{4} \frac{S29}{S32}$ <p style="text-align: center;">1955</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.</p>
62.20	Wash, 1 ch. wide, 2 ft. deep, drains S. 10° W.
67.00	Road, track, bears NE. and SW.
70.40	Wash, 15 lks. wide, 1 ft. deep, drains S. 20° W.
80.29	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.</p> <hr/> <p>N. $89^{\circ} 48'$ W. bet. secs. 30 and 31.</p> <p>Over nearly level grassland.</p>
1.90	Small draw, drains SW.
27.20	Wash, 10 lks. wide, 1 ft. deep, drains S. 45° W.
30.00	Wash, 90 lks. wide, 2 ft. deep, drains S. 20° W.
40.25	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at proportionate distance; no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> $\frac{1}{4} \frac{S30}{S31}$ <p style="text-align: center;">1955</p>
50.40	Road, graded, bears NE. and SW.
72.00	Wash, 15 lks. wide, 1 ft. deep, drains S. 20° W.
79.99	<p>The cor. of secs. 30 and 31, T. 23 N., R. 18 W., which is monumented with an iron post, set, mkd. and witnessed as described in the official record.</p> <p>Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. $1^{\circ} 10'$ W. bet. secs. 29 and 30.</p> <p>Over nearly level grassland.</p>

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

7.20 Small draw, bears S. 20° W.

38.60 Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.

40.525 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.




Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

55.60 Wash, 40 lks. wide, 2 ft. deep, drains S. 50° W.

81.05 Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.



Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, level.
Soil, sandy clay.
Timber, none; undergrowth, scattered greasewood, cacti and grass.

From the cor. of secs. 20, 21, 28 and 29.

S. 89° 41' W. bet. secs. 20 and 29.


Over nearly level grassland.

4.90 Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.

20.20 Road, track, bears NW. and SE.

40.22 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.



Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.

42.20 Telephone line, bears NW. and SE.

42.60 Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.

47.50 Road, track, bears NW. and SE.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
63.70	Wash, 1.40 chs. wide, 3 ft. deep, drains S. 40° W.
64.70	Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.
65.70	U. S. Highway 93 and 466, bears N. 30° 28' W. and S. 30° 28' E.
67.40	Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.
70.90	Power line, bears N. 30° 28' W. and S. 30° 28' E.
80.44	The cor. of secs. 19, 20, 29 and 30. Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.
	S. 89° 57' W. bet. secs. 19 and 30. Over nearly level grassland.
11.80	Road, graded, bears NE. and SW.
19.70	Wash, 15 lks. wide, 1 ft. deep, drains S. 25° W.
40.12	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate distance; no remaining evidence of the original cor. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd. $\frac{1}{4} \frac{S19}{S30}$ 1955 Deposit broken glass for witness.
54.30	Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
73.30	Wash, 5 lks. wide, 1 ft. deep, drains S. 30° W.
79.04	The cor. of secs. 19 and 30, T. 23 N., R. 18 W., monumented with an iron post, set, mkd. and witnessed as described in the official record. Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.
	From the cor. of secs. 19, 20, 29 and 30. N. 0° 24' W. bet. secs. 19 and 20. Over nearly level grassland.
12.70	Road, graded, bears NE. and SW.
16.50	Power line, bears N. 30° 28' W. and S. 30° 28' E.
22.30	Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.
23.20	Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
24.90	U. S. Highway 93 and 466, bears N. 30° 28' W. and S. 30° 28' E.
28.40	Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.
29.00	Wash, 15 lks. wide, 2 ft. deep, drains S. 10° W.
34.40	Road, track, bears NW. and SE.
40.52	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate distance; no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	$\frac{1}{4}$ S19 S20 1955
55.30	Wash, 12 lks. wide, $1\frac{1}{2}$ ft. deep, drains S. 70° W.
71.00	Wash, 10 lks. wide, 2 ft. deep, drains S. 70° W.
75.00	Telephone line, bears NW. and SE.
78.00	Wash, 10 lks. wide, 1 ft. deep, drains S. 60° W.
80.50	Enter wash, drains SW.
81.04	True point for the cor. of secs. 17, 18, 19 and 20, falls in center of wash, at proportionate dist.
	Witness cor. bears N. 89° 49' E., 50 lks. from true point, hereinafter described.
	Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89° 49' W. bet. secs. 17 and 20.
	Over nearly level grassland.
3.00	Wash, 1.50 chs. wide, 3 ft. deep, drains S. 45° W.
11.20	Wash, 10 lks. wide, 1 ft. deep, drains S. 15° W.
13.40	Road, track, bears NE. and SW.
40.34	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20 at proportionate distance; no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	$\frac{1}{4}$ $\frac{S17}{S20}$ 1955
41.50	Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.
45.10	Road, track, bears N. and S.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
47.80	Road, track, bears NE. and SW.
60.70	Wash, 15 lks. wide, 1 ft. deep, drains S. 40° W.
64.30	Road, track, bears NW. and SE.
80.18	Point for the Witness cor. of secs. 17, 18, 19 and 20. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T23N R18W W ← S18 S17 C ← S19 S20 1955
	Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
80.68	True point for the cor. of secs. 17, 18, 19 and 20. Land, level. Soil, sandy clay. Timber, none; undergrowth, scattered greasewood, cacti and grass.
	From the true point of the cor. of secs. 17, 18, 19 and 20. S. 89° 43' W. bet. secs. 18 and 19. Over nearly level grassland.
.40	Leave wash.
3.00	Telephone line, bears NW. and SE.
27.10	Road, track, bears NE. and SW.
30.70	Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.
32.50	U. S. Highway 93 and 466, bears N. 30° 28' W. and S. 30° 28' E.
34.30	Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.
37.80	Power line, bears N. 30° 28' W. and S. 30° 28' E.
40.29	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	¼ ——— S18 S19 1955
44.90	Wash, 15 lks. wide, 1 ft. deep, drains S. 70° W.
49.90	Road, track, bears NE. and SW.
60.00	Wash, 10 lks. wide, 1 ft. deep, drains S. 60° W.
69.70	Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.
79.27	The cor. of secs. 18 and 19, T. 23 N., R. 18 W., monumented with an iron post, set, mkd. and witnessed as described in the official record.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

Land, level.
Soil, sandy clay.
Timber, none; undergrowth, scattered greasewood, cacti and grass.

From the true point for the cor. of secs. 17, 18, 19 and 20.

N. 0° 40' W. bet. secs. 17 and 18.

- .90 Wash, 10 lks. wide, 2 ft. deep, drains S. 45° W.
- 5.60 Road, track, bears NW. and SE.
- 6.30 Wash, 30 lks. wide, 3 ft. deep, drains S. 45° W.
- 24.00 Wash, 5 lks. wide, 1 ft. deep, drains S. 40° W.
- 40.52 Point for the $\frac{1}{2}$ sec. cor. of secs. 17 and 18, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

$\frac{1}{2}$
 S18 | S17
 1955

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

- 45.60 Wash, 5 lks. wide, 1 ft. deep, drains S. 40° W.
- 48.40 Telephone line, bears NE. and SW.
- 50.50 Wash, 5 lks. wide, 1 ft. deep, drains S. 40° W.
- 51.00 Road, track, bears NE. and SW.
- 69.50 Wash, 10 lks. wide, 2 ft. deep, drains S. 60° W.
- 81.04 The cor. of secs. 7, 8, 17 and 18, monumented with a granite stone, 16x14x10 ins., mkd. set and witnessed as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T23N R18W
 S 7 | S 8
 S18 | S17
 1955

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor. and bury the original cor. stone alongside the iron post.

Land, level.
Soil, sandy clay.
Timber, none; undergrowth, scattered greasewood, cacti and grass.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains	
	From the cor. of secs. 8, 9, 16 and 17.
	West, bet. secs. 8 and 17.
	Over nearly level grassland.
3.80	Road, track, bears NE. and SW.
8.20	Wash, 20 lks. wide, 2 ft. deep, drains S. 60° W.
10.20	Wash, 5 lks. wide, 1 ft. deep, drains S. 20° W.
18.50	Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.
23.80	Fence, bears NW. and SE.
28.60	Wash, 20 lks. wide, 4 ft. deep, drains S. 20° W.
33.10	Telephone line, bears NE. and SW.
41.78	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate distance; no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\frac{1}{4} \frac{S 8}{S 17}$ 1955
	Deposit broken glass for witness.
55.50	Road, bladed, bears NE. and SW.
74.20	Wash, 10 lks. wide, 1 ft. deep, drains S. 70° W.
83.56	The cor. of secs. 7, 8, 17 and 18.
	Land, level.
	Soil, sandy clay.
	Timber, none; undergrowth, scattered greasewood, cacti and grass.
	S. 89° 26' W. bet. secs. 7 and 18.
	Over nearly level grassland.
40.25	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\frac{1}{4} \frac{S 7}{S 18}$ 1955
	Deposit broken glass for witness.
49.00	Wash, 40 lks. wide, 2 ft. deep, drains S. 20° W.
50.10	Road, track, bears NW. and SE.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

- 52.90 Telephone line, bears NW. and SE.
- 77.40 Highway right-of-way fence, bears N. 30° 28' W. and S. 30° 28' E.
- 79.00 The cor. of secs. 7 and 18, T. 23 N., R. 18 W., monumented with an iron post, set, mkd. and witnessed as described in the official record. This cor. is buried in the NE. edge of U. S. Highway 93 and 466.

Land, level.
Soil, sandy clay.
Timber, none; undergrowth, scattered greasewood, cacti and grass.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 07' W. bet. secs. 7 and 8.

Over nearly level grassland.

18.50 Wash, 20 lks. wide, 3 ft. deep, drains S. 80° W.

31.50 Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.

31.70 Road, track, bears NE. and SW.

40.22 Point for the 1/2 sec. cor. of secs. 7 and 8, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

†
 S 7 | S 8
 1955

Deposit broken glass for witness.

43.00 Wash, 5 lks. wide, 1 ft. deep, drains S. 30° W.

48.00 Road, track, bears NE. and SW.

52.40 Wash, 40 lks. wide, 2 ft. deep, drains S. 65° W.

54.10 Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.

75.00 Draw, drains SW.

79.20 State Highway No. 62, bears ENE. and WSW.

80.44 Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T23N R18W
 S 6 | S 5
 S 7 | S 8
 1955

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.

Land, level.
Soil, sandy clay.
Timber, none; undergrowth, scattered greasewood, cacti and grass.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains

From the cor. of secs. 4, 5, 8 and 9.

N. 89° 58' W. bet. secs. 5 and 8.

Over nearly level grassland.

- 5.30 Wash, 15 lks. wide, 1 ft. deep, drains S. 20° W.
- 12.30 Wash, 10 lks. wide, 2 ft. deep, drains S. 35° W.
- 26.10 Wash, 20 lks. wide, 2 ft. deep, drains S. 45° W.
- 32.80 Wash, 5 lks. wide, 1 ft. deep, drains S. 30° W.
- 40.28 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate distance; no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S 5}{S 8}$$

1955

Deposit broken glass as witness.

- 40.40 Wash, 10 lks. wide, 4 ft. deep, drains S. 60° W.
- 58.60 Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.
- 73.20 Draw, drains SW.
- 77.50 State Highway No. 62, bears ENE. and WSW.
- 80.56 The cor. of secs. 5, 6, 7 and 8.
- Land, level.
Soil, sandy clay.
Timber, none; undergrowth, scattered greasewood, cacti and grass.

S. 89° 32' W. bet. secs. 6 and 7.

Over rolling grassland.

- 10.40 Wash, 20 lks. wide, 1 ft. deep, drains S. 50° W.
- 14.00 Spur, low, slopes WSW.; desc. 30 ft. over NW. slope.
- 22.30 Wash, 10 lks. wide, 2 ft. deep, drains S. 60° W.
- 32.00 Spur, low, slopes SW.; desc. 50 ft. over NW. slope.
- 40.28 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S 6}{S 7}$$

1955

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.

Dependent Resurvey,
Subdivision, T. 23 N., R. 18 W.

Chains


44.50 Wash, 5 lks. wide, 1 ft. deep, drains S. 40° W.
 58.00 Wash, 4 lks. wide, ½ ft. deep, drains S. 40° W.
 69.50 Road, track, bears NNE. and SSW.
 72.00 Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.
 78.85 The cor. of secs. 6 and 7, T. 23 N., R. 18 W., monumented with an iron post, set, mkd. and witnessed as described in the official record.
 Land, rolling.
 Soil, sandy clay.
 Timber, none; undergrowth, scattered greasewood, cacti and grass.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 10' E. bet. secs. 5 and 6.

Over rolling grassland.

5.60 Wash, 20 lks. wide, 1 ft. deep, drains S. 45° W.
 34.00 Wash, 20 lks. wide, 1 ft. deep, drains S. 20° W.
 40.22 Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; no remaining evidence of the original cor.
 Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

53.80 Road, graded, bears NE. and SW.
 57.00 Wash, 15 lks. wide, 2 ft. deep, drains S. 80° W.
 57.00 Power line, bears E. and W.
 63.10 Road, track, bears E. and W.
 75.40 Wash, 40 lks. wide, 2 ft. deep, drains S. 40° W.
 80.34 The cor. of secs. 5 and 6, T. 23 N., R. 18 W., monumented with an iron post, set, mkd. and witnessed as described in the official record.
 Land, rolling.
 Soil, sandy clay.
 Timber, none; undergrowth, scattered greasewood, cacti and grass.

General Description

The extreme northeast portion of this township is mountainous and rough, covered for the most part with scattered timber and brush. The balance of the township is rolling land with good grass.

T. 23 N., R. 18 W.

U. S. Highway 93 and 466 bisects the southwest corner of the township, and State Road 62, from Grasshopper Junction to the town of Chloride, Arizona, crosses the extreme northwest corner of the township. The town of Chloride lies in section 3, with a small portion extending into section 4. There are numerous roads, both track and graded, throughout the township.

There is limited mining activity in this township and the major source of revenue is derived from stock grazing by ranchers. The water for stock, for the most part, is held in man-made earthen dams.

The elevation ranges from a low of 3250 ft. in the southwest corner to a high of 6054 ft. in section 1.

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 19th day of October, 1955, I have surveyed /dependently resurveyed the South Boundary of Section 31 and the Subdivision of Township 23 North, Range 18 West

Gila and Salt River of the Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

June 7, 1956 Salt Lake City, Utah

Donald E. Harding Donald E. Harding Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT, Washington, D. C., FEB 12 1957, 19

The foregoing field notes of the /dependent survey of resurvey of the South Boundary of Section 31 and the Subdivision of Township 23 North, Range 18 West, Gila and Salt River Meridian

executed by Donald E. Harding, Cadastral Engineer having been critically examined and found correct, are hereby approved.

Earl G. Harrington Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Cadastral Engineering Staff Officer.