

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

of the

Resurvey

of the

West Boundary

and

A Portion of the Subdivision

of

Township 7 North, Range 4 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald E. Harding, Cadastral Surveyor

Under special instructions dated October 3, 1955, which provided
for the surveys included under Group No. 307, approved October 3, 1955
and assignment instructions dated January 14, 1957.

Survey commenced January 21, 1957.

Survey completed February 15, 1957.

BOOK 4539

INDEX DIAGRAM

Township 7 North, Range 4 West

7 6	34 5	22 4	3	2	1
33	33	21			
5 7	32 8	20 9	10	11	12
31	30	20			
5 18	29 17	19 16	15	14	13
29	28	18			
3 19	27 20	17 21	16 22	14 23	10 24
26	25		16	13	10
3 30	24 29	28	27	12 26	9 25
24	23		15	12	8
2 31	22 32	17 33	14 34	11 35	7 36

Township 7 North, Range 4 West

Chains

The south boundary of the township was surveyed by S. W. Foreman in 1871 and 1872 and was resurveyed by Voigt and Gill in 1916. The south four miles of the east boundary were surveyed by S. W. Foreman in 1872 and resurveyed by B. J. Kinsey in 1934. The north two miles were surveyed by Kinsey in 1934. The west boundary was surveyed by S. W. Foreman in 1871. The south five miles were resurveyed by H. D. Voigt in 1916; however, no iron post monuments were set. The $W\frac{1}{2}$ of the north boundary was surveyed by S. W. Foreman in 1872. The $W\frac{1}{2}$ was resurveyed and the $E\frac{1}{2}$ surveyed by B. J. Kinsey in 1929.

The township was partially subdivided by S. W. Foreman in 1872. The subdivision was completed and a portion of the NE. cor. of the township was resurveyed by Forrest and Wakeman in 1946. The four boundaries of sec. 28 were resurveyed by B. J. Kinsey in 1938.

The record of the 1916 resurvey of the south boundary of the township shows that the $\frac{1}{4}$ sec. cor. monuments on the south boundaries of secs. 32, 33 and 34 were marked for corners of maximum control. The marks have been deleted on the $S\frac{1}{2}$ of these iron posts. They now refer to the secs. to the north only.

The survey was executed with a W. and L. E. Gurley solar transit, serial No. 541332, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition and placed in proper adjustment prior to the beginning of the survey. The azimuths of the lines were established and checked by the direct solar method from time to time throughout the survey.

Measurements were made with a Chicago steel tape, 8 chains in length, graduated every $1/10$ link for the first link, every link for the next 99 links and every 10 links thereafter. The tape was tested by comparison with a standard tape and found correct. Measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustment. The horizontal equivalents only are entered in this field note record.

The following transcribed field notes are those of the resurvey of the west boundary and a portion of the subdivision, T. 7 N., R. 4 W.

On January 22, 1957, at 9:30 a.m., at the cor. of secs. 5, 6, 31 and 32, on the north boundary of the township, the following direct solar observation was made:

Mean vertical angle	20° 23'
Mean horizontal angle	47° 28' 30"
Latitude of station	33° 59' 10"
Declination	19° 37'
Bearing of sun	S. 46° 58' 10" E.
True bearing of object sighted	S. 0° 30' 20" W.

The geographic position of the SE. cor. of the township is in latitude 33° 53' 46" N. and longitude 112° 36' 59" W. The mean magnetic declination is 14° 30' E.

Dep. Resurvey of the West Bdy., T. 7 N., R. 4 W.

Chains

From the cor. of Tps. 7 N., Rs. 4 and 5 W., a 3 in. iron post, set mkd. and witnessed, as described in the official record.

N. 0° 11' E., bet. secs. 31 and 36.

Over mountainous land, through scattered undergrowth.

Desc. 85 ft. over NNE. slope.

3.70 Wash, 10 lks. wide, 4 ft. deep, drains ESE.; asc. 35 ft. over S. slope.

7.80 Spur, slopes E.; asc. 35 ft. over broken E. slope.

21.90 Spur, slopes E.; asc. 70 ft. over broken S. slope.

27.10 Spur, slopes E.; asc. 75 ft. over broken S. slope.

39.85 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a granite stone, 18x14x5 ins., mkd. $\frac{1}{4}$ on W. face, firmly set in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground and in a mound of stone to top, with brass cap mkd.

T7N
R5W R4W
 $\frac{1}{4}$
S 36 | S 31
1957

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Deposit the original corner alongside the iron post.

N. 0° 11' E., beginning new measurement.

1.50 Ridge, bears ENE. and SW.; desc. 205 ft. over NNW. slope.

22.30 Wash, 1 ch. wide, 3 ft. deep, drains ENE.

35.90 Small wash, drains ESE.

39.85 The cor. of secs. 25, 30, 31 and 36, monumented with a granite stone 15x10x5 ins., mkd. 5 notches on N. side and 1 notch on the S., firmly set in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T7N
R5W R4W
S 25 | S 30
S 36 | S 31
1957

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Deposit the original cor. alongside the iron post.

Dep. Resurvey of the West Bdy., T. 7 N., R. 4 W.

Chains

Land, mountainous.
Soil, rocky clay.
Timber, none; undergrowth, scattered mesquite, palo verde,
greasewood, cacti, and sparse grass.

N. 0° 07' E., bet. secs. 25 and 30.

Over mountainous land, through scattered undergrowth.

4.30 Small wash, drains SSW.; asc. 220 ft. over S. slope.

22.00 Ridge, bears E. and W.; desc. 55 ft. over N. slope.

39.86 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with a granite stone
24x10x4 ins., mkd. $\frac{1}{4}$ on W. face, firmly set in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the
ground, in a mound of stone to top, with brass cap mkd.

T7N
R5W R4W
 $\frac{1}{4}$
S 25 | S 30
1957

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Deposit the original corner alongside the iron post.

N. 0° 12' E., beginning new measurement.

Desc. 85 ft. over N. slope.

16.60 Spur, breaks to and slopes W.; desc. 160 ft. over broken N. slope.

39.84 The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone,
18x10x3 ins., mkd. 4 notches on N., 2 notches on S. face, and firmly
set in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the
ground, in a mound of stone to top, with brass cap mkd.

T7N
R5W R4W
S 24 | S 19
S 25 | S 30
1957

Place the original corner alongside the iron post.

Land, mountainous.
Soil, rocky clay.
Timber, none; undergrowth, scattered mesquite, palo verde, grease-
wood, cacti and sparse grass.

N. 0° 09' E., bet. secs. 19 and 24.

Desc. 30 ft. over N. slope.

Dep. Resurvey of the West Bdy., T. 7 N., R. 4 W.

Chains	
5.26	Wash, 1 ch. wide, 6 ft. deep, drains NE.
11.30	Low spur, slopes E.
12.95	Wash, 1 ch. wide, 4 ft. deep, drains E.; asc. 60 ft. over SE. slope.
22.00	Spur, slopes E.
31.50	Spur, slopes E.; desc. 50 ft. over N. slope.
39.87	The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, monumented with a granite stone, 14x10x6 ins., mkd. $\frac{1}{4}$ on W. face, firmly set in the ground, with a mound of stone W.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.
	T7N R5W R4W $\frac{1}{4}$ S 24 S 19 1957
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
	Bury the original cor. alongside the iron post.
	—————
	N. $0^{\circ} 03'$ W., beginning new measurement.
	Desc. 40 ft. over N. slope.
3.35	Small wash, drains N. 20° W.
9.20	Small wash, drains W.; asc. 50 ft. over S. slope.
12.10	Ridge, bears E. and W.; desc. 60 ft. over N. slope.
16.10	Wash, 10 lks. wide, 6 ft. deep, drains W.; asc. 35 ft. over S. slope.
21.90	Knoll, on ridge bearing E. and W.; desc. 130 ft. over NW. slope.
40.08	The cor. of secs. 13, 18, 19 and 24, monumented with a granite stone 12x8x6 ins., mkd. with 3 notches on N. and S. edges, firmly set in the ground, with a mound of stone W.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a mound of stone to top, with brass cap mkd.
	T7N R5W R4W <u>S 13 S 18</u> S 24 S 19 1957
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
	Bury the original cor. alongside the iron post.
	Land, mountainous.
	Soil, rocky clay.
	Timber, none; undergrowth, scattered mesquite, palo verde, greasewood, cacti and sparse grass.

Dep. Resurvey of the West Bdy., T. 7 N., R. 4 W.

Chains

N. 0° 10' E., bet. secs. 13 and 18.

Desc. 90 ft. over broken N. slope, through scattered undergrowth.

17.60 Wash, 40 lks. wide, 6 ft. deep, drains E.; asc. 110 ft. over SW. slope.

25.60 Ridge, bears NW. and SE.; desc. 50 ft. over rolling E. slope.

39.70 The $\frac{1}{4}$ sec. cor. of secs. 13 and 18; monumented with a sandstone, 14x12x6 ins., mkd. $\frac{1}{4}$ on W. face, firmly set in the ground, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N
R5W R4W
 $\frac{1}{4}$
S 13 | S 18
1957

Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Bury the original cor. alongside the iron post.

N. 0° 02' E., beginning new measurement.

.26 Small wash, drains NE.

3.75 Low ridge, bears NE. and SW.; desc. 80 ft. over N. slope.

16.70 Wash, 10 lks. wide, 4 ft. deep, drains E.; asc. 50 ft. over S. slope.

23.50 Low ridge, bears E. and W.; desc. 35 ft. over NE. slope.

29.70 Wash, 15 lks. wide, 2 ft. deep, drains S. 70° E.; asc. 40 ft. over S. slope.

35.10 Low ridge, bears E. and W.; desc. 40 ft. over N. slope.

39.83 The cor. of secs. 7, 12, 13 and 18, monumented with a 2 ins. iron post, set, mkd. and witnessed, as described in the official record.

Land, high and rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered mesquite, palo verde, cacti, greasewood and sparse grass.

N. 1° 00' E., bet. secs. 7 and 12.

Over low rolling land, through scattered undergrowth.

7.10 Fence, bears NE. and SW.

9.10 Fence, bears NW. and SE.

10.20 A. T. and S. F. Railroad (branch line) bears NW. and SE.

11.50 Fence, bears NW. and SE.

15.80 Fence, bears E. and W.

Dep. Resurvey of the West Bdy., T. 7 N., R. 4 W.

Chains	
18.30	Farm house, bears West 3 chs. dist.
19.30	Fence, bears NW. and SE.
37.44	Fence, bears WNW. and ESE.
37.58	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 7 and 12. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground with brass cap mkd. <div style="text-align: center;"> W C T7N R5W R4W $\frac{1}{4}$ S 12 S 7 1957 </div>
	from which A mesquite, 6 ins. diam., bears N. 80° E., 38 lks. dist., mkd. $\frac{1}{4}$ S7 WC BT. A mesquite, 4 ins. diam., bears N. 79° W., 26 lks. dist., mkd. $\frac{1}{4}$ S12 WC BT. Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
37.80	South bank of the Hassayampa River, bears NW. and SE.
40.18	True point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, falls in this river bottom; impractical to monument.
42.00	Main channel (dry) of the Hassayampa River, 1 ch. wide, 2 ft. deep, drains S. 60° E.
46.00	North bank of the Hassayampa River, bears NW. and SE.
50.55	Fence, bears NNW. and SE.
50.65	Power line, bears NNW. and SE.
51.25	U. S. Highway Nos. 60, 70 and 89, bears NNW. and SE.
52.85	Fence, bears NNW. and SE.; asc. 40 ft. over S. slope.
53.50	Spur, slopes W.; desc. 45 ft. over N. slope.
56.50	Wash, 1 ch. wide, 2 ft. deep, drains SW.; asc. 130 ft. over broken S. slope.
71.80	Telephone line, bears NW. and SE.
75.80	Spur, slopes W.; desc. 50 ft. over N. slope.
80.36	The cor. of secs. 1, 6, 7 and 12, monumented with a 2 ins. iron post, set, mkd. and witnessed, as described in the official record. Land, high and rolling. Soil, rocky clay. Timber, none; undergrowth, scattered mesquite, palo verde, cacti, greasewood and sparse grass.

Dep. Resurvey of the West Bdy., T. 7 N., R. 4 W.

Chains

- N. $0^{\circ} 27'$ E., bet. secs. 1 and 6.
Over rolling land, through scattered undergrowth.
- .20 Small wash, drains S. 70° W.; asc. 45 ft. over S. slope.
- 8.00 Spur, slopes WSW.; desc. 60 ft. over NW. slope.
- 21.40 Wash, 1 ch. wide, 1 ft. deep, drains SSW.; asc. 50 ft. over SE. slope.
- 28.00 Spur, slopes SSW.; desc. 60 ft. over NW. slope.
- 34.50 Road, graded, bears NE. and SW., in wash 50 lks. wide, 1 ft. deep, draining S. 35° W.
- 40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate dist.; no remaining evidence of the original cor.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, in a mound of stone to top, with brass cap mkd.
- T7N
R5W R4W
 $\frac{1}{4}$
S 1 | S 6
1957
- from which
- A mesquite, 6 ins. diam., bears S. 30° W., 39 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
- Asc. 150 ft. over SSE. slope.
- 57.50 Ridge, bears E. and W.; desc. 70 ft. over NW. slope.
- 72.20 Small wash, drains SW.; asc. 35 ft. over S. slope.
- 80.02 The cor. of Tps. 7 and 8 N., Rs. 4 and 5 W., monumented with a 3 ins. iron post, set, mkd. and witnessed, as described in the official record.
- Land, high and rolling.
Soil, rocky clay.
Timber, none; undergrowth, scattered mesquite, palo verde, cacti, greasewood and sparse grass.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

- From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., which is monumented with an iron post, set, mkd. and witnessed, as described in the official record.
- N. $0^{\circ} 04'$ W., bet. secs. 35 and 36.
- Over low rolling land, through scattered undergrowth.
- 33.30 Track road, bears NE. and SW.; earthen dam, in a small wash, bears West, 9 chs. dist.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
39.97	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R4W $\frac{1}{4}$ S 35 S 36 1957</p>
	<p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p>
48.20	<p>Wash, 20 lks. wide, 1 ft. deep, drains SW.</p>
61.80	<p>Small wash, drains SW.</p>
79.94	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R4W S 26 S 25 S 35 S 36 1957</p>
	<p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p>
	<p>Land, low and rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, palo verde, cacti, and sparse grass.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., which is monumented with an iron post, set, mkd. and witnessed, as described in the official record.</p>
	<p>N. $89^{\circ} 56'$ W., bet. secs. 25 and 36.</p>
	<p>Over mountainous land, through scattered undergrowth.</p>
	<p>Asc. 195 ft. over NE. slope.</p>
16.00	<p>Small peak, on ridge bearing N. and S.; desc. 190 ft. over SW. slope.</p>
22.60	<p>Saddle, between peaks E. and W.; asc. 190 ft. over NE. slope.</p>
31.60	<p>Ridge, bears N. and S.; desc. 220 ft. over W. slope.</p>
39.965	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R4W $\frac{1}{4}$ — S 25 S 36 1957</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

Desc. 230 ft. over NW. slope.

56.80 Track road, old, bears SE. and NW.

75.00 Track road, old, bears N. and S.

79.93 The cor. of secs. 25, 26, 35 and 36.

Land, mountainous.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, palo verde, cacti, and sparse grass.

N. 0° 15' E., bet. secs. 25 and 26.

Over rolling land, through scattered undergrowth.

4.60 Track road, bears NW. and SE.

16.90 Same road, bears NE. and SW.

18.20 Desc. 80 ft. over NE. slope.

24.00 Desc. 60 ft. into San Domingo wash.

25.60 Main channel of San Domingo wash, 30 lks. wide, 1 ft. deep, drains S. 50° W. from N., thence up San Domingo wash.

33.40 Leave wash, drains S. from NE.; asc. 140 ft. over S. slope.

39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate dist.; no remaining evidence of the original cor.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7N R4W

$$\begin{array}{c} \frac{1}{4} \\ S\ 26\ | \ S\ 25 \\ 1957 \end{array}$$
Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

50.00 Asc. 180 ft. over rolling SW. slope.

79.94 Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W

$$\begin{array}{c} S\ 23\ | \ S\ 24 \\ S\ 26\ | \ S\ 25 \\ 1957 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From above cor., unpatented mining claim cor. No. 4 of Dragon No. 13, identical to cor. No. 3 of Dragon No. 14, mineral survey No. 4110, bears S. 41° 59' W., 2.55 chs. dist.

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., which is monumented with an iron post, set, mkd. and witnessed as described in the official record.
	S. 89° 57' W., bet. secs. 24 and 25. Over mountainous land, through scattered undergrowth. Desc. over gentle W. slope.
12.30	Wash, 10 lks. wide, 2 ft. deep, drains N. 80° W.; desc. 60 ft. over rolling general W. slope.
28.90	Wash, 20 lks. wide, 1 ft. deep, drains NW.; asc. 90 ft. over NE. slope.
39.77	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, in a mound of stone to top, with brass cap mkd.
	T7N R4W $\frac{1}{4}$ $\frac{S\ 24}{S\ 25}$ 1957
	Asc. 75 ft. over NNE. slope.
50.10	Spur, slopes N.; desc. 265 ft. over W. slope.
59.70	Wash, 30 lks. wide, 1 ft. deep, drains S. 10° W., rock and masonry dam, 5 chs. N. of line; asc. 410 ft. over steep rocky E. slope.
74.30	Saddle in high ridge, bears N. and S.; desc. 195 ft. over W. slope.
79.54	The cor. of secs. 23, 24, 25 and 26. Land, mountainous. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, palo verde, cacti, and sparse grass.
	N. 0° 03' E., bet. secs. 23 and 24. Over rolling land, through scattered undergrowth. Asc. 55 ft. over general W. slope.
8.50	Slope changes to NW.; desc. 120 ft.
33.20	Small ridge, bears NW. and SE.
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, in a mound of stone to top, with brass cap mkd.
	T7N R4W $\frac{1}{4}$ S 23 S 24 1957
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
41.00	Slope changes; asc. 130 ft. over S. slope of rocky point.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

- 49.00 High rocky point, bears East 1 ch.; desc. 65 ft. over NW. slope.
- 62.50 Small rocky ridge, bears NNW. and SSE.; desc. 100 ft. over NE. slope.
- 78.10 Wash, 12 lks. wide, 6 ins. deep, drains S. 20° E.
- 79.94 The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, set, mkd. and witnessed, as described in the official record.

Land, mountainous.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., which is monumented with an iron post, set, mkd. and witnessed, as described in the official record.

N. 0° 04' E., bet. secs. 34 and 35.

Over rolling land, through scattered undergrowth.

- 2.80 Small wash, drains SW.
- 17.00 Small wash, drains SW.
- 21.50 Track road, old, bears NE. and SW.
- 36.00 Small wash, drains SW.
- 39.00 Small wash, drains SW.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate dist.; no remaining evidence of the original cor.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7N R4W

$\frac{1}{4}$
S 34 | S 35
1957

- Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
- 43.20 Old road, bears NE. and SW.
- 51.10 Old road, bears N. 70° E. and SW.
- 53.65 Wash, 15 lks. wide, 1 ft. deep, drains SW.
- 68.35 Small wash, drains S. 70° W.
- 76.00 Small wash, drains SW.
- 80.00 Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; no remaining evidence of the original cor.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
	<p>T7N R4W <u>S 27 S 26</u> <u>S 34 S 35</u> 1957</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, mountainous. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89° 54' W., bet. secs. 26 and 35.</p> <p>Over rolling land, through scattered undergrowth.</p>
6.70	Small wash, drains S. 20° W.
10.00	Low flat spur, slopes SW.; desc. 105 ft. over W. slope.
18.90	Desc. 60 ft. into San Domingo wash.
22.20	Main channel of San Domingo wash, 30 lks. wide, 1 ft. deep, drains S. 20° W.
28.70	Leave wash bottom; asc. 110 ft. over SE. slope.
36.60	Road, track, bears NE. and SW.
39.935	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p>T7N R4W $\frac{1}{4}$ <u>S 26</u> <u>S 35</u> 1957</p>
	<p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.</p>
55.25	Small wash, drains SW.
74.60	Small wash, drains SW.
79.87	The cor. of secs. 26, 27, 34 and 35.
	<p>Land, mountainous. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
	<p>N. 0° 24' E., bet. secs. 26 and 27.</p> <p>Over rolling land, through scattered undergrowth.</p>
7.70	Wash, 10 lks. wide, 4 ft. deep, drains SW.
16.10	Low ridge, bears NE. and SW.
22.80	Wash, 15 lks. wide, 1 ft. deep, drains W.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
29.30	Wash, 20 lks. wide, 2 ft. deep, drains S. 35° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone to top, with brass cap mkd. T7N R4W $\frac{1}{4}$ S 27 S 26 1957 Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
61.30	Low ridge, bears NE. and SW.
64.50	Small wash, drains SW.
70.90	Old road, bears NE. and SW.
80.00	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T7N R4W S 22 S 23 S 27 S 26 1957 Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor. Land, mountainous. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.
	From the cor. of secs. 23, 24, 25 and 26. N. 89° 58' W., bet. secs. 23 and 26. Over rolling land, through scattered undergrowth.
2.00	Small wash, drains S. 80° W.; desc. 100 ft. over W. slope.
10.00	Slope changes to SW.; desc. 60 ft.
32.60	Slope changes to SE.; asc. 40 ft.
39.86	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. T7N R4W $\frac{1}{4}$ S 23 S 26 1957 Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor. From above cor. point, U.S.L.M. No. 4110, bears N. 0° 49' W., 23.97 chs. dist.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
42.30	Old road, bears NE. and SW.; desc. 110 ft. over W. slope.
49.20	Wash, 15 lks. wide, 2 ft. deep, drains S. 20° W.; asc. 80 ft. over SE. slope.
68.30	Road, track, bears NE. and SW.
74.00	Dim track road, bears NE. and SW.
79.72	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
	N. 0° 08' E., bet. secs. 22 and 23.
	Over rolling land, through scattered undergrowth.
4.80	Small wash, drains S. 15° W.
33.50	Low flat ridge, bears NE. and SW.
37.90	Wash, 25 lks. wide, 2 ft. deep, drains SSW.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{8}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p>T7N R4W</p> <p>$\frac{1}{4}$</p> <p>S 22 S 23</p> <p>1957</p>
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
52.40	Wash, 10 lks. wide, 1 ft. deep, drains SW.
74.50	Wash, 40 lks. wide, 2 ft. deep, drains S. 20° W.
80.00	<p>The cor. of secs. 14, 15, 22 and 23, monumented by an iron post, set, mkd. and witnessed, as described in the official record.</p> <p>Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
	<p>From the cor. of secs. 33 and 34, and cor. No. 1 of Tract 37, on the S. bdy. of the Tp., monumented by an iron post, set, mkd., and witnessed, as described in the official record.</p>
	N. 0° 21' E., bet. secs. 33 and 34.
	Over rolling land, through scattered undergrowth.
	Asc. 70 ft. over SE. slope.
3.50	Fence, bears N. 70° E. and S. 70° W.
9.60	Spur, slopes SW.; desc. 30 ft. over NW. slope.

BOON

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
15.10	Wash, 10 lks. wide, 1 ft. deep, drains SW.; asc. 70 ft. over S. slope.
28.20	Fence, on low ridge, bears E. and W.; desc. 55 ft. over N. slope.
35.10	Wash, 25 lks. wide, 1 ft. deep, drains W.; asc. 60 ft. over S. slope.
39.33	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.
	T7N R4W $\frac{1}{4}$ S 33 S 34 1957
45.70	Small wash, drains S. 50° W.
60.50	Wash, 30 lks. wide, 6 ft. deep, drains S. 80° W.
69.00	Telephone line, bears NW. and SE.; asc. 60 ft. over S. slope.
78.66	The cor. of secs. 27, 28, 33 and 34, monumented by an iron post, set, mkd. and witnessed, as described in the official record. Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.
	From the cor. of secs. 26, 27, 34 and 35.
	S. $89^{\circ} 10'$ W., bet. secs. 27 and 34.
	Over rolling land, through scattered undergrowth.
8.80	Small wash, drains SW.
39.885	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate dist.; no remaining evidence of original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T7N R4W $\frac{1}{4}$ $\frac{S 27}{S 34}$ 1957
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Desc. 40 ft. over NW. slope.
49.40	Wash, 30 lks. wide, 10 ft. deep, drains SW.; asc. 40 ft. over SE. slope.
63.30	Spur, slopes SW.; desc. 55 ft. over NW. slope.
68.40	Small wash, drains SW.; asc. 65 ft. over SE. slope.
79.77	The cor. of secs. 27, 28, 33 and 34.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	<p>Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p>
	<p>S. 88° 40' W., bet. secs. 22 and 27.</p>
	<p>Over rolling land, through scattered undergrowth.</p>
2.70	<p>Small wash, drains S.; asc. 40 ft. over SE. slope.</p>
21.70	<p>Ridge, bears NE. and SW.; desc. 95 ft. over NW. slope.</p>
39.865	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate dist. no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T7N R4W $\frac{1}{4}$ S 22 S 27 1957</p>
	<p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.</p>
	<p>Desc. 70 ft. over rolling NW. slope.</p>
71.50	<p>Wash, 40 lks. wide, 3 ft. deep, drains S. 15° W.; asc. 70 ft. over SE. slope.</p>
79.73	<p>The cor. of secs. 21, 22, 27 and 28, monumented by an iron post, set, mkd. and witnessed, as described in the official record.</p>
	<p>Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
	<p>N. 0° 13' E., bet. secs. 21 and 22.</p>
	<p>Over rolling land, through scattered undergrowth.</p>
	<p>Asc. 30 ft. over SE. slope of low ridge.</p>
26.40	<p>Low flat ridge, bears NE. and SW.</p>
31.60	<p>Wash, 30 lks. wide, 2 ft. deep, drains SSW.; asc. 40 ft. over SE. slope.</p>
40.37	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate dist.; no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T7N R4W $\frac{1}{4}$ S 21 S 22 1957</p>

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

61.20 Low ridge, bears NE. and SW.

67.80 Small wash, drains SW.

80.74 The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, set, mkd. and witnessed, as described in the official record.

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented by an iron post, set, mkd. and witnessed, as described in the official record.

N. 0° 25' E., bet. secs. 32 and 33.

Over mountainous land, through scattered undergrowth.

Desc. 30 ft. over W. slope.

9.90 Slope changes to N.; desc. 80 ft.

14.90 Wash, 10 lks. wide, 2 ft. deep, drains E.; asc. 105 ft. over S. slope.

23.30 Spur, slopes E.; desc. 100 ft. over broken NE. slope.

39.69 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W
 $\frac{1}{4}$
 S 32 | S 33
 1957

Desc. 25 ft. over N. slope.

41.40 Wash, 20 lks. wide, 2 ft. deep, drains S. 70° E.; asc. 100 ft. over broken E. slope.

77.10 Spur, slopes E.; desc. 25 ft. over N. slope.

79.38 The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, set, mkd. and witnessed, as described in the official record.

Land, mountainous.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 20, 21, 28 and 29, monumented by an iron post, set, mkd. and witnessed, as described in the official record.

N. 0° 44' W., bet. secs. 20 and 21.

Over rolling land, through scattered undergrowth.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
	Asc. 70 ft. over SW. slope.
4.10	Telephone line, bears NW. and SE., and buried natural gas line bears NW. and SE.
5.00	Spur, slopes WSW.; desc. 90 ft. over N. slope.
11.00	Small wash, drains NW.; desc. 30 ft. over NW. slope.
16.30	Wash, 20 lks. wide, 4 ft. deep, drains SW.; asc. 115 ft. over S. slope.
25.00	Old road, bears W. and SE., on ridge bearing NE. and SW.; desc. 85 ft. over N. slope.
32.20	Wash, 30 lks. wide, 6 ft. deep, drains W.; asc. 110 ft. over SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid bedrock, in a mound of stone to top, with brass cap mkd. <div style="text-align: center;"> <p>T7N R4W</p> <p>$\frac{1}{4}$</p> <p>S 20 S 21</p> <p>1957</p> </div>
54.80	Low flat ridge, bears NE. and SW.
78.20	Wash, 30 lks. wide, 6 ft. deep, drains SW.
80.00	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T7N R4W</p> <p>S 17 S 16</p> <p>S 20 S 21</p> <p>1957</p> </div>
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, W. of cor. Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.
	From the cor. of secs. 15, 16, 21 and 22, monumented with an iron post, set, mkd. and witnessed, as described in the official record. S. $89^{\circ} 29'$ W., bet. secs. 16 and 21. Over rolling land, through scattered undergrowth.
10.90	Small wash, drains SW.
29.70	Small wash, drains SW.
39.905	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate dist.; no remaining evidence of the original cor.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T7N R4W
 $\frac{1}{4}$ S 16
 S 21
 1957

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

- 42.00 Wash, 30 lks. wide, 2 ft. deep, drains SW.; asc. over rolling SE. slope.
- 60.00 Low ridge, bears NE. and SW.
- 75.80 Wash, 20 lks. wide, 4 ft. deep, drains SW.
- 79.81 The cor. of secs. 16, 17, 20 and 21.

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

N. $0^{\circ} 02'$ E., bet. secs. 16 and 17.

Over rolling land, through scattered undergrowth.

- 8.35 Low spur, slopes SW.
- 14.10 Wash, 25 lks. wide, 2 ft. deep, drains SW.
- 34.50 Low ridge, bears NE. and SW.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W
 $\frac{1}{4}$
 S 17 | S 16
 1957

- 41.60 Wash, 10 lks. wide, 2 ft. deep, drains SW.
- 74.70 Flat ridge, bears NE. and SW.
- 79.80 Point selected for the witness cor. of secs. 8, 9, 16 and 17.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., over cross (X) cut in solid rock, in a mound of stone to top, with brass cap mkd.

T7N R4W
 W C
S 8 | S 9
 S 17 | S 16
 1957

- 80.00 True point for cor. of secs. 8, 9, 16 and 17, at proportionate dist., falls on steep W. slope of gully, impossible to monument.

Land, rolling.

Soil, rocky clay.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
	Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.
	From the cor. of secs. 9, 10, 15 and 16, monumented with an iron post, set, mkd. and witnessed, as described in the official record.
	S. 89° 40' W., bet. secs. 9 and 16.
	Over rolling land, through scattered undergrowth.
3.10	Wash, 50 lks. wide, 2 ft. deep, drains SW.
9.40	Fence, bears N. 15° W. and S. 15° E., 1 ch. to fence cor.
11.10	Wash, 20 lks. wide, 2 ft. deep, drains S.
34.20	Small wash, drains SW.
34.90	Small wash, drains SW.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate dist.; no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a mound of stone to top, with brass cap mkd.
	T7N R4W $\frac{1}{4}$ $\frac{S\ 9}{S\ 16}$ 1957
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
41.70	Small wash, drains SW.
71.40	Wash, 20 lks. wide, 2 ft. deep, drains N. 80° W. from ENE.
78.60	Same wash, drains W. from ENE.
80.06	True point for the cor. of secs. 8, 9, 16 and 17.
	Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.
	N. 0° 53' E., bet. secs. 8 and 9.
	Over rolling land, through scattered undergrowth.
.15	Wash, in gully 15 lks. wide, 20 ft. deep, drains S. 60° W.
4.40	Spur, slopes SW.
7.60	Wash, 20 lks. wide, 2 ft. deep, drains SW.
14.90	Small wash, drains SW.
21.10	Spur, slopes W.
34.60	Wash, 20 lks. wide, 6 ft. deep, drains SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7N R4W

$\frac{1}{4}$
S 8 | S 9
1957

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

52.50 Wash, 20 lks. wide, 6 ft. deep, drains SW.

58.00 Flat ridge, bears NE. and SW.

67.70 Wash, 30 lks. wide, 6 ft. deep, drains S. 65° W.

80.00 Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7N R4W

S 5 | S 4
S 8 | S 9
1957

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 3, 4, 9 and 10, monumented with an iron post, set, mkd. and witnessed as described in the official record.

S. $89^\circ 49'$ W., bet. secs. 4 and 9.

Over rolling land, through scattered undergrowth.

9.40 Wash, 30 lks. wide, 4 ft. deep, drains SW.

20.00 Low ridge, bears NE. and SW.

39.30 Wash, 1 ch. wide, 4 ft. deep, drains SW.

40.09 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground with brass cap mkd.

T7N R4W
 $\frac{1}{4}$ S 4
S 9
1957

from which

A mesquite, 8 ins. diam., bears S. 85° E., 80 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
46.20	Small wash, drains SW.
60.30	Spur, slopes S.
66.10	Wash, 10 lks. wide, 3 ft. deep, drains S.
69.30	Spur, slopes S.
73.80	Wash, 50 lks. wide, 6 ft. deep, drains SW.
80.18	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
35.00	<p>N. 0° 19' E., bet. secs. 4 and 5.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>Low flat ridge, bears NE. and SW.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R4W $\frac{1}{4}$ S 5 S 4 1957</p>
40.50	<p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p> <p>Wash, 50 lks. wide, 4 ft. deep, drains SW.</p>
60.50	Wash, 15 lks. wide, 6 ft. deep, drains SW.
80.22	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, set, mkd. and witnessed, as described in the official record.</p> <p>Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
29.70	<p>From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented by an iron post, set, mkd. and witnessed, as described in the official record.</p> <p>N. 0° 19' E., bet. secs. 31 and 32.</p> <p>Over mountainous land, through scattered undergrowth.</p> <p>Asc. 450 ft. over S. slope.</p> <p>Top of slope, on E. side of peak in ridge bearing E. and NW.; desc. 290 ft. over NE. slope.</p>

BOOK 4539

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

39.77

Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W
 $\frac{1}{4}$
 S 31 | S 32
 1957

Desc. 20 ft. over NE. slope.

41.20

Wash, 10 lks. wide, 1 ft. deep, drains N. 75° E.; asc. 125 ft. over rocky SE. slope.

51.00

Rocky spur, slopes NNE.; desc. 30 ft. over W. slope.

58.20

Spur, slopes NW.; desc. 260 ft. over NE. slope.

77.00

Wash, 20 lks. wide, 8 ft. deep, drains S. 80° E.; asc. 65 ft. over SE. slope.

79.54

Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W
 S 30 | S 29
 S 31 | S 32
 1957

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 28, 29, 32 and 33.

N. $89^{\circ} 55'$ W., bet. secs. 29 and 32.

Asc. 200 ft. over rocky, rolling NE. slope.

34.90

Spur, slopes N.; desc. 70 ft. over NW. slope.

39.91

Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W
 $\frac{1}{4}$ S 29
 S 32
 1957

43.90

Slope changes to N.; desc. 80 ft.

65.40

Wash, 25 lks. wide, 6 ft. deep, drains N. 70° E.; asc. 75 ft. over S. slope.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
79.82	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, mountainous. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
	<p>S. 89° 56' W., bet. secs. 30 and 31.</p> <p>Over mountainous land, through scattered undergrowth.</p> <p>Asc. 50 ft. over S. slope.</p>
10.30	Wash, 20 lks. wide, 1 ft. deep, drains SE.
21.20	Wash, 10 lks., 1 ft. deep, drains SE.; asc. 90 ft. over NE. slope.
26.70	Spur, slopes S. 70° E.; desc. 50 ft. over SW. slope.
36.70	Wash, 10 lks. wide, 5 ft. deep, drains S. 75° E.; asc. 30 ft. over NE. slope.
39.82	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R4W</p> <p>$\frac{1}{4}$ $\frac{S\ 30}{S\ 31}$</p> <p>1957</p> </div>
	Asc. 145 ft. over NE. slope.
47.50	Saddle, in ridge, bears S. and NW.; desc. 95 ft. over SW. slope.
59.80	Small wash, drains S.
67.30	Wash, 10 lks. wide, 2 ft. deep, drains S.; asc. 20 ft. over SE. slope.
79.79	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.</p> <p>Land, mountainous. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0° 50' E., bet. secs. 29 and 30.</p> <p>Over mountainous land, through scattered undergrowth.</p>
1.00	Top of E. edge of rocky knoll; desc. 50 ft. over E. slope.
11.40	Wash, 10 lks. wide, 1 ft. deep, drains SE.; asc. 110 ft. over S. slope of rocky spur.
20.40	Top of spur, slopes S. from NNW.; desc. 115 ft. over NE. slope.

BOOK 4000

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

39.77 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W
 $\frac{1}{4}$
 S 30 | S 29
 1957

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Desc. 40 ft. over N. slope.

46.40 Wash, 10 lks. wide, 6 ft. deep, drains E.; asc. 100 ft. over S. slope.

59.00 Ridge, bears E. and W.; desc. 125 ft. over N. slope.

69.50 Wash, 20 lks. wide, 4 ft. deep, drains NE.; asc. 65 ft. over SE. slope.

77.50 Spur, slopes E.; desc. 35 ft. over NE. slope.

79.54 Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W
 S 19 | S 20
 S 30 | S 29
 1957

Land, mountainous.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 20, 21, 28 and 29.

N. $89^{\circ} 39'$ W., bet. secs. 20 and 29.

Over rolling land, through scattered undergrowth.

Desc. 100 ft. over SW. slope.

4.80 U. S. Highway, Nos. 60, 70, and 89, bears NW. and SE.

5.40 Fence, bears NW. and SE.

8.90 Hassayampa River, 4 chs. wide, 4 ft. deep, drains S. 50° E.

16.00 Fence, bears NW. and SE.

22.90 Fence, bears S. 34° E. and N. 34° W.

23.50 Railroad track (spur or siding), bears S. 34° E. and N. 34° W.

23.75 A. T. and S. F. Railroad, bears S. 34° E. and N. 34° W.

24.40 Telephone line, parallel to railroad tracks.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
24.60	Fence, parallel to railroad tracks.; asc. 150 ft. over E. slope.
40.21	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T7N R4W</p> <p>$\frac{1}{4}$ $\frac{S\ 20}{S\ 29}$</p> <p>1957</p> </div>
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
41.00	Ridge, bears ENE. and SW.; desc. 60 ft. over W. slope.
48.30	Small wash, drains N.; asc. 130 ft. over rolling E. slope.
70.80	Hillside drain, course NE.
78.00	Ridge, bears NE. and SW.; desc. 20 ft. over NW. slope.
80.42	The cor. of secs. 19, 20, 29 and 30. Land, rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.
	S. 89° 58' W., bet. secs. 19 and 30. Over rolling land, through scattered undergrowth. Desc. 75 ft. over W. slope.
21.50	Wash, 10 lks. wide, 6 ft. deep, drains NE.; asc. 85 ft. over SE. slope.
26.50	Low spur, slopes ENE., thence over N. slope.
40.21	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate dist.; no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd. <div style="text-align: center;"> <p>T7N R4W</p> <p>$\frac{1}{4}$ $\frac{S\ 19}{S\ 30}$</p> <p>1957</p> </div>
	Asc. 30 ft. over E. slope.
47.10	Ridge, bears N. and S.; desc. 80 ft. over W. slope.
52.10	Wash, 10 lks. wide, 6 ft. deep, drains N. 15° E.; asc. 170 ft. over SE. slope.
70.10	Ridge, bears NE. and SW.; desc. 145 ft. over NW. slope.
80.67	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

Land, rolling.
Soil, rocky clay.
Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 19, 20, 29 and 30.

N. $0^{\circ} 14'$ W., bet. secs. 19 and 20.

Over rolling land, through scattered undergrowth.

Desc. 60 ft. over NE. slope.

7.80 Wash, 15 lks. wide, 6 ft. deep, drains N. 75° E.; asc. 50 ft. over SE. slope.

17.60 Spur, slopes E.; desc. 110 ft. over NE. slope.

27.20 Wash, 15 lks. wide, 2 ft. deep, drains E.; asc. 70 ft. over S. slope.

33.40 Road, track, bears E. and W.

35.20 Spur, slopes E.; desc. 90 ft. over N. slope.

39.77 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W
S 19 $\frac{1}{4}$ S 20
1957

40.00 Wash, 10 lks. wide, 1 ft. deep, drains E.; asc. 100 ft. over S. slope.

44.80 Spur, slopes E.; desc. 130 ft. over general N. slope.

62.00 Fence, bears NW. and SE.

62.90 A. T. and S. F. Railroad, bears NW. and SE.

63.70 Fence, bears NW. and SE.

73.50 Hassayampa River, 5 chs. wide, 4 ft. deep, drains SE.

78.50 Enter dense brush and scattered timber.

79.54 Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T7N R4W
S 18 | S 17
S 19 | S 20
1957

from which

A mesquite, 10 ins. diam., bears N. 40° E., 26 lks. dist., mkd. T7N R4W S17 BT.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

A mesquite, 8 ins. diam., bears N. 35° W., 41 lks. dist.,
mkd. T7N R4W S18 BT.

A mesquite, 6 ins. diam., bears S. 60° W., 33 lks. dist.,
mkd. T7N R4W S19 BT.

Land, rolling.
Soil, rocky clay.
Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 16, 17, 20 and 21.

West, bet. secs. 17 and 20.

Over rolling land, through scattered undergrowth.

Asc. 30 ft. over SE. slope.

3.40 Spur, slopes S.; desc. 70 ft. over W. slope.

7.60 Wash, 1 ch. wide, 4 ft. deep, drains S.; asc. 95 ft. over E. slope.

12.00 Spur, slopes S.; desc. 100 ft. over broken W. slope.

22.00 Fence, bears NE. and SW.

27.60 Fence, bears NW, and SE.

28.60 Wash, 30 lks. wide, 6 ft. deep, drains SW.; asc. 50 ft. over SE. slope.

39.00 Small wash, drains S.

39.965 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T7N R4W
 $\frac{1}{4}$ $\frac{S 17}{S 20}$
1957

Raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

Desc. 60 ft. over W. slope.

56.70 Telephone line, bears NW. and SE.

62.40 Fence, bears NW. and SE.

63.20 U. S. Highway, Nos. 60, 70, and 89, bears NW. and SE.

64.00 Fence, bears NW. and SE.

68.00 Enter dense undergrowth in river bottom.

79.93 The cor. of secs. 17, 18, 19 and 20.

Land, rolling.
Soil, rocky clay.
Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

Dép. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

N. 89° 49' W., bet. secs. 18 and 19.

Over rolling land, through scattered undergrowth.

4.00 Leave dense undergrowth; enter overflow bottom of Hassayampa River.

12.60 Main channel of Hassayampa River, 4 chs. wide, 4 ft. deep, drains SE.

15.00 Leave overflow bottom

18.80 Fence, bears NNW. and SE.

19.60 A. T. and S. F. Railroad, bears NNW. and SE.

20.20 Fence, bears NNW. and SE.; asc. 60 ft. over broken E. slope.

39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate dist.; no remaining evidence of the original cor.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W
 $\frac{1}{4}$ $\frac{S 18}{S 19}$
 1957

Asc. 40 ft. over NE. slope.

55.70 Low spur, slopes NE.; desc. 30 ft. over NW. slope.

61.70 Wash, 10 lks. wide, 2 ft. deep, drains NE.; asc. 75 ft. over NE. slope.

70.00 Top of ascent, on N. slope of large knoll; desc. 70 ft. over NW. slope.

80.10 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 17, 18, 19 and 20.

N. 0° 11' W., bet. secs. 17 and 18.

Over rolling land, through scattered undergrowth.

12.00 Leave dense undergrowth in river bottom; also, fence, bears NW. and SE.

15.00 Fence, bears NW. and SE.

16.00 U. S. Highway, Nos. 60, 70, and 89, bears NW. and SE.

17.00 Fence, bears NW. and SE.; asc. 100 ft. over broken S. slope.

37.50 Telephone line, bears NW. and SE.

39.77 The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented with a steel pin, set firmly in the ground in a mound of stone. This corner position has been accepted and used by the local land owners and local surveyors for over 25 years. It is accepted as the best available evidence of the position of the original corner.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R4W $\frac{1}{4}$ S 18 S 17 1957</p> <p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 11'$ E., beginning new measurement.</p> <p>Desc. 30 ft. over N. slope.</p> <p>2.80 Fence, bears E. and W.</p> <p>5.50 Wash, 20 lks. wide, 6 ft. deep, drains W.; asc. 80 ft. over S. slope.</p> <p>16.30 Low spur, slopes W.; desc. 50 ft. over W. slope.</p> <p>25.40 Wash, 10 lks. wide, 6 ft. deep, drains W.; asc. 65 ft. over broken W. slope.</p> <p>38.60 Spur, slopes W.</p> <p>40.08 Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7N R4W S 7 S 8 S 18 S 17 1957</p> <p>Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land, rolling. Soil, rocky clay. Timber, none, undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
	<p>From the true point for the cor. of secs. 8, 9, 16 and 17.</p> <p>S. $89^{\circ} 57'$ W., bet. secs. 8 and 17.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>6.30 Wash, 20 lks. wide, 1 ft. deep, drains S. 70° W.</p> <p>7.50 Spur, slopes S. 70° W.</p> <p>17.40 Wash, drains S. 70° W.</p> <p>25.60 Wash, 25 lks. wide, 2 ft. deep, drains SW.</p> <p>36.30 Low ridge, bears N. and S.</p> <p>40.055 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate dist.; no remaining evidence of the original cor.</p>

BOOK 4580

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 11 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W
 $\frac{1}{4}$ $\frac{S 8}{S 17}$
 1957

Asc. 30 ft. over SE. slope.

46.00 Spur, slopes S.; desc. 60 ft. over W. slope.

48.80 Wash, 30 lks. wide, 6 ft. deep, drains S.; asc. 135 ft. over E. slope.

55.60 Knoll, on line; desc. 155 ft. over W. slope.

64.30 Wash, 15 lks. wide, 6 ft. deep; drains NW. from NE.; asc. 80 ft. over SE. slope.

69.40 Top of slope, on S. side of knoll; desc. 30 ft. over S. slope.

76.00 Spur, slopes SW.; desc. 60 ft. over NW. slope.

80.11 The cor. of secs. 7, 8, 17 and 18.

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

S. $89^{\circ} 58'$ W., bet. secs. 7 and 18.

Over rolling land, through scattered undergrowth.

Desc. 50 ft. over NW. slope.

13.30 Wash, 30 lks. wide, 6 ft. deep, drains SW.; asc. 160 ft. over steep E. slope.

18.40 Spur, slopes S.; desc. 80 ft. over W. slope.

23.50 Telephone line, bears NW. and SE.

27.50 Ridge, bears N. and S.; desc. 90 ft. over W. slope.

29.90 Fence, bears N. 30° W. and S. 30° E.

33.30 U. S. Highway, Nos. 60, 70, and 89, bears N. 30° W. and S. 30° E.

34.20 Fence, bears N. 30° W. and S. 30° E.

39.10 Fence corner, with fences bearing S. 55° W. and NE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7N R4W
 $\frac{1}{4}$ $\frac{S 7}{S 18}$
 1957

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

from which

A mesquite, 10 ins. diam., bears S. 38° 30' E., 22 lks. dist., mkd. $\frac{1}{4}$ S18 BT.

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.

46.20 Enter Hassayampa River bottom.

53.00 Hassayampa River, 4 chs. wide, 3 ft. deep, drains SE.

65.00 Leave river bottom.

67.00 Fence, bears NW. and SE.

67.80 A. T. and S. F. Railroad, bears NW. and SE.

68.60 Fence, bears NW. and SE.

80.00 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 50' E., bet. secs. 7 and 8.

Over rolling land, through scattered undergrowth.

Desc. 40 ft. over NW. slope.

6.00 Wash, 30 lks. wide, 6 ft. deep, drains SW.

Asc. 65 ft. over SE. slope.

13.00 Low spur, slopes S. 25° W.; asc. 65 ft. over SW. slope of knoll.

23.30 Top of ascent, on W. side of knoll; desc. 35 ft. over N. slope.

35.80 Low ridge, bears NE. and SW.

40.08 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W

$\frac{1}{4}$
S 7 | S 8

1957

43.20 Wash, 20 lks. wide, 6 ft. deep, drains SW.

51.40 Small wash, drains SW.

59.00 Small wash, drains SW.

74.90 Low spur, slopes W.

80.16 Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; no remaining evidence of the original cor.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T7N R4W

S 6 | S 5

S 7 | S 8

1957

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

From the cor. of secs. 4, 5, 8 and 9.

West, bet. secs. 5 and 8.

Over rolling land, through scattered undergrowth.

5.60 Small wash, drains SW.

30.50 Wash, 50 lks. wide, 6 ft. deep, drains NW. from ESE.

33.10 Same wash, drains SW.

35.20 Low spur, slopes SW.

39.20 Wash, 1 ch. wide, 6 ft. deep, drains S.

40.05 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T7N R4W

 $\frac{1}{4}$ S 5

S 8

1957

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.

73.90 Low spur, slopes SW.

80.10 The cor. of secs. 5, 6, 7 and 8.

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

N. $89^{\circ} 49'$ W., bet. secs. 6 and 7.

Over high rolling land, through scattered undergrowth.

1.10 Small wash, drains S. 10° W.

5.00 Spur, slopes SW.; desc. 75 ft. over W. slope.

13.60 Wash, 1 ch. wide, 4 ft. deep, drains S. 35° W.; asc. 55 ft. over E. slope.

16.95 Spur, slopes SSW.; desc. 40 ft. over W. slope.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains	
18.85	Wash, 10 lks. wide, 6 ft. deep, drains S.; asc. 120 ft. over broken E. slope.
27.40	Rocky spur, slopes S.; desc. 50 ft. over W. slope.
30.40	Wash, 10 lks. wide, 6 ft. deep, drains S. 10° E.; asc. 100 ft. over E. slope.
37.80	Long spur, slopes S.; desc. 25 ft. over W. slope.
39.99	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a mound of stone to top, with brass cap mkd.</p>
	<p>T7N R4W</p> $\frac{1}{4} \frac{S 6}{S 7}$ <p>1957</p>
	Desc. 180 ft. over WNW. slope.
54.00	Wash, 15 lks. wide, 3 ft. deep, drains S. 20° W.; asc. 130 ft. over broken ESE. slope.
68.20	Ridge, bears N. and S.; desc. 150 ft. over W. slope.
79.92	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.</p> <p>Land, high and rolling. Soil, rocky clay. Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.</p>
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0° 28' E., bet. secs. 5 and 6.
	Over rolling land, through scattered undergrowth.
2.00	Wash, 20 lks. wide, 6 ft. deep, drains SW.
19.50	Wash, 2 chs. wide, 2 ft. deep, drains SW.
25.65	Rocky gully, drains S. 15° W.
34.20	Small wash, drains SW.
39.60	Small wash, drains SW.
40.08	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate dist.; no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p>T7N R4W</p> $\frac{1}{4} \frac{S 6}{S 5}$ <p>1957</p>
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
51.90	Road, graded, bears NE. and W.

Dep. Resurvey of a Portion of the Subdivision, T. 7 N., R. 4 W.

Chains

58.72 Small wash, drains W.

72.50 Low spur, slopes W.

78.60 Wash, 50 lks. wide, 2 ft. deep, drains SW.

80.26 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented by an iron post, set, mkd. and witnessed, as described in the official record.

Land, rolling.

Soil, rocky clay.

Timber, none; undergrowth, scattered greasewood, mesquite, palo verde, cacti, and sparse grass.

General Description

The major portion of this township is rolling, rocky ridges and spurs, with scattered to medium dense undergrowth of brush and very poor grass. There is some limited-scale farming along the banks of the Hassayampa River even though the river is dry most of the year.

There is some mining activity in the township. U. S. Highway Nos. 60, 70, and 89, bisects the SW. portion, and there are numerous roads leading from the highway out through the township. The major portion of the people living within the boundaries live along the Hassayampa River bottom. There is a natural gas line running parallel to the highway to serve the city of Wickenburg, Arizona, which is just west of the cor. of secs. 1, 6, 7 and 12, on the west bdy.

The A. T. and S. F. Railroad parallels the Hassayampa River through the township.

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 3rd day of October, 1955
I have ~~surveyed~~ resurveyed the west boundary and a portion of the subdivision of
Township 7 North, Range 4 West.

of the G. & S. R. Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Salt Lake City, Utah
July 26, 1957

Donald E. Harding
Donald E. Harding, Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., NOV 25 1957, 1957

The foregoing field notes of the ~~survey of~~ resurvey of the west boundary and a portion of
the subdivision of Township 7 North, Range 4 West.

executed by Donald E. Harding, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

Carl G. Harvinger
Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in _____
_____, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.