

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH BOUNDARY

AND

A PORTION OF THE SUBDIVISION

OF

TOWNSHIP 4 SOUTH, RANGE 14 EAST

Of the Gila and Salt River *Meridian,*

In the State of Arizona

EXECUTED BY

..... Horace G. Parker - Cadastral Surveyor

Under special instructions dated January 29 , 1958 , *which provided*
for the surveys included under Group No. 324 , *approved* January 29, 1958
and assignment instructions dated February 17 , 1958

Survey commenced February 21 , 19 58

Survey completed March 10 , 19 58

BOOK 4554

INDEX DIAGRAM

Township 4 South, Range 14 East

6	5	4	3	2	1
7	8	9	10	11	12
18	22 17	21 16	15	14	13
19	20	20 21	19 22	13 23	24
30	29	18 28	17 16 27	12 10 26	8 25
31	32	16 33 5	15 14 34 4	9 8 35 3	7 6 36 2

Township 4 South, Range 14 East

Chains

The south boundary of the township was surveyed by John L. Harris in 1878. Portions of the north, east and west boundaries and subdivisional lines were surveyed by John L. Harris in 1879. The south two miles of the east boundary were resurveyed by A. O. Stinson, and the north four miles were resurveyed by W. B. Kimmell, U.S. Cadastral Engineer, and A. O. Stinson in 1918. The subdivision of the township was completed by Dupree A. Averill and Roger F. Wilson in 1924, at which time they resurveyed the west 1 mile of the north boundary, the west 2½ miles of the south boundary, the north 4 miles of the east boundary and a portion of the subdivisional lines, as represented on the plat approved March 17, 1926.

The following field notes are those of a dependent resurvey of the east 3½ miles of the south boundary and a portion of the subdivisional lines, intended to complete the iron post monumentation of T. 4 S., R. 14 E. The resurvey was initiated upon the official request of the Range Manager in charge of Arizona Grazing Districts Nos. 2 and 3, to facilitate general administration.

Before restoring the corners, the lines of the original survey were retraced and diligent search made for any evidence of the original corners, bearing trees and other calls of the original field note record. When duly identified, the corner positions were remonumented with a standard iron post and a corner accessory or new bearing trees marked.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with the identified corner locations, but not until exhausting every reasonable possibility of finding direct evidence for the control of each particular corner.

The survey was executed with a W. and L. E. Gurley transit, serial No. 49657, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition, having been placed in proper adjustment prior to the beginning of the field work, and was maintained in precise adjustment throughout the progress of the survey.

The directions of all lines herein reported were determined by sustained angulation carried forward from meridians established by observations upon the sun, throughout the survey.

The measurements were made with a narrow steel tape, 8 chains in length, graduated to tenths of a link for the first link, to links for the next 99 lks., and thereafter at intervals of 10 links. The tape was tested by comparison with a standard steel tape, 1 chain in length, and found to be correct. The measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustment. The slope distances were properly reduced to horizontal equivalents, which are entered in this field note record. All lengths of lines were determined by chaining where possible, otherwise by triangulation or traverse. The details of such traverses or triangulations have been thoroughly verified and in order to simplify the record, the diagrams and reductions are omitted from these field notes.

The geographic position of the southeast corner of the township is latitude 33° 01' 56" N. and longitude 110° 51' 40" W., as determined by scaling on U. S. Geological Survey sheet Arizona "Ray" quadrangle.

The magnetic declination was read at a number of stations throughout the township, and the average of the several readings was found to be 14° 30' E.

BOOK 4554

Dependent Resurvey of a Portion of the S. Bdy., T. 4 S., R. 14 E.

Chains

Reestablishment of the survey executed by J. L. Harris in 1878.

From the cor. of Ts. 4 and 5 S., Rs. 14 and 15 E.; which is monumented with an iron post, 3 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

S. 89° 27' W., bet. secs. 1 and 36.

Over rolling land, through scattered timber and heavy undergrowth.

Desc. 29 ft. over W. slope.

5.40 Wash, 3 chs. wide, 15 ft. deep, drains S. 30° W.; asc. 50 ft. over E. slope.

16.60 Top of spur, slopes S.; desc. 162 ft. over W. slope.

23.85 Wash, 50 lks. wide, 6 ft. deep, drains S. 20° W.; asc. 30 ft. over E. slope.

31.15 Top of spur, slopes S.; desc. 89 ft. over W. slope.

39.20 Wash, 30 lks. wide, 10 ft. deep, drains S.

39.95 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T4S R14E
 $\frac{1}{4}$ $\frac{S36}{S1}$
 T5S
 1958

Continue over heavily rolling land.

42.60 Wash, 3 chs. wide, 3 ft. deep, drains S. 20° W.; asc. 66 ft. over E. slope.

48.00 Wash, 40 lks. wide, 15 ft. deep, drains S. 70° E.

55.40 Wash, 30 lks. wide, 3 ft. deep, drains SE.; asc. 28 ft. over E. slope.

57.80 Top of spur, slopes S.; unimproved road bears N. and S.; desc. 177 ft. over W. slope along top of spur, slopes WNW.

79.50 Road, improved, on curve, bears NE. and SE.

79.90 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T4S R14E
 $\frac{S35}{S2} | \frac{S36}{S1}$
 T5S
 1958

from which

A pole, 12 ins. diam., in power line, bears S. 66° 39' E., 514 lks. dist.

The SE. cor. of a concrete building, bears N. 75° 50' W., 278 lks. dist.

A telephone pole, 10 ins. diam., bears N. 20° 07' W., 51 lks. dist.

BOOK 485

Dependent Resurvey of a Portion of the S. Bdy., T. 4 S., R. 14 E.

Chains

Land, heavily rolling.
Soil, sandy and gravelly loam.
Timber, pinon, juniper and mesquite.
Undergrowth, cacti, yucca, creosote bush and sagebrush.

S. 89° 27' W., bet. secs. 2 and 35.

Over nearly level land; desc. 90 ft. over gradual W. slope.

- 3.20 Ranch house, bears N., 2 chs. dist.
- 4.00 Fence, bears N. 20° W. and S. 20° E.
- 4.80 Arizona State Highway No. 177, under construction, bears N. 20° W. to Ray, Arizona and S. 20° E. to Winkelman, Arizona.
- 5.80 Fence, bears N. 20° W. and S. 20° E.
- 6.20 Power line, bears N. 20° W. and S. 20° E.
- 8.26 Arizona Eastern Railroad, bears N. 20° W. and S. 20° E.
- 9.00 Unimproved road, bears S. and ENE.
- 9.20 Fence, bears N. 20° W. and W.
- 10.50 Right bank of the Gila River, bears NNW. and SSE.
- 11.10 Main channel of the Gila River, flows NW.
- 11.80 Left bank of the Gila River, bears NNW. and SSE.; enter heavy undergrowth and timber.
- 24.80 Leave heavy timber and undergrowth, edge bears NW. and SW.; continue through open land and scattered undergrowth.
- 39.95 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T4S R14E
 $\frac{1}{4}$ $\frac{S35}{S 2}$
T5S
1958
- Deposit broken glass around the iron post, 12 ins. below the surface of the ground.
- 42.00 Enter heavy timber and undergrowth; edge bears N. and S.
- 46.70 Fence, 4 strand barbed wire, bears NW. and S. 20° E.; leave timber, edge bears NW. and S. 20° E.
- 50.75 Enter heavy timber and undergrowth, edge bears N. and S.
- 74.33 Fence, 3 strand barbed wire, bears S. 20° E. and N. 30° W.
- 74.68 Unimproved road, bears S. 20° E. and N. 30° W.; asc. 40 ft. over E. slope.
- 76.20 Top of spur, slopes NE.; desc. 30 ft. over W. slope.
- 79.88 Wash, 15 lks. wide, 4 ft. deep, drains N. 60° E.

Dependent Resurvey of a Portion of the S. Bdy., T. 4 S., R. 14 E.

Chains	
79.90	<p>The cor. of secs. 2, 3, 34 and 35, which is monumented with a squared mesquite post, firmly set in the ground, and in a mound of stone, mkd. and witnessed as described in the official record.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R14E</p> <p>S34 S35</p> <p>S 3 S 2</p> <p>T5S</p> <p>1958</p> </div> <p>Reset the original corner post alongside the iron post, and raise a mound of stone, 4 ft. base, 2½ ft. high, W. of cor.</p> <p>Land, nearly level. Soil, sandy loam. Timber, mesquite, Undergrowth, cacti and sagebrush.</p>
	<p>N. 89° 58' W., bet. secs. 3 and 34.</p>
	<p>Over gently rolling land, through scattered timber and heavy undergrowth.</p>
4.50	<p>Top of low spur, slopes N.; desc. 60 ft. over W. slope.</p>
38.60	<p>Wash, 30 lks. wide, 4 ft. deep, drains NE.</p>
39.58	<p>The ¼ sec. cor. of secs. 3 and 34, which is monumented with an unmarked stone, firmly set in a mound of earth and stone. This is the position of the ¼ sec. cor. according to residents who stated it had been used as the position of the ¼ sec. cor. for years, and it is accepted as the best available evidence for the position of the original cor.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T4S R14E</p> <p>¼ <u>S34</u></p> <p>S 3</p> <p>T5S</p> <p>1958</p> </div>
	<p>Reset the unmarked stone alongside the iron post, and raise a mound of stone, 4 ft. base, 2½ ft. high, N. of cor.</p>
	<hr style="width: 20%; margin: auto;"/>
	<p>S. 89° 19' W., beginning new measurement.</p>
	<p>Continue over rolling land, through heavy timber and undergrowth.</p>
4.50	<p>Wash, 30 lks. wide, 3 ft. deep, drains NE.; asc. 58 ft. over SE. slope.</p>
7.60	<p>Top of spur, slopes N.; desc. 21 ft. over W. slope.</p>
14.20	<p>Wash, 40 lks. wide, 5 ft. deep, drains N. 55° E.; asc. 73 ft. over SE. slope.</p>
28.32	<p>Top of spur, slopes N. 60° E.; desc. 20 ft. over W. slope.</p>

Dependent Resurvey of a Portion of the S. Bdy., T. 4 S., R. 14 E.

Chains											
34.62	Wash, 20 lks. wide, 4 ft. deep, drains N. 60° E.; asc. 12 ft. over E. slope.										
40.00	Top of spur, slopes NE.										
40.43	Fence, 4 strand barbed wire, bears N. and S.										
40.44	The cor. of secs. 3, 4, 33 and 34, which is monumented with the remains of a squared mesquite post, firmly set in a mound of earth and stone, mkd. and witnessed as described in the official record. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd. <table style="margin-left: auto; margin-right: auto;"> <tr><td>T4S</td><td>R14E</td></tr> <tr><td>S33</td><td>S34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>T5S</td><td></td></tr> <tr><td>1958</td><td></td></tr> </table> Reset the remains of the squared mesquite post alongside the iron post, and raise a mound of stone, 4 ft. base, 2½ ft. high, W. of cor. Land, gently rolling. Soil, sandy and gravelly loam. Timber, mesquite and juniper. Undergrowth, cacti, creosote bush, ocotillo, Joshua tree, yucca and sagebrush.	T4S	R14E	S33	S34	S 4	S 3	T5S		1958	
T4S	R14E										
S33	S34										
S 4	S 3										
T5S											
1958											
	S. 89° 44' W., bet. secs. 4 and 33. Over rolling land, through scattered timber and heavy undergrowth. Desc. 30 ft. over W. slope.										
3.90	Wash, 25 lks. wide, 5 ft. deep, drains N. 65° E.; asc. 29 ft. over E. slope.										
9.20	Spur, slopes N.; desc. 30 ft. over W. slope.										
19.10	Wash, 40 lks. wide, 10 ft. deep, drains NE.; asc. 20 ft. over E. slope.										
20.37	Top of spur, slopes NE.; desc. 30 ft. over W. slope.										
23.27	Wash, 80 lks. wide, 4 ft. deep, drains N. 50° E.; asc. 30 ft. over E. slope.										
26.66	Unimproved road, bears N. 50° E. and S. 70° W.										
29.36	Top of spur, slopes N. 50° E.										
36.06	Wash, 150 lks. wide, 4 ft. deep, drains N. 65° E.; asc. 40 ft. over E. slope.										
40.10	The ¼ sec. cor. of secs. 4 and 33, which is monumented with an iron post, 1 in. diam., firmly set in the ground, mkd. and witnessed as described in the official record. Land, gently rolling. Soil, sandy and gravelly loam. Timber, mesquite and juniper. Undergrowth, cacti, creosote bush, ocotillo, yucca and sagebrush.										

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	Description
	Reestablishment of the survey executed by J. L. Harris in 1879. From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the township. N. 0° 04' E., bet. secs. 35 and 36. Over nearly level land, through scattered undergrowth.
1.89	Wash, 50 lks. wide, 3 ft. deep, drains W.
6.69	S. side of board corral, bears E. and W.
10.45	N. side of board corral, bears E. and W.
17.35	Fence, 4 strand barbed wire, bears N. 30° E. and S. 30° W.
18.45	Irrigation ditch, 3 ft. wide, bears NNE. and SSW.
19.65	Fence, 4 strand barbed wire, bears N. 30° E. and S. 30° W.
21.75	Irrigation ditch, 3 ft. wide, bears E. and W.
36.55	Fence, 3 strand barbed, bears N. 70° E. and S. 70° W.
37.15	Irrigation ditch, 3 ft. wide, bears S. 60° E. and N. 60° W.
37.75	Fence, 4 strand barbed wire, bears S. 70° E. and N. 70° W.
39.09	Woven wire fence, bears E. and W.
39.83	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate dist., there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T4S R14E $\frac{1}{4}$ S35 S36 1958 </div> from which A mesquite, 8 ins. diam., bears N. 53° E., 69 lks. dist., mkd. BT. A mesquite, 6 ins. diam., bears S. 72° 30' E., 55 lks. dist., mkd. BT. Continue over level land, along W. side of N. and S. fence, E. edge of field.
46.25	Enter heavy timber and undergrowth, bears NW. and SE.
49.44	Fence, 3 strand barbed wire, bears S. 70° E. and N. 70° W.
60.00	Begin ascent, asc. 27 ft. over gradual S. slope.
67.65	Fence line, bears N. 80° W. and S. 30° E.; leave heavy timber and undergrowth; asc. 152 ft. over SSE. slope.
68.38	Graded road, bears S. 80° E. and N. 80° W.
79.66	The cor. of secs. 25, 26, 35 and 36, which is monumented with a squared mesquite post, firmly set in the ground, and in a mound of stone, mkd. and witnessed as described in the official record. At the corner point

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4S R14E	
S26	S25
S35	S36
1958	

Reset the squared mesquite stake alongside the iron post, and raise a mound of stone, 4 ft. base, 2½ ft. high, W. of cor.

Land, nearly level.

Soil, sandy loam.

Timber, mesquite,

Undergrowth, sagebrush and cacti.

From the cor. of secs. 25 and 36 on the E. bdy. of the township, which is monumented with an iron post, 3 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

N. 89° 42' W., bet. secs. 25 and 36.

Over heavy rolling land, through scattered timber and undergrowth.

Desc. 154 ft. over NW. slope.

17.60 Wash, 70 lks. wide, 10 ft. deep, drains S. 35° W.; asc. 80 ft. over E. slope.

37.50 Top of spur, bears S. 10° W.; desc. 32 ft. over W. slope.

37.60 Road, bears N. 10° E. and S. 10° W.

39.98 Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T4S R14E	
¼	S25
	S36
1958	

from which

A paloverde, 3 ins. diam., bears N. 88° W., 26 lks. dist., mkd. BT.

No other suitable bearing trees available.

Continue over heavily rolling land, through scattered timber; desc. 110 ft. over W. slope.

56.30 Wash, 30 lks. wide, 4 ft. deep, drains S. 30° W.; asc. 142 ft. over E. slope.

58.30 Top of spur, slopes S. 15° W.; desc. 30 ft. over an abrupt W. slope.

63.90 Wash, 70 lks. wide, 5 ft. deep, drains S. 10° W.; asc. 78 ft. over SE. slope.

67.40 Top of spur, slopes S. 10° W.; desc. 105 ft. over W. slope.

71.80 Wash, 40 lks. wide, 3 ft. deep, drains S. 10° W.; asc. 120 ft. over E. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains

79.96

The cor. of secs. 25, 26, 35 and 36.

Land, heavily rolling.

Soil, sandy and gravelly loam.

Timber, paloverde, mesquite and juniper.

Undergrowth, cacti, creosote bush and sagebrush.

N. 0° 55' E., bet. secs. 25 and 26.

Over heavily rolling land, through medium heavy undergrowth.

Asc. 152 ft. over SE. slope, along top of spur, sloping SSE.

19.54

Top of round knoll in spur, sloping SSE.; desc. 155 ft. over NNW. slope.

31.18

Wash, 100 lks. wide, 10 ft. deep, drains S. 70° W.; continue descent, desc. 27 ft, over NW. slope.

36.47

Top of spur, slopes W.; desc. 15 ft. over NW. slope.

40.04

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T4S R14E

 $\frac{1}{4}$

S26 | S25

1958

Continue over heavily rolling land, through scattered timber and undergrowth.

45.90

Wash, 100 lks. wide, 5 ft. deep, drains SW.; asc. 98 ft. over SE. slope.

64.60

Top of spur, slopes SW.; desc. 34 ft. over NW. slope.

75.30

Wash, 90 lks. wide, 4 ft. deep, drains SW.; asc. 30 ft. over gradual SSE. slope to cor.

80.08

The cor. of secs. 23, 24, 25 and 26, erroneously mkd. for secs. 13, 14, 23 and 24, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record. I remark this cor. for secs. 23, 24, 25 and 26.

Land, heavily rolling.

Soil, sandy and gravelly loam.

Timber, pinon and juniper.

Undergrowth, cacti, yucca, ocotillo and sagebrush.

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township.

N. 0° 17' E., bet. secs. 34 and 35.

Over gently rolling land, through medium heavy timber and heavy undergrowth.

Asc. 25 ft. over S. slope.

5.08

Unimproved road, bears N. 70° W. and S. 30° E.

16.18

Wash, 20 lks. wide, 3 ft. deep, drains N. 70° E.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
24.60	Top of low spur, slopes N. 50° E.
39.07	Unimproved road, bears N. 20° E. and S. 40° W.
39.91	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T4S R14E $\frac{1}{4}$ S34 S35 1958</p>
	Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
	Continue over nearly level land, through scattered timber.
40.06	Fence, 4 strand barbed wire, bears W. and E., 30 lks., thence NNW. and SSE.
43.20	Fence, 3 strand barbed wire, bears NNW. and SSE.
47.40	Old abandoned farm house, bears E., 130 chs. dist.
52.05	Well, with pump, bears E., 9.10 chs. dist.
54.10	Fence, 4 strand barbed wire, bears W. and E., 15 lks., thence NNE. and SSE.
56.15	Fence, 3 strand barbed wire, bears E. and W.
60.25	Fence, 4 strand barbed wire, bears W. and E., 25 lks. dist., thence S.
71.05	Left bank of Gila River on bend, bears N. 15° W. and S. 30° E.
73.55	Left bank of Gila River, bears N. 30° E. and S. 30° W.
79.82	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist. there is no remaining evidence of the original cor.</p> <p>The point for the cor. falls on a low, gravelly sand bar near the left bank of the Gila River. This point is deemed unsafe for the cor. and it is not monumented.</p> <p>Land, gently rolling and nearly level. Soil, sandy loam. Timber, paloverde, mesquite and juniper. Undergrowth, cacti, sagebrush and ocotillo.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89° 31' W., bet. secs. 26 and 35.</p> <p>Over rolling land, through scattered timber.</p> <p>Desc. 211 ft. over WSW. slope.</p>
8.70	Wash, 20 lks. wide, 3 ft. deep, drains SW.
19.50	Graded, graveled road, bears N. 70° W. and S. 30° E.; continue over nearly level land.
19.90	Fence, 3 strand barbed wire, bears N. 70° W. and S. 30° E.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
33.00	House and highway maintenance sheds, bears S., 2 chs. dist.
35.00	Enter heavy timber and undergrowth; continue along inside of fence.
39.83	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T4S R14E $\frac{1}{4}$ $\frac{S26}{S35}$ 1958
	from which
	A mesquite, 4 ins. diam., bears N., 10 lks. dist., mkd. BT.
	A mesquite, 4 ins. diam., bears S. 30° E., 125 lks. dist., mkd. BT.
	Continue over heavy timber and undergrowth.
55.00	Fence, 4 strand barbed wire, bears NW. and SE.
56.00	Arizona State Highway No. 177, under construction, bears N. 45° W. to Ray, Arizona, and S. 45° E. to Winkelman, Arizona.
56.96	Fence, 4 strand barbed wire, bears NW. and SE.
58.00	Arizona Eastern Railroad, bears N. 45° W. and S. 45° E.
59.00	Fence, 4 strand barbed wire, bears NW. and SE.
59.20	Power line, bears NW. and SE.
62.00	Wash, 30 lks. wide, 3 ft. deep, drains SW.
62.30	Old graded road, bears NW. and SE.
77.60	Right bank of Gila River, bears S. 30° E. and WNW.
79.25	Left bank of Gila River, bears NW. and SE.
79.66	The true point for the cor. of secs. 26, 27, 34 and 35, not monumented. Land, nearly level. Soil, sandy and gravelly loam. Timber, mesquite and paloverde. Undergrowth, sagebrush, cacti and yucca.
	From the true point for the cor. of secs. 26, 27, 34 and 35, N. $0^{\circ} 24'$ W., bet. secs. 26 and 27.
.40	Left bank of the Gila River, bears WSW. and ENE.
1.40	Main channel of the Gila River, flows WSW.
2.90	Right bank of the Gila River, bears WSW. and ENE.; continue over nearly level land, through scattered timber and undergrowth.
3.55	Point selected for the witness cor. of secs. 26, 27, 34 and 35: Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
	T4S R14E S27 S26 S34 S35 W C 1958
	from which
	A mesquite, 6 ins. diam., bears N. 30° E., 41 lks. dist., mkd. WC BT.
	A mesquite, 6 ins. diam., bears N. 30° W., 33 lks. dist., mkd. WC BT.
5.50	Road, bears E. and W.
6.53	Fence, 4 strand barbed wire, bears N. 82° 10' E. and S. 82° 10' W.
7.38	Arizona Eastern Railroad, bears N. 82° 10' E. and S. 82° 10' W.
8.00	Telephone line, bears N. 82° 10' E. and S. 82° 10' W.
8.24	Fence, 4 strand barbed wire, bears N. 82° 10' E. and S. 82° 10' W.
9.34	Graded road, bears N. 82° 10' E. to Winkelman, Arizona, and S. 82° 10' W. to Ray, Arizona.
11.64	Power line, bears N. 40° W. and S. 40° E.
19.63	Arizona State Highway No. 177, under construction, bears N. 47° W. and S. 47° E.
21.34	Power line, bears N. 40° W. and S. 40° E.
23.13	NW. cor. of old corral and shed, bears E., 30 lks. dist.; begin ascent, asc. 145 ft. over SSW. slope, along W. side of spur.
39.22	Top of spur, slopes SW.
39.91	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.
	T4S R14E $\frac{1}{4}$ S27 S26 1958
	Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
	Continue over rolling land, through heavy timber and undergrowth.
	Desc. 40 ft. over N. slope.
41.30	Power line, bears N. 70° W. and S. 70° E.
42.70	Wash, 25 lks. wide, 4 ft. deep, drains S. 65° W.; asc. 18 ft. over S. slope.
49.58	Top of spur, slopes SW.; desc. 30 ft. over NW. slope.
54.70	Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. 34 ft. over S. slope.
65.04	Top of spur, slopes S. 40° W.; desc. 44 ft. over N. slope.
70.74	Wash, 30 lks. wide, 4 ft. deep, drains S. 60° W.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
73.42	Wash, 20 lks. wide, 4 ft. deep, drains WSW.; asc. 15 ft. over S. slope.
79.82	<p>The cor. of secs. 22, 23, 26 and 27, which is monumented with an unmarked stone, firmly set in the ground, and in a mound of earth and stone, with a 1 in. iron pipe, firmly set alongside. This is the position of the sec. cor. according to residents, who stated it had used as the position for the sec. cor. for years, and it is accepted as the best available evidence for the position of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R14E S22 S23 S27 S26 1958</p> </div> <p>Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of cor.</p> <p>Land, heavily rolling. Soil, sandy and gravelly clay loam. Timber, pinon, pine, paloverde and juniper. Undergrowth, cacti, yucca, mountain oak and sagebrush.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89° 28' W., bet. secs. 23 and 26.</p> <p>Over heavily rolling land, through medium heavy timber and undergrowth.</p> <p>Asc. 15 ft. over SE. slope.</p>
3.25	Top of spur, slopes SSW.; desc. 80 ft. over SW. slope.
10.33	Wash, 30 lks. wide, 6 ft. deep, drains S. 30° W.; asc. 19 ft. over E. slope.
14.92	Top of spur, slopes S.; desc. 26 ft. over SW. slope.
25.30	Wash, 25 lks. wide, 5 ft. deep, drains S.; asc. 60 ft. over E. slope.
33.80	Road, bears N. 20° E. and S. 20° W., on top of low spur, slopes SSW.; desc. 20 ft. over gradual W. slope.
37.18	Wash, 35 lks. wide, 10 ft. deep, drains SSW.; asc. 30 ft. over ESE. slope.
40.63	<p>Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R14E ¼ S23 S26 1958</p> </div> <p>Raise a mound of stone, 4 ft. base, 2½ ft. high, N. of cor.</p> <p>Continue over nearly level land, through scattered timber and heavy undergrowth.</p>
42.00	Top of low, flat spur, slopes S.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
47.94	Wash, 25 lks. wide, 1 ft. deep, drains S. 30° W.; asc. 15 ft. over ESE. slope.
51.00	Top of spur, slopes S. 30° W.; desc. 25 ft. over W. slope.
54.74	Wash, 30 lks. wide, 3 ft. deep, drains S. 30° W.; asc. 40 ft. over SE. slope.
59.00	Top of spur, slopes S. 40° W.; desc. 76 ft. over SW. slope.
71.68	Wash, 30 lks. wide, 5 ft. deep, drains S. 30° W.; asc. 65 ft. over E. slope.
81.26	The cor. of secs. 22, 23, 26 and 27. Land, E. $\frac{1}{2}$ heavily rolling, W. $\frac{1}{2}$ nearly level. Soil, sandy and gravelly loam. Timber, pine, pinon, paloverde and juniper. Undergrowth, cacti, yucca, mountain oak and sagebrush.
	N. 1° 15' E., bet. secs. 22 and 23. Over gently rolling land, through medium heavy timber and undergrowth.
2.10	Road, bears N. 55° E. and S. 55° W.
5.30	Begin descent, desc. 37 ft. over N. slope.
12.00	Wash, 1 ch. wide, 3 ft. deep, drains S. 50° W.
24.40	Top of spur, bears S. 30° W.; desc. 25 ft. over N. slope.
28.40	Wash, 30 lks. wide, 3 ft. deep, drains SW.; asc. 64 ft. over SW. slope.
39.70	Top of spur, slopes SW.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T4S R14E $\frac{1}{4}$ S22 S23 1958
	from which A paloverde, 6 ins. diam., bears S. 74° 30' E., 88 lks. dist., mkd. $\frac{1}{4}$ S23 BT. A paloverde, 6 ins. diam., bears S. 62° W., 52 lks. dist., mkd. $\frac{1}{4}$ S22 BT. Raise a mound of stone, 4 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.
43.90	Wash, 30 lks. wide, 4 ft. deep, drains SW.; asc. 26 ft. over S. slope.
52.60	Top of spur, slopes SW.; continue along NW. slope.
67.40	Wash, 50 lks. wide, 4 ft. deep, drains S. 15° W.; asc. 50 ft. over S. slope.
79.98	The cor. of secs. 14, 15, 22 and 23, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

Dependent Resurvey of a portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
	Land, gently rolling. Soil, sandy and gravelly loam. Timber, paloverde, mesquite and juniper. Undergrowth, creosote bush, cacti, yucca and sagebrush.
	From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township N. 0° 25' E., bet. secs. 33 and 34. Over rolling land, through scattered timber and medium heavy under- growth; along E. side of wire fence. Desc. 97 ft. over N. slope.
10.00	Wash, 25 lks. wide, 5 ft. deep, drains NE.; asc. 20 ft. over S. slope.
12.00	Top of spur, slopes NE.; desc. 30 ft. over N. slope.
18.95	Wash, 20 lks. wide, 2 ft. deep, drains N. 70° E.
23.74	Continue descent, desc. 20 ft. over NE. slope.
28.64	Wash, 25 lks. wide, 6 ft. deep, drains NE.; asc. 17 ft. over ESE. slope.
33.50	Top of spur, slopes E.; road bears E. and W.
40.28	The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, which is monumented with the remains of a squared mesquite post, firmly set in the ground, and in a mound of stone alongside a 1 in. iron pipe, mkd. and witnessed as described in the official record. At the corner point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd. T4S R14E $\frac{1}{4}$ S33 S34 1958 Reset the remains of the squared mesquite post and the 1 in. iron pipe alongside the iron post. <hr/> N. 0° 25' E., beginning new measurement. Continue over rolling land, along wire fence; desc. 20 ft. over N. slope.
1.70	Wash, 20 lks. wide, 4 ft. deep, drains N. 40° E.
6.30	Top of spur, slopes N. 30° E.; desc. 120 ft. over NNE. slope.
28.00	Left bank of Gila River, bears WNW. and ESE.
31.00	Main channel of Gila River, flows WNW.
33.80	Right bank of Gila River, bears WNW. and ESE.; enter dense timber and undergrowth, continue along W. side of fence.
40.25	The cor. of secs. 27, 28, 33 and 34, which is monumented with a squared mesquite post, firmly set in the ground, mkd. and witnessed as described in the official record. The cor. post is set alongside a cor. fence post, fence bears S. and W.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4S R14E
 S28 | S27
 S33 | S34
 1958

from which

A mesquite, 8 ins. diam., bears N. 62° 15' E., 183 lks. dist., mkd. T4S R14E S27 BT.

A mesquite, 10 ins. diam., bears S. 74° 50' E., 47 lks. dist., mkd. T4S R14E S34 BT.

A mesquite, 8 ins. diam., bears S. 71° 45' W., 154 lks. dist., mkd. T4S R14E S33 BT.

A mesquite, 6 ins. diam., bears N. 74° 25' W., 151 lks. dist., mkd. T4S R14E S28 BT.

Reset the squared mesquite post alongside the iron post.

Land, S. ½ gently rolling, N. ½ nearly level.

Soil, sandy and gravelly loam.

Timber, mesquite and paloverde.

Undergrowth, cacti, yucca and sagebrush.

From the true point for the cor. of secs. 26, 27, 34 and 35.

N. 89° 50' W., bet. secs. 27 and 34.

.80 Left bank of Gila River, bears WSW. and ENE.

5.30 Right bank of Gila River, bears WSW. and ENE.; enter heavy timber and undergrowth, continue over nearly level land.

28.60 Wash, 2 chs. wide, 4 ft. deep, drains S. 30° E.

34.40 Fence, 3 strand barbed wire, bears N. and S.

39.91 Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T4S R14E
 S27
 ¼ S34
 1958

Raise a mound of stone, 4 ft. base, 2½ ft. high, N. of cor.

41.46 Fence, bears S. and N., 15 lks., thence W.

42.80 Ranch house, abandoned, bears S., 130 lks. dist.

79.83 The cor. of secs. 27, 28, 33 and 34.

Land, nearly level.

Soil, sandy and gravelly loam.

Timber, mesquite and paloverde.

Undergrowth, creosote bush, cacti, yucca and sagebrush.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
	S. 89° 00' W., bet. secs. 28 and 33.
	Continue over level land, through heavy timber and undergrowth; along N. side of fence.
17.20	Right bank of Gila River, bears NNW. and SSE.
17.70	Main channel of the Gila River, flows NNW.
18.80	Left bank of Gila River, bears NNW. and SSE.; continue through heavy timber and undergrowth.
34.00	Road, bears N. 15° W. and S. 15° E.
36.40	Fence, bears N. 20° W. and S. 20° E.
37.30	Fence, bears S. 70° W. and N. 70° E.
39.16	Road, bears N. and S.
39.88	Fence, 4 strand barbed wire, bears N. and S.
40.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at porportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T4S R14E $\frac{1}{4}$ $\frac{S28}{S33}$ 1958
	from which
	A mesquite, 6 ins. diam., bears N. 76° 30' E., 107 lks. dist., mkd. $\frac{1}{4}$ S28 BT.
	A mesquite, 8 ins. diam., bears S. 12° E., 120 lks. dist., mkd. $\frac{1}{4}$ S33 BT.
	Continue over gently rolling land, through heavy timber.
50.00	Road, bears S. 40° E. and N. 21° W.
58.00	Ditch, 60 lks. wide, 8 ft. deep, bears S. 70° E. and N. 70° W.
61.00	Begin ascent, asc. 65 ft. over E. slope.
73.40	Top of spur, slopes NE.
80.13	The cor. of secs. 28, 29, 32 and 33, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.
	Land, E. $\frac{1}{2}$ nearly level, W. $\frac{1}{2}$ gently rolling. Soil, sandy and gravelly loam. Timber, mesquite and paloverde. Undergrowth, creosote bush, cacti, yucca and sagebrush.
	From the cor. of secs. 27, 28, 33 and 34.
	N. 0° 06' W., bet. secs. 27 and 28.
	Over gently rolling land, through medium heavy timber and undergrowth.
19.54	Road, bears E. and W.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
24.29	Fence, 4 strand barbed wire, bears N. 53° 20' W. and S. 53° 20' E.
25.39	Arizona Eastern Railroad, bears N. 53° 20' W. and S. 53° 20' E.
26.19	Telephone line, bears N. 53° 20' W. and S. 53° 20' E.; leave timber, continue over gently rolling land; enter an area now being cleared for a new townsite location.
39.74	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T4S R14E
	$\frac{1}{4}$
	S28 S27
	1958
	from which
	The point of intersection of Tilbury Drive and Greenwich road of the new townsite now under construction, bears S. 54° 08' W., 27 lks. dist.
	A point of intersection on the Arizona Eastern Railroad, which is monumented with a steel rail, firmly set in the ground, 4 ft. above ground, bears N. 87° 26' W., 20.52 chs. dist.
	The NE. cor. of a prominent rock outcropping, near top of ridge, bears S. 85° 24' W.
	The NE. cor. of a prominent cliff, bears S. 71° 20' W.
	Continue across townsite.
42.35	Telephone line, bears N. 32° 17' W. and S. 32° 17' E.
54.60	Road, bears S. 46° 03' W.
56.37	Graded, graveled road, bears N. 32° 18' W. and S. 32° 18' E.
62.15	Leave townsite; enter scattered timber; asc. 71 ft. over S. slope.
79.48	The cor. of secs. 21, 22, 27 and 28, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.
	Land, nearly level and gently rolling.
	Soil, sandy and gravelly loam.
	Timber, mesquite and paloverde.
	Undergrowth, yucca, cacti and sagebrush.
	From the cor. of secs. 22, 23, 26 and 27.
	S. 89° 52' W., bet. secs. 22 and 27.
	Over gently rolling land, through medium heavy timber and undergrowth.
2.65	Road, bears N. 40° E. and S. 40° W.; desc. 40 ft. over SW. slope.
12.07	Wash, 70 lks. wide, 3 ft. deep, drains S. 30° W.; asc. 38 ft. SE. slope.
17.43	Top of spur, slopes S. 35° W.
18.93	Road, bears N. 20° E. and S. 20° W.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
29.00	Begin descent, desc, 14 ft. over SW. slope.
34.32	Wash, 30 lks. wide, 4 ft. deep, drains S. 30° W.
39.70	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T4S R14E $\frac{1}{4}$ $\frac{S22}{S27}$ 1958
	Raise a mound of stone, 4 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
40.00	Top of spur, slopes SW.; desc. 84 ft. over SW. slope.
46.00	Power line, bears NW. and SE.
49.40	Wash, 40 lks. wide, 5 ft. deep, drains S. 50° W.; continue descent, desc. 51 ft. over SW. slope.
53.13	Wash, 25 lks. wide, 3 ft. deep, drains S. 20° W.; asc. 33 ft. over SE. slope.
56.20	Fence, 4 strand barbed wire, bears N. 50° W. and S. 50° E.
57.83	Arizona State Highway No. 177, under construction, bears N. 50° W. to Ray, Arizona, and S. 50° E. to Winkelman, Arizona.
60.28	Fence, 4 strand barbed wire, bears N. 50° W. and S. 50° E.
61.50	Power line, bears NW. and SE.
74.50	Wash, 30 lks. wide, 3 ft. deep, drains S. 50° W.
79.40	The cor. of secs. 21, 22, 27 and 28. Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, pinon, pine, paloverde and juniper.. Undergrowth, cacti, yucca, creosote bush, and sagebrush.
	S. 89° 40' W., bet. secs. 21 and 28. Over gently rolling land, through heavy timber and undergrowth.
2.45	Road, bears N. 75° E. and S. 70° W.
14.30	Graded, graveled road, old Arizona State Highway No. 177, bears N. 32° 17' W. and S. 32° 17' E.; desc. 49 ft. over W. slope.
23.00	Power line, bears NW. and SE.
30.67	Telephone line, bears N. 20° W. and S. 20° E.
30.97	Arizona Eastern Railroad, bears N. 20° W. and S. 20° E.; desc. 10 ft. over W. slope.
34.00	Bottom of descent; continue over nearly level land, through heavy timber and undergrowth.
39.50	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 21 and 28. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T4S R14E $\frac{1}{4}$ $\frac{W S21}{C S28}$ 1958

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
	<p>from which</p> <p>A mesquite, 8 ins. diam., bears N. 42° 45' E., 73 lks. dist., mkd. $\frac{1}{4}$ S21 BT.</p> <p>A mesquite, 4 ins. diam., bears S. 38°30' E., 33 lks. dist., mkd. BT.</p>
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor. This point falls near the right bank of the Gila River, which at this point is a sheer cutbank, 10 ft. high, and it is deemed unsafe for the cor.; not monumented.
40.00	Right bank of the Gila River, bears NNW. and SSE.
40.80	Main channel of Gila River, flows NNW.
42.00	Left bank of the Gila River, bears NNW. and SSE.; continue over level land, through heavy timber and undergrowth.
79.80	Fence, 3 strand barbed wire, bears N. and S.
79.96	<p>The cor. of secs. 20, 21, 28 and 29, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.</p> <p>Land, E. $\frac{1}{2}$ gently rolling, W. $\frac{1}{2}$ nearly level. Soil, sandy loam. Timber, mesquite and paloverde. Undergrowth, creosote bush, cacti, yucca and sagebrush.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 1° 45' E., bet. secs. 21 and 22.</p> <p>Over gently rolling land, through scattered timber and heavy undergrowth.</p> <p>Asc. 21 ft. over SE. slope.</p>
4.30	Road, bears N. 70° E. and S. 70° W.
12.00	Low spur, slopes SW.; continue ascent, asc. 50 ft. over SSE. slope.
19.90	Power line, bears N. 50° W. and S. 50° E.
21.00	Fence, 4 strand barbed wire, bears N. 50° W. and S. 50° E.
23.20	Arizona State Highway No. 177, under construction, bears N. 50° W. and S. 50° E.
25.60	Fence, 4 strand barbed wire, bears N. 50° W. and S. 50° E.
28.00	Low spur, slopes SW.
30.30	Wash, 1 ch. wide, 15 ft. deep, drains S. 70° W.
40.00	Powerline, bears N. 50° W. and S. 50° E.
40.24	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	<p style="text-align: center;">T4S R14E $\frac{1}{4}$ S21 S22 1958</p>
	<p>from which</p> <p>A paloverde, 5 ins. diam., bears S. 73° 30' W., 25 lks. dist., mkd. BT.</p> <p>No other suitable bearing trees available.</p> <p>Continue over gently rolling land, through medium heavy timber and undergrowth.</p>
43.80	Main wash, 2 chs. wide, 6 ft. deep, drains S. 75° W.; asc. 21 ft. over SE. slope.
49.20	Top of spur, slopes SW.
52.00	Wash, 20 lks. wide, 3 ft. deep, drains S. 80° W.
57.00	Top of low spur, slopes SW.
59.60	Wash, 30 lks. wide, 4 ft. deep, drains SW.; asc. 78 ft. over S. slope.
64.60	Top of spur, slopes S. 40° W.
75.80	Wash, 40 lks. wide, 4 ft. deep, drains S. 60° W.; asc. 60 ft. over S. slope.
79.64	Top of spur, slopes S. 65° W.
80.48	<p>The cor. of secs. 15, 16, 21 and 22, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, pinon, paloverde, juniper and mesquite, Undergrowth, cacti, yucca, creosote bush, ocotillo and sagebrush.</p>
	<p>N. 88° 19' W., bet. secs. 16 and 21.</p> <p>Over gently rolling land, through scattered timber.</p>
3.00	Top of spur, slopes SW.; desc. 46 ft. over W. slope.
8.00	Wash, 20 lks. wide, 2 ft. deep, drains S. 60° W.
10.00	Top of spur, slopes S. 60° W.
11.90	Wash, 3 chs. wide, 6 ft. deep, drains S. 50° W.; asc. 30 ft. over SE. slope.
15.30	Top of spur, slopes SW.; desc. 20 ft. over SW. slope.
18.30	Wash, 40 lks. wide, 4 ft. deep, drains SSW.; asc. 30 ft. over SW. slope.
23.70	Top of spur, slopes S. 30° W.; desc. 60 ft. over SW. slope.
33.65	Power line, bears N. 50° W. and S. 50° E.
36.65	Wash, 3 chs. wide, 3 ft. deep, drains SW.; asc. 80 ft. over SE. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains 41.39	<p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, which is monumented with an unmarked stone and the remains of a squared mesquite post, firmly set in the ground, and in a mound of stone. This is the position for the $\frac{1}{4}$ sec. cor. according to residents who stated that this cor. had been used for years. It is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R14E $\frac{1}{4}$ $\frac{S16}{S21}$ 1958</p> <p>Reset the unmarked stone and the remains of the squared mesquite post alongside the iron post.</p> <p>Deposit broken glass around the iron post, 12 ins. below the surface of the ground.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $87^{\circ} 33'$ W., beginning new measurement.</p> <p>Continue over gently rolling land, through scattered timber and undergrowth.</p>
6.90	Arizona State Highway No. 177, under construction, bears N. 50° W. and S. 50° E.
9.53	Graded, graveled road, old Arizona State Highway No. 177, on curve, bears N. 30° E. and S. 30° W.
16.53	Power line, bears N. $31^{\circ} 21'$ W. and S. $31^{\circ} 21'$ E.; desc. 35 ft. over W. slope.
23.60	Wash, 30 lks. wide, 3 ft. deep, drains S. 70° W.; asc. 20 ft. over SE. slope.
33.13	Top of spur, slopes S. 65° W.; desc. 108 ft. over W. slope.
38.60	Wash, 5 chs. wide, 3 ft. deep, drains S. 70° W.
41.56	<p>The cor. of secs. 16, 17, 20 and 21, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, paloverde and mesquite. Undergrowth; creosote bush, cacti, yucca and sagebrush.</p>
	<p>N. $2^{\circ} 55'$ E., bet. secs. 16 and 17.</p> <p>Over rolling land, through heavy timber and undergrowth.</p>
2.70	Wash, 40 lks. wide, 4 ft. deep, drains SW.; asc. 115 ft. over S. slope.
6.60	Top of spur; slopes SW.; desc. 25 ft. over NNW. slope.
26.92	Begin descent, desc. 15 ft. over N. slope.
35.40	Wash, 40 lks. wide, 6 ft. deep, drains SW.; asc. 50 ft. over SE. slope.
39.20	The point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 16 and 17.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains	
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T4S R14E ½ S17↗S16 W C 1958
39.50	Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor. This point falls on the face of a small sloping cliff, 4 ft. high, and could not be monumented. Continue over rolling land; asc. 69 ft. over SE. slope.
42.60	Power line, bears N. 31° W. and S. 40° W.
49.00	Top of spur, slopes S. 30° W.; desc. 53 ft. over NNW. slope.
52.00	Road, bears E. and W.
58.10	Wash, 30 lks. wide, 3 ft. deep, drains S. 70° W.
60.75	Power line, bears N. 31° W. and S. 31° E.; asc. 30 ft. over S. slope.
64.57	Power line, bears N. 31° W. and S. 31° E.
65.45	Top of spur, slopes S. 70° W.
67.45	Wash, 20 lks. wide, 3 ft. deep, drains S. 70° W.; continue ascent, asc. 32 ft. over S. slope.
77.74	Wash, 25 lks. wide, 4 ft. deep, drains S. 50° W.
79.00	The cor. of secs. 8, 9, 16 and 17, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record. Land, gently rolling. Soil, sandy and gravelly loam. Timber, mesquite, paloverde and juniper. Undergrowth, cacti, yucca and sagebrush.
	N. 88° 36' W., bet. secs. 8 and 17. Over gently rolling land, through heavy timber and undergrowth.
9.80	Wash, 30 lks. wide, 4 ft. deep, drains SW.
12.00	Top of spur, slopes S.; desc. 50 ft. over SW. slope.
18.62	Power line, bears N. 31° W. and S. 31° E.
23.10	Wash, 30 lks. wide, 12 ft. deep, drains S. 60° W.
25.82	Top of spur, slopes S. 60° W.
26.52	Power line, bears N. 31° W. and S. 31° E.
30.95	Telephone line, bears N. and S.; desc. 20 ft. over W. slope.
33.20	Wash, 50 lks. wide, 2 ft. deep, drains SW.; road in wash, bears NE. and SW.; asc. 20 ft. over E. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 4 S., R. 14 E.

Chains

41.21

Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T4S R14E

$$\frac{1}{4} \frac{S 8}{S 17}$$

1958

Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Continue over heavily rolling land, through medium heavy timber and undergrowth.

Asc. 50 ft. over E. slope.

46.34

Top of spur, slopes SSW.; oiled road, bears N. 30° E. and S. 60° W.; desc. 114 ft. over W. slope.

55.40

Wash, 1 ch. wide, 3 ft. deep, drains SW.

59.30

Wash, 30 lks. wide, 2 ft. deep, drains S. 40° W.; asc. 167 ft. over E. slope.

73.60

Top of spur, slopes S. 30° W.

77.00

Begin descent, desc. 107 ft. over W. slope.

82.42

The cor. of secs. 7, 8, 17 and 18, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

Land, gently rolling E. $\frac{1}{2}$, heavily rolling W. $\frac{1}{2}$.

Soil, sandy and gravelly loam.

Timber, mesquite, paloverde and juniper.

Undergrowth, creosote bush, cacti, yucca and sagebrush.

GENERAL DESCRIPTION

The general elevation of the portion of the township resurveyed ranges in elevation from about 1,800 ft. in the valley along the Gila River, to about 2,200 ft. within distance of two miles on either side of the valley.

In the valley where the Gila River flows, the land is nearly level, covered with a heavy growth of mesquite timber. The land adjacent to the valley, for the most part, is gently to heavily rolling with a medium heavy growth of timber. The soil of the bottom land along the Gila River is a silt and sandy loam; the remainder of the land in the area resurveyed is a sandy and gravelly clay loam.

The Gila River enters the township from the south, about 10 chs. west of the corner of secs. 1, 2, 34 and 36 on the south boundary of the township, flows in a NNW. direction through sec. 35, westerly through sec. 34, WNW. through the NE. portion of sec. 33, thence NNW. through secs. 28, 21, 20, 17, 18 and 7, and NNW. and SW. through sec. 6; leaving the township near the cor. of secs. 6 and 7 on the west boundary of the township.

The Arizona Eastern Railroad enters the portion of the township resurveyed about 8 chs. west of the corner of secs. 1, 2, 35 and 36 on the south boundary of the township, traverses in a general NW. direction through secs. 35, 26, 27, 28, 21, 17 and 7, and leaves the township near the corner of secs. 6 and 7 on the west boundary of the township.

Township 4 South, Range 14 East

Chains

Arizona State Highway No. 177, a graded, graveled road enters the township at the corner of secs. 1, 2, 35 and 36 on the south boundary of the township, traverses through the township in a general NW. direction and leaves near the corner of secs. 6 and 7 on the west boundary of the township. This road is being relocated and construction work is being carried out on the new location at the present time. Arizona State Highway No. 177, now under construction, enters the township from the south, about 5 chs. west of the corner of secs. 1, 2, 35 and 36 and traverses northwesterly through secs. 35, 26, 27, 22, and 21, and north about $\frac{1}{4}$ mile in sec. 16 where it joins the old highway. This is the end of the construction at this time.

There are settlers living in secs. 35, 33 and 29 who have fields in cultivation under irrigation. There is a vacant ranch house in sec. 34 and two vacant houses in sec. 35, where land has been brought under cultivation with some of the land being irrigated. The predominating interest however appears to be in stock grazing, as there is a fair growth of native grasses over most of the area.

A townsite is being surveyed and construction has been started for a new town in the northwest portion of sec. 27 and the northeast portion of sec. 28. This town is being constructed in order to relocate the majority of the inhabitants of the mining town of Ray, Arizona, which is being abandoned.

25

BOOK 4004

4-680
(Feb., 1950)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Craig P. Sylvester	Principal Assistant
William R. Savage	Note Keeper
Max L. Sevy	Drag Chainman
Max T. Ricketts	Flagman
Andrew M. Nelson	Truckdriver, Cornerman

CERTIFICATE OF CADASTRAL ENGINEER

I, Horace G. Parker, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of January, 1958, I have surveyed dependently resurvey a portion of the south boundary and a portion of the subdivision, Township 4 South, Range 14 East

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
October 16, 1958

Horace G. Parker
Horace G. Parker - Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., APR 3 1959, 19

The foregoing field notes of the survey of dependent resurvey of a portion of the south boundary and a portion of the subdivision, Township 4 South, Range 14 East, Gila and Salt River Meridian

executed by Horace G. Parker, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

Donald Clement
Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in is a true copy of the original field notes.

Cadastral Engineering Staff Officer.