

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE

FIRST STANDARD PARALLEL NORTH,

SURVEY OF A PORTION OF

THE NORTH BOUNDARY

AND SURVEY OF A PORTION

OF THE SUBDIVISIONAL LINES OF

TOWNSHIP 5 NORTH, RANGE 6 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Horace G. Parker, Cadastral Surveyor

*Under special instructions dated August 11, 1959, which provided  
for the surveys included under Group No. 335, approved August 20, 1959  
and assignment instructions dated September 16, 1959*

*Survey commenced September 30, 1959*

*Survey completed October 29, 1959*

1A

BOOK 4566

# INDEX DIAGRAM

Township 5 North, Range 6 East

|          |       |      |      |      |    |
|----------|-------|------|------|------|----|
| 19<br>19 | 5     | 4    | 3    | 2    | 1  |
| 18<br>17 | 8     | 9    | 10   | 11   | 12 |
| 16<br>16 | 17    | 16   | 15   | 14   | 13 |
| 14<br>14 | 20    | 21   | 22   | 23   | 24 |
| 13<br>12 | 29    | 28   | 27   | 26   | 25 |
| 11<br>1  | 32 10 | 33 8 | 34 7 | 35 6 | 36 |
|          | 2     | 3    | 3    | 4    |    |

## Township 5 North, Range 6 East

## Chains

The First Standard Parallel North along the south boundary of the township was surveyed by W. H. Pierce, Deputy Surveyor, in 1867, and was independently resurveyed by S. E. Blout, Cadastral Engineer, in 1919. The west boundary of the township was surveyed by S. E. Blout in 1919.

In the present work a retracement of the west five miles of the south boundary of the township discloses the fact that all the 1919 corners are extant and in a good state of preservation, but courses and distances are erratic to the extent that resurvey is desirable. A complete retracement of the west boundary of the township discloses the fact that all corners are extant and in a good state of preservation and all courses and distances substantially as appears in the official record of the 1919 survey, thus a resurvey of this boundary is unnecessary at this time.

The survey returns hereinafter shown are limited to the resurvey of the west five miles of the south boundary, survey of the north boundary of section 6, and survey of sections 6, 7, 18, 19, 30 to 35, inclusive, thus covering the area requested for survey by the U. S. Forest Service in this township.

The field work was executed with W. & L. E. Gurley solar transit No. 590909, property of the Bureau of Land Management. The instrument is fully equipped, with full vertical circle and improved Smith type telescopic solar attachment. The transit and solar instruments were maintained in good adjustment throughout the course of the work.

October 5, 1959, at the standard corner of Tps. 5 N., Rs. 5 and 6 E., in latitude  $33^{\circ} 43' 36.031''$  N. and longitude  $111^{\circ} 47' 10.482''$  W., we make a series of four altitude observations on the sun, reading the horizontal angles from a flag about 20 chains distant (which, according to determination by the solar attachment, bears East), in the direction east to south.

|   |                             |
|---|-----------------------------|
| Mean watch time (mountain standard time) of observation | 8h 57m 30s A.M.             |
| Mean vertical angle                                     | $29^{\circ} 07' 37.5''$     |
| Mean horizontal angle                                   | $85^{\circ} 52'$            |
| Reduced bearing of flag                                 | S. $89^{\circ} 59' 55''$ E. |

Dependent Resurvey, Portion of First Standard Parallel North, through T. 5 N., R. 6 E.

Reestablishment of the survey executed by S. E. Blout, Cadastral Engineer, in 1919.

Beginning at the 1919 standard cor. of Tps. 5 N., Rs. 5 and 6 E., which is monumented with an iron post, 3 ins. diam., firmly set in ground, mkd. and witnessed as described in the official record.

From this cor. the SW. cor. of a 4-strand wire fence bears NE. 8 lks. dist.

N.  $89^{\circ} 54'$  E., along the S. bdy. of sec. 31, T. 5 N., R. 6 E.

Over gently rolling land, through medium dense timber and undergrowth, desc. slightly over generally ESE. slope along S. side of E.-W. fence.

8.09 Wash, 10 lks. wide,  $1\frac{1}{2}$  ft. deep, drains NE.; asc. over gradual NW. slope.

22.10 Low spur, slopes N.; desc. over gradual E. slope.

Dependent Resurvey, Portion of First Standard Parallel North, through  
T. 5 N., R. 6 E.

|        |   |
|--------|---|
| Chains |   |
| 27.20  | Wash, 20 lks. wide, 6 ins. deep, drains ESE.  |
| 40.04  | The 1919 standard $\frac{1}{2}$ sec. cor. of sec. 31, which is monumented with an iron post, 1 in. diam., firmly set in ground, mkd. and witnessed as described in the official record.<br><br>This cor. is situated 8 lks. S. of 4-strand wire fence on steel posts bearing E. and W.<br><br><hr/>   |
|        | N. 89° 52' E., beginning new measurement.<br><br>Over nearly flat land, through heavy timber and undergrowth; desc. slightly over general ESE. slope.   |
| 12.70  | Wash, 10 lks. wide, 1 ft. deep, drains NE.  |
| 14.88  | Branch fence, bears N. from E.-W. fence, 8 lks. to N. of line.  |
| 23.45  | Wash, 30 lks. wide, 2 ft. deep, drains NE.  |
| 36.49  | The original closing cor. of secs. 5 and 6, T. 4 N., R. 6 E., which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.  |
| 40.01  | The 1919 standard cor. of secs. 31 and 32, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.<br><br>This cor. is situated 10 lks. S. of fence bearing E. and W.<br><br>Land, slightly rolling.<br>Soil, sandy and gravelly clay loam.<br>Timber, palo verde, mesquite and saguaro.<br>Undergrowth, cactus, cat claw, yucca and desert sage.<br><br><hr/> |
|        | N. 89° 50' E., along the S. bdy. of sec. 32.<br><br>Over nearly flat land, through heavy timber and undergrowth; desc. gradually over general ESE. slope, along S. side of wire fence.  |
| 22.80  | Wash, 20 lks. wide, 3 ft. deep, drains SE.  |
| 40.02  | The 1919 standard $\frac{1}{2}$ sec. cor. of sec. 32, which is monumented with an iron post, 1 in. diam., firmly set in ground, mkd. and witnessed as described in the official record.<br><br><hr/>  |
|        | N. 89° 46' E., beginning new measurement.<br><br>Desc. slightly over nearly flat land, over general ESE. slope, through heavy timber and undergrowth.   |
| 9.30   | Wash, 10 lks. wide, 2 ft. deep, drains NE.  |
| 36.89  | The original closing cor. of secs. 4 and 5, T. 4 N., R. 6 E., which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.  |
| 40.01  | The 1919 standard cor. of secs. 32 and 33, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.<br><br>Land, slightly rolling.<br>Soil, sandy and gravelly clay loam.   |

## Dependent Resurvey, Portion of South Boundary, T. 5 N., R. 6 E.

## Chains

Timber, mesquite, palo verde, and saguaro.  
Undergrowth, cactus, Spanish dagger, desert sage and yucca.

N. 89° 50' E., along the S. bdy. of sec. 33.

Desc. slightly over gently rolling ESE. slope, through heavy timber and undergrowth.

8.10 Wash, 20 lks. wide, 2½ ft. deep, drains SE.

15.90 Same wash, 30 lks. wide, 2½ ft. deep, drains N. 50° E.

33.20 Same wash, 25 lks. wide, 2 ft. deep, drains S. 25° E.

40.02 The 1919 standard ¼ sec. cor. of sec. 33, which is monumented with an iron post, 1 in. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

N. 89° 50' E., beginning new measurement.

Desc. over gradual ESE. slope, through scattered timber and undergrowth.

2.00 Fence cor., bears N. 8 lks. dist.; 4-strand barbed wire fences run E., W. and N. therefrom.

4.40 Wash, 60 lks. wide, 1½ ft. deep, drains N. 35° E.

36.88 The original closing cor. of secs. 3 and 4, T. 4 N., R. 6 E., which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

40.01 The 1919 standard cor. of secs. 33 and 34, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

Land, nearly flat desert.

Soil, sandy and gravelly clay loam.

Timber, mesquite, palo verde and saguaro.

Undergrowth, cactus, yucca, mesquite and sagebrush.

N. 89° 49' E., along the S. bdy. of sec. 34.

Desc. over nearly flat, very gradual ESE. slope through scattered timber and undergrowth.

12.40 Wash, 15 lks. wide, 1½ ft. deep, drains N. 50° E.

16.40 Same wash, 25 lks. wide, 1½ ft. deep, drains S. 35° E.

40.02 The 1919 standard ¼ sec. cor. of sec. 34, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

N. 89° 48' E., beginning new measurement.

Desc. over gradual ESE. slope through sparse timber and undergrowth.

37.03 The original closing cor. of secs. 2 and 3, T. 4 N., R. 6 E., which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

## Dependent Resurvey of Portion of South Boundary, T. 5 N., R. 6 E.

| Chains |   |
|--------|---|
| 40.08  | The 1919 standard cor. of secs. 34 and 35, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.   |
|        | <p>Land, nearly flat.<br/>           Soil, sandy and gravelly clay loam.<br/>           Timber, mesquite, palo verde and saguaro.<br/>           Undergrowth, cactus, catclaw, acacia, yucca and sagebrush.</p>                     |
|        | N. 89° 51' E., along the S. bdy. of sec. 35.  |
| 16.05  | Over gradual ESE. slope through heavy timber and undergrowth.<br>Wash, 20 lks. wide, 1½ ft. deep, drains S. 50° E.  |
| 23.70  | Leave nearly flat land, beginning of gently rolling land.   |
| 25.60  | Wash, 10 lks. wide, 1 ft. deep, drains SE.  |
| 28.60  | Crest of small spur, slopes S.; desc. over gradual E. slope.  |
| 33.80  | Wash, 10 lks. wide, 1 ft. deep, drains NE.; asc. over gradual W. slope.   |
| 39.90  | Crest of ascent, bears NW. and SE.  |
| 39.97  | The 1919 standard ¼ sec. cor. of sec. 35, which is monumented with an iron post, 1 in. diam., firmly set in the ground, mkd. and witnessed as described in the official record.   |
|        | N. 89° 50' E., beginning new measurement.   |
| 1.80   | Over gently rolling land, through scattered timber and undergrowth; desc. 60 ft. over short E. slope.<br>Draw, 5 lks. wide, drains S.; asc. 200 ft. over W. slope.  |
| 10.70  | Crest of flat topped hill, bears N. 20° E. and S. 20° W.; desc. 185 ft. over ESE. slope.  |
| 21.04  | Drain, 20 lks. wide, course S.; asc. 135 ft. over W. slope.   |
| 30.00  | Spur, slopes S.; desc. 155 ft. over E. slope to standard sec. cor.  |
| 36.64  | The original closing cor. of secs. 1 and 2, T. 4 N., R. 6 E., which is monumented with an iron post, 2 ins. diam., firmly set in ground, mkd. and witnessed as described in the official record.                                    |
| 39.98  | The 1919 standard cor. of secs. 35 and 36, which is monumented with an iron post, 2 ins. diam., firmly set in ground, mkd. and witnessed as described in the official record.   |
|        | This cor. is situated at a point 6 lks. S. of fence bearing E. and W. Geographic position of this cor., reduced from U. S. C. & G. S. triangulation station "Line" is Latitude 33° 43' 36.788" N. and longitude 111° 41' 57.809" W. |
|        | <p>Land, mostly gently rolling.<br/>           Soil, sandy and gravelly clay loam.<br/>           Timber, palo verde and mesquite.<br/>           Undergrowth, cactus, Spanish dagger, saguaro, catclaw and acacia.</p>             |

## Survey of Portion of the North Boundary, T. 5 N., R. 6 E.

## Chains

At the point for cor. of secs. 5, 6, 31 and 32, Tps. 5 and 6 N., R. 6 E. (which has previously been determined as situated N.  $0^{\circ} 03'$  W. 489.05 chs. dist. from the standard cor. of secs. 31 and 32, T. 5 N., R. 6 E.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T6N R6E

S31 | S32

S6 | S5

T5N R6E

1959

Raise a mound of stone,  $3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Thence

West, bet. secs. 6 and 31.

Over rolling land, through dense timber and undergrowth; asc. short E. slope.

2.36 Low flat spur, slopes S.; desc. gradual W. slope.

5.06 Wash, 20 lks. wide, 3 ft. deep, drains S.; asc. gentle E. slope.

7.36 Low spur, slopes S.; desc. gradual W. slope.

12.90 Wash, 25 lks. wide, 2 ft. deep, drains SE.; asc. E. slope.

21.00 Spur, slopes S.; desc. W. slope.

27.33 Wash, 10 lks. wide, 1 ft. deep, drains S.; asc. rolling E. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T6N R6E

$\frac{1}{4}$  S31

S 6

T5N R6E

1959

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Cont. over rolling land, through timber and undergrowth.

58.40 Wash, 20 lks. wide, 2 ft. deep, drains SE.; asc. gradual E. slope.

72.75 Spur, slopes S.; desc. W. slope.

76.40 Wash, drains SE.; asc. E. slope.

77.26 Low spur, slopes N.; desc. slightly to Tp. cor.

79.66 The original cor. of Tps. 5 and 6 N., Rs. 5 and 6 E., which is monumented with an iron post, 3 ins. diam., firmly set in ground, mkd. and witnessed as described in the official record.

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, palo verde, mesquite and saguaro.

Undergrowth, cactus, yucca, mesquite and sagebrush.

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

| Chains |  |
|--------|--|
|        | From the 1919 standard cor. of secs. 35 and 36, on the S. bdy. of the township.  |
|        | N. 0° 01' W., bet. secs. 35 and 36.  |
|        | Through medium dense timber and undergrowth; asc. 60 ft. over SW. slope.   |
| .06    | Four-strand barbed wire fence with steel fence posts, bears E. and W.  |
| 2.65   | Spur, slopes W.; desc. 40 ft. over N. slope.   |
| 6.65   | Draw, drains E.; asc. 75 ft. over SE. slope.   |
| 14.50  | Spur, slopes E.; desc. 95 ft. over NW. slope.  |
| 21.14  | Unimproved road, along bottom of slope, bears E. and W.; thence over nearly flat land.   |
| 24.30  | Wash, 45 lks. wide, 2 ft. deep, drains E.  |
| 35.12  | Wash, 40 lks. wide, 1½ ft. deep, drains E.   |
| 40.00  | Point for the ¼ sec. cor. of secs. 35 and 36.<br>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. |
|        | T5N R6E<br>¼<br>S35   S36<br>1959  |
|        | from which   |
|        | A palo verde, 8 ins. diam., bears N. 77° 35' E., 263 lks. dist., mkd. T5N R6E ¼ S36 BT.  |
|        | A palo verde, 8 ins. diam., bears N. 26° 12' W., 67 lks. dist., mkd. T5N R6E ¼ S35 BT.   |
|        | Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of the iron post.  |
|        | Cont. over gently rolling land, through dense timber and undergrowth.  |
| 79.60  | Wash, 25 lks. wide, 3 ft. deep, drains E.  |
| 80.00  | Point for the cor. of secs. 25, 26, 35 and 36.   |
|        | Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  |
|        | T5N R6E<br>S26   S25<br>S35   S36<br>1959.   |
|        | from which   |
|        | A palo verde, 8 ins. diam., bears N. 50° 02' E., 97 lks. dist., mkd. T5N R6E S25 BT.   |
|        | A palo verde, 8 ins. diam., bears S. 69° 35' E., 148 lks. dist., mkd. T5N R6E S36 BT.  |
|        | A palo verde, 6 ins. diam., bears S. 58° 30' W., 56 lks. dist., mkd. T5N R6E S35 BT.   |
|        | A palo verde, 4 ins. diam., bears N. 32° 57' W., 88 lks. dist., mkd. T5N R6E S26 BT.   |



## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

Chains

Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of the iron post.

Land, gently rolling to flat.

Soil, gravelly and sandy clay loam.

Timber, palo verde and mesquite.

Undergrowth, cactus, ocotillo, catclaw, yucca, black brush, creosote bush and saguaro.

From the 1919 standard cor. of secs. 34 and 35.

N. 0° 01' W., bet. secs. 34 and 35.

Over slightly rolling land, through heavy timber and undergrowth.

.05 Four strand barbed wire fence with steel fence posts, bears E. and W.

1.40 Wash, 30 lks. wide, 1½ ft. deep, drains E.

40.00 Point for the ¼ sec. cor. of secs. 34 and 35.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of earth to cap, with brass cap mkd.

T5N R6E

¼

S34 | S35

1959

from which

A palo verde, 18 ins. diam., bears N. 73° 05' W., 62 lks. dist., mkd. T5N R6E ¼ S34 BT.

A palo verde, 8 ins. diam., bears N. 43° 23' E., 133 lks. dist., mkd. T5N R6E ¼ S35 BT.

Cont. over gently rolling land, through heavy timber and undergrowth.

47.00 Wash, 40 lks. wide, 1½ ft. deep, drains E.

50.20 Wash, 30 lks. wide, 1 ft. deep, drains E.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T5N R6E

S27 | S26

S34 | S35

1959

Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of iron post.

Land, very gently rolling to nearly flat.

Soil, sandy and gravelly clay loam.

Timber, palo verde and mesquite.

Undergrowth, cactus, catclaw, black brush and saguaro.

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

|        |  |
|--------|--|
| Chains | From the cor. of secs. 25, 26, 35 and 36.  |
|        | S. 89° 49' W., bet. secs. 26 and 35.   |
|        | Over slightly rolling land, through heavy timber and undergrowth.                                      |
| 17.60  | Unimproved road, bears N. and S.   |
| 39.97  | Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.  |
|        | Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. |
|        | T5N R6E<br>$\frac{1}{4}$ $\frac{S26}{S35}$<br>1959   |
|        | from which   |
|        | A palo verde, 6 ins. diam., bears N. 16° 54' W., 51 lks. dist., mkd. T5N R6E $\frac{1}{4}$ S26 BT.     |
|        | A palo verde, 6 ins. diam., bears S. 4° 45' E., 96 lks. dist., mkd. T5N R6E $\frac{1}{4}$ S35 BT.      |
|        | Cont. over gently rolling land, through heavy timber and undergrowth.                                  |
| 45.20  | Graded road, bears NE. and SW.   |
| 62.10  | Unimproved road, bears N. and S., joins a graded road at a point approx. 3 chs. N.                     |
| 79.94  | The cor. of secs. 26, 27, 34 and 35.   |
|        | Land, flat to gently rolling.  |
|        | Soil, sandy and gravelly clay loam.  |
|        | Timber, palo verde and mesquite.   |
|        | Undergrowth, catclaw, acacia, black brush, creosote bush, ocotillo, yucca and saguaro.                 |
|        | From the 1919 standard cor. of secs. 33 and 34, on the S. bdy. of the Tp.                              |
|        | N. 0° 02' W., bet. secs. 33 and 34.  |
|        | Over slightly rolling land, through heavy timber and undergrowth.                                      |
| .06    | Four-strand barbed wire fence, bears E. and W.   |
| 9.90   | Wash, 60 lks. wide, 1 $\frac{1}{2}$ ft. deep, drains E.  |
| 28.70  | Wash, 25 lks. wide, 1 $\frac{1}{2}$ ft. deep, drains S. 75° E.   |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.  |
|        | Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. |
|        | T5N R6E<br>$\frac{1}{4}$ S33 S34<br>1959   |
|        | from which   |

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

Chains

A palo verde, 8 ins. diam., bears S. 75° 30' E., 130 lks. dist.,  
mkd. T5N R6E  $\frac{1}{4}$  S34 BT.

A palo verde, 4 ins. diam., bears N. 50° 30' W., 60 lks. dist.,  
mkd. T5N R6E  $\frac{1}{4}$  S33 BT.

Cont. over gently rolling land, through heavy timber and undergrowth.

45.90 Wash, 25 lks. wide, 1½ ft. deep, drains E.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground,  
in a mound of earth to top, with brass cap mkd.

|         |     |
|---------|-----|
| T5N R6E |     |
| S28     | S27 |
| S33     | S34 |
| 1959    |     |

No accessories available.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, palo verde and mesquite.

Undergrowth, catclaw, acaçia, black brush, mesquite, cactus and  
saguaro.

From the cor. of secs. 26, 27, 34 and 35.

S. 89° 50' W., bet. secs. 27 and 34.

Over gently rolling land, through heavy timber and undergrowth.

40.05 Point for the  $\frac{1}{4}$  sec. cor. of secs. 27 and 34.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,  
with brass cap mkd.

|                   |  |
|-------------------|--|
| T5N R6E           |  |
| $\frac{1}{4}$ S27 |  |
| S34               |  |
| 1959              |  |

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of the iron post.

No trees suitable for bearing trees available.

This cor. is situated on the N. bank of a wash, 5 lks. wide, 10 ins.  
deep, draining SE.

Cont. over gently rolling land, through timber and undergrowth.

80.10 The cor. of secs. 27, 28, 33 and 34.

Land, very gently rolling.

Soil, sandy and gravelly.

Timber, palo verde and mesquite.

Undergrowth, catclaw, acaçia, black brush, creosote bush, cactus and  
saguaro.

From the 1919 standard cor. of secs. 32 and 33 on the S. bdy. of the  
Tp.

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

Chains

N. 0° 02' W., bet. secs. 32 and 33.

Over gently rolling land, through medium heavy timber and undergrowth.

.06 Four-strand barbed wire fence, with steel fence posts, bears E. and W.

1.50 Wash, 15 lks. wide, 2 ft. deep, drains E.

11.20 Wash, 20 lks. wide, 2 ft. deep, drains E.

26.60 Wash, 25 lks. wide, 3 ft. deep, drains E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 32 and 33.Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, in a mound of earth, 4 ft. base, 10 ins. high, with brass cap mkd.

T5N R6E

$$\frac{1}{4}$$

|      |  |     |
|------|--|-----|
| S32  |  | S33 |
| 1959 |  |     |

No suitable bearing trees available.

Cont. over gently rolling land, through heavy timber and undergrowth.

57.00 Wash, 40 lks. wide, 3 ft. deep, drains SE.

72.70 Wash, 50 lks. wide, 3 ft. deep, drains SE.

80.00 Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T5N R6E

|      |  |     |
|------|--|-----|
| S29  |  | S28 |
| S32  |  | S33 |
| 1959 |  |     |

Raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of the iron post.

Land, very gently rolling.

Soil, sandy and gravelly clay loam.

Timber, palo verde and mesquite.

Undergrowth, cactus, Spanish dagger, saguaro, catclaw and acacia.

From the cor. of secs. 27, 28, 33 and 34.

S. 89° 50' W., bet. secs. 28 and 33.

Over gently rolling land, through heavy timber and undergrowth.

39.48 Four-strand barbed wire fence with steel posts, bears N. and S.

39.98 Point for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 33.Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T5N R6E

$$\frac{1}{4}$$

|      |  |     |
|------|--|-----|
| S28  |  | S33 |
| 1959 |  |     |

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

| Chains |  |
|--------|--|
| 79.96  | <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of the iron post.<br/>Cont. over gently rolling land, through heavy timber and undergrowth.</p> <p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, gently rolling to flat.<br/>Soil, sandy and gravelly clay loam.<br/>Timber, palo verde and mesquite.<br/>Undergrowth, catclaw, acacia, black brush, mesquite, cactus and saguaro.</p> |
| .06    | <p>From the 1919 standard cor. of secs. 31 and 32 on the S. bdy. of the township.</p> <p>N. 0° 03' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land, through heavy timber and undergrowth.</p> <p>Four-strand barbed wire fence with steel posts, bears E. and W.</p>   |
| 5.30   | <p>Wash, 10 lks. wide, 1 ft. deep, drains E.</p>   |
| 40.00  | <p>Point for the ½ sec. cor. of secs. 31 and 32.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>  |
|        | <p style="text-align: center;">T5N R6E<br/>          ½<br/>          S31 S32<br/>          1959</p>  |
| 44.30  | <p>Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of the iron post.<br/>Cont. over gently rolling land, through heavy timber and undergrowth.</p> <p>Unimproved road, bears E. and W.</p>   |
| 47.90  | <p>Wash, 1.00 ch. wide, 2 ft. deep, drains E.</p>  |
| 48.10  | <p>Five-strand barbed wire fence, with steel posts, bears E. and W.</p>  |
| 49.86  | <p>Similar fence, bears E. and W.</p>  |
| 51.10  | <p>Stock watering reservoir, approx, 8 chs. diam., bears E. approx. 15 chs. dist.</p>  |
| 64.60  | <p>Wash, 80 lks. wide, 3 ft. deep, drains E.</p>   |
| 68.94  | <p>Graded road, bears NE. and SW.</p>  |
| 79.70  | <p>Wash, 20 lks. wide, 1 ft. deep, drains E.</p>   |
| 80.00  | <p>Point for the cor. of secs. 29, 30, 31 and 32.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to solid rock, with a collar of stone to top, with brass cap mkd.</p>  |
|        | <p style="text-align: center;">T5N R6E<br/>          S30 S29<br/>          S31 S32<br/>          1959</p>  |
|        | <p>Land, gently rolling.<br/>Soil, sandy to gravelly clay loam.<br/>Timber, palo verde and mesquite.</p>   |

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

|        |  |
|--------|--|
| Chains | Undergrowth, catclaw, acacia, black brush and cactus.  |
|        | From the cor. of secs. 28, 29, 32 and 33.  |
|        | S. 89° 46' W., bet. secs. 29 and 32.   |
|        | Over slightly rolling land, through medium heavy timber and undergrowth.   |
| 25.18  | Graded road, bears N. 70° E. and S. 70° W.   |
| 40.07  | Point for the $\frac{1}{2}$ sec. cor. of secs. 29 and 32.  |
|        | Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.   |
|        | T5N R6E<br>$\frac{1}{2}$ $\frac{S29}{S32}$<br>1959   |
|        | Raise a mound of stone, 3 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, N. of iron post.   |
|        | Cont. over gently rolling land, through heavy timber and undergrowth.  |
| 61.60  | Wash, 50 lks. wide, 2 ft. deep, drains SE.   |
| 80.15  | The cor. of secs. 29, 30, 31 and 32.   |
|        | Land, very gently rolling.<br>Soil, sandy and gravelly clay loam.<br>Timber, palo verde and mesquite.<br>Undergrowth, black brush, cactus, yucca, creosote bush, catclaw, acacia and aguaro. |
|        | S. 89° 57' W., bet. secs. 30 and 31.   |
|        | Over slightly rolling land, through medium heavy timber and undergrowth.   |
| .30    | Wash, 20 lks. wide, 1 ft. deep, drains SE.   |
| 25.00  | Small flat spur, slopes SE.; desc. slightly over SSW. slope.   |
| 29.50  | Draw, 20 lks. wide, 1 ft. deep, drains SW.; asc. slightly over rolling SE. slope.  |
| 40.00  | Point for the $\frac{1}{2}$ sec. cor. of secs. 30 and 31.  |
|        | Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.   |
|        | T5N R6E<br>$\frac{1}{2}$ $\frac{S30}{S31}$<br>1959   |
|        | Raise a mound of stone, 4 ft. base, 2 $\frac{1}{2}$ ft. high, N. of iron post.   |
|        | Asc. gradually over rolling land, through heavy timber and undergrowth.  |
| 58.80  | Wash, 30 lks. wide, 2 ft. deep, drains SE.   |
| 63.90  | Unimproved road, bears N. 40° E. and S. 40° W.   |

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

|        |  |
|--------|--|
| Chains |  |
| 78.48  | Unimproved road, bears N. and SE.  |
| 79.73  | Four-strand barbed wire fence, bears N. and S.   |
| 79.97  | The original cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.                         |
|        | Land, gently rolling.<br>Soil, sandy and gravelly clay loam.<br>Timber, palo verde and mesquite.<br>Undergrowth, catclaw, black brush and cactus.  |
|        | From the cor. of secs. 29, 30, 31 and 32.<br>N. 0° 03' W., bet. secs. 29 and 30.<br>Over slightly rolling land, through heavy timber and undergrowth; asc. gradual S. slope.   |
| 3.70   | Low flat spur, slopes W.; desc. gentle rolling N. slope.   |
| 6.60   | Wash, 20 lks. wide, 1 ft. deep, drains E.; asc. gradually over a series of low spurs with small intervening washes.  |
| 16.60  | Wash, 30 lks. wide, 2 ft. deep, drains S. 60° E.   |
| 33.70  | Wash, 2 chs. wide, 3 ft. deep, drains E.   |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.<br>Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  |
|        | T5N R6E<br>$\frac{1}{4}$<br>S30   S29<br>1959  |
|        | from which   |
|        | A palo verde, 8 ins. diam., bears N. 61° 38' E., 106 lks. dist., mkd. T5N R6E $\frac{1}{4}$ S29 BT.  |
|        | A palo verde, 8 ins. diam., bears S. 36° 24' W., 121 $\frac{1}{2}$ lks. dist., mkd. T5N R6E $\frac{1}{4}$ S30 BT.  |
|        | Cont. over rolling land, through dense timber and undergrowth.   |
| 59.58  | Unimproved road, bears E. and W.   |
| 78.54  | Wash, 20 lks. wide, 2 ft. deep, drains E.  |
| 80.00  | Point for the cor. of secs. 19, 20, 29 and 30.<br>Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground to solid rock, with a collar of stone, 2 $\frac{1}{2}$ ft. diam., 8 ins. high, with brass cap mkd. |
|        | T5N R6E<br>S19   S20<br>S30   S29<br>1959  |
|        | from which   |

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

## Chains

A mesquite, 6 ins. diam., bears N. 58° 20' E., 81 lks. dist., mkd. T5N R6E S20 BT.

A palo verde, 6 ins. diam., bears S. 72° 26' E., 176 lks. dist., mkd. T5N R6E S29 BT.

A palo verde, 8 ins. diam., bears S. 81° 18' W., 269 lks. dist., mkd. T5N R6E S30 BT.

A palo verde, 8 ins. diam., bears N. 67° 43' W., 124 lks. dist., mkd. T5N R6E S19 BT.

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, palo verde and mesquite.

Undergrowth, black brush, cactus, yucca and creosote bush.

S. 89° 55' W., bet. secs. 19 and 30.

Over rolling land, through medium heavy timber and undergrowth.

5.10 Wash, 20 lks. wide, 2 ft. deep, drains SE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 30.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T5N R6E

$\frac{1}{4}$  S19

S30

1959

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of iron post.

from which

A palo verde, 6 ins. diam., bears N. 15° 55' W., 71 lks. dist., mkd. T5N R6E  $\frac{1}{4}$  S19 BT.

A palo verde, 8 ins. diam., bears S. 17° 46' E., 113 lks. dist., mkd. T5N R6E  $\frac{1}{4}$  S30 BT.

Cont. over rolling land, through medium dense timber and undergrowth.

48.90 Wash, 20 lks. wide, 2 ft. deep, drains S. 70° E.

79.74 Four-strand barbed wire fence with steel fence posts, bears N. and S.

79.86 The original cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp., which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, palo verde and mesquite.

Undergrowth, black brush, cactus, yucca and creosote bush.

From the cor. of secs. 19, 20, 29 and 30.

N. 0° 03' W., bet. secs. 19 and 20.

Over gently rolling land, through heavy timber and undergrowth.



Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

|        |   |
|--------|---|
| Chains |   |
| 9.60   | Wash, 20 lks. wide, 2 ft. deep, drains E.   |
| 20.30  | Four-strand barbed wire fence, bears E. and W.  |
| 21.20  | Wash, 25 lks. wide, 2 ft. deep, drains S. 50° E.  |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.<br>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.<br><br>T5N R6E<br>$\frac{1}{4}$<br>S19   S20<br>1959<br><br>from which<br><br>A palo verde, 6 ins. diam., bears S. 57° 00' W., 57 lks. dist., mkd. T5N R6E $\frac{1}{4}$ S19 BT.<br><br>A palo verde, 10 ins. diam., bears S. 64° 43' E., 200 lks. dist., mkd. T5N R6E $\frac{1}{4}$ S20 BT.<br><br>Cont. over rolling land, through heavy timber and undergrowth.   |
| 41.00  | Wash, 20 lks. wide, 1 ft. deep, drains E.   |
| 49.40  | Wash, 20 lks. wide, 2 ft. deep, drains E.   |
| 60.00  | Wash, 100 lks. wide, 1 ft. deep, drains E.  |
| 63.40  | Wash, 100 lks. wide, 1 ft. deep, drains E.  |
| 78.00  | Wash, 20 lks. wide, 2 ft. deep, drains E.   |
| 80.00  | Point for the cor. of secs. 17, 18, 19 and 20.<br>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.<br><br>T5N R6E<br>S18   S17<br>S19   S20<br>1959<br><br>from which<br><br>A palo verde, 6 ins. diam., bears N. 89° 12' E., 230 lks. dist., mkd. T5N R6E S17 BT.<br><br>A palo verde, 6 ins. diam., bears S. 30° 33' E., 180 lks. dist., mkd. T5N R6E S20 BT.<br><br>A palo verde, 8 ins. diam., bears S. 25° 21' W., 40 lks. dist., mkd. T5N R6E S19 BT.<br><br>A palo verde, 6 ins. diam., bears N. 7° 56' W., 150 lks. dist., mkd. T5N R6E S18 BT.<br><br>Land, rolling, cut by numerous washes.<br>Soil, sandy and gravelly clay loam.<br>Timber, palo verde and mesquite.<br>Undergrowth, saguaro, mesquite, palo verde, Spanish bayonet, yucca, cholla and ocotillo. |

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

Chains

S. 89° 59' W., bet. secs. 18 and 19.

Over rolling land, through medium dense timber and undergrowth.

5.90 Wash, 20 lks. wide, 1½ ft. deep, drains S. 35° E.

22.40 Wash, 70 lks. wide, 2 ft. deep, drains SE.

40.00 Point for the ¼ sec. cor. of secs. 18 and 19.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T5N R6E

¼ S18

S19

1959

from which

A palo verde, 6 ins. diam., bears N. 34° 13' E., 117 lks. dist., mkd. T5N R6E ¼ S18 BT.

A palo verde, 8 ins. diam., bears S. 19° 48' W., 391 lks. dist., mkd. T5N R6E ¼ S19 BT.

Cont. over rolling land, through medium heavy timber and undergrowth.

74.50 Wash, 40 lks. wide, 2½ ft. deep, course ESE. from SW.

78.70 Same wash, 20 lks. wide, 2½ ft. deep, drains S. 85° E.

79.95 The original cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., which is monumented with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

Land, gently rolling.

Soil, sandy and gravelly clay loam.

Timber, palo verde.

Undergrowth, cactus, yucca, cholla, saguaro, mesquite, ocotillo and desert sage.

From the cor. of secs. 17, 18, 19 and 20.

N. 0° 03' W., bet. secs. 17 and 18.

Over rolling land, through heavy timber and undergrowth.

8.90 Unimproved road, bears NW. and SE.

22.30 Wash, 25 lks. wide, 2 ft. deep, drains S. 70° E.

40.00 Point for the ¼ sec. cor. of secs. 17 and 18.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T5N R6E

¼

S18 | S17

1959

from which

A palo verde, 6 ins. diam., bears N. 24° 07' E., 350 lks. dist., mkd. T5N R6E ¼ S17 BT.

Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

Chains

A palo verde, 8 ins. diam., bears N. 88° 46' W., 488 lks. dist.,  
mkd. T5N R6E  $\frac{1}{4}$  S18 BT.

Cont. over rolling land, through heavy timber and undergrowth.

57.90 Wash, 35 lks. wide, 3 ft. deep, drains E.

79.20 Five-strand barbed wire fence, bears E. and W.

80.00 Point for the cor. of secs. 7, 8, 17 and 18.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground,  
with brass cap mkd.

|         |     |
|---------|-----|
| T5N R6E |     |
| S7      | S8  |
| S18     | S17 |
| 1959    |     |

from which

A palo verde, 6 ins. diam., bears N. 33° 55' E., 69 lks. dist.,  
mkd. T5N R6E S8 BT.

A palo verde, 4 ins. diam., bears S. 43° 21' E., 184 lks. dist.,  
mkd. T5N R6E S17 BT.

A palo verde, 6 ins. diam., bears S. 26° 30' W., 240 lks. dist.,  
mkd. T5N R6E S18 BT.

A palo verde, 6 ins. diam., bears N. 62° 33' W., 93 lks. dist.,  
mkd. T5N R6E S7 BT.

Land, rolling to nearly flat.

Soil, sandy and gravelly.

Timber, palo verde and mesquite.

Undergrowth, barrel cactus, prickly pear, yucca, saguaro, mesquite,  
Spanish bayonet, cholla and palo verde.

S. 89° 57' W., bet. secs. 7 and 18.

Over rolling land; through heavy timber and undergrowth.

8.10 Low spur, slopes S.; desc. over gradual W. slope.

13.10 Bottom of slope, thence over gently rolling land.

21.60 Wash, 75 lks. wide, 1 ft. deep, drains S.

37.78 Unimproved road, bears N. and S.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 18.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground  
with brass cap mkd.

|                  |  |
|------------------|--|
| T5N R6E          |  |
| $\frac{1}{4}$ S7 |  |
| S18              |  |
| 1959             |  |

from which

A mesquite, 6 ins. diam., bears N. 84° 55' W., 49½ lks. dist.,  
mkd. T5N R6E  $\frac{1}{4}$  S7 BT.

A palo verde, 6 ins. diam., bears S. 23° 02' W., 93 lks. dist.,  
mkd. T5N R6E  $\frac{1}{4}$  S18 BT.

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

Chains

Asc. 100 ft. over nearly flat E. slope, through timber and undergrowth to W. bdy. of Tp.

79.75

The original cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., which is monumented with an iron post, 2 ins. diam., firmly set in ground, mkd. and witnessed as described in the official record.

Land, gently rolling to flat.

Soil, sandy and gravelly clay loam.

Timber, palo verde.

Undergrowth, cholla, ocotillo, mesquite, Spanish dagger and yucca.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 03' W., bet. secs. 7 and 8.

Over gently rolling land, through medium heavy timber and undergrowth.

28.30 Wash, 20 lks. wide, 1 ft. deep, drains SE.

32.40 Wash, 15 lks. wide, 3 ft. deep, drains SSE.

38.30 Wash, 20 lks. wide, 1 ft. deep, drains S, 80° E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 8.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T5N R6E

$\frac{1}{4}$

S7|S8

1959

from which

A palo verde, 6 ins. diam., bears N. 56° 07' E., 290 lks. dist., mkd. T5N R6E  $\frac{1}{4}$  S8 BT.

A palo verde, 6 ins. diam., bears N. 79° 00' W., 115 $\frac{1}{2}$  lks. dist., mkd. T5N R6E  $\frac{1}{4}$  S7 BT.

Cont. over rolling land, through medium heavy timber and undergrowth.

43.50 Wash, 20 lks. wide, 1 ft. deep, drains S. 30° E.

65.50 Unimproved road, bears E. and W.

71.70 Wash, 20 lks. wide, 2 ft. deep, drains E.

80.00 Point for the cor. of secs. 5, 6, 7 and 8.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T5N R6E

S6|S5

S7|S8

1959

from which

A palo verde, 8 ins. diam., bears N. 22° 58' E., 38 lks. dist., mkd. T5N R6E S5 BT.

A palo verde, 6 ins. diam., bears S. 72° 15' E., 48 lks. dist., mkd. T5N R6E S8 BT.

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

Chains

A palo verde, 6 ins. diam., bears S. 5° 27' W., 112 lks. dist., mkd. T5N R6E S7 BT.

A palo verde, 6 ins. diam., bears N. 19° 10' W., 92 lks. dist., mkd. T5N R6E S6 BT.

Land, gently rolling.

Soil, sandy and gravelly clay loam.

Timber, palo verde and mesquite.

Undergrowth, mesquite, cactus, yucca and black brush.

N. 89° 59' W., bet. secs. 6 and 7.

Over rolling land, through medium heavy timber and undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 7.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T5N R6E

$\frac{1}{4}$   $\frac{S}{S}$   $\frac{6}{7}$

1959

from which

A palo verde, 6 ins. diam., bears N. 3° 20' W., 87 lks. dist., mkd. T5N R6E  $\frac{1}{4}$  S6 BT.

A palo verde, 4 ins. diam., bears S. 53° 29' E., 226 lks. dist., mkd. T5N R6E  $\frac{1}{4}$  S7 BT.

Cont. over rolling land, through medium heavy timber and undergrowth.

40.56 Unimproved road, bears N. and S.

62.20 Wash, 10 lks. wide, 2 ft. deep, drains SE.

72.20 Wash, 10 lks. wide, 1 ft. deep, drains S. 80° E.

79.72 The original cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., which is monumented with an iron post, 2 ins. diam., firmly set in earth, mkd. and witnessed as described in the official record.

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, palo verde and mesquite.

Undergrowth, cactus, yucca, cholla, saguaro, mesquite, ocotillo and desert sage.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 03' W., bet. secs. 5 and 6.

Over gently rolling land, through heavy timber and undergrowth.

19.48 Wash, 40 lks. wide, 1 ft. deep, drains E.

20.50 Small spur, slopes E.

23.20 Wash, 100 lks. wide, 2 ft. deep, drains E.; asc. over rather gradual S. slope.

## Survey of a Portion of the Subdivision of T. 5 N., R. 6 E.

Chains  
40.00Point for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 6.Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T5N R6E

 $\frac{1}{4}$ 

S6 | S5

1959

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Desc. 15 ft. over N. slope.

44.35 Small draw, drains E.; asc. 30 ft. over S. slope.

46.15 Small spur, slopes E.; desc. 30 ft. over N. slope.

56.47 Wash, 20 lks. wide, 1 ft. deep, drains E.; asc. 50 ft. over S. slope.

58.70 Spur, slopes E.; desc. 35 ft. over N. slope.

60.17 Small draw, drains SE.; asc. 40 ft. over rolling S. slope.

64.50 Flat rolling spur, slopes E.; desc. 35 ft. over N. slope.

75.84 Main wash, 30 lks. wide, 2 ft. deep, drains E.; asc. 40 ft. over SE. slope.

80.05 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.

Land, rolling to broken.

Soil, sandy and gravelly clay loam.

Timber, palo verde and mesquite.

Undergrowth, yucca, black brush and mesquite.

## General Description

The area included in this survey lies entirely within the Tonto National Forest. The west and south boundaries of the township constitute portions of the west and south boundaries of the National Forest.

The area covered by this survey is generally flat or gently rolling, and slopes eastward at the rate of 100 to 200 feet per mile, towards the Verde River, which flows southward through the next township to the east. Elevations over the area vary from about 1,800 feet above sea level along the east boundary of section 35 to about 2,700 feet above sea level at the northwest corner of section 6.

The entire area is forested with a more or less dense growth of non-commercial desert trees such as palo verde, mesquite and saguaro. There is also a general cover of undergrowth, which becomes quite dense in favored areas. Undergrowth generally consists of desert plants such as cactus, scrub palo verde, mesquite, yucca, Spanish dagger, desert sage, cholla, ocotillo, scrub saguaro, catclaw and acacia, as well as various desert grasses and annuals such as sego lily and wild poppy.

There are no settlers living within the area covered by this survey and the only improvements consist of a considerable mileage of fencing to control stock grazing distribution, and fairly numerous roads, mostly unimproved, and a stock watering reservoir of several acres situated in the SW $\frac{1}{4}$ NW $\frac{1}{4}$  of section 32. The area is principally used for stock grazing, with watershed protection and erosion control by the U. S. Forest Service.

4-680  
(Feb., 1950)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| NAMES               | CAPACITY      |
|---------------------|---------------|
| Dee Von Thompson    | Survey Aid    |
| Darrell D. Holbrook | Head Chainman |
| Lynn S. Griffin     | Notekeeper    |
| Jeddie J. Judd      | Flagman       |
|                     |               |
|                     |               |
|                     |               |
|                     |               |
|                     |               |
|                     |               |
|                     |               |
|                     |               |
|                     |               |
|                     |               |
|                     |               |
|                     |               |
|                     |               |

**CERTIFICATE OF CADASTRAL ENGINEER**

I, Horace G. Parker, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11th day of August, 1959 of a portion I have ~~surveyed~~ made a dependent resurvey/ of the First Standard Parallel North and surveyed a portion of the north boundary and a portion of the subdivision of T. 5 N., R. 6 E.

of the Gila & Salt Riv. Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah

January 5, 1960

*Horace G. Parker*

Horace G. Parker  
Cadastral Surveyor

**CERTIFICATE OF APPROVAL**

BUREAU OF LAND MANAGEMENT,

Washington, D. C., FEB 10 1960, 1960

The foregoing field notes of the ~~survey of~~ dependent resurvey of a portion of the First Standard Parallel North, and survey of a portion of the north boundary and a portion of the subdivision of T. 5 N., R. 6 E., Gila and Salt River Meridian, Arizona

executed by Horace G. Parker, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

*Donald Clement*

Chief, Division of Cadastral Engineering.  
Cadastral Engineering Staff Officer

**CERTIFICATE OF TRANSCRIPT**

I CERTIFY that the foregoing ~~transcript~~ of the field notes of the above-described surveys in T. 5 N., R. 6 E., G. & S. R. M., Ariz., is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.