

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

RESURVEY OF A PORTION OF THE

NINTH STANDARD PARALLEL NORTH IN R. 5 W.

THE EAST BOUNDARY

A PORTION OF THE SOUTH BOUNDARY

AND THE SURVEY OF THE SUBDIVISION OF

TOWNSHIP 36 NORTH, RANGE 5 WEST

Of the *Gila and Salt River* *Meridian,*

In the State of *Arizona*

EXECUTED BY

.....
Robert C. Yundt, Cadastral Surveyor (Chief of Party)

.....
Donald A. Cannon, Cadastral Surveyor

Under special instructions dated *October 9*, *1958*, *which provided*
for the surveys included under Group No. *329*, *approved* *October 13, 1958*
and assignment instructions dated *October 28*, *1958*

Survey commenced *November 3*, *1958*

Survey completed *December 12*, *1958*

1A

BOOK 4573

INDEX DIAGRAM

Township 36 North, Range 5 West

48 6	48 47 5	38 37 4	30 30 3	22 21 2	14 13 1 5
46 7	46 45 8	37 36 9	29 28 10	21 20 11	13 12 12 5
45 18	44 44 17	35 34 16	27 27 15	19 19 14	11 11 13 4
43 19	43 42 20	34 33 21	26 25 22	18 17 23	10 9 24 3
41 30	41 40 29	32 32 28	25 24 27	17 16 26	8 8 25 2
40 31 6	39 38 32	31 31 33	23 22 34	15 15 35	7 7 36 2

Township 36 North, Range 5 West

Chains

The east and south boundaries were surveyed by Horace G. Parker in 1954. The west boundary was surveyed by Walter H. Good in 1933. The north boundary (Ninth Standard Parallel North) was surveyed by T. B. Matthews in 1915.

The following field notes are those of the resurvey of the east boundary, a portion of the north boundary (Ninth Standard Parallel North), a portion of the south boundary, and the survey of the subdivision of T. 36 N., R. 5 W.

The survey was executed with a W. & L. E. Gurley Transit No. 541331 constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition prior to the beginning of the survey and was maintained in proper adjustment throughout the progress of the survey.

The directions of all lines herein reported were established by observations upon the sun and Polaris, taken at intervals throughout the survey.

Corners on east-west lines were set on the true latitudinal curve. Lines connecting previously established corners were run by random and true method, but for simplification of the record the random lines are omitted from the field notes. In accordance with the intent of the special instructions, all subdivisional corners established are calculated to be at the position they would occupy if the entire township were subdivided.

Measurements herein contained were made with a narrow steel tape, 8 chains in length, graduated every link for the first 100 links and thereafter at intervals of 10 links. The tape was tested by comparison with a 1 chain standard steel tape and found to be correct. Measurements were made on the slope with the vertical angle of each interval ascertained by a clinometer in good adjustment; horizontal equivalents alone are entered in the field notes. All lines of this survey were run by direct method where the lines were accessible; lines inaccessible were run by traverse or triangulation methods. Distances to topography on lines run by traverse or triangulation are approximately as scaled from U. S. G. S. topographic sheets. The details of such traverses or triangulations have been thoroughly checked and verified and in order to simplify the record the diagrams and reductions are omitted from these field notes.

The direction of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris or altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other numerous altitude observations on the sun taken throughout the progress of the survey.

The geographic position for the southeast corner of the township is at latitude $36^{\circ} 28' 12''$ N. and longitude $112^{\circ} 46' 12''$ W., as adjusted from traverses to U. S. G. S. triangulation stations within the area.

The magnetic declination was read at a number of stations throughout the township and the average of these readings was found to be $14^{\circ} 45'$ East.

Dependent Resurvey of the West Boundary of T. 36 N., R. 4 W.

Reestablishment of the survey executed by Horace G. Parker, Cartographer-Cadastral in 1954.

Beginning at the cor. of Tps. 35 and 36 N., Rs. 4 and 5 W., an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

Dependent Resurvey of the West Boundary of T. 36 N., R. 4 W.

Chains	
	N. 1° 01' W., bet. secs. 31 and 36.
	Over gently rolling land, through heavy undergrowth.
.30	Road, bears NE. and SW.
20.00	Enter scattered timber.
35.00	Low spur from ridge, slopes NE.
40.01	The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	<hr/>
	N. 0° 02' W., beginning new measurement.
5.00	Leave scattered timber.
18.80	Road, bears NE. and SW.
19.60	Road, bears NE. and SW.
25.50	Wash, 10 lks. wide, 3 ft. deep, drains SE.
31.70	Wash, 10 lks. wide, 2 ft. deep, drains SE.
32.20	Road, bears E. and W.
40.02	The cor. of secs. 25, 30, 31 and 36, an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	Land, gently rolling.
	Soil, sandy and gravelly clay loam.
	Timber, scattered juniper and pinon.
	Undergrowth, sagebrush and mountain holly.
	<hr/>
	N. 0° 01' W., bet. secs. 25 and 30.
	Over gently rolling land, through scattered timber and heavy undergrowth.
15.00	Low spur from ridge, slopes W.; enter heavy timber; desc. 20 ft. over gradual N. slope.
29.00	Wash, 10 lks. wide, 2 ft. deep, drains NE.; asc. gradual S. slope.
39.80	Spur, slopes E.
40.02	The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	<hr/>
	N. 0° 05' E., beginning new measurement.
	Desc. 20 ft. over N. slope.
5.10	Base of descent; thence over gently rolling land.
10.70	Low spur, slopes E.
13.00	Small wash, drains E.
17.90	Begin ascent; asc. 80 ft. over S. slope.

Dependent Resurvey of the West Boundary of T. 36 N., R. 4 W.

Chains	
22.60	Spur, slopes E.
24.30	Begin descent; desc. 25 ft. over N. slope.
26.30	Small wash, drains NE.
31.00	Fence, 4-strand barbed wire, bears E. and W.
40.03	The cor. of secs. 19, 24, 25 and 30, an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.
	Land, low and rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	N. 0° 02' W., bet. secs. 19 and 24. Over rolling land, through heavy timber.
7.50	Begin descent; desc. 50 ft. over NW. slope.
10.50	Wash, 10 lks. wide, 2 ft. deep, drains NE.; asc. 70 ft. over SE. slope.
22.50	Spur, slopes E.; desc. 30 ft. over NNE. slope.
26.50	Base of descent; asc. 25 ft. over gradual S. slope.
40.00	Point for the ¼ sec. cor. of secs. 24, T. 36 N., R. 5 W. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone to top, 3 ft. base, with brass cap mkd.
	T36N ¼ S24 R5W 1958
40.16	The ¼ sec. cor. of secs. 19 and 24, an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record. Remarked for the ¼ sec. cor of sec. 19 only.
	N. 0° 05' W., beginning new measurement. Desc. 15 ft. over gradual N. slope.
24.90	Begin steeper descent; desc. 270 ft. over N. slope.
38.70	Wash, 25 lks. wide, .5 ft. deep, drains E.
39.84	Point for the cor. of secs. 13 and 24, T. 36 N., R. 5 W. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36S S13 S24 R5W 1958

Dependent Resurvey of the West Boundary of T. 36 N., R. 4 W.

Chains	
40.00	The witness cor. of secs. 13, 18, 19 and 24, an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record. I remark this cor. to function for secs. 18 and 19, T. 36 N., R. 4 W. only.
40.15	True point for the cor. of secs. 18 and 19. Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and mountain holly.
	N. 0° 05' W., bet. secs. 13 and 18. Over rolling land, through scattered timber and heavy undergrowth; asc. 140 ft. over S. slope.
12.30	Enter heavy timber.
15.60	Low ridge, bears E. and W.; road on top of ridge, bears E. and W.; desc. 100 ft. over N. slope.
26.10	Wash, 10 lks. wide, 2 ft. deep, drains NE.
28.00	Wash, 10 lks. wide, 3 ft. deep, drains E.; asc. 120 ft. over S. slope.
39.22	The ¼ sec. cor. of secs. 13 and 18, an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record. I remark for sec. 18 only.
	N. 0° 05' W., beginning new measurement.
.30	Point for the ¼ sec. cor. of sec. 13, T. 36 N., R. 5 W. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N ¼ S13 R5W 1958
	Cont. over ; rolling land.
8.70	Spur, slopes E.; desc. 15 ft. over N. slope.
14.00	Base of descent; asc. 15 ft. over S. slope.
17.60	Top of ascent; slopes E.
26.60	Begin descent; desc. 235 ft. over NE. slope.
36.10	Top of sandstone rim, 75 ft. high, bears NW. and E.; leave heavy timber, bears NW. and E.
37.50	Wash in bottom of gulch, 30 lks. wide, drains E.; asc. 50 ft. over S. slope.
40.12	The cor. of secs. 7, 12, 13 and 18, an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record. Land, rolling. Soil, gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush and mountain holly.

Dependent Resurvey of the W. Bdy. of T. 36 N., R. 4 W.

Chains	North, bet. secs. 7 and 12.
	Over rolling land, through scattered timber and heavy undergrowth; asc. 130 ft. along S. slope.
5.00	Spur, slopes E.; desc. 170 ft. along NE. slope.
15.30	Wash, 30 lks. wide, 2 ft. deep, drains E.
22.20	Wash, 20 lks. wide, 5 ft. deep, drains E.; asc. 30 ft. over S. slope.
34.30	Spur, slopes ENE.; desc. 80 ft. over N. slope.
39.98	The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	North, beginning new measurement.
	Desc. 70 ft. over N. slope.
2.10	Top of rim, 100 ft. high, bears NW. and SE.
9.70	Base of descent; asc. 140 ft. over S. slope.
19.90	Spur, slopes E.; desc. 40 ft. over N. slope.
25.30	Base of descent; asc. 70 ft. to cor.
39.90	Spur, slopes NE.
39.96	The cor. of secs. 1, 6, 7 and 12, an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	Land, rolling. Soil, gravelly clay loam. Timber, scattered juniper and pinon. Undergrowth, sagebrush.

Independent Resurvey of the West Boundary of T. 36 N., R. 4 W.

	Superseding the survey made by Horace G. Parker in 1954.
	North, bet. secs. 1 and 6.
	Desc. gradual N. slope, through scattered timber.
10.50	Top of S. rim of Hack's Canyon, bears NW. and SE.
	Thence by traverse, as line falls along the W. side of inaccessible canyon draining NNE. into Hack's Canyon.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6 is inaccessible. From this point the witness point bears N. 89° 39' W., 11.27 chs. dist., an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	Cont. by traverse.
77.60	Intersect the Ninth Standard Parallel North.
	The witness closing cor. of secs. 1 and 6 bears W. 7.01 chs. dist., an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.
	From this witness cor. the standard cor. of secs. 31 and 36 bears W. 3.48 chs. dist., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1915 survey.

Independent Resurvey of the West Boundary of T. 36 N., R. 4 W.

Chains

Land, broken and rolling.
Soil, gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

Dependent Resurvey of the Ninth Standard Parallel North in R. 5 W.

From the standard cor. of T. 37 N., Rs. 4 and 5 W., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

West, along the S. bdy. of sec. 36.

By triangulation, over broken mountainous land, through scattered timber and undergrowth; topography essentially the same as given in the official record and not recorded herein.

39.02 Proportionate point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, not monumented.

78.05 The standard cor. of secs. 35 and 36, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

Land, broken.
Soil, gravelly clay.
Timber, juniper and pinon.
Undergrowth, sagebrush.

Dependent Resurvey of a Portion of the North Boundary, T. 35 N., R. 5 W.

Reestablishment of the survey executed by Horace G. Parker in 1954.

Beginning at the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp.

S. $89^{\circ} 59'$ W., bet. secs. 6 and 31.

Over gently rolling land, through scattered timber.

20.30 Road, bears N. and S.

26.00 Leave scattered timber; bears NE. and SW.; enter railed area.

40.00 The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

41.90 Road, bears N. and S.; leave railed area.

53.60 Enter scattered pinon and juniper; edge bears N. and S.

78.10 The cor. of Tps. 35 and 36, Rs. 5 and 6 W., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

Land, gently rolling.
Soil, sandy and gravelly clay loam.
Timber, pinon and juniper.
Undergrowth, sagebrush.

Survey of the Subdivision of T. 36 N., R. 5 W.

Beginning the subdivisional survey at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

N. 0° 01' W., bet. secs. 35 and 36.

Over rolling land, through scattered timber and undergrowth.

1.00 Spur, slopes SE.; desc. 20 ft. over rolling land.

11.00 Spur, slopes SW.; desc. 30 ft. over NW. slope.

20.50 Gully, 10 lks. wide, 3 ft. deep, drains SW.; asc. 100 ft. over SE. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground in a mound of stone, 2 ft. base to top, with brass cap mkd.

T36N R5W

 $\frac{1}{4}$

S35 | S36

1958

Cont. over nearly level land.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

S26 | S25

S35 | S36

1958

Land, rolling to nearly level.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp. an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

S. 89° 54' W., bet. secs. 25 and 36.

Over gently rolling land, through scattered juniper and pinon.

Desc. 30 ft. over gradual SW. slope.

7.60 Small draw, drains SE.; asc. 75 ft. over gentle NE. slope.

39.32 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

 $\frac{1}{4}$

S25

S36

1958

Thence over nearly level land.

79.32 The cor. of secs. 25, 26, 35 and 36.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

Land, gently rolling to nearly level.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

N. 0° 01' W., bet. secs. 25 and 26.

Over nearly level land, through scattered timber and undergrowth.

15.60 Fence, 4-strand barbed wire, bears NE. and SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

$\frac{1}{4}$

S26|S25

1958

Thence over nearly level land.

42.00 Begin descent; desc. 60 ft. over N. slope.

53.60 Shallow draw, 9.00 chs. wide, drains NW.; asc. 40 ft. over SW. slope.

62.70 Spur, slopes NE.; desc. 40 ft. over gentle NW. slope.

78.00 Wash, 10 lks. wide, 1 ft. deep, drains W.; asc. 10 ft. over S. slope.

80.00 Point for the cor. of secs. 23, 24, 25 and 26.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36N R5W

S23|S24

S26|S25

1958

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, nearly level to rolling.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

S. 89° 52' W., bet. secs. 24 and 25.

Over rolling land, through scattered timber and undergrowth.

3.30 Ridge, bears NE. and SW.; desc. 30 ft. over NW. slope.

5.60 Wash, 10 lks. wide, 1 ft. deep, drains N.

14.30 Wash, 10 lks. wide, 1 ft. deep, drains NW.

23.30 Wash, 10 lks. wide, 1 ft. deep, drains N.

32.40 Wash, 5 lks. wide, 1 ft. deep, drains NE.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
36.80	Wash, 10 lks. wide, 1 ft. deep, drains NE.; asc. 40 ft. over SE. slope.
38.50	Ridge, bears SW. and NE.
39.40	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T36N R5W $\frac{1}{4}$ S24 S25 1958 Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor. Desc. 25 ft. over NW. slope.
44.30	Wash, 20 lks. wide, 2 ft. deep, drains NE.; asc. 40 ft. over E. slope.
51.30	Spur, slopes S.; desc. 20 ft. over W. slope.
54.50	Wash, 10 lks. wide, 2 ft. deep, drains N.; asc. 15 ft. over E. slope.
59.90	Top of ascent; desc. 70 ft. over W. slope.
79.40	The cor. of secs. 23, 24, 25 and 26. Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	N. $0^{\circ} 01'$ W., bet. secs. 23 and 24. Over rolling land, through light timber and undergrowth. Asc. 60 ft. over SE. slope.
11.90	Spur, slopes SW.; desc. 70 ft. over NW. slope.
32.20	Wash, 10 lks. wide, 2 ft. deep, drains NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 9 ins. in the ground to bedrock, in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd. T36N R5W $\frac{1}{4}$ S23 S24 1958
41.80	Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. 75 ft. over SW. slope.
60.00	Ridge, bears NW.
62.70	Road, bears SW. and NE.; desc. 35 ft. over N. slope.
71.50	Wash, 10 lks. wide, 2 ft. deep, drains NW.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
73.50	Road, bears NW. and SE.; asc. 10 ft. over S. slope.
80.00	Point for the cor. of secs. 13, 14, 23 and 24. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T36N R5W S14 S13 S23 S24 1958 Bury broken glass at base of post. Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	From the cor. of secs. 13 and 24, on the E. bdy. of the Tp., an iron post, 2½ ins. diam., set, mkd. and witnessed as previously described. S. 89° 54' W., bet. secs. 13 and 24. Over rolling land, through scattered timber and undergrowth. Asc. 40 ft. over NE. slope.
7.70	Wash, 30 lks. wide, 2 ft. deep, drains SE.; asc. 60 ft. over NE. slope.
10.80	Wash, 30 lks. wide, 2 ft. deep, drains NE.; asc. 15 ft. over NE. slope.
16.60	Spur, slopes S.; desc. 20 ft. over W. slope.
18.60	Wash, 5 lks. wide, 1 ft. deep, drains SE.; asc. 50 ft. over E. slope.
35.60	Spur, slopes S.; desc. 20 ft. over W. slope.
39.32	Point for the ¼ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd. T36N R5W ¼ S13 S24 1958
39.50	Wash, 10 lks. wide, 1 ft. deep, drains SE.; asc. 70 ft. over NE. slope.
45.90	Spur, slopes SE.; desc. 20 ft. over SW. slope.
52.80	Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. 20 ft. over E. slope.
63.00	Spur, slopes S.; desc. 15 ft. over W. slope.
64.60	Small wash, drains SE.
65.80	Small wash, drains SE.
72.20	Road, bears N. 25° E. and S. 25° W.
79.32	The cor. of secs. 13, 14, 23 and 24.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

Land, rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

N. 0° 01' W., bet. secs. 13 and 14.

Over rolling land, through scattered timber and undergrowth; asc. 35 ft. over S. slope.

12.00 Top of ascent; desc. 100 ft. over NW. slope.

38.30 Small wash, drains NW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

$\frac{1}{4}$
S14 | S13

1958

43.70 Wash, 15 lks. wide, 2 ft. deep, drains NE.; asc. 30 ft. over SE. slope.

49.00 Spur, slopes NE.; desc. 25 ft. over NW. slope.

53.90 Small wash, drains N. 25° E.; asc. 50 ft. over SE. slope.

61.00 Spur, slopes NE.; desc. 30 ft. over NW. slope.

65.70 Wash, 10 lks. wide, 1 ft. deep, drains NE.; asc. 90 ft. over S. slope.

77.50 Ridge, projects E.; desc. 15 ft. over N. slope.

80.00 Point for the cor. of secs. 11, 12, 13 and 14.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

S11 | S12

S14 | S13

1958

Land, rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

N. 89° 50' W., bet. secs. 12 and 13.

Over heavy rolling land, through scattered timber and undergrowth.

Asc. 70 ft. over rolling SE. slope.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
25.10	Ridge, projects NE.; road, bears NE. and SW.; desc. 90 ft. over NW. slope.
38.10	Small wash, drains SW.
39.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T36N R5W. $\frac{1}{4}$ $\frac{S12}{S13}$ 1958 Asc. 15 ft. over E. slope.
40.90	Spur, slopes S.; desc. 40 ft. over W. slope.
45.40	Wash, 10 lks. wide, 1 ft. deep, drains NW.; asc. 40 ft. over NE. slope.
57.60	Spur, slopes N.; desc. 120 ft. over W. slope.
68.00	Wash, 20 lks. wide, 2 ft. deep, drains N.; asc. 80 ft. over E. slope.
76.40	Top of ascent; desc. 20 ft. over W. slope.
79.07	The cor. of secs. 11, 12, 13 and 14. Land, rolling. Soil, gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	N. 0° 01' W., bet. secs. 11 and 12. Over sharp rolling land, through scattered timber and undergrowth. Desc. 10 ft. over NW. slope.
.60	Wash, 10 lks. wide, 1 ft. deep, drains NE.; asc. 30 ft. over SE. slope.
4.90	Spur, slopes NE.; desc. 30 ft. over NW. slope.
12.10	Wash, 10 lks. wide, 1 ft. deep, drains N. 65° E.; asc. 60 ft. over S. slope.
18.90	Spur, slopes E.; desc. 40 ft. over N. slope.
37.90	Wash, 10 lks. wide, 2 ft. deep, drains E.; asc. 10 ft. over S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam, 22 ins. in the ground, with brass cap mkd. T36N R5W $\frac{1}{4}$ S11 S12 1958 Asc. 20 ft. over S. slope.
41.30	Spur, slopes E.; desc. 25 ft. over N. slope.
56.40	Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. 120 ft. over S. slope.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains 67.70	Spur, slopes E.; desc. 30 ft. over N. slope.
80.00	Point for the cor. of secs. 1, 2, 11 and 12. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T36N R5W S2 S1 S11 S12 1958 </div> Land, rolling. Soil, gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
14.80	From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp., an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record. N. 89° 51' W., bet. secs. 1 and 12. Over sharp rolling land, through scattered timber and undergrowth. Desc. 50 ft. over W. slope.
24.00	Wash, 10 lks. wide, 2 ft. deep, drains N. 25° E.; asc. 110 ft. over E. slope.
38.86	Ridge, bears N. and S.; desc. 150 ft. over W. slope. Point for the ¼ sec. cor. of secs. 1 and 12. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T36N R5W ¼ S 1 S12 1958 </div> Desc. 20 ft. over W. slope.
41.00	Wash, 10 lks. wide, 2 ft. deep, drains NW.; asc. 50 ft. over NE. slope.
57.80	Spur, slopes NW.; desc. 70 ft. over SW. slope.
66.70	Wash, 20 lks. wide, 2 ft. deep, drains NE.; asc. 180 ft. over steep SE. slope.
75.20	Top of steep ascent; asc. 20 ft. over gradual SE. slope.
78.86	The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	N. 0° 01' W., bet. secs. 1 and 2.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

Over sharp rolling land, through scattered timber and undergrowth.

6.50 Begin descent; desc. 180 ft. over steep NW. slope.

26.60 Wash, 15 lks. wide, 2 ft. deep, drains NE.; asc. 40 ft. over S. slope.

32.70 Spur, slopes E.; desc. 30 ft. over N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, in a mound of stone to top, 3 ft. base, with brass cap mkd.

T36N R5W

$\frac{1}{4}$

S2|S1

1958

Begin ascent; asc. 145 ft. over S. slope.

45.20 Spur; slopes E.; desc. 50 ft. over N. slope.

55.90 Wash, 5 lks. wide, 1 ft. deep, drains W.; asc. 40 ft. over S. slope.

57.90 Top of ascent; desc. 75 ft. over N. slope.

77.46 Intersect the Ninth Standard Parallel North.

Point for the closing cor. of secs. 1 and 2.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone, 5 ft. base to top, with brass cap mkd.

T37N R5W

S36

S2|S1

T36N R5W

C C

1958

From this closing cor. the standard cor. of secs. 35 and 36 bears W. 9.37 chs. dist., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

Land, rolling.

Soil, gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

True point for the N. $\frac{1}{4}$ sec. cor. of sec. 1 is on the Ninth Standard Parallel North and at an easting of 40.00 chs. from the closing cor. of secs. 1 and 2; falls in small wash and cannot be perpetuated.

Point selected for the witness $\frac{1}{4}$ sec. cor. of sec. 1 bears W. 1.82 chs. dist.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

WC $\frac{1}{4}$ S1

T36N R5W

1958

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

From the true point for the N. $\frac{1}{4}$ sec. cor. of sec. 1 the standard $\frac{1}{4}$ sec. cor. of sec. 36 bears West 10.34 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp., an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record.

N. 0° 01' W., bet. secs. 34 and 35.

Over rolling land, through scattered juniper and pinon.

1.10 Wash, 10 lks. wide, 1 ft. deep, drains SW.

2.70 Fence, 4-strand barbed wire, bears NE. and SW.; asc. 90 ft. over SE. slope.

15.80 Spur, slopes S. 25° W.; desc. 80 ft. over NW. slope.

25.70 Wash, 5 lks. wide, 1 ft. deep, drains NW.; asc. 90 ft. over NW. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R5W

$\frac{1}{4}$
S34|S35
1958

Bury charcoal alongside the post.

Cont. over rolling land.

66.00 Small wash, drains NW.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R5W

S27|S26
S34|S35
1958

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

From the cor. of secs. 25, 26, 35 and 36.

S. 89° 58' W., bet. secs. 26 and 35.

Over rolling land, through scattered timber and undergrowth; desc. 40 ft. over NW. slope.

9.00 Wash, 15 lks. wide, 2 ft. deep, drains SW.

16.20 Fence, 4-strand barbed wire, bears NE. and SW.; desc. 70 ft. over rolling SW. slope.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T36N R5W $\frac{1}{4}$ $\frac{S26}{S35}$ 1958 Bury charcoal alongside the post. Cont. over rolling land.
49.10	Wash, 10 lks. wide, 2 ft. deep, drains NW.; asc. 75 ft. over NE. slope.
58.70	Spur, slopes NW.; desc. 75 ft. over SW. slope.
71.00	Wash, 10 lks. wide, 2 ft. deep, drains NW.; asc. 30 ft. over NE. slope.
80.00	The cor. of secs. 26, 27, 34 and 35. Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	N. $0^{\circ} 01'$ W., bet. secs. 26 and 27. Over rolling land, through moderate timber and undergrowth; desc. 80 ft. over N. 25° E. slope.
16.10	Wash, 20 lks. wide, 1 ft. deep, drains W.; asc. 40 ft. over S. slope.
29.50	Spur, slopes SW.; cont. ascent of 35 ft. over SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, in a mound of stone, 3 ft. base to top, with brass cap mkd. T36N R5W $\frac{1}{4}$ $\frac{S27}{S26}$ 1958 Asc. 10 ft. over SE. slope.
42.00	Spur, slopes SW.; desc. 30 ft. over N. slope.
47.30	Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. 50 ft. over SSE. slope.
52.60	Spur, slopes SW., thence along W. slope.
71.70	Begin descent; desc. 70 ft. over N. slope.
78.90	Wash, 15 lks. wide, 2 ft. deep, drains SW.; asc. 20 ft. over SE. slope.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

T36N R5W
 S22|S23
 S27|S26
 1958

Land, rolling.
 Soil, sandy and gravelly clay loam.
 Timber, juniper and pinon.
 Undergrowth, sagebrush.

From the cor. of secs. 23, 24, 25 and 26.

S. 89° 56' W., bet. secs. 23 and 26.

Over rolling land, through moderate timber, and undergrowth; asc. 10 ft. over E. slope.

- 4.80 Small spur, slopes S.; desc. 60 ft. over W. slope.
- 32.00 Reservoir, bears N. 2.50 chs. dist., 110 ft. dist., thence over nearly level land.
- 33.40 Road, bears NW. and SE.
- 40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T36N R5W
 $\frac{1}{4}$ S23
 S26
 1958
- Bury broken glass alongside the post.
- Cont. over nearly level land.
- 50.60 Road, bears N. and S.; asc. 20 ft. over gradual NE. slope.
- 59.10 Small ridge, projects NW.; desc. 110 ft. over SW. slope.
- 80.02 The cor. of secs. 22, 23, 26 and 27.

Land, rolling.
 Soil, sandy and gravelly clay loam.
 Timber, juniper and pinon.
 Undergrowth, sagebrush.

N. 0° 01' W., bet. secs. 22 and 23.

Over rolling land, through moderate timber and heavy undergrowth; asc. 70 ft. over S. slope.

- 9.00 Ridge spur, projects W.
- 9.90 Road, bears NE. and SW. 1.00 ch., thence W.; desc. 20 ft. over N. slope.
- 11.10 Wash, 10 lks. wide, 1 ft. deep, drains NE.
- 11.70 Head of spur, slopes W.; thence over nearly level land.
- 19.10 Road, bears NE. and SW.; begin descent; desc. 30 ft. over gradual N. slope.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R5W $\frac{1}{4}$ S22 S23 1958</p> <p>Bury broken glass alongside the post.</p> <p>Cont. over nearly level land.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock; in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T36N R5W S15 S14 S22 S23 1958</p> <p>Land, rolling to nearly level. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling land, through dense timber and undergrowth; desc. 30 ft. over SW. slope.</p>
10.50	Wash, 10 lks. wide, 1 ft. deep, drains NW.; thence over rolling land.
25.90	Road, bears NW. and SE.
34.90	Wash, 15 lks. wide, 2 ft. deep, drains N. 80° W.
39.94	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T36N R5W $\frac{1}{4}$ S14 S23 1958</p>
	Desc. 90 ft. over W. slope.
72.30	Road, bears N. and S.
75.20	Wash, 10 lks. wide, 1 ft. deep, drains N.; asc. 20 ft. over E. slope.
79.88	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.</p>

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

N. 0° 01' W., bet. secs. 14 and 15.

Over rolling land, through scattered timber and undergrowth; desc. 30 ft. over rolling N. slope.

36.00 Small wash, drains NNW.; thence over nearly level land.

39.70 Road, bears NNW. and SSE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R5W

$\frac{1}{4}$
S15|S14
1958

Bury broken glass alongside the post.

Cont. over low rolling land with numerous small washes and spurs, draining northerly.

49.80 Road, bears NNE. and SSW.

58.90 Road, bears NNW. and SSE.

73.10 Reservoir, 100 ft. diam.; asc. 10 ft. over S. slope.

80.00 Point for the cor. of secs. 10, 11, 14 and 15.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

S10|S11
S15|S14
1958

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon;

Undergrowth, sagebrush.

From the cor. of secs. 11, 12, 13 and 14.

N. 89° 54' W., bet. secs. 11 and 14.

Over rolling land, through scattered timber and undergrowth; desc. 10 ft. over NW. slope.

1.40 Wash, 10 lks. wide, 2 ft. deep, drains ENE.; asc. 70 ft. over SE. slope.

12.30 Spur, slopes NNE.; desc. 30 ft. over NW. slope.

20.20 Wash, 10 lks. wide, 2 ft. deep, drains NE.; asc. 30 ft. over NE. slope.

23.00 Ridge, bears NW. and SE.; desc. 70 ft. over SW. slope.

39.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

T36N R5W

$$\frac{1}{4} \frac{S11}{S14}$$
 1958

Desc. 30 ft. over W. slope.

47.00 Wash, 5 lks. wide, 1 ft. deep, drains SW.

48.50 Road, bears NNE. and SSW.

51.70 Small wash, drains SE.; asc. 25 ft. over E. slope.

63.50 Spur, slopes S.; desc. 80 ft. over W. slope.

73.10 Small wash, drains SW.; asc. 30 ft. over E. slope.

79.94 The cor. of secs. 10, 11, 14 and 15.

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

N. 0° 01' W., bet. secs. 10 and 11.

Over rolling land, through scattered timber and undergrowth; asc. 90 ft. over SW. slope.

15.30 Spur, slopes NW.; desc. 60 ft. over rolling N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.

T36N R5W

$$\frac{1}{4} \frac{S10|S11}{S14}$$
 1958

40.40 Wash, 10 lks. wide, 2 ft. deep, drains NE.; asc. 30 ft. over S. slope.

48.00 Top of ascent; desc. 30 ft. over N. slope.

52.50 Wash, 10 lks. wide, 1 ft. deep, drains W.; asc. 160 ft. over SW. slope.

78.00 Ridge, bears NW. and SE.; desc. 20 ft. over NE. slope.

80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

$$\frac{S3|S2}{S10|S11}$$
 1958

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	From the cor. of secs. 1, 2, 11 and 12. N. 89° 54' W.; bet. secs. 2 and 11. Over rolling land, through scattered timber and undergrowth; asc. 15 ft. over E. slope.
3.50	Top of ascent; desc. 20 ft. over W. slope.
8.50	Small wash, drains N.; asc. 30 ft. over E. slope.
15.90	Top of ascent; desc. 20 ft. over W. slope.
32.00	Base of descent; asc. 20 ft. over E. slope.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T36N R5W $\frac{1}{4}$ S 2 S11 1958 Bury broken glass alongside the post. Desc. 60 ft. over W. slope.
50.70	Wash, 10 lks. wide, 2 ft. deep, drains NNE.; asc. 80 ft. over E. slope.
64.90	Road, bears N. and S.; asc. 20 ft. over E. slope.
73.50	Top of ascent; desc. 20 ft. over W. slope.
79.90	The cor. of secs. 2, 3, 10 and 11. Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	N. 0° 01' W., bet. secs. 2 and 3. Over rolling land, through dense timber and undergrowth; asc. 10 ft. over gentle S. slope.
10.80	Spur, slopes W.; desc. 50 ft. over N. slope.
16.60	Wash, 10 lks. wide, 1 ft. deep, drains W.; asc. 40 ft. over S. slope.
22.80	Low spur, slopes W.; desc. 30 ft. over N. slope.
32.40	Base of descent; asc. 10 ft. over gentle S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd. T36N R5W $\frac{1}{4}$ S3 S2 1958 Desc. 40 ft. over N. slope.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
44.40	Wash, 10 lks. wide, 1 ft. deep, drains W.
52.90	Small wash, drains W.; asc. 20 ft. over S. slope.
56.00	Spur, slopes W.; cont. ascent of 30 ft. over rolling S. slope.
72.10	Road, bears ESE. and WNW.
77.44	Intersect the Ninth Standard Parallel North and point for the closing cor. of secs. 2 and 3. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone to top, with brass cap mkd. <div style="text-align: center;"> T37N R5W S35 S3 S2 T36N T5W C C 1958 </div> <p>From this closing cor. the standard cor. of secs. 34 and 35, bears W. 9.36 chs. dist., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.</p>
	<p>The point for the N. ¼ sec. cor. of sec. 2 is on the Ninth Standard Parallel North and at midpoint on the N. bdy. of sec. 2.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> ¼ S2 T36N R5W 1958 </div> <p>From this cor. the standard ¼ sec. cor. of sec. 35 bears W. 9.37 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.</p> <p>N. 0° 02' W., bet. secs. 33 and 34.</p> <p>Over rolling land, through scattered timber and heavy sagebrush; asc. 45 ft. over S. slope.</p>
18.00	Spur, slopes NE.; desc. 80 ft. over N. slope.
32.40	Wash, 10 lks. wide, 2 ft. deep, drains ENE.; asc. 35 ft. over S. slope.
38.90	Spur, slopes E.
40.00	Point for the ¼ sec. cor. of secs. 33 and 34.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T36N R5W

¼

S33|S34

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Desc. 50 ft. over gentle N. slope of small valley.

68.90 Road, bears E. and W.; base of descent; asc. 15 ft. over S. slope.

72.70 Spur, slopes E.; desc. 5 ft. over gradual N. slope.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

S28|S27

S33|S34

1958

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

From the cor. of secs. 26, 27, 34 and 35.

N. 89° 59' W., bet. secs. 27 and 34.

Over rolling land, through scattered timber and heavy undergrowth.

1.90 Ridge, bears NNW.; desc. 60 ft. over W. slope.

12.90 Small draw, drains NW.; asc. 40 ft. over E. slope.

22.50 Spur, slopes W.; desc. 35 ft. over W. slope.

32.20 Road, bears N. and S.

33.50 Small spur, slopes S.; asc. 10 ft. over E. slope.

38.00 Spur, slopes S.; desc. 10 ft. over W. slope.

40.07 Point for the ¼ sec. cor. of secs. 27 and 34.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

¼ S27

S34

1958

Desc. 70 ft. over W. slope to wash.

52.10 Road, bears NW. and SE.

54.00 Fence, 4-strand barbed wire, bears NW. and SE.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
56.00	Bottom of small valley, drains NW.; asc. 50 ft. over E. slope.
66.50	Spur, slopes N.; desc. 40 ft. over W. slope.
74.20	Wash, 10 lks. wide, 3 ft. deep, drains NE.; asc. 30 ft. over W. slope.
80.14	The cor. of secs. 27, 28, 33 and 34.
	Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	N. 0° 02' W., bet. secs. 27 and 28. Over rolling land, through scattered timber and heavy undergrowth. Asc. 25 ft. over S. slope.
11.80	Spur, slopes E.; asc. 30 ft. over rolling S. slope.
19.60	Spur, slopes E.; cont. over rolling land.
26.88	Fence post on S. end of reservoir, bears N. 69° 51' E., 16.43 chs. dist.
40.00	Point for the ¼ sec. cor. of secs. 27 and 28. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N R5W S28 S27 1958
	Desc. 40 ft. over N. slope.
48.00	Wash, 10 lks. wide, 1 ft. deep, drains E. to reservoir; asc. 30 ft. over SSE. slope to spur.
56.00	Fence, bears N. 25° W. and S. 25° E.
57.50	Road, bears NW. and SE.
61.70	Spur, slopes SSE.; desc. 20 ft. over NE. slope.
65.80	Wash, 10 lks. wide, 3 ft. deep, drains SSE.; asc. 50 ft. over SW. slope.
78.00	Spur, slopes SSE.; desc. 10 ft. over NE. slope.
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N R5W S21 S22 S28 S27 1958
	Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
12.70	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89° 54' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through scattered timber and heavy undergrowth.</p> <p>Asc. 30 ft. over SE. slope.</p>
24.80	<p>Spur, slopes SW.; desc. 100 ft. along NW. slope.</p>
32.00	<p>Wash, 10 lks. wide, 5 ft. deep, drains generally W.; cont. over rolling land.</p>
40.05	<p>Road, bears NE. and SW.</p>
40.60	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">T36N R5W $\frac{1}{4}$ $\frac{S22}{S27}$ 1958</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
69.90	<p>Robinson wash, 30 lks. wide, 4 ft. deep, drains NE.; asc. 80 ft. over E. slope.</p>
74.60	<p>Spur, slopes generally E.; desc. 15 ft. over NW. slope.</p>
80.10	<p>Wash, 10 lks. wide, 2 ft. deep, drains NE.; asc. 10 ft. over E. slope.</p>
6.60	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.</p>
9.00	<p>N. 0° 02' W., bet. secs. 21 and 22.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p>
10.50	<p>Wash, 10 lks. wide, 2 ft. deep, drains SE.; asc. 20 ft. over S. slope.</p>
26.00	<p>Spur, slopes SW.; desc. 10 ft. over N. slope.</p>
40.00	<p>Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. 80 ft. over S. slope.</p>
40.00	<p>Spur, slopes S. 65° E.; desc. 75 ft. over rolling N. slope.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T36N R5W $\frac{1}{4}$ S21 S22 1958</p> <p>Desc. 80 ft. over NW. slope.</p>

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
51.50	Wash, 10 lks. wide, 2 ft. deep, drains NE.; asc. 20 ft. over S. slope.
57.20	Spur, slopes E.; desc. 20 ft. over N. slope.
62.80	Wash, 30 lks. wide, 3 ft. deep, drains W. 4.50 chs., thence N. 20° W.; asc. 40 ft. over S. slope.
64.90	Spur, slopes S. 65° W.; desc. 20 ft. over N. slope.
68.40	Wash, 5 lks. wide, 2 ft. deep, drains S. 25° W.; asc. 45 ft. over SW. slope.
76.50	Spur, slopes SW.; desc. 25 ft. over NW. slope.
80.00	Point for the cor. of secs. 15, 16, 21 and 22. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock; in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N R5W S16 S15 S21 S22 1958
	Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	From the cor. of secs. 14, 15, 22 and 23. N. 89° 59' W., bet. secs. 15 and 22. Over rolling land, through dense timber and undergrowth. Asc. 10 ft. over E. slope.
2.00	Top of ascent; desc. 150 ft. over W. slope.
33.30	Wash in Robinson Canyon, 20 lks. wide, 2 ft. deep, drains SW.; asc. 20 ft. over E. slope.
40.05	Point for the ¼ sec. cor. of secs. 15 and 22. Set an iron post, 30 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock; in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N R5W ¼ S15 S22 1958
	Asc. 55 ft. over SE. slope.
61.00	Ridge, bears S.; desc. 105 ft. over W. slope.
71.30	Spur, slopes SW.; desc. 40 ft. over NW. slope.
75.20	Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. 10 ft. over SE. slope.
80.10	The cor. of secs. 15, 16, 21 and 22. Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.

Survey of the Subdivision, T. 36 N., R. 5 W.

Chains

N. 0° 02' W., bet. secs. 15 and 16.

Over rolling and broken land, through medium dense timber and undergrowth; asc. 75 ft. over S. slope.

5.30 Top of small knob, 40 ft. diam.; asc. 20 ft.

9.60 Saddle, bears N. and S.; asc. 35 ft. over S. slope.

13.20 Spur, slopes W. to Robinson Canyon; desc. 15 ft. over N. 20° E. slope.

28.60 Desc. 110 ft. over steeper N. 20° E. slope.

35.40 Spur, slopes NE.; desc. 45 ft. over NW. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd.

T36N R5W

$\frac{1}{4}$
S16|S15
1958

Desc. 10 ft. over N. slope.

43.50 Wash, 20 lks. wide, 2 ft. deep, drains NW.; asc. 50 ft. over S. slope.

48.80 Spur, slopes W.; desc. 60 ft. over NE. slope.

57.60 Base of descent; asc. 55 ft. over SE. slope.

62.00 Spur, slopes E.; desc. 140 ft. over NE. slope.

79.70 Wash, 20 lks. wide, 2 ft. deep, drains W.

80.00 Point for the cor. of secs. 9, 10, 15 and 16.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd.

T36N R5W

S9|S10
S16|S15
1958

Land, rolling.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

From the cor. of secs. 10, 11, 14 and 15.

S. 89° 59' W., bet. secs. 10 and 15.

Over rolling land, through medium dense timber and scattered undergrowth; asc. 15 ft. over NE. slope.

6.30 Spur, slopes SE.; desc. 40 ft. over SW. slope.

12.50 Wash, 15 lks. wide, 1 ft. deep, drains NW.; asc. 20 ft. over E. slope.

20.10 Low spur, slopes N.; desc. 20 ft. over W. slope.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
28.70	Same wash, 20 lks. wide, 2 ft. deep, drains S.; asc. 70 ft. over E. slope.
32.20	Spur, slopes S.; desc. 70 ft. over W. slope.
38.60	Same wash, 20 lks. wide, 2 ft. deep, drains W.
40.10	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T36N R5W $\frac{1}{4}$ S10 S15 1958</p>
	Asc. 10 ft. over NE. slope.
41.30	Top of ascent; desc. 45 ft. over N. 65° W. slope.
56.30	Spur, slopes N.; desc. 50 ft. over W. slope.
60.50	Same wash, drains SW.
63.50	Same wash, drains W.
66.50	Same wash, drains SW.; asc. 50 ft. over E. slope.
72.00	Spur, slopes S. 4.00 chs. to end; desc. 90 ft. over S. 65° W. slope.
80.20	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling and broken. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.</p>
	N. 0° 02' W., bet. secs. 9 and 10.
	Over rolling and broken land, through moderate timber and undergrowth; asc. 75 ft. over S. slope.
5.30	Spur, slopes W.; desc. 40 ft. over NW. slope.
14.80	Wash, 10 lks. wide, 2 ft. deep, drains W.; asc. 20 ft. over broken S. slope.
19.10	Spur, slopes S. 65° W.; desc. 20 ft. over N. slope.
22.70	Wash, 10 lks. wide, 1 ft. deep, drains SW.; asc. 110 ft. over S. slope.
34.40	Ridge, bears S. 70° W.; desc. 20 ft. over NE. slope.
39.30	Rim of canyon, bears NW. and SE.; desc. 20 ft. over steep NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T36N R5W $\frac{1}{4}$ S9 S10 1958</p>

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

Desc. 240 ft. over steep NE. slope.

50.30 Wash, 20 lks. wide, 3 ft. deep, drains NW.; asc. 60 ft. over S. slope.

51.70 Spur, slopes W.; desc. 60 ft. over N. slope.

56.80 Same wash, bears N. 3.00 chs., thence NW.; asc. 230 ft. over SW. slope.

64.70 N. rim of canyon, bears S. 65° E. and N. 65° W.

65.00 Ridge, bears W.; desc. 90 ft. over N. slope.

71.50 Wash, 15 lks. wide, 3 ft. deep, drains SW.; asc. 110 ft. over S. slope.

77.70 Ridge, bears W.; desc. 10 ft. over NW. slope.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

S4 | S3

S9 | S10

1958

Land, broken and rolling.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

From the cor. of secs. 2, 3, 10 and 11.

S. 89° 58' W., bet. secs. 3 and 10.

Over rolling land, through moderate timber and undergrowth; desc. 100 ft. over W. slope.

11.60 Wash, 10 lks. wide, 1 ft. deep, drains SW.; asc. 40 ft. over SE. slope.

16.20 Spur, slopes SW.; desc. 115 ft. over rolling W. slope.

40.11 Point for the ¼ sec. cor. of secs. 3 and 10.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T36N R5W

¼ | S3

S10

1958

Desc. 60 ft. over W. slope.

45.40 Wash, 15 lks. wide, 1 ft. deep, drains SW.; desc. 110 ft. over numerous spurs and washes putting SW.

80.22 The cor. of secs. 3, 4, 9 and 10.

Land, rolling and broken.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
	N. $0^{\circ} 02'$ W., bet. secs. 3 and 4.
	Over rolling and broken land, through dense timber and scattered undergrowth; desc. 140 ft. over broken NW. slope.
14.00	Base of descent; asc. 180 ft. over steep S. slope and ledges.
17.00	Top of ledges, 40 ft. high, bears E. and W.; asc. 70 ft. over broken spurs and washes putting S. 40° W.
39.90	Spur, slopes N. 10° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> T36N R5W $\frac{1}{4}$ S4 S3 1958 </div>
	Desc. 180 ft. over N. slope.
57.10	Wash, 15 lks. wide, 2 ft. deep, drains N. 75° W.; asc. 80 ft. over S. slope.
68.30	Spur, slopes N. 80° W.; desc. 160 ft. over NE. slope.
77.62	Intersect the Ninth Standard Parallel North,
	Point for the closing cor. of secs. 3 and 4.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> T37N R5W S34 S4 S3 T36N R5W C C 1958 </div>
	From this closing cor. the true point for the standard cor. of secs. 33 and 34 bears W. 9.08 chs. dist. and is witnessed W. 20.46 chs. dist. by an iron post, set, mkd. and witnessed as described in the official record.
	Land, rolling and broken.
	Soil, sandy and gravelly clay loam.
	Timber, juniper and pinon.
	Undergrowth, sagebrush.
	The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3 is on the Ninth Standard Parallel North and at midpoint on the N. bdy. of sec. 3.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> $\frac{1}{4}$ S3 T36N R5W 1958 </div>

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 34 bears W. 9.22 chs. dist., an iron post, set, mkd. and witnessed as described in the official record.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp., an iron post firmly set, mkd. and witnessed as described in the official record.

N. $0^{\circ} 03' W.$, bet. secs. 32 and 33.

Over nearly level land, through moderate timber and sagebrush.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R5W

$\frac{1}{4}$

S32|S33

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

63.45

Fence, 4-strand barbed wire, bears N. $80^{\circ} W.$ and S. $80^{\circ} E.$

66.80

Wash, 10 lks. wide, 1 ft. deep, drains N. $35^{\circ} E.$

80.00

Point for the cor. of secs. 28, 29, 32 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R5W

S29|S28

S32|S33

1958

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, moderate growth of pinon and juniper.

Undergrowth, mostly sagebrush.

From the cor. of secs. 27, 28, 33 and 34.

S. $89^{\circ} 58' W.$, bet. secs. 28 and 33.

Over rolling land, through light timber and heavy sagebrush.

Asc. 35 ft. over E. slope.

8.60

Spur, slopes SE.; desc. 10 ft. over W. slope.

16.00

Wash, 5 lks. wide, 2 ft. deep, drains S. $10^{\circ} E.$; asc. 25 ft. over E. slope.

20.50

Access road, bears N. $30^{\circ} W.$ and S. $30^{\circ} E.$; asc. 20 ft. over E. slope.

26.40

Top of ascent, thence over nearly level land.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N R5W $\frac{1}{4}$ <u>S28</u> S33 1958
56.20	Wash, 10 lks. wide, 1 ft. deep, drains N.
60.50	Small spur, slopes N.
77.20	Fence, 4-strand barbed wire, bears N. 5° W. and S. 5° E.
78.50	Wash, 5 lks. wide, 1 ft. deep, drains N.
80.10	The cor. of secs. 28, 29, 32 and 33. Land, rolling to nearly level. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, mostly sagebrush.
	N. $0^{\circ} 03'$ W., bet. secs. 28 and 29. Over rolling land, through scattered juniper and pinon.
1.60	Wash, 10 lks. wide, 2 ft. deep, drains N. 30° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T36N R5W $\frac{1}{4}$ S29 S28 1958
	Bury broken glass at the base of the iron post.
48.00	Wash, 10 lks. wide, drains NW.
80.00	Point for the cor. of secs. 20, 21, 28 and 29. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N R5W <u>S20 S21</u> S29 S28 1958
	Land, rolling. Soil, sandy and gravelly clay loam. Timber, scattered juniper and pinon. Undergrowth, mostly sagebrush.
	From the cor. of secs. 21, 22, 27 and 28. S. $89^{\circ} 58'$ W., bet. secs. 21 and 28.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
	Over gently rolling land, through moderately dense juniper and pinon. Asc. 10 ft. over E. slope.
2.20	Spur, slopes S. 10° E.; desc. 10 ft. over W. slope.
9.20	Wash, 5 lks. wide, 1 ft. deep, drains S. 40° E.; asc. 25 ft. over rolling E. slope.
17.50	Road to Robinson Tanks, bears N. 10° W. and S. 10° E.; asc. 40 ft. over rolling E. slope.
34.00	Top of ascent; desc. 20 ft. over W. slope.
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N R5W $\frac{1}{4}$ S21 S28 1958
	Desc. 30 ft. over rolling W. slope.
58.90	Fence, 4-strand barbed wire, bears N. 70° W. and S. 70° E.; desc. 35 ft. over W. slope.
77.60	Fence, 4-strand barbed wire, bears N. and S.; enter rail cleared land.
80.10	The cor. of secs. 20, 21, 28 and 29. Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, scattered juniper and pinon. Undergrowth, mostly sagebrush.
	N. 0° 03' W., bet. secs. 20 and 21. Over gently rolling rail cleared land.
5.00	Leave railed land, enter moderately heavy timber.
11.60	Wash, 10 lks. wide, 3 ft. deep, drains NW.; asc. 15 ft. over gentle S. slope.
22.00	Road, 18 lks. wide, bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N R5W $\frac{1}{4}$ S20 S21 1958
	Asc. 15 ft. over S. slope.
42.30	Spur, slopes generally W.; desc. 35 ft. over rolling NE. slope.
54.00	Wash, 5 lks. wide, 2 ft. deep, drains NW.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
57.30	Spur, slopes W.; desc. 70 ft. over numerous small spurs and washes putting N. 85° W.
80.00	Point for the cor. of secs. 16, 17, 20 and 21. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T36N R5W S17 S16 S20 S21 1958 </div> Land, gently rolling to rolling, Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, mostly sagebrush.
	From the cor. of secs. 15, 16, 21 and 22. West, bet. secs. 16 and 21. Over broken and rolling land, through dense timber and sagebrush. Desc. 90 ft. over W. slope.
10.70	Wash in Robinson Canyon, 35 lks. wide, 6 ft. deep, drains N.; asc. 110 ft. over E. slope.
21.50	Spur, slopes S.; desc. 10 ft. over W. slope.
27.40	Wash, 10 lks. wide, 2 ft. deep, drains S.; desc. 20 ft. over W. slope.
40.09	Point for the ¼ sec. cor. of secs. 16 and 21. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T36N R5W ¼ S16 S21 1958 </div> Desc. 150 ft. to the sec. cor. over W. slope, with numerous small spurs and washes putting N.
78.10	Fence, 4-strand barbed wire, bears N. and S.
79.10	Wash, 5 lks. wide, 1 ft. deep, drains generally N. 10° W.
80.18	The cor. of secs. 16, 17, 20 and 21. Land, rolling and broken. Soil, gravelly clay loam. Timber, pinon and juniper. Undergrowth, mostly sagebrush.
	N. 0° 03' W., bet. secs. 16 and 17. Over rolling land, through dense timber and sagebrush.
4.80	Wash in Little Robinson Canyon, 10 lks. wide, 3 ft. deep, drains N. 80° E.; asc. 15 ft. over S. slope.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
6.20	Saddle in low spur, slopes S. 80° E.; asc. 90 ft. over broken SE. slope.
15.20	Wash, 10 lks. wide, 2 ft. deep, drains S. 60° E.; to above wash; asc. 40 ft. over S. slope.
27.60	Ridge, bears N. 60° E. and S. 60° W.; desc. 10 ft. over broken spurs sloping generally NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd. T36N R5W $\frac{1}{4}$ S17 S16 1958 Thence over broken spurs and washes sloping NE.
55.10	Spur, slopes E.; desc. 75 ft. over N. slope.
61.60	Wash, 20 lks. wide, 3 ft. deep, drains E.; asc. 20 ft. over S. slope.
65.20	Spur, slopes S. 40° E.; desc. 10 ft. over N. slope.
67.40	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° E.; asc. 155 ft. over S. slope.
80.00	Point for the cor. of secs. 8, 9, 16 and 17. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd. T36N R5W S8 S9 S17 S16 1958 Land, rolling and broken. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, mostly sagebrush.
	From the cor. of secs. 9, 10, 15 and 16. N. 89° 58' W., bet. secs. 9 and 16. Over broken and rolling land, through dense timber and scattered undergrowth. Desc. 20 ft. over W. slope.
5.50	Wash, 25 lks. wide, 3 ft. deep, drains N. 10° W.; asc. 25 ft. over E. slope.
7.70	Spur, slopes N.; desc. 50 ft. over W. slope.
13.90	Wash, 10 lks. wide, 2 ft. deep, drains N. 10° W.; asc. 50 ft. over E. slope.
16.60	Spur, slopes N.; desc. 20 ft. over W. slope.
21.20	Wash, 40 lks. wide, 5 ft. deep, drains N. 35° E.; asc. 40 ft. over SE. slope.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
23.80	Spur, slopes N. 35° E.
32.30	Fence, 4-strand barbed wire, bears N. 5° W. and S. 5° E.
34.60	Spur, slopes NW.; desc. 140 ft. over steep SW. slope.
40.09	True point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16 falls on inaccessible SW. slope and cannot be perpetuated.
40.30	Wash, drains N.
41.28	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 9 and 16. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T36N R5W $\frac{1}{4}$ S 9 W S16 C 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Asc. 175 ft. over broken E. slope.
62.40	Top of steep ascent; asc. 10 ft. over gentle E. slope.
78.80	Spur, slopes S. 40° E.; desc. 10 ft. over SW. slope.
80.18	The cor. of secs. 8, 9, 16 and 17. Land, rolling and broken. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, mostly sagebrush.
	N. 0° 03' W., bet. secs. 8 and 9. Over rolling land, through moderately dense timber and scattered undergrowth. Desc. 50 ft. over gentle N. slope.
24.30	Wash, 10 lks. wide, 1 ft. deep, drains N. 80° E.; asc. 70 ft. over broken S. slope.
35.70	Fence, 4-strand barbed wire, bears N. 80° W. and S. 80° E.; asc. 10 ft. over S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground with brass cap mkd.
	T36N R5W $\frac{1}{4}$ S8 S9 1958
	Bury charcoal alongside the post.
	Asc. 60 ft. over S. slope.
62.00	Low ridge, projects E.; desc. 10 ft. over gentle N. slope.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W
 $\frac{S5}{S8} | \frac{S4}{S9}$
 1958

Land, rolling.
 Soil, sandy and gravelly clay loam.
 Timber, juniper and pinon.
 Undergrowth, mostly sagebrush.

From the cor. of secs. 3, 4, 9 and 10.

N. 89° 58' W., bet. secs. 4 and 9.

Over broken and rolling land, through medium dense timber and scattered undergrowth.

Desc. 190 ft. over broken W. slope.

12.20 Wash, 15 lks. wide, 2 ft. deep, drains N. 10° E.; asc. 35 ft. over broken E. slope.

16.70 Spur, slopes N. 5° E.; desc. 145 ft. over W. slope of canyon.

26.00 Wash, 20 lks. wide, 2 ft. deep, drains N.; asc. 230 ft. over steep E. slope of canyon.

34.30 Top of steep ascent; asc. 15 ft. over rolling E. slope.

40.05 Point for the ¼ sec. cor. of secs. 4 and 9.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T36N R5W
 $\frac{1}{4} \frac{S4}{S9}$
 1958

Desc. 60 ft. over series of small spurs and washes putting N. 10° W.

53.90 Wash, 10 lks. wide, 1 ft. deep, drains N. 50° E.; asc. 50 ft. over SE. slope.

72.50 Enter light timber; leave dense timber; asc. 10 ft. over E. slope.

80.10 The cor. of secs. 4, 5, 8 and 9.

Land, rolling and broken.
 Soil, sandy and gravelly clay loam.
 Timber, juniper and pinon.
 Undergrowth, mostly sagebrush.

N. 0° 03' W., bet. secs. 4 and 5.

Over rolling land, through scattered timber.

40.00 Point for the ¼ sec. cor. of secs. 4 and 5.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T36N R5W

$$\frac{1}{4}$$

S5	S4
1958	

Thence over rolling land.

77.62

Intersect the S. bdy. of T. 37 N., R. 5 W. (Ninth Standard Parallel North).

Point for the closing cor. of secs. 4 and 5.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T37N R5W

<u>S33</u>	
S5	S4
C C	
T36N R5W	
1958	

Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of cor.

From this closing cor. the standard cor. of secs. 32 and 33, bears W. 8.86 chs. dist., an iron post, 3 ins. diam., conforming to the official record.

Land, rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper.
Undergrowth, mostly sagebrush.

The point for the N. ¼ sec. cor. of sec. 4 is on the Ninth Standard Parallel North and at midpoint on the N. bdy. of sec. 4.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

$\frac{1}{4}$	S4
T36N R5W	
1958	

From this ¼ sec. cor. the standard ¼ sec. cor. of sec. 33 bears W. 8.97 chs. dist., an iron post, set, mkd. and witnessed as described in the official record.

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp., an iron post, set, mkd. and witnessed as described in the official record.

N. 0° 03' W., bet. secs. 31 and 32.

Over nearly level land, through scattered timber and dense sagebrush.

40.00

Point for the ¼ sec. cor. of secs. 31 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

T36N R5W

 $\frac{1}{2}$

S31|S32

1958

Deposit charcoal at the base of the post.

80.00

Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground in a mound of stone, 2½ ft. base to top, with brass cap mkd.

T36N R5W

S30|S29

S31|S32

1958

Land, nearly level.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, mostly sagebrush.

From the cor. of secs. 28, 29, 32 and 33.

S. 89° 59' W., bet. secs. 29 and 32.

Over gently rolling land, through scattered timber and moderate sagebrush.

Asc. 40 ft. over E. slope.

3.40

Ridge spur, bears irregularly NE. and SW.; thence over gently rolling rail cleared land.

33.50

Wash, 5 lks. wide, 1 ft. deep, drains N.

40.00

Point for the $\frac{1}{2}$ sec. cor. of secs. 29 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 2½ ft. base to top, with brass cap mkd.

T36N R5W

 $\frac{1}{2}$ S29

S32

1958

Asc. 50 ft. over gentle E. slope.

78.60

Fence, 4-strand barbed wire, bears N. 80° W. and S. 80° E.; leave rail cleared land.

80.00

The cor. of secs. 29, 30, 31 and 32.

Land, gently rolling.

Soil, sandy and gravelly clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
	S. 89° 56' W., bet. secs. 30 and 31. Over nearly level land, through scattered timber and dense sagebrush.
30.80	Wash, 10 lks. wide, 1 ft. deep, drains N.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T36N R5W $\frac{1}{4}$ <u>S30</u> S31 1958
	Deposit charcoal at the base of the post.
48.70	Access road, bears N. 5° E. and S. 5° W.
60.30	Access road, bears N. 30° E. and S. 30° W.
76.50	Wash, 10 lks. wide, 1 ft. deep, drains N.
78.08	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., an iron post, set, mkd. and witnessed as described in the official record. Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, mostly sagebrush.
	From the cor. of secs. 29, 30, 31 and 32. N. 0° 03' W., bet. secs. 29 and 30. Over gently rolling land, through scattered timber and dense sagebrush.
4.60	Fence, 4-strand barbed wire, bears N. 80° W. and S. 80° E.; enter rail cleared land.
9.90	Wash, 10 lks. wide, 1 ft. deep, drains generally W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd. T36N R5W $\frac{1}{4}$ <u>S30</u> S29 1958
47.70	Wash, 10 lks. wide, 2 ft. deep, drains N. 30° E.
80.00	Point for the cor. of secs. 19, 20, 29 and 30. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T36N R5W <u>S19</u> <u>S20</u> <u>S30</u> <u>S29</u> 1958
	Deposit charcoal at the base of the post.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

Land, gently rolling.
Soil, sandy and clay loam.
Timber, juniper and pinon.
Undergrowth, mostly sagebrush.

From the cor. of secs. 20, 21, 28 and 29.

S. 89° 59' W., bet. secs. 20 and 29.

Over gently rolling land; no timber and scattered undergrowth.

Asc. 55 ft. over E. slope.

14.00 Top of ascent; thence over nearly level land.

25.50 Wash, 10 lks. wide, 2 ft. deep, drains N.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T36N . R5W.

$\frac{1}{4}$ S20

S29

1958

Deposit charcoal at the base of the post.

49.10 Wash, 5 lks. wide, 1 ft. deep, drains N. 25° E.

56.00 Enter scattered timber, bears N. 5° E. and S. 5° W.; asc. 40 ft. over E. slope.

65.00 Spur, slopes N. 10° W.

67.00 Leave timber, enter nearly level railed cleared land.

74.90 Wash in Little Robinson Canyon, 10 lks. wide, 2 ft. deep, drains N. 10° W.

80.04 The cor. of secs. 19, 20, 29 and 30.

Land, gently rolling to nearly level.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

S. 89° 57' W., bet. secs. 19 and 30.

Over gently rolling land, through scattered juniper and sagebrush.

Asc. 30 ft. over rail cleared E. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
	<p style="text-align: right;">T36N R5W $\frac{1}{4}$ S19 S30 1958</p>
	<p>Deposit charcoal at the base of the post.</p> <p>Thence over nearly level land.</p>
59.40	Access road, bears N. 40° E. and S. 49° W.
62.50	Wash, 10 lks. wide, 4 ft. deep, drains N. 80° E.; asc. 40 ft. over gentle E. slope.
78.04	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., an iron post, set, mkd. and witnessed as described in the official record.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, scattered juniper. Undergrowth, sagebrush.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 03' W., bet. secs. 19 and 20.</p> <p>Over nearly level rail cleared land; no timber and scattered undergrowth.</p>
27.90	Wash, 10 lks. wide, 2 ft. deep, drains N. 70° E.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: right;">T36N R5W $\frac{1}{4}$ S19 S20 1958</p>
	<p>Deposit broken glass alongside the post.</p> <p>Thence over gently rolling land.</p>
51.70	Access road, bears NW. and SE.
73.50	Enter timber, bears E. and W.
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: right;">T36N R5W S18 S17 S19 S20 1958</p>
	<p>Land, nearly level to gently rolling. Soil, sandy and gravelly clay loam. Timber, juniper last half. Undergrowth, sagebrush.</p>

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	From the cor. of secs. 16, 17, 20 and 21. N. 89° 59' W., bet. secs. 17 and 20. Over rolling land, through dense timber and sagebrush. Asc. 10 ft. over E. slope.
1.70	Spur, slopes N.; desc. 15 ft. over W. slope.
5.40	Wash in Little Robinson Canyon, 10 lks. wide, 2 ft. deep, drains N.; asc. 65 ft. over E. slope.
20.40	Slope changes to NNE.; asc. 25 ft.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd. T36N R5W $\frac{1}{4}$ <u>S17</u> S20 1958 Thence over gently rolling land.
79.00	Access road, bears N. 50° W. and S. 50° E.
80.04	The cor. of secs. 17, 18, 19 and 20. Land, rolling to gently rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	S. 89° 54' W., bet. secs. 18 and 19. Over gently rolling land, through moderate timber and heavy sagebrush.
36.50	Leave dense timber, enter nearly level valley.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd. T36N R5W $\frac{1}{4}$ <u>S18</u> S19 1958
65.70	Wash, 5 lks. wide, 2 ft. deep, drains N. 5° E.
71.20	Access road, bears N. 10° E. and S. 10° W.
77.98	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., an iron post, set, mkd. and witnessed as described in the official record. Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0° 03' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land, through dense timber and sagebrush.</p>
2.20	Access road, bears N. 50° W. and S. 50° E.; desc. 5 ft. over NW. slope.
7.90	Wash, 5 lks. wide, 1 ft. deep, drains N. 35° E.; asc. 40 ft. over S. slope.
18.00	Low spur, slopes S. 80° E.; desc. 15 ft. over N. slope.
21.30	Shallow draw, drains S. 80° E.; asc. 60 ft. over S. slope.
34.00	Low spur, slopes S. 70° E.; desc. 5 ft. over gentle N. slope.
40.00	<p>Point for the ¼ sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R5W ¼ S18 S17 1958</p> <p>Deposit broken glass alongside the post.</p> <p>Thence over nearly level land.</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R5W S7 S8 S18 S17 1958</p> <p>Land, gently rolling to nearly level. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89° 57' W., bet. secs. 8 and 17.</p> <p>Over rolling land, through medium dense timber and sagebrush.</p> <p>Desc. 35 ft. over SW. slope.</p>
5.50	Head of shallow draw, drains S. 25° E.; asc. 50 ft. over NE. slope.
24.50	Top of ascent; desc. 35 ft. over W. slope.
39.98	<p>Point for the ¼ sec. cor. of secs. 8 and 17.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone; 3 ft. base to top; with brass cap mkd.</p> <p style="text-align: center;">T36N R5W ¼ S 8 S17 1958</p>

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

Thence over gently rolling land, through scattered timber and sagebrush.

79.96

The cor. of secs. 7, 8, 17 and 18.

Land, rolling to gently rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

S. 89° 49' W., bet. secs. 7 and 18.

Over gently rolling land, through medium dense timber and scattered sagebrush.

3.30

Access road, bears N. and S.; asc. 45 ft. over E. slope.

21.20

Top of ascent; desc. 10 ft. over gradual W. slope.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T36N R5W

 $\frac{1}{4}$ S 7

S18

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Desc. 40 ft. over S. 25° W. slope.

63.90

Access road, bears N. and S.

68.00

Low spur, slopes N. 10° W.

70.30

Fence, sheep wire and 2-strand barbed wire, bears N. 10° E. and S. 10° W.; fence encloses reservoir about 5.00 chs. N. and S.

76.00

W. edge of reservoir, bears N. and S.; asc. 25 ft. over E. slope.

78.05

The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., an iron post, set, mkd. and witnessed as described in the official record.

Land, gently rolling.
Soil, sandy and gravelly clay loam.
Timber, juniper and pinon.
Undergrowth, sagebrush.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 03' W., bet. secs. 7 and 8.

Over gently rolling land, through medium dense timber and sagebrush.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T36N R5W

 $\frac{1}{4}$

S7 | S8

1958

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
	Thence over small rolling hills.
61.90	Wash, 15 lks. wide, 1 ft. deep, drains N. 30° W.; asc. 65 ft. over S. slope.
68.70	Spur, slopes N. 70° E.; desc. 30 ft. over N. slope.
80.00	Point for the cor. of secs. 5, 6, 7 and 8. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T36N R5W S6 S5 S7 S8 1958
	Land, gently rolling to rolling. Soil, sandy and gravelly clay loam. Timber, juniper and pinon. Undergrowth, sagebrush.
	From the cor. of secs. 4, 5, 8 and 9. N. 89° 57' W., bet. secs. 5 and 8. Over rolling land, through scattered timber and sagebrush. Asc. 40 ft. over E. slope.
18.00	Top of ascent; desc. 50 ft. over W. slope.
39.93	Point for the ¼ sec. cor. of secs. 5 and 8. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone to top, 4 ft. base, with brass cap mkd.
	T36N R5W ¼ S 5 S 8 1958
	Desc. 35 ft. over W. slope.
55.00	Fence, 4-strand barbed wire, bears S. 50° E. and N. 50° W.; asc. 10 ft. over E. slope.
73.60	Spur, slopes S. 20° W.; desc. 65 ft. over W. slope.
79.86	The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper. Undergrowth, sagebrush.
	S. 89° 51' W. bet. secs. 6 and 7. Over rolling hilly land, through scattered timber and sagebrush. Desc. 15 ft. over W. slope.
6.80	Wash, 10 lks. wide, 1 ft. deep, drains N.; asc. 30 ft. over E. slope.

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains	
9.40	Access road, bears N. 30° W. and S. 30° E.; desc. 20 ft. over W. slope.
21.10	Wash, 10 lks. wide, 2 ft. deep, drains N. 20° E.; asc. 20 ft. over E. slope.
23.00	Access road, bears N. and S.; asc. 130 ft. over E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. T36N R5W $\frac{1}{4}$ $\frac{S 6}{S 7}$ 1958 Asc. 5 ft. over E. slope.
41.70	Spur, slopes N.; desc. 25 ft. over W. slope.
51.80	Base of descent; asc. 65 ft. over E. slope.
61.70	Spur, slopes N.; desc. 20 ft. over W. slope.
70.00	Wash, 10 lks. wide, 2 ft. deep, drains N. 10° E.; asc. 40 ft. over E. slope.
77.92	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record. Land, rolling. Soil, sandy and gravelly clay loam. Timber, juniper. Undergrowth, sagebrush.
	From the cor. of secs. 5, 6, 7 and 8. N. 0° 03' W., bet. secs. 5 and 6. Over rolling land, through scattered timber and undergrowth.
21.20	Wash, 40 lks. wide, 6 ft. deep, drains N. 30° E.
22.20	Access road, bears N. 20° E. and S. 30° W.; asc. 30 ft. over S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd. T36N R5W $\frac{1}{4}$ S6 S5 1958 Asc. 60 ft. over SE. slope.
43.60	Spur, slopes SW.; desc. 85 ft. over NE. slope.
62.60	Wash, 20 lks. wide, 2 ft. deep, drains N.

.Survey of the Subdivision of T. 36 N., R. 5 W.

Chains
 63.60 .Access road, bears S. 20° E. and N. 10° W.
 66.20 Same road, bears N. 30° E.
 69.10 Reservoir, bears E. and W.
 74.00 N. edge of reservoir, bears E. and W.
 76.40 Wash, 30 lks. wide, 5-ft. deep, drains N. 30° E.
 77.52 Intersect the Ninth Standard Parallel North.
 Point for the closing cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T37N R5W
 S32
 S6 | S5
 C | C
 T36N
 1958

Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of cor.

From this closing cor. the standard cor. of secs. 31 and 32 bears W. 8.92 chs. dist., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

Land, rolling.
 Soil, sandy and gravelly clay loam.
 Timber, juniper.
 Undergrowth, sagebrush.

The point for the N. ¼ sec. cor. of sec. 5 is on the Ninth Standard Parallel North and at midpoint on the N. bdy. of sec. 5.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼ S5
 T36N R5W
 1958

Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of cor.

From this ¼ sec. cor. the standard ¼ sec. cor. of sec. 32 bears W. 8.89 chs. dist., an iron post, set, mkd. and witnessed as described in the official record.

The point for the N. ¼ sec. cor. of sec. 6 is on the Ninth Standard Parallel North and at a westing of 40.00 chs. from the closing cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, in a mound of stone, 2½ ft. base to top, with brass cap mkd.

¼ S6
 T36N R5W
 1958

Survey of the Subdivision of T. 36 N., R. 5 W.

Chains

From this $\frac{1}{4}$ sec. cor. the standard $\frac{1}{4}$ sec. cor. of sec. 31 bears W. 8.92 chs. dist., an iron post, set, mkd. and witnessed as described in the official record.

General Description

The land in the township is a high rolling mountain top. In the southwest part, the slopes are gentle, gradually becoming more abrupt along the north boundary and particularly in the northeast corner.

The soil is a heavy, sandy clay and along the bottom of Robinson Canyon and in the northeast corner there is considerable exposed sandstone bedrock and sandstone rims.

The timber is mainly scrub juniper with a few pinon pine on the higher elevations. The undergrowth is predominately sagebrush, with lesser amounts of bitter brush, mountain rush, amole, weeds and grass.

The drainage is to the north and northeast. In the bottom of Robinson Canyon is a small intermittent stream of water.

The land is used for grazing and many small reservoirs have been constructed to impound the water for the use of stock. There are many secondary roads in the township, constructed by the cattlemen in order to reach the more remote areas.

There are no inhabitants in the township and no evidence of commercial deposits of mineral were found.

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald A. Cannon, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of October, 1958 I have surveyed resurveyed a portion of the north boundary (Ninth Standard Parallel North), the east boundary, a portion of the south boundary and the survey of the subdivision of T. 36 N., R. 5 W.

of the Gila & Salt Riv. Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
July 30, 1959

Donald A. Cannon
Donald A. Cannon
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., 19

The foregoing field notes of the survey of
executed by
having been critically examined and found correct, are hereby approved.

Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in
is a true copy of the original field notes.

Cadastral Engineering Staff Officer.

CERTIFICATE OF CADASTRAL ENGINEER

I, Robert C. Yundt, HEREBY CERTIFY upon honor that, in
pursuance of special instructions bearing date of the 9th day of October, 1958

I have ~~surveyed~~ supervised the resurvey of a portion of the north boundary (Ninth
Standard Parallel North), the east boundary, a portion of the south boundary and
the survey of the subdivision of T. 36 N., R. 5 W.

of the Gila & Salt River Meridian, in the State of Arizona, which are
represented in the foregoing field notes as having been executed by me and under my direction; and that
said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
field notes.

Salt Lake City, Utah
July 30, 1959

Robert C. Yundt
Robert C. Yundt
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., FEB 9 1960, 1960

The foregoing field notes of the ~~survey of~~ resurvey of a portion of the north boundary
(Ninth Standard Parallel North), the east boundary, a portion of the south boundary
and the survey of the subdivision of T. 36 N., R. 5 W., Gila and Salt River Meridian,
Arizona.

executed by Donald A. Cannon under the supervision of Robert C. Yundt
having been critically examined and found correct, are hereby approved.

Donald A. Cannon
Cadastral Engineering Staff Officer.

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 36 N.,
R. 5 W., G. & S. R. M., Ariz is a true copy of the original field notes.

Cadastral Engineering Staff Officer.