

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

RESURVEY OF A

PORTION OF THE WEST BOUNDARY

AND A

PORTION OF THE SUBDIVISION

OF

TOWNSHIP 1 SOUTH, RANGE 4 WEST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald E. Harding Cadastral Surveyor

Under special instructions dated December 26, 1957, which provided
for the surveys included under Group No. 322, approved December 26, 1957
and assignment instructions dated January 20, 1958.

Survey commenced January 30, 1958.

Survey completed March 17, 1958.

1A

BOOK 4575

INDEX DIAGRAM

Township 1 South, Range 4 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
27	26	20	16	12	8
3 19	25 20	19 21	15 22	11 23	7 24
25	24	19	15	11	6
2 30	23 29	18 28	14 27	10 26	5 25
22	22	17	13	9	4
1 31	21 32	17 33	12 34	8 35	4 36

Resurvey of a Portion of T. 1 S., R. 4 W.
Gila and Salt River Meridian, Arizona

Chains

The four boundaries were surveyed in 1882 and the subdivisional lines surveyed in 1883 by R. C. Powers as represented on the plat approved February 21, 1883. The south boundary was resurveyed by K. L. Siebecker in 1931, as represented on the plat of T. 2 S., R. 4 W., approved June 14, 1932. The original southwest corner of the township was retained as a corner of maximum control. All others were made to refer to the north only.

The south four (4) miles of the east boundary were resurveyed concurrently under this same group by Donald E. Harding.

The following notes are those of the resurvey of the south three miles of the west boundary and a portion of the subdivision.

For the test of the equipment and methods used see the notes for T. 1 S., R. 3 W. of this group.

The geographic position of the southeast corner of the township is in latitude $33^{\circ} 17' 26.114''$ N. and longitude $112^{\circ} 36' 26.782''$ W.

The mean magnetic declination is $14^{\circ} 30'$ E.

Dependent Resurvey of a Portion of West Boundary

Reestablishment of the survey executed by R. C. Powers in 1882.

From the cor. of Tps. 1 and 2 S., Rs. 4 and 5 W., which is monumented with a 3 ins. iron post, set, mkd. and witnessed as described in the official record.

N. $0^{\circ} 03'$ E., bet. secs. 31 and 36.

Desc. 40 ft. over NE. slope.

4.80 Wash, 30 lks. wide, 10 ft. deep, drains N. 60° E.

9.30 Wash, 10 lks. wide, 3 ft. deep, drains NE.

12.90 Wash, 30 lks. wide, 10 ft. deep, drains NE.; asc. 100 ft. over SE. slope.

25.00 Spur, slopes S. 70° E.; desc. 135 ft. over NE. slope.

33.70 Foot of hill, bears NW. and SE.; thence over NE. slope.

40.04 Point for the $\frac{1}{2}$ sec. cor. of secs. 31 and 36, at proportionate dist.; no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a mound of stone to top, with brass cap mkd.

T1S
R5W R4W

$\frac{1}{2}$
S36|S31

1958

Desc. 30 ft. over NE. slope.

44.90 Wash, 10 lks. wide, 5 ft. deep, drains N. 20° E.

48.50 Wash, 20 lks. wide, 4 ft. deep, drains N. 30° E.; asc. 25 ft. over SE. slope.

53.40 Spur, slopes NE.; desc. 50 ft. over N. slope.

58.10 Wash, 5 lks. wide, 1 ft. deep, drains N. 70° E.

Dependent Resurvey, Portion of West Bdy., T. 1 S., R. 4 W.

Chains	
	Asc. 50 ft. over general S. slope.
6562020	Top of knoll on spur sloping NE; desc. 120 ft. over general NW. slope.
79.60	Road, bears E. and W.
80.08	The cor. of secs. 25, 30, 31 and 36, which is monumented by a rotted wood stake at the cor. of a fence bearing N. and W.
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R5W R4W
	S25 S30 S36 S31
	1958
	Land, rolling and rocky. Soil, rocky and gravel.
	Timber, none. Undergrowth, scattered greasewood, mesquite, paloverde, cacti and grass.
	N. 0° 07' E., bet. secs. 25 and 30.
	Over nearly level bottom land.
5.00	Enter dense undergrowth, bears E. and W.
33.00	Gila River, 1 ch. wide, 4 ft. deep, flows W.
39.78	Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate dist.; no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R5W R4W
	¼ S25 S30
	1958
	Set an oak post, .6 ft. long, 6 ins. diam., 1 lk. W. of the cor. for witness.
51.00	Flood channel, 50 lks. wide, 2 ft. deep, drains SW.
60.00	Flood channel, 40 lks. wide, 4 ft. deep, drains SW.
79.56	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R5W R4W
	S24 S19 S25 S30
	1958

Dependent Resurvey, Portion of West Bdy., T. 1 S., R. 4 W.

Chains

Set a cedar post, 6 ft. long, 4 ins. diam., 1 lk. W. of cor. for witness.

Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, dense salt cedar and willows with very sparse grass.

N. 0° 07' E., bet. secs. 19 and 24.

Over nearly level bottom land, through dense undergrowth.

9.00 Leave dense undergrowth, bears NE. and SW.

12.00 Flood channel of Hassayampa River, 3 chs. wide, 2 ft. deep, drains S. 30° W.

36.00 Siphon, bears E. and W. on Arlington Canal, also Hassayampa River, drains S. 10° E.

39.78 Point for the $\frac{1}{2}$ set. cor. of secs. 19 and 24, at proportionate dist. No remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S
R5W R4W.
 $\frac{1}{2}$
S24 S19
1958

57.00 Enter dense undergrowth, bears N. 10° W. and S. 10° E.

71.00 Leave dense undergrowth, bears N. 10° W. and S. 10° E., enter cultivated land.

79.30 Fence, bears E. and W.

79.56 The cor. of secs. 13, 18, 19 and 24, as established from the intersection of a fenced road N., a fenced road E. and a fence W. It is accepted as the best available evidence of the position of the original cor.

At the cor. point

Bury a sandstone, 4x4x3 ins., marked by a cross (X), 12 ins. in the ground.

from which

An iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground for reference monument, bears N. 51° 45' W., 54 lks. dist., with brass cap mkd. T1S R5W S13 RM 1958, with an arrow pointing to the true cor.

An iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, for reference monument, bears S. 51° 45' E., 54 lks. dist., with brass cap mkd. T1S R4W S19 RM 1958, with an arrow pointing to the true cor.

Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, dense salt cedar and willows with very sparse grass.

Dependent Survey of Portion of the Subdivision, T. 1 S., R. 4 W.

Chains		
	<p>Reestablishment of the survey executed by R. C. Powers in 1883.</p> <p>From the cor. of secs. 35 and 36, which is monumented with an iron post, set, mkd. and witnessed as described in the official record.</p> <p>N. 0° 23' E., over rolling N. slope.</p>	
3.10	Wash, 10 fks wide, 1 ft. deep, drains N. 30° W.	
5.60	Wash, 10 lks. wide, 2 ft. deep, drains NW.	
23.00	Wash, 20 lks. wide, 3 ft. deep, drains NW.	
29.40	Wash, 10 lks. wide, 1 ft. deep, drains NW.	
32.60	Wash, 10 lks. wide, 1 ft. deep, drains W.	
38.10	Low spur, slopes W.	
40.56	<p>Point for the 1/2 sec. cor. of secs. 35 and 36, at proportionate dist.</p> <p>No remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone 4 1/2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S35 S36 1958</p> <p>Asc. 40 ft. over S. slope.</p>	
43.60	Small knoll; desc. 50 ft. over N. slope.	
81.12	<p>The cor. of secs. 25, 26, 35 and 36, which is monumented with a granite stone 15x12x8 ins. dimly mkd., firmly set in a mound of stone.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S26 S25 S35 S36 1958</p> <p>Bury the original corner stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.</p> <p>(A) to be a section, the same, on section 35 and 36.</p> <p>Land, rolling.</p> <p>Soil, rocky and gravelly.</p> <p>Timber, none.</p> <p>Undergrowth, scattered greasewood, mesquite, palo verde, cacti and grass.</p>	
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., which is monumented with an iron post recently set</p> <p>N. 88° 52' W., bet. secs. 25 and 36.</p> <p>Over rolling land, through scattered undergrowth.</p>	
4.20	Road, bears N. and S.	
4.30	Wash, 10 lks. wide, 1 ft. deep, drains N.	

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains	Asc. 85 ft. over E. slope.
8.10	Low ridge, bears N. and S.; desc. 60 ft. over W. slope.
23.30	Wash, 10 lks. wide, 5 ft. deep, drains N.
27.90	Wash, 20 lks. wide, 10 ft. deep, drains N. 10° E.
31.50	Wash, 20 lks. wide, 10 ft. deep, drains N.
39.94	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate dist. No remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R4W $\frac{1}{4}$ $\frac{S25}{S36}$ 1958 Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor. Thence over rolling N. slope.
40.20	Wash, 10 lks. wide, 2 ft. deep, drains NE.
48.30	Ridge, bears N. 30° W. and S. 10° E.
64.90	Wash, 20 lks. wide, 2 ft. deep, drains N. 70° W.
71.20	Wash, 30 lks. wide, 10 ft. deep, drains N. 30° W.
78.30	Low spur, slopes N. 10° W.
79.88	The cor. of secs. 25, 26, 35 and 36. Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, scattered greasewood, mesquite, palo verde, cacti and grass.
	N. 0° 45' E., bet. secs. 25 and 26. Over general N. slope, through scattered undergrowth.
14.00	Wash, 30 lks. wide, 4 ft. deep, drains NW.
16.60	Highway right-of-way fence, bears N. 9° 30' E. and S. 9° 30' W.
25.00	Wash, 10 lks. wide, 2 ft. deep, drains W.
27.90	U. S. Highway No. 80, bears N. 9° 30' E. and S. 9° 30' W.
35.10	Highway right-of-way fence, bears N. 9° 30' E. and S. 9° 30' W.
39.00	Wash, 10 lks. wide, 2 ft. deep, drains WNW.
39.23	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, which is monumented with a granite stone 12x10x6 ins. dimly mkd. At the cor. point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains	
	<p>T1S R4W</p> <p>$\frac{1}{4}$</p> <p>S26 S25</p> <p>1958</p> <p>Bury the original corner stone alongside the iron post, and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p>
	N. $0^{\circ} 58'$ W., beginning new measurement.
6.00	Wash, 30 lks. wide, 4 ft. deep, drains N. on E. side of line, from S. 25° W.
22.00	Same wash, drains NNW.
39.44	<p>The cor. of secs. 23, 24, 25 and 26, which is monumented with a 1 in. iron pin firmly set in the ground. This point has been used by the local land owners and the local surveyors for years as the true cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p>T1S R4W</p> <p>S23 S24</p> <p>S26 S25</p> <p>1958</p> <p>Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.</p> <p>Land, rolling.</p> <p>Soil, rocky and gravelly.</p> <p>Timber, none.</p> <p>Undergrowth, scattered greasewood, mesquite, palo verde, cacti and grass.</p>
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., which is monumented with an iron post recently set.</p> <p>N. $89^{\circ} 49'$ W., bet. secs. 24 and 25.</p> <p>Over rolling land, through scattered undergrowth.</p>
12.30	Wash, 10 lks. wide, 1 ft. deep, drains NW.
12.80	Road, bears SE. and N.
16.60	Wash, drains NNW.
25.90	Low spur, slopes N.
37.10	Road, bears WSW. and ENE.
39.94	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate dist. No remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p>T1S R4W</p> <p>$\frac{1}{4}$ S24</p> <p>S25</p> <p>1958</p>

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains	
	Set a cedar post, 6 ft. long, 6 ins. diam., 1 lk. N. of cor. for witness.
54.50	Wash, 10 lks. wide, 1 ft. deep, drains NW.
59.15	Highway right-of-way fence, bears N. and S.
71.09	U. S. Highway 80, bears N. and S.
72.20	Highway right-of way fence, bears N. and S.
79.88	The cor. of secs. 23, 24, 25 and 26.
	Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, scattered greasewood, mesquite, palo verde, cacti and grass.
	N. 0° 07' E., bet. secs. 23 and 24.
	Over nearly level bottom land, through scattered undergrowth.
1.30	Road, bears E. and W.
1.50	Fence, bears E. and W.; enter cultivated land.
24.00	Fence, bears E. and W.; leave cultivated land.
27.60	Wash, 30 lks. wide, 3 ft. deep, drains N. 80° W.
39.80	Point for the $\frac{1}{2}$ sec. cor. of secs. 23 and 24, at proportionate dist. No remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam, 22 ins. in the ground, with brass cap mkd.
	T1S R4W S23 S24 1958
	Set a cedar post, 6 ft. long, 6 ins. diam., 1 lk. W. of cor. for witness.
63.00	Enter dense undergrowth, bears E. and W.
65.80	Wash, 1 ch. wide, 4 ft. deep, drains W.
79.60	The cor. of secs. 13, 14, 23 and 24, at proportionate position in longitude and control for latitude by evidence of an old fence.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R4W S14 S13 S23 S24 1958
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor. for witness.
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, scattered to dense salt cedar, willows, mesquite and some grass.

Portion of the Subdivision, T. 1 S., R. 4 W.

<p>Chains</p> <p>39.97</p> <p>58.00</p> <p>62.80</p> <p>64.70</p> <p>65.80</p> <p>79.94</p>	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., which is monumented with an iron post recently set.</p> <p>N. 89° 54' W., bet. secs. 13 and 24.</p> <p>Over nearly level bottom land, through scattered undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate dist. No remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W $\frac{1}{4}$ S13 S24 1958</p> <p>Set a cedar post, 6 ft. long, 6 ins. diam., 1 lk. N. of cor. for witness.</p> <p>Enter dense undergrowth, bears ENE. and SW.</p> <p>Highway fence, bears N. and S.</p> <p>U. S. Highway No. 80, bears N. and S.</p> <p>Highway right-of-way fence, bears N. and S.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, scattered to dense salt cedar, willows, mesquite and grass.</p>	
	<p>From the cor. of secs. 34 and 35, which is monumented with a 2 in. iron post, set, mkd. and witnessed as described in the official record.</p> <p>N. 0° 04' E., bet. secs. 34 and 35.</p> <p>Desc. over general N. slope.</p> <p>33.70 Wash, 10 lks. wide, 1 ft. deep, drains NW.</p> <p>39.89 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35; which is monumented with a mound of stone.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W $\frac{1}{4}$ S34 S35 1958</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>N. 0° 25' E., beginning new measurement.</p> <p>Desc. over rolling general N. slope.</p>	

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains

39.95

Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.
No remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground,
with brass cap mkd.

T1S R4W

S27 | S26

S34 | S35

1958

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling.

Soil, rocky; and gravelly.

Timber, none.

Undergrowth, scattered greasewood, palo verde, cacti and grass.

From the cor. of secs. 25, 26, 35 and 36.

N. 89° 52' W., bet. secs. 26 and 35.

Over rolling land, through scattered undergrowth.

2.50 Wash, 10 lks. wide, 1 ft. deep, drains N.

2.80 Highway right-of-way fence, bears N. 10° E. and S. 10° W.

4.70 U. S. Highway No. 80, bears N. 10° E. and S. 10° W.

5.90 Highway right-of-way fence, bears N. 10° E. and S. 10° W.

13.90 Wash, 20 lks. wide, 10 ft. deep, drains N. 10° E.

21.30 Low spur, slopes N.

31.60 Wash, 20 lks. wide, 1 ft. deep, drains NW.

40.09 The ¼ sec. cor. of secs. 26 and 35, monumented with a mound of stone
partly imbedded in the ground.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground,
with brass cap mkd.

T1S R4W

S26

S35

1958

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

S. 88° 13' W., beginning new measurement.

10.60 Road, bladed, bears N. and S.

15.90 Wash, 20 lks. wide, 1 ft. deep, drains N. 30° W.

30.90 Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.

40.00 The cor. of secs. 26, 27, 34 and 35.

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains	<p>Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, scattered greasewood, palo verde, cacti and grass.</p>
<p>12.10 39.20 39.95</p>	<p>N. 0° 21' W., bet. secs. 26 and 27. Desc. over general N. slope through scattered undergrowth. Wash, 10 lks. wide, 2 ft. deep, drains NW. Road, bears E. and W. Point for the $\frac{1}{2}$ sec. cor. of secs. 26 and 27, as determined latitudinally by a fence bearing E. and W., and proportioned for longitude.</p>
<p>19.40</p>	<p>At the cor. point Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R4W S27 S26 1958 Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. N. 0° 21' W., beginning new measurement.</p>
<p>39.93</p>	<p>Irrigation ditch, bears E. and W.; enter cultivated land bearing E. and W. Thence along road, bearing N. and E.</p>
<p>39.93</p>	<p>The cor. of secs. 22, 23, 26 and 27, as reestablished at the intersection of a road south, a road east, a fence line west and a fence line north. At the cor. point Bury an oak stub, 2 ft. long, 2 ins. sq., 2 ft. in the ground, from which An iron post, 28 ins. long, 2 ins. diam., 22 ins. in the ground for reference monument, bears N. 74° 58' W., 40 lks. dist., with brass cap mkd. T1S R4W S22 RM 1958, and an arrow pointing to the true cor. An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground for reference monument, bears S. 74° 58' E., 40 lks. dist., with brass cap mkd. T1S R4W S26 RM 1958, and an arrow pointing to the true cor. Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, scattered greasewood, palo verde, cacti and grass.</p>

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains	
	From the cor. of secs. 23, 24, 25 and 26. N. 89° 44' W., bet. secs. 23 and 26. Over nearly level land, through scattered undergrowth.
8.40	Fence, bears ENE. and SW.; enter cultivated land.
39.97	The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, as determined by the center line of a road N. and S., a fence line E. At the cor. point Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R4W $\frac{1}{4}$ S23 S26 1958 Deposit broken glass at base of post for witness. <hr/> West, beginning new measurement. Continue through farming land.
40.51	The cor. of secs. 22, 23, 26 and 27. Land, level. Soil, sandy loam. Timber, none. Undergrowth, none.
	N. 0° 36' E., bet. secs. 22 and 23. Over level bottom land, through scattered undergrowth on E. and cultivated land on W.
22.00	Fence, bears W. from fence bearing N. and S.; leave cultivated land, enter scattered undergrowth,
34.80	Clay bank, 10 ft. high, bears N. 70° W. and S. 70° E.
38.00	Fence, bears N. 30° E. and S. 30° W.
39.50	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate dist. No remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R4W $\frac{1}{4}$ S22 S23 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.
42.50	Gila River, 1 chain wide, 4 ft. deep, drains NW.
68.50	Flood channel, 60 lks. wide, 2 ft. deep, drains W.
75.00	

Portion of the Subdivision, T. 1 S., R. 4 W.

<p>Chains 79.00</p>	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist. in longitude and control for latitude by an old fence.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S15 S14 S22 S23 1958</p> <p>Set an oak post, 6 ft. long, 4 ins. diam., 2 lks. W. of cor. for witness.</p> <p>Land, level. Soil, sandy loam. Timber, none. Undergrowth, scattered mesquite, salt cedar, willows and sparse grass.</p>
<p>39.90</p>	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89° 38' W., bet. secs. 14 and 23.</p> <p>Over nearly level bottom land, through medium dense undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate dist. No remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ S14 S23 1958</p> <p>Set a mesquite post, 6 ins. diam., 6 ft. long, 2 ft. in the ground, 2 lks. W. of cor. for witness.</p>
<p>66.20</p>	<p>Fence, bears N. 70° E. and S. 70° W.</p>
<p>73.40</p>	<p>Fence, bears N. 70° W. and S. 70° E.</p>
<p>79.80</p>	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, level. Soil, sandy loam. Timber, none. Undergrowth, scattered mesquite, salt cedar, willows and sparse grass.</p>
<p>9.40</p>	<p>Small gulch, course N. 10° E.</p>
<p>15.60</p>	<p>Same gulch, course N. 30° W.</p>
<p>39.97</p>	<p>From the cor. of secs. 33 and 34, on the S. bdy. of the Tp., which is monumented with a 2 ins. iron post, set, mkd. and witnessed as described in the official record.</p> <p>N. 0° 10' E., bet. secs. 33 and 34.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 33 and 34. No remaining evidence of the original cor.</p>

Portion of the Subdivision, T₁ S., R. 4 W.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R4W

½

S33|S34

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

65.20 Wash, 10 lks. wide, 1 ft. deep, drains N. from SSE.

71.20 Leave wash, course N. 20° W.

79.94 Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist. No remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R4W

S28|S27

S33|S34

1958

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Land, rolling.

Soil, rocky and gravelly.

Timber, none.

Undergrowth, scattered greasewood, mesquite, palo verde, cacti and sparse grass.

From the cor. of secs. 26, 27, 34 and 35.

N. 89° 44' W., bet. secs. 27 and 34.

Over rolling land, through scattered undergrowth.

9.10 Fence, bears N. and S.

39.98 Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate dist. No remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R4W

¼ S27

S33|S34

1958

Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of cor.

47.50 Wash, 40 lks. wide, 2 ft. deep, drains N. 30° W.

54.30 Road, bears N. 20° E. and S. 20° E.

57.20 Wash, 10 lks. wide, 2 ft. deep, drains N.

59.30 Wash, 10 lks. wide, 2 ft. deep, drains NE.

62.10 Wash, 6 lks. wide, 2 ft. deep, drains N.

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains	
76.80	Wash, 10 lks. wide, 2 ft. deep, drains N. 20° W.
79.96	The cor. of secs. 27, 28, 33 and 34. Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, scattered greasewood, mesquite, palo verde, cacti and sparse grass.
	N. 0° 26' E., bet. secs. 27 and 28. Desc. over general N. slope, through scattered undergrowth.
14.10	Bend in wash, 10 lks. wide, 1 ft. deep, drains N. 30° E. from S. 20° E.
22.00	Wash, drains N. 20° E. from S. 10° E.
39.50	Road, bears E. and W.
39.97	The point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, controlled latitudinally by an old fence E. and W. and proportion for longitude. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R4W $\frac{1}{4}$ S28 S27 1958
	Raise a mound of stone 3 ft. base, 2½ ft. high, W. of cor. N. 0° 26' E., beginning new measurement.
13.10	Flood dike, bears N. 70° E. and S. 70° W.
17.00	Drainage ditch, drains S. 80° W.
17.50	Road, bears N. 70° E. and S. 70° W.
17.80	Irrigation ditch, flows S. 70° W.
19.10	Drainage ditch, drains S. 80° E.
19.70	Road on dike, bears S. 80° E. and N. 80° W.; thence over cultivated land.
27.20	Concrete ditch, drains W.
33.60	Road, bears E. and W.
38.10	Irrigation ditch, flows W.
39.95	The cor. of secs. 21, 22, 27 and 28, which is monumented by a rotted stake and an old fence cor. with fences N. and E. At the cor. point

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R4W

S21 | S22

S28 | S27

1958

Bury a sandstone 4x3x2 ins., mkd. with a cross (X) at the base of the post for witness.

Land, S.½ rolling, N.½ cultivated land.

Soil, S.½ rocky and gravel, N.½ sandy loam.

Timber, none.

Undergrowth, S.½ scattered mesquite, greasewood, cacti and sparse grass. N.½ none.

From the cor. of secs. 22, 23, 26 and 27.

N. 89° 38' W., bet. secs. 22 and 27.

Over level cultivated land.

39.44

Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate dist. No remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R4W

S22

S27

1958

Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

46.60

Leave cultivated land, enter dense mesquite, bears N. and S.

78.88

The cor. of secs. 21, 22, 27 and 28.

Land, level.

Soil, sandy loam.

Timber, none.

Undergrowth, E.½ none, W.½ dense mesquite.

N. 0° 09' W., bet. secs. 21 and 22.

Over level bottom land, through medium dense brush.

5.00

Fence, corner, bears W. and S.

39.05

Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate dist. No remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R4W

¼

S21 | S22

1958

Set a cedar post, 6 ft. long, 6 ins. diam., 2 lks. W. of the iron post for witness.

Partion of the Subdivision, T. 1 S., R. 4 W.

Chains	
60.00	Enter dense brush, bears E. and W.
70.50	Gila River, 80 lks. wide, 4 ft. deep, flows W.
75.10	Leave dense brush, Arlington Canal, 40 lks. wide, 15 ft. deep, flows SW.
78.10	<p>Point for the cor. of secs. 15, 16, 21 and 22, at the intersection of the on line with unimproved road from the north and an old fence line bearing east and west. road from the north and an old fence line bearing east and west.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p>T1S R4W S16 S15 S21 S22 1958</p>
	Set a mesquite post, 6 ft. long, 4 ins. diam., 2 ft. in the ground, 2 lks. W. of cor.
	<p>Land, level. Soil, sandy loam. Timber, none. Undergrowth, dense mesquite, salt cedar, willows and sparse grass.</p>
	From the cor. of secs. 14, 15, 22 and 23.
	S. 89° 43' W., bet. secs. 15 and 22.
	Over level bottom land, through medium dense undergrowth.
21.20	Asc. over clay bank, 10 ft. high, bears N. 70° E. and S. 70° W.
39.97	Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate dist. No remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T1S R4W S15 ¼ S22 1958</p>
	Set a mesquite post, 6 ft. long, 4 ins. diam., 2 lks. N. of cor.
77.00	Leave dense undergrowth, also Arlington Canal, 40 lks. wide, 15 ft. deep, flows SW.; enter farming land.
79.94	The cor. of secs. 15, 16, 21 and 22.
	<p>Land, level. Soil, sandy loam. Timber, none. Undergrowth, medium to dense mesquite, salt cedar, willows and sparse grass.</p>

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains

From the cor. of secs. 32 and 33, on the S. bdy. of the Tp., which is monumented with a 2 ins. iron post, set, mkd. and witnessed as described in the official record.

N. 0° 10' E., bet. secs. 32 and 33.

Desc. over general N. slope, through scattered undergrowth.

15.30 Wash, 20 lks. wide, 1 ft. deep, drains N. 70° E.

22.90 = Wash, 30 lks. wide, 3 ft. deep, drains NW.

25.50 Wash, 30 lks. wide, 1 ft. deep, drains NW.

39.66 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate dist. No remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R4W

S32|S33

1958

Raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

40.60 Wash, 20 lks. wide, 3 ft. deep, drains NE.

42.60 Same wash, drains NW.

53.20 Wash, 10 lks. wide, 1 ft. deep, drains NW.

62.30 Track road, bears N. 10° W. and S. 10° E.

79.32 Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist. No remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R4W

S29|S28

S32|S33

1958

Raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, rocky and gravelly.

Timber, none.

Undergrowth, scattered greasewood, palo verde, mesquite, cacti and grass.

From the cor. of secs. 27, 28, 33 and 34.

S. 89° 42' W., bet. secs. 28 and 33.

Over rolling land, through scattered undergrowth.

8.70 Wash, 5 lks. wide, 2 ft. deep, drains N. 20° W.

16.30 Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains	
23.80	Track road, bears N. 10° W. and S. 10° E.
26.50	Wash, 10 lks. wide, 2 ft. deep, drains NW.
36.10	Wash, 30 lks. wide, 1 ft. deep, drains N.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate dist. No remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R4W $\frac{1}{4}$ S28 S33 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
44.90	Track road, bears N. and S.
49.20	Wash, 20 lks. wide, 2 ft. deep, drains N. 10° E.
64.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.
65.50	Wash, 20 lks. wide, 3 ft. deep, drains N. 20° W.
80.04	The cor. of secs. 28, 29, 32 and 33. Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, scattered greasewood, palo verde, mesquite, cacti and grass.
	N. 0° 18' E., bet. secs. 28 and 29. Desc. over general N. slope, through scattered undergrowth.
18.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.
29.90	Wash, 20 lks. wide, 2 ft. deep, drains NW.
39.66	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist. No remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R4W $\frac{1}{4}$ S29 S28 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
56.20	Track road, bears N. 70° E. and S. 70° W.
77.40	Desc. over clay bank 10 ft. high, bears N. 70° E. and S. 70° W.; enter Gila River bottom, and dense underbrush.
79.32	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist. No remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains	
	T1S R4W S20 S21 S29 S28 1958
	Set a mesquite post, 6 ft. long, 4 ins. diam., 2 ft. in the ground, 2 lks. W. of the cor.
	Land, rolling.
	Soil, rocky and gravelly.
	Timber, none.
	Undergrowth, scattered greasewood, palo verde, mesquite, cacti and grass.
	From the cor. of secs. 21, 22, 27 and 28.
	S. 89° 14' W., bet. secs. 21 and 28.
	Over level farming land.
10.00	Track road, bears N. and S.
30.00	Concrete irrigation ditch, flows N.; thence over cultivated land.
39.20	Road, on top of dike, bears N. and S.; leave cultivated land, enter scattered undergrowth.
39.90	Fence, bears N. and S.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate dist. No remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R4W S21 $\frac{1}{4}$ S28 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
44.30	Foot of large knoll, bears NW. and S. 20° E.; asc. 200 ft. over E. slope.
50.00	Flat spur, slopes N.; asc. 50 ft. over N. slope.
56.00	Spur, slopes N. 30° W.; desc. 230 ft. over W. slope.
75.00	Foot of knoll, bears NE. and S.; enter dense undergrowth.
80.12	The cor. of secs. 20, 21, 27 and 28.
	Land, E $\frac{1}{2}$ level, W $\frac{1}{2}$ high and rocky.
	Soil, E $\frac{1}{2}$ sandy loam, W $\frac{1}{2}$ rocky clay.
	Timber, none.
	Undergrowth, E $\frac{1}{2}$ none, W $\frac{1}{2}$ scattered greasewood, palo verde, mesquite, willows and salt cedar.
	N. 0° 16' E., bet. secs. 20 and 21.
	Over level bottom land, through dense undergrowth.

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains	
2.00	S. channel of the Gila River, 50 lks. wide, 4 ft. deep, flows SW.
6.00	N. channel of the Gila River, 60 lks. wide, 4 ft. deep, flows S. 70° W.
21.00	Leave dense undergrowth, enter scattered undergrowth.
39.66	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate dist. No remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R4W ¼ S20 S21 1958
	Set an oak post, 6 ft. long, 6 ins. diam., 2 lks. W. of cor. for witness.
48.50	Enter dense undergrowth, bears E. and W.
50.00	Wash, 1 ch. wide, 1 ft. deep, drains ESE.
72.50	Flood canal, 130 lks. wide, 10 ft. deep, flows W. (Arlington Canal)
78.90	Fence, bears E. and W.
79.32	Point for the cor. of secs. 16, 17, 20 and 21, as established from the center line of a fenced road N. and a fenced road W. At the cor. point Set an iron post 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R4W S17 S16 S20 S21 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, level. Soil, sandy loam. Timber, none, Undergrowth, medium to dense salt cedar, willows, some greasewood, rabbit brush and sparse grass.
	From the cor. of secs. 15, 16, 21 and 22. N. 89° 56' W., bet. secs. 16 and 21. Over level farming land.
83.34	Fence, bears N. and S.; this point was selected for the witness ¼ sec. cor. of secs. 16 and 21. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T1S R4W W ¼ S16 C ¼ S21 1958

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains 39.73 79.00 79.46	<p>True point for the $\frac{1}{2}$ sec. cor. of secs. 16 and 2P. This point falls in the middle of a cultivated field and it was impractical to set an iron post at this point. Bury a stone 9x6x5 ins., mkd. with a cross (X), 24 ins. in the ground.</p> <p>Fence, bears N. and S.</p> <p>The cor. of secs. 16, 17, 20 and 2P.</p> <p>Land, level. Soil, sandy loam. Timber, none. Undergrowth, none.</p>
15.60 21.00 34.00 39.87 =	<p>From the cor. of secs. 31 and 32 on the S. bdy. of the Tp., which is monumented with a 2 ins. iron post, set, mkd. and witnessed as described in the official record.</p> <p>N. 0° 12' E., bet. secs. 31 and 32.</p> <p>Desc. over general N. slope, through scattered undergrowth.</p> <p>Enter small rocky gulch, drains N. from SW.</p> <p>Leave rocky gulch, drains NE.</p> <p>Low, flat spur, slopes N. 10° E.</p> <p>Point for the $\frac{1}{2}$ sec. cor. of secs. 31 and 32, at proportionate dist. No remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S31 S32 1958</p>
41.25 42.85 54.25 79.74	<p>Enter wash, 20 lks. wide, 2 ft. deep, drains N. from S. 20° W.</p> <p>Leave wash, drains N. 10° W.</p> <p>Wash, 30 lks. wide, 10 ft. deep, drains NW.</p> <p>The cor. of secs. 29, 30, 31 and 32, which is monumented with a granite stone 18x12x8 ins., mkd. with 5 notches on the E, and 1 notch on the S., firmly set in a mound of stone.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S30 S29 S31 S32 1958</p> <p>Bury original corner stone alongside the iron post. Raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, scattered greasewood, palo verde, mesquite, cacti and grass.</p>

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains	
	<p>From the cor. of secs. 28, 29, 32 and 33, bearing N. 88° 22' W., bet. secs. 29 and 32.</p>
	<p>Over rolling land, through scattered undergrowth.</p>
50.50	<p>Track road, bears N. and S.</p>
4.30	<p>Wash, 30 lks. wide, 2 ft. deep, drains N.</p>
13.60	<p>Track road, bears N. and S.</p>
21.90	<p>Low spur, slopes N. 20° W.</p>
28.80	<p>Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.</p>
40.05	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, which is monumented with a granite stone, 12x9x8 ins. mkd. $\frac{1}{4}$ on the N. face and firmly set in a mound of stone.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W $\frac{1}{4}$ S29 S32 1958</p>
	<p>Bury the original corner stone alongside the iron post.</p>
	<p>S. 89° 54' W., beginning new measurement.</p>
2.15	<p>Ridge, bears N. 70° W. and S. 70° E.</p>
11.90	<p>Wash, 20 lks. wide, 5 ft. deep, drains NE.</p>
22.70	<p>Wash, 20 lks. wide, 6 ft. deep, drains S. 70° W.</p>
30.50	<p>Wash, 20 lks. wide, 3 ft. deep, drains N. 80° W.</p>
33.30	<p>Wash, 80 lks. wide, 2 ft. deep, drains N. 60° W.</p>
39.94	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling.</p> <p>Soil, rocky and gravelly.</p> <p>Timber, none.</p> <p>Undergrowth, scattered greasewood, palo verde, mesquite, cacti and grass.</p>
	<p>S. 88° 57' W., bet. secs. 30 and 31.</p>
	<p>Over rolling land, through scattered undergrowth.</p>
3.25	<p>Low spur, slopes N. 20° E.</p>
5.75	<p>Wash, 30 lks. wide, 2 ft. deep, drains N. 30° E.</p>
8.20	<p>Low spur, slopes N. 30° E.</p>
28.50	<p>Wash, 40 lks. wide, 5 ft. deep, drains N. 30° W.</p>

Portion of the Subdivision, T41 S., R. 4 W.

Chains	
40.16	The $\frac{1}{2}$ sec. cor. of secs. 30 and 31, which is monumented with a granite stone 30x10x8 ins., mkd. $\frac{1}{2}$ on N. face, firmly set in a mound of stone. At the cor. point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T1S R4W 830 S31 1958 Bury the original corner stone alongside the iron post. Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
	N. $89^{\circ} 50'$ W., beginning new measurement.
7.90	Asc. 35 ft. over E. slope.
7.90	Spur, slopes N.; thence along N. slope.
10.00	Spur, slopes N. 30° W.; desc. 40 ft. over W. slope.
19.00	Wash, 80 lks. wide, 2 ft. deep, drains NW.
27.50	Wash, 1 ch. wide, 3 ft. deep, drains NW.
36.60	Road, bears W. and S. 80° E.
39.40	Road, bears WSW and NE.
39.63	The cor. of secs. 25, 30, 31 and 36. Land, rolling. Soil, rocky and gravelly. Timber, none. Undergrowth, scattered greasewood, palo verde, mesquite, cacti and grass.
	From the cor. of secs. 29, 30, 31 and 32. N. $0^{\circ} 14'$ E., bet. secs. 29 and 30. Over rolling land, through scattered undergrowth.
8.20	Wash, 60 lks. wide, 3 ft. deep, drains NW.
26.70	Wash, 30 lks. wide, 5 ft. deep, drains NW.; enter dense brush.
32.50	Road, bears E. and W.
39.20	Point for the $\frac{1}{2}$ sec. cor. of secs. 29 and 30, at proportionate dist. No remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Portion of the Subdivision, T1S R4W

Chains	
	<p>T1S R4W S30 S29 1958</p> <p>Set a mesquite post, 6 ft. long, 4 ins. diam., 2 ft. in the ground, 2 lks. W. of cor. for witness.</p> <p>Cont. through dense undergrowth.</p>
78.40	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist. No remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p>T1S R4W S19 S20 S30 S29 1958</p> <p>Set a mesquite post, 6 ft. long, 4 ins. diam., 2 ft. in the ground, 2 lks. W. of cor. for witness.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, dense mesquite, salt cedar, willows, palo verde, cacti and sparse grass.</p>
3.00	<p>From the cor. of secs. 20, 21, 28 and 29: N. 89° 56' W., bet. secs. 20 and 29.</p> <p>Over nearly level bottom land, through dense undergrowth.</p> <p>South channel of the Gila River, 50 lks. wide, 4 ft. deep, flows S. 70° W.</p>
21.00	<p>North channel of the Gila River, 70 lks. wide, 4 ft. deep, flows S. 70° W.</p>
40.025	<p>Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate dist. No remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p>T1S R4W S20 S29 1958</p> <p>Set a mesquite post, 6 ft. long, 4 ins. diam., 2 ft. in the ground, 2 lks. N. of cor. for witness.</p>
63.50	<p>Track road, bears N. and S.</p>
73.00	<p>Gila River, 60 lks. wide, 4 ft. deep, flows N. 2 chs., thence W.</p>
80.05	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, dense mesquite, salt cedar, willows, palo verde, cacti and sparse grass.</p>

Portion of the Subdivision, T1S, R4W.

Chains

N. 89° 36' W., bet. secs. 19 and 30.

Over nearly level bottom land, through dense undergrowth.

2.50 Gila River, 80 lks. wide, 4 ft. deep, flows S. 80° W.

34.50 Waste or overflow ditch, 20 lks. wide, 6 ft. deep, flows SW.

40.06 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate point in latitude and control for longitude by evidence of an old fence line.Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R4W

 $\frac{1}{4}$ S19

S30

1958

Set a mesquite post, 6 ft. long, 5 ins. diam., 2 ft. in the ground, 2 lks. N. of cor. for witness.

N. 89° 36' W., beginning new measurement.

23.00 Main channel of the Hassayampa River, 1 ch. wide, 2 ft. deep, flows S. from NW.

39.85 The cor. of secs. 19, 24, 25 and 30.

Land, nearly level.

Soil, sandy loam.

Timber, none.

Undergrowth, dense mesquite, salt cedar, willows and sparse grass.

From the cor. of secs. 19, 20, 29 and 30.

N. 0° 28' E., bet. secs. 19 and 20.

Over nearly level bottom land, through dense undergrowth.

1.00 Gila River, 70 lks. wide, 6 ft. deep, flows S. 80° W.

39.20 The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, as identified with the center of a fenced lane N, and old fences E. and W.

At the cor. point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T1S R4W

 $\frac{1}{4}$ S19

S20

1958

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 22' W., beginning new measurement; along center of fenced lane.

Portion of the Subdivision, T. 1 S., R. 4 W.

<p>Chains 12.30</p>	<p>Arlington Canal, 40 lks. wide, 10 ft. deep; flows SW. from NE.</p>
<p>39.99</p>	<p>The cor. of secs. 17, 18, 19 and 20, as identified at the intersection of fenced roads bearing N., E., S. and W.</p> <p>At the cor. point</p> <p>Bury an oak stub, 2 ins. sq., 6 ins. long, 1 ft. in the ground, from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground for reference monument, bears S. 54° E., 80 lks. dist., with brass cap mkd. T1S R4W S20 RM 1958, and an arrow pointing to the true cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground for reference monument, bears N. 54° W., 80 lks. dist., with brass cap mkd. T1S R4W S18 RM 1958, and an arrow pointing to the true cor.</p> <p>Land, level. Soil; sandy loam. Timber, none. Undergrowth, dense mesquite, salt cedar, willows, S½; N½ none.</p>
<p>40.26</p>	<p>From the cor. of secs. 16, 17, 20 and 21. S. 89° 55' W., bet. secs. 17 and 20.</p> <p>Down center of fenced lane.</p> <p>The ¼ sec. cor. of secs. 17 and 20, as determined by the center line of fenced road E. and W., and fences N. and S.</p> <p>At the cor. point</p> <p>Set an oak stub 2x2x6 ins. long, 1 ft. in the ground, from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground for reference monument, bears N. 39° E., 75 lks. dist., with brass cap mkd. T1S R4W S17 RM 1958, and an arrow pointing to the true cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground for reference monument, bears S. 39° W., 75 lks. dist., with brass cap mkd. T1S R4W S20 RM 1958, and an arrow pointing to the true cor.</p> <p>S. 89° 55' W., beginning new measurement.</p> <p>Cont. down center of fenced lane.</p>
<p>39.95</p>	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, level. Soil, sandy loam. Timber, none. Undergrowth, none. Farming land both sides of line.</p>

Portion of the Subdivision, T. 1 S., R. 4 W.

Chains

N. 89° 20' W., bet. secs. 18 and 19.

Down center of fenced lane.

2.00 Farm house, bears S. 3 chs.

27.00 Farm house, bears S. 2 chs.

40.02 The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, as determined by the center of fenced road E. and W., and fences N. and S.

At the cor. point

Set a wooden stub 2x2x6 ins., 1 ft. in the ground; from which

An iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground for reference monument, bears N. 21° W., 38 lks. dist., with brass cap mkd. T1S R4W $\frac{1}{4}$ S18 RM 1958, and an arrow pointing to the true cor.

An iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground for reference monument, bears S. 21° W., 38 lks. dist., with brass cap mkd. T1S R4W $\frac{1}{4}$ S18 RM 1958, and an arrow pointing to the true cor.

N. 89° 20' W., beginning new measurement.

8.00 Farm house, bears S. 2 chs.

39.91 The cor. of secs. 13, 18, 19 and 24.

Land, level.

Soil, sandy loam.

Timber, none.

Undergrowth, none. Farming land both sides of line.

General Description

The extreme south portion of the township surveyed is low rolling land with rocky and sandy gravel soil, and is unsuitable for anything except very limited grazing. A small portion of the area surveyed is being farmed and is very good soil. Balance of the portion surveyed is sandy overflow river bottom covered with very dense mesquite, salt cedar and willows, which is of no value in its present condition as there is no control of the occasional floods.

The average elevation is less than 1,000 ft. The Arizona State Game Commission has a bird refuge in parts of secs. 28, 29 and 30.

There is one dirt road which bisects part of the township surveyed from east to west. U. S. Highway No. 80 bisects the extreme eastern portion of the township from north to south.

4-680
(Feb., 1950)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Boyd S. Owens	Transitman
Donald A. Cannon	Notekeeper
Landon A. Kittell	Chainman
Vernon R. Griffin	Flagman
Richard Brand	Axeman - Cornerman
James E. Jepson	Truck Driver

19

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 26th day of December, 1957, I have ~~surveyed~~ resurveyed a portion of the west boundary and a portion of the subdivision of T. 1 S., R. 4 W.

of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

August 12, 1958
Salt Lake City, Utah

Donald E. Harding
Donald E. Harding
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., JAN 25 1960, 19

The foregoing field notes of the ~~survey of~~ resurvey of a portion of the west boundary and a portion of the subdivision of T. 1 S., R. 4 W., MDM, Nevada

executed by Donald E. Harding having been critically examined and found correct, are hereby approved.

Donald E. Curran
Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 1 S., R. 4 W., MDM, Nevada, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.