

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE DEPENDENT RESURVEY

OF

A PORTION OF THE NORTH BOUNDARY,

A PORTION OF THE EAST BOUNDARY,

THE SOUTH BOUNDARY

AND

A PORTION OF THE SUBDIVISION

OF

TOWNSHIP 2 SOUTH, RANGE 5 WEST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Donald E. Harding - Cadastral Surveyor

Under special instructions dated December 26, 1957, which provided
for the surveys included under Group No. 323, approved December 26, 1957
and assignment instructions dated December 27, 1957.

Survey commenced January 3, 1958.

Survey completed January 29, 1958.

1A

BOOK 4578

INDEX DIAGRAM

Township 2 South, *Range* 5 West

				2	1
6	5	4	3	26 2	17 1
				25	16
7	8	9	10	24 11	15 12
				23	15
18	17	16	15	22 14	14 13
41	40	34	30	21	13
19	39 20	33 21	29 22	20 23	12 24
38	38	33	28	20	11
30	37 29	31 28	27 27	19 26	11 25
36	36	31	27	18	10
31	35 32	30 33	26 34	18 35	9 36 3
8	7	7	6	5	4

Township 2 South, Range 5 West

Chains

A portion of the south and east boundaries and a portion of the subdivisional lines of this township were surveyed by S. W. Foreman in 1871 as represented on the plat approved May 18, 1871. These were all superseded by the survey executed in 1882. The four boundaries and subdivisional lines of the township were surveyed by R. C. Powers in 1882, as represented on the plat approved February 21, 1883. A portion of the south boundary of sec. 36, westerly from the southeast corner of the township to the corner of Ts. 3 S., Rs. 4 and 5 W., was resurveyed by K. L. Siebecker in 1930, as represented on the plat of T. 3 S., R. 4 W., approved June 14, 1932. The east boundary was resurveyed by K. L. Siebecker in 1931, as represented on the plat of T. 2 S., R. 4 W., approved June 14, 1932. The west boundary was resurveyed by P. K. Russell in 1955, as represented on the plat of T. 2 S., R. 6 W., accepted November 15, 1955. The west two miles of the north boundary and a portion of the subdivisional lines in the western part of the township were retraced by S. E. Blout in 1915, partially represented on the supplemental plat of sec. 5, approved February 27, 1917.

The following notes are those of the resurvey of the east 2 miles of the north boundary, the east boundary of sec. 36, the south boundary and a portion of the subdivision. The request for the resurvey was made by the Range Manager, Arizona Grazing Districts 2 and 3, in a memorandum dated December 6, 1955, to facilitate range management and land classification.

The survey was executed with a W. and L. E. Gurley solar transit, serial No. 541332, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition and placed in proper adjustment prior to the beginning of the survey.

Measurements were made with a Lallie steel tape, 5 chains in length, graduated every 1/10 link for the first link, every link for the next 99 links, and every 10 links thereafter. The tape was tested by comparison with a standard steel tape and found to be correct. The measurements were made on the slope, the vertical angle of each interval was ascertained by a clinometer in good adjustment. The horizontal equivalents only are entered in the field note record.

The azimuth of the lines was determined by sustained angulation from U. S. Coast and Geodetic Survey triangulation station "Gillespie", which is located in the NW $\frac{1}{4}$ of sec. 28 of this township, and checked from time to time by solar.

The geographic position of the southeast corner of the township is in latitude 33° 12' 10.738" N. and longitude 112° 42' 35.693" W. The mean magnetic declination was found to be 14° 30' E.

Dependent Resurvey of a Portion of the N. Bdy., T. 2 S., R. 5 W.

Reestablishment of the survey
executed by R. C. Powers in 1882

From the cor. of Ts. 1 and 2 S., Rs. 4 and 5 W., which is monumented with a 3 in. iron post, set, mkd. and witnessed as described in the official record.

S. 87° 39' W., bet. secs. 1 and 36.

Asc. over E. slope, through scattered undergrowth.

3.30 Foot of hill; asc. 350 ft. over S. slope of spur, sloping E.

29.60 Ridge, bears NE. and SW., over N. slope.

Dependent Resurvey of a Portion of the N. Bdy., T. 2 S., R. 5 W.

Chains	
34.00	Spur slopes NW.; desc. 110 ft. over W. slope.
37.80	Wash, 20 lks. wide, 4 ft. deep, drains WNW.; asc. 20 ft. over N. slope.
38.86	The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with a granite stone, 17x10x5 ins., mkd. $\frac{1}{4}$ on N. face. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T1S R5W $\frac{1}{4}$ $\frac{S36}{S 1}$ T2S 1958 Place the original corner stone alongside the iron post. S. 87° 10' W., beginning new measurement. Asc. 10 ft. over N. slope.
7.20	Spur, slopes N.; desc. 40 ft. over NNW. slope.
16.40	Wash, 30 lks. wide, 4 ft. deep, drains N. 20° E.; asc. 220 ft. over rocky E. slope.
22.40	Spur, slopes N.; desc. 170 ft. over NW. slope.
28.10	Wash, 10 lks. wide, 2 ft. deep, drains NW.; desc. 40 ft. over N. slope.
32.80	Spur, slopes NW.; desc. 190 ft. over W. slope.
39.90	Wash, 10 lks. wide, 2 ft. deep, drains N. 10° W.
43.04	The cor. of secs. 1, 2, 35 and 36, monumented with a granite stone, 24x16x10 ins., firmly set in a mound of stone, mkd. with 1 notch on E. and 5 notches on W. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T1S R5W $\frac{S35}{S 2}$ $\frac{S36}{S 1}$ T2S 1958 Place the original corner stone alongside the iron post. Land, mountainous. Soil, rocky, mostly decomposed granite. Timber, none; undergrowth, scattered mesquite, paloverde, greasewood and grass.
12.30	S. 89° 51' W., bet. secs. 2 and 35. Desc. 120 ft. over NW. slope, through scattered undergrowth. Wash, 10 lks. wide, 4 ft. deep, drains WSW.

Dependent Resurvey of a Portion of the N. Bdy., T. 2 S., R. 5 W.

Chains						
20.10	Enter wash, 10 lks. wide, 2 ft. deep, drains W. from S. 60° E.					
22.50	Leave wash, drains N. 60° W.; desc. over gentle W. slope.					
34.10	Wash, 20 lks. wide, 4 ft. deep, drains S. 70° W.					
40.02	The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, which is monumented with an ironwood stake, set in a mound of earth and small stones.					
	At the corner point					
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.					
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T1S R5W</td></tr> <tr><td>$\frac{1}{4}$ S35</td></tr> <tr><td>S 2</td></tr> <tr><td>T2S</td></tr> <tr><td>1958</td></tr> </table>	T1S R5W	$\frac{1}{4}$ S35	S 2	T2S	1958
T1S R5W						
$\frac{1}{4}$ S35						
S 2						
T2S						
1958						
	Bury the ironwood stake alongside the iron post.					
	Raise a small mound of small stones N. of corner.					

	N. 89° 06' W., beginning new measurement.					
	Continue descent over gentle W. slope.					
18.60	Wash, 20 lks. wide, 2 ft. deep, drains N. 80° W.					
38.94	The cor. of secs. 2, 3, 34 and 35, monumented with a rotted stake in a mound of earth and small stones.					
	At the corner point					
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam.; 22 ins. in the ground, with brass cap mkd.					
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T1S R5W</td></tr> <tr><td>S34 S35</td></tr> <tr><td>S 3 S 2</td></tr> <tr><td>T2S</td></tr> <tr><td>1958</td></tr> </table>	T1S R5W	S34 S35	S 3 S 2	T2S	1958
T1S R5W						
S34 S35						
S 3 S 2						
T2S						
1958						
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.					
	Land, rolling.					
	Soil, sandy and rocky.					
	Timber, none.; undergrowth, scattered mesquite, paloverde, greasewood and grass.					

Dependent Resurvey of a Portion of the E. Bdy., T. 2 S., R. 5 W.

<p>Reestablishment of the resurvey executed by K. L. Siebecker in 1931</p>	
<p>From the cor. of secs. 25 and 36 on the E. bdy. of the township, monumented with a 2 in. iron post, set, mkd. and witnessed as described in the official record.</p>	
<p>S. 0° 04' E., on the E. bdy. of sec. 36.</p>	
8.00	Wash, 15 lks. wide, 1 ft. deep, drains S. from N. 20° E.
25.00	Road, bears S. and N. 20° E.

Dependent Resurvey of a Portion of the E. Bdy., T. 2 S., R. 5 W.

Chains 40.00	<p>Point for the $\frac{1}{2}$ sec. cor. of sec. 36.</p> <p>The original iron post was found laying loose on the ground.</p> <p>Reset the 1 in. iron post, 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{2}$ S36 1915</p> <p>From the above corner point, an irrigation well bears W., 22 lks. dist. S. $0^{\circ} 04'$ E., beginning new measurement.</p> <p>Line continues down center of road on bank, W. of drainage ditch.</p>
42.17	<p>Point for the cor. of Ts. 2 S., Rs. 4 and 5 W., as determined by the remains of concrete dug out of the ground on the E. side of an old fence corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T2S R5W R4W S36 S31 1958</p> <p>Set an iron pipe, 6 ft. long, 3 ins. diam., 2 ft. in the ground, 1 lk. W. of iron post.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none; undergrowth, paloverde, greasewood, cacti and sparse grass in N. $\frac{1}{2}$, cultivated land in S. $\frac{1}{2}$.</p>
Dependent Resurvey of the South Boundary of T. 2 S., R. 5 W.	
<p>Reestablishment of the resurvey of the E. $\frac{1}{2}$ of the S. bdy. of sec. 36 executed by K. L. Siebecker in 1930, and the survey of the W. $5\frac{1}{2}$ miles of the S. bdy. executed by R. C. Powers in 1882</p> <p>From the cor. of Ts. 2 S., Rs. 4 and 5 W., a $2\frac{1}{2}$ in. iron post, just established.</p> <p>N. $87^{\circ} 08'$ W., on the S. bdy. of sec. 36.</p> <p>Over level land, through scattered undergrowth.</p> <p>29.95 Irrigation canal, 40 lks. wide, 6 ft. deep, flows SE.</p> <p>31.80 Paved U.S. Highway No. 80, bears NW. and SE.</p> <p>31.95 Power line, bears WNW. and ESE.</p> <p>32.85 Fence, bears NW. and SE.</p> <p>36.94 Point for closing cor. of Ts. 2 S., Rs. 4 and 5 W., as determined by remains of concrete dug out of the ground on the N. side of fence corner.</p> <p>At the corner point</p>	

Dependent Resurvey of the South Boundary, T. 2 S., R. 5 W.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

S36

S 1 | S 6

C C

R5W R4W

T3S

1958

Bury the remains of the concrete at the base of the post.

N. 89° 21' W., beginning new measurement.

3.04 Point for the ¼ sec. cor. of sec. 36 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

¼ S36

1958

Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of corner.

24.70 Drainage ditch, flows S. 60° E.

42.70 Fence, bears N. 10° W. and S.

42.97 Point for the cor. of secs. 35 and 36 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

S35 | S36

1958

Land, level.

Soil, sandy loam.

Timber, none; undergrowth, scattered salt cedar, greasewood.

N. 89° 21' W., on the S. bdy. of sec. 35.

Over level land, through very scattered undergrowth.

39.93 Point for the ¼ sec. cor. of sec. 35 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

¼ S35

1958

Deposit broken glass at base of post.

Dependent Resurvey of the South Boundary, T. 2 S., R. 5 W.

Chains	<p>79.86 Point for the cor. of of secs. 34 and 35 at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T2S R5W S34 S35 1958</p> <p>Deposit a sandstone, 5x3x2 ins., mkd. with a cross (X) at base of post.</p> <p>Land, level. Soil, sandy. Timber, none; undergrowth, very scattered greasewood, ragweed and grass.</p>
30.90	<p>N. 89° 21' W., on the S. bdy. of sec. 34.</p> <p>Over level ground, through very scattered undergrowth.</p> <p>Power line, bears NE. and SW.</p>
39.93	<p>Point for the ¼ sec. cor. of sec. 34 at proportionate dist., there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T2S R5W ¼ S34 1958</p> <p>Deposit a sandstone, 5x4x2 ins., mkd. with a cross (X) at base of post.</p>
46.90	<p>Gila River, 1 ch. wide, 4 ft. deep, flows S. 60° E.</p>
55.50	<p>Dirt bank, 10 ft. high, bears NW. and SE.</p>
64.30	<p>Enterprise canal, 20 lks. wide, 6 ft. deep, flows SE.</p>
65.10	<p>Road, bladed, bears N. 70° W. and SE.</p>
75.60	<p>Road, track, bears N. 70° E. and S. 70° W.</p>
79.86	<p>Point for the cor. of secs. 33 and 34 at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T2S R5W S33 S34 1958</p> <p>Deposit broken glass at base of post.</p> <p>Land, nearly level. Soil, E. of Gila River sandy, W. of river sandy loam. Timber, none; undergrowth, very scattered greasewood, ragweed and sparse grass.</p>

Dependent Resurvey of the South Boundary, T. 2 S., R. 5 W.

Chains	N. 89° 21' W., on the S. bdy. of sec. 33.
	Asc. 50 ft. over gentle E. slope.
8.30	Track road, bears N. 60° W. and S. 60° E.
37.03	The closing cor. of secs. 3 and 4, T. 2 S., R. 5 W., monumented with a granite stone, 12x10x8 ins. above ground, mkd. with 3 notches on E. and W. faces and 6 notches and CC on S. face.
39.93	The $\frac{1}{4}$ sec. cor. of sec. 33, monumented with a granite stone, 20x16x10 ins., dimly mkd.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T2S R5W $\frac{1}{4}$ S33 1958
	Place the original corner alongside the iron post.
	N. 89° 48' W., beginning new measurement.
0.60	Wash, 40 lks. wide, 3 ft. deep, drains N. 60° E.; asc. 90 ft. over SE. slope.
6.30	Short spur, slopes S.; thence over broken S. slope.
27.75	Point of rim rock, bears ENE. and NW.; desc. 60 ft. over SW. slope.
29.85	Wash, 20 lks. wide, 5 ft. deep, drains S. 30° E.; asc. 60 ft. over E. slope.
32.85	Rim of mesa, bears NE. and S. 70° W.; asc. 30 ft. over E. slope.
40.66	The cor. of secs. 32 and 33, monumented with a malpais stone, 18x14x12 ins., firmly set in a mound of stone and mkd. with 4 notches on E. and 2 notches on W.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T2S R5W S32 S33 1958
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
	Land, rolling.
	Soil, sandy loam E. $\frac{1}{2}$, rocky W. $\frac{1}{2}$.
	Timber, none; undergrowth, scattered greasewood, paloverde, cacti and grass.
	West, on the S. bdy. of sec. 32.
	Over nearly level mesa top, through scattered undergrowth.
23.00	Rim, 10 ft. high, bears N. 20° W. and S. 20° E.; desc. 40 ft. over W. slope.
26.40	Wash, 30 lks. wide, 2 ft. deep, drains S. 10° W.; asc. 110 ft. over SE. slope.

Dependent Resurvey of the South Boundary, T. 2 S., R. 5 W.

Chains	
40.20	Spur, slopes S.
40.47	The $\frac{1}{4}$ sec. cor. of sec. 32, monumented with a granite stone, 24x16x10 ins., firmly set in a mound of stone and mkd. $\frac{1}{4}$ on N. face. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. T2S R5W <u>$\frac{1}{4}$ S32</u> 1958 Bury the original corner alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. S. 89° 57' W., beginning new measurement. Desc. 60 ft. over S. slope.
16.60	Wash, 40 lks. wide, 3 ft. deep, drains S. 10° E.; asc. 40 ft. over SE. slope.
23.30	Spur, slopes S.; desc. 10 ft. over SW. slope.
30.10	Bend in wash, 30 lks. wide, 8 ft. deep, drains S. 70° E. from S. 80° W.
35.20	Wash, 30 lks. wide, 2 ft. deep, drains S. 60° E.; asc. 80 ft. over NE. slope.
38.60	Short spur, slopes NE.
40.20	Rocky gulch, 30 lks. wide, 30 ft. deep, drains N. 30° E.
40.63	The cor. of secs. 31 and 32, monumented with a malpais stone, 18x14x12 ins., firmly set in a mound of stone and mkd. with 5 notches on E. and 1 notch on W. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T2S R5W <u>S31 S32</u> 1958 Place the original corner alongside the iron post. Raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor. Land, rolling. Soil, sandy loam E. $\frac{1}{2}$, rocky W. $\frac{1}{2}$. Timber, none; undergrowth, scattered greasewood, paloverde, cacti and grass.
10.30	N. 89° 53' W., on the S. bdy. of sec. 31. Asc. 50 ft. over gentle E. slope.
16.00	Low saddle between hills, bearing N. and S. Wash, 10 lks. wide, 1 ft. deep, drains S.

Dependent Resurvey of the South Boundary, T. 2 S., R. 5 W.

Chains	
26.80	Low, flat spur, slopes S.
35.60	Wash, 10 lks. wide, 1 ft. deep, drains S. 10° E.
40.11	The $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a malpais stone, 18x12x6 ins., firmly set in a mound of stone and mkd. $\frac{1}{4}$ on N. face.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T2S R5W $\frac{1}{4}$ S31 .1958
	Place the original corner alongside the iron post.
	Raise a mound of stone, 3 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.
	N. 89° 53' W., beginning new measurement.
	Desc. 40 ft. over SW. slope.
9.10	Wash, 10 lks. wide, 3 ft. deep, drains S.
17.30	Wash, 5 lks. wide, 1 ft. deep; drains S. 10° W.
22.30	Fence, bears NE. and SW.
31.50	Wash, 5 lks. wide, 1 ft. deep, drains SW.
41.04	The cor. of Ts. 2 S., Rs. 5 and 6 W., monumented with a 3 in. iron post, set, mkd. and witnessed as described in the official record.
	Land, rolling.
	Soil, sandy loam E. $\frac{1}{2}$, rocky W. $\frac{1}{2}$.
	Timber, none; undergrowth, scattered greasewood, paloverde, cacti and grass.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

	Reestablishment of the survey executed by R. C. Powers in 1882
	From the cor. of secs. 35 and 36 on the S. bdy. of the township.
	N. 0° 12' W., bet. secs. 35 and 36.
	Over nearly level land.
12.50	Bend in drainage ditch, drains S. 30° E. from N. 10° W.
21.80	Same drainage ditch, course S. 10° W. from N. 30° E.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W
 $\frac{1}{4}$ S35 S36
1958

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains									
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.								
	Continue over nearly level land, through greasewood.								
40.10	Old fence line, bears E. 40 lks., thence S. and W. 80 lks., thence N. 60° W.								
41.50	Highway right-of-way fence, bears N. 60° W. and S. 60° E.; power line follows right-of-way fence.								
42.50	U.S. Highway No. 80, bears N. 60° W. and S. 60° E.								
44.90	Gila Bend Canal, 30 lks. wide, 6 ft. deep, flows S. 60° E.								
60.20	Wash, 20 lks. wide, 1 ft. deep, drains SW.								
79.96	Point for the cor. of secs. 25, 26, 35 and 36 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr><td colspan="2">T2S R5W</td></tr> <tr><td>S26</td><td>S25</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2">1958</td></tr> </table>	T2S R5W		S26	S25	S35	S36	1958	
T2S R5W									
S26	S25								
S35	S36								
1958									
	Deposit a stone, 4x3x2 ins., mkd. with a cross (X) at base of post.								
	Land, level.								
	Soil, sandy loam.								
	Timber, none; undergrowth, greasewood, rabbit brush and grass.								
	From the cor. of secs. 25 and 36 on the E. bdy. of the township, a 2 in. iron post, set, mkd. and witnessed as described in the official record.								
	N. 89° 27' W., bet. secs. 25 and 36.								
	Over nearly level land, through scattered undergrowth.								
15.50	Wash, 30 lks. wide, 3 ft. deep, drains S. 10° W.								
33.70	Wash, 10 lks. wide, 3 ft. deep, drains S. 10° W.								
40.00	The ¼ sec. cor. of secs. 25 and 36, monumented with a decayed wooden stake, set in a mound of stone and earth at the corner point. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.								
	<table border="0"> <tr><td colspan="2">T2S R5W</td></tr> <tr><td>¼</td><td>S25</td></tr> <tr><td></td><td>S36</td></tr> <tr><td colspan="2">1958</td></tr> </table>	T2S R5W		¼	S25		S36	1958	
T2S R5W									
¼	S25								
	S36								
1958									
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.								
	S. 89° 36' W., beginning new measurement.								
11.35	Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.								
20.15	Wash, 20 lks. wide, 1 ft. deep, drains SW.								
27.20	Wash, 20 lks. wide, 1½ ft. deep, drains SW.								

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
40.23	The cor. of secs. 25, 26, 35 and 36. Land, nearly level. Soil, sandy loam. Timber, none; undergrowth, scattered greasewood, mesquite and grass.
	N. 0° 16' E., bet. secs. 25 and 26. Over nearly level land.
28.10	Wash, 20 lks. wide, 1 ft. deep, drains SSW.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T2S R5W $\frac{1}{4}$ S26 S25 1958
	Set a 2x4 in.x10 ft. board alongside the iron post.
42.30	Road and El Paso Natural Gas Co. underground gas line bear E. and W.
43.90	Wash, 10 lks. wide, 6 ins. deep, drains SW.
78.00	Drainage ditch, drains S. from N. 10° E.
79.96	Point for the cor. of secs. 23, 24, 25 and 26 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd. T2S R5W S23 S24 S26 S25 1958
	Land, gently rolling. Soil, sandy loam. Timber, none; undergrowth, greasewood, mesquite, palo verde, saguaro cactus and grass.
	From the cor. of secs. 24 and 25 on the E. bdy. of the township, monumented with a 2 in. iron post, set, mkd. and witnessed as described in the official record. S. 89° 58' W., bet. secs. 24 and 25. Over nearly level land.
1.10	Wash, 20 lks. wide, 2 ft. deep, drains S. 20° W.
11.40	Wash, 80 lks. wide, 6 ft. deep, drains SW.
15.00	Wash, 10 lks. wide, 1 ft. deep, drains SW.
39.85	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25 at proportionate dist.; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T2S R5W ¼ S24 S25 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
55.50	Wash, 20 lks. wide, 1 ft. deep, drains SW.
79.60	Drainage ditch, drains S. 10° W, from NE.
79.70	The cor. of secs, 23, 24, 25 and 26.
	Land, gently rolling. Soil, sandy loam, gravel. Timber, none.; undergrowth, greasewood, mesquite, paloverde, saguaro cactus and grass.
	N. 0° 08' E., bet. secs. 23 and 24.
8.90	Wash, 10 lks. wide, 3 ft. deep, drains S. 20° E.; asc. 125 ft. over steep S. slope of hill.
15.50	Spur, slopes sharply S. 10° E.; asc. 610 ft. over rocky SE. slope.
32.00	Top of ascent of hill, 50 lks. E. of top, slopes sharply S. 70° E.; desc. 195 ft. over rocky ENE. slope.
39.98	Point for the ¼ sec. cor. of secs. 23 and 24 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.
	T2S R5W ¼ S23 S24 1958
40.50	Spur, slopes sharply E.; desc. 415 ft. abruptly over NE. slope.
47.00	Wash, 10 lks. wide, 3 ft. deep, drains E.; asc. 375 ft. over S. slope.
60.80	Spur, slopes sharply SE.; desc. over E. slope.
66.50	Spur, slopes sharply E.; desc. 120 ft. abruptly on N. slope.
68.90	Wash, 20 lks. wide, 2 ft. deep, drains E.; asc. 35 ft. over S. slope.
70.40	Spur, slopes sharply E.; desc. 25 ft. over NE. slope.
71.80	Wash, 10 lks. wide, 3 ft. deep, drains S. 70° E., 4 chs. to junction with wash from the E.; asc. 195 ft. over steep SE. slope.
79.96	The cor. of secs. 13, 14, 23 and 24, monumented with a granite stone, 12x10x6 ins., mkd. with 3 notches on the S. face and 1 notch on the E. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

T2S	R5W
S14	S13
S23	S24
1958	

Land, mountainous.
Soil, rocky gravel.
Timber, none; undergrowth, scattered paloverde, mesquite, greasewood and grass.

From the cor. of secs. 13 and 24 on the E. bdy. of the township, monumented with a 2 in. iron post, set, mkd. and witnessed as described in the official record.

N. 89° 56' W., bet. secs. 13 and 24.

Over steep rocky slopes.

- 3.85 Spur, slopes S. 10° E.; desc. 55 ft. over SW. slope.
- 12.25 Wash, 30 lks. wide, 10 ft. deep, drains S. 10° E.
- 17.35 Foot of slope, bears N. 10° W. and S. 20° E.; asc. 35 ft.
- 22.55 Spur, slopes S. 10° E.; desc. 115 ft. over NE. slope.
- 24.95 Wash, 5 lks. wide, 1 ft. deep, drains S. 30° W., about 2 chs. from head; asc. 50 ft. over SE. slope.
- 29.05 Spur, projects S. 20° W., 1 ch. to end; desc. 175 ft.
- 34.25 Wash, 30 lks. wide, 8 ft. deep, drains S. 10° W., foot of spur.
- 36.50 Wash, 5 lks. wide, 3 ft. deep, drains SE. about 3 chs. to junction with wash from N., gentle S. slope.
- 39.63 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24 at proportionate dist.; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S	R5W
$\frac{1}{4}$	S13
	S24
1958	

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

- 43.35 Wash, 50 lks. wide, 10 ft. deep, drains S. 10° W.; asc. 360 ft. over SE. slope.
- 56.25 Spur, slopes S. 20° W.; desc. 10 ft. over S. slope.
- 62.95 Wash, 20 lks. wide, 3 ft. deep, drains S. 10° E.; asc. 205 ft. over SE. slope.
- 68.45 Spur, slopes S. 10° W.; desc. 130 ft. over broken S. slope.
- 76.25 Wash, 10 lks. wide, 2 ft. deep, drains S. 10° W.
- 77.46 Wash, 10 lks. wide, 2 ft. deep, drains S. 10° E. about 4 chs. to junction with wash from N. 10° W.; asc. 85 ft. over steep SE. slope.
- 79.26 Cor. of secs. 13, 14, 23 and 24.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

Land, mountainous.
Soil, rocky, sand and gravel.
Timber, none; undergrowth, scattered mesquite, paloverde, greasewood and grass.

From the cor. of secs. 13, 14, 23 and 24.

N. 0° 15' W., bet. secs. 13 and 14.

Asc. 70 ft. over S. slope.

3.40 Top of mountain, bears NE. and SW.; desc. 600 ft. to the $\frac{1}{4}$ sec. cor. over rocky NNW. slope.

39.05 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

$\frac{1}{4}$

S14 | S13

1958

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

41.70 Wash, 30 lks. wide, 10 ft. deep, drains N. 80° W., over rolling W. slope; desc. 55 ft.

49.65 Wash, 10 lks. wide, 6 ft. deep, drains N. 70° W.

57.00 Wash, 10 lks. wide, 5 ft. deep, drains N. 70° W.; asc. 15 ft. over rolling SW. slope.

62.00 Low spur, projects N. 70° W.; desc. 60 ft. over rolling land draining W.

66.10 Wash, 20 lks. wide, 6 ft. deep, drains N. 80° W.

78.10 The cor. of secs. 11, 12, 13 and 14, monumented with a granite stone, 16x8x6 ins., dimly mkd.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

S11 | S12

S14 | S13

1958

Raise mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Land, mountainous.

Soil, sandy loam and gravel.

Timber, none; undergrowth, scattered mesquite, paloverde, greasewood, saguro cactus and grass.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
	From the cor. of secs. 12 and 13 on the E. bdy. of the township, monumented with a 2 in. iron post, set, mkd. and witnessed as described in the official record.
	S. 89° 58' W., bet. secs. 12 and 13.
	Asc. 120 ft. over SE. slope.
9.55	Saddle in ridge, bearing N. 30° E. and S. 30° W.; desc. 100 ft. over W. slope.
13.85	Wash, 10 lks. wide, 3 ft. deep, drains N. 20° W. about 1 ch., thence N. 70° W.
18.80	Low spur, slopes NW.; desc. 260 ft. over rolling N. slope.
36.45	Wash, 100 lks. wide, 2 ft. deep, drains N. 30° W.
38.65	Wash, 20 lks. wide, 10 ft. deep, drains NW.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T2S R5W. $\frac{1}{4}$ $\frac{S12}{S13}$ 1958
41.85	Asc. 105 ft. over SE. slope.
48.15	Top of ascent, slopes S.; desc. 200 ft. over rolling NW. slope.
67.65	Wash, 40 lks. wide, 10 ft. deep, drains N. 70° W.
75.65	Wash, 10 lks. wide, 10 ft. deep, drains S. 80° W. from SE.; rolling land drains W.
77.65	Wash, 20 lks. wide, 10 ft. deep, drains SW., 1 ch. to junction with wash from SE.
79.25	Wash, 30 lks. wide, 15 ft. deep, drains NW.
79.86	Cor. of secs. 11, 12, 13 and 14.
	Land, rolling. Soil, sandy loam and rocky. Timber, none; undergrowth, mesquite, paloverde, cacti and grass.
	N. 0° 19' W., bet. secs. 11 and 12.
	Asc. over rolling W. slope.
1.45	Wash, 20 lks. wide, 10 ft. deep, drains NW.; over rolling W. slope.
5.05	Wash, 50 lks. wide, 6 ft. deep, drains NW., 1 ch. to junction with wash from E.
7.45	Wash, 30 lks. wide, 10 ft. deep, drains W.; asc. rolling W. slope.
17.35	Foot of hill, bears NE. and W.; asc. 440 ft. over SE. slope.
31.40	Top of hill, bears E. and S. 80° W.; desc. 125 ft. over NW. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

- 35.85 Wash, 5 lks. wide, 2 ft. deep, drains sharply NW.
- 38.65 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12 at proportionate dist.; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
- T2S. R5W
 $\frac{1}{4}$
S11 | S12
1958
- 39.50 Spur, slopes sharply N. 30° W.; desc. 275 ft. over N. slope.
- 48.20 Wash, 20 lks. wide, 3 ft. deep, drains N. 20° W. over rolling W. slope.
- 54.50 Wash, 20 lks. wide, 3 ft. deep, drains NW., about 2 chs. to junction with wash from E.
- 59.00 Wash, 40 lks. wide, 15 ft. deep, drains S. 70° W.; asc. 10 ft. over rolling land, draining W.
- 63.85 Wash, 20 lks. wide, 10 ft. deep, drains W.; asc. 50 ft. over S. slope.
- 67.80 Spur, slopes N. 70° W.; desc. 70 ft. over N. slope.
- 77.20 Wash, 60 lks. wide, 10 ft. deep, drains W.
- 77.30 Point for the cor. of secs. 1, 2, 11 and 12 at proportionate dist.; there is no remaining evidence of the original corner. Point falls in a wash, hereinafter described.
- Witness cor. for secs. 1, 2, 11 and 12 bears N. $1^{\circ} 59'$ W., 50 lks. dist.
- Land, rolling slopes.
Soil, sandy loam.
Timber, none; undergrowth, mesquite, paloverde, saguaro cactus, greasewood and grass.
-
- From the cor. of secs. 1 and 12 on the E. bdy., monumented with an iron post, set, mkd. and witnessed as described in the official record.
- S. $88^{\circ} 37'$ W., bet. secs. 1 and 12.
- Over gently rolling land.
- 14.00 Wash, 20 lks. wide, 2 ft. deep, drains N. 60° W.; desc. 30 ft. to $\frac{1}{4}$ sec. cor.
- 16.80 Wash, 30 lks. wide, 1 ft. deep, drains NW.
- 22.20 Wash, 10 lks. wide, 3 ft. deep, drains NW.
- 27.40 Fence, bears N. 30° W. and S. 30° E.
- 29.30 Wash, 10 lks. wide, 2 ft. deep, drains N. 30° W.
- 36.50 Wash, 10 lks. wide, 3 ft. deep, drains NW.
- 39.86 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12 at proportionate dist.; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
	T2S R5W $\frac{1}{4}$ $\frac{S\ 1}{S12}$ 1958
44.90	Wash, 10 lks. wide, 4 ft. deep, drains N. 10° W.; asc. 20 ft.
46.00	Wash, 10 lks. wide, 3 ft. deep, drains N. 20° W.
50.50	Spur; slopes NW.; continue over rolling land; desc. 65 ft.
60.50	Wash, 10 lks. wide, 2 ft. deep, drains NW.
63.40	Road, bears NW. and SE.; desc. 10 ft.
74.60	Wash, 30 lks. wide, 1 ft. deep, drains NW.
79.72	True point for the cor. of secs. 1, 2, 11 and 12. Land, gently rolling. Soil, sandy loam, gravel. Timber, none; undergrowth, mesquite, paloverde, greasewood, cacti and grass.
	From the true point for the cor. of secs. 1, 2, 11 and 12. N. 1° 59' W., bet. secs. 1 and 2. Over rolling land, draining W.
0.50	Point for the witness cor. of secs. 1, 2, 11 and 12. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T2S R5W $\frac{S\ 2}{S11} \frac{S\ 1}{S12}$ W C 1958
7.35	Wash, 50 lks. wide, 3 ft. deep, drains N. 80° W.
8.25	Wash, 20 lks. wide, 2 ft. deep, drains W., about 2 chs. to junction with larger wash.
9.05	Wash, 20 lks. wide, 1 ft. deep, drains SW.; asc. 40 ft. over S. slope.
23.25	Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. 40 ft. over rolling S. slope.
27.55	Recross wash at bend, drains S. 10° E. from N. 20° E.; asc. 35 ft. over SE. slope.
38.66	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T2S R5W $\frac{1}{4}$ $\frac{S\ 2}{S11} \frac{S\ 1}{S12}$ 1958
	Asc. 430 ft. over rocky ESE. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
57.25	Top of ridge, bears NE. and S. 30° W.; desc. 270 ft. over rocky W. slope.
62.45	Wash, 10 lks. wide, 2 ft. deep, drains S. 80° W.; asc. 90 ft. over S. slope.
70.75	Spur, projects N. 30° W.; desc. 290 ft. over NE. slope.
78.66	The cor. of secs. 1, 2, 35 and 36.
	<p>Land, mountainous. Soil, gravel and rocky. Timber, none; undergrowth, scattered mesquite, greasewood, paloverde, cacti and grass.</p>
	<p>From the cor. of secs. 34 and 35 on the S. bdy. of the township. N. 0°32' W., bet. secs. 34 and 35. Over nearly level overflow land of the Gila River.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T2S R5W $\frac{1}{4}$ S34 S35 1958</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Deposit broken glass at base of post.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T2S R5W S27 S26 S34 S35 1958</p> <p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, W. of cor. Land, nearly level. Soil, sandy clay and loam. Timber, none; undergrowth, scattered greasewood and mesquite and grass.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p>
	<p>N. 89° 14' W., bet. secs. 26 and 35.</p>
	<p>Over nearly level land.</p>
8.30	Wash, 10 lks. wide, 6 ins. deep, drains SW.
12.90	Wash, 10 lks. wide, 6 ins. deep, drains SW.
28.10	Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
35.10	Wash, 20 lks. wide, 3 ft. deep, drains S. 20° W.
38.40	Cultivated land, bears N. and S., about 1 ch., thence NW.
39.10	Drainage ditch, bears SE. from NW.; leave cultivated land.
40.23	Point for the $\frac{1}{2}$ sec. cor. of secs. 26 and 35 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T2S R5W $\frac{1}{2}$ $\frac{S26}{S35}$ 1958 </div>
	Set a mesquite post alongside the iron post.
46.15	Gila Bend Canal, 40 lks. wide, 6 ft. deep, flows SE.
48.85	U.S. Highway No. 780, bears NW. and SE.
50.05=	Highway right-of-way fence and power lines bears NW. and SE.
65.65	Drainage ditch, 30 lks. wide, 5 ft. deep, flows SE.
74.85	Desc. over clay bank, 10 ft. high, bears NW. and SE.
80.46	The cor. of secs. 26, 27, 34 and 35. Land, nearly level. Soil, sandy loam. Timber, none; undergrowth, scattered greasewood and mesquite and grass.
	From the cor. of secs. 26, 27, 34 and 35. N. 0° 46' E., bet. secs. 26 and 27. Over nearly level land.
3.10	Asc. over clay bank, 10 ft. high, bears NW. and SE.
9.80	Power line, bears N. 20° E. and S. 20° W.
14.80	Fence, bears N. 70° W. and S. 70° E.
15.60	U.S. Highway No. 780, bears N. 70° W. and S. 70° E.
17.50	Gila Bend Canal, 20 lks. wide, 6 ft. deep, flows S. 70° E. over cultivated land.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 26 and 27 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T2S R5W $\frac{1}{2}$ S27 S26 1958 </div>
40.40	El Paso Natural Gas Co. underground gas line bears E. and W.
60.60	Leave cultivated land, bears E. and W.; over level land, through greasewood and mesquite.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

80.00

Point for the cor. of secs. 22, 23, 26 and 27 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T2S R5W	
S22	S23
S27	S26
1958	

Set a 2x4 in.x 10 ft. board in the ground alongside the iron post.

Land, level.

Soil, loam and sand.

Timber, none; undergrowth, greasewood, mesquite and grass.

From the cor. of secs. 23, 24, 25 and 26.

N. 89° 08' W., bet. secs. 23 and 26.

Over gently rolling land, draining S.

0.50 Dike, bears N. and S., about 2 chs. dist.

21.20 Wash, 20 lks. wide, 10 ft. deep, drains S. 20° W.

27.30 Wash, 20 lks. wide, 10 ft. deep, drains S. 30° E.

39.89 Point for the ¼ sec. cor. of secs. 23 and 26 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T2S R5W	
¼ S23	
S26	
1958	

Desc. 35 ft. over gently rolling land.

52.00 Wash, 20 lks. wide, 3 ft. deep, drains S. 30° W.; continue over rocky level land.

60.30 Wash, 20 lks. wide, 3 ft. deep, drains S.

79.78 The cor. of secs. 22, 23, 26 and 27.

Land, rolling and rocky.

Soil, sand and gravel.

Timber, none; undergrowth, mesquite, paloverde, greasewood, saguaro cactus and grass.

From the cor. of secs. 22, 23, 26 and 27.

N. 1° 25' E., bet. secs. 22 and 23.

0.70 Flood control dike, bears N. 80° E. and S. 70° W.

9.90 Road, bears N. 70° E. and S. 60° W., over S. slope.

24.00 Base of abrupt ascent, bears E. and SW.; asc. 30 ft. over S. slope.

26.20 Power line, bears S. 5° E. and N. 5° W.; asc. 110 ft. over S. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

- 33.60 Ridge, bears E. and W.; fence along top of ridge; desc. 65 ft. over N. slope.
- 38.20 Wash, 10 lks. wide, 3 ft. deep, drains N. 20° W.; desc. 15 ft. over W. slope.
- 40.01 The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented by a granite stone, 13x6x12 ins., mkd. $\frac{1}{4}$ on the W. face.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, with brass cap mkd.
- T2S R5W
 $\frac{1}{4}$
S22 | S23
1958
- Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
-
- N. 0° 05' E., beginning new measurement.
- Desc. 50 ft. over N. slope.
- 9.10 Wash, 20 lks. wide, 4 ft. deep, drains SW. about 3 chs., thence W.; asc. 60 ft. over SE. slope.
- 14.30 Spur, slopes S. 30° W.; desc. 75 ft. over NW. slope.
- 19.10 Wash, 30 lks. wide, 4 ft. deep, drains S. 20° W.; asc. 10 ft. over rolling land, draining W.
- 21.80 Wash, 10 lks. wide, 5 ft. deep, drains S. 60° W.; asc. 10 ft.
- 28.70 Wash, 10 lks. wide, 10 ft. deep, drains W.
- 34.50 Wash, 10 lks. wide, 4 ft. deep, drains W.
- 39.00 Wash, 30 lks. wide, 20 ft. deep, drains S. 80° W.
- 39.91 The cor. of secs. 14, 15, 22 and 23, monumented with a granite stone, 16x14x12 ins., dimly mkd.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 2 $\frac{1}{2}$ ft. base to top, with brass cap mkd.
- T2S R5W
S15 | S14
S22 | S23
1958
- Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
- Land, rolling.
Soil, sandy, loam and gravel.
Timber, none.
Undergrowth, mesquite, paloverde, cacti and grass.
-
- From the cor. of secs. 13, 14, 23 and 24.
- N. 89° 06' W., bet. secs. 14 and 23.
- Asc. 50 ft. to top of mountain, over SE. slope.
- 2.30 Top of mountain, bears ENE. and WSW.; desc. 200 ft. over broken N. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
20.40	Spur, slopes N.; desc. 230 ft. over broken N. slope.
36.90	Spur, projects NW. about 2 chs., thence N. 70° W.
39.54	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 ins. in solid granite, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T2S R5W $\frac{1}{4}$ $\frac{S14}{S23}$ 1958 Asc. 60 ft. over SE. slope.
43.60	Spur, slopes SW., 1 ch. to end; desc. W. slope; desc. 310 ft. to sec. cor.
48.10	Wash, 10 lks. wide, 1 ft. deep, drains sharply S. 70° W.; desc. steep W. slope.
56.10	Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.
60.10	Wash, 10 lks. wide, 3 ft. deep, drains NW.; desc. rolling NW. slope.
76.10	Wash, 30 lks. wide, 10 ft. deep, drains W. from S. 60° E. along wash.
77.90	Leave wash, drains SW.
79.08	The cor. of secs. 14, 15, 22 and 23. Land, rolling and slopes. Soil, sandy and gravel. Timber, none. undergrowth, mesquite, paloverde, greasewood, and grass.
	N. 0° 26' E., bet. secs. 14 and 15. Over rolling land draining W.
5.00	Wash, 30 lks. wide, 4 ft. deep, drains N. 60° W.
6.90	Wash, 10 lks. wide, 5 ft. deep, drains S. 60° W.
15.40	Wash, 30 lks. wide, 20 ft. deep, drains SW.
25.80	Wash, 40 lks. wide, 20 ft. deep, drains W., 4 chs. to junction with wash from NE.
31.90	Wash, 80 lks. wide, 20 ft. deep, drains SW. from E.; asc. 65 ft. over S. slope.
40.14	The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with a granite stone, 24x20x16 ins., mkd. $\frac{1}{4}$ on W. face. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 2 $\frac{1}{2}$ ft. base to top, with brass cap mkd. T2S R5W $\frac{1}{4}$ S15 S14 1958 Bury corner stone in mound.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

N. 1° 28' E., beginning new measurement.

- 9.80 High rocky hogs back on E. end, slopes S. 60° W.; desc. 360 ft. over NW. slope.
- 28.50 Base of abrupt descent, bears N. 70° E. and SW.; desc. 50 ft. over N. slope.
- 39.80 Wash, 20 lks. wide, 10 ft. deep, drains S. 80° W.
- 39.98 The cor. of secs. 10, 11, 14 and 15, monumented with a granite stone, 16x10x6 ins., dimly mkd.
- Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T2S R5W

S10 | S11

S15 | S14

1958

Bury the original corner alongside the iron post.

Land, rolling.

Soil, sandy loam and gravel.

Timber, none; undergrowth, mesquite, greasewood, paloverde, cacti and grass.

From the cor. of secs. 11, 12, 13 and 14.

N. 85° 40' W., bet. secs. 11 and 14.

Over rolling land.

- 12.80 Small gulch, 40 lks. wide, 20 ft. deep, drains NW.; over rolling land, draining NW.
- 15.10 Wash, 10 lks. wide, 6 ft. deep, drains NW.; asc. 30 ft. over NE. slope.
- 20.90 Spur, projects NW.; desc. 45 ft.
- 25.80 Wash, 10 lks. wide, 2 ft. deep, drains N.; asc. 60 ft. over E. slope.
- 30.80 Top of ascent, slopes N.; desc. 50 ft. over W. slope.
- 36.70 Wash, 10 lks. wide, 2 ft. deep, drains N.; asc. 15 ft. over E. slope.
- 38.49 The ¼ sec. cor. of secs. 11 and 14, monumented with a granite stone, 36x16x14, dimly mkd.
- Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T2S R5W

¼ S11

S14

1958

Bury the original corner stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

	N. 89° 21' W., beginning new measurement.
	Asc. 85 ft. over E. slope.
3.70	Top of ascent; desc. 125 ft. over rolling SW. slope.
21.00	Wash, 20 lks. wide, 10 ft. deep, drains SW.; desc. 10 ft. over rolling slope.
23.10	Top of ascent, slopes S.; desc. 15 ft. over S. slope.
29.90	Wash, 10 lks. wide, 6 ft. deep, drains S., about 2 chs. to junction with wash from E.; desc. 15 ft.
33.10	Wash, 10 lks. wide, 4 ft. deep, drains S., about 50 lks. to junction with wash from E.
38.92	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling. Soil, sandy loam, gravel. Timber, none; undergrowth, mesquite, greasewood, paloverde, cacti and grass.
	N. 2° 45' W., bet. secs. 10 and 11.
	Over rolling land; asc. 10 ft. over S. slope.
2.70	Wash, 10 lks. wide, 3 ft. deep, drains S. 10° W.; asc. 50 ft. over SE. slope.
10.10	Base of steep ascent, bears N. 60° E. and SW.; asc. 60 ft. over SE. slope.
13.50	Top of ascent, slopes E.; desc. 70 ft. over NE. slope.
17.20	Base of steep descent, bears E. and S. 70° W.; desc. 70 ft. over N. slope.
30.80	Wash, 30 lks. wide, 2 ft. deep, drains N. 60° W. turning to N.; desc. 10 ft. over nearly level land.
37.30	Wash, 30 lks. wide, 1 ft. deep, drains NW.
39.06	The $\frac{1}{2}$ sec. cor. of secs. 10 and 11, monumented with a granite stone, 20x14x12 ins., mkd. $\frac{1}{2}$.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T2S R5W $\frac{1}{2}$ S10 S11 1958
	Bury the original corner stone alongside the iron post.
	N. 1° 16' W., beginning new measurement.
14.90	Wash, 40 lks. wide, 1 ft. deep, drains W.; asc. over rolling land, draining W.
15.30	Road, from N. 20° W. turning to S. 10° W.
18.40	Wash, 20 lks. wide, 2 ft. deep, drains SW.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

29.70 Wash, 20 lks. wide, 3 ft. deep, drains S. 20° W., road crosses wash at this point bearing N. 30° E. and S. 20° W.; asc. 30 ft. over SE. slope.

36.00 Power line, bears N. 10° E. and S. 10° W.

36.30 Top of ascent, slopes E. and NE.; desc. 15 ft. over NE. slope.

39.16 The cor. of secs. 2, 3, 10 and 11, monumented with a granite stone, 14x14x6 ins., dimly mkd.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 4½ ft. base to top, with brass cap mkd.

T2S R5W

S 3 | S 2

S10 | S11

1958

Bury the original corner stone alongside the iron post.

Land, rolling.

Soil, sandy loam and gravel.

Timber, none; undergrowth, mesquite, greasewood, paloverde, cacti, and grass.

From the true point for the cor. of secs. 1, 2, 11 and 12.

N. 87° 00' W., bet. secs. 2 and 11.

Over rolling land.

4.55 Wash, 10 lks. wide, 6 ft. deep, drains NW.; desc. 30 ft. over rolling land to ¼ sec. cor.

17.35 Wash, 30 lks. wide, 4 ft. deep, drains S. 70° W.

18.42 Dike, bears N. 70° E. about 10 chs. and S. 70° W.

32.25 Wash, 1 ch. wide, 6 ins. deep, drains SW.

39.89 Point for the ¼ sec. cor. of secs. 2 and 11 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T2S R5W

¼ S 2

S11

1958

Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

65.50 Wash, 20 lks. wide, 1 ft. deep, drains N. 80° W. over rolling land; desc. 10 ft.

78.50 Road, bears N. 20° W. and S. 20° E.; power line bears N. 10° E. for about 10 chs., thence N.

79.78 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.

Soil, sandy loam and gravel.

Timber, none; undergrowth, mesquite, greasewood, paloverde, cacti and grass.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

N. 1° 30' W., bet. secs. 2 and 3.

Over rolling land, draining W.

3.00 Road, bears N. 20° W. and S. 20° E.

7.40 Wash, 20 lks. wide, 2 ft. deep, drains N. 60° W.

12.20 Same road, bears N. 30° E. and S. 10° W.

18.90 Road, bears S. 80° E., about 2 chs. to junction with road bearing N. and S. and S. 80° W.

36.90 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T2S R5W

 $\frac{1}{4}$

S 3 | S 2

1958

Raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.

38.00 Wash, drains N. 30° W.

41.55 Road, bears N. 30° W. and S. 30° E.

47.15 Top of low knoll; desc. gently rolling land.

61.05 Same road, bears N. 10° W, and S. 10° W.

75.10 The cor. of secs. 2, 3, 34 and 35.

Land, rolling.

Soil, sandy loam and gravel.

Timber, none; undergrowth, greasewood, mesquite, cacti and grass.

From the cor. of secs. 33 and 34 on the S. bdy. of the township.

N. 0° 56' W., bet. secs. 33 and 34.

Over nearly level land.

14.85 Road, bears NW. and SE.

15.15 ~~Enterprise~~ Canal, flows SE.

19.65 Desc. over clay bank, bears N. 30° W. and S. 30° E.; continue along river bottom.

39.93 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T2S R5W

 $\frac{1}{4}$

S33 | S34

1958

Raise a collar of stone to top of the iron post.

41.25 Gila River, 60 lks. wide, 4 ft. deep, drains S. 20° E.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

79.86

Point for the cor. of secs. 27, 28, 33 and 34 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

S28 | S27

S33 | S34

1958

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.

Land, nearly level, old river bottom.

Soil, sand clay, gravel.

Timber, none; undergrowth, salt cedar, mesquite and sparse grass.

From the cor. of secs. 26, 27, 34 and 35.

N. 89° 29' W., bet. secs. 27 and 34.

Over nearly level land.

40.20

Point for the ¼ sec. cor. of secs. 27 and 34 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

¼ S27

S34

1958

Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.

80.40

The cor. of secs. 27, 28, 33 and 34.

Land, nearly level.

Soil, sand, clay and gravel.

Timber, none; undergrowth, mesquite, salt cedar and sparse grass.

N. 1° 14' E., bet. secs. 27 and 28.

Over nearly level land.

28.35

Asc. over clay bank, 10 ft. high, bears NW. and SE.

34.05

El Paso Natural Gas Co. underground gas line, bears E. about 8 chs., thence N. 4 chs., thence E; and W. about 19 chs. to bridge across the Gila River, thence NW.

35.35

Fence, bears N. 80° W. and S. 80° E.

36.15

U.S. Highway No. 80; bears NS. 80° W. and S. 80° E.

37.95

Gila Bend Canal, flows S. 80° E. asc. 25 ft. over S. slope.

39.94

Point for the ¼ sec. cor. of secs. 27 and 28 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

T2S R5W

S28 | S27

1958

Asc. 135 ft. over steep S. slope.

40.90 Road at turn, bears N. 70° E. and E.; asc. 120 ft. over steep S. slope.

44.30 Same road, bears N. 20° E. and S. 10° E.; asc. 95 ft. over S. slope.

47.80 Slope changes; asc. 115 ft. over steep SE. slope.

51.90 High rocky spur, projects S. 10° W., about 3 chs. to end; continue along W. slope; asc. 80 ft.

63.10 Spur, slopes S. 80° W., about 8 chs. to end; asc. W. slope, 55 ft.

77.40 Top of ascent, slopes sharply W.; desc. 75 ft. over NW. slope.

79.88 The cor. of secs. 21, 22, 27 and 28, monumented with a malpais stone, 6x8x16 ins., dimly mkd.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 8 ft. base to top, with brass cap mkd.

T2S R5W

S21 | S22

S28 | S27

1958

Place original corner stone alongside the iron post.

Land, level and steep rocky slopes.

Soil, sandy clay and rocky.

Timber, none; undergrowth, greasewood, mesquite, cacti and grass.

From the cor. of secs. 22, 23, 26 and 27.

N. 89° 38' W., bet. secs. 22 and 27.

Over rolling land, through scattered undergrowth.

3.80 Dike, bears N. 70° E. and S. 70° W.; desc. 15 ft.

5.10 Wash, 20 lks. wide, 2 ft. deep, drains S. 70° W.

15.00 Wash, 8 lks. wide, 2 ft. deep, drains S. 10° W.

20.70 Wash, 20 lks. wide, 2 ft. deep, drains S. 20° W., about 4 chs. to junction with wash from E.

23.50 Wash, 20 lks. wide, 2 ft. deep, drains S.

28.60 Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.

33.80 Wash, 10 lks. wide, 2 ft. deep, drains S. 10° E.

39.89 Point for the ¼ sec. cor. of secs. 22 and 27 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
	T2S R5W $\frac{1}{2}$ $\frac{S22}{S27}$ 1958
	Over slightly broken S. slope.
54.00	Road, bears N. and S.; asc. 465 ft. over rocky E. slope.
76.10	Top of mountain, bears N. and S.; desc. 95 ft. over rocky W. slope.
79.78	The cor. of secs. 21, 22, 27 and 28. Land, rolling and rocky slopes. Soil, sandy loam, gravel and rocky. Timber, none; undergrowth, mesquite, greasewood, paloverde, cacti and grass.
	N. 1° 03' E., bet. secs. 21 and 22. Desc. 170 ft. over rocky W. slope.
9.40	Wash, 20 lks. wide, 4 ft. deep, drains sharply S. 70° W. from head, about 4 chs. S. 70° E.; asc. 290 ft. over SW. slope.
13.10	Wash, 5 lks. wide, 2 ft. deep, drains sharply SW. from head, about 2 chs. NE.
17.60	Top of ascent on high rocky knoll, slopes W., about 2 chs. to end, top is 30 lks. E.; desc. 440 ft. over N. slope.
18.00	Wash, 20 lks. wide, 2 ft. deep, drains W.
18.90	Road, unimproved, bears E. and W.
40.08	The $\frac{1}{2}$ sec. cor. of secs. 21 and 22, monumented with a malpais stone, 16x12x10 ins., mkd. $\frac{1}{2}$. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T2S R5W $\frac{1}{2}$ $\frac{S21}{S22}$ 1958
	Bury the original corner alongside the iron post. Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.
	N. 0° 02' W., beginning new measurement. Asc. 205 ft. over S. slope.
11.45	Spur, slopes S. 70° E.; asc. along E. slope.
12.40	Top of E. slope of mountain bearing E. and W.; desc. 230 ft. over NE. slope. This point used for control.
21.45	Base of hill, bears E. and W.
23.00	Wash, 1 ch. wide, 3 ft. deep, drains W.
23.60	Fence, bears N. and W.; cont. over nearly level land alongside fence.
33.50	Fence, bears E. and S.; enter cultivated land.
39.20	Point for the cor. of secs. 15, 16, 21 and 22 at proportionate dist. in latitude as determined from original topographical points and on an extended line of old fence for longitude; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T2S R5W $\frac{1}{2}$ $\frac{S16}{S21} \frac{S15}{S22}$ 1958

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
	<p>Set a 4 in. cedar post W. of cor.</p> <p>From the above corner, top of mountain on sharp ridge bears N., 71.50 chs. dist. This point used for control.</p> <p>Land, mountainous. Soil, sandy clay, rocky gravel. Timber, none; undergrowth, greasewood, mesquite, cacti and grass.</p>
24.00	<p>From the cor. of secs. 14, 15, 22 and 23. S. 89° 56' W., bet. secs. 15 and 22. Desc. over rolling W. slope, through scattered undergrowth. Wash, 40 lks. wide, 5 ft. deep, drains SW.</p>
28.00	Road, graded, bears WNW. and SE.
39.97	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22 at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T2S R5W $\frac{1}{4}$ $\frac{S15}{S22}$ 1958</p>
40.30	Wash, 10 lks. wide, 2 ft. deep, drains WSW.
55.00	Track road, bears NW. and SE.
65.00	Enter cultivated land, bears N. and S.
79.94	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, rocky. Timber, none; undergrowth, scattered greasewood, paloverde, cacti and grass.</p>
3.50	<p>From the cor. of secs. 32 and 33 on the S. bdy. of the township. N. 2° 06' W., bet. secs. 32 and 33. Asc. 20 ft. over rolling bench land, through cacti and greasewood. Wash, 10 lks. wide, 1 ft. deep, drains SE.; asc. 15 ft.</p>
25.00	Top of ascent, slopes SE.; desc. 20 ft. over NE. slope.
40.28	<p>The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with a malpais stone, 12x8x6 ins., mkd. $\frac{1}{4}$.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T2S R5W $\frac{1}{4}$ $\frac{S32}{S33}$ 1958</p>
	<p>Bury the original corner alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
14.20	<p>N. 0° 17' E., beginning new measurement. Desc. 20 ft. over NE. slope. S. ridge of small gulch, bears N. 70° E. and S. 70° W.; desc. 15 ft. over N. slope.</p>
16.40	Wash in bottom of gulch, 20 lks. wide, 2 ft. deep, drains N. 70° E.
17.00	N. edge of gulch, bears N. 70° E. and S. 70° W. over rolling S. slope; desc. 20 ft.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains 40.15	<p>The cor. of secs. 28, 29, 32 and 33, monumented with a malpais stone, 4x14x24 ins., mkd. with 1 notch on S. and 4 notches on E.</p> <p>Set an iron post; 28 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T2S R5W S29 S28 S32 S33 1958</p> <p>Place the original corner stone alongside the iron post.</p> <p>Land, rolling bench land. Soil, rocky. Timber, none; undergrowth, greasewood, cacti and grass.</p>
23.50	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89° 06' W., bet. secs. 28 and 33.</p> <p>Gillespie Dam overflow bottom.</p>
40.24	<p>Gila River, 1 ch. wide, 2 ft. deep, flows S. 10° E.</p> <p>Point for the ¼ sec. cor. of secs. 28 and 33 at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T2S R5W ¼ S28 S33 1958</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
45.90	Dike, bears N. and S.
46.70	Enterprise Canal drains S.
50.00	Road, bears N. and S.; asc. 95 ft.
53.10	Rim of bench, a ledge 10 ft. high, bears N. and S., over nearly level land.
73.10	Wash, 5 lks. wide, 1 ft. deep, drains N.
80.48	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, river bottom and bench land. Soil, sand, clay and gravel. Timber, none; undergrowth, greasewood, mesquite, cacti and grass.</p>
3.00	<p>N. 0° 27' W., bet. secs. 28 and 29.</p> <p>Over rolling E. slope.</p> <p>Wash, 5 lks. wide, 2 ft. deep, drains N. 80° E.</p>
8.60	S. edge of gulch, bears NE. and S. 70° W.
9.90	Wash in bottom of gulch, 20 lks. wide, 3 ft. deep, drains NE.; asc. S. slope.
11.70	N. edge of gulch, bears NE. and S. 70° W., over rolling E. slope.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
23.70	Spur, slopes S. 70° E.; desc. 25 ft.
28.80	S. edge of small gulch, bears N. 70° E. and S. 70° W.
31.90	Wash in bottom of gulch, 10 lks. wide, 2 ft. deep, drains N. 70° E.
33.40	N. edge of gulch, bears N. 70° E. and S. 70° W., over rolling E. slope; asc. 10 ft.
39.70	Wash, 30 lks. wide, 30 ft. deep, drains N. 80° W.
40.75	The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with a malpais stone, 24x18x16 ins., mkd. $\frac{1}{4}$.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T2S R5W $\frac{1}{4}$ S29 S28 1958
	Place the original corner stone alongside the iron post.
	Raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.

	N. 1° 12' E., beginning new measurement.
3.40	Spur, slopes N. 60° E.; desc. 25 ft. over N. slope.
10.30	Wash, 10 lks. wide, 2 ft. deep, drains E. about 3 chs., thence SE.; asc. S. slope, 15 ft.
18.90	El Paso Natural Gas Co. underground gas line and road, bear N. 70° W. and S. 70° E.; desc. 15 ft. over N. slope.
20.00	S. edge of small gulch, bears N. 70° W. and N. 70° E.
22.00	Wash in bottom of gulch, 20 lks. wide, 3 ft. deep, drains N. 70° E.
24.80	N. edge of gulch, bears N. 70° E. and N. 70° W., over rolling land.
33.50	Fence; bears N. 30° E. and S. 30° W.
39.00	Track road, bears ENE. and WNW.
40.39	The cor. of secs. 20, 21, 28 and 29, monumented with a malpais stone, 16x12x10 ins., mkd. with 2 notches on S. and 4 notches on E.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd.
	T2S R5W S20 S21 S29 S28 1958
	Bury the original corner stone alongside the iron post.
	From the above corner, U.S.C. & G.S. triangulation station "Gillespie" bears S. 51° 36' E., 41.49 chs. dist., and is in latitude 33° 13' 42.759" N. and longitude 112° 46' 19.239" W.
	Land, rolling bench.
	Soil, sandy and rocky.
	Timber, none; undergrowth, greasewood, mesquite, cacti and grass.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
	From the cor. of secs. 21, 22, 27 and 28.
	N. 88° 11' W., bet. secs. 21 and 28.
	Desc. 380 ft. over rocky W. slope.
14.50	Foot of mountain, bears N. and S.; enter Gila River bottom.
38.00	Gila River, 1 ch. wide, 2 ft. deep, flows S.
40.85	Point for the $\frac{1}{2}$ sec. cor. of secs. 21 and 28 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T2S R5W $\frac{1}{2}$ $\frac{S21}{S28}$ 1958
	Deposit charcoal at the base of the post.
	Set an oak post, 6 ft. long, 5 ins. diam., 2 ft. in the ground, N. of cor.
56.20	Arlington Canal, drains SE.
	Leave river bottom, bears NNW. and SSE.; asc. 100 ft. over ENE. slope.
59.00	Rim rock on E. edge of bench, bears NNW. and SSE. over bench.
64.10	Track road, bears NE. and SW.
70.20	Track road, bears NE. and SW.
74.60	U.S. Highway No. 80, bears NW. and SE.
75.90	Fence, bears NW. and SE.
76.20	Fence, bears SW. and NE., 1 ch. to cor. with fence, bears NW. and SE.
77.10	Track road, bears ENE. and WSW.
81.70	The cor. of secs. 20, 21, 28 and 29.
	Land, E. $\frac{1}{2}$ high, W. $\frac{1}{2}$ level.
	Soil, sandy loam and rocky.
	Timber, none; undergrowth, salt cedar, mesquite, cacti and grass.
	N. 0° 35' E., bet. secs. 20 and 21.
2.50	Edge of mesa; bears NW. and SE.; desc. 110 ft. over NNE. slope.
4.90	Fence, bears NW. and SE.
5.80	U.S. Highway No. 80, bears NW. and SE.
11.50	Foot of mesa; enter dense salt cedar.
14.80	Fence, bears N. 20° W. and SE.
20.90	Arlington Canal, 10 lks. wide, 3 ft. deep, flows SE.; enter pasture land.
43.78	Point for the $\frac{1}{2}$ sec. cor. of secs. 20 and 21 at proportionate dist.; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

$$\frac{1}{4}$$

S20	S21
-----	-----

1958

Set a cedar post, 6 ft. long, 6 ins. diam., 1 lk. W. of cor.

47.60 Fence, bears E., W. and N.

67.30 Fence cor. bearing N., S. and W.

87.56 The cor. of secs. 16, 17, 20 and 21, as determined by the remains of a wooden stake at a fence cor. bearing S. and W. Also this point corresponds with the point accepted by S. E. Blout in the retracement made in the NW. portion of this township in 1915.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

S17	S16
-----	-----

S20	S21
-----	-----

1958

Land, rolling S. ½, level N. ½.

Soil, rocky S. ½, sandy loam N. ½.

Timber, none; undergrowth, salt cedar, greasewood and grass S. ½, grass only N. ½.

From the cor. of secs. 15, 16, 21 and 22.

N. 82° 23' W., bet. secs. 16 and 21.

Through cultivated farm land.

22.50 Leave cultivated land bearing N. and S.; enter river bottom.

25.70 Gila River, 1 ch. wide, 3 ft. deep, flows S.

29.40 Irrigation ditch, flows S.; enter farm land bearing N. and S.

41.10 Point for the ¼ sec. cor. of secs. 16 and 21 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W

$$\frac{1}{4}$$

S16

S21

1958

Set a mesquite post, 6 ft. long, 4 ins. diam., 1 lk. N. of iron post.

41.40 Track road, bears N. and S.

47.20 Leave farm land, bears N. and S.; enter dense salt cedars and willows.

76.30 Drainage ditch, flows S.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
77.00	Fence, bears N. and S.
82.20	The cor. of secs. 16, 17, 20 and 21. Land, level. Soil, sandy loam. Timber, none; undergrowth, salt cedar and willows.
	From the cor. of secs. 31 and 32 on the S. bdy. of the township. N. 1° 03' W., bet. secs. 31 and 32.
1.40	Rocky gully, 40 lks. wide, 40 ft. deep, drains S. 80° E.; asc. 150 ft. over S. slope, through scattered undergrowth.
39.90	Track road, bears N. 30° E. and S. 30° W.
40.50	Fence, bears N. 30° E. and S. 30° W.
40.70	The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with a malpais stone, 14x8x6 ins., firmly set in a mound of stone, and mkd. $\frac{1}{4}$ on W. face. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. T2S R5W $\frac{1}{4}$ S31 S32 1958 Bury the original corner alongside the iron post. Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor. N. 0° 23' E., beginning new measurement.
0.30	Low flat spur, slopes E.; desc. 40 ft. over NE. slope.
5.20	S. edge of rocky gulch, bears E. and W.; desc. 30 ft. over N. slope.
8.50	Wash, 10 lks. wide, 2 ft. deep, drains S. 80° E.; asc. 30 ft. over S. slope.
10.00	N. edge of rocky gulch, bears E. and W.
13.50	Low flat spur, slopes E.; desc. 80 ft. over NE. slope.
39.99	The cor. of secs. 29, 30, 31 and 32, monumented with a malpais stone, 16x8x6 ins., mkd. with 5 notches on E. and 1 notch on S. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a mound of stone, to top, with brass cap mkd. T2S R5W S30 S29 S31 S32 1958 Place the original corner alongside the iron post. Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

Dependent Resurvey of a portion of the Subdivision, T. 2 S., R. 5 W.

Chains

Land, rolling.
Soil, rocky.
Timber, none; undergrowth, scattered greasewood, paloverde, cacti, ocotillo and sparse grass.

From the cor. of secs. 28, 29, 32 and 33.

N. 89° 46' W., bet. secs. 29 and 32.

Over nearly level mesa land, through scattered undergrowth.

4.60 Wash, 20 lks. wide, 5 ft. deep, drains NE.

24.40 Low flat spur, slopes N.

27.00 Wash, 20 lks. wide, 2 ft. deep, drains NE.

40.18 The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with a malpais stone, 10x8x8 ins., firmly set in a mound of stone, and mkd. $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T2S R5W

$\frac{1}{4}$ $\frac{S29}{S32}$
1958

Place the original corner alongside the iron post.

N. 89° 51' W., beginning new measurement.

Asc. 130 ft. over general ENE. slope.

11.40 Track road, bears NE. and SW.

11.60 Fence, bears NE. and SW.

40.10 The cor. of secs. 29, 30, 31 and 32.

Land, low and rolling.

Soil, rocky.

Timber, none; undergrowth, scattered greasewood, ocotillo, cacti and sparse grass.

S. 89° 31' W., bet. secs. 30 and 31.

Over low rolling land, through scattered undergrowth.

7.10 Slope changes to NW.; desc. 80 ft.

38.10 Wash, 10 lks. wide, 1 ft. deep, drains N. 10° W.

40.10 The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a malpais stone, 18x16x14 ins., firmly set in a mound of stone and mkd. $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

T2S R5W

$$\frac{1}{4} \frac{S30}{S31}$$

1958

Place the original corner alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 89° 44' W., beginning new measurement.

9.50 Wash, 10 lks. wide, 1 ft. deep, drains NW.; desc. 60 ft. over WNW. slope.

40.27 The cor. of secs. 30 and 31 on the W. bdy. of the township, monumented with a 2½ in. iron post, set, mkd. and witnessed as described in the official record.

Land, low and rolling.

Soil, rocky.

Timber, none; undergrowth, scattered greasewood, ocotillo, cacti and sparse grass.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 12' W., bet. secs. 29 and 30.

Desc. 80 ft. over N. slope.

23.60 Wash, 5 lks. wide, 6 ins. deep, drains N. 70° E., wash heads 5 chs. S. 70° W.; desc. 40 ft. over N. slope.

40.14 The ¼ sec. cor. of secs. 29 and 30, monumented with a malpais stone, 18x10x8 ins., firmly set in a mound of stone, and mkd. ¼ on W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T2S R5W

$$\frac{1}{4} \frac{S30|S29}{S30|S29}$$

1958

Place the original corner alongside the iron post.

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

N. 0° 47' E., beginning new measurement.

Desc. 50 ft. over N. slope.

40.81 The cor. of secs. 19, 20, 29 and 30, monumented with a malpais stone, 16x14x10 ins., firmly set in a mound of stone, and mkd. with 5 notches on E. and 2 notches on S.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T2S R5W

S19|S20

S30|S29

1958

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

Place the original corner alongside the iron post.

Land, low and rolling.

Soil, rocky.

Timber, none; undergrowth, scattered greasewood, ocotillo, cacti and sparse grass.

From the cor. of secs. 20, 21, 28 and 29.

West, bet. secs. 20 and 29.

Over slightly rolling land, through scattered undergrowth.

2.20 Track road, bears N. 70° W. and S. 70° E.

15.00 Bend in road, bears N. 80° E. and N. 80° W.

40.25 The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented with a malpais stone, 16x8x6 ins., firmly set in a mound of stone, and mkd. $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T2S R5W

 $\frac{1}{4}$ S20

S29

1958

Place the original corner alongside the iron post.

N. 89° 56' W., beginning new measurement.

12.40 Road, bears N. 60° E. and S. 60° W.

22.10 El Paso Natural Gas Co. underground gas line bears N. 56° W. and S. 56° E.

40.21 The cor. of secs. 19, 20, 29 and 30.

Land, low and rolling.

Soil, rocky.

Timber, none; undergrowth, scattered greasewood, ocotillo, cacti and sparse grass.

N. 89° 48' W., bet. secs. 19 and 30.

Over slightly rolling land, through scattered undergrowth.

5.70 Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.

40.34 The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a malpais stone, 22x14x10 ins., mkd. $\frac{1}{4}$ on N. face, and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd.

T2S R5W

 $\frac{1}{4}$

S19

S30

1958

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains	
	Place the original corner alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	S. 88° 44' W., beginning new measurement.
9.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 10° E.
34.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 10° E.
40.48	The cor. of secs. 19 and 30 on the W. bdy. of the township, monumented with a 2½ in. iron post, set, mkd. and witnessed as described in the official record. Land, low and rolling. Soil, rocky. Timber, none; undergrowth, scattered greasewood, ocotillo, cacti and sparse grass.
	From the cor. of secs. 19, 20, 29 and 30. N. 0° 07' E., bet. secs. 19 and 20. Desc. 65 ft. over gentle N. slope.
15.30	El Paso Natural Gas Co. underground gas line bears N. 56° W. and S. 56° E.
16.30	Road, bears N. 56° W. and S. 56° E.
31.80	Wash, 5 lks. wide, 1 ft. deep, drains N. 30° W.
40.03	The ¼ sec. cor. of secs. 19 and 20, monumented with a malpais stone, 16x14x10 ins., firmly set in a mound of stone, and mkd. ¼ on W. face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd. T2S R5W ¼ S19 S20 1958
	Place the original corner alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 2° 15' E., beginning new measurement. Desc. 30 ft. over N. slope.
24.00	S. edge of rocky draw, bears N. 30° W. and S. 20° E.; desc. 20 ft. over NE. slope.
26.60	Wash, 40 lks. wide, 1 ft. deep, drains N. 30° W.; asc. 20 ft. over SW. slope.
27.70	N. edge of rocky draw, bears N. 30° W. and S. 20° E.
39.15	The cor. of secs. 17, 18, 19 and 20, monumented with a malpais stone, 20x20x12 ins., firmly set in a mound of stone, and mkd. with 5 notches on E. and 3 notches on S.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T2S R5W	
S18	S17
S19	S20
1958	

Place the original corner alongside the iron post.
Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

Land, low and rolling.

Soil, rocky.

Timber, none; undergrowth, scattered greasewood, ocotillo, cacti and sparse grass.

From the cor. of secs. 16, 17, 20 and 21.

S. 84° 13' W., bet. secs. 17 and 20.

Over level farming land paralleling fence.

18.00 Fence, bears S.

26.70 Fence, bears S.

40.12 The ¼ sec. cor. of secs. 17 and 20, as determined from the description and location given by S. E. Blout in his retracement made in 1915.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T2S R5W	
¼	S17
	S20
1958	

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

This corner point is 1 lk. W. of the fence cor. bearing N., S. and E.

S. 83° 56' W., beginning new measurement.

3.00 ~~Arlington Canal~~, flows S.

5.90 Wash, 60 lks. wide, 10 ft. deep, drains S. 20° E.

7.90 Paved road, bears NW. and S. 20° E.; asc. 70 ft. over NE. slope.

8.80 E. rim of mesa, bears NW. and SE.; asc. 25 ft. over NE. slope.

25.00 Flat spur, slopes N. 20° W.; desc. 50 ft. over gentle W. slope.

35.00 E. edge of rocky gully, bears N. and S.; desc. 50 ft.

37.90 Wash, 10 lks. wide, 3 ft. deep, drains NW.; asc. 50 ft.

39.90 W. edge of rocky gully.

39.96 The cor. of secs. 17, 18, 19 and 20.

Dependent Resurvey of a Portion of the Subdivision, T. 2 S., R. 5 W.

Chains

Land, E. $\frac{1}{2}$ level farm land, W. $\frac{1}{2}$ rolling mesa.
 Soil, E. $\frac{1}{2}$ sandy loam, W. $\frac{1}{2}$ rocky.
 Timber, none; undergrowth, E. $\frac{1}{2}$ none, W. $\frac{1}{2}$ scattered greasewood, ocotillo, cacti and sparse grass.

N. 89° 22' W., bet. secs. 18 and 19.

Over mesa top.

- 2.00 W. rim of mesa, bears NE. and SW.; desc. 50 ft. over NW. slope.
- 10.10 Wash, 50 lks. wide, 3 ft. deep, drains NE.
- 14.50 Wash, 20 lks. wide, 3 ft. deep, drains NE.
- 17.40 Wash, 10 lks. wide, 2 ft. deep, drains NE.
- 36.50 Wash, 20 lks. wide, 1 ft. deep, drains N. 80° E.

41.97 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T2S R5W
 $\frac{1}{4}$ $\frac{S18}{S19}$
 1958

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.

- 43.60 Wash, 5 lks. wide, 2 ft. deep, drains S. 80° E.
- 50.90 Wash, 10 lks. wide, 1 ft. deep, drains N. 80° E.

64.00 El Paso Natural Gas Co. underground gas line bears N. 30° W. and S. 30° E., with road parallel to line.

66.00 S. fence line of El Paso Natural Gas Co. pumping station, bears N., 2 chs. dist.

81.94 The cor. of secs. 18 and 19 on the W. bdy. of the township, monumented with a 2 $\frac{1}{2}$ in. iron post, set, mkd. and witnessed as described in the official record.

Land, rolling.
 Soil, sandy and rocky.
 Timber, none; undergrowth, scattered greasewood, paloverde, ocotillo, cacti and sparse grass.

GENERAL DESCRIPTION

The east portion of the township is high and very rocky terrain, unsuitable for anything except very limited grazing. There was some mining activity in the years past; no activity at this time.

In the southeast part of the township there is very good farming land. The water is obtained by pumping wells. They raise lettuce, carrots, cotton and grain. The south center portion is sandy river bed bottom of the Gila River, unfit for anything. The southwest portion of the township is rolling mesa land, with fair grass for limited grazing.

Township 2 South, Range 5 West

Chains

The township is bisected by the Gila River from north and south, by the El Paso Natural Gas Co. underground gas line east and west, and a paved road north and south.

Gillespie Diversion Dam on the Gila River is in sec. 28; the elevation is from 750 ft. to about 2500 ft.

44

BOOK 4576

CERTIFICATE OF CADASTRAL ENGINEER

I, Donald E. Harding, HEREBY CERTIFY upon honor that, in
 pursuance of special instructions bearing date of the 26th day of December, 1957
 I have ~~surveyed~~ independently resurveyed a portion of the north boundary, a portion of
 the east boundary, the south boundary and a portion of the subdivision of Township
2 South, Range 5 West

of the Gila & Salt River Meridian, in the State of Arizona, which are
 represented in the foregoing field notes as having been executed by me and under my direction; and that
 said survey has been made in strict conformity with said instructions, the Manual of Instructions for the
 Survey of the Public Lands of the United States, and in the specific manner described in the foregoing
 field notes.

July 17, 1958

Salt Lake City, Utah

Donald E. Harding
 Donald E. Harding - Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
 Washington, D. C., NOV 3 1959, 19

The foregoing field notes of the ~~survey of~~ independent resurvey of a portion of the north
 boundary, a portion of the east boundary, the south boundary and a portion of the
 subdivision of Township 2 South, Range 5 West, Gila and Salt River Meridian, Arizona

executed by Donald E. Harding - Cadastral Surveyor
 having been critically examined and found correct, are hereby approved.

Donald B. Clement
 Chief, Division of Cadastral Engineering
 Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in~~
~~is a true copy of the original field notes.~~

Chief, Division of Cadastral Engineering