

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

# FIELD NOTES

of the

Dependent Resurvey and Survey

of the

East and South Boundaries and Subdivisions;

Traverse of the 1920 Abandoned Channel

of the Colorado River;

and,

Portion of the Medial Line of the Gila River,

Township 8 South, Range 22 ~~East~~

*West (Should be "West")*

Of the Gila & Salt River Meridian,

In the State of Arizona

## EXECUTED BY

Gerald F. Pittman, Robert S. Kaiser and Donald A. Cannon

under the supervision of Robert C. Yundt

Under special instructions dated September 15, 1960, which provided

for the surveys included under Group No. 355, approved September 22, 1960  
and supplemental special instructions dated November 3, 1960,  
and assignment instructions dated September 26, 1960,

Survey commenced October 10, 1960

Survey completed March 14, 1961

1A

BOOK 4592

# INDEX DIAGRAM

Township 8 South, Range 22 West

6	5	4	36	3	26	2	1				
54		44		35		26	18				
7	8	9	34	10	25	11	17	12	11		
53	43	42		33		24	17				
18	52	17	41	16	32	15	23	14	16	13	10
51		51		41		32		23		15	
57	49	20	39	21	30	22	22	23	14	24	9
49		48		39		29		21		14	
55	47	29	38	28	29	27	20	26	13	25	8
46		46		38		28		19		12	
31	45	32	37	33	27	34	19	35	12	36	7
6		5		4		3		3		2	

16-56770-1

- Medial Line, Gila River, sec. 30 Pg. 56
- Subdivision of sec. 7 Pgs. 58 - 59
- Resurvey of Right Bank 1920 Colo. R. channel Pgs. 60 - 67
- Meander of Colorado River, sec. 19 (E $\frac{1}{2}$ ) Pg. 67

Dependent Resurvey of Township 8 South, Range 22 West,  
Gila and Salt River Meridian, Arizona

Chains

The original survey of the boundaries and subdivision of Township 8 South, Range 22 West of the Gila and Salt River Meridian, Arizona, was executed by T. F. White, Deputy Surveyor in 1874. In 1948, Q. R. Campbell, Cadastral Engineer, made a dependent resurvey and extension survey of portions of the west boundary and subdivisions. Part of the north boundary was dependently resurveyed in connection with the resurvey of Township 7 South, Range 22 West, concurrently executed, and the west boundary was dependently resurveyed as the east boundary of Township 8 South, Range 23 West under this same group. The following field notes are those of a dependent resurvey of the south boundary, part of the east boundary, the subdivisions, and, a survey of portions of the meanders of the Colorado River, portions of the subdivision of section lines and, the medial line of the Gila River in section 30 as the river was returned by the original survey.

The survey was executed with W. and L. E. Gurley solar transits numbered 541331, 590906, and 461255, property of the Bureau of Land Management and constructed in accordance with standard specifications. The instruments were in good condition, and prior to the beginning of the field work, were tested and all errors corrected. They were maintained in proper adjustment throughout the field work. The directions of the lines of the survey were determined by reference to true meridians, established on line during the progress of the field work, by altitude observations on the sun or hour angle observations on Polaris. The lines were carried forward as transit lines, taking the mean of double forward and backward sights, and the bearings were checked by succeeding observations. The measurements were made with Chicago steel ribbon tapes, eight chains in length. These tapes are graduated every link for the first chain, and thereafter at intervals of ten links. The measurements were made on the slope, the vertical angle of each interval determined by the use of clinometers or the transit and the slope measurements properly reduced to horizontal equivalents for use in these notes.

The dependent resurvey is a complete restoration of the lines of the original survey in their true, original position according to the identified evidence of that survey. Before remonumenting an original corner position, or restoring a lost corner, the lines of the original survey were retraced, and searches made for evidence of the original corner monuments and other calls of the field notes, and for collateral evidence of more recent date. After completing the necessary retracements and searches, the rules of proportionate measurement were applied in order to ascertain the position of each lost corner, and when duly identified or restored, the corner positions were remonumented with regulation iron posts. Only the true line data, referring to the completed resurvey, are supplied here.

The geographic position of the southeast corner of the township, calculated by section line traverse from the southeast corner of Township 8 South, Range 23 West, is as follows: Latitude  $32^{\circ} 41' 06''$  N., and Longitude  $114^{\circ} 27' 38''$  W. The mean magnetic declination was found to be  $14^{\circ} 30'$  E.

Dependent Resurvey of the South Boundary of Township 8 South,  
Range 22 West.

Reestablishment of the Surveys Executed by  
T. F. White, Deputy Surveyor in 1874.

Beginning at the standard corner of T. 8 S., Rs. 21 and 22 W., marked by an iron post 3 ins. in diameter, conforming to the record of the dependent resurvey of T. 9 S., R. 21 W.

Dependent Resurvey, South Boundary, T. 8 S., R. 22 W.

Chains

S. 89° 45' W., between sections 1 and 36, along the South boundary.

Over nearly level desert land.

6.35 Telephone line, bears NE. and SW.

7.65 Southern Pacific Railroad tracks, bear NE. and SW.

11.30 Rut road, bears NE. and SW.

19.70 Rut road, bears NE. and SW.

40.07 The point for the 1/4 section corner of sections 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. in diameter, 26 ins. in the ground, and in a mound of stone, with brass cap marked:

SC
T8S R22W
S36
1/4 S1
T9S
1960

Corner falls 19 links southeasterly from the corner post in a steel chain-link fence surrounding an asphalt paved storage yard adjacent to a Bureau of Reclamation establishment. From this corner post the fence bears SW. and SE.

49.50 Gila Gravity Main Canal, 2 chains wide, flows SE.

80.14 The corner of sections 1, 2, 35, and 36, marked by an iron post, 2 ins. in diameter, set 18 ins. below the surface of a gravel road bearing N. and S. I accept this post as the best remaining evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. in diameter, 18 ins. below road grade, with brass cap marked:

SC
T8S R22W
S35   S36
S2   S1
T9S
1960

from which

A redwood post, 7 ft. long, 4x4 ins. square, set 4 ft. in the ground, bears southwesterly 50 links, marked "RP 50 LKS" on NE. and "S2" on SW. face.

A redwood post, 7 ft. long, 4x4 ins. square, marked "RP 50 LKS" on SE. face and S35 on NW. face, set 4 ft. in the ground, bears northwesterly 50 links.

Land, nearly level desert.

Soil, sand.

Timber, none.

Undergrowth, scattered creosote brush and mesquite.

## Dependent Resurvey, South Boundary, T. 8 S., R. 22 W.

Chains

S. 89° 27' W., between sections 2 and 35.

Over nearly level desert land.

40.31

The  $\frac{1}{4}$  section corner of sections 2 and 35, marked by a 4x4 inch square redwood post, set firmly in the ground, with " $\frac{1}{4}$  S35" on N. face. I accept this post as the best remaining evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 26 ins. in the ground, with brass cap marked:

SC  
T8S R22W  
 $\frac{1}{4}$  S35  
 $\frac{1}{4}$  S2  
T9S  
1960

Set the redwood post alongside the iron post.

S. 89° 27' W., beginning new measurement.

40.31

The corner of sections 2, 3, 34, and 35, marked by a 4x4 ins. square redwood post, set firmly in the ground, correctly marked. I accept this redwood post as the best remaining evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 26 ins. in the ground, with brass cap marked:

SC  
T8S R22W  
S34 S35  
S3 S2  
T9S  
1960

Set the redwood post alongside the iron post.

Land, nearly level desert.

Soil, sand.

Timber, none.

Undergrowth, scattered creosote brush and mesquite.

S. 89° 43' W., between sections 3 and 34.

Over nearly level desert land.

40.06

The standard  $\frac{1}{4}$  section corner of sections 3 and 34, marked by a 4x4 ins. square redwood post set firmly in the ground, marked  $\frac{1}{4}$  S34 on N. face. I accept this redwood post as the best remaining evidence of the original position of the corner.

At the corner point.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground, with brass cap marked:

Dependent Resurvey, South Boundary, T. 8 S., R. 22 W.

Chains

SC  
T8S R22W  
S34  
4  
S3  
1953  
1960  
Set the redwood post alongside the iron post.  
S. 89° 43' W., beginning new measurement.

40.06 The corner of sections 3, 4, 33, and 34, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set 12 ins. below the surface of the ground, in a 4 inch well casing, with brass cap marked:  
S33|S34  
S4 |S3  
1953  
This post is accepted as the best available evidence of the original corner position.  
Land, nearly level desert.  
Soil, sand.  
Timber, none.  
Undergrowth, scattered creosote brush and mesquite.

S. 89° 46' W., between sections 4 and 33.  
Over top of Yuma mesa; through sparse undergrowth. Power lines, 46 links N. and S., parallel to the section line.  
39.96 The 1/4 section corner of sections 4 and 33, which is marked by a Bureau of Reclamation iron post, 30 ins. long, 1 inch in diameter, buried 14 ins. below the road surface, with brass cap marked:  
S33 1/4  
S4 1/4  
1936  
This post is accepted as the best available evidence of the original corner position, and I reference it as follows:  
An iron post, 30 ins. long, 2 1/2 ins. in diameter, set 24 ins. in the ground, for reference monument, bears N. 45° 00' E., 67 links dist., marked S33 RM 1960, with arrow pointing to the corner.  
An iron post, 30 ins. long, 2 1/2 ins. in diameter, set 24 ins. in the ground, for reference monument, bears N. 45° 00' W., 67 links dist., marked S33 RM 1960, with arrow pointing to corner.  
The corner falls 1 link E. of intersection of blacktop road bearing N. and S. and gravel road bearing W.

S. 89° 46' W., beginning new measurement.  
0.01 Intersection of black top and gravel roads; thence along center of gravel road.

## Dependent Resurvey, South Boundary, T. 8 S., R. 22 W.

## Chains

- 0.41 Telephone line parallel to blacktop road.
- 13.30 Rim of Yuma Mesa, bearing N. and S.; descend 75 ft. over W. slope to base.
- 32.80 Base of slope; enter bottom land.
- 39.42 Power line, bears N. and S.
- 39.92 The corner of sections 4, 5, 32, and 33, marked by a Bureau of Reclamation iron post, 30 ins. long, 2 ins. in diameter, buried 12 ins. below road surface, with brass cap marked:
- |     |     |
|-----|-----|
| S32 | S33 |
| S5  | S4  |
- This post is accepted as the best available evidence of the original corner position and I reference it as follows:
- An iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, set 24 ins. in the ground, for reference monument, bears N.  $45^{\circ} 00' E.$ , 62 links dist. marked, T8S R22W S33 RM 1960, with arrow pointing to corner.
- An iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, set 24 ins. in the ground for reference monument, bears N.  $45^{\circ} 00' W.$ , 67 links dist., marked T8S R22W S32 RM 1960, with arrow pointing to corner.
- Land, level mesa and bottom land.  
Soil, sandy clay loam.  
Timber, none.  
Undergrowth, sparse greasewood.
- 
- S.  $89^{\circ} 20' W.$ , between sections 5 and 32.
- Over bottom land, along center of gravel road. Power lines, 46 links N. and S., run parallel to the section line.
- 39.89 The  $\frac{1}{4}$  section corner of sections 5 and 32, which is marked by a Bureau of Reclamation iron post, 1 inch in diameter, buried 16 ins. below road surface with brass cap marked:
- |                   |
|-------------------|
| $\frac{1}{4}$ S32 |
| S5                |
| 1953              |
- This post is accepted as the best available evidence of the original corner position and I reference it as follows:
- An iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, set 24 ins. in the ground, for reference monument, bears N.  $45^{\circ} 00' E.$ , 67 links dist., marked T8S R22W S32 RM 1960, with arrow pointing to corner.
- An iron post, 30 ins. long, and  $2\frac{1}{2}$  ins. in diameter, set 24 ins. in the ground, for reference monument, bears S.  $45^{\circ} 00' E.$ , 67 links dist., marked T8S R22W S5 RM 1960, with arrow pointing to corner.
- S.  $89^{\circ} 20' W.$ , beginning new measurement.
- 40.49 The corner of sections 5, 6, 31, and 32, which is marked by a

## BOOK 4592

Dependent Resurvey, South Boundary, T. 8 S., R. 22 W.

## Chains

Bureau of Reclamation iron post, 2 ins. in diameter, buried 12 ins. below road surface, with brass cap marked:

S31	S32
S6	S5

from which

A power pole, with spike, bears N. 42° 50' E., 63.6 links dist. The pole is marked: BM 15 ELEV. 142.522. Add the marks RP 42'.

A power pole, with spike, bears S. 46° 06' W., 65.2 links dist. Mark the pole, RP 43'.

This post is accepted as the best available evidence of the original corner position.

Land, boggy bottom.

Soil, sandy clay loam.

Timber, none.

Undergrowth, bermuda grass.

S. 89° 32' W., between sections 6 and 31.

Over bottom land, along center of gravel road. Power lines, 46 links N. and S., run parallel to the section line.

21.90 E. bank of canal; end of gravel road.

22.32 Center line of canal, flowing NW.

22.70 W. bank of canal.

24.72 Base of Yuma Mesa, bearing N. 50° W. and SE.; ascend 50 ft. to rim.

36.80 N. rim of Yuma Mesa, bears N. 4 chains then W. and SE.

39.99 The  $\frac{1}{4}$  section corner of sections 6 and 31, which is marked by a 4x4 redwood post, projecting 2 ft. above ground, marked  $\frac{1}{4}$  S32 on N. face and 6 on S. face, is accepted as the best available evidence of the original corner position.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, with brass cap marked:

T8S R22W
$\frac{1}{4}$ S31
6
S6

T9S

1960

from which

A set redwood post, 4x4x18 ins. above ground, bears N. 0° 12' E., 50.5 links dist., marked RP 33.3 FT.

A set redwood post, 4x4x18 ins. above ground, bears S. 0° 39' W., 50 links dist., marked RP 33 FT.

I reset the redwood post alongside the iron post.



## Dependent Resurvey, South Boundary, T. 8 S., R. 22 W.

## Chains

S. 89° 29' W., beginning new measurement.

19.50 The power line on S. side crosses my line, bearing N. 65° W.

39.68 The corner of Ts. 8 and 9 S., Rs. 22 and 23 W., which is marked by a redwood post, 4x4 ins. set flush with ground, accepted as the best available evidence of the original corner position.

At the corner point.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, with brass cap marked:

T8S	
R23W R22W	
S36	S31
S1	S6
T9S	
1960	

from which

A U. S. Geological Survey regulation bench mark iron post, set in concrete, bears W., 4.6 links dist. with brass cap marked 216 FT. DATUM V.

Land, boggy bottom and mesa top.  
Soil, sandy clay loam.  
Timber, none.

Undergrowth, bermuda in bottom and greasewood on Mesa.

Dependent Resurvey of a Portion of the  
East Boundary of T. 8 S., R. 22 W.

Reestablishment of the Surveys Executed by T. F. White  
in 1874

From the standard corner of T. 8 S., Rs. 21 and 22 W., heretofore described.

N. 0° 12' W., between sections 31 and 36, along the East Boundary.

Over slightly rolling desert land, with scattered undergrowth.

4.25 Telephone line, bears NE. and SW.

5.45 Southern Pacific Railroad track, bears NE. and SW.

7.45 Rut road, bears NE. and SW.

16.75 Power line, bears NE. and SW.

34.60 Gila Gravity Main Canal, 1.50 chains wide; flows SW:

36.20 Gravel road, bears NE. and SW.

39.00 Enter area of cultivated fields; enter bladed road, bears N.

39.96 The  $\frac{1}{4}$  section corner of sections 31 and 36, marked by a Bureau of Reclamation iron post, 1 inch in diameter, set 6 ins. below road grade. Markings on cap illegible. It is accepted as the best available evidence of the original position of the corner.

Dependent Resurvey, Portion of East Boundary, T. 8 S., R. 22 W.

Chains

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. in diameter, 48 ins. in the ground, with brass cap marked:

T8S  
R22W R21W  
S36 | S31  
1960

from which

A Bureau of Reclamation test well pipe, 2 ins. in diameter, bears N. 45° W., 12 links dist.

N. 0° 28' W., beginning new measurement.

39.25 Power line, bears E. and W.

39.90 The corner of sections 25, 30, 31, and 36, marked by a Bureau of Reclamation iron pipe with brass cap, set 1 ft. below road grade in a man-hole 1 ft. in diameter, with steel cover in center of State Hwy. No. 95, bearing E. and W. Impossible to determine marking on brass cap because of rusted condition of pipe and presence of water in man-hole.

I accept this pipe as the best remaining evidence of the original position of the corner. The point was not remonumented.

Land, S. 1/2, rolling desert; N. 1/2, cultivated farm land.  
Soil, S. 1/2, sand; N. 1/2, irrigated first rate.

Timber, none  
Undergrowth, S. 1/2, scattered creosote brush and mesquite; N. 1/2, none.

N. 0° 28' W., between sections 25 and 30.

0.33 Enter bladed farm road, bears N. from State Hwy. No. 95.

39.90 The 1/4 section corner of sections 25 and 30, which is marked by a Bureau of Reclamation iron post, 1 inch in diameter, set 2 ins. below road grade, with brass cap marked:

S25 | S30

Other marking illegible. I accept this iron post as being the best available evidence of the original position of the corner. The point was not remonumented.

N. 0° 28' W., beginning new measurement.

39.92 The corner of sections 19, 24, 25, and 30, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set firmly in the ground, with brass cap marked:

T8S R21W  
S24 | S19  
S25 | S30  
1960

## Dependent Resurvey, Portion of East Boundary, T. 8 S., R. 22 W.

## Chains

It is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 26 ins. in the ground and in a mound of stone, 2 ft. base to top, with brass cap marked:

T8S  
R22W R21W  
S24 | S19  
S25 | S30  
1960

Destroy Bureau of Reclamation post. Corner falls at N. edge of intersection of bladed road bearing E. and W. and a bladed road bearing S.

Land, level farm.

Soil, cultivated, irrigated, first rate.

Timber, none.

Undergrowth, none.

N.  $0^{\circ}$  21' W., between sections 19 and 24.

Enter cultivated fields.

40.03 Point for the  $\frac{1}{4}$  section corner of sections 19 and 24, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 22 ins. in the ground, with brass cap marked:

T8S  
R22W R21W  
 $\frac{1}{4}$   
S24 | S19  
1960

Enter level desert land with medium growth of underbrush.

41.50 South bank of main channel of the Gila River, 1 chains wide, 3 ft. deep, flows W.

42.50 North bank; thence over flooded swamp area.

63.40 Leave swamp; enter nearly level desert land.

80.06 The corner of sections 13, 18, 19, and 24, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, firmly set in the ground, with brass cap marked:

R22W R21W  
S13 | S18  
S24 | S19  
T8S  
1936

It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

Land, S.  $\frac{1}{2}$ , level farm; N.  $\frac{1}{2}$ , swampy and flooded with N. 17 chains nearly level desert.

Dependent Resurvey, Portion of East Boundary, T. 8 S., R. 22 W.

## Chains

Soils, S.  $\frac{1}{2}$ , irrigated first rate; N.  $\frac{1}{2}$ , sand.  
Timber, none.  
Undergrowth, arrowweed, salt cedar, tamarisk and creosote brush.

N.  $0^{\circ} 23' W.$ , between sections 13 and 18.

Over nearly level desert land, through scattered undergrowth.

11.75 Fence, bears E. and W.; enter irrigated farm land.

13.49 Point for the record meander corner of the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 44 ins. in the ground, with brass cap marked:

MC  
S13 | S18  
R22W | R21W  
T8S  
1960

from which

An iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, set 24 ins. in the ground as a reference monument, bears S.  $0^{\circ} 23' E.$ , 1.80 chains dist., with brass cap marked: T8S R22W R21W S13 S18 MC RP 118.8' with arrow pointing to the true point.

18.76 Point for the record meander corner of the right bank of the Gila River, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 48 ins. in the ground, with brass cap marked:

T8S  
R22W | R21W  
S13 | S18

MC

1960

40.02 Point for the  $\frac{1}{4}$  section corner of sections 13 and 18, at proportionate dist.; there is no remaining evidence of the original corner. Point for corner falls at the intersection of farm roads bearing W. and S.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 48 ins. below road grade, with brass cap marked:

T8S  
R22W | R21W  
 $\frac{1}{4}$   
S13 | S18  
1960

from which

A concrete irrigation ditch headwall bears NE., 12 ft. dist., with chisel markings on top "RP 12"

A concrete irrigation ditch headwall bears SW., 26.5 ft. dist., with chisel markings on top, "RP 26.5"

## Dependent Resurvey, Portion of East Boundary, T. 8 S., R. 22 W.

## Chains

80.04 Continue along E. side of concrete irrigation ditch, bears N.  
The corner of sections 7, 12, 13, and 18, marked by a Bureau of Reclamation iron post, 3 ins. in diameter, firmly set in the ground, with brass cap marked:

T8S R22W T8S R21W  
S12|S7  
S13|S18  
1914

It is accepted as being the best available evidence of the original position of the corner. Corner falls 20 links E. of concrete irrigation ditch. The point was not remonumented.

Land, level farm.  
Soil, irrigated first rate.  
Timber, none.  
Undergrowth, none.

6.20 N. 0° 30' W., between sections 7 and 12.  
Graded access road, paralleling S. bank, Gila Gravity Main Canal.  
7.20 Right bank, Gila Gravity Main Canal, flows ESE.  
9.20 Left bank; enter rolling hills with medium growth of underbrush.  
40.04 The  $\frac{1}{4}$  section corner of sections 7 and 12, marked by a Bureau of Reclamation iron post, 1 inch in diameter, set firmly in the ground, with brass cap marked:

$\frac{1}{4}$   
S12|S7  
1936

It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

N. 0° 30' W., beginning new measurement.

2.50 Dry wash, 2 chains wide, 2 ft. deep, drains WSW.  
37.29 The corner of sections 1, 6, 7, and 12, marked by a granite stone, 4"x12"x14", firmly set in the ground, with 5 notches on South edge and 1 on North edge, with mound of stone to S. and W.  
At the corner point  
Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. in diameter, on solid rock and in a mound of stone, 4 ft. base, to top, with brass cap marked:

T8S  
R22W R21W  
S1|S6  
S12|S7  
1960

Deposit original stone alongside iron post.

Corner falls on SE. slope of spur, bearing S., and 1.50 chains dist. NW. from dry wash, draining SW.

## Dependent Resurvey, Portion of the East Boundary, T. 8 S., R. 22 W.

Chains	
	<p>Land, rolling hills Soil, sandy to rocky. Timber, none. Undergrowth, scattered creosote brush and mesquite.</p>
	<p style="text-align: center;">Dependent Resurvey of the Subdivision of T. 8 S., R. 22 W.</p>
	<p style="text-align: center;">Reestablishment of the Surveys Executed by T. F. White in 1874.</p>
	<p>Beginning at the standard corner of sections 35 and 36 on the south boundary of the township.</p>
	<p>N. 0° 22' W., between sections 35 and 36.</p>
	<p>Along a bladed gravel road, bearing N. and S.; over nearly level desert land.</p>
10.00	<p>Enter cultivated area; continue along gravel road.</p>
39.97	<p>The <math>\frac{1}{4}</math> section corner of sections 35 and 36, marked by a Bureau of Reclamation iron post, 1 inch in diameter, set 6 ins. below road grade, with brass cap marked:</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S35   S36</p>
	<p>Other marking illegible. It is accepted as being the best available evidence of the original position of the corner. The corner was not remonumented.</p>
	<p>N. 0° 22' W., beginning new measurement.</p>
39.99	<p>The corner of sections 25, 26, 35, and 36, marked by a Bureau of Reclamation iron post, with brass cap properly marked and set 12 ins. below the road grade in a 12 inch riser, in center of Highway No. 95, bearing E. and W. It is accepted as being the best available evidence of the original position of the corner. This point is not remonumented.</p>
	<p>Land, S. 10 chains, nearly level desert; remainder, cultivated farm. Soil, S. 10 chains, sand; remainder, cultivated first rate. Timber, none. Undergrowth, none.</p>
	<p>From the corner of sections 25, 30, 31, and 36 on the east boundary of the township.</p>
	<p>S. 89° 52' W., between sections 25 and 36.</p>
	<p>Along Highway No. 95.</p>
40.10	<p>The <math>\frac{1}{4}</math> section corner of sections 25 and 36, marked by a Bureau of Reclamation iron post, with cap properly marked, 2 ins. in diameter,</p>

Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

set in concrete in a 12 inch steel casing with cover and 12 ins. below road grade. It is accepted as being the best available evidence of the original position of the corner.

S. 89° 52' W., beginning new measurement.

40.07

The corner of sections 25, 26, 35, and 36.

Land, level, cultivated.  
Soil, irrigated first rate.  
Timber, none.  
Undergrowth, none.

N. 0° 04' E., between sections 25 and 26.

Over level land in cultivated area. Along bladed farm road.

39.99

The  $\frac{1}{4}$  section corner of sections 25 and 26, marked by a Bureau of Reclamation iron post, 1 inch in diameter, set 6 ins. below road grade, with brass cap marked:

S26  
S25

1913

It is accepted as being the best available evidence of the original position of the corner. Point falls 26 links easterly from corner of rail fence, bearing W. and S. The corner was not remonumented.

N. 0° 04' E., beginning new measurement.

19.70

Power line, bears E. and W.

39.99

The corner of sections 23, 24, 25, and 26, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set firmly in the ground, with brass cap marked:

T8S R22W	
S23	S24
S26	S25
1960	

It is accepted as being the best available evidence of the original position of the corner. This point was not remonumented.

Corner falls 3 links E. of the corner of wire fence, bearing W. and S.

Land, level, cultivated.  
Soil, irrigated first rate.  
Timber, none.  
Undergrowth, none.

Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township. N. 89° 04' W., between sections 24 and 25.

Over level land under cultivation, along bladed farm road.

39.72

The 1/4 section corner of sections 24 and 25, marked by a Bureau of Reclamation iron post, 1 inch in diameter, firmly set in the ground, with brass cap marked:

1/4 S24 S25 1960

It is accepted as being the best available evidence of the original position of the corner. This point was not remonumented.

S. 89° 04' W., beginning new measurement.

0.20

Power line, bears N. and S.

20.00

Power line, bears N. and S.

39.73

The corner of sections 23, 24, 25, and 26.

Land, level cultivated. Soil, irrigated, first rate. Timber, none. Undergrowth, none.

N. 0° 22' W., between sections 23 and 24.

Over level cultivated fields.

20.00

Enter nearly level desert land with scattered undergrowth.

40.11

Point for the 1/4 section corner of sections 23 and 24 at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. in diameter, 24 ins. in the ground, with brass cap marked:

T8S R22W

1/4 S23 S24 1960

from which

Bureau of Reclamation B. M. No. 5, bears S. 14° 11' W., 5.06 chs. dist.

43.82

Point for the record meander corner of the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. in diameter, 24 ins. in the ground, with brass cap marked:



## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

- 
- 69.50 Left bank of the present Gila River, 8 chains wide, 2 feet deep, flows W.
- 77.50 Right bank Gila River.
- 80.16 Point for the record meander corner of the right bank of the Gila River at proportionate distance; there is no remaining evidence of the original corner. The point was not remonumented.
- 80.22 The corner sections 13, 14, 23, and 24, marked by a Bureau of Reclamation, iron post 2 ins. in diameter, firmly set, in the ground with brass cap marked:

T8S  
 R22W  
 S14 | S13  
 S23 | S24  
 1939

It is accepted as being the best available evidence of the original position of the corner. The corner was not remonumented.

Land, S. 20 chains. level, cultivated; remainder, nearly level desert. Soil, S. 20 chains, irrigated, first rate; remainder, sand. Timber, none.

Undergrowth; scattered growth of creosote brush, arrowweed, and salt cedar.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township:

N. 89° 58' W., between sections 13 and 24.

Over nearly level desert land with medium growth of underbrush.

- 22.50 Enter cultivated fields.
- 39.78 Point for the  $\frac{1}{4}$  corner of sections 13 and 24, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 48 ins. in the ground, with brass cap marked:

T8S R22W  
 $\frac{1}{4}$  S13  
 $\frac{1}{4}$  S24  
 1960

from which

Wooden pole of high-tension power line bears N. 4° 31' W., 1.10 chains dist.

Wooden pole of high-tension power line bears N. 8° 56' E., 1.12 chains dist.

- 46.80 Enter nearly level desert land with heavy growth underbrush.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

48.11

Point for the record meander corner of the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground and in a mound of stone at the restored meander corner with brass cap marked:

T8S  
 S13  
 MC / S24  
 R22W  
 1960

Enter heavy growth of arrowweed.

79.56

The corner of sections 13, 14, 23, and 24.

Land, E. 22 chains, and W. 32 chains, nearly level desert; remainder, cultivated fields.

Soil, E. 22 chains, and W. 32 chains, sand; remainder, irrigated, first rate.

Timber, none.

Undergrowth, E. 22 chains, and W. 32 chains, medium to heavy growth arrowweed, creosote brush, and salt cedar; remainder, none.

N.  $0^{\circ} 56'$  W., between sections 13 and 14.

Over nearly level desert land with heavy growth of underbrush.

36.00

Enter cultivated fields.

40.35

Point for the  $\frac{1}{4}$  section corner of sections 13 and 14, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 28 ins. in the ground, with brass cap marked:

T8S R22W  
 $\frac{1}{4}$   
 S14 | S13  
 1960

Set a redwood post, 8 ft. long, 4x4 ins. square, 4 ft. in the ground alongside iron post.

Enter nearly level desert land, with scattered undergrowth.

76.00

Enter bladed road, bears N. and S.

80.70

The corner of sections 11, 12, 13, and 14, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, firmly set in the ground, with brass cap marked:

T8S  
 S11 | S12  
 S14 | S13  
 R22W  
 1914

It is accepted as being the best available evidence of the original position of the corner. The corner was not remonumented.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

Land, nearly level desert, with scattered areas of cultivated fields.  
Soil, sand.  
Timber, none.  
Undergrowth, scattered to heavy growth of arrowweed, creosote brush,  
and mesquite and salt cedar.

From the corner of sections 7, 12, 13, and 18, on the east boundary  
of the township.

N. 89° 31' W., between sections 12 and 13.

Over level cultivated land.

0.60 Bladed road, bears N. and S.; enter bladed road, bears W.

12.00 Leave bladed road; enter area of cleared land.

40.17 Point for the  $\frac{1}{4}$  section corner of sections 12 and 13, at proportion-  
ate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the  
ground, with brass cap marked:

T8S R22W

$\frac{1}{4}$  S12  
 $\frac{1}{4}$  S13

1960

Set a redwood post 4"x4"x7', 4 ft. in the ground alongside the  
iron post.

Corner falls 4 links S. of wire fence, bears E. and W.

73.20 Leave cultivated fields; enter heavy brush.

80.34 The corner of sections 11, 12, 13, and 14.

Land, E. 73 chains, level cultivated; remainder, desert.

Soil, E. 73 chains irrigated, first rate; remainder, sand.

Timber, none.

Undergrowth, E. 73 chains, none; remainder, heavy undergrowth of salt  
cedar, arrowweed and mesquite.

N. 0° 33' W., between sections 11 and 12.

Over nearly level desert land with medium growth of underbrush.

21.00 Gila Gravity Main Canal, 2 chains wide, flows E.

32.00 Enter rolling hills.

39.53 The  $\frac{1}{4}$  section corner of sections 11 and 12, marked by a Bureau of  
Reclamation post, 2 ins. in diameter, firmly set in the ground, with  
brass cap marked:

T8S R22W

$\frac{1}{4}$  S11  
S12

This point is also marked by the remains of the original mesquite  
post set in the ground alongside the iron post. The corner was not

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

remonumented.

N. 0° 46' W., beginning new measurement.

39.76

The corner of sections 1, 2, 11, and 12, marked by a granite stone, 12" x 12" x 18", marked with 1 notch on the E. edge and 5 notches on the S. edge, set in a mound of stone.

At the corner point:

Set an iron post, 30 ins. long, 2½ ins. in diameter, 15 ins. in the ground and in a mound of stone, with brass cap marked:

T8S R22W	
S2	S1
S11	S12

S2	S1
S11	S12

1960

Deposit the original stone, alongside the iron post.

Land, S. 32 chains, nearly level desert; remainder, rolling hills.  
Soil, sand to rocky.

Timber, none.

Undergrowth, medium to scattered growth of creosote brush, salt cedar and mesquite.

From the cor. of secs. 1, 6, 7, and 12, on the east boundary of the township.

N. 86° 05' W., between sections 1 and 12.

Over rolling hills, no timber.

40.99

The ¼ section corner of sections 1 and 12, marked by decayed mesquite post, 3 ins. in diameter, projecting 24 ins. above the ground, with charring evident on base of post, and with mound of stone to N., accepted as being the original corner post.

At the corner point.

Set an iron post, 30 ins. long, 2½ ins. in diameter, 20 ins. in the ground and in a mound of stone, with brass cap marked:

T8S R22W	
¼ S1	
¼ S12	

¼ S1	
¼ S12	

1960

Deposit original post alongside the iron post.

S. 89° 51' W., beginning new measurement.

39.68

The corner of sections 1, 2, 11, and 12.

Land, rolling hills.

Soil, rocky to sandy.

Timber, none.

Undergrowth, none.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

From the standard corner of sections 34 and 35 on the south boundary of the township.

N. 0° 10' W., between sections 34 and 35.

Over nearly level desert land, with scattered undergrowth.

2.45

Power line, bears E. and W.

40.11

The  $\frac{1}{4}$  section corner of sections 34 and 35, marked by a Bureau of Reclamation iron post 1 inch in diameter, firmly set in the ground, with brass cap marked:

$$\begin{array}{c} \text{S34} \\ | \\ \text{S35} \\ \hline \text{1"} \\ \hline 1913 \end{array}$$

It is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 26 ins. in the ground, with brass cap marked:

$$\begin{array}{c} \text{T8S R22W} \\ | \\ \text{S34} | \text{S35} \\ \hline 1960 \end{array}$$

Deposit the original corner alongside the iron post.

N. 0° 10' W., beginning new measurement.

8.00

Enter area of cultivated fields; enter bladed road, bears N.

40.11

The corner of sections 26, 27, 34, and 35, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set in a steel casing, 12 ins. in diameter, 8 ins. below road grade in the center of Hwy. No. 95, bearing E. and W., with brass cap marked:

$$\begin{array}{c} \text{T8S R22W} \\ | \\ \text{S27} | \text{S26} \\ \hline \text{S34} | \text{S35} \end{array}$$

It is accepted as being the best available evidence of the original position of the corner. This point was not remonumented.

Land, S. 48 chains, nearly level desert; remainder, cultivated.

Soil, S. 48 chains, sand; remainder, irrigated first rate.

Timber, none.

Undergrowth, S. 48 chains, scattered growth of creosote brush, remainder, none.

From the corner of sections 25, 26, 35, and 36.

S. 89° 39' W., between sections 26 and 35.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

Along Highway No. 95.

40.17

The  $\frac{1}{4}$  section corner of sections 26 and 35, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set in concrete 8 ins. below road grade, in a steel casing, 12 ins. in diameter, properly marked. It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

S. 89° 39' W., beginning new measurement.

40.18

The corner of sections 26, 27, 34, and 35.

Land, level, cultivated.  
Soil, irrigated first rate.  
Timber, none.  
Undergrowth, none.

N. 0° 06' E., between sections 26 and 27.

Along W. side of bladed road; field to E. and stock feeding ranch to W.

40.10

The point for the  $\frac{1}{4}$  section corner of sections 26 and 27, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 6 ins. below road grade, with brass cap marked:

T8S R22W

$\frac{1}{4}$   
S27 | S26  
1960

from which

A concrete block bears northeasterly, 36 links dist., with chiselled marks on top, RP 36.5.

Corner falls 8 links E. of corner of corral fence, bearing W. and S.

78.00

Leave cultivated land, enter scattered undergrowth.

80.20

The corner of sections 22, 23, 25, and 27, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, firmly set in the ground, with brass cap marked:

T8S  
S22 | S23  
S27 | S26  
R22W  
1913

It is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 22 ins. in the ground and in a base of concrete, with brass cap marked:

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

T8S R22W

S22 | S23

S27 | S26

1960

Deposit the old post alongside the iron post.

Set a redwood post, 7 ft. long, 4 inches square, alongside the iron post.

Note: After initially reestablishing this corner, land clearing and filling operations destroyed both iron posts. A new iron post was set with identical markings with a 4x4 wood post set alongside.

Land, level, cultivated.

Soil, irrigated, first rate.

Timber, none.

Undergrowth, none.

From the corner of sections 23, 24, 25, and 26:

S. 89° 50' W., between sections 23 and 26.

Over level cultivated land.

20.16 Wire fence, bears N. and S.

30.06 Concrete irrigation ditch, 10 links wide, drains N.

40.16 The  $\frac{1}{4}$  section corner of sections 23 and 26, marked by a Bureau of Reclamation iron post, 1 inch in diameter, firmly set in the ground, with brass cap marked:

$\frac{1}{4}$  S23  
S26

1960

It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

S. 89° 49' W., beginning new measurement.

0.20 Bladed road bears westerly and northerly.

1.00 Enter nearly level desert land with medium growth of underbrush.

39.00 Ascend to leveled field area.

40.16 The corner of sections 22, 23, 26, and 27.

Land, E.  $\frac{1}{2}$ , cultivated; W.  $\frac{1}{2}$ , cultivated to the S., and level desert to the N.

Soil, E.  $\frac{1}{2}$ , irrigated, first rate; W.  $\frac{1}{2}$ , irrigated to the S. and sand to the N.

Timber, none.

Undergrowth, E.  $\frac{1}{2}$ , none; W.  $\frac{1}{2}$ , none to the S., and scattered growth creosote brush and salt cedar to the N.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

N. 0° 31' E., between sections 22 and 23.

Along fence line bearing N., 20 lks. to W. and gradually converging on sec. line: cleared land to the W. and raw lands to the E.; descend from leveled fields.

1.00 Foot of leveling activity.

40.16 The point for the  $\frac{1}{4}$  section corner of sections 22 and 23, determined latitudinally by a fence bearing W. and longitudinally by a fence bearing S. This is accepted as the best available evidence of the original position of the corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, with brass cap marked:

T8S R22W  
 $\frac{1}{4}$   
 S22 | S23  
 1960

from which

Bureau of Reclamation bench mark No. 6, bears S. 0° 33' W., 4.24 chains dist.

N. 0° 36' W., beginning new measurement.

Enter nearly level desert land, with scattered undergrowth.

12.25 Left bank of the present Gila River, 2 chains wide, 3 ft. deep, flows W.

14.25 Right bank.

17.23 Point for the original meander corner of the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 26 ins. in the ground with brass cap marked:

MC  
 S22  
 T8S | S23  
 R22W  
 1960

38.32

A Bureau of Reclamation iron post, 2 ins. in diameter, projecting 7 ins. above the ground. By records of the Bureau of Reclamation this iron post is set 2.51 chains south of the original meander corner of the right bank of the Gila River on the line bet. 14 and 15. I accept it for determination of the position for the corner of sections 14, 15, 22, and 23.

39.83

The true point for the corner of sections 14, 15, 22, and 23. This point was not monumented in the original survey as it fell in the channel of the original Gila River. I do not monument this point.

Land, desert.

Soil, sandy silt.

Timber, none.

Undergrowth, scattered growth of creosote brush and mesquite.



## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

From the corner of sections 13, 14, 23, and 24.

S. 89° 41' W., between sections 14 and 23.

Over cultivated fields.

24.40 Enter heavy undergrowth in bottom land.

39.88 The  $\frac{1}{4}$  section corner of sections 14 and 23, marked by a Bureau of Reclamation iron post 1 inch in diameter, firmly set in the ground, with brass cap marked:
$$\frac{1}{4} \begin{array}{l} S14 \\ S23 \end{array}$$

1960

It is accepted as being the best available evidence of the original position of the corner. This point was not remonumented.

S. 89° 41' W., beginning new measurement.

34.95 Point for the record meander corner on the right bank of the Gila River at proportionate distance; there is no remaining evidence of the original corner and the point is not remonumented.

39.94 The true point for the corner of sections 14, 15, 22, and 23.

Land, cultivated to the N; level bottom land to the S.

Soil, irrigated first rate to the N; sand to the S.

Timber, none.

Undergrowth, none to the N.; medium to heavy growth of creosote brush, arrowweed, and mesquite and salt cedar to the S.

N. 0° 05' E., between sections 14 and 15.

Enter cultivated land.

1.00 Point for the record meander corner on the right bank of the Gila River, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 48 ins. below surface of the ground, with brass cap marked.

T8S	R22W
S15	S14

MC

1960

from which

A cottonwood, 36 ins. in diameter, bears S. 26° 47' E., 2.27 chains dist. marked T8S R22W S23 MC BT.

A cottonwood, 30 ins. in diameter, bears S. 16° 09' W., 1.84 chains dist. marked T8SR22WS22MCBT.

35.00 Continue along fence line, bears N.; heavy undergrowth to E., pasture land to W.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

39.99

The  $\frac{1}{4}$  section corner of sections 14 and 15, marked by an iron pipe, 3 ins. in diameter, firmly set in the ground, with no cap and no markings. This point is used by the owners of adjacent lands and is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground, with brass cap marked:

T8S R22W

$\frac{1}{4}$   
S15|S14  
1960

Corner falls 2 links E. of corner of wire fence, bearing NW. and S.

North, beginning new measurement.

3.00

Enter cultivated fields.

40.00

The corner of sections 10, 11, 14, and 15, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set 4 ins. below the surface of a gravel road, bears E. and W., with brass cap marked:

S10|S11  
S15|S14

Other markings illegible. It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

Land, level cultivated, pasture and level desert.

Soil, irrigated first rate, to sand.

Timber, none.

Undergrowth, creosote brush, salt cedar and mesquite.

From the corner of sections 11, 12, 13, and 14.

S. 88° 20' W., between sections 11 and 14.

Over nearly level land; through scattered creosote brush, salt cedar, and mesquite.

17.00

Small lake, 8 chains wide; thence across lake.

25.00

West shore of lake.

40.13

The  $\frac{1}{4}$  section corner of sections 11 and 14, marked by a lead plug, set in an iron post, 12 ins. below road grade in a gravel road bearing irregularly E. and W. I accept this plug as the best available evidence of the original position of the corner. The point was not remonumented.

S. 89° 57' W., beginning new measurement.

Along gravel road.

20.00

Enter cultivated lands, continue along gravel road.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

38.37

The corner of sections 10, 11, 14, and 15.  
Land, nearly level desert, E. 3/4; remainder, cultivated.  
Soil, sand, E. 3/4; remainder, irrigated first rate.  
Timber, none.  
Undergrowth, scattered growth of creosote brush, mesquite, E. 3/4;  
remainder, none.

N. 1° 53' W., between sections 10 and 11.

Over nearly level desert land with scattered undergrowth.

18.00

Enter rolling hills.

34.00

Power line, bears NW. and SE.

39.76

The  $\frac{1}{4}$  section corner of sections 10 and 11, marked by a 4x4 ins. redwood post, firmly set in the ground with illegible scribe marked on W. face, alongside a Bureau of Reclamation iron post, 1 inch in diameter, set firmly in the ground, with steel cap marked:

S10 | S11  
1941

The redwood post is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground and in a mound of stone, with brass cap marked:

T8S R22W  
 $\frac{1}{4}$   
S10 | S11  
1960

Deposit the redwood post alongside the iron post.

N. 1° 53' W., beginning new measurement.

8.00

Enter nearly level desert land.

39.10

Gravel access road to Gila Gravity Main Canal, bears E. and W.

39.77

The corner of sections 2, 3, 10, and 11, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, firmly set in the ground, with brass cap marked:

T8S R22W  
S3 | S2  
S10 | S11  
1941

It is accepted as being the best available evidence of the original position of the corner. Corner falls on steep embankment of access road paralleling Gila Gravity Main Canal, bearing NW. and SE. The point was not remonumented.

Land, level desert to rolling hills.

Soil, sand.

Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

<p>Chains</p>	<p>Timber, none. Undergrowth, scattered growth of creosote brush and mesquite.</p>
	<p>From the corner of sections 1, 2, 11, and 12.</p>
	<p>S. 89° 09' W., between sections 2 and 11.</p>
	<p>Over rolling hills.</p>
<p>39.87</p>	<p>The <math>\frac{1}{4}</math> section corner of sections 2 and 11, marked by a Bureau of Reclamation iron post, 1 inch in diameter, firmly set in the ground, with brass cap marked:</p>
	<p style="text-align: center;"><math>\frac{1}{4} \frac{S2}{S11}</math></p>
	<p>It is accepted as being the best available evidence of the original position of the corner.</p>
	<p>At the corner point,</p>
	<p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. in diameter, 20 ins. in the ground and in a mound of stone, with brass cap marked:</p>
	<p style="text-align: center;">T8S R22W <math>\frac{1}{4} \frac{S2}{S11}</math></p>
	<p style="text-align: center;">1960</p>
	<p>Deposit old post, alongside iron post.</p>
	<p>Raise a mound of stone to N. of iron post.</p>
	<p>S. 89° 27' W., beginning new measurement.</p>
<p>6.00</p>	<p>Enter nearly level desert land.</p>
<p>38.70</p>	<p>Gila Gravity Main Canal, 1 chain wide, flows SE.</p>
<p>40.33</p>	<p>The corner of sections 2, 3, 10, and 11.</p>
	<p>Land, W. <math>\frac{1}{2}</math>, nearly level desert; remainder, rolling hills.</p>
	<p>Soil, sand to rocky.</p>
	<p>Timber, none.</p>
	<p>Undergrowth, scattered growth of creosote brush and mesquite.</p>
	<p>N. 0° 25' W., between sections 2 and 3.</p>
<p>0.90</p>	<p>Gravel access road paralleling the W. bank of the Gila Gravity Main Canal.</p>
<p>1.90</p>	<p>West bank of the Gila Gravity Main Canal, flowing SE.; thence across canal.</p>
<p>4.80</p>	<p>East bank; enter low rolling hills.</p>
<p>19.20</p>	<p>East bank, same canal, thence across canal.</p>

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

22.90

West bank.

38.35

The  $\frac{1}{4}$  section corner of sections 2 and 3, marked by a 4x4 ins. redwood post, firmly set in the ground, with  $\frac{1}{4}$  S3 on W. face. This is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 22 ins. in the ground and in a mound of stone, with brass cap marked:

T8S R22W

 $\frac{1}{4}$   
S3|S2

1960.

Set the redwood post, alongside the iron post, as a guard stake.

N.  $0^{\circ}$  34' W., beginning new measurement.

19.00

Gila Gravity Main Canal, flowing SE. from NW., 1 chain wide.

40.07

Intersect the corner of sections 2, 3, 34, and 35 on the N. boundary of the township, which is an iron post,  $2\frac{1}{2}$  ins. diam., conforming to the official record of the resurvey of T. 7 S., R. 22 W., executed concurrently.

Land, nearly level desert and rolling hills.

Soil, sand.

Timber, none.

Undergrowth, scattered creosote brush and mesquite.

From the standard corner of sections 3, 4, 33, and 34, on the South boundary of the township.

N.  $0^{\circ}$  17' W., between sections 33 and 34.

Over nearly level top of Yuma Mesa, through thinly scattered undergrowth.

0.46

Power line, bears E. and W.

24.00

North edge of Yuma Mesa, bears E. and W. Enter road bearing N. and SW.; descend 60 feet along center of road on N. slope.

39.60

Base of Yuma Mesa, bears irregularly E. and W., enter cultivated bottom land of Gila Valley.

40.03

The  $\frac{1}{4}$  section corner of sections 33 and 34, marked by a Bureau of Reclamation iron post, 1 inch in diameter, set 42 ins. in the ground, with brass cap marked:

 $\frac{1}{4}$   
S33|S34  
1936

It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

from which

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, as reference, bears S.  $44^{\circ} 22' W.$ , 0.576 chains dist., marked T8S R22W S33 RM 380 FT, with arrow pointing to corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, as reference, bears S.  $44^{\circ} 22' E.$ , 0.576 chains dist., marked T8S R22W S34 RM 380 FT, with arrow pointing to the corner.

N.  $90^{\circ} 16' W.$ , beginning new measurement.

Over nearly level bottom land of Gila Valley, along road bearing N. and S., with cultivated fields on each side.

0.10 Bladed road, bears W.

39.49 Power line bears E. and W.

40.02 The corner of sections 27, 28, 33, and 34, in the center of Highway No. 95 bearing E. and W., marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set 42 ins. in the ground in an 8 ins. riser, with brass cap marked:

T8S R22W

S28 | S27

S33 | S34

It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

from which

A 4x4 ins. angle iron, projecting 2 ft. above the ground, painted white, marked HWY RofW POT 360 + 78.15, bears N.  $30^{\circ} 35' E.$ , 90.5 links dist.

An Arizona Highway Dept. bronze tablet,  $2\frac{1}{2}$  ins. in diameter, set in concrete, marked ELEV + STA 360 + 78.15, bears S.  $33^{\circ} 48' E.$ , 91.0 links dist.

From the corner of sections 26, 27, 34, and 35.

S.  $89^{\circ} 38' W.$ , between sections 27 and 34.

Along Highway No. 95.

40.11 The  $\frac{1}{4}$  section corner of sections 27 and 34, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, properly marked, set in a man-hole, 1 foot below road grade. This is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

S.  $89^{\circ} 38' W.$ , beginning new measurement.

40.11 The corner of sections 27, 28, 33, and 34.

Land, level, cultivated.  
Soil, irrigated, first rate.  
Timber, none.  
Undergrowth, none.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

- N.  $0^{\circ} 16'$  W., between sections 27 and 28.
- Over nearly level bottom land, along the black-topped road leading to Laguna Dam, with cultivated land on both sides.
- 0.70 Power line, bears E. and W. along N. side of Highway No. 95.
- 40.03 The  $\frac{1}{4}$  section corner of sections 27 and 28, marked by Bureau of Reclamation iron post, 1 inch in diameter, set 42 ins. in the ground, in concrete, in an 8 inch riser, with brass cap marked:
- $$\begin{array}{c} \frac{1}{4} \\ S28 | S27 \end{array}$$
- It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.
- from which
- A power line pole, bears S.  $17^{\circ} 16'$  W., 150.0 links dist.
- A southwest corner of fence, bears S.  $89^{\circ} 01'$  W., 51.5 links dist.
- 
- N.  $0^{\circ} 16'$  W., beginning new measurement.
- Continue along Laguna Dam Road, bearing N. and S. with cultivated fields on both sides.
- 40.06 The corner of sections 21, 22, 27, and 28, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set 42 ins. in the ground, in concrete, and in an 8 inch riser, with brass cap marked:
- $$\begin{array}{c} T8S R22W \\ S21 | S22 \\ S28 | S27 \end{array}$$
- It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.
- from which
- Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, set 24 ins. in the ground, in concrete, as reference, bears N.  $46^{\circ} 07'$  E., 0.695 chains distant, marked T8S R22W S22 RM 39 FT. with arrow pointing to corner.
- A spike in a power line pole, marked RP X 47 FT., bears N.  $50^{\circ} 08'$  W., 0.648 chains dist.
- The corner is located at the intersection of roads N., S., E. and W.
- Land, nearly level bottom land of Gila Valley.  
Soil, sandy loam and clay.  
Timber, a few scattered cottonwood trees.  
Undergrowth, none.
- 
- From the corner of sections 22, 23, 26, and 27.
- S.  $89^{\circ} 49'$  W., between sections 22 and 26.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

0.20 Wire fence, bears N. and S. 10 lks., thence W.; enter cleared land.

27.25 Wire fence, bears N. and S. 15 lks. to cor. with E-W fence; enter bladed road, bearing W.

40.39 The  $\frac{1}{4}$  section corner of sections 22 and 27, marked by a Bureau of Reclamation iron post, 1 inch in diameter, set 18 ins. below road grade at the intersection of the centerline of a graded road bearing W. and the E. edge of same road turning N., with brass cap marked:

$$\frac{1}{4} \frac{S22}{S27}$$

1913

It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

S. 89° 14' W., beginning new measurement.

Continue along graded road.

40.30 The corner of sections 21, 22, 27, and 28.

Land, level cultivated.  
Soil, irrigated first rate.  
Timber, none.  
Undergrowth, none.

N. 0° 09' E., between sections 21 and 22.

Over nearly level bottom land, along Laguna Dam Road bearing N. and S., with cultivated fields on either side.

37.47 The point for the record meander corner on the left bank of the abandoned channel of the Gila River, at proportionate distance; there is no remaining evidence of the original corner.

Set a copper-coated steel rod,  $\frac{5}{8}$  in. in diameter, 36 ins. long, flush with the surface of the road, in concrete, with brass plug cap marked:

USBLM

MC

S21 | S22  
T8S | R22W  
1960

from which

Bureau of Reclamation "BM No. 8", a 3 inch bronze tablet in concrete; marked 143.531 FT ABOVE MEAN SEA LEVEL; bears S. 61° 02' W., 23 links dist.


Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S21 RM 28.5 FT 1960, with an arrow pointing to the corner; bears N. 45° 00' W., 43.2 links dist.

40.10 Fall 8 links W. of the local  $\frac{1}{4}$  section corner of sections 21 and 22, marked by a Bureau of Reclamation brass cap,  $2\frac{1}{2}$  ins. in diameter, set 6 ins. below the surface, in concrete, and in an 8 inch riser, marked:



Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains



This corner fell in the bed of the Gila River at the time of the original survey and was not monumented. The point is not monumented at this time.

54.74

The point for the record meander corner on the right bank of the abandoned channel of the Gila River, at proportionate distance; there is no remaining evidence of the original corner.

Set a copper-coated steel rod, 5/8 ins. in diam., 36 ins. long, flush with the road surface, in concrete, with brass blug cap marked:



from which

Set an iron post, 30 ins. long, 2 1/2 ins. in diameter, 24 inches in the ground, in concrete, with brass cap marked, T8S R22W S22 RM 87.9 FT 1960, with an arrow pointing to the corner; bears S. 23° 48' E., 133 chains distant.

Set an iron post, 30 ins. long, 2 1/2 ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S21 RM 81.2 FT. 1960, with an arrow pointing to the corner, bears S. 25° 20' W., 123 chains dist.

55.20

Descend over cut bank about 10 ft. high, bears E. and W.

57.70


The Gila River, about 60 links wide, 2 ft. deep, course W.

69.20

Ascend over cut bank, about 10 ft. high, bears E. and W.

80.16

The corner of sections 15, 16, 21, and 22, marked by a Bureau of Reclamation brass cap, set in concrete, 6 ins. below the surface and in an 8-inch riser, marked:



As this point is used by the adjacent property owners it is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

from which

Set an iron post, 30 ins. long, 2 1/2 ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S15 RM 43.5 FT 1960, with an arrow pointing to the corner, bears N. 45° 00' E., 0.66 chain dist.

Set an iron post 30 ins. long, 2 1/2 ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S16 RM 54.8 FT 1960, with an arrow pointing to the corner; bears N. 45° 00' W., 0.83 chain dist.

Land, nearly level bottom lands of the Gila Valley.  
Soil, sandy loam and clay.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

Timber, a few scattered cottonwoods.  
Undergrowth, salt cedar, rushes, and mesquite along the channel of the Gila River.

East, on record course between sections 15 and 22.  
Over nearly level bottom land, with cultivated fields to the north.

0.32 Power line bears N. and S. and a fence bearing E. and N., continue along fence.

14.70 Fence, bears N. from fence bearing E. and W. along line.

21.20 Fence, bears N. from fence bearing E. and W. along line.

21.70 Fence bears N. and W.

38.70 The point for the record meander corner on the right bank of the Gila River, at record distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked:

T8S  
S15 / M  
S22 / C  
R22W  
1960

Set a redwood post, 6 ft. long, 4 ins. square, 3 ft. in the ground, N. of corner, as a guard stake.

Discontinue line.

Land, nearly level bottom land of the Gila Valley.

Soil, sandy loam and clay.

Timber, scattered cottonwoods.

Undergrowth, salt cedar in the extreme East.

From the corner of sections 15, 16, 21, and 22.

N.  $1^{\circ} 32'$  W., between sections 15 and 16.

Over nearly level land, along E. edge of Laguna Dam Road, bearing N. and S., with cultivated fields on either side.

40.16 The point for the  $\frac{1}{4}$  section corner of sections 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set a copper-coated steel rod,  $\frac{5}{8}$  in. in diam., 36 ins. long, flush with the road surface, in concrete, with brass plug cap marked:

USBLM  
T8S R22W  
 $\frac{1}{4}$   
S16 | S15  
1960

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

from which.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S15 RM 45.0 FT 1960, with an arrow pointing to the corner, bears N.  $45^{\circ} 00'$  E. 0.68 chain dist.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S16 RM 45.0 FT 1960, with an arrow pointing to the corner; bears N.  $45^{\circ} 00'$  W., 0.68 chain dist.

45.80

Southern Pacific Pipe Line Co., oil transmission pipe line bears E. and W.

80.32

The corner of sections 9, 10, 15, and 16, marked by a Bureau of Reclamation brass cap, set 6 ins. below the surface, in concrete, in an 8 inch riser, marked:

T8S R22W	
S9	S10
S16	S15
19	

As this point is used by the adjacent property owners, it is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

from which

An "X" chiseled in head wall of inverted syphon, marked RP X 30.6 FT; bears N.  $29^{\circ} 27'$  W., 0.46 chain dist.

An "X" chiseled in head wall of inverted syphon, marked RP X 29.0 FT.; bears N.  $31^{\circ} 31'$  E., 0.44 chain dist.

Land, nearly level bottom land.

Soil, sandy loam.

Timber, a few scattered cottonwoods.

Undergrowth, none.

From the corner of sections 10, 11, 14, and 15.

N.  $89^{\circ} 51'$  W., between sections 10 and 15.

Along gravel road, through area of cultivated fields.

39.89

The  $\frac{1}{4}$  section corner of sections 10 and 15, as determined from the field notes of Bureau of Reclamation surveys. This point falls in a wooden bridge over an irrigation canal bearing N. and S., establishing longitudinal control and the E. and W. gravel road establishing latitudinal control. This point is unmonumented.

At the corner point

Set a 60 penny spike in a bridge timber.

from which

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 26 ins. in the ground, bears northeasterly 27 ft. dist. at NE. corner of bridge, with brass cap marked with an arrow pointing to the true point. T8S R22W S10 RP 27 Ft. 1960.

Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

Set an iron post, 30 ins. long, 2½ ins. in diameter, 26 ins. in the ground bears southeasterly 8.2 ft. dist. at the SE end of the bridge, with brass cap marked T8S R22W S15 RP 8.2 ft. 1960 with an arrow pointing to the true point.

S. 89° 33' W., beginning new measurement.

2.00 Leave road, continue along irrigation ditch bears E. and W.

42.54 The corner of sections 9, 10, 15, and 16.

Land, level, cultivated.

Soil, irrigated first rate.

Timber, none.


Undergrowth, none.

N. 0° 46' W., between sections 9 and 10.

Over nearly level bottom land, along Laguna Dam Road, bearing N. and S., with cultivated fields on either side.

0.10 Syphon in irrigation canal draining W.

39.09 The ¼ section corner of sections 9 and 10, marked by a Bureau of Reclamation brass cap, set 6 ins. below the surface, in concrete, and in an 8 inch riser, marked:



As this point is used by the adjacent property owners, it is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.


from which

Set an iron post, 30 ins. long, 2½ ins. in diameter, 24 ins. in the ground, in concrete, for a reference monument with brass cap marked T8S R22W S10 RM 55.0 FT 1960, with an arrow pointing to the corner, bears N. 41° 10' E., 76.5 links dist.

Set an iron post, 30 ins. long, 2½ ins. in diameter, 24 ins. in the ground, in concrete, for reference monument, with brass cap marked T8S R22W S9 RM 37.0 FT 1960, with an arrow pointing to the corner, bears N. 52° 43' W., 65.1 links dist.

N. 0° 03' E., beginning new measurement.

40.04 The corner of sections 3, 4, 9, and 10, which is marked by a Bureau of Reclamation brass cap, set 6 ins. below the surface in concrete, and in an 8 inch riser, marked:



## Dependent Resurvey of Subdivision of T. 8 S., R. 22 W.

## Chains

As this point is used by the local surveyors and adjacent property owners, it is accepted as the best available evidence of the original corner. The point was not remonumented.

From the corner as references:

An "X" chiseled in the end of a concrete lined head ditch, marked RP 47.0'; bears N. 37° 57' E., 71.2 links dist.

Set an iron post, 30 ins. long, 2½ ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S4 RM 42.0 FT. 1960, with an arrow pointing to the corner; bears N. 45° 00' W., 63.6 links dist.

Land, nearly level bottom land.

Soil, sandy loam, and clay.

Timber, thinly scattered cottonwoods.

Undergrowth, none.

From the corner of sections 2, 3, 10, and 11.

S. 89° 31' W., between sections 3 and 10.

Over nearly level desert land, on N. side of gravel road bearing E. and W.

12.86 Continue along fence, bears W.

40.13 The point for the ¼ section corner of sections 3 and 10, at proportionate dist.; there is no remaining evidence of the original corner. Point falls in the channel of irrigation ditch, 30 links wide, flowing S. Impossible to monument point.

40.40 Set an iron post, 30 ins. long, 2½ ins. in diameter, 26 ins. in the ground, with brass cap marked for witness cor. to the ¼ sec. cor. of secs. 3 and 10:

¼ S3 WC  
S10  
1961

Enter area of level cultivated fields; begin gravel road bearing W.

63.60 Power line, bears NW. and SE.

79.70 Power line, bears N. and S.

80.26 The corner of sections 3, 4, 9, and 10.

Land, E. ½, nearly level desert; remainder, level cultivated.

Soil, E. ½, sand; remainder, irrigated, first rate.

Timber, none.

Undergrowth, none.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

N. 0° 21' W., between sections 3 and 4.

Over nearly level land, along Laguna Dam Road, bearing N. and S., with cultivated fields on either side.

39.64

The  $\frac{1}{4}$  section corner of sections 3 and 4, marked by a Bureau of Reclamation brass cap, set 6 ins. below the surface of the ground in concrete, and in an 8 inch riser, marked:

$\frac{1}{4}$   
S4 S3  
19

It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

from which

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S3 RM 64.2 FT 1960, with an arrow pointing to the corner; bears S. 45° 18' E., 0.97 chains dist.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S4 RM 46.4 FT 1960; with an arrow pointing to the corner; bears S. 45° 00' W., 0.70 chains dist.

N. 0° 31' W., beginning new measurement.

25.80

Leave road bearing N. 30° E. and S.

39.44

The corner of sections 3, 4, 33, and 34, on the N. boundary of the township, marked by an iron post,  $2\frac{1}{2}$  ins. in diameter, set, marked, and witnessed as described in the concurrent survey of T. 7 S., R. 22 W.

Land, nearly level.

Soil, sandy loam and clay.

Timber, a few scattered cottonwoods.

Undergrowth, none.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

From the standard corner of sections 4, 5, 32, and 33, on the south boundary of the township.

N.  $0^{\circ} 17' W.$ , between sections 32 and 33.

Over nearly level bottom land of Gila Valley, along a bladed road bearing N. from E-W road, through cultivated fields.

39.97

The  $\frac{1}{4}$  section corner of sections 32 and 33, marked by a redwood post, 4 ins. x 4 ins. x 18 ins., 24 ins. in the ground. As this point is used by adjacent property owners and local surveyors, it is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 42 ins. in the ground, in concrete, with brass cap marked:

T8S R22W

$\frac{1}{4}$   
S32 | S33

1960

from which

A galvanized fence post, the NW. corner of fence around electrical substation, marked RP X 29.3 FT., bears S.  $65^{\circ} 04' E.$ , 44.4 links dist.

A power pole, marked RP X 38.9 FT., bears S.  $48^{\circ} 18' W.$ , 59.0 links dist.

N.  $0^{\circ} 12' W.$ , beginning new measurement.

39.27

Power line, bears E. and W.

39.97

The corner of sections 28, 29, 32, and 33, marked by a Bureau of Reclamation brass cap set 6 ins. below the surface, in concrete and in an 8 inch riser, in center of Highway No. 95, with brass cap marked:

T8S R22W

S29 | S28

S32 | S33

As this point is used by the local surveyors and adjacent property owners, it is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

from which

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S30 RM 64.7 FT 1960, with an arrow pointing to the corner; bears N.  $45^{\circ} 00' E.$ , 98 links dist.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked T8S R22W S31 RM 64.7 FT 1960, with an arrow pointing to the corner; bears N.  $45^{\circ} 00' W.$ , 98 links dist.

Land, nearly level bottom lands of Gila Valley.

Soil, clay.

Timber, a few scattered cottonwoods.

Undergrowth, none.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

From the corner of sections 27, 28, 33, and 34.

S. 89° 42' W., between sections 28 and 33.

Over nearly level bottom land, along the center of Highway No. 95, with cultivated fields on either side.

39.88

The  $\frac{1}{4}$  section corner of sections 28, and 33, marked by a Bureau of Reclamation brass cap, set 6 ins. below the surface, in concrete, and in an 8 inch riser, marked:

$$\frac{1}{4} \begin{array}{l} S28 \\ S33 \end{array}$$

As this point is used by the local surveyors and adjacent property owners it is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

S. 89° 42' W., beginning new measurement.

Continue along Highway No. 95.

39.92

The corner of sections 28, 29, 32, and 33.

Land, nearly level bottom land of the Gila Valley.

Soil, sandy loam and clay.

Timber, none.

Undergrowth, none.

N. 0° 26' W., between sections 28 and 29.

Over nearly level bottom land, along a road bearing N. and S. from Highway No. 95, with cultivated fields on either side.

0.64

Power line bears E. and W. along the N. side of highway.

39.96

The  $\frac{1}{4}$  section corner of sections 28 and 29, marked by a Bureau of Reclamation iron post, 1 ins. in diameter, with top 4 ins. below the surface, with brass cap marked:

$$\frac{1}{4} \begin{array}{l} S29 \\ S28 \\ 1960 \end{array}$$

As this point is used by the local surveyors and adjacent property owners, it is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

from which

Bureau of Reclamation "BM No. 11," a brass tablet, marked, 143.109 ELEV FT ABOVE MEAN SEA LEVEL 1960 BM, bears N. 0° 49' W., 16.29 chains dist.

N. 0° 31' W., beginning new measurement.

Continue along lane bearing N.

21.90

Lane ends, continue through brushy swamp land.



## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

39.89 The corner of sections 20, 21, 28, and 29, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, 10 ins. above the ground, with brass cap marked:

T8S R22W  
S20 | S21  
S29 | S28  
1960

It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

Land, nearly level bottom land of the Gila Valley.

Soil, sandy loam and clay.

Timber, a few scattered cottonwoods.

Undergrowth, a dense growth of salt cedar and rushes in the N.  $\frac{1}{4}$  mile.

From the corner of sections 21, 22, 27, and 28:

S. 89° 35' W., between sections 21 and 28.

Over nearly level land, along a lane bearing E. and W., with cultivated fields on either side.

40.00 The  $\frac{1}{4}$  section corner of sections 21 and 28, marked by a galvanized pipe, 1 ins. x 14 ins. As this point is used by the local surveyors and adjacent property owners, it is accepted as being the best available evidence of the original position of the corner.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked:

T8S R22W  
S21  
S28  
1960

Set a redwood post, 4 x 4 ins. x 6 ft. 36 ins. in the ground, N. of corner, as a guard stake.

S. 89° 29' W., beginning new measurement.

Continue along fence bearing E. and W.

40.17 The corner of sections 20, 21, 28, and 29.

Land, nearly level bottom land of Gila Valley.

Soil, sandy loam and clay.

Timber, a few scattered cottonwoods.

Undergrowth, dense salt cedar and small brush around the corner of sections 20, 21, 28, and 29.

N. 0° 32' W., between sections 20 and 21.

Over nearly level land, through dense salt cedar.

13.60 The Gila River, about 60 links wide, 1 $\frac{1}{2}$  ft. deep, course SW.; continue along Gila River bottoms.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

18.50 Edge of undergrowth, bears NE. and SW.; enter cultivated land.

40.27 Point for the  $\frac{1}{4}$  section corner of sections 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground in concrete, with brass cap marked:

T8S R22W

S20 | S21

1960

from which

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete for a reference monument, marked T8S R22W S20 RM 55.5 FT 1960 with an arrow pointing to the corner, bears S.  $47^{\circ} 57' W.$ , 84.1 links dist.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, set 24 ins. in the ground, in concrete, for a reference monument, marked T8S R22W S20 RM 56.6 FT 1960, with an arrow pointing to the corner, bears N.  $46^{\circ} 50' W.$ , 85.8 links dist.

69.72

The point for the record meander corner of the left bank of the Gila River, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked:

M C

S20 | S21

T8S | R22W

1960

Set a redwood post, 4 ins. x 4 ins. x 6 ft., 36 ins. in the ground, W. of corner.

80.52

The point for the record meander corner of the right bank of the Gila River, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter 36 ins. in the ground, in concrete, with brass cap marked:

T8S | R22W

S20 | S21

MC

1960

80.54

The corner of sections 16, 17, 20, and 21, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set with brass cap 6 ins. below the surface of the ground, marked:

T8S R22W

S17 | S16

S20 | S21

1941

As this point is used by the local surveyors and adjacent property owners, it is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

Land, nearly level bottom land.  
Soil, sandy loam and clay.  
Timber, a few scattered cottonwoods.  
Undergrowth, dense growth of salt cedar and small brush along the Gila River.

From the corner of sections 15, 16, 21, and 22.

S. 89° 46' W., between sections 16 and 21.

Over nearly level land, on the S. edge of macadam road bearing W. from N-S road, with cultivated fields to the N.

12.00 Leave road, bears N. 60° W. and E.

24.20 Lane, bears NE. and W. continue along lane.

40.53 The point for the  $\frac{1}{4}$  section corner of sections 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 42 ins. in the ground, in concrete, with brass cap marked:

T8S R22W

$\frac{1}{4}$  S16

$\frac{1}{4}$  S21

1960

from which

Set a redwood post, 4 ins. x 4 ins. x 7 ft., set 36 ins. in the ground, marked REF 33 FT SW, bears N. 45° 00' E., 50 links dist.

A redwood post, 4 ins. x 4 ins. x 7 ft., set 36 ins. in the ground, marked REF 33 FT SE, bears N. 45° 00' W., 50 links dist.

81.06 The corner of sections 16, 17, 20, and 21.

Land, nearly level bottom land.

Soil, sandy loam and clay.

Timber, a few scattered cottonwoods.

Undergrowth, none.

N. 0° 28' W., between sections 16 and 17.

Over nearly level land, along lane bearing N. and S.

0.30 Center of lane bearing E. and W.

40.00 The  $\frac{1}{4}$  section corner of sections 16 and 17, marked by a redwood post, 4 ins. x 4 ins. x 18 ins. As this point is used by the local surveyors and adjacent property owners it is accepted as being the best available evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 42 ins. in the ground, with brass cap marked:

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

T8S R22W

S17 | S16

1960

from which

Set a redwood post, 4 ins. x 4 ins. x 6 ft., set, 30 ins. in the ground, marked REF 35 FT NE, bears S. 45° 00' W., 53 links dist.

Set a redwood post, 4 ins. x 4 ins. x 6 ft., set 30 ins. in the ground, marked REF 35 FT. SE, bears N. 45° 00' W., 53 links dist.

N. 0° 28' W., on a projection of the S. half mile, beginning new measurement.

16.54

Set an iron post, 30 ins. long, 2½ ins. in diameter, 24 ins. in the ground, in concrete, for witness point, with brass cap marked:

WP

T8S R22W

S17 | S16

1960

19.10

Left bank of the Colorado River, bears N. 30° E. and S. 30° W.; continue across Colorado River.

40.09

The corner of sections 8, 9, 16, and 17 as determined at the intersection of the projection of the lines between the S. ½ mile of sections 16 and 17 and the E. ½ mile between sections 9 and 16, hereinafter described. This point presently falls in the bed of the Colorado River, near the right bank thereof, an impractical point to monument. Set witness corner as hereinafter described.

Land, nearly level.

Soil, sandy loam and clay.

Timber, none.

Undergrowth, medium dense salt cedar and mesquite along the river bed.

From the corner of section 9, 10, 15, and 16.

S. 89° 40' W., between sections 9 and 16.

Between an irrigation ditch draining W. on the N. and a macadam road bearing E. and W. to S., with cultivated fields on either side.

37.00

Macadam road turns to SE; continue along N. side of bladed dirt road.

39.10

Bladed road, bears N. from E-W road.

39.29

The ¼ section corner of sections 9 and 16, marked by a Bureau of Reclamation brass cap, set in a concrete post, 4 ins. x 4 ins. x 36 ins., dimly marked, buried 40 ins. in the ground. As this point is used by the local surveyors and adjacent property owners, it is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. in diameter, set 36 ins. in the ground, in concrete, with brass cap marked:

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

- T8S R22W  
 $\frac{1}{4}$   $\frac{S9}{S16}$   
 1960
- from which
- Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, for a reference monument, with brass cap marked T8S R22W S9 RM 55.0 FT 1960, with an arrow pointing to the corner, bears N.  $41^{\circ} 00'$  E., 83.3 links dist.
- Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, for a reference monument, with brass cap marked T8S R22W S16 RM 52.0 FT 1960, with an arrow pointing to the corner, bears S.  $52^{\circ} 00'$  E., 78.8 links dist.
- 
- S.  $89^{\circ} 40'$  W., on a projection of the E.  $\frac{1}{2}$  mile, beginning new measurement.
- 23.80 Enter undergrowth, bears W. and SW.
- 28.28 Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, for witness point, with brass cap marked:
- T8S R22W  
 W S9  
 P S16  
 1960
- Set a redwood post, 4 ins. x 4 ins. x 7 ft., N. of iron post.
- 29.50 The left bank of the Colorado River; bears N.  $30^{\circ}$  E. and S.  $30^{\circ}$  W.; continue across the river.
- 40.28 The corner of sections 8, 9, 16, and 17.
- Land, nearly level Colorado River Valley.  
 Soil, sandy loam and clay.  
 Timber, none.  
 Undergrowth, medium to dense salt cedar and mesquite along the river.
- 
- West, between sections 8 and 17.
- 0.50 The right bank of the Colorado River, bears N. and S.  $30^{\circ}$  W.; ascend 10 ft. over bank.
- 0.70 Top of bank, bears N. and S.  $30^{\circ}$  W.; continue over nearly level land.
- 0.78 Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, for witness corner of sections 8, 9, 16, and 17, with brass cap marked:
- T8S R22W  
 S8 | S9 W  
 S17 | S16 C  
 1960
- 3.50 Enter dense undergrowth, bears W. and S.
- 10.18 Intersect the traverse line of the left bank of the 1920 abandoned channel of the Colorado River, between Angle Points Nos. 1 and 2.

Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

Set an iron post, 30 ins. long, 2½ ins. in diameter, 24 ins. in the ground, in concrete, for a witness point, with brass cap marked:

T8S  
W S8  
P S17  
R22W  
1960

From the witness point, Angle Point No. 2, of the abandoned channel surveys, bears S. 37° 48' W., 11.05 chains dist.

Land, nearly level.  
Soil, sandy clay.  
Timber, none.  
Undergrowth, salt cedar.

From the corner of sections 8, 9, 16, and 17.

North, between sections 8 and 9.

5.20 The right bank of the Colorado River, bears N. 5° E. and S. 5° W.; ascend 10 feet over cut bank facing E.

5.90 Top of bank, bears N. 5° E. and S. 5° W., continue along top of bank

13.13 Intersect the traverse line of the left bank of the abandoned channel of the Colorado River, between Angle Points Nos. 1 and 2.

Set an iron post, 30 ins. long, 2½ ins. in diameter, 24 ins. in the ground, in concrete, for a witness point, with brass cap marked:

P  
W  
S8 | S9  
T8S | R22W  
1960

From the witness point, Angle Point No. 1, of the abandoned channel surveys, bears N. 37° 48' E., 2.22 chains dist.

Land, nearly level bottom land of the Colorado River Valley.  
Soil, sand and sandy clay.  
Timber, none.  
Undergrowth, salt cedar and rushes.

From the corner of sections 3, 4, 9, and 10.

N. 89° 53' W., between sections 4 and 9, on record bearing.

Over nearly level land, along center of road bearing W. from N-S road, with cultivated fields on either side.

40.06 The ¼ section corner of sections 4 and 9, at record distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked:

BOOK 402

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

T8S R22W

 $\frac{1}{4}$  S4

S9

1960

Set a redwood post, 4 ins. x 4 ins. x 7 ft., 36 ins. in the ground, N. of corner, as a guard stake.

Continue the same line and measurement.

40.15 Through cultivated fields, road ends.

51.90 Drainage canal, 20 ft. deep, 40 links wide, drains SW.

54.02 Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, for a witness point, with brass cap marked:

T8S R22W

W S4

P S9

1960

The point is set atop high cut bank.

The mean high water line of the left bank of the Colorado River, bearing N.  $10^{\circ}$  E. and S.  $10^{\circ}$  W., bears West, 73 lks. dist.

Land, nearly level bottom land of the Colorado River Valley.

Soil, sandy, loam.

Timber, none.

Undergrowth, none.

From the standard corner of sections 5, 6, 31, and 32, on the S. boundary of the township.

N.  $0^{\circ}$  07' W., between sections 31 and 32.

Over nearly level marshland, along road bearing N. and S.

40.04 The  $\frac{1}{4}$  section corner of sections 31 and 32, marked by a galvanized iron pipe, 18 ins. long, 1 inch in diameter, driven flush with the surface of the road. As this point is used by the adjacent property owners and local surveyors, it is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 42 ins. in the ground, with brass cap marked:

T8S R22W

 $\frac{1}{4}$  S31 | S32

1960

N.  $0^{\circ}$  07' W., beginning new measurement.

39.50 Power line, bears E. and W., along the S. side of Highway 95.

40.21 The corner of sections 29, 30, 31, and 32, in the center of Highway No. 95, which is marked by Bureau of Reclamation, brass cap, set 6 ins. below the surface of the road, in concrete, and in an 8 inch

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

riser, with cap marked:

S30	S29
S31	S32

This point is used by the adjacent property owners and local surveyors, and is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

Land, nearly level bottom land of Gila Valley.

Soil, sandy loam and clay.

Timber, none.

Undergrowth, none.

From the corner of sections 28, 29, 32, and 33.

S. 89° 35' W., between sections 29 and 32.

Over nearly level bottom land, along the center of Highway No. 95, with cultivated fields on either side.

40.09 The  $\frac{1}{4}$  section corner of sections 29 and 32, in the center of Highway No. 95, marked by a Bureau of Reclamation brass cap, set 6 ins. below the surface, in concrete, and in an 8 inch riser, with cap marked:

S29
S32

This point is used by the adjacent property owners and local surveyors, and is accepted as being the best available evidence of the original position of the corner. It is not remonumented.

S. 89° 35' W., beginning new measurement.

40.10 The corner of sections 29, 30, 31, and 32.

Land, nearly level bottom land of Gila Valley.

Soil, sandy loam and clay.

Timber, none.

Undergrowth, none.

S. 89° 22' W., between sections 30 and 31

Over nearly level bottom land, along the center of Highway No. 95, with cultivated fields on either side.

40.00 The  $\frac{1}{4}$  section corner of sections 30 and 31, in the center of Highway No. 95, which is marked by a Bureau of Reclamation, brass cap, set 6 ins. below the surface of the highway, in concrete, and in an 8 in. riser, with cap marked:

S30
S31

As this point is used by the adjacent property owners and local surveyors, it is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.



Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

S. 89° 22' W., beginning new measurement.

39.96

The corner of sections 25, 30, 31, and 36, on the West boundary of the township, as more particularly described in the concurrent resurveys of T. 8 S., R. 23 W.

Land, nearly level bottom land of Gila Valley.  
Soil, sandy loam.  
Timber, none.  
Undergrowth, none.

From the corner of sections 29, 30, 31, and 32.


N. 0° 08' W., between sections 29 and 30.

Over nearly level bottom land, along a road bearing N. and S. with cultivated fields on either side.

21.26

The record meander corner of sections 29 and 30, of the left bank of the abandoned channel of the Gila River, at proportionate dist.; there is no remaining evidence of the original corner.


Set an iron post, 30 ins. long, 2½ ins. in diameter, 42 ins. in the ground, with brass cap marked:



37.11


The record meander corner of sections 29 and 30, of the right bank of the abandoned channel of the Gila River, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. in diameter, 42 ins. in the ground, with brass cap marked:



40.12

The ¼ section corner of sections 29 and 30, marked by a Bureau of Reclamation iron post, 1 ins. in diameter, set with cap 6 ins. below the surface of the road, with brass cap marked:



It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

from which

A Bureau of Reclamation Bench Mark, a bronze tablet, set in concrete, marked 136.479 FT ELEV 1960, bears N. 1° 28' W., 13.32 chains dist.

A nail, in the E. rim of end of concrete lined irrigation canal, marked RP 20 FT., bears S. 59° 49' W., 30.3 links dist.

Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

Nail, in the N. rim of end of concrete lined irrigation canal, marked RP 24 FT., bears N. 85° 07' W., 36.4 links dist.

N. 0° 08' W., beginning new measurement.

4.00 End of road, continue through cultivated field.

16.00 Enter brush land, bears E. and W., continue over nearly level land,, through medium undergrowth.

32.90 The Gila River, 80 links wide, 1 foot deep, flows W.

40.12 The corner of sections 19, 20, 29, and 30, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, 6 ins. above the ground, with brass cap marked:

T8S R22W  
S19 | S20  
S30 | S29  
1941

As this point is used by the adjacent property owners and local surveyors, it is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

Land, nearly level bottom land of Gila Valley.  
Soil, sandy loam and sand.  
Timber, a few scattered cottonwoods.  
Undergrowth, medium salt cedar and mesquite.

From the corner of sections 20, 21, 28, and 29.

S. 89° 51' W., between sections 20 and 29.

Over nearly level bottom land, through dense undergrowth.

10.90 The Gila River, 60 links wide, 1 foot deep, course S. 60° W. from N. 60° E.

23.06 The record meander corner of sections 20 and 29, of the left bank of the abandoned channel of the Gila River, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. in diameter, 24 ins. in the ground, with brass cap marked:

M / T8S  
C / S20  
S29  
R22W  
1960

39.845 Point for ¼ sec. cor. of secs. 20 and 29, at midpoint. This corner originally fell in the Gila River and was not established. The point is not monumented.

58.00 The record meander corner of sections 20 and 29 of the right bank of the abandoned channel of the Gila River, at proportionate dist.; no evidence of the original corner remains.

Set an iron post, 30 ins. long, 2½ ins. in diameter, 24 ins. in the ground, with brass cap marked:

BOOK

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

T8S

S20

M

S29

C

R22W

1960

79.69 The corner of sections 19, 20, 29, and 30.

Land, nearly level bottom land.

Soil, sand and sandy loam.

Timber, a few scattered cottonwoods.

Undergrowth, salt cedar, rushes, and mesquite.

S. 89° 18' W., between sections 19 and 30.

Over nearly level land, through medium undergrowth and timber.

30.00 Gila River, 60 links wide, 10 feet deep, flows N.

39.97 The  $\frac{1}{4}$  section corner of sections 19 and 30, marked by an old 2 x 2 x 12 ins. hub; as this point is used by the adjacent property owners and local surveyors, it is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked:

T8S R22W

 $\frac{1}{4}$  S19

S30

1960

S. 89° 18' W., beginning new measurement.

19.98 The point for the west sixteenth section corner of sections 19 and 30, at proportionate dist.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked:

T8S R22W

1/16 S19

S30

1960

39.91 The corner of sections 19, 24, 25, and 30, on the west boundary of the township as more particularly described in the concurrent resurveys of T. 8 S., R. 23 W.

Land, nearly level bottom land of Gila Valley.

Soil, sand and sandy loam.

Timber, a few scattered cottonwood.

Undergrowth, medium growth of salt cedar and mesquite in the E. half mile.

From the corner of sections 19, 20, 29, and 30.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

N. 0° 24' W., between sections 19 and 20.

Over nearly level land, through dense undergrowth.

21.30 North edge of undergrowth, bears E. and W.; continue over cultivated land.

39.72 The  $\frac{1}{4}$  section corner of sections 19 and 20, at proportionate dist.; there is no remaining evidence of the original corner.Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked:

T8S R22W

 $\frac{1}{4}$ 

S19 | S20

1960

40.10 Bladed road, bears E. and W.

46.70 Fence, net wire, bears N. 60° E. and S. 60° W.

46.75 Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, for witness point, with brass cap marked:

T8S R22W

W | P

S19 | S20

1960

46.90 Edge of high cut bank, bears N. 58° E. and S. 58° W.; descend abruptly 30 feet.

47.70 Point for meander corner of section 19 only on present mean high water line of the left bank of the Colorado River. The corner was not monumented.

55.40 Low sand bar, bears ENE. and W.; continue over river bed.

65.22 Mean high water line on right bank of the Colorado River on steep sloping bank, 5 ft. high, bearing N. 45° E. and S. 45° W.; point for the meander corner of section 19 only.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground, and in a collar of stone, cemented together with concrete. with brass cap marked:

T8S R22W

S19

1960

65.95 An abandoned irrigation well, bears E., 8 links dist.

79.44 The corner of sections 17, 18, 19, and 20, marked by a Bureau of Reclamation iron post, firmly set with brass cap marked:

USBR

T8S R22W

S18 | S17

S19 | S20

1960

It is accepted as being the best available evidence of the original position of the corner. The point was not remonumented.

Land, nearly level sedimentary bottom.

Soil, river silt and sand, first-rate.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains	
	Timber, scattered cottonwoods. Undergrowth, salt cedar, arrowweed, willow, and mesquite.
	From the corner of sections 16, 17, 20, and 21. S. 89° 03' W., between sections 17 and 20. Over nearly level land, along bladed road.
0.18	Intersection with improved dirt road extending N. and S.
0.76	Irrigation canal, 30 links wide, 5 feet deep, course South; continue over nearly level land, along road.
26.80	Road, bears NW.; thence leave road, and descend 5 ft. over rough gullied land.
28.00	A patch of salt cedars, 2.50 chains long, 1.00 chain wide, 40 to 50 feet high.
37.25	Center line of an abandoned concrete wasteway on end of an old irrigation canal, bearing N. and S.
37.53	Set an iron post, 30 ins. long, 2½ ins. in diameter, 25 ins. in the ground, with a collar of granite stone cemented together with concrete, for witness cor. to the ¼ sec. cor. of secs. 19 and 20, with brass cap marked:  T8S R22W WC ¼ $\frac{S17}{S20}$ 1960
38.50	Left bank of the main channel of the Colorado River, on bluff 10 feet high, bearing NE. and SW.
39.74	Point for the ¼ section corner of sections 17 and 20, at proportionate dist., falls in river; set the W.C. as described above.
60.35	Right bank of Colorado River, on bluff 10 feet high, bearing N. 20° E., and S. 20° W.; enter dense undergrowth.
70.95	Old river channel or slough, 40 links wide, 4 feet deep, bears NE. and SW.
79.48	The corner of sections 17, 18, 19, and 20. Land, nearly level, sedimentary bottom. Soil, river silt and sand, first rate. Timber, scattered cottonwood and salt cedar. Undergrowth, dense salt cedar, mesquite, young willow and small brush.
	S. 89° 40' W., between sections 18 and 19. Over level land through dense undergrowth.
13.90	Ascend steep south slope of government levee.

## Dependent Resurvey, Subdivision, T. 8 S., R. 22 W.

## Chains

14.14

Intersect a Bureau of Reclamation brass cap, 3 ins. in diameter, set in concrete block 6 ins. square, 6 ins. below surface of road, atop the new government levee, marked:

U.S.B.R.  
P.O.C. & P.O.S.L.  
Sta. 4281 + 65.59

1953

The levee bears NE. and SW. on wide sweeping curve.

14.45

Northwest edge of road descend steep NW. slope of levee; thence over level land through dense undergrowth, along the base of levee.

25.60

East edge of cultivated field bears N. and S.

39.67

The  $\frac{1}{4}$  section corner of sections 18 and 19, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set 10 ins. below the surface. It is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 40 ins. in the ground, with a collar of granite stone cemented together with concrete, with brass cap marked:

T8S R22W

 $\frac{1}{4}$  S18

S19

1960

from which

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground, for a reference monument, bears S.  $60^\circ$  E., 112 ft. dist., with brass cap marked: T8S R22W  $\frac{1}{4}$  S19 RM 112 FT. 1960 and an arrow pointing to the corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground, for a reference monument, bears S.  $60^\circ$  W., 112 FT. 1960 and an arrow pointing to the corner.

S.  $89^\circ 40'$  W., beginning new measurement.

19.45

West edge of cultivated field, enter dense undergrowth.

39.73

The corner of sections 13, 18, 19, and 24, on the west boundary of the township as more particularly described in the field notes of T8S R23W., resurveyed concurrently under this same group.

Land, level.

Soil, river silt and sand, first rate.

Timber, scattered cottonwood.

Undergrowth, salt cedar, arrowweed, willows, and mesquite.

From the corner of sections 17, 18, 19, and 20.

North, between sections 17 and 18.

Over nearly level land through dense undergrowth.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains

6.85

Center line of road on top of new levee curving NE. and SW. Thence over level land which has been under cultivation but is now covered with a dense growth of arrowweed and salt cedar.

39.71

The  $\frac{1}{4}$  section corner of sections 17 and 18, marked by a Bureau of Reclamation iron post, 2 ins. in diameter, set flush with the ground, in trail road bearing E. and W. It is accepted as being the best available evidence of the original position of the corner.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground with a collar of granite stone cemented together with concrete, with brass cap marked:

T8S R22W  
 $\frac{1}{4}$   
 S18 | S17  
 1960

North, beginning new measurement.

2.23

Intersect the traverse line of the left bank of the 1920 abandoned channel of the Colorado River, between Angle Points 5 and 6.

At the point of intersection

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground, with a collar of granite stone cemented together with concrete, brass cap marked:

WP  
 T8S R22W  
 S18 | S17  
 1960

from which

Angle point No. 15 on the traverse of the 1920 abandoned channel of the Colorado River as originally established in the 1949 surveys bears N.  $4^{\circ} 15'$  E., 11.69 chains dist., described in the field notes of T. 16 S., R. 23 E., S.B.M., California, surveyed concurrently under this same group.

Angle Point No. 5 bears N.  $64^{\circ} 34'$  E., 0.58 ch. dist.

Land, level.

Soil, sandy silt, first and second rate.

Timber, none.

Undergrowth, arrowweed and salt cedar.

Reestablishment of the Survey and Resurvey as  
 Executed by Quintin R. Campbell, Cadastral  
 Surveyor, in 1949.

From the corner of sections 7, 12, 13, and 18, on the west boundary of the township, described in the field notes of T8S., R23W., surveyed concurrently under this same group.

## Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

## Chains

N. 89° 33' E., between sections 7 and 18.

Over nearly level land, along wandering trail road between cultivated fields.

18.82

The corner of fractional sections 7 and 18 and angle point No. 11 on the left bank of the 1920 abandoned channel of the Colorado River, marked by an iron post 3 ins. in diameter, in concrete cone 6 ins. in diameter, set and marked as described in the official record.

from which

An irrigation pump and well bears N. 73° 23' W., 4.42 chains dist.

Land, level.

Soil, silt, first rate.

Timber, none.

Undergrowth, none.

From the corner of sections 1, 6, 7, and 12, on the west boundary of the township, described in the field notes of T. 8 S., R. 23 W., re-surveyed concurrently under this same group.

S. 89° 59' E., between sections 6 and 7.

Over nearly level land, through cultivated fields.

11.90 A cottonwood tree, 42 ins. in diameter, bears N., 46 links dist.

13.43 Irrigation ditch, course S. 75° E.

14.65 Unimproved road paralleling ditch between fields.

31.70 Trail road between fields bears N. 7° E. and S. 7° W.

39.92 Point for the  $\frac{1}{4}$  section corner of sections 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground with a collar of granite stone cemented together with concrete, with brass cap marked:

T8S R22W

$$\frac{1}{4} \frac{S6}{S7}$$

1960

43.90 East edge of cultivated field bears N. and S.; thence over level cleared land.

53.50 West edge of gently rolling sand dunes, bears N. and S.

63.62 The corner of fractional sections 6 and 7 and angle point No. 18 on the left bank of the 1920 abandoned channel of the Colorado River, marked by an iron post, 3 ins. in diameter, in concrete cone 6 ins. in diameter, set, marked and witnessed as described in the official record.

Land, level to gently rolling.

Soil, sandy silt to very sandy first and second rate.

Timber, none.

Undergrowth, none.



BOOK 4532

Dependent Resurvey, Subdivision of T. 8 S., R. 22 W.

Chains	
	<p>Partial Subdivision of Section 30, T. 8 S., R. 22 W.</p> <hr/>
	<p>From the <math>\frac{1}{4}</math> section corner of sections 30 and 31.</p> <p>N. <math>0^{\circ} 08' W.</math>, on the north-south center line of section 30.</p>
40.09	<p>Intersect the east-west center line of section 30, the center <math>\frac{1}{4}</math> section corner of section 30.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked:</p> <p style="text-align: center;">T8S R22W C <math>\frac{1}{4}</math> S30 1960</p>
60.14	<p>The center north sixteenth section corner of section 30, at midpoint between the center <math>\frac{1}{4}</math> section corner of section 30 and the <math>\frac{1}{4}</math> section corner of sections 19 and 30.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked:</p> <p style="text-align: center;">T8S R22W C N <math>1/16</math>   S30 C 1960</p>
80.19	<p>The <math>\frac{1}{4}</math> section corner of sections 19 and 30.</p> <p>Land, nearly level bottom land of Gila Valley. Soil, sand and sandy loam. Timber, none. Undergrowth, none.</p>
	<p>From the <math>\frac{1}{4}</math> section corner of sections 29 and 30.</p> <p>S. <math>89^{\circ} 21' W.</math>, on the east-west center line of section 30.</p> <p>Over nearly level land, through cultivated fields.</p>
30.90	Edge of undergrowth, bears N. and S.; leave cultivated area.
39.90	West edge of undergrowth, bears N. and S. enter cultivated field.
40.01	The center $\frac{1}{4}$ section corner of section 30.
59.70	Concrete lined irrigation ditch, 10 links wide, 3 feet deep, flows S. from W., continue along S. side of ditch.
60.40	Unimproved road, bears W. and S.; continue along center of road.
79.95	<p>The <math>\frac{1}{4}</math> section corner of sections 25 and 30, on the W. boundary of the township.</p> <p>Land, nearly level bottom land of Gila Valley. Soil, sand and sandy loam. Timber, none. Undergrowth, greasewood and mesquite.</p>

## Partial Subdivision of Section 30, T. 8 S., R. 22 W.

## Chains

From the west sixteenth section corner of sections 19 and 30.

S.  $0^{\circ} 08' E.$ , on calculated mean bearing, on the west sixteenth line of section 30.

Over nearly level cultivated land.

20.06'

Intersect the north sixteenth line of section 30, point for the northwest sixteenth corner of section 30.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, with brass cap marked:

T8S R22W  
NW 1/16 S30  
1960

Land, nearly level bottom land of Gila Valley.

Soil, sandy loam.

Timber, none.

Undergrowth, none.

Subdivision of the Abandoned Bed of the Gila River, as originally surveyed.

Lot 1, section 30, as originally surveyed was bounded on its southwest side by the right bank of the Gila River, a non-navigable stream. The river has subsequently abandoned this channel by devious movements. The following surveys are of the division of that part of the abandoned channel inuring to former Lot 1.

From the center north sixteenth section corner of section 30.

S.  $89^{\circ} 19' W.$ , along the north sixteenth line of section 30.

Over nearly level cultivated land.

19.99

The northwest sixteenth corner of section 30.

25.67

Intersect the adjusted record meander line on the right bank of the Gila River as originally surveyed; point for the special meander corner of section 30.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, with brass cap marked:

T8S R22W  
SMC S  
N 30  
1960

S.  $75^{\circ} 17' W.$ , beginning new measurement, on the extension of the north sixteenth line, normal to the medial line of the channel of the Gila River, now abandoned, as originally surveyed.

8.43

Intersect the medial line of the Gila River.

Subdivision, Section 30, T. 8 S., R. 22 W.

Chains

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, for A.P. 2, with brass cap marked:

T8S R22W  
 AP 2  
 S30  
 1960

Thence

N.  $14^{\circ} 43'$  W., along the medial line of the Gila River.

4.39 Angle Point No. 1.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, with brass cap marked:

T8S R22W  
 S30 AP 1  
 1960

Thence

N.  $57^{\circ} 11'$  W., continue along medial line.

5.97

The special meander corner of sections 25 and 30, on the west boundary of the township, which is marked by an iron post,  $2\frac{1}{2}$  ins. diam., set as described in the official record for T. 8 S., R. 23 W., executed concurrently.

Land, nearly level cultivated bottom land of Gila Valley.

Soil, sandy loam.

Timber, none.

Undergrowth, none.

Partial Subdivision of Section 19

From the  $\frac{1}{4}$  section corner of sections 19 and 30.

N.  $0^{\circ} 12'$  W., along the north-south center line of section 19.

Over nearly level cultivated land.

21.80

The mean high water line on the left bank of the Colorado River, bearing N.  $56^{\circ} 23'$  E. and S.  $60^{\circ}$  W.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 24 ins. in the ground, in concrete, for the special meander cor. on the N-S center line of sec. 19, with brass cap mkd:

SMC  
 C  
 S 19  
 C  
 T8S R22W  
 1960

## Subdivision of Section 19, T. 8 S., R. 22 W.

## Chains

42.18

The mean high water line on the right bank of the Colorado River, bears N. 85° E. and S. 85° W. Water at present low stage, 2 to 5 feet deep.

Set an iron post, 30 ins. long, 2½ ins. in diameter, 20 ins. in the ground, in a collar of stone, cemented together with concrete, with brass cap marked, for the special meander cor. on the N-S centerline of Sec. 19:

T8S R22W

C  
S | 19  
C

SMC  
1960

Thence over gently rolling land, through dense undergrowth.

46.75

Ascend bluff bank, 6 ft. high, bearing E. and W.

59.10

Abandoned irrigation canal, bears E. and W. along S. edge of field; continue through dense undergrowth along E. edge of field.

77.00

South toe of new government levee.

77.85

Center of road, on top of levee, bears E. and W.

78.65

North toe of government levee; continue over nearly level cultivated field.

79.67

The ¼ section corner of sections 18 and 19, hereinbefore described.

Land, level to gently rolling sedimentary bottom.

Soil, river silt and sand, first rate.

Timber, scattered cottonwood.

Undergrowth, arrowweed, salt cedar, willow, and mesquite.

Resurvey of the Partial Subdivision, Section 7, as surveyed by  
Quintin R. Campbell, 1949.

From the ¼ section corner of sections 7 and 12 on the west boundary of the township, described in the field notes of T. 8 S., R. 23 W., surveyed concurrently under this same group.

N. 89° 33' E., on the east-west center line of section 7.

38.75

Angle Point No. 5 on the 1874 meander line of the left bank of the Colorado River, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.

N. 89° 33' E., beginning new measurement.

1.16

The center ¼ section corner of fractional section 7, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.

N. 89° 33' E., beginning new measurement.

## Subdivision of Section 7, T. 8 S., R. 22 W.

## Chains

8.30 The  $\frac{1}{4}$  section corner of fractional section 7, on the left bank of the 1920 abandoned channel of the Colorado River, marked by an iron post, 2 ins. in diameter, in concrete form 5 ins. square, set, and marked as described in the official record.

From this corner, angle point No. 16, hereinafter described, on the traverse of the left bank of the 1920 abandoned channel of the Colorado River, bears S. 23° 16' W., 4.63 chains dist.

From angle point No. 1, on the west boundary of Section 7, described in the field notes of T. 8 S., R. 23 W., surveyed concurrently under this same group.

Thence on the 1874 original meander line, established as a fixed and limiting boundary in the resurvey of 1949.

N. 45° 30' E., over level land.

0.25 Unimproved road bears N. and S.

Thence through cultivated fields.

5.90 Angle point No. 2, which is marked by an iron post, 1 inch in diameter, 10 ins. below the surface, set, and marked as described in the official record.

Thence

S. 86° 00' E.

14.75 Angle point No. 3, which is marked by a mutilated iron post 1 inch in diameter, and a broken concrete cone, 15 ins. below the surface.

At the angle point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. in diameter, 40 ins. in the ground with a collar of granite stone, with brass cap marked:

AP 3

S 7

T8S

R22W

1960

Thence

N. 47° 00' E.

15.50 Angle point No. 4, which is marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set marked, and witnessed as described in the official record.

Thence

N. 48° 03' E.

11.39 Angle point No. 5, on the East-west center line of fractional section 7, hereinbefore described.

Land, nearly level.

Soil, sandy loam.

Timber, none.

Undergrowth, arrowweed, salt cedar, willow, and mesquite.

## Subdivision of Section 7, T. 8 S., R. 22 W.

## Chains

Dependent Resurvey of the Traverse of the Left Bank of the 1920 (abandoned) channel of the Colorado River as originally surveyed by Quintin R. Campbell in 1949.

The initial point of this traverse, and angle point No. 1 thereof, is situated at the point of departure of the 1920 (abandoned) channel from the present right margin of the Colorado River, here flowing S. 25° W.

Angle point No. 1 is monumented by a rusted railroad rail firmly set in the ground.

At the angle point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground, with a collar of granite stone cemented together with concrete, with brass cap marked:

T8SR22W

AP 1

1960

Reset the rail alongside. A reference monument, set and marked, as described in the official record, bears S. 60° W., 1.00 chains distant. The northwest reference monument was missing and was not reestablished.

Angle point No. 9 and the corner of fractional sections 22 and 27, T. 16 S., R. 23 E., S.B.M., California, on right bank of 1920 channel, bears N. 89° 16' W. 19.72 chains distant, described in the field notes of the survey executed concurrently.

Thence

S. 37° 48' W., along the traverse of the left bank of the 1920 abandoned channel.

Ascend through dense arrowweed and mesquite.

0.78 Top of the Colorado River bank.

2.22 The witness point for sections 8 and 9, hereinbefore, described.

Thence in section 8, continue same line and measurement.

3.30 Irrigation ditch bears E. and W.

7.20 Enter cotton field, edge of field bears N. and S.

14.45 Field road bears N. and S.

18.55 Field road bears N. 74° E. and S. 74° W.; enter dense undergrowth.

18.80 Fence bears E. and W.


18.82 The witness point for sections 8 and 17 hereinbefore described.

Thence in section 17, continue same line and measurement.

28.60 Trail road bears N. 28° W., and S. 17° E.

29.89 Angle point No. 2, marked by an iron post, 1 inch in diameter, in concrete cone, 6 ins. in diameter, set, marked, and witnessed as described in the official record.

Dependent Resurvey of Traverse of Right Bank  
of 1920 Channel of Colorado River,  
T. 8 S., R. 22 W.

Chains	
	<p>Thence</p> <p>S. 49° 40' W.</p>
23.62	<p>Angle point No. 3, marked by a mutilated iron post 1 inch in diameter, and broken concrete cone.</p>
	<p>At the angle point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. in diameter, 25 ins. in the ground with a collar of granite stone cemented together with concrete with brass cap marked:</p> <div style="text-align: center;">  <p>1960</p> </div>
	<p>from which</p> <p>A buried Southern Pacific Gas Co. pipe line bears South, approximately 29 links dist.</p>
	<p>Thence</p> <p>S. 53° 42' W.</p>
16.07	<p>Approximate distance, buried Southern Pacific Gas Co. pipe line, in curve bearing NE. and WSW.</p>
19.15	<p>Toe of levee, ascend E. slope.</p>
20.45	<p>Top of levee, E. edge of road.</p>
20.792	<p>Center line of new government levee, marked by U.S.B.R. brass cap, 3 ins. in diameter, set in concrete block, 6 ins. square, 6 ins. below the surface of road, marked:</p> <div style="text-align: center;"> <p>U.S.B.R. P.O.T. &amp; P.O.M.L. sta. 384 + 04.76 1953</p> </div>
21.15	<p>Western edge of road, descend W. slope of levee.</p>
22.45	<p>Toe of levee.</p>
24.14	<p>Angle point No. 4, marked by an iron post, 1 inch in diameter, in concrete cone 6 ins. in diameter, set, and marked as described in the official record.</p>
	<p>Thence</p> <p>S. 87° 41' W.</p> <p>Over level land through dense undergrowth.</p>
23.90	<p>Angle point No. 5, marked by an iron post, 1 inch in diameter, in concrete cone 6 ins. in diameter, set, and marked as described in the official record.</p> <p>Thence</p> <p>S. 64° 34' W.</p>

Dependent Resurvey of Traverse of Right Bank  
of 1920 Channel of Colorado River,  
T. 8 S., R. 22 W.

Chains

0.58 The witness point on the section line between section 17 and 18, hereinbefore described. Thence in section 18.


5.78 Trail road, bears E. and W.

28.13 Ascend 6 ft. bank, enter rolling sand dunes.

29.05 Angle point No. 6, marked by a mutilated iron post 1 inch in diameter and broken concrete cone.

At the angle point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 28 ins. in the ground with a collar of granite stone cemented together with concrete with brass cap marked:



1960

from which

A mesquite 20 ins. in diameter, bears N.  $20^{\circ}$  W., 77 links dist. marked X BT.

Thence

N.  $89^{\circ}$  58' W.

15.30 Angle point No. 7, marked by an iron post, 1 inch in diameter, in concrete cone 6 ins. in diameter, set, marked, and witnessed as described in the official record.

Thence


N.  $52^{\circ}$  27' W.

21.00 Cross old channel; ascend bank 8 ft. high, bearing N.  $30^{\circ}$  E. and S.  $30^{\circ}$  W.; enter cultivated fields.

23.10 Angle point No. 8, marked by a mutilated iron post, 1 inch in diameter, and broken concrete cone.

At the angle point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground with a collar of granite stone cemented together with concrete with brass cap marked:



1960

Thence

N.  $16^{\circ}$  34' E.

7.94

Angle point No. 9, marked by a mutilated iron post, 1 inch in diameter, and broken concrete cone.

At the angle point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground with a collar of granite stone cemented together with concrete



Dependent Resurvey of Traverse of Right Bank  
of 1920 Channel of Colorado River,  
T. 8 S., R. 22 W.

## Chains

with brass cap marked:

S19  
T8S  
R22W  
AP9  
1960

Thence

N. 21° 59' W.

8.80

Irrigation ditch, course E. leave cultivated field. Thence along sharply defined bank, 8 ft. high, through dense arrowweed.

11.02

Angle point No. 10, marked by a mutilated iron post, 1 inch in diameter, and broken concrete cone.

At the angle point.

Set an iron post, 30 ins. long, 2½ ins. in diameter, 25 ins. in the ground with a collar of granite stone cemented together with concrete, brass cap marked:

S18  
T8S  
R22W  
AP10  
1960

N. 2° 13' E.

18.04

The corner of fractional sections 7 and 18, and angle point No. 11, hereinbefore described.

Thence in section 7.

N. 12° 33' E.

2.65

Angle point No. 12, marked by a mutilated iron post 1 inch in diameter.

At the angle point

Set an iron post, 30 ins. long, 2½ ins. in diameter, 28 ins. in the ground with a collar of granite stone cemented together with concrete with brass cap marked:

T8S  
R22W  
S7  
AP12  
1960

Thence

N. 48° 00' E.

5.21

Angle point no. 13, marked by an iron post 1 inch in diameter, in concrete form 5 ins. square, set, and marked as described in the official record.

Thence

N. 20° 34' E.

8.15

Angle point No. 14, marked by a mutilated iron post 1 inch in diameter.

At the angle point.

Dependent Resurvey of Traverse of Right Bank  
of 1920 Channel of Colorado River,  
T. 8 S., R. 22 W.

Chains

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 20 ins. in the ground with a collar of granite stone cemented together with concrete. Brass cap marked:

T8S  
R22W AP14  
S7  
1960

Thence

N.  $45^{\circ} 20'$  E.

5.00 The south end of a narrow slough extending N. bears E. 1.00 chains dist.

9.10 South edge of cultivated field.

10.25 East edge of same field.

12.50 South edge of cultivated field.

18.75 East edge of same field. Trail road extends N. and S. along field.

23.60 Angle point No. 15, marked by an iron post, 1 inch in diameter, in concrete form, 5 ins. square, set, marked as described in the official record.

From this point, the corner of fractional sections 21 and 28 and angle point No. 24, T. 16 W., R. 23 E., S.B.M., California, bears S.  $19^{\circ} 48'$  W., 14.18 chains dist., described in the field notes of the survey executed concurrently.

Thence

N.  $31^{\circ} 17'$  E.

Along 12 ft. bank.

6.65 Angle point No. 16, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.

Thence

N.  $23^{\circ} 16'$  E.

4.63 The  $\frac{1}{4}$  section corner of fractional section 7, hereinbefore described.

Thence

N.  $23^{\circ} 16'$  E.

0.10 Trail road, bears E. and W., thence over gently rolling sand dunes.

18.35 Power line, single pole, bears E. and W.

20.46 Angle point No. 17, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.

Thence

N.  $19^{\circ} 20'$  E.

Across gently rolling sand dunes.

22.08 The corner of fractional sections 6 and 7 and angle point No. 18, hereinbefore described.

Dependent Resurvey of Traverse of Right Bank  
of 1920 Channel of Colorado River,  
T. 8 S., R. 22 W.

Chains	
	<p>Thence in sec. 6. Thence in section 6 N. 15° 03' E. Over gently rolling sand dunes through scattered undergrowth.</p>
10.52	Fence line, bears E. and W.
19.76	<p>Angle point No. 19, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.</p>
	<p>Thence N. 13° 12' E.</p>
18.11	<p>Angle point No. 20, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.</p>
	<p>Thence N. 2° 45' E.</p>
11.87	<p>Electric power transmission line, 5 wires on double wood poles, bears N. 86° 09' E. and S. 86° 09' W.; a service road follows this line.</p>
3.32	<p>The <math>\frac{1}{4}</math> section corner of fractional section 6, marked by an iron post, 2 ins. in diameter, in concrete cone 6 ins. in diameter, set, marked, and witnessed as described in the official record.</p>
	<p>Thence N. 2° 45' E.</p>
9.70	S. edge of cultivated field, bears E. and W.
12.18	<p>Angle point No. 21, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.</p>
	<p>The corner of fractional <del>sections</del> sections 15 and 16 and angle point No. 36, T. 16 S., R. 23 E., S.B.M., California, bears N. 30° 18' E. 12.46 chains dist., described in the field notes of the surveys executed concurrently.</p>
	<p>Thence N. 38° 13' W.</p>
20.90	<p>Angle point No. 22, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.</p>
	<p>Corner is situated 2 links E. of fence line extending N. and S. Thence</p>
	<p>N. 64° 28' W. Over level land through dense undergrowth.</p>
10.80	<p>Angle point No. 23, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.</p>
	<p>Thence N. 73° 56' W.</p>

Dependent Resurvey of Traverse of Right Bank  
of 1920 Channel of Colorado River,  
T. 8 S., R. 22 W.

## Chains

- 7.70 Angle point No. 24, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.
- Thence  
S. 78° 30' W.
- 3.74 The  $\frac{1}{4}$  section corner on N-S centerline of fractional section 6, marked by an iron post, 2 ins. in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.
- Thence  
S. 78° 30' W.
- 2.25 Trail road, bears SW. and E.
- 2.75 Abandoned pumping plant, bears N. 40 links dist.
- 4.06 Angle point No. 25, marked by a mutilated iron post, 1 inch in diameter.
- At the angle point.  
Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diameter, 25 ins. in the ground, with a collar of stone cemented together with concrete, with brass cap marked:
- AP25

S6

T8S R22W

1960
- Thence  
N. 87° 30' W.
- 13.30 Angle point No. 26, marked by an iron post, 1 inch in diameter, in concrete form 5 ins. square, set, marked, and witnessed as described in the official record.
- Thence  
S. 77° 19' W.
- 18.20 Fence line, bears E. and W.
- 23.16 Corner of fences extending N., S., and E.
- 23.19 Intersect the corner of fractional sections 1 and 6, on the West boundary of the township, and angle point No. 27, described in the field notes of T. 8 S., R. 23 W., G. & S. R. M., Arizona, surveyed concurrently under this same group.
- Land, nearly level.  
Soil, sandy loam.  
Timber, mesquite, salt cedar, and cottonwood.  
Undergrowth, arrowweed, salt cedar, mesquite, willow, and small brushes.

Meanders of the Present Right Bank of the Colorado River,  
Section 19 ( $E\frac{1}{2}$ )

Dependent Resurvey of Traverse of Right Bank  
of 1920 Channel of Colorado River,  
T. 8 S., R. 22 W.

## Chains

From the meander corner of sections 19 and 20, on the right bank of the Colorado River, hereinbefore described.

In section 19 (E.  $\frac{1}{4}$  mile).

Along bluff bank of river, through dense undergrowth, downstream.

S. 45° W., 6.90 chains.

S. 52° W., 5.60 chains.

S. 43° W., 5.60 chains.

S. 52° W., 12.80 chains.

S. 70° W., 4.80 chains.

S. 76° W., 7.10 chains.

N. 88° 20' W. 5.03 chains. To the special meander corner on the longitudinal center line, section 19, hereinbefore described.

Meanders of the Present Left Bank of the Colorado River,  
Section 19 (E $\frac{1}{2}$ )

From the intersection of the line between sections 19 and 20 with the mean high water line of the present left bank of the Colorado River, from which the witness point on the line bet. secs. 19 and 20, as hereinbefore described, bears S. 0° 23' E., 95 lks. dist.

In Section 19 (E $\frac{1}{2}$  mile).

Through dense undergrowth, along the left bank, downstream.

S. 56° 23' W., 39.09 chains Mouth of the Gila River, 60 lks. wide, flows from the S.

S. 56° 23' W., 8.60 chains The special meander cor. on the longitudinal centerline of section 19, as hereinbefore described.

Land, nearly level to gently rolling sedimentary bottom.

Soil, sand and sandy loam.

Timber, scattered cottonwood.

Undergrowth, salt cedar, willows, mesquite and arrowweed.

General Description

The area covered by these resurveys is located in the bottom land of the Gila and Colorado Rivers. The land varies from flat to gently rolling. A good portion is presently under cultivation. The soil is a deep sandy clay loam. The timber along the banks of the rivers consists of willow, mesquite, palo verde, palo fierro and salt cedar. The undergrowth is largely tamarisk, salt cedar, weeds and grass. Most of the land is under cultivation.

Arizona State Highway No. 95 is located on the first latitudinal line and the road to the north Gila area follows the third meridional line. There are a great number of roads along the section and quarter-section lines, together with various other trail roads which make the whole area very accessible.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

BOOK 4592

68

FIELD ASSISTANTS

NAMES	CAPACITY
Paul G. Bauer	Surveying Technician
Theodore L. Thayer	Cartographic Surveying Aide
Jerry Lee Thomas	"
Anthony W. Coombs	"
Frank W. Rogers	"
Harold W. Grusing	"
Gilbert V. Olson	"
Morris Blackburn	"
Darwin A. Johnston	"
LaVern Griffin	"
Max Asay	"
Dan V. Coleman	"
Gart T. Oviatt	"
Kimble H. Moffitt	"
Douglas L. McInelly	"

CERTIFICATE OF CADASTRAL SURVEYOR

We, Donald A. Cannon, Robert S. Kaiser

and Gerald F. Pittman, HEREBY CERTIFY upon honor that, in

pursuance of special instructions bearing date of the 15th day of September, 1960, and supplemental special instructions dated November 3, 1960, we have executed, under the supervision of Robert C. Yundt, the dependent resurvey and survey of the south boundary, east boundary and subdivisional lines; the traverse of the 1920 abandoned channel of the Colorado River; and, a portion of the medial line of the Gila River, Township 8 South, Range 22 West,

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

May 22, 1961 (Date)

Donald A. Cannon Robert S. Kaiser (Cadastral Surveyor)

(Date)

Gerald F. Pittman (Cadastral Surveyor)

Robert C. Yundt

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., AUG 28 1961, 19

The foregoing field notes of the dependent resurvey and survey of Township 8 South, Range 22 West, Gila & Salt River Meridian, Arizona,

executed by Donald A. Cannon, Robert S. Kaiser and Gerald F. Pittman, under the supervision of Robert C. Yundt, having been critically examined and found correct, are hereby approved.

Clark J. Gamm

Acting Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Cadastral Engineering Staff Officer)