

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

OF

REMONUMENTED

CADASTRAL SURVEY CORNERS

TOWNSHIP 7 SOUTH, RANGE 23 EAST

IN

COOPERATION WITH

U. S. FOREST SERVICE

Of the *Gila & Salt River Meridian,*

In the State of *Arizona*

### EXECUTED BY

*Lester S. Mann, Office Cadastral Engineer*

*Under special instructions dated March 4, 1960, which provided*

*for the surveys included under Group No. 350, approved March 11, 1960*

*and assignment instructions dated March 11, 1960*

*Survey commenced May 9, 1960*

*Survey completed May 9, 1960*

12

BOOK 4597

# INDEX DIAGRAM

Township 7 South, Range 23 East

6	5	4	3	2	1
7	8	9	10	11	12
13	2	17	16	15	14
19	20	21	1	1	24
29	28	27	26	25	1
31	32	33	34	35	36

## Chains

The following field notes are those of remonumented cadastral survey corner monuments by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958. The approval of the Special Instructions on March 11, 1960, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 54 dated April 21, 1954.

The cor. of secs. 23, 24, 25 and 26 is monumented with a granite stone, 16 x 12 x 8 ins., firmly set with mound of stone to W., mkd. with 1 notch on the E. and 2 notches on the S.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R23E  
S23|S24  
S26|S25  
1960

Bury the original cornerstone alongside the iron post. Iron post is on a gentle NW slope.

The cor. of secs. 14, 15, 22 and 23 is monumented with a granite stone, 14 x 10 x 8 ins., loosely set with mound of stone to W., mkd. with 2 notches on one edge and 3 notches on adjoining edge.

from which

A mesquite stump, 6 ins. diam., bears N.  $62^{\circ}$  E.,  $32\frac{1}{2}$  lks.

A mesquite stump, 6 ins. diam., bears N.  $88^{\circ}$  W., 12 lks.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R23E  
S15|S14  
S22|S23  
1960

Bury the original cornerstone alongside the iron post. Iron post is  $2\frac{1}{2}$  lks. W. of the head of a very small wash, course N.  $10^{\circ}$  E.

NOTE: This cor. is not on the National Forest boundary but is set for control.

The cor. of secs. 15, 16, 21 and 22 is monumented with a granite stone, 20 x 12 x 10 ins., firmly set with a mound of stone to W., mkd. with 3 notches on the E. and S. faces.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

(2)

Chains

T7S R23E  
S16|S15  
S21|S22  
1960

Bury the original cornerstone alongside the iron post. Iron pipe is on a NW slope.

The  $\frac{1}{4}$  cor. of secs. 17 and 18 is monumented with a granite stone, 16 x 6 x 4 ins., firmly set in a collar of stone, mkd.  $\frac{1}{4}$  on N. face.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, brass cap mkd.

T7S R23E  
 $\frac{1}{4}$   
S18|S17  
1960

from which

Build a mound of stone, 3-foot base,  $2\frac{1}{2}$  ft. high to W.

Bury the original cornerstone alongside the iron post. Iron post is on a NW slope.

NOTE: This corner is not on the National Forest boundary but is set for control.

BOOK 487

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
U. S. Forest Service Personnel	
C. C. Doak	Cartographic Engineer
Joseph Sisneros	Engineering Aide
John R. Holbrook	Cartographic Aide

CERTIFICATE OF CADASTRAL ENGINEER

I, Lester S. Mann, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of March, 1960, I have surveyed and remonumented the cadastral survey corners in T. 7 S., R. 23 E. in cooperation with the U. S. Forest Service.

of the G&SR Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona
June 21, 1960

Lester S. Mann
Lester S. Mann
Office Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., SEP 5 1961

The foregoing field notes of the surveyed and remonumented cadastral survey corners in Township 7 South, Range 23 East, Gila and Salt River Meridian, Arizona,

executed by Lester S. Mann, Office Cadastral Engineer having been critically examined and found correct, are hereby approved.

Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Cadastral Engineering Staff Officer