

①

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF

REMONUMENTED

CADASTRAL SURVEY CORNERS

TOWNSHIP 7 SOUTH, RANGE 22 EAST

IN

COOPERATION WITH

U. S. FOREST SERVICE

Of the Gila & Salt River Meridian,

In the State of Arizona

EXECUTED BY

Lester S. Mann, Office Cadastral Engineer

Under special instructions dated March 4, 1960, which provided

for the surveys included under Group No. 350, approved March 11, 1960

and assignment instructions dated March 11, 1960

Survey commenced May 17, 1960

Survey completed May 18, 1960

1A

BOOK 4598

BOOK 4598

INDEX DIAGRAM

Township 7 South, Range 22 East

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

Chains

The following field notes are those of remonumented cadastral survey corner monuments by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958. The approval of the Special Instructions on March 11, 1960, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 54 dated April 21, 1954.

The $\frac{1}{4}$ cor. of secs. 13 and 24 is monumented with a granite stone, 14 x 12 x 6 ins., lying in a loose mound of stone, mkd. $\frac{1}{4}$ on one face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R22E

$\frac{1}{4}$ S13

S24

1960

Bury the original cornerstone alongside the iron post. Iron post is on a very old E.-W. fence line and about 1.50 chs. N. of a newer E.-W. fence, on a gentle E. slope.

The cor. of secs. 13, 14, 23 and 24 is monumented with a granite stone, 30 x 8 x 6 ins., firmly set, mkd. with 1 notch on the E. and 3 notches on the S. faces.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R22E

S14 | S13

S23 | S24

1960

Place the original cornerstone in collar of stone around iron post. Iron post is 9 lks. N. of an E.-W. fence on a steep N. slope.

The $\frac{1}{4}$ cor. of secs. 14 and 23 is monumented with a granite stone 24 x 6 x 4 ins., firmly set in a loose collar of stone, mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, collar of stone, brass cap mkd.

T7S R22E

$\frac{1}{4}$ S14

S23

1960

Bury the original cornerstone alongside the iron post. Iron post is $2\frac{1}{2}$ lks. N. and 29 lks. E. of a fence corner from which fences bear E.-W.-S., and on a N. slope.

Chains

The cor. of secs. 14, 15, 22 and 23 is monumented with a granite stone, 20 x 8 x 6 ins., firmly set in a loose mound of stone, mkd. with 2 notches on the E. and 3 notches on the S. faces.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R22E
 S15 | S14
 S22 | S23
 1960

Bury the original cornerstone alongside the iron post. Iron post is 7 lks. N. of an E.-W. fence on a steep W. slope.

The $\frac{1}{4}$ cor. of secs. 15 and 22 is monumented with a granite stone, 30 x 12 x 6, firmly set and in a collar of stone, mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R22E
 $\frac{1}{4}$ S15
 S22
 1960

Bury the original cornerstone alongside the iron post. Iron post is $7\frac{1}{2}$ lks. N. of an E.-W. fence on a gentle S. slope.

The $\frac{1}{4}$ cor. of secs. 16 and 21 is monumented with a granite stone, 22 x 10 x 8 ins., firmly set in a scattered mound of stone, mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R22E
 $\frac{1}{4}$ S16
 S21
 1960

Bury the original cornerstone alongside the iron post. Iron post is on a gentle, eroded S. slope.

NOTE: This cor. is not on the National Forest bdy., but is set for control.

The cor. of secs. 28, 29, 32 and 33 is monumented with a granite stone, 14 x 6 x 6 ins., firmly set with a mound of stone to the SE., mkd. with 4 notches on the E. and 1 notch on the S. edges.

At the cor. point

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, collar of stone, brass cap mkd.

T7S R22E	
S29	S28
S32	S33
1960	

from which

A juniper, 24 ins. diam., bears N. 31° E., 129 lks. dist., mkd. BT.

A double juniper, 5 ins. diam., bears N. 64° W., 38½ lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. Iron post is 11 lks. W. and 2½ lks. N. of a fence corner post; fences bear N. and W.

The ¼ cor. of secs. 29 and 32 is monumented with a granite stone, 16x12x8 ins., loose on ground with a mound of stone to SW., mkd. ¼ on one face.

At the cor. point (where the original stone was lying)

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T7S R22E	
¼ S29	
¼ S32	
1960	

from which

A juniper with many shoots, 24 ins. diam. at base, bears S. 79° W., 87½ lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. Iron pipe is 2½ lks. S. of an E.-W. fence on a small spur.

The cor. of secs. 29, 30, 31 and 32 is monumented with a granite stone, 18x12x8 ins., firmly set in a collar of stone, mkd. with 5 notches on the E. and 1 notch on the S. edges.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, collar of stone, brass cap mkd.

T7S R22E	
S30	S29
S31	S32
1960	

Bury the original cornerstone alongside the iron post. Iron post is 5 lks. N. of a fence corner post from which fences bear E. and S., and on an eroded N. slope.

UNITED STATES GOVERNMENT

Chains

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1952
1953
1954
1955

1956

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1956
1957
1958
1959

1960

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1961

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1962
1963
1964
1965

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES GOVERNMENT
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
U. S. Forest Service Personnel	
C. C. Doak	Cartographic Engineer
Joseph Sisneros	Engineering Aide
John R. Holbrook	Cartographic Aide

CERTIFICATE OF CADASTRAL ENGINEER

I, Lester S. Mann, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of March, 1960, I have ~~surveyed~~ remonumented the cadastral survey corners in T. 7 S., R. 22 E. in cooperation with the U. S. Forest Service

of the G&SR Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona

June 21, 1960

Lester S. Mann
Lester S. Mann
Office Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., SEP 5 1961, 1961

The foregoing field notes of the survey of remonumented cadastral survey corners in Township 7 South, Range 22 East, Gila and Salt River Meridian, Arizona,

executed by Lester S. Mann, Office Cadastral Engineer

having been critically examined and found correct, are hereby approved.

John Pennington
Chief, ~~Division of Engineering~~ Cadastral Engineering Staff Office

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in~~

~~is a true copy of the original field notes.~~

~~Cadastral Engineering Staff Office~~