

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

OF

REMONUMENTED

CADASTRAL SURVEY CORNERS

TOWNSHIP 9 SOUTH, RANGE 25 EAST

IN

COOPERATION WITH

U. S. FOREST SERVICE

Of the Gila & Salt River Meridian,

In the State of Arizona

EXECUTED BY

Lester S. Mann, Office Cadastral Engineer

Under special instructions dated March 4, 1960, which provided  
for the surveys included under Group No. 350, approved March 11, 1960  
and assignment instructions dated March 11, 1960

Survey commenced May 4, 1960

Survey completed May 4, 1960

12

BOOK 4600

# INDEX DIAGRAM

Township 9 South, Range 25 East

|    |    |    |    |    |    |   |
|----|----|----|----|----|----|---|
| 6  | 5  | 4  | 3  | 2  | 1  | 3 |
| 7  | 8  | 9  | 10 | 11 | 12 | 2 |
| 13 | 14 | 15 | 16 | 17 | 18 | 1 |
| 19 | 20 | 21 | 22 | 23 | 24 | 1 |
| 25 | 26 | 27 | 28 | 29 | 30 | 1 |
| 31 | 32 | 33 | 34 | 35 | 36 | 1 |

## Chains

The following field notes are those of remonumented cadastral survey corner monuments by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958. The approval of the Special Instructions on March 11, 1960, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 54 dated April 21, 1954.

The cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp. is monumented with a granite stone, 12 x 8 x 6 ins., firmly set in a mound of stone, mkd. with 1 notch on the S. and 5 notches on the N. edges.

from which

A dead mesquite, 10 ins. diam., bears S.  $84\frac{1}{2}^{\circ}$  W., 202 lks. dist.; scribe marks S36 BT visible.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, collar of stone, brass cap mkd.

T9S  
R25E R26E  
S25 | S30  
S36 | S31  
1960

from which

A mesquite, 16 ins. diam. at the base, bears S.  $74\frac{1}{4}^{\circ}$  W., 126 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. The iron post is  $3\frac{1}{2}$  lks. E. of a N.-S. fence.

The cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp. is monumented with a granite rock in place, 30 x 30 x 18 ins., mkd. with an "X" and 3 notches on the S. and N. edges.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, collar of stone, brass cap mkd.

T9S  
R25E R26E  
S13 | S18  
S24 | S19  
1960

Bury the original cornerstone alongside the iron post. The iron post is  $2\frac{1}{2}$  lks. E. of a N.-S. fence and on a small spur sloping E.

The  $\frac{1}{4}$  cor. of secs. 13 and 18 on the E. bdy. of the Tp. is monumented with a granite stone, 18 x 12 x 6 ins., firmly set in a loose mound of stone, mkd.  $\frac{1}{4}$  on W. face.

Chains

from which

A mesquite, 12 ins. at the base, bears N.  $76\frac{1}{2}^{\circ}$  W., 108 lks. dist., mkd. with a blaze and faint scribe marks.

A mesquite stump, 14 ins. at the base, bears N.  $14^{\circ}$  E., 172 lks.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, brass cap mkd.

T9S  
R25E R26E  
 $\frac{1}{4}$   
S13 | S18  
1960

from which

A mesquite, 4 ins. diam., bears S.  $41^{\circ}$  W.,  $67\frac{1}{2}$  lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post.

The iron post is 3 lks. E. of a N.-S. fence and 20 lks. N. of gate.

The cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp. is monumented with a granite stone 18 x 6 x 4 ins., set flush to ground, mkd. with 4 notches on the S. and 2 notches on the N. sides.

from which

A dead mesquite, 14 ins. diam., bears N.  $75\frac{1}{2}^{\circ}$  W., 241 lks. dist., mkd. T. 9 S., R. 25 E. S12 BT.

A 4-pronged tesota, 12 ins. at the base, bears N.  $27^{\circ}$  E., 138 lks. dist.; no marks.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, brass cap mkd.

T9S  
R25E R26E  
S12 | S 7  
S13 | S18  
1960

from which

A mesquite, 8 ins. diam., bears S.  $49^{\circ}$  E., 91 lks. dist. mkd. BT.

A mesquite, 4 ins. diam., bears S.  $54\frac{1}{2}^{\circ}$  W., 68 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post.

The iron post is  $2\frac{1}{2}$  lks. E. of a N.-S. fence and in a small drain. A fence cor. bears N.  $10^{\circ}$  W., 15 lks. dist.

## Township 9 South, Range 25 East, Arizona

3

## Chains

The  $\frac{1}{4}$  cor. of secs. 1 and 6 on the E. bdy. of the Tp. is monumented with a hard sandstone,  $1\frac{1}{4}$  x 8 x 6 ins., firmly set in an area of loose rock, mkd.  $\frac{1}{4}$  on W. face.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, brass cap mkd.

T9S  
R25E R26E

$\frac{1}{4}$   
S1|S6  
1960

Bury the original cornerstone alongside the iron post. The iron post is on a U-shaped mesa and 10 lks. E. of a N.-S. fence.

4

BOOK 4600

4-680  
(Feb., 1960)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| NAMES                          | CAPACITY              |
|--------------------------------|-----------------------|
| U. S. Forest Service Personnel |                       |
| C. C. Doak                     | Cartographic Engineer |
| Joseph Sisneros                | Engineering Aide      |
| John R. Holbrook               | Cartographic Aide     |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |
|                                |                       |

CERTIFICATE OF CADASTRAL ENGINEER

I, Lester S. Mann, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of March, 1960, I have surveyed remonumented the cadastral survey corners in T. 9 S., R. 25 E. in cooperation with the U. S. Forest Service.

of the G&SR Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona
June 21, 1960

Lester S. Mann
Lester S. Mann
Office Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., SEP 5 1961

The foregoing field notes of the remonumented cadastral survey corners in Township 9 South, Range 25 East, Gila and Salt River Meridian, Arizona,

executed by Lester S. Mann, Office Cadastral Engineer
having been critically examined and found correct, are hereby approved.

Chief, Division of Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in is a true copy of the original field notes.

Cadastral Engineering Staff Officer