

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF

REMONUMENTED

CADASTRAL SURVEY CORNERS

TOWNSHIP 9 SOUTH, RANGE 21 EAST

IN

COOPERATION WITH

U. S. FOREST SERVICE

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Lester S. Mann, Office Cadastral Engineer

Under special instructions dated March 4, 1960, which provided
for the surveys included under Group No. 350, approved March 11, 1960
and assignment instructions dated March 11, 1960

Survey commenced May 10, 1960

Survey completed May 11, 1960

1A

BOOK 4602

INDEX DIAGRAM

Township 9 South, Range 21 East

6	5	4	3	2	1
7	8	9	10	11	12
14	13	12	11	10	9
18	17	16	15	14	13
4	3	2	1	30	29
19	20	21	22	23	24
30	3	29	28	27	26
31	2	2	1	34	33
	32	31	30	29	28

Chains

The following field notes are those of remonumented cadastral survey corner monuments by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958. The approval of the Special Instructions on March 11, 1960, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 54 dated April 21, 1954.

The cor. of secs. 32 and 33 on the S. bdy. of the Tp. is monumented with the remains of a wood post in a mound of stone. A steel fence post has been driven at this point.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, collar of stone to top, brass cap mkd.

T9S R21E
S32 | S33
S5
T10S
1960

from which

An iron post, 2 ins. diam., bears E., 65 lks. dist., mkd.

T9S R21E
S32 | S33
C C
S5 | S4
T10S
1915

and is at a fence cor. post from which fences bear E. and S.

Iron post is on fairly steep E. slope of a small spur.

The $\frac{1}{4}$ cor. of secs. 32 and 33 is monumented with a granite stone, 14 x 10 x 6 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on the W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T9S R21E
 $\frac{1}{4}$
S32 | S33
1960

Bury the original cornerstone alongside the iron post. Iron post is on a ridge of a mesa, 30 lks. S. of a track road bearing S. 70° W. and N. 70° E.

The cor. of secs. 28, 29, 32 and 33 is monumented with a granite stone, 16 x 10 x 8 ins., firmly set in a mound of stone, mkd. with 1 notch on S. and 4 poor notches on E. edges and a faint $\frac{1}{4}$ on the S.

Chains

from which

A black oak, 22 ins. diam., bears S. 28 $\frac{1}{2}$ ° E., 297 lks. dist.; blaze has completely grown over.

A dead oak, 20 ins. diam., bears S. 30° W., 327 lks. dist.; blaze has grown over, but chopped out scribe mks. XXI E.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone to top, brass cap mkd.

T9S	R21E
S29	S28
S32	S33
1960	

from which

A black oak, 10 ins. diam., bears S. 16 $\frac{1}{2}$ ° E., 306 lks. dist., mkd. BT.

A black oak, 24 ins. diam., bears S. 4° W., 295 lks. dist., mkd. BT.

A black oak, 22 ins. diam., bears S. 28 $\frac{1}{2}$ ° E., 297 lks. dist., mkd. BT. (Original B.T.)

Iron post is on a S. slope about 3.00 chs. N. of a large drain, course E.

The $\frac{1}{4}$ cor. of secs. 29 and 32 is monumented with a granite stone, 16 x 8 x 6 ins., firmly set with a mound of stone to N., mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T9S	R21E
$\frac{1}{4}$ S29	
$\frac{1}{4}$ S32	
1960	

Bury the original cornerstone alongside the iron post. Iron post is on a gentle S.E. slope.

The cor. of secs. 29, 30, 31 and 32 is monumented with the rotted point of an oak post in a mound of stone. Corner has been accepted locally and appears to be the original.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground, collar of stone to top, brass cap mkd.

T9S	R21E
S30	S29
S31	S32
1960	

Chains

Iron post is on a gentle S.E. slope about 7.00 chs. N. of a drain, course E.

The $\frac{1}{4}$ cor. of secs. 29 and 30 is monumented with a granite stone, 16 x 10 x 10 ins., firmly set with a mound of stone to N., mkd. $\frac{1}{4}$ on W. face.

from which

A fallen oak (badly rotted), 18 ins. diam., bears N. $27\frac{1}{2}^{\circ}$ W., 180 lks. dist.

A fallen oak, 16 ins. diam., bears N. 10° E., 167 lks., has rotten scar of a blaze.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T9S R21E

S30 | S29
1960

from which

A white oak, 16 ins. diam., bears N. 22° E., 231 lks. dist., mkd. BT.

A black oak, 10 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ W., 188 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post.

The cor. of secs. 19, 20, 29 and 30 is monumented with a granite stone, 12 x 8 x 8 ins., firmly set in a collar of stone, mkd. with 5 notches on E. and 2 notches on the S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone to top, brass cap mkd.

T9S R21E

S19 | S20
S30 | S29
1960

Bury the original cornerstone alongside the iron post. Iron post is on a gentle S. slope about 4.50 chs. N. of a drain, course S. 70° E.

The cor. of secs. 17, 18, 19 and 20 is monumented with a volcanic stone, 18 x 12 x 8 ins., firmly set with a mound of stone to the S.E., mkd. with 5 notches on the E. and 3 notches on the S. edges.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, collar of stone to top, brass cap mkd.

Chains

T9S R21E	
S18	S17
S19	S20
1960	

Bury the original cornerstone alongside the iron post. Iron post is on a steep N.E. slope.

The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp. is monumented with a granite stone, 18 x 12 x 8 ins., firmly set in a collar of stone, mkd. with 3 notches on the N. and S. edges.

At the cor. point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, collar of stone, brass cap mkd.

T9S	
R20E	R21E
S13	S18
S24	S19
1960	

Bury the original cornerstone alongside the iron post. Iron post is on a high mesa.

The $\frac{1}{4}$ cor. of secs. 13 and 18 on the W. bdy. of the Tp. is monumented with granite stone, 14 x 12 x 8 ins., firmly set with a mound of stone to N., mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone to top, brass cap mkd.

T9S	
R20E	R21E
S13	S18
1960	

Bury the original cornerstone alongside the iron post. Iron post is on a ridge of a high mesa.

The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp. is monumented with a mound of stone. The original cornerstone seems to be broken and top part could not be found.

from which

An oak, 30 ins. at base, bears N. 10° E., 32 lks. dist., mkd. with a blaze.

An oak, 14 ins. diam., bears N. 55° W., 153 lks. dist., mkd. with a small blaze.

An oak, 18 ins. diam., bears N. 82° W., 40 lks. dist., mkd. with an upper and lower blaze.

A dead oak, 20 ins. diam., bears S. 81° W., 113 lks. dist., mkd. with an overgrown blaze.

Chains

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground,
collar of stone to top, brass cap mkd.

T9S	
R20E	R21E
S12	S 7
S13	S18
1960	

from which

A black oak, 14 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ W., 129 lks. dist.,
mkd. BT.

Iron post is on a N. slope.

CERTIFICATE OF CADASTRAL ENGINEER

I, Lester S. Mann, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of March, 1960, I have ~~surveyed~~ remonumented the cadastral survey corners in T. 9 S., R. 21 E., in cooperation with the U. S. Forest Service.

of the G&SR Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona
June 21, 1960

Lester S. Mann
Lester S. Mann
Office Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., SEP 5 1961, 19

The foregoing field notes of the ~~survey~~ of remonumented cadastral survey corners in Township 9 South, Range 21 East, Gila and Salt River Meridian, Arizona,

executed by Lester S. Mann, Office Cadastral Engineer having been critically examined and found correct, are hereby approved.

Chief, Division of Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Cadastral Engineering Staff Officer.