

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF

REMONUMENTED

CADASTRAL SURVEY CORNERS

TOWNSHIP 22 SOUTH, RANGE 9 EAST

IN

COOPERATION WITH

U. S. FOREST SERVICE

Of the Gila & Salt River Meridian,

In the State of Arizona

EXECUTED BY

Lester S. Mann, Office Cadastral Engineer

Under special instructions dated March 4, 19 60, which provided
for the surveys included under Group No. 350, approved March 11, 1960
and assignment instructions dated March 11, 19 60

Survey commenced May 21, 1960

Survey completed June 18, 19 60

114

BOOK 4604

INDEX DIAGRAM

Township 22 South, Range 9 East

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

Township 22 South, Range 9 East, Arizona

18

Chains

The following field notes are those of remonumented cadastral survey corner monuments by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958. The approval of the Special Instructions on March 11, 1960, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 54 dated April 21, 1954.

The cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp. is monumented with a granite stone, 14 x 12 x 7 ins., firmly set in scattered mound of stone, mkd. with 5 notches on the E. and 1 notch on the W. faces.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, collar of stone to top, brass cap mkd.

T22S R9E	
S31	S32
S 6	S 5
T23S	
1960	

from which

A mesquite, 7 ins. diam., bears S. 5° E., 157 lks. dist., mkd. BT.

A mesquite, 5 ins. diam., bears S. 81° E., 74 lks. dist., mkd. BT.

A mesquite, 6 ins. diam., bears N. $7\frac{1}{2}^{\circ}$ W., 145 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. Iron post is 6 lks. W. and 6 lks. S. of a steel fence post set in concrete from which fences bear S. and W.

The cor. of secs. 29, 30, 31 and 32 is monumented with a granite stone, 16 x 10 x 8 ins., firmly set in a loose mound of stone, mkd. with 5 notches on the E. and 1 notch on the S. faces.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone to top, brass cap mkd.

T22S R9E	
S30	S29
S31	S32
1960	

Bury the original cornerstone alongside the iron post. Iron post is on an old N. and S. fence line and on a small spur.

The $\frac{1}{4}$ cor. of secs. 29 and 30 is monumented with a granite stone, 14 x 8 x 5 ins., firmly set with a mound of stone to W., mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., .20 ins. in the ground, collar of stone, brass cap mkd.

Chains

T22S R9E

S30	S29
1960	

from which

A mesquite, 5 ins. diam., bears N. $53\frac{1}{2}^{\circ}$ W., 109 lks. dist., mkd. BT.

A mesquite, 4 ins. diam., bears S. 13° W., 137 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post,

The cor. of secs. 19, 20, 29 and 30 is monumented with a granite stone, 18 x 12 x 8 ins., firmly set at an old fence cor. with fence lines S. and W., mkd. with 2 notches on S. face. Could not see any notches on the E. face.

from which

A mesquite, 14 ins. diam., bears N. $47-3/4^{\circ}$ W., 292 lks. dist., mkd. with a blaze and faint scribe marks.

A mesquite, 16 ins. diam., bears N. $11\frac{1}{2}^{\circ}$ E., 136 lks. dist., mkd. with a grown-over blaze.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T22S R9E	
S19	S20
S30	S29
1960	

from which

A mesquite, 7 ins. diam., bears S. 67° W., 116 lks. dist., mkd. BT.

A mesquite, 7 ins. diam., bears S. $2-3/4^{\circ}$ E., 195 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post.

The $\frac{1}{4}$ cor. of secs. 19 and 20 is monumented with a granite stone, 12 x 8 x 8 ins., in concrete around a steel fence post, mkd. $\frac{1}{4}$ on W. face

from which

A dead mesquite, 16 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ W., 192 lks. dist., mkd. with a blaze and scribe marks $\frac{1}{4}$ S BT.

A steel fence post, 4 ins. diam., filled with concrete and set in concrete, bears 1 lk. E. and $1\frac{1}{2}$ lks. N., from which fences bear N., S., and W.

Could not set an iron post due to heavy concrete.

Chains

The cor. of secs. 17, 18, 19 and 20 is monumented with a granite stone, 18 x 8 x 6 ins., firmly set with a mound of stone to W., mkd. with 5 notches on the E. and 3 notches on the S. faces.

At the cor point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, collar of stone, brass cap mkd.

T22S R9E	
S18	S17
S19	S20
1960	

from which

A mesquite, 8 ins. diam., bears S. 22° W., 57 lks. dist., mkd. BT.

A mesquite, 5 ins. diam., bears S. $29\text{-}3/4^{\circ}$ E., 47 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. Iron post is $1\frac{1}{2}$ lks. W. of a N. and S. fence.

The $\frac{1}{4}$ cor. of secs. 20 and 29 is monumented with a granite stone, 16 x 12 x 10 ins., firmly set, mkd. $\frac{1}{4}$ on N. face

from which

A partly dead mesquite, 16 ins. diam., bears N. $43\frac{1}{2}^{\circ}$ E., 42 lks. dist., mkd. with a blaze and scribe marks $\frac{1}{4}$ S20 BT.

A partly dead mesquite, 30 ins. diam., bears S. 67° E., 129 lks. dist., mkd. with a blaze and scribe marks $\frac{1}{4}$ S29 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, collar of stone, brass cap mkd.

T22S R9E	
$\frac{1}{4}$ S20	
$\frac{1}{4}$ S29	
1960	

from which

A mesquite, 8 ins. diam., bears N. 71° E., 26 lks. dist., mkd. BT.

A mesquite, 16 ins. diam., bears S. 30° W., $52\frac{1}{2}$ lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post.

The cor. of secs. 20, 21, 28 and 29 is monumented with a granite stone, 20 x 10 x 8 ins., firmly set, mkd. with 4 notches on the E. and 2 notches on the S. faces.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, collar of stone to top, brass cap mkd.

Chains

T22S R9E	
S20	S21
S29	S28
1960	

from which

A mesquite, 6 ins. diam., bears N. 76° W., 10 lks. dist., mkd. BT.

A mesquite, 6 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ E., 38 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post.

The cor. of secs. 16, 17, 20 and 21 is monumented with a granite stone, 20 x 10 x 8 ins., firmly set, mkd. with 4 notches on the E. and 3 notches on the S. faces

from which

A mesquite, 14 ins. diam., bears N. $16\frac{1}{2}^{\circ}$ W., 26 lks. dist., mkd. T22S R9E S17 BT.

A mesquite, 12 ins. diam., bears N. $81-3/4^{\circ}$ E., 125 lks. dist., mkd. T22S R9E S16 BT.

A dead mesquite, 16 ins. diam., bears S. 80° W., 136 lks. dist., mkd. with a blaze and dim scribe marks.

A mesquite, 12 ins. diam., bears S. $78\frac{1}{2}^{\circ}$ E., 114 lks. dist., mkd. T 22 S R9E S21 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, collar of stone, brass cap mkd.

T22S R9E	
S17	S16
S20	S21
1960	

from which

A mesquite, 7 ins. diam., bears S. 24° E., $146\frac{1}{2}$ lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. Iron post is $\frac{1}{4}$ lks. W. of a small hillside drain, course S.

The $\frac{1}{4}$ cor. of secs. 17 and 20 is monumented with a granite stone, $14 \times 8 \times 4$ ins., firmly set, mkd. $\frac{1}{4}$ on N. face

from which

A dead mesquite, 18 ins. diam., bears S. $20-3/4^{\circ}$ W., 90 lks. dist. mkd. with an open and rotted blaze.

A mesquite, 12 ins. diam., bears N. $57-3/4^{\circ}$ E., 157 lks. dist., mkd. with a blaze and faint scribe marks.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, collar of stone to top, brass cap mkd.

T22S R9E	
$\frac{1}{4}$ S17	
S20	
1960	

Township 22 South, Range 9 East, Arizona

5

Chains

from which

A mesquite, 7 ins. diam., bears S. $21-3/4^{\circ}$ E., 59 lks. dist., mkd.
BT.

A mesquite, 6 ins. diam., bears S. $68\frac{1}{2}^{\circ}$ E., 88 lks. dist., mkd.
BT.

Bury the original cornerstone alongside the iron post.

The $\frac{1}{4}$ cor. of secs. 17 and 18 is monumented with a granite stone,
16 x 12 x 10 ins., firmly set, mkd. $\frac{1}{4}$ on the W. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground,
collar of stone, brass cap mkd.

T22S R9E

$\frac{1}{4}$	S18	S17
1960		

from which

A mesquite, 14 ins. diam., bears S. 24° E., 36 lks. dist., mkd.
BT.

A mesquite, 8 ins. diam., bears S. $88-3/4^{\circ}$ W., 78 lks. dist., mkd.
BT.

Bury the original cornerstone alongside the iron post. Iron post is
under a N. and S. fence and on a gentle N.E. slope.

The cor. of secs. 7, 8, 17 and 18 is monumented with a granite stone,
14 x 7 x 7 ins., firmly set, mkd. with 4 notches on S. face (E. side
has flaked off)

from which

A mesquite, 16 ins. diam., bears N. 81° E., 345 lks. dist., mkd.
T22S R9E S8BT.

A mesquite, 18 ins. diam., bears S. $38\frac{1}{2}^{\circ}$ W., 281 lks. dist., mkd.
T22S R9E S18BT.

A dead and fallen mesquite, 8 ins. diam., bears S. 53° E., 132 lks.
dist., mkd. with a blaze.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground,
collar of stone to top, brass cap mkd.

T22S R9E

S 7	S 8
S18	S17
1960	

from which

Chains

A mesquite, 6 ins. diam., bears S. $41\frac{1}{2}^\circ$ W., $108\frac{1}{2}$ lks. dist., mkd. BT.

A mesquite, 5 ins. diam., bears S. 22° E., $129\frac{1}{2}$ lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. Iron post is $1\frac{1}{2}$ lks. S. and $\frac{1}{2}$ lk. E. of a fence post from which fences bear N., S., and W.

The W.C. for the $\frac{1}{4}$ cor. of secs. 7 and 8 is monumented with a granite stone, firmly set, mkd. WC $\frac{1}{4}$ on W. face

from which

A mesquite, 8 ins. diam., bears S. $44\frac{1}{2}^\circ$ E., 280 lks. dist., mkd. WC $\frac{1}{4}$ S8 BT.

A mesquite, 16 ins. diam., bears S. $7-3/4^\circ$ W., 205 lks. dist., mkd. WC $\frac{1}{4}$ S7 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, collar of stone, brass cap mkd.

WC
T22S R9E
 $\frac{1}{4}$
S7 | S8
1960

from which

A mesquite, 8 ins. diam., bears N. 54° W., 106 lks. dist., mkd. WC BT.

A mesquite, 5 ins. diam., bears S. 78° E., $142\frac{1}{2}$ lks. dist., mkd. WC BT.

Bury the original cornerstone alongside the iron post. The iron post is under a N. and S. fence.

The cor. of secs. 5, 6, 7 and 8 is monumented with a granite stone, 12 x 8 x 8 ins., firmly set with a scattered mound of stone to W., mkd. with 5 notches on the E. and S. faces

from which

A mesquite, 14 ins. diam., bears S. 31° E., 183 lks. dist., mkd. T22S R9E S8 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, collar of stone, brass cap mkd.

T22S R9E
S 6 | S 5
S 7 | S 8
1960

Chains

from which

A mesquite, 7 ins. diam., bears N. 87° W., 279 lks. dist., mkd. BT.

A mesquite, 14 ins. diam., bears S. 31° E., 183 lks. dist., mkd. BT (Orig. B.T.).

Bury the original cornerstone alongside the iron post. Iron post is $2\frac{1}{2}$ lks. W. of a N. and S. fence and on a gentle S.W. slope.

The cor. of secs. 33 and 34 on the N. bdy. of the Tp. is monumented with a granite stone, 18 x 12 x 8 ins., loosely set, mkd. with 3 notches on the E. and W. faces.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, collar of stone, brass cap mkd.

T21S R9E
S33 | S34
S 4
T22S
1960

from which

A mesquite, 8 ins. diam., bears N. 27 $\frac{1}{2}$ ° W., 49 lks. dist., mkd. BT.

A mesquite, 8 ins. diam., bears N. 70- $\frac{3}{4}$ ° E., 92 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. Iron post is on a gentle W. slope at an old fence cor. from which fence lines bear N. and E.

The cor. of secs. 34 and 35 on the N. bdy. of the Tp. is monumented with a granite stone, 18 x 12 x 10 ins., firmly set, mkd. with 2 notches on the E. and 4 notches on the W. faces.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, collar of stone, brass cap mkd.

T21S R9E
S34 | S35
S 3
1960

from which

A mesquite, 5 ins. diam., bears N. 32 $\frac{1}{4}$ ° E., 57 lks. dist., mkd. BT.

A mesquite, 6 ins. diam., bears N. 72 $\frac{1}{2}$ ° W., 69 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. Iron post is on an old E. and W. fence line.

The S. $\frac{1}{4}$ cor. of sec. 35 on the N. bdy. of the Tp. is monumented with a granite stone, 16 x 10 x 6 ins., firmly set with mound of stone to N., mkd. $\frac{1}{4}$ on N. face.

BOOK 4604

Township 22 South, Range 9 East, Arizona

8

Chains

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, collar of stone to top, brass cap mkd.

T21S R9E

 $\frac{1}{4}$ S35

T22S

1960

from which

A mesquite, 5 ins. diam., bears N. $45\frac{1}{2}^{\circ}$ W., 34 lks. dist., mkd. BT.

A mesquite, 6 ins. diam., bears N. $43\text{-}3/4^{\circ}$ E., 62 lks. dist., mkd. BT.

Bury the original cornerstone in collar of stone around iron post.

The $\frac{1}{4}$ cor. of secs. 24 and 25 is monumented with a granite stone 14 x 12 x 6 ins., firmly set with a mound of stone to N., mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, collar of stone, brass cap mkd.

T22S R9E

 $\frac{1}{4}$ S24 $\frac{1}{4}$ S25

1960

from which

A mesquite, 10 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ E., 77 lks. dist., mkd. BT.

A mesquite, 10 ins. diam., bears N. $40\frac{1}{2}^{\circ}$ W., 165 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. Iron post is 49 lks. N. of a fence and about 2.50 chs. S. of a road, in flat land.

The $\frac{1}{4}$ cor. of secs. 23 and 26 is monumented with a granite stone, 12 x 10 x 8 ins., firmly set with a mound of stone to N., mkd. $\frac{1}{4}$ on N. face.

from which

An oak stump, 18 ins. diam., bears N. 50° W., 45 lks. dist., mkd. with an old blaze.

A dead oak, 14 ins. diam., bears N. 36° E., 96 lks. dist., mkd. with an old blaze.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, collar of stone to top, brass cap mkd.

T22S R9E

 $\frac{1}{4}$ S23 $\frac{1}{4}$ S26

1960

Chains

from which

A mesquite, 8 ins. diam., bears S. $85\frac{1}{2}^{\circ}$ W., 64 lks. dist., mkd. BT.

A mesquite, 12 ins. diam., bears N. 48° W., 20 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post. Iron post is on a steep N. slope.

The cor. of secs. 22, 23, 26 and 27 is monumented with a sandstone, $14 \times 7 \times 5$ ins., firmly set with a mound of stone to W., mkd. with 2 notches on the E. and S. faces

from which

A partly dead mesquite, 18 ins. diam., bears S. 70° E., 66 lks. dist., mkd. T22S R9E S26 BT.

A dead mesquite, 16 ins. diam., bears N. $7\frac{1}{2}^{\circ}$ W., 226 lks. dist., has rotted out blaze.

A dead mesquite, 10 ins. diam., bears N. 67° E., 298 lks. dist., mkd. with a blaze and dim scribe marks.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, collar of stone, brass cap mkd.

T22S R9E	
S22	S23
S27	S26
1960	

from which

A mesquite, 5 ins. diam., bears S. $39\frac{1}{2}^{\circ}$ W., 69 lks. dist., mkd. BT.

A mesquite, 4 ins. diam., bears N. 15° E., $91\frac{1}{2}$ lks. dist., mkd. BT.

A mesquite, 8 ins. diam., bears N. 43° W., 221 lks. dist., mkd. BT.

Bury the original cornerstone alongside the iron post.

The $\frac{1}{4}$ cor. of secs. 26 and 27 is monumented with a volcanic granite stone, $24 \times 12 \times 5$ ins., firmly set with a mound of stone to the W., mkd. $\frac{1}{4}$ on the W. face

from which

A dead mesquite, 14 ins. diam., bears S. $64\frac{1}{4}^{\circ}$ E., 197 lks. dist., mkd. with a blaze and parts of scribe marks.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, collar of stone to top, brass cap mkd.

10

Chains

T22S R9E
 $\frac{1}{4}$
 S27 | S26
 1960

from which

A mesquite, 6 ins. diam., bears N. 63° E., 80 lks. dist., mkd. ET.
 Bury the original cornerstone in collar of stone around the iron post.
 Iron post is on an E. slope.

The cor. of secs. 26, 27, 34 and 35 is monumented with a granite stone 20 x 12 x 4 ins., loosely set with a scattered mound of stone to the N.E., mkd. with 2 notches on the E. and 1 notch on the S. faces.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, collar of stone, brass cap mkd.

T22S R9E
 S27 | S26
 S34 | S35
 1960

from which

A mesquite, 12 ins. diam., bears N. 11 $\frac{1}{2}$ ° W., 21 lks. dist., mkd. ET.

A mesquite, 5 ins. diam., bears N. 73° E., 82 lks. dist., mkd. ET.

A mesquite, 8 ins. diam., bears S. 55° E., 104 lks. dist., mkd. ET.

Bury the original cornerstone alongside the iron post. Iron post is on W. bank of a small drain, course S., and W. of a corral with a windmill and steel water tank to the E. and N.E.

CERTIFICATE OF CADASTRAL ENGINEER

I, Lester S. Mann, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of March, 1960, I have ~~surveyed~~ remonumented the cadastral survey corners in T. 22 S., R. 9 E., in cooperation with the U. S. Forest Service

of the G&SR Meridian, in the State of Arizona; which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Phoenix, Arizona
June 21, 1960

Lester S. Mann
Lester S. Mann
Office Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., SEP 5 1961, 19

The foregoing field notes of the ~~survey of~~ remonumented cadastral survey corners in Township 22 South, Range 9 East, Gila and Salt River Meridian, Arizona,

executed by Lester S. Mann, Office Cadastral Engineer having been critically examined and found correct, are hereby approved.

[Signature]
Cadastral Engineering Staff Officer
Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in _____, is a true copy of the original field notes.~~

Cadastral Engineering Staff Officer