

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

EAST BOUNDARY

AND THE

SURVEY OF THE SUBDIVISION

OF

TOWNSHIP 5 NORTH, RANGE 9 WEST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Robert C. Yundt - Cadastral Surveyor (Chief of Party)

Donald A. Cannon - Cadastral Surveyor

Under special instructions dated September 5, 1958, *which provided*

for the surveys included under Group No. 327, *approved* September 10, 1958

and assignment instructions dated December 1, 1958
January 14, 1959

Survey commenced December 17, 1958

Survey completed January 27, 1959

1A

BOOK 4605

INDEX DIAGRAM

Township 5 North, Range 9 West

•	44 5	35 4	28 3	22 2	15 1 6
44	43	35	28	21	14
7	43 8	34 9	27 10	21 11	13 12 5
42	42	34	27	20	13
18	41 17	33 16	26 15	20 14	12 13 4
40	40	32	26	19	11
19	39 20	32 21	25 22	18 23	10 24 3
39	38	31	25	18	9
30	37 29	30 28	24 27	17 26	8 25 2
37	36	30	23	16	7
31	36 32	29 33	23 34	15 35	7 36 1

Township 5 North, Range 9 West

Chains

The south boundary of the township, or the First Standard Parallel North, was originally surveyed by J. F. Hesse in 1909. An independent resurvey by D. R. Averill in 1931 was superseded by an independent resurvey by G. M. Litz in 1942. The east boundary was surveyed by A. N. Oliver in 1911. The west boundary was surveyed by D. R. Averill in 1931 and an independent resurvey was executed by G. M. Litz in 1942. The north boundary was surveyed by D. R. Averill in 1931.

The following field notes are those of a dependent resurvey of the east boundary and the survey of the subdivision in T. 5 N., R. 9 W.

The survey was executed with W. & L. E. Gurley solar transit No. 541331, conforming to the standard specifications of the Bureau of Land Management. The instrument was maintained in good adjustment throughout the survey.

The direction of all lines of the survey was determined from meridians established by observations upon the sun and Polaris throughout the survey.

Corners on the east-west lines were set on the true latitudinal curve. Lines connecting previously established corners, were run by the random and true line method, but for simplification of the record the random lines are omitted from these field notes.

Measurements were made with a narrow steel tape, 8 chains in length, graduated every link for the first chain, and thereafter at intervals of ten links. The tape was tested by comparison with a standard steel tape, one chain in length, and found to be correct. All measurements were made on the slope and the vertical angle of each interval determined by use of a clinometer in good adjustment; the horizontal equivalents only are entered in the field note record. The lengths of all lines in this survey were determined by chaining.

The geographic position for the southeast corner of this township is: Latitude $33^{\circ} 43' 32''$ N., Longitude $113^{\circ} 08' 15''$ W., as determined by taking an average of all known geographic positions in the vicinity.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be: $14^{\circ} 30'$ E.

Dependent Resurvey of the East Boundary of T. 5 N.; R. 9 W.

Reestablishment of survey executed by A. N. Oliver in 1911. Beginning at the standard cor. of Tps. 5 N., Rs. 8 and 9 W.; which is monumented with an iron post, 3 ins. diam., set, marked, and witnessed as described in the official record.

N. $0^{\circ} 18'$ E., along the E. bdy. of sec. 36.

Over rolling, hilly, land which drains westerly, through scattered to medium undergrowth; asc. 20 ft.

22.00 Spur, slopes W.; desc. along rolling W. slope.

41.60 Wash, 40 lks. wide, 20 ft. deep, drains W.; asc. 5 ft. on S. slope.

43.09 The original $\frac{1}{4}$ sec. cor. of secs. 31 and 36 is monumented by an iron post, 36 ins. long, 1 in. diam., set 10 ins. in the ground and in a mound of stone, 3 ft. base, to top, 36 ins. long, 1 in. diam., and 10 ins. in the ground and in a mound of stone, 3 ft. base, to top.

Dependent Resurvey of the E. Bdy. of T. 5 N., R. 9 W.

Chains	Remarks												
	<p>I remark the brass cap to read for $\frac{1}{4}$ sec. cor. of sec. 36 only:</p> <div style="text-align: center;"> <table border="0"> <tr><td>T5N</td><td> </td></tr> <tr><td>$\frac{1}{4}$S36</td><td> </td></tr> <tr><td>R9W</td><td> </td></tr> <tr><td>1958</td><td> </td></tr> <tr><td>1959</td><td> </td></tr> </table> </div>	T5N		$\frac{1}{4}$ S36		R9W		1958		1959			
T5N													
$\frac{1}{4}$ S36													
R9W													
1958													
1959													
	N. 0°03' W., beginning new measurement.												
	Asc. 70 ft. over SW. slope.												
11.00	Spur, slopes W.; desc. 90 ft. along W. slope.												
31.70	Wash 30 lks. wide, 5 ft. deep, drains S. 60° W.; asc. 10 ft. over SE. slope.												
36.93	The closing cor. for secs. 30 and 31, T. 5 N., R. 8 W., which is monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.												
40.11	The original cor. of secs. 25, 30, 31, and 36.												
	Which is monumented with an iron post, 36 ins. long, 3 ins. diam., 24 ins. in the ground.												
	I remark the brass cap to function for the cor. of secs. 25 and 36 only:												
	<div style="text-align: center;"> <table border="0"> <tr><td>T5N</td><td> </td></tr> <tr><td>S25</td><td> </td></tr> <tr><td>S36</td><td> </td></tr> <tr><td>R9W</td><td> </td></tr> <tr><td>1958</td><td> </td></tr> <tr><td>1911</td><td> </td></tr> </table> </div>	T5N		S25		S36		R9W		1958		1911	
T5N													
S25													
S36													
R9W													
1958													
1911													
	Land, rolling hills.												
	Soil, sand and rocky shale.												
	Timber, none.												
	Undergrowth, greasewood, paloverde, ocotillo, catclaw, and saguaro cactus.												
	N. 0°07' E., along the E. bdy. of sec. 25.												
	Over rolling land, through medium undergrowth, desc. 10 ft.												
8.30	Wash, 20 lks. wide, 3 ft. deep, drains N. 70° W.; asc. 130 ft. over SW. slope.												
27.00	Spur, projects N. 70° W.; desc. 10 ft. over N. slope.												
39.93	The original $\frac{1}{4}$ cor. for secs. 25 and 30, which is monumented by an iron post, 36 ins. long, 3 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top:												
	I remark the brass cap to function for sec. 25 only:												
	<div style="text-align: center;"> <table border="0"> <tr><td>T5N</td><td> </td></tr> <tr><td>$\frac{1}{4}$S25</td><td> </td></tr> <tr><td>R9W</td><td> </td></tr> <tr><td>1958</td><td> </td></tr> <tr><td>1911</td><td> </td></tr> </table> </div>	T5N		$\frac{1}{4}$ S25		R9W		1958		1911			
T5N													
$\frac{1}{4}$ S25													
R9W													
1958													
1911													

Dependent Resurvey of the E. bdy. of T. 5 N., R. 9 W.

Chains

- N. 0°05' E., beginning new measurement.
- 3.00 Top of ascent on knoll, slopes NW.; desc. 200 ft. over rolling N. slope.
- 37.11 The closing cor. for secs. 19 and 30, which is monumented by an iron post, 2 ins. diam., set, marked and witnessed as described in the official record.
- 39.97 The original cor. of secs. 19, 24, 25, and 30, which is monumented by an iron post, 36 ins. long, 3 ins. diam., 24 ins. in the ground, and a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

I remark the brass cap to function for the cor. of secs. 24 and 25 only:

T5N
S24
S25
R9W
1958
1911

Land, rolling hills.

Soil, rocky.

Timber, none.

Undergrowth, greasewood, paloverde, ocotillo, catclaw, and saguaro cactus.

- N. 0°04' E., along the E. bdy. of sec. 24.
- Over rolling land, through medium undergrowth, desc. 40 ft. over rolling N. slope.
- 7.40 Wash, 4 chs. wide, 10 ft. deep, drains NW.; asc. 30 ft. over SW. slope.
- 16.10 Spur, slopes NW.; desc. 90 ft. over NW. slope.
- 21.40 Track road, bears N. 60° W. and S. 80° E.
- 29.40 Wash, 20 lks. wide, 10 ft. deep, drains NW.; asc. 10 ft. over series of low spurs and minor drains putting irregularly NW.
- 40.09 The original ¼ cor. of secs. 19 and 24, which is monumented by an iron post, 36 ins. long, 1 in. diam., 26 ins. in the ground, with a mound of stone, 2 ft. base, 1½ ft. high W. of cor.
- I remark the cor. to function for the ¼ sec. cor. of sec. 24 only:

T5N
¼S24
R9W
1958
1911

N. 0°05' E., beginning new measurement.

Asc. 10 ft. over SW. slope.

- 5.40 Spur, slopes N. 30° W.; desc. 80 ft. over rolling N. slope.

Dependent Resurvey of the E. bdy. of T. 5 N., R. 9 W.

Chains							
17.80	Wash, 30 lks. wide, 10 ft. deep, drains N. 30° W.; asc. 30 ft. over SE. slope.						
37.09	The closing cor. for secs. 18 and 19, T. 5 N., R. 8 W., which is monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record. Asc. 5 ft.						
38.00	Spur, projects NW.; desc. 10 ft. over NW. slope.						
40.02	The original cor. of secs. 13, 18, 19, and 24, which is monumented by an iron post, 36 ins. long, 3 ins. diam., 26 ins. in the ground. I remark the cor. to function for the cor. of secs. 13 and 24 only: <div style="text-align: center;"> <table border="0"> <tr><td>T5N</td></tr> <tr><td>S13</td></tr> <tr><td><u>S24</u></td></tr> <tr><td>R9W</td></tr> <tr><td>1958</td></tr> <tr><td>1911</td></tr> </table> </div> Land, rolling hills. Soil, shallow gravel. Timber, none. Undergrowth; greasewood, paloverde, ocotillo, catclaw, and saguaro cactus.	T5N	S13	<u>S24</u>	R9W	1958	1911
T5N							
S13							
<u>S24</u>							
R9W							
1958							
1911							
	N. 0°04' E., along the E. bdy. of sec. 13.						
	Over rolling land, through scattered undergrowth, desc. 100 ft. over N. slope.						
13.00	Wash, 20 lks. wide, 1 ft. deep, drains N. 30° W.; asc. 20 ft. over SE. slope.						
24.20	Spur, slopes N. 70° W.; desc. 20 ft. over N. slope.						
31.60	Road, improved gravel, bears N. 70° W. and S. 70° E.						
37.40	Wash, 50 lks. wide, 4 ft. deep, drains N. 70° W.; asc. 60 ft. over S. slope.						
40.04	The original $\frac{1}{4}$ cor. of secs. 13 and 18, which is monumented by an iron post, 36 ins. long, 1 in. diam., 22 ins. in the ground, with a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor. I remark the brass cap to function for the $\frac{1}{4}$ sec. cor. of sec. 13 only: <div style="text-align: center;"> <table border="0"> <tr><td>T5N</td></tr> <tr><td>$\frac{1}{4}$S13</td></tr> <tr><td>R9W</td></tr> <tr><td>1958</td></tr> <tr><td>1911</td></tr> </table> </div> N. 0°07' E., beginning new measurement.	T5N	$\frac{1}{4}$ S13	R9W	1958	1911	
T5N							
$\frac{1}{4}$ S13							
R9W							
1958							
1911							
1.50	Ridge, bears N. 70° W. and S. 70° E. Desc. 110 ft. over series of low spurs and minor drains putting NW.						

Dependent Resurvey of the East Boundary of T. 5 N., R. 9 W.

Chains							
36.94	The closing cor. for the secs. 7 and 18, T. 5 N., R. 8 W., which is monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.						
40.00	The original cor. of secs. 7, 12, 13, and 18, which is monumented by an iron post, 36 ins. long, 3 ins. diam., set 24 ins. in the ground.						
	I remark the brass cap to function for the cor. of secs. 12 and 13 only:						
	<table border="0"> <tr><td>T5N</td></tr> <tr><td>S12</td></tr> <tr><td>S13</td></tr> <tr><td>R9W</td></tr> <tr><td>1958</td></tr> <tr><td>1911</td></tr> </table>	T5N	S12	S13	R9W	1958	1911
T5N							
S12							
S13							
R9W							
1958							
1911							
	<p>Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, greasewood, paloverde, ocotillo, catclaw, and saguaro cactus.</p>						
	N. 0°10' E., along the E. bdy. sec. 12.						
	Over rolling land, through medium undergrowth, desc. 20 ft. over NW. slope.						
3.60	Wash, 10 lks. wide, 1 ft. deep, drains W.; asc. 30 ft. over SW. slope.						
14.10	Low spur, slopes NW.; desc. 130 ft. over NW. slope.						
40.07	The original $\frac{1}{4}$ sec. cor. of secs. 7 and 12, which is monumented by an iron post, 36 ins. long, 1 in. diam., 26 ins. in the ground with a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.						
	I remark the brass cap to function for the $\frac{1}{4}$ sec. cor. of sec. 12 only:						
	<table border="0"> <tr><td>T5N</td></tr> <tr><td>$\frac{1}{4}$S12</td></tr> <tr><td>R9W</td></tr> <tr><td>1958</td></tr> <tr><td>1911</td></tr> </table>	T5N	$\frac{1}{4}$ S12	R9W	1958	1911	
T5N							
$\frac{1}{4}$ S12							
R9W							
1958							
1911							
	N. 0°04' E., beginning new measurement.						
	Desc. 70 ft. over NW. slope.						
15.10	Wash, 8 lks. wide, 2 ft. deep, drains N. 70° W.						
18.10	Wash, 10 lks. wide, 3 ft. deep, drains N. 80° W.						
20.80	Wash, 5 lks. wide, 2 ft. deep, drains S. 70° W.; asc. 30 ft. over SW. slope.						
36.80	The closing cor. for secs. 6 and 7, T. 5 N., R. 8 W., which is monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.						
40.08	The original cor. of secs. 1, 6, 7, and 12, which is monumented by an iron post, 36 ins. long, 3 ins. diam., set 25 ins. in the ground with mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.						

Dependent Resurvey of the East Boundary of T. 5 N., R. 9 W.

Chains

I remark the brass cap to function for the cor. of secs. 1 and 12 only:

T5N

S1

S12

R9W

1958

1911

Land, rolling.

Soil, rocky.

Timber, none.

Undergrowth, greasewood, paloverde, ocotillo, catclaw, and saguaro cactus.

N. 0°04' E., along the E. bdy. of sec. 1.

Over rolling land, through medium undergrowth, desc. 140 ft. over NE slope.

40.06

The original $\frac{1}{4}$ sec. cor. of secs. 1 and 6, which is monumented by an iron post, 36 ins. long, 1 ins. diam., set 26 ins. in the ground.

I remark the brass cap to function for the $\frac{1}{4}$ sec. cor. of sec. 1 only:

T5N

S1

R9W

1958

1911.

Desc. 80 ft. over NW slope.

65.00

Wash, 30 lks. wide, 4 ft. deep, drains W.; asc. 10 ft. over S. slope.

76.87

The closing cor. of Tps. 5 and 6 N., R. 8 W., which is monumented by an iron post, 3 ins. diam., set, marked, and witnessed as described in the official records.

80.12

The cor. of Tps. 5 and 6 N., R. 9 W., which is monumented by an iron post, 36 ins. long, 3 ins. diam., set 22 ins. in the ground and in a mound of stone, 2 ft. base, to top.

I remark the brass cap to function for R. 9 W. only:

T6N

R9W

S36

S 1

T5N

1958

1911

Land, gently rolling.

Soil, rocky clay.

Timber, none.

Undergrowth, greasewood, paloverde, ocotillo, catclaw, and saguaro cactus.

The Survey of the Subdivisional lines in T. 5 N., R. 9 W.

Beginning at the standard cor. of secs. 35 and 36, on the S. bdy. of the T.

The Survey of the Subdivision Lines in T. 5 N., R. 9 W.

Chains

N. $0^{\circ}05'$ E., along the W. bdy. of sec. 36.

Over rolling hills, through medium undergrowth.

13.40 Wash, 1 chs. wide, 4 ft. deep, drains W.; asc. 90 ft. over rolling SW. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 35.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N
 $\frac{1}{4}$ S35
 R9W
 1958

Asc. 10 ft. over S. slope.

43.14 Point for the $\frac{1}{4}$ sec. cor. of sec. 36.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N
 $\frac{1}{4}$ S36
 R9W
 1958

Asc. 160 ft. over S. slope.

67.00 Spur, slopes N. 70° E.; asc. along E. slope.

80.00 Point for the cor. of secs. 26 and 35.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap marked.

T5N
 S26
 S35
 R9W
 1958

Asc. 10 ft. along E. slope.

83.14 Point for the cor. of secs. 25 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N
 S25
 S36
 R9W
 1958

Land, rolling hills.

Soil, rocky.

Timber, none.

Undergrowth, cholla and saguaro cactus, greasewood, paloverde, cat-claw, ocotillo, and rubber plant.

From the cor. of secs. 25 and 36, on the E. bdy. of the T.

N. $89^{\circ}53'$ W., bet. secs. 25 and 36.

The Survey of the Subdivisional lines in T. 5 N., R. 9 W.

Chains	
	Through medium undergrowth, asc. 20 ft. along S. slope.
4.00	Spur, slopes S. 20° W.; desc. 30 ft. along S. slope.
9.50	Wash, 1 ch. wide, 3 ft. deep, drains NW.; asc. 20 ft. over NE. slope.
13.90	Spur, slopes N. about 3 chs. to end; desc. 40 ft. over NW. slope.
18.40	Same wash, drains S. 60° W.; desc. 10 ft. over rolling S. slope.
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap marked. T5N R9W $\frac{1}{4}$ S25 $\frac{1}{4}$ S36 1958 Asc. 110 ft. along rolling S. slope.
69.40	Spur, slopes N. 20° E.; desc. 110 ft. over NW. slope.
74.80	Wash, 5 lks. wide, 3 ins. deep, drains N.; asc. 50 ft. over E. slope.
80.10	Point for the cor. of secs. 25 and 36. Land, rolling. Soil, rocky clay. Timber, none. Undergrowth, cholla and saguaro cactus, greasewood, paloverde; cat-claw, ocotillo, and rubberplant.
	N. 0°05' E., along the W. bdy. of sec. 25. Through medium undergrowth; along E. slope.
.50	Spur, slopes N. 30° E.; desc. 80 ft. over NE. slope.
19.80	Wash, 20 lks. wide, 3 ft. deep, drains N. 60° W.; asc. 10 ft. over SW. slope.
26.40	Track road, bears N. 50° E. and S. 40° W.; asc. 10 ft. over SW. slope.
36.86	Point for the $\frac{1}{4}$ sec. cor. of sec. 26. Set an iron post, 30 ins. long, 2½ ins. diam., 5 ins. in the ground, and in a mound of stone, 3½ ft. base, to top, with brass cap marked. T5N $\frac{1}{4}$ S26 R9W 1958 Asc. 10 ft. over SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of sec. 25. Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap marked. T5N $\frac{1}{4}$ S25 R9W 1958

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

Desc. 20 ft. over NW. slope.

41.00 Wash, 10 lks. wide, 6 ins. deep, drains W. asc. SW. slope.

53.10 Spur, slopes S. 70° W.; desc. 50 ft. over NW. slope.

58.40 Wash, 10 lks. wide, 1 ft. deep, drains S. 70° W.; asc. S. slope.

72.80 Ridge, bears N. 70° E. and W.; desc. 60 ft. over N. slope.

76.86 Point for the cor. of secs. 23 and 26.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W
S23 | S25
S26 |
1958

Desc. 20 ft. over N. slope.

80.00 Point for the cor. of secs. 24 and 25.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked.

T5N R9W
S23 | S24
S25 |
1958

Land, rolling hills.

Soil, rocky clay.

Timber, none.

Undergrowth, cholla and saguaro cactus, greasewood, paloverde, cat-claw, ocotillo, and rubberplant.

From the cor. of secs. 24 and 25, on the E. bdy. of the T.

N. 89°52' W., bet. secs. 24 and 25.

Over rolling land, through medium undergrowth, asc. 40 ft. along N. slope.

3.40 Wash, 10 lks. wide, 1 ft. deep, drains N. 70° W.

6.90 Low spur, slopes N. 8 chs. to end.

10.10 Wash, 10 lks. wide, 6 ins. deep, drains N. 30° E.

20.20 Spur, slopes N.

26.80 Small wash, drains N. 30° W.

40.04 Point for the cor. of secs. 24 and 25.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W
¼ S24
S25
1958

The survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

Desc. 40 ft. over NW. slope.

43.90 Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.; asc. 90 ft. over series of low spurs and minor drains putting N.

70.80 Spur, slopes N.; desc. 30 ft. over W. slope.

76.70 Wash, 20 lks. wide, 2 ft. deep, drains N.; asc. 50 ft. over E. slope.

78.40 Spur, slopes N.; desc. 20 ft. over W. slope.

80.08 The cor. of secs. 24 and 25.

Land, rolling hills.

Soil, rocky clay and sand.

Timber, none.

Undergrowth, cholla and saguaro cactus, greasewood, paloverde, cat-claw, ocotillo, and rubberplant.

N. 0°05' E. along the W. bdy. of sec. 24.

Through medium undergrowth; desc. 90 ft. over series of spurs and washes putting NW.

36.86 Point for the 1/4 sec. cor. of sec. 23.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap marked.

T5N
1/4 S23
R9W
1958

Desc. 10 ft.

40.00 Point for the 1/4 sec. cor. of sec. 24.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N
1/4 S24
R9W
1958

Desc. 40 ft. over NW. slope.

52.50 Wash, 20 lks. wide, 1 ft. deep, drains N. 70° W.; asc. 20 ft.

57.60 Spur, slopes NW.; desc. 30 ft. over NE. slope.

64.50 Road, unimproved, bears NW. and SE.; over nearly level land.

76.36 Point selected for the witness cor. of secs. 14 and 23.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap marked.

W C
T5N, R9W
S14
S23 | S24
1958

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	
	Deposit glass at base of cor.
76.86	The point for the cor. of secs. 14 and 23, falls in wash, where cor. cannot be perpetuated.
77.50	Wash, 120 lks. wide, 5 ft. deep, drains N. 60° W.
80.00	Point for the cor. of secs. 13 and 24. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked.
	T5N R9W S13 S24 1958
	Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cactus, greasewood, paloverde, cat-claw, ocotillo, and rubberplant.
	From cor. of secs. 13 and 24, on the E. bdy. of the T. N. 89°56' W., bet. secs. 13 and 24. Over rolling land, through scattered to medium undergrowth; asc. 30 ft.
9.20	Spur, slopes NW; desc. 60 ft. over SW. slope.
11.60	Wash, 5 lks. wide, 1 ft. deep, drains N. 30° W.; asc. 30 ft. over NE. slope.
21.10	Spur, slopes N. 30° W.; desc. 60 ft. over SW. slope.
34.30	Wash, 10 lks. wide, 1 ft. deep, drains N. 30° W.; asc. 30 ft. over E. slope.
40.05	Point for the ¼ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked.
	T5N R9W ¼ S13 ¼ S24 1958
	Asc. 5 ft.
41.90	Spur, slopes N. 30° W.; desc. 40 ft. over SW. slope.
48.70	Wash, 10 lks. wide, 1 ft. deep, drains N. 30° W.; asc. 60 ft. over NE. slope.
56.90	Spur, slopes N. 30° W.; desc. 60 ft. over SW. slope.
73.00	Unimproved road, bears NW. and SE.; desc. 10 ft. over W. slope.
80.10	The cor. of secs. 13 and 24.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

Land, rolling.
Soil, rocky.
Timber, none.
Undergrowth, cholla and saguaro cactus, greasewood, paloverde, cat-claw, and ocotillo.

N. $0^{\circ}05'$ E., along the W. bdy. of sec. 13.

Over rolling land, through scattered to medium undergrowth; asc. 10 ft.

3.00 Unimproved road, bears N. 70° W., and S. 70° E.; desc. 30 ft. over NW slope.

31.00 Wash, 20 lks. wide, 2 ft. deep, drains N. 70° W.; continue over nearly level land.

36.86 Point for the $\frac{1}{4}$ sec. cor. of sec. 14.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked.

T5N
 $\frac{1}{4}$ S14
R9W
1958

Deposit glass at base of iron post.

Over nearly level land.

40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 13.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked.

T5N.
 $\frac{1}{4}$ S13
R9W
1958

Deposit glass at base of iron post.

Continue over nearly level land.

62.10 Wash, 20 lks. wide, 2 ft. deep, drains W.

74.20 Low spur, slopes N. 70° W.

76.86 Point for the cor. of secs. 11 and 14.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W
 $\frac{1}{4}$ S11 | S13
 $\frac{1}{4}$ S14
1958

80.00 Point for the cor. of secs. 12 and 13.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked.

T5N R9W
 $\frac{1}{4}$ S12
 $\frac{1}{4}$ S13
1958

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

Land, gently rolling.
Soil, sandy clay.
Timber, none.
Undergrowth, cholla and saguaro cactus, greasewood, paloverde, catclaw, ocotillo.

From the cor. of secs. 12 and 13 on the E. bdy. of the T.
S. 89°55' W., bet. secs. 12 and 13.

Over rolling land, through scattered to medium undergrowth; desc. 30 ft.

15.10 Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.; asc. 20 ft.

30.70 Low spur, slopes N. 30° W.; desc. 30 ft.

35.50 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° W.; asc. 5 ft.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked.

T5N R9W

$\frac{1}{4}$ S12

S13

1958

Raise collar of stone around iron post.

Asc. 10 ft. on NE. slope.

47.50 Spur, slopes NW.; desc. 80 ft. over W. slope.

73.20 Unimproved road, bears N. 70° W. and S. 70° E.; desc. 10 ft.

80.04 The cor. of secs. 12 and 13.

Land, rolling.
Soil, rocky.
Timber, none.
Undergrowth, cholla and saguaro cactus, greasewood, catclaw, paloverde, and ocotillo.

N. 0°05' E., on the W. bdy. of sec. 12.

Over rolling land, through medium undergrowth; desc. 20 ft.

4.00 Unimproved road, bears N. 70° W. and S. 70° E.; asc. 50 ft. over gentle SW. slope.

31.70 Spur, slopes NW.; desc. 10 ft. over NE. slope.

36.86 Point for the $\frac{1}{4}$ sec. cor. of sec. 11.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap marked.

T5N

$\frac{1}{4}$ S11

R9W

1958

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	
	Desc. 20 ft. over NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of sec. 12 <i>etc</i>
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.
	<div style="text-align: center;"> T5N $\frac{1}{4}$ S12 R9W 1958 </div>
	Desc. 30 ft. over NE. slope.
56.40	Wash, 20 lks. wide, 2 ft. deep, drains N. 70° W.; asc. 10 ft.
67.80	Low spur, slopes N. 70° W.; desc. 110 ft. over NW. slope.
76.86	Point for the cor. of secs. 2 and 11.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.
	<div style="text-align: center;"> T5N R9W S 2 S12 S11 1958 </div>
80.00	Point for the cor. of secs. 1 and 12.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap marked.
	<div style="text-align: center;"> T5N R9W S2 S 1 S12 1958 </div>
	Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cactus, greasewood, catclaw, palo verde, and ocotillo.
	From the cor. of secs. 1 and 12, on the E. bdy. of the T.
	S. $89^\circ 46'$ W., bet. secs. 1 and 12.
	Over rolling land, through scattered undergrowth; desc. 60 ft. over NW. slope.
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked.
	<div style="text-align: center;"> T5N R9W $\frac{1}{4}$ S 1 S12 1958 </div>
	Desc. 30 ft. over rolling NW. slope.
55.60	Wash, 10 lks. wide, 1 ft. deep, drains NW.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	
73.50	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.
80.10	The cor. of secs. 1 and 12.
	Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cactus, greasewood, catclaw, ocotillo, paloverde.
	N. 0°08' E., along W. bdy. of sec. 1. Over gently rolling land, through scattered undergrowth.
7.50	Wash, 10 lks. wide, 1 ft. deep, drains W.
23.20	Low spur, slopes W.
30.40	Wash, 20 lks. wide, 1 ft. deep, drains S. 70° W.
36.86	Point for the $\frac{1}{4}$ sec. cor. of sec. 2.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.
	T5N 1/4S2 R9W 1958
40.00	Point for the $\frac{1}{4}$ sec. cor. of sec. 1.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked.
	T5N 1/4S1
47.60	Spur, slopes N. 70° W.; desc. 50 ft. over N. slope.
56.50	Wash, 30 lks. wide, 2 ft. deep, drains N. 70° W.
76.30	Low spur, slopes N. 70° W.
80.44	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the T. monumented by a 2 in. iron post, set, mkd. and witnessed as described in the official record.
	Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cactus, greasewood, catclaw, ocotillo, and paloverde.
	Beginning at the standard cor. of secs. 34 and 35, on the S. bdy. of the T.; which is monumented by an iron post, 2 ins. diam., set, marked and witnessed as described in the official record.
	N. 0°05' E., bet. secs. 34 and 35.
	Over rolling hills, through medium undergrowth.
1.90	Wash, 20 lks. wide, 1 ft. deep, drains W.; asc. 100 ft. over rolling W. slope.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	
35.90	Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
40.00	The point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over (X) on solid stone, and in a mound of stone, 4 ft. base, to top, with brass cap marked.
	T5N R9W $\frac{1}{4}$ S34 S35 1959
	Asc. 10 ft. over S. slope.
41.30	Spur, slopes S. 70° W.; desc. 20 ft. over N. slope.
49.10	Wash, 20 lks. wide, 1 ft. deep, drains S. 70° W.; asc. 250 ft. over S. slope.
59.50	Top of ascent on high knoll slopes W.; desc. 220 ft. over NW. slope.
67.20	Wash, 30 lks. wide, 10 ft. deep, drains W.; asc. 70 ft. over rolling S. slope.
79.85	Point selected for the witness cor. of secs. 26, 27, 34, and 35.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap marked.
	T5N R9W S27 S26 S34 S35 1959
80.00	True point for cor. of secs. 26, 27, 34, and 35 falls on steep rock face, sloping S., where cor. cannot be perpetuated.
	Land, rolling hills. Soil, rocky. Timber, none. Undergrowth, cholla and saguaro cactus, greasewood, catclaw, ocotillo, and paloverde.
	From the cor. of secs. 26 and 35.
	N. 89°58' W., bet. secs. 26 and 35.
	Over rolling hills, through medium undergrowth; asc. 50 ft. along N. slope.
16.60	Spur, projects N.; desc. 120 ft. over W. slope.
31.10	Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.; asc. 20 ft. over E. slope.
36.90	Ridge bears NW. and SE.; desc. 30 ft. over W. slope.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap marked.
	T5N R9W $\frac{1}{4}$ S26 S35 1959

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

Desc. 20 ft. over W. slope.

42.00 Wash, 10 lks. wide, 6 ins. deep, drains S. 30° W.; asc. 100 ft. over E. slope.

60.10 Spur, slopes S. 30° W.; asc. 10 ft. along rolling S. slope.

76.70 Spur, slopes S.; desc. 60 ft. along rolling S. slope.

79.98 The true point for cor. of secs. 26, 27, 34, and 35.

Land, rolling hills.

Soil, rocky.

Timber, none.

Undergrowth, cholla and saguaro cactus, palo verde, catclaw, ocotillo, and greasewood.

N. 0°05' E., bet. secs. 26 and 27.

Over rolling hills, through medium undergrowth; asc. 160 ft. over rolling S. slope.

9.80 Spur, slopes S. 70° E.; desc. 60 ft. over NE. slope.

17.10 Wash, 10 lks. wide, 1 ft. deep, drains S. 70° E.; asc. 70 ft. over SE. slope.

24.50 Spur, slopes S. 70° E.; desc. 30 ft. over NE. slope.

32.00 Wash, 10 lks. wide, 1 ft. deep, drains S. 70° E.; asc. 80 ft. over SE. slope.

40.00 The point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W

$$\begin{array}{c} \frac{1}{4} \\ S27 \mid S26 \\ 1959 \end{array}$$

Asc. 50 ft. over SE. slope.

41.70 Ridge, bears N. 70° W. and E.; desc. over N. slope.

54.95 Wash, 20 lks. wide, 3 ft. deep, drains N. 70° E.; asc. 30 ft. over S. slope.

57.70 Spur, slopes N. 70° E.; desc. 40 ft. over N. slope.

64.70 Wash, 10 lks. wide, 2 ft. deep, drains N. 70° E.; asc. 20 ft. over rolling E. slope.

72.40 Spur, slopes N. 70° E.; desc. 30 ft. over N. slope.

77.80 Wash, 20 lks. wide, 1 ft. deep, drains N. 70° E.; asc. 30 ft. over S. slope.

79.00 Spur, slopes N. 70° E.; desc. 20 ft. over NW. slope.

80.00 The point for the cor. of secs. 22, 23, 26, and 27.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap marked.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

T5N R9W
 S22 | S23
 S27 | S26
 1959

Land, rolling hills.
 Soil, rocky.
 Timber, none.
 Undergrowth, cholla and saguaro cactus, paloverde, ocotillo, catclaw,
 and greasewood.

From the cor. of secs. 23 and 26.

N. 89°51' W., bet. secs. 23 and 26.

Over rolling land, through medium undergrowth; asc. 30 ft. over E.
 slope.

- 3.70 Spur, slopes N.; asc. 50 ft. over NE. slope.
- 20.80 Low saddle on spur projecting NW.; desc. SW. slope.
- 39.90 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 23 and 26,
 Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground,
 and in a mound of stone, 3 ft. base, to top, with brass cap marked.
- T5N R9W
 W1S23
 C4S26
 1959
- 39.96 The point for the $\frac{1}{4}$ cor. of secs. 23 and 26, falls in E. edge of
 wash, where cor. cannot be perpetuated.
- 40.10 Wash, 30 lks. wide, 3 ft. deep, drains NW. for about 6 chs. thence N.
 irregularly; asc. 100 ft. over series of low spurs and small washes
 putting N., remains of road in bottom of wash.
- 58.60 Spur, slopes sharply N. 20° E. about 5 chs. to end.
- 59.80 Wash, 20 lks. wide, 2 ft. deep, drains N. 30° E.
- 66.40 Spur, slopes NE.; desc. 20 ft. over NW. slope.
- 73.80 Wash, 20 lks. wide, 2 ft. deep, drains NE.; asc. 50 ft. over SE.
 slope.
- 79.92 The cor. of secs. 22, 23, 26, and 27.

Land, rolling hills.

Soil, rocky.

Timber, none.

Undergrowth, cholla and saguaro cactus, greasewood, paloverde, cat-
 claw, and ocotillo.

N. 0°05' E., bet. secs. 22 and 23.

Over rolling hills, through scattered undergrowth; desc. 90 ft. over
 series of spurs and washes putting irregularly E.

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.
	<p>T5N R9W $\frac{1}{4}$ S22 S23 1959</p>
	Asc. 30 ft. over rolling E. slope.
50.20	Spur, slopes E.; desc. 50 ft. over N. slope.
56.00	Wash, 20 lks. wide, 2 ft. deep, drains E.; asc. 120 ft. over SE. slope.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground and in a mound of stone, 3 ft. base, to top, with brass cap marked.
	<p>T5N R9W S15 S14 S22 S23 1959</p>
	Land, rolling hills. Soil, rocky. Timber, none. Undergrowth, cholla and saguaro cactus, greasewood, paloverde, cat-claw, and ocotillo.
	From the true point for the cor. of secs. 14 and 23.
	N. 89°55' W., bet. secs. 14 and 23.
	Over rolling land, through scattered to medium undergrowth; asc. 10 ft.
6.60	Unimproved road, bears N. 10° W. and S. 20° E.; desc. 50 ft. over rolling N. slope.
14.60	Wash, 20 lks. wide, 3 ft. deep, drains N. 30° W.
22.60	Wash, 10 lks. wide, 2 ft. deep, drains N. 10° W.
28.90	Road, bladed, bears N. 10° W. and S. 10° E.
35.90	Wash, 1 ch. wide, 5 ft. deep, drains N. 10° E.; asc. 20 ft.
39.98	The point for the ¼ sec. cor. of secs. 14 and 23.
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.
	<p>T5N R9W $\frac{1}{4}$ S14 S23 1959</p>
	Over gently rolling land, draining N.
42.30	Low spur, slopes N. 10° E.
44.90	Wash, 30 lks. wide, 10 ft. deep, drains N.; asc. 200 ft. over SE. slope.

BOOK 4305

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	
78.90	Sptr, slopes SE.; desc. 10 ft. over W. slope.
79.96	The cor. of secs. 14, 15, 22, and 23. Land, rolling hills. Soil, rocky. Timber, none. Undergrowth, saguaro and cholla cacti, greasewood, catclaw, paloverde, and ocotillo.
	N. 0°05' E.; bet. secs. 14 and 15. Over rolling hills through scattered to medium undergrowth; asc. 40 ft. along W. slope.
8.00	Top of hill, bears SE. and S. 70° W.; desc. 280 ft. over N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked. T5N R9W $\frac{1}{4}$ S15 S14 1959
	Over nearly level bottom land.
62.90	Wash, 1 ch. wide, 4 ft. deep, drains N. 70° W.
80.00	Point for the cor. of secs. 10, 11, 14, and 15. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground, and in a mound of stone, 2 $\frac{1}{2}$ ft. base, to top, with brass cap marked. T5N R9W S10 S11 S13 S14 1959
	Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, paloverde, and catclaw.
	From the cor. of secs. 11 and 14. N. 89°59' W., bet. secs. 11 and 14. Over gently rolling land, through scattered to medium undergrowth.
27.00	Wash, 20 lks. wide, 3 ft. deep, drains NW.
39.90	Wash, 10 lks. wide, 1 ft. deep, drains NW.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 2 $\frac{1}{2}$ ft. base, to top, with brass cap marked. T5N R9W $\frac{1}{4}$ S11 S11 1959

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

Over gently rolling land.

43.20 Low spur, slopes gently N. 10° E.

47.70 Wash, 10 lks. wide, 1 ft. deep, drains N.

71.60 Road, graded, bears N. 30° W. and SE.

79.96 The cor. of secs. 10, 11, 14, and 15.

Land, rolling.

Soil, sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

N. 0°05' E., bet. secs. 10 and 11.

Over gently rolling land, through scattered to medium undergrowth.

5.80 Road, graded, bears N. 70° W. and S. 70° E.

22.40 Wash, 10 lks. wide, 1½ ft. deep, drains N. 60° W.

40.00 Point for the ¼ sec. cor. of secs. 10 and 11.

Set an iron post, 30 ins. diam., 24 ins. in the ground, with brass cap marked.

T5N R9W

¼	
S10	S11
1959	

Over gently rolling land.

52.20 Wash, 20 lks. wide, 1 ft. deep, drains N. 70° W.

59.20 Road, graded, bears N. 70° W. and S. 70° E.

80.00 Point for the cor. of secs. 2, 3, 10, and 11.

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap marked.

T5N R9W

S 3 S 2	
S10	S11
1959	

Land, rolling.

Soil, sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, catclaw, palo-verde, and ocotillo.

From the cor. of secs. 2 and 11.

N. 89°53' W., bet. secs. 2 and 11.

Over rolling land, through scattered to medium undergrowth.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	
13.40	Wash, 20 lks. wide, 2 ft. deep, drains N. 30° W.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked. T5N R9W $\frac{1}{4}$ S 2 S11 1959 Over nearly level land.
79.98	The cor. of secs. 2, 3, 10, and 11. Land, gently rolling. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cacti, greasewood, catclaw, palo verde, and ocotillo.
	N. 0°05' E., bet. secs. 2 and 3. Over gently rolling land, through scattered to medium undergrowth.
32.00	Wash, 10 lks. wide, 3 ft. deep, drains N. 60° W.
40.00	The point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap marked. T5N R9W S 3 $\frac{1}{4}$ S 2 1959 Over gently rolling land.
42.90	Wash, 10 lks. wide, 2 ft. deep, drains N. 60° W.
49.60	Road, unimproved bears E. and W.
51.20	Fence, barb wire, bears N. 70° E. and W.
63.80	Fence, barb wire, bears E. and W.
64.10	Road, unimproved, bears E. and W.
71.70	Road, unimproved, bears NW. and SE.
83.28.	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the T. monumented by a 2 in. iron post, set, mkd. & witnessed as described in the official record. From this cor. The NW. cor. of porch on house bears S. 24°25' E., 30.19 chs. dist. A well bears S. 26°20' E., 23.14 chs. dist. Land, gently rolling. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cacti, greasewood, catclaw, palo verde, mesquite, and ocotillo.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

From the standard cor. of secs. 33 and 34, on the S. bdy. of the T. which is monumented by an iron post, 2 ins. diam., set, marked and witnessed as described in the official records.

N. 0°04' E., bet. secs. 33 and 34.

Over rolling hills, through scattered to medium undergrowth; asc. 190 ft. over SE. slope.

16.60 Ridge, bears E. and W. irregularly; desc. 280 ft. over N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W
 $\frac{1}{4}$
S33|S34
1959

Desc. 30 ft. over N. slope.

46.10 Wash, 10 lks. wide, 2 ft. deep, drains N. 70° W.; asc. 70 ft. over S. slope.

61.70 Spur, projects W.; desc. 50 ft. over NE. slope.

80.00 The point for the cor. of secs. 27, 28, 33, and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap marked.

T5N R9W
S28|S27
S33|S34
1959

Land, rolling hills.

Soil, rocky.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, catclaw, paloverde, and ocotillo.

From the cor. of secs. 26, 27, 34, and 35.

N. 89°47' W., bet. secs. 27 and 34.

Over rolling land, through scattered to medium undergrowth; asc. 80 ft. over rolling S. slope.

8.20 Spur, slopes S. 20° E.

15.00 Top of ascent, in saddle on spur, sloping S. 20° W.; desc. 110 ft. over series of spurs and washes putting S.

25.10 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.

33.60 Spur, slopes S. 20° W.

37.10 Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.

39.99 The point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

T5N R9W

 $\frac{1}{4}$ S27

S34

1959

- 41.10 Ridge, bears N. 30° E. and SW.; desc. 60 ft. over rolling S. slope.
- 66.50 Road, bladed, bears N. 60° W. and S. 60° E.
- 69.10 Wash, 20 lks. wide, 5 ft. deep, drains N. 60° W.; asc. 30 ft. along rolling N. slope.
- 73.30 Road, unimproved, bears N. and S.
- ~~79.98~~ The cor. of secs. 27, 28, 33, and 34.
- Land, rolling.
Soil, rocky.
Timber, none.
Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

N. 0°04' E., bet. secs. 27 and 28.

Over rolling hilly land, through scattered to medium undergrowth; desc. 30 ft. over N. slope.

- 11.50 Wash, 30 lks. wide, 4 ft. deep, drains N. 60° W.
- 15.60 Road, bladed, bears N. 60° W. and S. 60° E.; asc. 70 ft. over SW. slope.
- 29.50 Spur, slopes SW.
- 32.50 Wash, 30 lks. wide, 10 ft. deep, drains S. 60° W.
- 40.00 The point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap marked.

T5N R9W

S28 | S27

1959

Asc. 70 ft. along SW. slope.

- 49.70 Spur, slopes S. 30° W.; desc. 40 ft. along W. slope
- 57.60 Wash, 10 lks. wide, 3 ft. deep, drains S. 30° W.; asc. 150 ft. over rolling S. slope.
- 80.00 The point for the cor. of secs. 21, 22, 27, and 28.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap marked.

T5N R9W

S21 | S22

S28 | S27

1959

Land, rolling and hilly.

Soil, rocky.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

From the cor. of secs. 22, 23, 26, and 27.

N. 89°51' W., bet. secs. 22 and 27.

Over hilly land, through scattered to medium undergrowth; asc. 270 ft. over series of spurs and draws putting NE.

31.10 Spur, slopes sharply N. 10° E.; desc. 168 ft. over NW. slope.

39.99 Point for the 1/4 sec. cor. of secs. 22 and 27.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W
1/4 S22
S27
1959

40.32 Wash, 10 lks. wide, 3 ft. deep, drains N.; asc. 130 ft. over NE. slope.

55.50 Ridge, bears N. 30° W. and S. 30° E.; desc. 240 ft. over spurs and small washes putting SW.

79.98 The cor. of secs. 21, 22, 27, and 28.

Land, hilly.

Soil, rocky.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

N. 0°04' E., bet. secs. 21 and 22.

Over rolling hills, through scattered to medium undergrowth; asc. 100 ft. over SW. slope.

7.90 Ridge, NE. and SW.; asc. 20 ft. along W. slope.

15.70 Spur, slopes W.; desc. 290 ft. over N. slope.

40.00 The point for the 1/4 sec. cor. of secs. 21 and 22.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap marked.

T5N R9W
1/4 S21/S22
1959

Desc. 90 ft. over rolling NE. slope.

70.60 Wash, 20 lks. wide, 2 ft. deep, drains N. 30° W.

76.20 Spur, slopes N. 30° W.

80.00 Point for the cor. of secs. 15, 16, 21, and 22.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, and in a mound of stone, 4 ft. base; to top, with brass cap marked.

T5N R9W
S16/S15
S21/S22
1959

Land, steeply rolling hills.

Soil, rocky.

Timber, none.

Undergrowth, saguaro and cholla cacti, greasewood, ocotillo, palo-verde, and catclaw.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

From the cor. of secs. 14, 15, 22, and 23.

N. 89°55' W., bet. secs. 15 and 22.

Over steeply rolling land, through medium undergrowth; desc. 200 ft. over series of spurs and minor washes putting SW.

30.90 Wash, 30 lks. wide, 4 ft. deep, drains N. 60° W. over rolling land in bottom of draw.

39.43 The point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 15 and 22.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked.

T5N R9W

W 1S15

C 4S22

1959

40.02 True point for $\frac{1}{4}$ sec. cor. of secs. 15 and 22; Wash, 30 lks. wide, 6 ft. deep, drains NW. about 3 chs. to junction with wash from E.

Asc. 90 ft. over rolling NE. slope.

70.70 Spur, slopes NW.; desc. 90 ft. over W. slope.

80.04 The cor. of secs. 15, 16, 21, and 22.

Land, steeply rolling hills.

Soil, rocky.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, catclaw, paloverde, and ocotillo.

N. 0°04' E., bet. secs. 15 and 16.

Over rolling land, through medium undergrowth; desc. 70 ft. over NW. slope.

15.40 Wash, 20 lks. wide, 5 ft. deep, drains N. 70° W.; asc. 30 ft. over SW. slope.

27.60 Wash, 10 lks. wide, 1 ft. deep, drains N. 70° W.

40.00 The point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked.

T5N R9W

$\frac{1}{4}$

S16|S15

1959

Deposit glass at base of cor.

Desc. 60 ft. over NW. slope.

60.20 Wash, 20 lks. wide, 3 ft. deep, drains S. 70° W., asc. 10 ft. over SW. slope.

80.00 Point for the cor. of secs. 9, 10, 15, and 16.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

T5N R9W
S 9 | S10
S16 | S15
1959.

Land, rolling.
Soil, rocky.
Timber, none.
Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

From the cor. of secs. 10, 11, 14 and 15.

N. 89°59' W., bet. secs. 10 and 15,

Over rolling land, through medium undergrowth; desc. 20 ft. along S. slope.

39.98 The point for the 1/4 sec. cor. of secs. 10 and 15.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap marked.

T5N R9W
1/4 S10
S15
1959

Desc. 30 ft. along S. slope.

52.90 Wash, 2 chs. wide, 10 ft. deep, drains N. 80° W.; asc. 30 ft. along N. slope.

79.96 The cor. of secs. 9, 10, 15, and 16.

Land, rolling.
Soil, sandy clay.
Timber, none.
Undergrowth, cholla and saguaro cacti, greasewood, mesquite, palo-verde, ocotillo, and catclaw.

N. 0°04' E., bet. secs. 9 and 10.

Over gently rolling land, through medium undergrowth; desc. 30 ft. on N. slope.

2.90 Wash, 2 chs. wide, 10 ft. deep, drains W.

40.00 The point for the 1/4 sec. cor. of secs. 9 and 10.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap marked.

T5N R9W
1/4
S 9 | S10
1959.

Deposit glass at base of cor.

Continue over nearly level land.

72.50 Graded dirt road, bears N. 10° E. and S. 10° W.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

<p>Chains</p> <p>80.00</p>	<p>The point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked.</p> <div style="text-align: center;"> <p>T5N R9W</p> <p>S 4 S 3</p> <p>S 9 S10</p> <p>1959</p> </div> <p>Deposit glass at base of cor.</p> <p>Land, gently rolling bottom land. Soil, sandy clay. Timber, none. Undergrowth, saguaro and cholla cacti, greasewood, mesquite, paloverde, catclaw, and ocotillo.</p>
<p>31.60</p> <p>39.00</p> <p>39.99</p>	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S. 89°57' W., bet. secs. 3 and 10.</p> <p>Over gently rolling land, through medium undergrowth.</p> <p>Road, unimproved, bears N. 50° W. and S. 50° E.</p> <p>Road, unimproved, bears N. 50° W. and S. 50° E.</p> <p>The point for the ¼ sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked.</p> <div style="text-align: center;"> <p>T5N R9W</p> <p>¼ S 3</p> <p>S10</p> <p>1959</p> </div> <p>Deposit glass at base of cor.</p> <p>Continue over nearly level bottom land.</p>
<p>73.80</p> <p>79.98</p>	<p>Road, unimproved, bears N. 30° E. and S. 30° W.</p> <p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, gently rolling hills and nearly level bottom land. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cacti, greasewood, mesquite, paloverde, ocotillo, and catclaw.</p>
<p>5.10</p> <p>19.50</p> <p>40.00</p>	<p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over nearly level bottom land, through medium to medium dense undergrowth.</p> <p>Wash, 1 ch. wide, 3 ft. deep, drains S. 70° W.</p> <p>Unimproved road bears E. and W.</p> <p>The point for the ¼ sec. cor. of secs. 3 and 4.</p>

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked.

T5N R9W

 $\frac{1}{4}$

S 4 | S 3

1959

Deposit glass at base of cor.

Continue over gently rolling land draining SW.

69.30 Wash, 20 lks. wide, 1 ft. deep, drains SW.

83.10 The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the T. monumented by a 2 in. iron post, set, mkd. & witnessed as described in the official record. Land, gently rolling. Soil, sandy clay. Timber, none. Undergrowth, saguaro and cholla cacti, greasewood, mesquite, paloverde, ocotillo and catclaw.

From the standard cor. of secs. 32 and 33, on the S. bdy. of the T.; which is monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.

N. $0^{\circ}04'$ E., bet. secs. 32 and 33.

Over steeply rolling hills, through medium undergrowth; desc. 40 ft.

8.10 Wash, 30 lks. wide, 10 ft. deep, drains N. 70° W.; asc. 40 ft. over S. slope.

11.10 Road, unimproved, bears E. and W.; asc. 150 ft. over rolling SW. slope.

33.20 Top of ascent, slopes W.; desc. 150 ft. over NW. slope.

40.00 The point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap marked.

T5N R9W

 $\frac{1}{4}$

S32 | S33

1959

Desc. 30 ft. over N. slope.

44.60 Wash, 30 lks. wide, 5 ft. deep, drains W.; asc. 180 ft. over rolling S. slope.

79.60 Ridge bears E. and W.

80.00 The cor. of secs. 28, 29, 32, and 33.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap marked.

T5N R9W

S29 | S28

S32 | S33

1959

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

Land, steeply rolling.
Soil, rocky to sandy clay.
Timber, none.
Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

From the cor. of secs. 27, 28, 33, and 34.

N. 89°59' W., bet. secs. 28 and 33.

Over steeply rolling hills, through medium undergrowth; asc. 70 ft.

7.60 Spur, slopes sharply N.; desc. 50 ft. over NW. slope.

19.70 Wash, 15 lks. wide, 2 ft. deep, drains N.; asc. 80 ft. over NE. slope.

29.50 Spur, projects N.; desc. 120 ft. over W. slope.

39.70 Wash, 15 lks. wide, 3 ft. deep, drains N. 35° W.

40.04 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W

$\frac{1}{4}$ S28
S33

1959

Over rolling N. slope; asc. 20 ft.

43.80 Spur, slopes N. 30° W.

51.40 Wash, 25 lks. wide, 2 ft. deep, drains N. 10° W.

69.20 Top of black knoll, on spur sloping N.

76.80 Wash, 20 lks. wide, 3 ft. deep, drains N. 40° W.

80.08 The cor. of secs. 28, 29, 32, and 33.

Land, rolling hills.

Soil, rocky.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

N. 0°04' E., bet. secs. 28 and 29.

Desc. 80 ft. over N. slope, through medium undergrowth.

6.70 Wash, 20 lks. wide, 3 ft. deep, drains NW.; asc. 10 ft.

9.90 Spur, slopes N. 70° W.; desc. 70 ft. along N. slope.

24.50 Unimproved road, bears N. 20° E. and S. 70° W.; desc. 10 ft. along N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground, and in a mound of stone, 3 $\frac{1}{2}$ ft. base, to top, with brass cap marked.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

T5N R9W

$$\begin{array}{c} \frac{1}{4} \\ \hline S29 | S28 \\ 1959 \end{array}$$

Asc. 40 ft. over gently rolling land.

42.10 Wash, 35 lks. wide, 6 ft. deep, drains W.

61.90 Unimproved road, bears N. 50° W. and S. 50° E.

72.10 Wash, 20 lks. wide, 3 ft. deep, drains S. 30° W.

80.00 The cor. of secs. 20, 21, 28, and 29.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap marked.

T5N R9W

$$\begin{array}{c} \frac{1}{4} \\ \hline S20 | S21 \\ \hline S29 | S28 \\ 1959 \end{array}$$

Land, rolling.

Soil, sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

From the cor. of secs. 21, 22, 27, and 28.

N, 89°59' W., bet. secs. 21 and 28.

Over steeply rolling hills, through medium undergrowth; asc. 100 ft. over SE. slope.

9.90 Spur, slopes S. 30° W.; desc. 190 ft. over W. slope.

23.30 Wash, 10 lks. 4 ft. deep, drains S. 40° W.; desc. 130 ft. over W. slope.

39.00 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 21 and 28.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W

$$\begin{array}{c} \frac{1}{4} \\ \hline S21 | WC \\ \hline S28 \\ 1959 \end{array}$$
40.02 The point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28 falls in wash, 40 lks. wide, 10 ft. deep, drains S. 10° W.; asc. 110 ft. over E. slope.

46.90 Spur, slopes S. 35° W.; desc. 60 ft. over NW. slope.

58.10 Wash, 15 lks. wide, 5 ft. deep, drains S. 30° W.; asc. 60 ft. over SE. slope.

62.50 Spur, slopes S. 30° W.; desc. 120 ft. over W. slope.

79.80 Wash, 30 lks. wide, 10 ft. deep, drains S. 10° W.

80.04 The cor. of secs. 20, 21, 28, and 29.

Land, steeply rolling hills.

The Survey of the Subdivisional Lines T. 5 N., R. 9 W.

Chains

Soil, sandy clay.
 Timber, none.
 Undergrowth, saguaro and cholla cacti, greasewood, ocotillo, palo-verde, and catclaw.

N. $0^{\circ}04'$ E., bet. secs. 20 and 21.

Over steeply rolling hills, through medium undergrowth; asc. 110 ft. over S. slope.

22.50 Spur, slopes W.; desc. 60 ft. over N. slope.

26.90 Wash, 15 lks. wide, 3 ft. deep, drains N. 70° W.; asc. 90 ft. over S. slope.

38.40 Spur, slopes W.; desc. 20 ft. over N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W
 $\frac{1}{4}$
 S20|S21
 1959

Continue over rolling W. slope.

51.60 Spur, slopes N: 70° W.; desc. 120 ft. over NE. slope.

69.20 Wash, 30 lks. wide, 10 ft. deep, drains N. 65° W.; asc. 30 ft. over rolling W. slope.

80.00 Point for the cor. of secs. 16, 17, 20, and 21.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap marked.

T5N R9W
 S17|S16
 S20|S21
 1959

Land, steeply rolling hills.

Soil, shallow sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo verde, and catclaw.

From the cor. of secs. 15, 16, 21, and 22.

N. $89^{\circ}51'$ W., bet. secs. 16 and 21.

Over rolling hills, through medium undergrowth; desc. 30 ft. over rolling N. slope.

13.60 Wash, 35 lks. wide, 6 ft. deep, drains N. 65° W.; asc. 100 ft. over E. slope.

31.80 Spur, slopes N. desc. 100 ft. over W. slope.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

40.02

The point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W

 $\frac{1}{4}$ S16

S21

1959

Desc. 30 ft. over W. slope.

49.30

Wash, 20 lks. wide, 5 ft. deep, drains N. 30° W.; desc. 70 ft. over rolling N. slope.

51.70

Spur, slopes N. 40° W.

54.20

Wash, 30 lks. wide, 4 ft. deep, drains N. 40° W.

64.50

Spur, slopes N. 40° W.

71.70

Wash, 15 lks. wide, 3 ft. deep, drains NW.

80.04

The cor. of secs. 16, 17, 20, and 21.

Land, rolling hills.

Soil, sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

N. $0^\circ 04'$ E., bet. secs. 16 and 17.

Over rolling hills, through medium undergrowth; desc. 40 ft. over N. slope.

5.70

Wash, 15 lks. wide, 3 ft. deep, drains N. 60° W.; asc. 10 ft.

18.20

Spur, slopes W.; desc. 60 ft. over N. slope.

25.00

Wash, 20 lks. wide, 3 ft. deep, drains W.; continue over rolling W. slope.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked.

T5N R9W

 $\frac{1}{4}$ S17

S16

1959

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W. of cor.

Over gently rolling land.

50.70

Wash, 30 lks. wide, 2 ft. deep, drains N. 75° W.

80.00

Point for the cor. of secs. 8, 9, 16, and 17.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked.

The Survey of the Subdivisional Lines T. 5 N., R. 9 W.

Chains

T5N R9W
 S 8 | S 9
 S17 | S16
 1959

Land, rolling.
 Soil, sandy clay.
 Timber, none.
 Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

From the cor. of secs. 9, 10, 15, and 16.

N. 89°54' W., bet. secs. 9 and 16.

Over gently rolling land, through medium undergrowth.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap marked.

T5N R9W
 $\frac{1}{4}$ S 9
 S16
 1959

Continue over gently rolling land.

80.02 The cor. of secs. 8, 9, 16, and 17.

Land, gently rolling.
 Soil, sandy clay.
 Timber, none.
 Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde.

N. 0°04' E., bet. secs. 8 and 9.

Over nearly level land, through medium undergrowth.

7.80 Unimproved road, bears N. 50° E. and S. 50° W.

10.10 Wash, 25 lks. wide, 2 ft. deep, drains W.

36.30 Wash, 35 lks. wide, 4 ft. deep, drains N. 60° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked.

T5N R9W
 $\frac{1}{4}$
 S 8 | S 9
 1959

Deposit glass at base of cor.

Continue over nearly level land.

41.00 Wash, 30 lks. wide, 2 ft. deep, drains S. 70° W.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	
56.00	Wash, 1 ch. wide, 4 ft. deep, drains S. 40° W.
80.00	Point for the cor. of secs. 4, 5, 8, and 9.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked.
	T5N R9W S 5 S 4 S 8 S 9 1959
	Deposit glass at base of cor.
	Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.
	From the cor. of secs. 3, 4, 9, and 10.
	N. 89°55' W., bet. secs. 4 and 9.
	Over nearly level land, through medium undergrowth.
34.00	Wash, 1 ch. wide, 4 ft. deep, drains S. 50° W.
40.04	Point for the ¼ sec. cor. of secs. 4 and 9.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked.
	T5N R9W ¼ S 4 S 9 1959
	Continue over nearly level land.
80.08	The cor. of secs. 4, 5, 8, and 9.
	Land, nearly level. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.
	N. 0°10' W., bet. secs. 4 and 5.
	Over gently rolling land, through medium undergrowth.
21.00	Unimproved road, bears E. and W.
40.00	Point for the ¼ sec. cor. of secs. 4 and 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked.
	T5N R9W ¼ S 4 S 5 S 4 1959

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	
82.73	<p>Continue over gently rolling land.</p> <p>The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the T.; monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.</p> <p>Land, gently rolling. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.</p>
19.10	<p>Beginning at the standard cor. of secs. 31 and 32, monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.</p> <p>N. 0°03' E., bet. secs. 31 and 32.</p> <p>Over rolling hills; through medium undergrowth.</p> <p>Unimproved road, bears S. 75° W. and N. 75° E.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.</p>
40.60	<p style="text-align: center;">T5N R9W $\frac{1}{4}$ S31 S32 1959</p> <p>Spur, slopes N. 70° W.; desc. 120 ft. over N. slope.</p>
55.60	<p>Wash, 15 lks. wide, 3 ft. deep, drains N. 70° W.; asc. 70 ft. over S. slope.</p>
66.80	<p>Spur, slopes W.; desc. 90 ft. over N. slope.</p>
75.30	<p>Wash, 1 ch. wide, 20 ft. deep, drains N. 70° W.; asc. 30 ft. over S. slope.</p>
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap marked.</p>
	<p style="text-align: center;">T5N R9W S30 S29 S31 S32 1959</p>
	<p>Land, rolling hills. Soil, shallow sandy clay. Timber, none.</p>
	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89°54' W., bet. secs. 29 and 32.</p> <p>Over steeply rolling hills, through medium undergrowth; asc. 30 ft. over N. slope.</p>
11.50	<p>Ridge, bears N. 80° W. and S. 80° E.; desc. 150 ft. over S. slope.</p>
38.30	<p>Wash, 20 lks. wide, 4 ft. deep, drains S. 20° E.; asc. 20 ft. over E. slope.</p>

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

40.04

Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked.

T5N R9W

 $\frac{1}{4}$ S29S32

1959

Asc. 100 ft. over SE. slope.

46.20

Top of ascent, slopes S.; desc. 180 ft. along S. slope.

64.20

Wash, 15 lks. wide, 4 ft. deep, drains S. 60° W.

80.08

The cor. of secs. 29, 30, 31, and 32.

Land, steeply rolling hills.

Soil, rocky clay.

Timber, none.

Undergrowth, saguaro and cholla cacti, greasewood, ocotillo, palo-verde, and catclaw.

N. 89°50' W., bet. secs. 30 and 31.

Over rolling land, through medium undergrowth; desc. 50 ft.

31.40

Wash, 30 lks. wide, 10 ft. deep, drains S. 60° W.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap marked.

T5N R9W

 $\frac{1}{4}$ S30S31

1959

Asc. 80 ft. over E. slope.

60.20

Spur, slopes S.; asc. desc. 30 ft. over rolling S. slope.

71.20

Spur, slopes S. 30° E.

80.08

The cor. of secs. 25, 30, 31, and 36, on the W. bdy., monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.

Land, rolling hills.

Soil, shallow sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

From the cor. of secs. 29, 30, 31, and 32.

N. 0°03' E., bet. secs. 29 and 30.

Over rolling hills, through medium undergrowth; asc. 90 ft. over rolling S. slope.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

39.00 Ridge, bears E. and W. irregularly; desc. 10 ft. over N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, to top, with brass cap marked.

T5N R9W

$$\begin{array}{c} \frac{1}{4} \\ \hline S30 | S29 \\ 1959 \end{array}$$

Desc. 70 ft. over rolling NW. slope.

80.00 Point for the cor. of secs. 19, 20, 29, and 30.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, to top, with brass cap marked.

T5N R9W

$$\begin{array}{c} S19 | S20 \\ \hline S30 | S29 \\ 1959 \end{array}$$

Land, rolling hills.

Soil, shallow sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

From the cor. of secs. 20, 21, 28, and 29.

N. $89^{\circ}51'$ W., bet. secs. 20 and 29.

Along S. slope.

6.30 Top of ascent, slopes S.; desc. 100 ft. along rolling S. slope.

39.50 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 20 and 29.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap marked.

T5N R9W

$$\begin{array}{c} \frac{1}{4} \\ \hline S20 \\ \hline S29 \\ 1959 \end{array} \text{ WC}$$
40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, an improved dirt road, bearing N. 50° W. and S. 50° E., where the cor. cannot be perpetuated.

Continue along gently rolling S. slope.

71.60 Wash, 1 ch. wide, 3 ft. deep, drains N. 50° W.; asc. 40 ft. along rolling N. slope.

80.04 The cor. of secs. 19, 20, 29, and 30.

Land, rolling hills.

Soil, shallow sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

N. 89°47' W.; bet. secs. 19 and 30.

Over rolling hills, through medium undergrowth.

.30 Road, unimproved, bears N. 10° E. and S. 10° W.; continue over rolling land, draining N.

22.30 Wash, 30 lks. wide, 2 ft. deep, drains N. 30° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top; with brass cap marked.

T5N R9W

 $\frac{1}{4}$ S19
S30
1959

From this point, a well bears N. 11°41' W., 49.56 chs. dist.

Over rolling land, desc. 80 ft.

61.20 Unimproved road, bears N. 60° E. and S. 60° W.

80.10 The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the T.; monumented by an iron post, 2 ins. diam., set; marked, and witnessed as described in the official record.

Land, rolling.

Soil, sandy clay.

Timber, none.

Undergrowth; cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

From the cor. of secs. 19, 20, 29, and 30.

N. 0°03' E., bet. secs. 19 and 20.

Over rolling land, through medium undergrowth.

1.50 Unimproved road, bears N. 80° E. and S. 10° W.

3.70 Wash, 1 ch. wide, 3 ft. deep, drains W.; asc. 60 ft. over S. slope.

21.40 Spur, slopes W.; desc. 80 ft. over N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked.

T5N R9W

 $\frac{1}{4}$
S19 | S20
1959

Deposit glass at base of iron post.

Continue over gently rolling land.

42.70 Improved dirt road, bears N. 70° W. and S. 70° E.

80.00 Point for the cor. of secs. 17, 18, 19, and 20.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked.

T5N R9W
S18|S17
S19|S20
1959

Deposit glass at base of cor.

Land, gently rolling.

Soil, sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

From the cor. of secs. 16, 17, 20, and 21.

N. $89^{\circ}54'$ W., bet. secs. 17 and 20.

Over rolling hills, through medium undergrowth; asc. 40 ft. over E. slope.

14.10 Spur, slopes N., continue over rolling N. slope.

31.50 Spur, slopes N. 10° W.; desc. 80 ft. over W. slope.

40.05 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap marked.

T5N R9W
 $\frac{1}{4}$ S17
S20
1959

Over rolling land, draining NW. desc. 160 ft.

80.10 The cor. of secs. 17, 18, 19, and 20.

Land, rolling hills.

Soil, shallow sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

N. $89^{\circ}50'$ W., bet. secs. 18 and 19.

Over gently rolling land, through medium to dense undergrowth; desc. 20 ft.

5.70 Improved dirt road, bears NE. and S. 10° W.

27.90 Wash, 1.50 chs. wide, 4 ft. deep, drains S. 10° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, and in a small mound of stone, to top, with brass cap marked.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

T5N R9W

 $\frac{1}{4}$ S18 $\frac{4}{4}$ S19

1959

Continue over gently rolling land.

62.50 Wash, 20 lks. wide, $\frac{1}{4}$ ft. deep, drains S. 30° E.

66.40 Low spur, slopes S. 20° E.

72.40 Wash, 20 lks. wide, 2 ft. deep, drains S. 50° E.

80.14 The true point for cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the T, which is witnessed N. 2.06 chs. dist. by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

Land, gently rolling.

Soil, sandy clay.

Timber, none.

Undergrowth, saguaro and cholla cacti, greasewood, ocotillo, palo-verde, mesquite, and catclaw.

From the cor. of secs. 17, 18, 19, and 20.

N. 0°03' E., bet. secs. 17 and 18.

Over gently rolling land, through medium to dense undergrowth.

6.60 Improved dirt road, bears NE. and SW.

38.90 Wash, 2 chs. wide, 5 ft. deep, drains S. 50° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 5 ft. base, to top, with brass cap marked.

T5N R9W

 $\frac{1}{4}$ S18

S17

1959

Continue over gently rolling land.

80.00 Point for the cor. of secs. 7, 8, 17, and 18.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked.

T5N R9W

S 7 | S 8

S18 | S17

1959

Deposit glass at base of cor.

Land, rolling.

Soil, sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, mesquite, and catclaw.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	
	From the cor. of secs. 8, 9, 16, and 17.
	N. 89°53' W., bet. secs. 8 and 17.
	Over gently rolling land, through medium undergrowth.
8.40	Improved dirt road, bears NE. and SW.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked.
	<p style="text-align: center;">T5N R9W $\frac{1}{4}$ S 8 SI7 1959</p>
	Deposit glass at base of iron post.
	Continue over nearly level land.
52.90	Wash, 2 chs. wide, 3 ft. deep, drains S. 10° W.
70.10	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.
80.08	The cor. of secs. 7, 8, 17, and 18.
	Land, nearly level.
	Soil, sandy clay.
	Timber, none.
	Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, mesquite, and catclaw.
	N. 89°46' W., bet. secs. 7 and 18.
	Over gently rolling land, through medium undergrowth.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap marked.
	<p style="text-align: center;">T5N R9W $\frac{1}{4}$ S 7 SI8 1959</p>
	Continue over gently rolling land, through medium undergrowth.
76.40	Wash, 20 lks. wide, 2 ft. deep, drains S. 30° E.
80.26	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the T.; monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.
	Land, gently rolling.
	Soil, sandy clay.
	Timber, none.
	Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, mesquite, and catclaw.

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains

From the cor. of secs. 7, 8, 17, and 18.

N. 0°03' E., bet. secs. 7 and 8.

Over gently rolling land, through medium undergrowth.

17.00 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked.

T5N R9W

$$\begin{array}{c} \frac{1}{4} \\ S 7 | S 8 \\ 1959 \end{array}$$

Continue over nearly level land.

80.00 Point for the cor. of secs. 5, 6, 7, and 8.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap marked.

T5N R9W

$$\begin{array}{c} S 6 | S 5 \\ S 7 | S 8 \\ 1959 \end{array}$$

Land, gently rolling.

Soil, shallow sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, mesquite, and catclaw.

From the cor. of secs. 4, 5, 8, and 9.

N. 89°54' W., bet. secs. 5 and 8.

Over gently rolling land, through medium undergrowth.

24.30 Wash, 20 lks. wide, 2 ft. deep, drains S. 10° E.

40.04 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked.

T5N R9W

$$\begin{array}{c} \frac{1}{4} S 5 \\ S 8 \end{array}$$

1959

Continue over gently rolling land.

80.08 The cor. of secs. 5, 6, 7, and 8.

Land, gently rolling.

Soil, shallow sandy clay.

Timber, none.

Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, mesquite, and catclaw.

BOOK 4005

The Survey of the Subdivisional Lines in T. 5 N., R. 9 W.

Chains	N. 89°52' W., bet. secs. 6 and 7.
	Over gently rolling land, through medium undergrowth.
11.80	Wash, 20 lks. wide, 2 ft. deep, drains S.; asc. 60 ft. over E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked
	T5N R9W $\frac{1}{4}$ S 6 S 7 1959
	Continue over gently rolling land, draining W.
73.80	Wash, 20 lks. wide, 3 ft. deep, drains S. 30° E.
80.38	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the T.; monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.
	Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, mesquite and catclaw.
	From the cor. of secs. 5, 6, 7, and 8.
	N. 0°03' W., bet. secs. 5 and 6.
	Over gently rolling land, through medium undergrowth.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone, $1\frac{1}{2}$ ft. base, to top, with brass cap marked.
	T5N R9W $\frac{1}{4}$ S 6 S 5 1959
	Continue over nearly level land.
41.20	Unimproved road, bears N. 80° E. and S. 80° W.
69.10	Wash, 15 lks. wide, 4 ft. deep, drains S. 65° W.
82.38	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the T., monumented by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.
	Land, gently rolling. Soil, sandy clay. Timber, none. Undergrowth, cholla and saguaro cacti, greasewood, ocotillo, palo-verde, and catclaw.

General Description

Chains

The land in township 5 north, range 9 west, runs from steeply rolling hills in the southeast and central parts of the township to gently rolling in the north and west.

There are several roads running through the township, and at the time of the survey there was quite a bit of mining activity going on.

There are few wells located in the township, which are used for the watering of stock.

The land is covered with a medium growth of undergrowth, and a little native grass.

The land is used principally for the grazing of livestock and mining.

BOOK 4005

4-680
(Feb., 1960)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Neil R. Forsyth	Principal Assistant
Richard N. Brand	Chainman
William R. Savage	Flagman
Dee Von Thompson	Cornerman
Virgil D. Albrecht	Axeman

CERTIFICATE OF CADASTRAL ENGINEER

I, Robert C. Yundt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of September, 1958, I have ~~surveyed~~ supervised the dependent resurvey of the east boundary and the survey of the subdivision of T. 5 N., R. 9 W.

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been ~~executed~~ supervised by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
July 27, 1959

Robert C. Yundt
Robert C. Yundt, Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., OCT 24 1961, 19

The foregoing field notes of the ~~survey of~~ dependent resurvey of the east boundary and the survey of the subdivision of T. 5 N., R. 9 W., Gila & Salt River Meridian, Arizona

executed by Donald A. Cannon, under the supervision of Robert C. Yundt, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in is a true copy of the original field notes.

Cadastral Engineering Staff Officer