

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES

OF THE
DEPENDENT RESURVEY

OF THE
EAST, SOUTH AND WEST BOUNDARIES

AND THE SUBDIVISIONAL LINES

OF
TOWNSHIP 6 SOUTH, RANGE 26 EAST

Of the Gila and Salt River Meridian,
the State of Arizona

EXECUTED BY

Dell Cazier, Cadastral Surveyor (Chief of Party)

Glen B. Hatch, Survey Aid

Eldon W. Sibley, Survey Aid

Under special instructions dated August 10, 1959, which provided

the surveys included under Group No. 338, approved August 24, 1959

Assignment instructions dated March 9, 1960

Survey commenced March 30, 1960

Survey completed April 11, 1960

1A

BOOK 4615

INDEX DIAGRAM

Township 6 South, Range 26 East

19 72	73 71	58 57	48 47	38 37	27 26	6
18 69	70 68	57 56	47 46	36 35	26 25	5
17 66	67 65	55 54	45 44	34 33	24 23	5
16 63	64 63	53 52	43 42	32 32	22 22	4
15 61	62 60	51 51	41 40	31 30	21 20	3
14 12	59 11	50 10	39 9	29 8	19 7	2

Township 6 South, Range 26 East

Chains

A portion of the north boundary, the First Standard Parallel South, between the closing corner of T. 6 S., Rs. 25 and 26 E. and the Standard corner of T. 5 S., Rs. 25 and 26 E. was originally surveyed by T. F. White in 1875. This portion of the line was dependently resurveyed and the remainder surveyed by Philip Contzen in 1895. The south boundary of section 36, T. 5 S., R. 26 E. was retraced and dependently resurveyed by Kimmel and Veal in 1916-1919. The entire First Standard Parallel South through Range 26 East was dependently resurveyed by W. H. Thorn in 1920. The south and west boundaries of T. 6 S., R. 26 E. were originally surveyed by T. F. White in 1875, and dependently resurveyed by Philip Contzen in 1895. The east boundary and the subdivision was originally surveyed by Contzen in 1896. The southeast corner of the township was reestablished by D. E. Harding in 1957.

The resurvey was initiated on the official request of the State Supervisor for Arizona to perpetuate the original corner positions and to provide identification of the boundaries of the public lands to facilitate administration under appropriate public land laws.

The following field notes are those of the dependent resurvey of reestablishment of the survey of the east boundary, south boundary, west boundary, subdivisional lines and the establishment of the north quarter section corner of sections 1, 2, 3, 4, 5 and 6 of T. 6 S., R. 26 E. About ninety per cent of the original corners were identified. The identified evidence consisting of marks and remains of original accessories. One location was restored from the testimony of persons who had known the location of the original monument before its disappearance. The remainder of the corner positions were lost. Before restoring the corners, the lines were retraced and a diligent search made for any evidence of the original corners, bearing objects and any other calls of the original field note record. When duly identified the corner positions were remonumented and new accessories established. After completing the necessary retracements to connect with the identified corner locations and exhausting every reasonable possibility of finding direct evidence for the control of each particular corner, the rules of proportionate measurement were applied in order to ascertain the position of lost corners. The true lines thus adjusted to the identified original evidence were then run.

This survey was executed with two W. and L. E. Gurley transits, serial numbers 491037 and 580158, both constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instruments were in good condition prior to the beginning of the survey and were maintained in proper adjustment throughout the progress of the survey.

The direction of the lines of the survey were determined generally by sustained angulation carried forward from altitude observations on the sun for azimuth and verified through ties to triangulation stations established by the Coast and Geodetic Survey. Measurements were made with narrow steel tapes, 8 chains in length, graduated in tenths for the first link, in links for the next 99 and thereafter at intervals of 10 links. The tapes were tested by comparison with a standard 1-chain steel tape and found to be correct. All measurements were made on the slope with the vertical angle of each interval ascertained by a clinometer in good adjustment; the horizontal equivalents alone are entered in the field notes. All lines of this survey were run by direct method. The retracement data were checked and verified prior to conclusion of the field work and in order to simplify the record the true line notes are supplied herewith which refer to the completed resurvey.

The geographic position for the southeast corner of T. 6 S., R. 26 E. is in latitude $32^{\circ} 51' 34.7''$ N. and longitude $109^{\circ} 37' 46.9''$ W., as determined by section line ties to U. S. C. & G. S. triangulation station "Bonit", which is situated in the northwest quarter of section 7, T. 6 S., R. 28 E.

Township 6 South, Range 26 East

Chains

The magnetic declination was read at a number of stations throughout the township and the average of these readings was found to be 13° East.

Dependent Resurvey of the East Boundary of T. 6 S., R. 26 E.
Gila and Salt River Meridian, Arizona

Reestablishment of the survey executed by Philip Contzen, U. S. Deputy Surveyor in 1895.

The cor. of Tps. 6 and 7 S., Rs. 26 and 27 E. was reestablished in 1957 by D. E. Harding. The point is now mkd. by an iron post, 2½ ins. diam. as described in the official record.

North, bet. secs. 31 and 36.

Over nearly level land, no timber.

15.60 Unimproved road, bears S. 60° E. and N. 60° W.

22.70 Dry wash, 20 lks. wide, 1 ft. deep, drains SW.

32.60 Wash, 20 lks. wide, 1 ft. deep, drains SW.

40.12 The ¼ sec. cor. of secs. 31 and 36 which is mkd. by a Malpais stone, 15x8x7 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a mound of stone, 3 ft. base, to brass cap mkd.

T6S
R26E R27E
¼
S36|S31
1960

Deposit original cor. stone alongside iron post.

Raise a mound of stone, 3½ ft. base, 18 ins. high W. of cor.

N. 0° 10' W., beginning new measurement.

Over series of small washes draining SW.

13.90 Gravel road, bears NE. and SW.

22.50 Wash, 30 lks. wide, 2 ft. deep, drains SW.

30.80 Bulldozed road, bears E. and W.

39.96 The cor. of Secs. 25, 30, 31 and 36 which is mkd. by a malpais stone, 16x12x10 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a mound of stone, 2 ft. base to brass cap mkd.

Dependent Resurvey, E. Bdy., T. 6 S., R. 26 E.

Chains

T6S
R26E R27E
S25|S30
S36|S31
1960

Deposit original cor. stone alongside iron post.

Land, gently rolling, with general SW. drainage.

Soil, gravelly sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

N. 0° 01' W., bet. secs. 25 and 30.

Over rolling land, with general SW. drainage.

7.20 Wash, 20 lks. wide, 2 ft. deep, drains SW.

26.50 Wash, 30 lks. wide, 1 ft. deep, drains SW.

39.70 The $\frac{1}{2}$ sec. cor. of secs. 25 and 30, which is mkd. by a malpais stone, 12x8x7 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground and in a mound of stone, 3 ft. base, to brass cap mkd.

T6S
R26E R27E
 $\frac{1}{2}$
S25|S30
1960

Deposit original cor. stone alongside iron post.

North, beginning new measurement.

14.50 Track road, bears E. and W.

27.70 Wash, 30 lks. wide, 3 ft. deep, drains N. 60° W.

37.20 Wash, 40 lks. wide, 2 ft. deep, drains S. 75° W.

40.26 The cor. of secs. 19, 24, 25 and 30, which is mkd. by a malpais stone, 16x12x5 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a mound of stone, 2 ft. base, to brass cap mkd.

T6S
R26E R27E
S24|S19
S25|S30
1960

Deposit the original cor. stone alongside iron post.

Land, rolling on general SW. slope.

Soil, gravelly, sandy clay.

Timber, none.

Undergrowth, mesquite, greasewood and cacti.

Dependent Resurvey; E. Bdy.; T. 6 S., R. 26 E.

Chains

N. 0° 02' W., bet. secs. 19 and 24.

Over rolling land, through scattered mesquite.

Asc. 10 ft. over S. slope.

7.50 Track road, bears NE. and SW.

10.60 Wash, 30 lks. wide, 2 ft. deep, drains SW.; asc. 20 ft. over S. slope.

14.20 Four strand barbed wire fence, bears N. 20° E. and S. 20° W.; asc. 50 ft. over S. slope.

39.20 Wash, 20 lks. wide, 2 ft. deep, drains S. 20° E.

40.01 The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, which is mkd. by a malpais stone, 18x12x10 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.

T6S
R26E R27E
 $\frac{1}{2}$
S24 | S19
1960

Deposit the original cor. stone alongside iron post.

N. 0° 06' W., beginning new measurements.

Asc. 90 ft. over S. slope.

31.95 Wash, 20 lks. wide, 1 ft. deep, drains SE.

36.45 Same wash, drains SW.; asc. 20 ft. over S. slope.

40.10 The cor. of secs. 13, 18, 19 and 24, which is mkd. by a malpais stone 18x8x6 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.

T6S
R26E R27E
S13 | S18
S24 | S19
1960

Deposit the original cor. stone alongside iron post.

Land, rolling on general S. slope.

Soil, gravelly, sandy clay.

Timber, none.

Undergrowth, mesquite, greasewood and cacti.

Dependent Resurvey, E. Bdy., T. 6 S., R. 26 E.

Chains	
	<p>N. 0° 02' W., bet. secs. 13 and 18.</p>
	<p>Over rolling land, on general S. slope, through scattered mesquite. Asc. 50 ft. over S. slope.</p>
18.60	<p>Wash, 30 lks. wide, 3 ft. deep, drains S. 30° W.; asc. 50 ft. over S. slope.</p>
34.00	<p>Wash, 40 lks. wide, 4 ft. deep, drains S. 30° W.</p>
40.06	<p>The $\frac{1}{2}$ sec. cor. of secs. 13 and 18, which is mkd. by a malpais stone, 18x12x8 ins., firmly set, mkd. and witnessed as described in the official record. At the cor. point</p>
	<p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.</p> <p style="text-align: center;">T6S R26E R27E $\frac{1}{2}$ S13 S18 1960</p>
	<p>Deposit the original cor. stone alongside iron post.</p>
	<p>N. 0° 03' W., beginning new measurement.</p>
4.50	<p>Wash, 30 lks. wide, 4 ft. deep, drains S. 10° W.; asc. 150 ft. over S. slope.</p>
40.09	<p>The cor. of secs. 7, 12, 13 and 18, which is mkd. by a malpais stone, 24x12x10 ins., firmly set, mkd. and witnessed as described in the official record. At the cor. point</p>
	<p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 14 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.</p> <p style="text-align: center;">T6S R26E R27E S12 S 7 S13 S18 1960</p>
	<p>Deposit the original cor. stone alongside the iron post.</p>
	<p>Land, rolling on general S. slope. Soil, gravelly, sandy clay. Timber, none, Undergrowth, scattered mesquite, greasewood and cacti.</p>
	<p>N. 0° 02' E., bet. secs. 7 and 12.</p>
	<p>Over rolling land on S. slope. <i>NOTE: This mile retraced - see resurvey of 6 S., 27 E.</i> Asc. 10 ft. over S. slope.</p>
6.60	<p>Wash, 50 lks. wide, 5 ft. deep, drains SW.; asc. 30 ft. over S. slope.</p>
14.70	<p>Bulldozed road, bears NE. and SW.</p>
22.15	<p>Bulldozed road, bears N. 60° W. and S. 60° E.; asc. 100 ft. over S. slope.</p>

Dependent Resurvey, E. Bdy., T. 6 S., R. 26 E.

Chains	
32.95	Bulldozed road, bears NE. and SW.; asc. 30 ft. over S. slope.
40.47	The $\frac{1}{2}$ sec. cor. of secs. 7 and 12, which is mkd. by a malpais stone, 18x12x12 ins., firmly set, mkd. and witnessed as described in the official record. At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.
	T6S R26E R27E S12 S 7 1960
	Deposit original cor. stone alongside iron post. Rebuild mound of stone, 3 ft. base, 18 ins. high, W. of cor.
	North, beginning new measurement.
5.00	Spur, slopes S.
12.30	Bulldozed road, bears N. 15° E. and S. 15° W.; asc. 160 ft. over S. slope.
30.00	Slope changes to SW.; desc. 40 ft. over NW. side of spur.
37.70	Wash, 30 lks. wide, 2 ft. deep, drains S. 20° W.; asc. 20 ft. over SE. slope of spur.
39.06	The cor. of secs. 1, 6, 7 and 12, which is mkd. by a malpais stone, 18x12x6 ins., firmly set; mkd. and witnessed as described in the official record. At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.
	T6S R26E R27E S 1 S 6 S12 S 7 1960
	Deposit the original cor. stone alongside iron post. Rebuild mound of stone, 3 ft. base, 18 ins. high, W. of cor.
	Land, rolling on general S. and SW. slope; slope of land becoming steeper on N. $\frac{1}{2}$ mile. Soil, gravelly sandy clay. Timber, none. Undergrowth, mesquite, greasewood and cacti.
	N. 0° 04' W., bet. secs. 1 and 6.
	Over rolling land on steep SE. slope, through scattered mesquite. Asc. 230 ft. over steep SE. slope.
14.00	Spur, sloping SW.; desc. 30 ft. along NW. slope.
22.50	Wash, 20 lks. wide, 3 ft. deep, drains S. 15° W.; asc. 250 ft. along steep SE. slope.

Dependent Resurvey, E. Bdy., T. 6 S., R. 26 E.

Chains	
39.63	The $\frac{1}{2}$ sec. cor. of secs. 1 and 6, which is mkd. by a malpais stone, 26x24x12 ins., firmly set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap. mkd.
	T6S R26E R27E
	S 1 S 6
	1960
	Deposit the original cor. stone alongside iron post.
	Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 16' W., beginning new measurement.
	Asc. 400 ft. over steep SE. slope.
18.00	Spur, slopes SW. from shoulder on mountain; asc. 240 ft. ledge and boulderstrewn SE. slope.
26.30	Spur, slopes abruptly W. from mountain; asc. 395 ft. along ledgy W. slope.
38.67	The closing cor. of secs. 1 and 6, which is mkd. by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.
	From this cor. the standard $\frac{1}{2}$ sec. cor. of sec. 36, which is mkd. by an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record, bears N. 89° 45' W., 3.05 chs. dist.
	Land, rolling and broken.
	Soil, rocky, sandy clay.
	Timber, none.
	Undergrowth, mesquite, greasewood and cacti.
	Dependent Resurvey of the South Boundary of T. 6 S., R. 26 E.
	Reestablishment of the resurvey executed by Philip Contzen, U. S. Deputy Surveyor, in 1895.
	From the cor. of Tps. 6 and 7 S., Rs. 26 and 27 E.
	S. 89° 58' W., bet. secs. 1 and 36.
	Over nearly level land, along east-west fence line.
39.80	The $\frac{1}{2}$ sec. cor. of secs. 1 and 36, which is mkd. by a malpais stone 15x8x8 ins., firmly set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.
	T6S R26E
	$\frac{1}{2}$ S36
	S 1
	T7S
	1960

Dependent Resurvey, S. Bdy., T. 6 S., R. 26 E.

Chains

Deposit the original cor. stone alongside iron post.

No evidence of the accessories remains.

S. 89° 55' W., beginning new measurement.

21.05 Graded road, bears N. 65° E. and S. 65° W.

21.30 Four strand barbed wire fence, bears N. 5° E. and S. 5° W.

39.70 The cor. of secs. 1, 2, 35 and 36, which is mkd. by a malpais stone, 15x9x4 ins. firmly set and properly mkd. There is no remaining evidence of the accessories.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R26E

S35 | S36

S 2 | S 1

T7S

1960

Deposit the original cor. stone alongside iron post.

Land, nearly level.

Soil, gravelly sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

S. 89° 59' W., bet. secs. 2 and 35.

Over nearly level land, through scattered mesquite and greasewood.

10.20 Fence, bears N. 15° E. and S. 15° W.

39.97 The ¼ sec. cor. of secs. 2 and 35, which is mkd. by a malpais stone, 24x8x7 ins., firmly set and properly mkd. There is no remaining evidence of the accessories.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.

T6S R26E

¼ S35

S 2

T7S

1960

Deposit the original cor. stone alongside iron post.

N. 88° 58' W., beginning new measurement.

39.65 The cor. of secs. 2, 3, 34 and 35, which is mkd. by a malpais stone, 18x8x6 ins., firmly set and properly mkd. There is no remaining evidence of the accessories.

At the cor. point

Dependent Resurvey, S. Bdy., T. 6-S., R. 26-E.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.

T6S R26E

$\frac{S34}{S 3}$ | $\frac{S35}{S 2}$

T7S

1960

Deposit the original cor. stone alongside post.

Land, nearly level.

Soil, gravelly sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

N. $89^{\circ} 56'$ W., bet. secs. 3 and 34.

Over nearly level land, through scattered mesquite and greasewood.

16.20 Wash, 40 lks. wide, 2 ft. deep, drains N. 45° W.

29.10 Wash, 30 lks. wide, 2 ft. deep, drains N. 30° W.

32.00 Rim of bench, bears NE. and SW.; desc. 130 ft. over steep NW. slope.

39.66 The $\frac{1}{4}$ -sec. cor. of secs. 3 and 34, which is mkd. by a malpais stone, 16x12x12 ins., firmly set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T6S R26E

$\frac{1}{4}$ $\frac{S34}{S 3}$

T7S

1960

Deposit the original cor. stone alongside iron post.

Rebuild the mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

N. $89^{\circ} 50'$ W., beginning new measurement.

Over wash bottom.

3.00 Main channel of wash, 1.00 wide, 3 ft. deep, drains S. 65° W.

15.00 Begin ascent over steep SE. sloping bank; asc. 40 ft.

16.40 Top of bank, bears NE. and SW.; thence over nearly level bench.

23.00 Leave bench; desc. 60 ft. over steep SW. slope.

28.00 Wash, 30 lks. wide, 2 ft. deep, drains S. approximately 6.00 chs. dist. to larger wash; asc. 120 ft. over steep SE. slope.

37.50 Rim of bench, bears NE. and SW.; thence over nearly level land.

BOOK 4815

Dependent Resurvey, S, Bdy., T. 6 S., R. 26 E.

Chains

39.83 The cor. of secs. 3, 4, 33 and 34, which is mkd. by a malpais stone, 12x10x6 ins. firmly set and properly mkd. There is no remaining evidence of the original accessories.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R26E

S33 | S34

S 4 | S 3

T7S

1960

Deposit the original cor. stone alongside iron post.

Raise a mound of stone, 3 ft. base, 18 ins. high, W. of cor.

Land, nearly level to rolling.

Soil, gravelly, sandy clay.

Timber, none.

Undergrowth, mesquite, greasewood and cacti,

N. 89° 51' W., bet. secs. 4 and 33.

Over rolling land through scattered mesquite and greasewood.

4.00 Graded road, bears N. 20° E. and S. 20° W.; desc. 30 ft. over SW. slope.

18.60 Wash, 20 lks. wide, 1 ft. deep, drains S. 20° W.; asc. 20 ft. over SE. slope.

24.00 Low spur, sloping SW.; desc. 30 ft. over SW. slope.

39.85 The 1/4 sec. cor. of secs. 4 and 35, which is mkd. by a malpais stone, 14x8x6 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R26E

S33

1/4 S 4

T7S

1960

Deposit the original cor. stone alongside iron post.

Rebuild the mound of stone, 2 ft. base, 1 1/2 ft. high, N. of the cor.

N. 89° 42' W., beginning new measurement.

Desc. 40 ft. over SW. slope.

14.20 Wash, 2.10 chs. wide, 3 ft. deep, drains S. 20° W.; asc. 40 ft. over E. slope.

26.27 Graded road, bears N. 15° E. and S. 15° W.

26.50 Fence, bears N. 15° E. and S. 15° W.

Dependent Resurvey, S. Bdy., T. 6 S., R. 26 E.

Chains	
37.90	Power line, bears N. 10° E. and S. 10° W.
39.67	The cor. of secs. 4, 5, 32 and 33, which is mkd. by a malpais stone, 15x10x6 ins., firmly set, mkd. and witnessed as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to brass cap mkd. T6S R26E S32 S33 S 5 S 4 T7S 1960 Deposit the original cor. stone alongside iron post. Rebuild the mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Land, rolling and nearly level. Soil, gravelly, sandy clay. Timber, none. Undergrowth, mesquite, greasewood and cacti.
	S. 89° 53' W., bet. secs. 5 and 32. Over nearly level land, through scattered mesquite and greasewood.
8.60	Fence on E. edge of cemetery, bears N. and S.
19.00	Leave cemetery grounds.
21.00	Fence, bears N. 75° W. and S. 75° E.
22.60	Paved road, bears N. 75° W. and S. 75° E. approximately 4 miles to Safford Airport.
39.91	The ¼ sec. cor. of secs. 5 and 32, which is mkd. by a malpais stone, 15x12x7 ins. firmly set and properly mkd. There is no remaining evidence of the bearing trees or the pits. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T6S R26E ¼ S32 S 5 T7S 1960 Deposit the original cor. stone alongside iron post. Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor. N. 89° 58' W., beginning new measurement.
1.20	Graded road, bears N. and S.

4615

Dependent Resurvey, S. Bdy., T. 6 S., R. 26 E.

Chains	
4.40	Track road, bears S. 50° W., and N. 50° E.; desc. 30 ft. over SW. slope.
7.10	Paved road, bears S. 80° W. and N. 80° E.
13.30	Wash, 40 lks. wide, 2 ft. deep, drains S. 65° W.; asc. 80 ft. over steep SE. slope.
24.00	Rim of bench, bears NE. and SW.; thence over nearly level land.
36.00	W. rim of bench, bears irregularly N. and S.; desc. 100 ft. over steep W. slope.
39.45	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.; asc. 10 ft. over steep E. slope.
39.75	Fence, four strand barbed wire, bears N. and S.; asc. 10 ft. over E. slope.
39.93	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground and in a mound of stone, 6 ft. base to brass cap mkd.
	T6S R26E S31 S32 S 6 S 5 T7S 1960
	Land, rolling and nearly level. Soil, gravelly, sandy clay. Timber, none. Undergrowth, scattered mesquite, greasewood and cacti.
	N. 89° 58' W., bet. secs. 6 and 31.
	Over rolling land, through scattered mesquite and greasewood. Asc. 40 ft. over steep E. slope.
1.80	E. edge of bench, bears irregularly N. and S.; thence over nearly level land.
7.00	W. edge of bench, bears NW. and SE.; desc. 60 ft. over steep SW. slope facing bank.
11.35	Power line, bears S. 35° E. and N. 35° W.
13.95	Paved road, bears N. 35° W. and S. 35° E.; Thence over nearly level bottom land.
21.35	Dirt road, bears S. 20° W.
25.60	Power line, bears S. 45° E. and N. 45° W.
29.50	Fence, bears S. 20° W. and N. 20° E.
30.20	Wash, 2.00 chs. wide, 4 ft. deep, drains S. 30° W.
35.80	Dirt road, bears S. 25° W. and N. 25° E.
36.34	Power line, bears S. 10° W. and N. 10° E.

Dependent Resurvey, S. Bdy., T. 6 S., R. 26 E.

Chains

- 39.95 Point for the $\frac{1}{4}$ sec. cor. of sec. 6 only, at proportionate dist.; there is no remaining evidence of the original cor.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base, to brass cap mkd.
- T6S
 $\frac{1}{4}$ S 6
T7S R26E
1960
- 40.10 Fence, bears S. 20° W. and N. 20° E.
- 42.15 Road, bears NE. and SW., 1.50 chs. to farmyard.
- 42.30 Fence cor. bears W. and N., thence along fence.
- 43.29 Point for the $\frac{1}{4}$ sec. cor. of sec. 31, based on a proportionate dist. to protect lot areas as shown upon the original plat approved January 23, 1897.
- At the cor. point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.
- T6S R26E
 $\frac{1}{4}$ S31
1960
- Deposit broken glass at base of iron post.
- From which
- A telephone pole bears N. 40° E. 1.30 chs. dist. the Northeast corner of a porch on North side of house bears South, .50 chs. dist.
- 77.96 The point for the cor. of Tps. 6 and 7 S., Rs. 25 and 26 E., shown to me by a land owner in sec. 31, determined at the intersection of the east edge of an irrigation ditch to the N. and the E.-W. fence; which was the position of the original cor. stone monument. This position is harmoniously related to existing original cors., has long been recognized as the cor. position by adjacent land owners, and is accepted as the best existing evidence of the position of the original cor.
- At the cor. point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
- T6S
R25E R26E
S36 | S31
S 1 | S 6
T7S
1960
- Deposit broken glass at base of iron post.
- From which
- The NW. cor. of cement foundation of well bears N. 35° E., 38 lks. dist.
- Land, E. $\frac{1}{2}$ rolling; W. $\frac{1}{2}$ nearly level.

Dependent Resurvey, S. Bdy., T. 6 S., R. 26 E.

Chains	<p>Soil, E. $\frac{1}{2}$ gravelly, sandy clay; W. $\frac{1}{2}$ deep river loam. Timber, none. Undergrowth, mesquite, greasewood and cacti on E. $\frac{1}{2}$; cleared land on W. $\frac{1}{2}$.</p> <p>Dependent Resurvey, W. Bdy.; T. 6 S., R. 26 E.</p> <hr/> <p>Reestablishment of the resurvey executed by Philip Contzen, U. S. Deputy Surveyor, in 1896.</p> <p>From the cor. of Tps. 6 and 7 S., Rs. 25 and 26 E.</p> <p>N. $0^{\circ} 11'$ E., bet. secs. 31 and 36.</p> <p>Over cultivated land.</p>
27.70	Fence, bears E. and W.
38.10	Fence, bears E. and W.
39.47	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 31, based on a proportionate dist. to protect areas of lots as shown upon the original plat approved January 23, 1897.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E R26E $\frac{1}{4}$ S31 1960</p>
39.86	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 36, T. 6 S., R. 25 E., at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E R26E $\frac{1}{4}$ S36 1960</p> <p>Deposit broken glass at base of iron post.</p>
40.20	Ditch, 20 lks. wide, 3 ft. deep, course NW.
48.33	Fence, bears S. 50° E. and N. 50° W.
48.96	Paved road, bears S. 50° E. and N. 50° W.
51.46	Power line, bears S. 50° E. and N. 50° W.
60.40	Enter rolling land, bears NW. and SE.; asc. 70 ft. along SW. slope.
64.47	Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.
73.80	Wash, 30 lks. wide, 2 ft. deep, drains S. 10° W., asc. 90 ft. over steep S. slope.
79.37	<p>The cor. of secs. 25, 30, 31 and 36, which is mkd. by a malpais stone, 16x8x6 ins., firmly set and mkd. as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to brass cap mkd.</p>

Dependent Resurvey, W. Bdy., T. 6 S., R. 26 E.

Chains

T6S
R25E R26E
S25|S30
S36|S31
1960

Deposit the original cor. stone alongside iron post.

Land, S. 3/4 nearly level cultivated, N. 1/4 rolling.
Soil, S. 3/4 deep river alluvium, loam.
Timber, none.
Undergrowth, scattered mesquite, greasewood and cacti on N. 1/4.

North, bet. secs. 25 and 30.

Over rolling land, through scattered mesquite and greasewood.

Desc. 80 ft. over N. slope.

11.40 Wash, 50 lks. wide, 2 ft. deep, drains S. 25° W.

Asc. 40 ft. over S. slope.

16.00 Top of ascent, thence over nearly level bench.

36.40 Road, bears NE. and SW.

39.86 The 1/2 sec. cor. of secs. 25 and 30, which is mkd. by a malpais stone, 15x8x8 ins., firmly set and properly mkd.; There is no evidence of the accessories.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 2 ft. base, to brass cap mkd.

T6S
R25E R26E
S25|S30
1960

Deposit the original cor. alongside of iron post.

N. 0° 12' E., beginning new measurement.

Desc. 50 ft. over slight N. slope.

7.90 Wash, 20 lks. wide, 2 ft. deep, drains N. 80° W.

20.80 Wash, 25 lks. wide, 2 ft. deep, drains SW.

34.90 Wash, 30 lks. wide, 2 ft. deep, drains S. 60° W.

39.66 The cor. of secs. 19, 24, 25 and 30, which is mkd. by a malpais stone, 15x8x7 ins., firmly set, and properly mkd.; there is no remaining evidence of the accessories.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

BOOK 4615 16

Dependent Resurvey, W. Bdy., T. 6 S., R. 26 E.

Chains

T6S
R25E R26E
S24|S19
S25|S30
1960

Deposit the original cor. stone alongside iron post.

Land, rolling.
Soil, gravelly, sandy clay.
Timber, none.
Undergrowth, mesquite, greasewood and cacti.

N. 0° 01' E., bet. secs. 19 and 24.

Over rolling land on general SW. slope, through scattered mesquite and greasewood.

.25 Fence, bears SW. and NE.

1.60 Wash, 30 lks. wide, 2 ft. deep, drains SW.

26.70 Wash, 6.70 chs. wide, with 8 ft. banks, drains S. 30° W.

39.93 The 1/2 sec. cor. of secs. 19 and 24 which is mkd. by a malpais stone, 18x10x10 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S
R25E R26E
S24|S19
S25|S30
1960

Deposit the original cor. stone alongside iron post.

Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 10' E., beginning new measurement.

1.20 Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.

16.00 Wash, 40 lks. wide, 3 ft. deep, drains S. 40° W.

30.60 Track road, bears SW. and NE.

38.40 Wash, 10 lks. wide, 1 ft. deep, drains S. 40° W.

39.96 The cor. of secs. 13, 18, 19 and 24, which is mkd. by a malpais stone, 15x8x8 ins., firmly set and properly mkd.; there is no remaining evidence of the bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, W. Bdy., T. 6 S., R. 26 E.

Chains

T6S
R25E R26E
S13|S18
S24|S19
1960

Deposit the original cor. stone alongside iron post.

Rebuild the mound of stone, 2½ ft. base, 1 ft. high, W. of cor.

Land, rolling.

Soil, gravelly, sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

N. 0° 08' E., bet. secs. 13 and 18.

Over rolling land, on general SW. slope; through scattered mesquite and greasewood.

7.60 Wash, 40 lks, wide, 2 ft. deep, drains S. 15° W.

34.20 Wash, 30 lks, wide, 2 ft. deep, drains W.

39.75 The ¼ sec. cor. of secs. 13 and 18, which is mkd. by a malpais stone, 18x10x6 ins., firmly set and properly mkd.; there is no evidence of the bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T6S
R25E R26E
½
S13|S18
1960

Deposit the original cor. stone alongside iron post.

Rebuild the mound of stone, 3 ft. base, 18 ins. high W. of cor.

N. 0° 05' E., beginning new measurement.

10.60 Bank of wash, 4 ft. high, bears SW.; thence over series of channels.

16.20 Bank of wash, 6 ft. high, bears SW.; asc, 30 ft. over SW. slope.

39.90 The cor. of secs. 7, 12, 13 and 18, which is mkd. by a malpais stone, 20x12x8 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T6S
R25E R26E
S12|S 7
S13|S18
1960

Deposit the original cor. stone alongside iron post.

Dependent Resurvey, W. Bdy., T. 6 S., R. 26 E.

Chains	
	<p>Rebuild the mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p> <p>Land, rolling on SW. slope. Soil, gravelly, sandy clay. Timber, none. Undergrowth, scattered mesquite, greasewood and cacti.</p>
	<p>N. 0° 10' E., bet. secs. 7 and 12.</p>
	<p>Over rolling land on SW. slope, through scattered brush.</p>
	<p>Asc. 10 ft. over SW. slope.</p>
7.50	<p>Wash, 30 lks. wide, 3 ft. deep, drains SW.; asc. 60 ft. over SW. slope.</p>
39.97	<p>The ¼ sec. cor. of secs. 7 and 12, which is monumented by a malpais stone, 18x10x6 ins., firmly set, mkd. and witnessed as described in the official record.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.</p>
	<p style="text-align: center;">T6S R25E R26E ¼ S12 S 7 1960</p>
	<p>Deposit the original cor. stone alongside iron post.</p>
	<p>Rebuild the mound of stone, 2 ft. base, 18 ins. high, W. of cor.</p>
	<p>N. 0° 15' E., beginning new measurement</p>
	<p>Asc. 10 ft. over SW. slope.</p>
3.55	<p>Wash, 40 lks. wide, 2 ft. deep, drains SW.; asc. 10 ft. over series of washes, draining SW.</p>
14.50	<p>Fence, bears NE. and SW.; cont. to ascend over washes; asc. 40 ft.</p>
34.65	<p>Wash, 70 lks. wide, 4 ft. deep, drains S. 40° W.; asc. 10 ft. over SW. slope.</p>
39.96	<p>The cor. of secs. 1, 6, 7 and 12, which is monumented by a malpais stone, 12x8x6 ins., firmly set and properly mkd.; there is no remaining evidence of the accessories.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base, to brass cap mkd.</p>
	<p style="text-align: center;">T6S R25E R26E S 1 S 6 S12 S 7 1960</p>
	<p>Deposit the original cor. stone alongside iron post.</p>

Dependent Resurvey, W. Bdy., T. 6 S., R. 26 E.

Chains	<p>Land, rolling on SW. slope. Soil, gravelly, rocky; sandy clay. Timber, none. Undergrowth, scattered mesquite, greasewood and cacti.</p>
	<p>N. 0° 17' E., bet. secs. 1 and 6.</p> <p>Over rolling land on general SW. slope; through scattered mesquite greasewood and cacti.</p> <p>Asc. 60 ft. over series of washes, draining SW.</p>
21.30	<p>Wash, 1.50 chs. wide, 3 ft. deep, drains S. 40° W.; asc. 40 ft. over SW. slope.</p>
37.65	<p>Wash, 40 lks. wide, 2 ft. deep, drains S, 40° W.; asc. 20 ft. over SW. slope.</p>
40.11	<p>Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and supported in a mound of stone, 3½ ft. base to brass cap mkd.</p> <p style="text-align: center;">T6S R25E R26E S 1 S 6 1960</p> <p>Asc. 10 ft. over SW. slope.</p>
46.00	<p>Wash, 30 lks. wide, 2 ft. deep, drains S. 20° W.; asc. 90 ft. over SW. slope.</p>
80.06	<p>Intersect the First Standard Parallel South at the closing cor. of T. 6 S., Rs. 25 and 26 E., which is monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record of the resurvey of the First Standard Parallel South, R. 25 E., surveyed in 1920 and 1921.</p> <p>From this closing cor. the standard cor. of T. 5 S., Rs. 25 and 26 E., mkd. and witnessed as described in the official record, bears S. 89° 51' E., 30.12 chs. dist.</p> <p>From the closing cor. the standard ¼ sec. cor. of sec. 36, T. 5 S., R. 25 E., bears N. 89° 51' W., 9.91 chs. dist., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.</p> <p>Land, rolling on general SW. slope. Soil, rocky sandy clay. Timber, none. Undergrowth, mesquite, greasewood and cacti.</p>
<p>Dependent Resurvey of the Subdivisional Lines of T. 6 S., R. 26 E.</p>	
<p>Reestablishment of the survey executed by Philip Contzen, U. S. Deputy Surveyor, in 1896.</p> <p>From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp.</p> <p>N. 0° 42' W., bet. secs. 35 and 36.</p> <p>Over nearly level land, through scattered brush.</p>	

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
21.00	Fence, bears N. 30° E. and S. 30° W.
39.70	Wash, 20 lks. wide, 1 ft. deep, drains S. 50° W.
39.87	The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, which is monumented by a malpais stone, 20x12x8 ins., firmly set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.
	T6S R26E $\frac{1}{4}$ S35 S36 1960
	Deposit the original cor. stone alongside iron post.
	N. 0° 11' W., beginning new measurement.
2.60	Wash, 20 lks. wide, 2 ft. deep, drains S. 60° W.
19.30	Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.
30.40	Dirt road, bears N. 10° W. and S. 10° E.
40.06	The cor. of secs. 25, 26, 35 and 36, which is monumented by a malpais stone, 20x12x10 ins. firmly set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T6S R26E S26 S25 S35 S36 1960
	Deposit the original cor. stone alongside iron post.
	Land, nearly level.
	Soil, gravelly sandy clay.
	Timber, none.
	Undergrowth, mesquite, greasewood and cacti.
	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp.
	S. 89° 50' W., bet. secs. 25 and 36.
	Over nearly level land, through scattered greasewood.
	Desc. 90 ft. over SW. slope.
32.00	Wash, 10 lks. wide, 1 ft. deep, drains S.
40.05	The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, which is monumented by a malpais stone, 15x7x7 ins. firmly set and properly mkd.; there is no remaining evidence of the bearing trees.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Recurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
	<p style="text-align: center;">T6S R26E $\frac{1}{4}$ S25 S36 1960</p> <p>Deposit the original cor. stone alongside of iron post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>S. 89° 50' W., beginning new measurement.</p>
8.50	Dirt road, bears S. 20° W. and N. 20° E.
8.70	Fence, bears S. 20° W. and N. 20° E.
14.70	Wash, 15 lks. wide, 1 ft. deep, drains S.
40.00	The cor. of secs. 25, 26, 35 and 36.
	<p>Land, nearly level. Soil, gravelly, sandy clay. Timber, none. Undergrowth, greasewood and cacti.</p>
	<p>N. 0° 14' W., bet. secs. 25 and 26</p> <p>Over rolling land, through scattered greasewood.</p>
26.00	Dirt road, bears S. 20° W. and N. 20° E.
40.10	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a mound of stone, 2 $\frac{1}{2}$ ft. base, to top of brass cap mkd.
	<p>T6S R26E $\frac{1}{4}$ S26 S25 1960</p>
43.40	Wash, 1.00 ch. wide, with 6 ft. banks, drains S. 80° W.
80.20	The cor. of secs. 23, 24, 25 and 26, which is monumented by a malpais stone, 16x12x6 ins. firmly set and properly mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T6S R26E S23 S24 S25 S26 1960</p>
	Deposit the original cor. stone alongside iron post.
	Rebuild the mound of stone, 2 $\frac{1}{2}$ ft. base, 1 ft. high, W. of cor.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	Land, nearly level bench, sloping SW. Soil, gravelly, sandy clay. Timber, none. Undergrowth, greasewood and cacti.
	From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp. S. 89° 58' W., bet. secs. 24 and 25.
	Over nearly level land, on general SW. slope, through scattered greasewood.
3.20	Dirt road, bears N. and S.
6.90	SE. cor. of tin shed, bears N. 15 lks. dist.
7.20	Water well, bears N. 128 lks.
7.35	Fence, bears N. and S.
9.20	Fence, bears S. 45° E. and N. 45° W.
10.00	Wash, 20 lks. wide, 1 ft. deep, drains SW.
12.20	Wash, 20 lks. wide, 2 ft. deep, drains SW.
37.00	Wash, 20 lks. wide, 3 ft. deep, drains S.
40.15	The 1/2 sec. cor. of secs. 24 and 25, which is monumented by a malpais stone, 18x10x6 ins. firmly set and properly mdkd. there is no remaining evidence of the bearing trees.
	At the cor. point
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to brass cap mdkd.
	T6S R26E
	1/2 S24
	1/2 S25
	1960
	Deposit the original cor. stone alongside iron post.
	S. 89° 57' W., beginning new measurement.
	Over series of washes, draining SW.
40.10	The cor. of secs. 23, 24, 25 and 26.
	Land, nearly level, with general SW. drainage. Soil, gravelly, sandy clay. Timber, none. Undergrowth, greasewood and cacti.
	N. 0° 05' W., bet. secs. 23 and 24.
	Over nearly level land, on SW. slope.
15.00	Dirt road, bears S. 60° E. and N. 60° W.
20.70	Wash, 20 lks. wide, 2 ft. deep, drains S. 50° W.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
27.30	Wash, 20 lks. wide, 2 ft. deep, drains S. 40° W.
40.07	True point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate dist.; falls in wash, 20 lks. wide, 2 ft. deep, where the monument cannot be perpetuated; there is no remaining evidence of the original cor.
40.45	<p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 23 and 24.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to brass cap mkd.</p> <p style="text-align: center;">T6S R26E S23 S24 W.C. 1960</p>
43.70	Dirt road, bears N. 70° E. and S. 70° W.
51.60	Wash, 1.00 ch. wide, with banks 4 ft. high, drains S. 30° W.
74.79	Wash, 1.00 ch. wide, with banks 6 ft. high, drains S. 30° W.
80.14	<p>The cor. of secs. 13, 14, 23 and 24, which is monumented by a malpais stone, 12x12x4 ins., firmly set and properly mkd. to the record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground and in a mound of stone, 3 ft. base, to brass cap mkd.</p> <p style="text-align: center;">T6S R26E S14 S13 S23 S24 1960</p> <p>Deposit the original cor. alongside iron post.</p> <p>Land, nearly level on SW. slope. Soil, gravelly, sandy clay. Timber, none. Undergrowth, greasewood and cacti.</p>
<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp. S. 89° 59' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through scattered greasewood and palo verda.</p>	
2.00	Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.
5.60	Wash, 10 lks. wide, 1 ft. deep, drains S. 15° W.
7.80	Wash, 90 lks. wide, with 3 ft. banks, drains SW.
26.30	Wash, 20 lks. wide, 2 ft. deep, drains SW.
35.10	Wash, 20 lks. wide, 2 ft. deep, drains S.
40.12	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, which is monumented with a malpais stone, 15x10x8 ins., firmly set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base, to brass cap mkd.</p>

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
	<p style="text-align: center;">T6S R26E</p> <p style="text-align: center;">1/2 S13 S24 1960</p> <p>Deposit the original cor. stone alongside iron post.</p>
	<p>S. 89° 57' W., beginning new measurement.</p> <p>Over series of washes, mostly 20 lks. wide, 1 ft. deep, draining SW.</p>
40.10	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, rolling on SW. slope. Soil, gravelly, sandy clay. Timber, none. Undergrowth, greasewood and cacti.</p>
	<p>N. 0° 06' W., bet. secs. 13 and 14</p> <p>Over rolling land on general SW. slope; through scattered greasewood. Asc. 20 ft. over SW. slope.</p>
9.60	Wash, 20 lks. wide, 2 ft. deep, drains S. 50° W.
18.70	Dirt road, bears N. 60° E. and S. 60° W.; asc. 40 ft. over SW. slope.
32.00	Spur, slopes SW.; desc. 20 ft. over NW. slope.
40.11	<p>The 1/2 sec. cor. of secs. 13 and 14, which is monumented with a malpais stone, 20x14x12 ins. firmly set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base, to brass cap mkd.</p> <p style="text-align: center;">T6S R26E</p> <p style="text-align: center;">1/2 S14 S13 1960</p> <p>Deposit the original cor. stone alongside iron post:</p>
	<p>N. 0° 11' W., beginning new measurement.</p>
2.60	Wash, 90 lks. wide, with banks 6 ft. high; asc. 60 ft. over SW. slope, drains SW.
16.00	Degree of slope increases; asc. 270 ft. over boulder strewn S. slope.
34.40	Spur, sloping S. 20° W.; desc. 10 ft. along W. slope.
40.25	<p>The cor. of secs. 11, 12, 13 and 14, which is monumented with a malpais stone, 40x20x12 ins., firmly set, and mkd. as described in the official record.</p> <p>At the cor. point</p>

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground and in a mound of stone, 3 ft. base, to brass cap mkd.

T6S R26E

S11|S12

S14|S13

1960

Deposit the original cor. stone alongside iron post.

Land, rolling on general SW. slope.

Soil, gravelly, sandy clay.

Timber, none.

Undergrowth, greasewood, cacti.

From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp.

N. 89° 54' W., bet. secs. 12 and 13.

Over rolling land, on SW. slope; desc. 10 ft.

- 6.20 Wash, 50 lks. wide, 4 ft. deep, drains SW.; asc. 10 ft. over SW. slope.
- 12.50 Dirt road, bears S. 30° W. and N. 30° E.; desc. 130 ft. over SW. slope.
- 39.55 Wash, 40 lks. wide, 2 ft. deep, drains SW.
- 40.06 The ¼ sec. cor. of secs. 12 and 13, which is monumented by a malpais stone, 24x7x7 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R26E

¼ S12

S13

1960

Deposit the original cor. stone alongside iron post.

Rebuild the mound of stone, 2 ft. base, 18 ins. high, N. of cor.

N. 89° 52' W., beginning new measurement.

- 3.90 Wash, 10 lks. wide, 1 ft. deep, drains S.
- 9.50 Wash, 30 lks. wide, 3 ft. deep, drains S. 10° E.; asc. 10 ft. over SE. slope.
- 14.10 Dirt road, bears N. and S.; asc. 250 ft. over steep SE. slope.
- 36.50 Spur, slopes S. 20° W.; desc. 70 ft. over NW. slope.
- 40.22 The cor. of secs. 11, 12, 13 and 14.

Land, rolling.

Soil, gravelly, sandy clay.

Timber, none.

Undergrowth, greasewood and cacti.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

N. 0° 33' E., bet. secs. 11 and 12.

Over rolling land, through scattered greasewood and mesquite.

Desc. 190 ft. along steep NW. slope.

24.70 Wash, 30 lks. wide, 3 ft. deep, drains S. 30° W.

Asc. 50 ft. over S. slope.

39.00 Spur, sloping S. 10° W.

39.76 The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, which is monumented with a malpais stone, 30x24x20 ins., firmly set and properly mkd.

At the cor. point set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.

T6S R26E

$\frac{1}{4}$

S11 | S12

1960

Deposit the original cor. stone alongside iron post.

N. 0° 12' W., beginning new measurement.

Desc. 20 ft. along SW. slope.

9.80 Dirt road, bears N. 30° E. and S. 30° W.; asc. 20 ft. over SW. slope.

24.00 Wash, 1.00 ch. wide, 4 ft. deep, drains S. 20° W.; 90 ft. along SW. slope.

40.13 The cor. of secs. 1, 2, 11 and 12, which is monumented by a malpais stone, 16x7x7 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to brass cap mkd.

T6S R26E

S 2 | S 1

S11 | S12

1960

Deposit the original cor. stone alongside iron post.

Land, rolling.

Soil, gravelly, sandy clay.

Timber, none.

Undergrowth, mesquite and greasewood.

From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp.

N. 89° 47' W., bet. secs. 1 and 12.

Over rolling land, through scattered greasewood and mesquite.

Asc. 20 ft. over SE. slope.

8.90 Wash, 50 lks. wide, 3 ft. deep, drains S. 20° W.; asc. 10 ft. over E. slope.

BOOK 4016

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
11.50	Dirt road, bears N. 20° W. and S. 20° E.; asc. 10 ft. over E. slope.
21.00	Spur, slopes S.; desc. 20 ft. over W. slope.
24.65	Wash, 40 lks. wide, 4 ft. deep, drains S.; asc. 120 ft. over steep E. slope.
28.60	Track road on spur; road bears S. 25° W. and N. 25° E.; spur slopes S. 25° W.; desc. 200 ft. over steep W. slope.
37.25	Wash, 60 lks. wide, 3 ft. deep, drains S. 25° W.; asc. 60 ft. over steep SE. slope.
39.85	The ¼ sec. cor. of secs. 1 and 12, which is monumented with a malpais stone, 20x8x5 ins., firmly set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base, to brass cap mkd.
	T6S R26E
	S 1
	¼ S12
	1960
	Deposit the original cor. stone alongside iron post.
	Rebuild mound of stone, 2 ft. base, 1 ft. high, N. of cor.

	S. 89° 48' W., beginning new measurement.
	Asc. 80 ft. over steep SE. slope.
5.00	Spur, slopes SW.; desc. 110 ft. over SW. slope.
18.00	Wash, near head, drains SE.; asc. 10 ft. over E. slope.
20.50	Track road, bears S. 30° W. and N. 30° E.
20.60	Spur, slopes N. from hill to the S.; asc. 130 ft. over W. slope.
27.30	Wash, 20 lks. wide, 2 ft. deep, drains S.; asc. 20 ft. over E. slope.
30.00	Spur, sloping SW.; desc. 20 ft. over W. slope.
32.40	Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.; asc. 30 ft. over E. slope.
37.00	Spur, slopes S. 20° W.; desc. 10 ft. over W. slope.
40.13	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling.
	Soil, gravelly, sandy clay.
	Timber, none.
	Undergrowth, mesquite, greasewood and cacti.
	N. 0° 28' W., bet. secs. 1 and 2.
	Over rolling land, on SW. slope, through scattered mesquite and greasewood.
	Asc. 80 ft. over SE. slope.

BOOK 4615

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
9.00	Spur, slopes from NE.; desc. 30 ft. over NW. slope.
13.05	Wash, 50 lks. wide, 4 ft. deep, drains SW.; asc. 100 ft. over SE. slope.
25.00	Spur, slopes SW.; desc. 10 ft. along W. side of spur.
29.75	Fence, bears N. 60° W. and S. 60° E.
37.82	The witness $\frac{1}{4}$ sec. cor. of secs. 1 and 2, which is monumented by a malpais stone, 20x10x6 ins., firmly set and properly mkd.
	<p>At the point for the witness cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T6S R26E WIC S 2 S 1 1960</p>
	Deposit the original cor. stone alongside iron post.
	Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.
40.10	True point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at record dist. from its witness cor. falls in wash, 20 lks. wide, 3 ft. deep, drains SW., where the monument cannot be perpetuated.
	N. 0° 04' W., beginning new measurement.
2.70	Enter wash, 4 chs. wide, 3 ft. deep, drains S. 20° W.
5.70	Bulldozed road, bears N. 20° E. and S. 20° W.
12.40	Wash, 30 lks. wide, 2 ft. deep, drains S. 10° W.; asc. 140 ft. over SE. slope.
27.00	Spur, slopes SW.; desc. 60 ft. along NW. slope.
35.00	End of bulldozed road, bears N. 50° W. approximately 2.00 chs.; thence curves SW.; asc. 40 ft. over S. slope.
38.44	Intersect First Standard Parallel South at the closing cor. of secs. 1 and 2, which is monumented by an iron post, 2 ins. diam., set 6½ ins. in the ground, surrounded with a mound of stone, 3 ft. diam., 2 ft. high and with brass cap mkd.
	<p>T5S R26E S 2 S 1 T6S R26E C C 1920</p>
	From this point the standard $\frac{1}{4}$ sec. cor. of sec. 35 bears N. 89° 54' W., 2.84 chs. dist., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.
	<p>Land, rolling. Soil, gravelly, sandy clay. Timber, none. Undergrowth, mesquite, greasewood and cacti.</p>

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

Point for the N. $\frac{1}{2}$ sec. cor. of sec. 1 at midpoint and on the N. bdy. of the Tp.

Set an iron post, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground surrounded with a mound of stone, 4 ft. base 15 ins. high, and with brass cap mkd.

S 1
T6S R26E
1960

From this point the standard cor. of secs. 35 and 36, T. 5 S., R. 26 E. bears N. $89^{\circ} 47' W.$, 2.97 chs. dist., monumented with an iron post 2 ins. diam., set 8 ins. in the ground and surrounded with a mound of stone, 3 ft. base, 20 ins. high and with brass cap mkd.

S | C
T5S | R26E
S35 | S36
1920

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp.

N. $0^{\circ} 46' W.$, bet. secs. 34 and 35.

Over nearly level land, through scattered mesquite and greasewood.

Desc. 60 ft. over slight NW. slope.

13.30 Wash, 30 lks. wide, 2 ft. deep, drains W.; asc. 20 ft. along W. slope.

23.60 Wash, 50 lks. wide, with banks 6 ft. high, drains S. $25^{\circ} W.$; asc. 20 ft. along W. slope.

37.45 The witness $\frac{1}{2}$ sec. cor. of secs. 34 and 35, which is monumented by a malpais stone, 20x12x7 ins., firmly set and mkd.

At the witness point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.

T6S R26E
W | C
 $\frac{1}{2}$
S34 | S35
1960

Deposit the original cor. stone alongside iron post.

39.17 True point for the $\frac{1}{2}$ sec. cor. of secs. 34 and 35, at record dist. from its witness cor. falls in wash, 50 lks. wide, with banks, 6 ft. high, draining S. $5^{\circ} W.$, where the monument cannot be perpetuated.

N. $0^{\circ} 50' W.$, beginning new measurement.

Over rolling land.

18.30 Wash, 20 lks. wide, 4 ft. deep, drains W.

29.20 Track road, bears N. $80^{\circ} E.$ and S. $80^{\circ} W.$

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

- 40.07 The cor. of secs. 26, 27, 34 and 35, which is monumented by a malpais stone, 20x12x10 ins. firmly set and properly mkd. There is no remaining evidence of the bearing trees.
- At the cor. point
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.
- T6S R26E
S27 | S26
S34 | S35
1960
- Deposit the original cor. stone alongside iron post.
- Rebuild mound of stone, 2½ ft. base 1 ft. high W. of cor.
- Land, nearly level.
Soil, gravelly, sandy clay.
Timber, none.
Undergrowth, mesquite, greasewood and cacti.
-
- From the cor. of secs. 25, 26, 35 and 36.
- S. 89° 59' W., bet. secs. 26 and 35.
- Over gently rolling land, through scattered mesquite and greasewood.
- 6.40 Bulldozed road, bears S. 20° W. and N. 20° E.
- 8.30 Wash, 10 lks. wide, 1 ft. deep, drains S.
- 17.40 Wash, 10 lks. wide, 1 ft. deep, drains S.
- 31.40 Wash, 60 lks. wide, 3 ft. deep, drains S.
- 40.04 The ¼ sec. cor. of secs. 26 and 35, which is monumented by a malpais stone, 12x8x6 ins. firmly set, mkd. and witnessed as described in the official record.
- At the cor. point
- Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base to brass cap mkd.
- T6S R26E
¼ S26
S35
1960
- Deposit the original cor. stone alongside iron post.
- Rebuild the mound of stone, 2 ft. base, 1 ft. high N. of cor.
-
- S. 89° 59' W., beginning new measurement.
- Over gently rolling land.
- 14.20 Wash, 10 lks. wide, 1 ft. deep, drains SW.
- 34.80 Bulldozed road, bears S. 70° E. and N. 70° W.
- 40.04 The cor. of secs. 26, 27, 34 and 35.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
	<p>Land, nearly level to gently rolling. Soil, gravelly, sandy clay. Timber, none. Undergrowth, scattered greasewood and cacti.</p>
	<p>North, bet. secs. 26 and 27.</p> <p>Over gently rolling land; through scattered greasewood and mesquite.</p>
1.80	Bulldozed road, bears S. 70° E. and N. 70° W.
18.20	Wash, 20 lks. wide, with banks 4 ft. high, drains SW.
22.70	Bulldozed road, bears N. 30° E. and S. 30° W.
31.50	Wash, 20 lks. wide, 2 ft. deep, drains SW.
40.03	<p>The ¼ sec. cor. of secs. 26 and 27, which is monumented by a malpais stone, 12x9x9 ins. firmly set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R26E ¼ S27 S26 1960</p> <p>Deposit the original cor. stone alongside iron post.</p> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Over gently rolling land.</p>
3.40	Wash, 30 lks. wide, with banks 4 ft. high, drains SW.
32.30	Wash, 20 lks. wide, 3 ft. deep, drains S. 30° W.
40.05	<p>The cor. of secs. 22, 23, 26 and 27, which is monumented by a malpais stone, 16x12x8 ins., firmly set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.</p> <p style="text-align: center;">T6S R26E S22 S23 S27 S26 1960</p> <p>Deposit the original cor. stone alongside iron post.</p> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Land, gently rolling. Soil, gravelly sandy clay. Timber, none. Undergrowth, mesquite, greasewood and cacti.</p>

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
	From the cor. of secs. 23, 24, 25 and 26.
	S. 89° 54' W., bet. secs. 23 and 26.
	Over nearly level land on SW. slope, through scattered mesquite and greasewood.
24.20	Wash, 10 lks. wide, 1 ft. deep, drains SW.
33.20	Wash, 20 lks. wide, 1 ft. deep, drains S. 20° W.
39.96	The $\frac{1}{2}$ sec. cor. of secs. 23 and 26, which is monumented by a malpais stone, 12x7x7 ins. firmly set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3 $\frac{1}{2}$ ft. base to brass cap mkd.
	T6S R26E.
	$\frac{1}{2}$ S23
	S26
	1960
	Deposit the original cor. stone alongside iron post.
	Rebuild mound of stone, 2 ft. base, 1 ft. high N. of cor.
	S. 89° 52' W., beginning new measurement.
	Over gently rolling land.
19.95	Wash, 30 lks. wide, 2 ft. deep, drains SW.
36.85	Wash, 20 lks. wide, 2 ft. deep, drains S.
39.91	The cor. of secs. 22, 23, 26 and 27.
	Land, nearly level to gently rolling on SW. slope.
	Soil, gravelly, sandy clay.
	Timber, none.
	Undergrowth, mesquite, greasewood and cacti.
	N. 0° 17' W., bet. secs. 22 and 23.
	Over nearly level bench land on general SW. slope, through scattered mesquite and greasewood.
	Asc. 60 ft. over SW. slope.
40.11	The $\frac{1}{2}$ sec. cor. of secs. 22 and 23, which monumented by a malpais stone, 15x14x4 ins. firmly set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
	<p style="text-align: center;">T6S R26E $\frac{1}{2}$ S22 S23 1960</p> <p>Deposit the original cor. stone alongside iron post.</p> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p style="text-align: center;">-----</p> <p>N. 0° 06' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
2.80	Wash, 30 lks. wide, 2 ft. deep, drains SW.; asc. 20 ft. along SW. slope.
20.60	Wash, 30 lks. wide, 3 ft. deep, drains S. 30° W.; asc. 10 ft. over SW. slope.
30.00	Bulldozed road, on curve, bears NE. and S. 80° W.; asc. 10 ft. over SW. slope.
40.14	The cor. of secs. 14, 15, 22 and 23, which is mkd. by a malpais stone 24x8x8 ins., firmly set and properly mkd. There is no remaining evidence of the bearing trees.
	<p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">T6S R26E S15 S14 S22 S23 1960</p> <p>Deposit the original cor. stone alongside iron post.</p> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high W. of cor.</p> <p>Land, nearly level to gently rolling.</p> <p>Soil, shallow, gravelly sandy clay.</p> <p>Timber, none.</p> <p>Undergrowth, greasewood and mesquite.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89° 58' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land, through scattered greasewood and mesquite.</p> <p>Desc. 10 ft. along SW. slope.</p>
8.20	Wash, 10 lks. wide, 3 ft. deep, drains SW.; desc. 50 ft. over SW. slope.
33.90	Wash, 1.10 ch. wide, 3 ft. deep, drains S. 40° W.
37.10	Wash, 20 lks. wide, 2 ft. deep, drains S. 20° W.
39.99	The ½ sec. cor. of secs. 14 and 23, which is monumented by a malpais stone, 15x12x6 ins., firmly set, mkd. and witnessed as described in the official record.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base to brass cap mkd.

T6S R26E

¼ S14

S23

1960

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, 2 ft. base, 1 ft. high N. of cor.

S. 89° 58' W., beginning new measurement.

Over gently rolling land, cut by series of washes, draining SW.

31.50 Bulldozed road, bears S. 40° W. and N. 40° E.

36.50 Wash, 40 lks. wide, 4 ft. deep, drains S.

38.65 Jeep trail, bears N. and S.

40.03 The cor. of secs. 14, 15, 22 and 23.

Land, nearly level to rolling bench.

Soil, shallow gravelly sandy clay.

Timber, none.

Undergrowth, mesquite, greasewood and cacti.

N. 0° 07' E., bet. secs. 14 and 15.

Over rolling bench land on SW. slope, through scattered mesquite and greasewood.

6.90 Bulldozed road, bears N. 20° E. and S. 20° W.; asc. 30 ft. over SW. slope.

40.42 The ¼ sec. cor. of secs. 14 and 15, which is monumented by a malpais stone, 20x12x9 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T6S R26E

¼ S15

S14

1960

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.

North, beginning new measurement.

Over rolling bench land.

BOOK 400

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
4.00	Wash, 20 lks. wide, 2 ft. deep, drains S. 20° W.; asc. 10 ft. over SW. slope.
19.20	Wash, 20 lks. wide, 2 ft. deep, drains SW.; asc. 30 ft. over SW. slope.
33.40	Bulldozed road, bears S. 60° E. and N. 60° W.
40.15	The cor. of secs. 10, 11, 14 and 15, which is monumented by a malpais stone, 15x12x8 ins., firmly set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.
	T6S R26E S10 S11 S15 S14 1960
	Deposit the original cor. stone alongside iron post.
	Rebuild the mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	Land, rolling bench.
	Soil, shallow, gravelly sandy clay.
	Timber, none.
	Undergrowth, mesquite, greasewood and cacti.
	From the cor. of secs. 11, 12, 13 and 14.
	N. 89° 50' W., bet. secs. 11 and 14.
	Over rolling bench land, through scattered mesquite and greasewood.
	Desc. 260 ft. over boulder strewn W. slope.
10.50	Wash, 30 lks. wide, 1 ft. deep, drains S.; thence over rolling bench.
13.10	Wash, 60 lks. wide, 2 ft. deep, drains S.; desc. 20 ft. over SW. slope.
18.30	Bulldozed road, bears S. 60° W. and N. 60° E.
20.00	Wash, near head, drains S. 20° W.
28.05	Bulldozed road, bears S. 80° E. and N. 80° W.
36.35	Wash, 20 lks. wide, 2 ft. deep, drains S. 20° W.
39.82	The ¼ sec. cor. of secs. 11 and 14, which is monumented by a malpais stone, 18x12x10 ins., firmly set and properly mkd.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base to brass cap mkd.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

T6S R26E

 $\frac{1}{4}$ S11
 S14

1960

Deposit the original cor. stone alongside iron post.

N. 89° 50' W., beginning new measurement.

Over rolling land.

3.50 Wash, 20 lks. wide, 2 ft. deep, drains SW.; desc. 20 ft. over SW. slope.

10.70 Graded road, bears S. 20° W. and N. 20° E.; desc. 10 ft. over SW. slope.

16.00 Wash, 1.50 chs. wide, 2 ft. deep, drains SW.; desc. 20 ft. over SW. slope.

35.20 Wash, 40 lks. wide, 3 ft. deep, drains SW.

38.80 Bulldozed road, bears N. and S.

40.01 The cor. of secs. 10, 11, 14 and 15.

Land, rolling.

Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, mesquite, greasewood and cacti.

N. 0° 02' W., bet. secs. 10 and 11.

Over-rolling land on SW. slope, through scattered mesquite and greasewood.

Asc. 40 ft. over SE. slope.

19.50 Bulldozed road, bears N. 10° W. and S. 10° E.; asc. 20 ft. over SE. slope.

26.00 Same road as noted above, bears N. 10° E. and S. 10° W.; asc. 80 ft. over SE. slope.

34.50 Spur, slopes SW.; desc. 60 ft. over NW. slope.

40.11 The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, which is monumented by a malpais stone, 20x12x6 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.

T6S R26E

 $\frac{1}{4}$ S10 | S11
 1960

Deposit the original cor. stone alongside iron post.

N. 0° 02' E., beginning new measurement.

Over rolling land.

BOOK 4616

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains									
	Desc. 20 ft. over NW. slope.								
2.40	Wash, 20 lks. wide, 2 ft. deep, drains S. 50° W.; asc. 100 ft. over SE. slope.								
13.00	Spur, slopes SW.; desc. 80 ft. over NW. slope.								
22.40	Wash, 20 lks. wide, with banks 5 ft. high, drains S. 30° W; asc. 140 ft. over SE. slope.								
36.50	Point of spur, sloping from the NE.; desc. 40 ft. over NW. slope.								
40.01	The cor. of secs. 2, 3, 10 and 11, which is monumented by a malpais stone, 18x12x6 ins., firmly set and properly mkd.								
	At the cor. point								
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to brass cap mkd.								
	<table style="margin: auto;"> <tr><td colspan="2">T6S R26E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td colspan="2">1960</td></tr> </table>	T6S R26E		S 3	S 2	S10	S11	1960	
T6S R26E									
S 3	S 2								
S10	S11								
1960									
	Deposit the original cor. stone alongside iron post.								
	Land, rolling on SW. slope.								
	Soil, gravelly, sandy clay.								
	Timber, none.								
	Undergrowth, mesquite, greasewood and cacti.								
	From the cor. of secs. 1, 2, 11 and 12.								
	N. 89° 23' W., bet. secs. 2 and 11.								
	Over rolling land, on steep SW. slope; through scattered mesquite and greasewood.								
	Desc. 20 ft. over W. slope.								
3.80	Wash, 10 lks. wide, 1 ft. deep, drains S.; asc. 60 ft. over SE. slope.								
8.40	Ridge, bears S. 30° W. and N. 30° E.; desc. 30 ft. over NW. slope.								
13.50	Wash, 35 lks. wide, 2 ft. deep, drains S.; asc. 80 ft. over E. slope.								
18.10	Elbow of spur, bears N. 40° E. and S.; desc. 120 ft. over W. slope.								
27.40	Wash, 1.00 ch. wide, 2 ft. deep, drains S. 40° W.; asc. 20 ft. along S. slope.								
31.40	Graded road, bears N. and S.								
35.00	Wash, 40 lks. wide, 2 ft. deep, drains S.; asc. 20 ft. over E. slope.								
40.14	The ¼ sec. cor. of secs. 2 and 11, which is mkd. by a malpais stone 24x14x4 ins., firmly set, mkd. and witnessed as described in the official record.								
	At the cor. point								
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 2 ft. base to brass cap mkd.								

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

T6S R26E

 $\frac{1}{4}$ S 2
S 11

1960

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, 2 ft. base, 1 ft. high, N. of cor.

S. 89° 59' W., beginning new measurement.

Over rolling land.

Asc. 10 ft. over E. slope.

1.70 Spur, slopes S.; desc. 50 ft. over W. slope.

4.80 Wash, 15 lks. wide, 1 ft. deep, drains S.; asc. 100 ft. over SE. slope.

13.50 Spur, sloping S. 15° W.; desc. 80 ft. over W. slope.

17.00 Wash, 20 lks. wide, 2 ft. deep, drains S.; asc. 50 ft. over E. slope.

22.80 Spur, slopes SW.; desc. 100 ft. over NW. slope.

27.50 Wash, 30 lks. wide, 2 ft. deep, drains S. 30° W.; asc. 120 ft. over SE. slope.

35.50 Spur, slopes SW.; desc. 80 ft. along NW. slope.

39.88 The cor. of secs. 2, 3, 10 and 11.

Land, rolling on SW. slope.

Soil, shallow, sandy clay.

Timber, none.

Undergrowth, scattered mesquite and greasewood.

N. 0° 19' W., bet. secs. 2 and 3.

Over rolling land on SW. slope; through scattered mesquite and greasewood.

Desc. 40 ft. along NW. slope.

4.40 Wash, 35 lks. wide, 4 ft. deep, drains S. 20° W.; asc. 140 ft. over SE. slope.

18.60 Spur, slopes SW.; desc. 20 ft. along W. slope.

39.92 The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, which is monumented by a malpais stone, 18x7x5 ins. firmly set and properly mkd. There is no remaining evidence of the bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.

T6S R26E

 $\frac{1}{4}$ S 3 | S 12

1960

Deposit the original cor. stone alongside iron post.

BOOK 4817

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

N. 0° 14' W., beginning new measurement.

Over rolling land.

1.50 Wash, 2.00 chs. wide, with banks 5 ft. high, drains SW.; asc. 140 ft. over SE. slope.

19.00 Spur, slopes SW.; desc. 80 ft. over NW. slope.

24.90 Wash, 20 lks. wide, 2 ft. deep, drains W.; asc. 50 ft. over S. slope.

29.00 Spur, sloping W.; desc. 40 ft. over N. slope.

33.50 Small wash, near head, drains S. 50° W.; asc. 20 ft. over SE. slope.

36.00 Spur, sloping W.; desc. 10 ft. over N. slope.

38.27 Intersect the First Standard Parallel South at the closing cor. of secs. 2 and 3, which is monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

From this point the standard $\frac{1}{4}$ sec. cor. of sec. 34 bears N. 89° 52' W., 2.99 chs. dist., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

Land, rolling.

Soil, shallow, sandy clay.

Timber, none.

Undergrowth, scattered mesquite and greasewood.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 2 is at mispoint and on the N. bdy. of the Tp.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.

T5S R26E

 $\frac{1}{4}$ S 2

T6S R26E

1960

From this cor. the standard cor. of secs. 34 and 35, T. 5 S., R. 26 E. which is mkd. by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears W. 2.90 chs. dist.

From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp.

N. 01° 14' W., bet. secs. 33 and 34.

Over gently rolling land, through scattered mesquite and greasewood.

Asc. 60 ft. over SW. slope.

9.50 Track road, bears N. 20° E. and S. 20° W.; thence over nearly level bench land.

39.29 The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, which is mkd. by a malpais stone 16x8x6 ins., firmly set and properly mkd. There is no remaining evidence of the bearing trees.

Dependent Resurvey, Subdivisional Lines, T. 16 S., R. 26 E.

Chains

At the cor. point.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to brass cap mkd.

T6S R26E
 $\frac{1}{4}$
 S33|S34
 1960

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.

N. 01° 14' W., beginning new measurement.

Over nearly level bench land.

8.00 Wash, 15 lks. wide, 1 ft. deep, drains W.

23.00 Wash, 15 lks. wide, 4 ft. deep, drains W.

28.00 S. bank of wash, bears SW.; thence over series of flood channels.

39.00 N. bank of wash, bears SW. and NE.

39.94 Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd.

T6S R26E
 S28|S27
 S33|S34
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level bench.
 Soil, shallow, gravelly sandy clay.
 Timber, none.
 Undergrowth, mesquite and greasewood.

From the cor. of secs. 26, 27, 34 and 35:

S. 89° 59' W., bet. secs. 27 and 34.

Over nearly level land, through scattered mesquite and greasewood.

14.90 Track road, bears S. 20° W. and N. 20° E.

30.10 Track road, bears N. and S.

35.40 Wash, 15 lks. wide, with banks 3 ft. high, drains SW.

40.07 The ¼ sec. cor. of secs. 27 and 34, which is monumented by a malpais stone, 12x8x6 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

T6S R26E

S27

¼ S34

1960

Rebuild mound of stone, 2 ft. base, 1 ft. high N. of cor.

Deposit the original cor. stone alongside iron post.

N. 89° 50' W., beginning new measurement.

Over nearly level land.

1.50 Wash, 10 lks. wide, 2 ft. deep, drains NW.

12.80 Wash, 10 lks. wide, 2 ft. deep, drains N. 20° W.

24.20 Wash, 15 lks. wide, 3 ft. deep, drains NW.

28.80 Wash, 30 lks. wide, 2 ft. deep, drains SW.

35.50 Wash, 1.10 chs. wide, 3 ft. deep, drains SW.

40.10 The cor. of secs. 27, 28, 33 and 34.

Land, nearly level bench.

Soil, gravelly sandy clay.

Timber, none.

Undergrowth, greasewood, mesquite and cacti.

N. 0° 02' W., bet. secs. 27 and 28.

Over nearly level land, through scattered mesquite and greasewood.

Asc. 20 ft. over SE. slope.

3.00 Edge of bench, bears NE. and SW.

22.40 Graded road, bears S. 50° W. and N. 50° E.

34.20 Wash, 10 lks. wide, with banks 3 ft. high, drains S. 40° W.

39.93 The ¼ sec. cor. of secs. 27 and 28, which is monumented by a malpais stone, 14x8x7 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T6S R26E

S28 | S27

1960

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, 2 ft. base, 1 ft. high W. of cor.

N. 0° 09' W., beginning new measurement.

Over nearly level land.

BOOK 4615

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
7.30	Wash, 20 lks. wide, 4 ft. deep, drains S. 40° W.; asc. 20 ft. over SW. slope.
40.13	<p>The cor. of secs. 21, 22, 27 and 28, which is monumented by a malpais stone, 15x12x10 ins. firmly set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.</p> <p style="text-align: center;">T6S R26E S21 S22 S28 S27 1960</p> <p>Deposit the original cor. stone alongside iron post.</p> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Land, nearly level.</p> <p>Soil, shallow, gravelly sandy clay.</p> <p>Timber, none.</p> <p>Undergrowth, mesquite, greasewood and cacti.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89° 56' W., bet. secs. 22 and 27.</p> <p>Over nearly level land, cut by numerous washes, draining SW.; through scattered mesquite and greasewood.</p> <p>Desc. 20 ft. along SW. slope to ¼ sec. cor.</p>
3.00	Wash, 20 lks. wide, 2 ft. deep, drains S.
9.05	Wash, 10 lks. wide, 1 ft. deep, drains SW.
10.95	Wash, 10 lks. wide, 1 ft. deep, drains S.
17.90	Wash, 10 lks. wide, 1 ft. deep, drains SW.
24.05	Wash, 10 lks. wide, 1 ft. deep, drains SW.
26.90	Wash, 40 lks. wide, 3 ft. deep, drains S. 20° E.
33.80	Wash, 10 lks. wide, 1 ft. deep, drains S.
37.90	Wash, 10 lks. wide, 1 ft. deep, drains SW.
39.60	Wash, 10 lks. wide, 2 ft. deep, drains S.
40.13	<p>The ¼ sec. cor. of secs. 22 and 27, which is monumented by a malpais stone, 15x10x9 ins. firmly set and properly mkd., with mound of stone N. There is no remaining evidence of the original bearing trees.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base to brass cap mkd.</p> <p style="text-align: center;">T6S R26E ¼ S22 S27 1960</p>

BOOK 4015

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

Deposit the original cor. stone alongside iron post.

N. 89° 48' W., beginning new measurement.

Over nearly level land.

Desc. 20 ft. along SW. slope to sec. cor.

1.10 Wash, 30 lks. wide, 2 ft. deep, drains SW.

4.20 Wash, 10 lks. wide, 1 ft. deep, drains S.

6.30 Graded road, bears S. 20° W. and N. 20° E.

9.85 Wash, 35 lks. wide, 2 ft. deep, drains S. 20° W.

12.05 Wash, 10 lks. wide, 1 ft. deep, drains S.

13.70 Track road, bears N. and S.

17.80 Wash, 10 lks. wide, 1 ft. deep, drains SE.

21.30 Wash, 10 lks. wide, 2 ft. deep, drains S.

25.65 Wash, 10 lks. wide, 3 ft. deep, drains S.

40.18 The cor. of secs. 21, 22, 27 and 28.

Land, nearly level bench.

Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, mesquite, greasewood and cacti.

N. 0° 09' W., bet. secs. 21 and 22.

Over rolling land, through scattered mesquite and greasewood.

Asc. 30 ft. over slight SW. slope to ¼ sec. cor.

26.50 Wash, 30 lks. wide, 2 ft. deep, drains SW.

40.14 The ¼ sec. cor. of secs. 21 and 22, which is monumented by a malpais stone, 18x8x6 ins., firmly set, mkd, and witnessed as described in the official records.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd,

T6S R26E

¼

S21 | S22

1960

Deposit the original cor. stone alongside iron post.

Rebuild the mound of stone, 2 ft. base, 1 ft. high, W. of cor.

N. 0° 07' W., beginning new measurement.

Over rolling land.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

3.30 Wash, 10 lks. wide, 2 ft. deep, drains S. 40° W.

6.50 Wash, 15 lks. wide, 2 ft. deep, drains S. 30° W.

21.40 Wash, 10 lks. wide, 3 ft. deep, drains S. 30° W.

40.14 The cor. of secs. 15, 16, 21 and 22, which is monumented by a malpais stone, 14x14x5 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.

T6S R26E	
S16	S15
S21	S22
1960	

Deposit the original cor. stone alongside iron post.

Land, rolling and nearly level.

Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

From the cor. of secs. 14, 15, 22 and 23.

N. 89° 58' W., bet. secs. 15 and 22.

Over rolling land on SW. slope, through scattered mesquite and greasewood.

3.40 Graded road, bears S. 20° W. and N. 20° E.

8.20 Wash, 10 lks. wide, 1 ft. deep, drains SW.

20.40 Wash, 10 lks. wide, 1 ft. deep, drains SW.

27.00 Wash, 35 lks. wide, 1 ft. deep, drains S.

37.15 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.

40.09 The ¼ sec. cor. of secs. 15 and 22, which is monumented by a malpais stone, 18x18x10 ins., firmly set and properly mkd. with mound of stone to N. There is no remaining evidence of the bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base to brass cap mkd.

T6S R26E	
¼ S15	
¼ S22	
1960	

Deposit the original cor. stone alongside iron post.

N. 89° 56' W., beginning new measurement.

Over rolling land.

1.80 Wash, 10 lks. wide, 1 ft. deep, drains S.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
7.30	Wash, 20 lks. wide, 1 ft. deep, drains S.
12.00	Wash, 25 lks. wide, 2 ft. deep, drains SW.
28.30	Wash, 10 lks. wide, 1 ft. deep, drains S.
30.50	Wash, 10 lks. wide, 1 ft. deep, drains S.
35.10	Wash, 15 lks. wide, 1 ft. deep, drains S.
40.10	The cor. of secs. 15, 16, 21 and 22.
	Land, rolling. Soil, shallow, sandy clay. Timber, none. Undergrowth, mesquite, greasewood and cacti.
	N. 0° 11' W., bet. secs. 15 and 16.
	Over nearly level land, through scattered mesquite and greasewood.
4.20	Wash, 20 lks. wide, 2 ft. deep, drains S. 10° W.; asc. 60 ft. over SW. slope.
40.09	The $\frac{1}{2}$ sec. cor. of secs. 15 and 16, which is monumented by a malpais stone, 18x12x5 ins. firmly set and properly mkd., with a mound of stone to the N.
	At the cor. point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 $\frac{1}{2}$ ft. base to brass cap mkd.
	T6S R26E $\frac{1}{2}$ S16 S15 1960
	Deposit the original cor. stone alongside iron post.
	N. 0° 04' W., beginning new measurement.
	Over rolling land.
14.40	Wash, 30 lks. wide, 3 ft. deep, drains S. 10° W.
36.60	Fence, bears W. and E. for 7.00 chs. thence N.
40.15	The cor. of secs. 9, 10, 15 and 16 which is monumented by a malpais stone, 15x8x6 ins. firmly set and properly mkd., with a mound of stone N. of cor., all according to the record.
	At the cor. point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3 $\frac{1}{2}$ ft. base to brass cap mkd.
	T6S R26E S 9 S10 S16 S15 1960

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

Deposit the original cor. stone alongside iron post.
 Land, rolling bench, with general SW. slope.
 Soil, shallow, sandy, gravelly clay.
 Timber, none.
 Undergrowth, scattered mesquite, greasewood and cacti.

From the cor. of secs. 10, 11, 14 and 15.

S. 89° 23' W., bet. secs. 10 and 15.

Over rolling land, through scattered mesquite and greasewood.

- 10.00 Wash, 30 lks. wide, 3 ft. deep, drains S. 20° W.
- 10.90 Bulldozed road, bears SE. and NW.
- 24.30 Wash, 20 lks. wide, 2 ft. deep, drains SW.
- 29.20 Wash, 15 lks. wide, 1 ft. deep, drains SE.
- 36.90 Small drainage, drains S.
- 40.41 The ¼ sec. cor. of secs. 10 and 15, which is monumented by a malpais stone, 20x12x12 ins., firmly set, mkd. and witnessed as described in the official records.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 2 ft. base, to brass cap mkd.

T6S R26E

¼ S10
 ¼ S15
 1960

Deposit the original cor. stone alongside iron post.

N. 89° 50' W., beginning new measurement.

Over nearly level land.

- 5.90 Wash, 2.00 chs. wide, with banks 2 ft. high, drains S.
- 10.00 Wash, 10 lks. wide, 1 ft. deep, drains S.
- 19.90 Wash, 15 lks. wide, 1 ft. deep, drains SE.
- 29.50 Wash, 30 lks. wide, 2 ft. deep, drains S.
- 33.20 Fence, bears N. and S.
- 35.70 Wash, 10 lks. wide, 1 ft. deep, drains S.
- 40.09 The cor. of secs. 9, 10, 15 and 16.

Land, rolling bench.
 Soil, gravelly, sandy clay.
 Timber, none.
 Undergrowth, scattered mesquite, greasewood and cacti.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

N. 0° 09' W., bet. secs. 9 and 10.

Over rolling land on SW. slope, through scattered mesquite and greasewood.

Asc. 50 ft. over SW. slope.

27.20 Wash, 20 lks. wide, with banks 4 ft. high, drains S. 40° W.

40.13 The 1/4 sec. cor. of secs. 9 and 10, which is monumented by a malpais stone, 18x10x10 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 1/2 ft. base to brass cap mkd.

T6S R26E
1/4
S 9 | S10
1960

Deposit the original cor. stone alongside iron post.

N. 0° 06' W., beginning new measurement.

Over rolling land; asc. 40 ft. over SW. slope to sec. cor.

19.60 Wash, 15 lks. wide, 3 ft. deep, drains S. 50° W.

31.70 Wash, 20 lks. wide, with banks 6 ft. high, drains S. 50° W.

34.10 Wash, 20 lks. wide, with banks 6 ft. high, drains S. 50° W.

40.12 The cor. of secs. 3, 4, 9 and 10, which is monumented by a malpais stone, 12x7x6 ins. firmly set and properly mkd., with a mound of stone, 2 ft. base, 1 ft. high, W. of monument. There is no remaining evidence of the bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 1/2 ft. base to brass cap mkd.

T6S R26E
S 4 | S 3
S 9 | S10
1960

Deposit the original cor. stone alongside iron post.

Land, rolling bench on SW. slope.

Soil, shallow, gravelly, sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

From the cor. of secs. 2, 3, 10 and 11.

S. 89° 40' W., bet. secs. 3 and 10.

Over rolling hills on SW. slope, through scattered mesquite and greasewood.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
4.60	Wash, 40 lks. wide, 3 ft. deep, drains SW. Track road follows wash, NE. and SW.
7.90	Begin ascent over steep boulder strewn SE. slope; asc. 360 ft.
24.00	Top of ascent on N. flank hill; desc. 320 ft. over steep W. slope.
40.54	The $\frac{1}{4}$ sec. cor. of secs. 3 and 10 which is monumented by a malpais stone, 14x8x8 ins. firmly set and mkd., and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, $3\frac{1}{2}$ ft. base to brass cap mkd.
	T6S R26E
	$\frac{1}{4}$ $\frac{S 3}{S 10}$
	1960
	Deposit the original cor. stone alongside iron post.
	N. $89^{\circ} 54'$ W., beginning new measurement.
	Over rolling hills.
2.10	Wash, 90 lks. wide, 2 ft. deep, drains S. 40° W.; thence over rolling bench.
9.70	Fence, four strand barbed wire, bears S. 20° W. and N. 20° E.
32.60	Wash, 30 lks. wide, 1 ft. deep, drains S. 30° W.
40.10	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling hills on SW. slope.
	Soil, shallow, gravelly sandy clay.
	Timber, none.
	Undergrowth, scattered mesquite, greasewood and cacti.
	N. $0^{\circ} 11'$ W., bet. secs. 3 and 4.
	Over series of spurs and washes putting SW.; asc. 20 ft. over SW. slope.
11.90	Wash, 15 lks. wide, with banks 3 ft. high, drains S. 60° W.; asc. 10 ft. along SW. slope.
25.80	Wash, 1.00 ch. wide, with banks 5 ft. high, drains SW.; asc. 10 ft. over SW. slope.
28.70	Bulldozed road, bears N. 60° E. and S. 60° W.; asc. 20 ft. over SW. slope.
33.40	Wash, 50 lks. wide, with banks 4 ft. high, drains SW.
38.20	Bulldozed road, bears N. 70° E. and S. 70° W.
38.60	Spur, sloping SW.; desc. 10 ft. over NW. slope.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

39.98 The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, which is monumented by a malpais stone, 15x9x5 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, $3\frac{1}{2}$ ft. base to brass cap mkd.

T6S R26E

$\frac{1}{4}$
S 4 | S 3
1960

Deposit the original cor. stone alongside iron post.

N. $0^{\circ} 05'$ W., beginning new measurement.

Over series of spurs and washes draining SW., through scattered mesquite and greasewood.

4.90 Wash, 10 lks. wide, 1 ft. deep, drains S. 50° W.; asc. 20 ft. over SE. slope.

7.00 Spur, sloping SW.; desc. 20 ft. over NW. slope.

12.40 Wash, 30 lks. wide, with banks 5 ft. high, drains S. 35° W.; asc. 60 ft. over SE. slope.

18.00 Spur, sloping SW.; desc. 30 ft. over NW. slope.

21.09 Wash, 15 lks. wide, 3 ft. deep, drains S. 40° W.; asc. 70 ft. over SE. slope.

25.00 Spur, slopes SW.; desc. 40 ft. along W. slope.

27.05 Bulldozed road, bears N. 50° E. and S. 50° W.

38.50 Intersect the First Standard Parallel South, at the closing cor. of secs. 3 and 4, which is monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

From this point the standard $\frac{1}{4}$ sec. cor. of sec. 33 bears W. 2.64 chs. dist., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

Land, SW. sloping bench land, cut by numerous washes.

Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3 is at midpoint and on the N. bdy. of the Tp. (First Standard Parallel South)

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, $3\frac{1}{2}$ ft. base to brass cap mkd.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

T5S R26E

$$\frac{1}{2} S 3$$

$$T6S$$

$$1960$$

From this cor. the standard sec. cor. of secs. 33 and 34, which is monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed according to the record, bears N. 89° 51' W., 2.88 chs. dist.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp.
N. 01° 52' W., bet. secs. 32 and 33.

Over nearly level land, through scattered mesquite and greasewood.

- 8.43 Bulldozed road, bears N. 60° E. and S. 60° W.
- 20.10 Graded road, bears N. 60° E. and S. 60° W.; asc. 20 ft. over SW slope.
- 39.16 The $\frac{1}{2}$ sec. cor. of secs. 32 and 33, which is monumented by a malpais stone, 18x12x6 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T6S R26E

$$\frac{1}{2}$$

$$S32 | S33$$

$$1960$$

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, 3 ft. base, 18 ins. high, W. of cor.

N. 01° 41' W., beginning new measurement.

Over nearly level land.

- 17.65 Wash, 15 lks. wide, 2 ft. deep, drains S. 60° W.
- 39.09 The witness cor. of secs. 28, 29, 32 and 33, which is monumented by a malpais stone, 16x12x12 ins., firmly set and properly mkd., and witnessed by remains of a mound of stone, W. of cor. There is no remaining evidence of bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to brass cap mkd.

T6S R26E

$$W \uparrow C$$

$$S29 | S28$$

$$S32 | S33$$

$$1960$$

Deposit the original cor. stone alongside iron post.

Rebuild the mound of stone, 2½ ft. base, 1 ft. high, W. of cor.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
40.09	<p>True point for the cor. of secs. 28, 29, 32 and 33, at record dist. from witness cor.; falls in wash, 1.50 lks. wide, 2½ ft. deep, draining W., where monument cannot be perpetuated.</p> <p>Land, nearly level on slight SW. slope. Soil, shallow, gravelly sandy clay. Timber, none. Undergrowth, scattered mesquite, greasewood and cacti.</p>
24.30	<p>From the cor. of secs. 27, 28, 33 and 34. N. 89° 37' W., bet. secs. 28 and 33.</p> <p>Over nearly level land on slight SW. slope, through scattered mesquite and greasewood.</p> <p>Asc. 20 ft. along SE. slope.</p>
40.09	<p>Graded road, on low spur, bears N. 50° E. and S. 50° W.</p> <p>The ¼ sec. cor. of secs. 28 and 33 which is monumented by a malpais stone, 15x10x5 ins. firmly set and properly mkd. There is no remaining evidence of the original bearing trees.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base, to brass cap mkd.</p>
	<p style="text-align: right;">T6S R26E ¼ S28 S33 1960</p> <p>Deposit the original cor. stone alongside iron post.</p>
4.90	<p>N. 89° 52' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>Track road, bears S. 65° E. and N. 65° W.</p>
23.00	<p>Fence, four strand barbed wire, bears N. and S.; desc. 70 ft. over W. slope.</p>
36.90	<p>Curve on wash, 1.50 chs. wide, 3 ft. deep, drains W. from NE., thence along wash bottom.</p>
40.09	<p>True point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Land, nearly level on slight SW. slope. Soil, shallow, gravelly sandy clay. Timber, none. Undergrowth, mesquite, greasewood and cacti.</p>
11.50	<p>N. 0° 04' W., bet. secs. 28 and 29.</p> <p>Over nearly level land, through scattered mesquite and greasewood.</p> <p>Wash, 30 lks. wide, 2 ft. deep, drains SW.; asc. 30 ft. over SW. slope.</p>
40.01	<p>The ¼ sec. cor. of secs. 28 and 29, which is monumented by a malpais stone, 18x8x6 ins. firmly set, mkd. & witnessed as described in the official record.</p>

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

At the cor. point
Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T6S R26E

S29 | S28
1960

Deposit the original cor. stone alongside iron post.
Rebuild the mound of stone, 2 ft. base, 1 ft. high, W. of cor.

N. 0° 06' W., beginning new measurement.

Over nearly level land.

36.80 Wash, 10 lks. wide, 4 ft. deep, drains S. 60° W.

40.12 The cor. of secs. 20, 21, 28 and 29, which is mkd. by a malpais stone, 20x12x10 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T6S R26E
S20 | S21
S29 | S28
1960

Deposit the original cor. stone alongside iron post.
Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Land, nearly level.
Soil, shallow, gravelly sandy clay.
Timber, none.
Undergrowth, mesquite, greasewood and cacti.

From the cor. of secs. 21, 22, 27 and 28.

N. 89° 49' W., bet. secs. 21 and 28.

Over nearly level land, through scattered mesquite and greasewood.

6.75 Wash, 15 lks. wide, 3 ft. deep, drains S. 20° W.

14.90 Wash, 10 lks. wide, 2 ft. deep, drains S. 25° E.

17.50 Wash, 10 lks. wide, 1 ft. deep, drains S. 10° E.

20.75 Wash, 20 lks. wide, 2 ft. deep, drains S.

33.75 Wash, 15 lks. wide, 2 ft. deep, drains S. 15° E.

40.11 The ¼ sec. cor. of secs. 21 and 22, which monumented by a malpais stone, 12x8x8 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd.

T6S R26E

S21

¼ S28

1960

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, 2 ft. base, 1 ft. high N. of cor.

N. 89° 35' W., beginning new measurement.

Over nearly level land.

2.90 Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.

5.90 Wash, 20 lks. wide, 3 ft. deep, drains S.

10.05 Wash, 15 lks. wide, 2 ft. deep, drains S.

34.30 Fence, bears N. 10° W. and S. 10° E.

35.50 Wash, 10 lks. wide, 1 ft. deep, drains SW.

40.05 The cor. of secs. 20, 21, 28 and 29.

Land, nearly level.

Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, mesquite, greasewood and cacti.

N. 0° 05' W., bet. secs. 20 and 21.

Over rolling land on slight SW. slope, through scattered mesquite and greasewood.

12.20 Wash, 50 lks. wide, 3 ft. deep, drains S. 60° W.; asc. 40 ft. over SW. slope.

40.10 The ¼ sec. cor. of secs. 20 and 21, which is monumented by a malpais stone, 15x10x8 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T6S R26E

S20 | S21

1960

Deposit the original cor. stone, alongside iron post.

Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.

N. 0° 07' W.; beginning new measurement.

Over nearly level land.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains									
12.60	Wash, 20 lks. wide, 4 ft. deep, drains S. 60° W.								
26.50	Wash, 20 lks. wide, 3 ft. deep, drains S. 50° W.								
40.08	The cor. of secs. 16, 17, 20 and 21, which is monumented by a malpais 18x12x6 ins. firmly set, mkd. and witnessed as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to brass cap mkd. <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T6S R26E</td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td>S20</td><td>S21</td></tr> <tr><td colspan="2">1960</td></tr> </table> Deposit the original cor. stone alongside iron post. Land, nearly level. Soil, shallow, gravelly sandy clay. Timber, none. Undergrowth, mesquite, greasewood and cacti.	T6S R26E		S17	S16	S20	S21	1960	
T6S R26E									
S17	S16								
S20	S21								
1960									
	From the cor. of secs. 15, 16, 21 and 22. N. 89° 45' W., bet. secs. 16 and 21. Over nearly level land, through scattered mesquite and greasewood.								
1.25	Wash, 15 lks. wide, 3 ft. deep, drains S. 20° W.								
9.50	Wash, 25 lks. wide, 2 ft. deep, drains S.								
18.80	Wash, 15 lks. wide, 1 ft. deep, drains S.								
40.13	The ¼ sec. cor. of secs. 16 and 21, which is monumented by a malpais stone, 18x10x5 ins., firmly set, mkd. and witnessed as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base, to brass cap mkd. <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T6S R26E</td></tr> <tr><td colspan="2">S16</td></tr> <tr><td>¼</td><td>S21</td></tr> <tr><td colspan="2">1960</td></tr> </table> Deposit the original cor. stone, alongside iron post. Rebuild mound of stone N. of cor. N. 89° 50' W., beginning new measurement. Over nearly level land.	T6S R26E		S16		¼	S21	1960	
T6S R26E									
S16									
¼	S21								
1960									
1.70	Wash, 20 lks. wide, 1 ft. deep, drains S.								
17.10	Wash, 90 lks. wide, 2 ft. deep, drains S. 30° E.								
38.20	Wash, 35 lks. wide, 1 ft. deep, drains SE.								

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains 40.03	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, nearly level. Soil, shallow, gravelly, sandy clay. Timber, none. Undergrowth, mesquite, greasewood and cacti.</p> <hr/> <p>N. 0° 06' W., bet. secs. 16 and 17.</p> <p>Over rolling land on general SW. slope, through scattered mesquite and greasewood.</p> <p>Asc. 20 ft. over SW. slope.</p>
13.00	Wash, 10 lks. wide, 3 ft. deep, drains S. 40° W.; asc. 40 ft. over SW. slope.
36.65	Fence, bears N. 25° E. and S. 25° W.
40.02	<p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, which is monumented by a malpais stone, 15x10x6 ins. firmly set, mkd. and witnessed as recorded in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base to brass cap mkd.</p> <p style="text-align: center;">T6S R26E S17 S16 1960</p> <p>Deposit the original cor. stone, alongside iron post. Rebuild mound of stone W. of cor.</p> <hr/> <p>N. 0° 09' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>Asc. 40 ft. over SW. slope.</p>
17.30	Fence, bears N. 75° E. and S. 75° W.
18.30	Wash, 50 lks. wide, 3 ft. deep, drains S. 10° W.
	Asc. 10 ft. over SW. slope.
25.50	Wash, 50 lks. wide, 3 ft. deep, drains S. 10° W.; asc. 20 ft. along SE. slope.
40.04	<p>The cor. of secs. 8, 9, 16 and 17, which is monumented by a malpais stone, 15x8x6 ins. firmly set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p>

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

T6S R26E

S 8 | S 9

S17 | S16

1960

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, W. of cor.

Land, rolling on general SW. slope.

Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, mesquite, greasewood and cacti.

From the cor. of secs. 9, 10, 15 and 16.

N. 89° 53' W., bet. secs. 9 and 16.

Over rolling land on general SW. slope, through scattered mesquite and greasewood.

Desc. 20 ft. over SW. slope.

17.80 Wash, 25 lks. wide, 1 ft. deep, drains SW.; desc. 20 ft. over SW. slope.

37.80 Wash, 25 lks. wide, 2 ft. deep, drains SW.

40.05 The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, which is monumented by a malpais stone, 15x10x4 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3 $\frac{1}{2}$ ft. base to brass cap mkd.

T6S R26E

S 9

S16

1960

Deposit the original cor. stone alongside iron post.

N. 89° 51' W., beginning new measurement.

Over rolling land.

Desc. 10 ft. over SW. slope.

8.60 Wash, 20 lks. wide, 1 ft. deep, drains S.; desc. 20 ft. over SW. slope.

21.70 Wash, 20 lks. wide, 2 ft. deep, drains SW.; desc. 10 ft. over SW. slope.

36.30 Wash, 80 lks. wide, 2 ft. deep, drains S.

39.98 The cor. of secs. 8, 9, 16 and 17.

Land, rolling on SW. slope.

Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
	<p>N. 0° 05' W., bet. secs. 8 and 9.</p> <p>Over rolling land on SW. slope, through scattered mesquite and greasewood.</p> <p>Asc. 10 ft. over SW. slope.</p>
15.10	Wash, 10 lks. wide, 3 ft. deep, drains S. 35° W.; asc. 10 ft. over SW. slope.
30.08	Wash, 20 lks. wide, 3 ft. deep, drains S. 30° W.
35.10	Bulldozed road, bears E. and W.
38.00	Wash, 2.00 chs. wide, 4 ft. deep, drains S. 25° W.
40.12	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4½ ft. base to brass cap mkd.</p> <p style="text-align: center;">T6S R26E $\frac{1}{4}$ S 8 S 9 1960</p> <p>Asc. 80 ft. over SW. slope.</p>
80.24	<p>The cor. of secs. 4, 5, 8 and 9 which is monumented by a malpais stone, 16x12x11 ins. firmly set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to brass cap mkd.</p> <p style="text-align: center;">T6S R26E S 5 S 4 S 8 S 9 1960</p> <p>Deposit the original cor. stone alongside iron post.</p> <p>Land, rolling on general SW. slope. Soil, gravelly sandy clay. Timber, none. Undergrowth, scattered mesquite, greasewood and cacti.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89° 53' W., bet. secs. 4 and 9.</p> <p>Over rolling land, through scattered mesquite and greasewood.</p> <p>Desc. 20 ft. over SW. slope.</p>
10.40	Wash, 10 lks. wide, 1 ft. deep, drains SW.; desc. 10 ft. over SW. slope.
18.60	Wash, 40 lks. wide, 2 ft. deep, drains S. 40° W.; desc. 30 ft. over SW. slope.
23.40	Wash, 30 lks. wide, 3 ft. deep, drains SW.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
26.10	Wash, 20 lks. wide, 1 ft. deep, drains SW.
35.50	Bulldozed road, bears S. 25° W. and N. 25° E.
40.04	The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, which is monumented by a malpais stone, 18x14x6 ins. firmly set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base, to brass cap mkd.
	T6S R26E
	$\frac{1}{4}$ S 4.
	$\frac{1}{4}$ S 9
	1960.
	Deposit the original cor. stone alongside iron post.
	N. 89° 55' W., beginning new measurement.
	Over rolling land.
	Desc. 10 ft. over SW. slope.
5.00	Bulldozed road, bears S. 50° W.; desc. 30 ft. over SW. slope.
13.70	Wash, 30 lks. wide, 2 ft. deep, drains S.; desc. 5 ft. over SW. slope.
22.60	Wash, 60 lks. wide, 2 ft. deep, drains S. 5° W.; desc. 10 ft. over SW. slope.
29.40	Wash, 30 lks. wide, 2 ft. deep, drains SW.
31.10	Bulldozed road, bears S. 15° W. and N. 15° E.; desc. 10 ft. over SW. slope.
40.03	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling on general SW. slope.
	Soil, shallow, gravelly sandy clay.
	Timber, none.
	Undergrowth, scattered mesquite, greasewood and cacti.
	N. 0° 07' W., bet. secs. 4 and 5.
	Over rolling land, through scattered mesquite and greasewood.
	Asc. 40 ft. over SW. slope.
24.30	Wash, 30 lks. wide, 2 ft. deep, drains SW.; asc. 40 ft. over SW. slope.
40.08	The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, which is monumented by a malpais stone, 20x14x6 ins. diam., firmly set, mkd. and witnessed as described in the official record.
	At the cor. point

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.

T6S R26E

S 5 | S 4

1960

Deposit the original cor. stone alongside iron post.

N. 0° 06' W., beginning new measurement.

Over rolling land on SW. slope.

Asc. 40 ft. over SW. slope.

19.60 Bulldozed road, bears E. and W.

21.60 Wash, 90 lks. wide, 6 ft. deep, drains S. 40° W.; asc. 30 ft. over SE. slope.

38.40 Intersect the N. bdy. of the Tp., First Standard Parallel South, at the closing cor. of secs. 4 and 5, which is monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

From this point the standard ¼ sec. cor. of sec. 32 bears W. 2.91 chs. dist., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

Land, rolling on general SW. slope.

Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, mesquite, greasewood and cacti.

The point for the N. ¼ sec. cor. of sec. 4 is at mispoint and on the N. bdy. of the Tp. (First Standard Parallel South)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to brass cap mkd.

T5S R26E

¼ S 4

T6S

1960

From this cor. the standard sec. cor. of secs. 32 and 33, which is monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed according to the record, bears N. 89° 57' W.; 2.76 chs. dist.

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp.

N. 02° 05' W., bet. secs. 31 and 32.

Over rolling land, through scattered mesquite and greasewood.

Asc. 20 ft. along steep E. slope.

2.00 Thence over nearly level bench.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

- 7.97 Fence, four strand barbed wire, bears N. 10° E. and S. 10° W.
- 14.57 Wash, 15 lks. wide, 3 ft. deep, drains W.
- 18.27 Fence, four strand barbed wire, bears N. 30° E.; same fence as noted above.
- 19.60 Edge of wash, bears NE. and SW.; desc. 40 ft. over steep NW. facing bank.
- 21.00 Base of descent, thence over level wash bottom, through dense mesquite and catclaw.
- 39.25 True point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor., which falls in present wash channel, where the monument cannot be perpetuated.
- 40.25 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 31 and 32.
Set an iron post, 30 ins. long, 2½ ins. diam.; 24 ins. in the ground, with brass cap mkd.
- T6S R26E
S31 | S32
W.C.
1960
- Raise mound of stone, 3 ft. base, 2 ft. high, W. of cor.
- 65.00 Main wash channel 1.00 ch. wide, drains S. 20° E.
- 73.00 Same channel, drains S. 10° W.
- 79.34 Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.
Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base, to brass cap mkd.
- T6S R26E
S30 | S29
S31 | S32
1960
- Land, rolling to nearly level on general SW. slope.
Soil, shallow, gravelly sandy clay.
Timber, none.
Undergrowth, mesquite, greasewood and cacti.
-
- From the true point for the cor. of secs. 28, 29, 32 and 33.
N. 89° 46' W., bet. secs. 29 and 32.
- Over rolling land, through scattered mesquite and greasewood.
- Along wash bottom
- 4.60 Leave wash, 1.50 chs. wide, 2 ft. deep; drains SW.; asc. 20 ft. over SW. slope.
- 16.40 Wash, 10 lks. wide, 1 ft. deep, drains S.
- 32.30 Track road, bears S. 10° W. and N. 10° E.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
40.05	The $\frac{1}{2}$ sec. cor. of secs. 29 and 32, which is monumented by a malpais stone, 14x6x6 ins., firmly set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
	T6S R26E $\frac{1}{2}$ $\frac{S29}{S32}$ 1960
	Deposit the original cor. stone alongside iron post.
	Rebuild mound of stone N. of cor.
	N. 89° 52' W., beginning new measurement.
	Over nearly level bench land.
8.02	Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.
18.00	Wash, 15 lks. wide, 3 ft. deep, drains S. 30° W.
34.27	Wash, 50 lks. wide, 4 ft. deep, drains S.
39.90	Wash, 10 lks. wide, 1 ft. deep, drains S.
40.08	The cor. of secs. 29, 30, 31 and 32.
	Land, rolling to nearly level. Soil, shallow, gravelly sandy clay. Timber, none.
	Undergrowth, scattered mesquite, greasewood and cacti.
	N. 89° 50' W., bet. secs. 30 and 31.
	Over gently rolling land, through scattered mesquite and greasewood.
13.90	Bulldozed road, bears N. and S. to Safford City Dump.
40.08	The $\frac{1}{2}$ sec. cor. of secs. 30 and 31, which is monumented by a malpais stone, 14x8x6 ins. firmly set, mkd. and witnessed as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.
	T6S R26E $\frac{1}{2}$ $\frac{S30}{S31}$ 1960
	Deposit the original cor. stone alongside iron post.
	N. 89° 57' W., beginning new measurement.
	Over nearly level land.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

- 34.74 The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp.
Land, nearly level to rolling.
Soil, shallow, gravelly sandy clay.
Timber, none.
Undergrowth, mesquite, greasewood and cacti.
- From the cor. of secs. 29, 30, 31 and 32.
N. 0° 22' W., bet. secs. 29 and 30.
Over nearly level land, through scattered mesquite and greasewood.
Asc. 20 ft. over SW. slope.
- 40.08 The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, which is monumented by a malpais stone, 15x8x7 ins. firmly set, mkd. and witnessed as described in the official record.
At the cor. point
Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
T6S R26E
S30 | S29
1960
Deposit the original cor. stone alongside iron post.
Rebuild mound of stone, 3 ft. base, 2 ft. high W. of cor.
N. 0° 02' E., beginning new measurement.
Over nearly level land.
Asc. 20 ft. over SW. slope.
- 40.13 The cor. of secs. 19, 20, 29 and 30, which is monumented by a malpais stone, 15x12x10 ins. firmly set, properly mkd., and witnessed by a mound of stone, W. of cor. There is no remaining evidence of the original bearing trees.
At the cor. point
Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.
T6S R26E
S19 | S20
S30 | S29
1960
Deposit the original cor. stone alongside iron post.
Land, nearly level bench, with general SW. drainage.
Soil, gravelly, sandy clay.
Timber, none.
Undergrowth, mesquite, greasewood and cacti.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

From the cor. of secs. 20, 21, 28 and 29.

N. 89° 41' W., bet. secs. 20 and 29.

Over nearly level land, through scattered mesquite and greasewood.

Desc. 10 ft. over SW. slope.

11.80 Wash, 1.00 ch. wide, 2 ft. deep, drains SW.; desc. 10 ft. over SW. slope.

21.90 Wash, 60 lks. wide, 3 ft. deep, drains S. 20° W.

29.10 Wash, 25 lks. wide, 2 ft. deep, drains SW.; desc. 10 ft. over SW. slope.

35.75 Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.

40.14 The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, which is monumented by a malpais stone, 15x12x6 ins. firmly set, properly mkd. and witnessed by a mound of stone to N. There is no remaining evidence of the bearing tree.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 2 $\frac{1}{2}$ ft. base to brass cap mkd.

T6S R26E

$\frac{1}{4}$ S20.

S29

1960

Deposit the original cor. stone alongside iron post.

N. 89° 54' W., beginning new measurement.

Over nearly level land.

1.20 Wash, 1.10 ch. wide, 3 ft. deep, drains S.

5.75 Wash, 25 lks. wide, 2 ft. deep, drains S.

22.40 Wash, 60 lks. wide, 2 ft. deep, drains S. 20° W.

27.60 Wash, 30 lks. wide, 1 ft. deep, drains S.

38.50 Wash, 15 lks. wide, 1 ft. deep, drains SE.

40.12 The cor. of secs. 19, 20, 29 and 30.

Land, nearly level to rolling on general SW. slope.

Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

S. 89° 42' W., bet. secs. 19 and 30.

Over nearly level land, through scattered mesquite and greasewood.

2.68 Wash, 20 lks. wide, 1 ft. deep, drains S. 20° E.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
16.00	Wash, 10 lks. wide, 1½ ft. deep, drains S. 30° W.
35.40	Wash, 20 lks. wide, 2 ft. deep, drains S. 20° W.
39.05	Track road, bears S. 25° W. and N. 25° E.
40.14	The ¼ sec. cor. of secs. 19 and 30, which is monumented by a malpais stone, 14x8x6 ins. firmly set, properly mkd. and witnessed by a mound of stone to N. There is no remaining evidence of the bearing trees.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 2½ ft. base, to brass cap mkd.
	T6S R26E ¼ <u>S19</u> ¼ <u>S30</u> 1960
	Deposit the original cor. stone alongside iron post.

	S. 89° 38' W., beginning new measurement.
	Over nearly level bench.
11.28	Wash, 40 lks. wide, 1 ft. deep, drains S. 30° W.
33.30	Wash, 10 lks. wide, 1 ft. deep, drains SW.
34.28	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp.
	Land, nearly level bench on general SW. slope.
	Soil, shallow, gravelly, sandy clay.
	Timber, none.
	Undergrowth, mesquite, greasewood and cacti.

	From the cor. of secs. 19, 20, 29 and 30.
	North, bet. secs. 19 and 20.
	Over nearly level land, through scattered mesquite and greasewood.
	Asc. 20 ft. over SW. slope.
24.70	Wash, 20 lks. wide, 2 ft. deep, drains SW.; asc. 10 ft. over SW. slope.
40.10	The ¼ sec. cor. of secs. 19 and 20, which is monumented by a malpais stone, 18x7x6 ins., firmly set, properly mkd. and witnessed by a mound of stone W. of cor. There is no remaining evidence of the original bearing tree.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

BOOK 411

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

T6S R26E

 $\frac{1}{4}$

S19 | S20

1960

Deposit the original cor. stone alongside iron post.

North, beginning new measurement.

Over nearly level land.

Asc. 10 ft. over SW. slope.

10.40 Track road, bears NE. and SW.

25.60 Wash, 20 lks. wide, 2 ft. deep, drains S. 40° W.

40.11 The cor. of secs. 17, 18, 19 and 20, which is monumented by a malpais stone, 18x11x8 ins., firmly set, properly mkd. and witnessed by a mound of stone to the W. There is no remaining evidence of the bearing trees.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3 ft. base, to brass cap mkd.

T6S R26E

S18 | S17

S19 | S20

1960

Deposit the original cor. stone alongside iron post.

From corner fences bear E., W. and S.

Land, nearly level to rolling on SW. slope and drainage.

Soil, shallow, gravelly, sandy clay.

Timber, none.

Undergrowth, scattered mesquite and greasewood.

From the cor. of secs. 16, 17, 20 and 21.

N. 89° 42' W., bet. secs. 17 and 20.

Over nearly level bench land, through scattered mesquite and cacti.

5.70 Fence, bears N. 10° W. and S. 10° E.

10.90 Wash, 30 lks. wide, 3 ft. deep, drains S. 20° E.

15.30 Wash, 40 lks. wide, 3½ ft. deep, drains SW.

27.70 Wash, 50 lks. wide, 2 ft. deep, drains SW.

34.50 Wash, 35 lks. wide, 2 ft. deep, drains S. 20° W.

40.02 The ¼ sec. cor. of secs. 17 and 20, which is monumented by a malpais stone, 20x12x10 ins. firmly set, mkd. and witnessed as described in the official record.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base to brass cap mkd.

T6S R26E

¼ S17

S20

1960

Deposit the original cor. stone alongside iron post.

N. 89° 57' W., beginning new measurement.

Over nearly level bench land.

- 1.35 Wash, 10 lks. wide, 1 ft. deep, drains S.
- 10.40 Wash, 20 lks. wide, 1 ft. deep, drains S. 20° W.
- 16.50 Wash, 20 lks. wide, 2 ft. deep, drains SW.
- 18.50 Track road, bears S. 30° W. and N. 30° E.
- 30.20 Wash, 20 lks. wide, 2 ft. deep, drains SW.
- 38.70 Wash, 10 lks. wide, 1 ft. deep, drains SW.
- 40.12 The cor. of secs. 17, 18, 19 and 20.

Land, nearly level bench on SW. slope with SW. drainage.
Soil, shallow, gravelly sandy clay.
Timber, none.
Undergrowth, scattered mesquite, greasewood and cacti.

S. 89° 22' W., bet. secs. 18 and 19.

Over nearly level land, through scattered mesquite and greasewood.

- 2.10 Wash, 30 lks. wide, 2 ft. deep, drains S. 20° W.
- 4.50 Wash, 30 lks. wide, 1 ft. deep, drains S.
- 11.30 Wash, 10 lks. wide, 1 ft. deep, drains SW.
- 26.00 Wash, 10 lks. wide, 1 ft. deep, drains SW.
- 30.60 Wash, 20 lks. wide, 1 ft. deep, drains S.
- 40.15 The ¼ sec. cor. of secs. 18 and 19, which is monumented by a malpais stone 12x10x10 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd.

Dependent Resurvey, Subdivisional Lines. T. 6 S., R. 26 E.

Chains

T6S R26E

 $\frac{1}{4}$ S18
S19

1960

Deposit the original cor. stone alongside iron post.

S. 89° 21' W., beginning new measurement.

Over nearly level land.

6.80 Wash, 10 lks. wide, 1 ft. deep, drains SW.

22.30 Track road, bears SW. and NE.

32.00 Wash, 10 lks. wide, 1 ft. deep, drains SW.

34.10 The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp.

Land, nearly level to rolling bench, with general SW. slope and drainage.

Soil, shallow, gravelly, sandy clay.

Timber, none.

Undergrowth, scattered mesquite and greasewood.

From the cor. of secs. 17, 18, 19 and 20.

N. 0° 13' W., bet. secs. 17 and 18.

Over slightly rolling land, on general SW. slope.

4.30 Wash, 30 lks. wide, 3 ft. deep, drains SW.; asc. 30 ft. over SW. slope.

29.60 Wash, 30 lks. wide, 2 ft. deep, drains S. 30° W.

36.40 Wash, 20 lks. wide, 3 ft. deep, drains S. 35° W.

40.10 The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, which is monumented by a malpais stone, 18x10x10 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.

T6S R26E

 $\frac{1}{4}$ S18 | S17

1960

Deposit the original cor. stone alongside iron post.

N. 0° 01' W., beginning new measurement.

Over slightly rolling land.

Asc. 20 ft. over SW. slope.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

12.30 Wash, 1.00 ch. wide, 4 ft. deep, drains S. 40° W.; asc. 10 ft. over SW. slope.

23.60 Track road, bears N. 50° E. and S. 50° W.

40.16 The cor. of secs. 7, 8, 17 and 18, which is monumented by a malpais stone, 24x12x6 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.

T6S R26E

S 7 | S 8

S18 | S17

1960

Deposit the original cor. stone alongside iron post.

Land, nearly level to rolling on SW. slope, with SW. drainage. Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

From the cor. of secs. 8, 9, 16 and 17.

N. 89° 41' W., bet. secs. 8 and 17.

Over slightly rolling land on SW. slope.

Desc. 10 ft. over SW. slope.

10.60 Wash, 1.20 chs. wide, 2 ft. deep, drains SW.

19.30 Wash, 1.10 chs. wide, 3 ft. deep, drains SW.

40.06 The ¼ seo. cor. of secs. 8 and 17, which is monumented by a malpais stone, 20x8x6 ins. firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground with brass cap mkd.

T6S R26E

¼ S 8

¼ S17

1960

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 89° 41' W., beginning new measurement.

Over nearly level to rolling land.

3.40 Wash, 10 lks. wide, 1 ft. deep, drains SW.; desc. 10 ft. over SW. slope.


12.00 Wash, 30 lks. wide, 2 ft. deep, drains SW.

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
20.00	Wash, 20 lks. wide, 2 ft. deep, drains SW.
22.10	Track road, bears NE. and SW.; desc. 10 ft. over SW. slope.
25.40	Wash, 25 lks. wide, 1 ft. deep, drains S.; desc. 30 ft. over SW. slope.
40.12	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, nearly level to rolling bench, with SW. slope and drainage. Soil, shallow, gravelly, sandy clay. Timber, none. Undergrowth, scattered mesquite, greasewood and cacti.</p>
	<p>S. 88° 54' W., bet. secs. 7 and 18.</p> <p>Over nearly level land, with SW. slope and drainage, through scattered mesquite and greasewood.</p>
.55	Wash, 10 lks. wide, 1 ft. deep, drains SW.; desc. 10 ft. over SW. slope.
6.50	Wash, 40 lks. wide, 2 ft. deep, drains S.; desc. 30 ft. over SW. slope.
24.00	Wash, 10 lks. wide, 1 ft. deep, drains SW.; desc. 10 ft. over SW. slope.
35.40	Wash, 30 lks. wide, 1½ ft. deep, drains SW.
40.05	<p>The ¼ sec. cor. of secs. 7 and 18, which is monumented by a malpais stone, 15x8x6 ins. firmly set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base, to brass cap mkd.</p> <p style="text-align: center;">T6S R26E ¼ S 7 S 18 1960</p> <p>Deposit the original cor. stone alongside iron post.</p> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p>
	<p>S. 89° 03' W., beginning new measurement.</p> <p>Over slightly rolling land.</p>
	Desc. 5 ft. over SW. slope.
4.40	Wash, 25 lks. wide, 2 ft. deep, drains SW.; desc. 5 ft. over SW. slope.
8.00	Wash, 40 lks. wide, 1 ft. deep, drains SW.; asc. 10 ft. over SW. slope.

BOOK 4615

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
12.40	Wash, 20 lks. wide, 1 ft. deep, drains SW.
25.30	Wash, 10 lks. wide, 1 ft. deep, drains SW.
33.80	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.</p> <p>Land, nearly level to rolling on general SW. slope and drainage. Soil, shallow, gravelly, sandy clay. Timber, none. Undergrowth, mesquite, greasewood and cacti.</p>
From the cor. of secs. 7, 8, 17 and 18.	
N. 0° 05' W., bet. secs. 7 and 8.	
Over rolling land, on SW. slope, through scattered mesquite and greasewood.	
Asc. 20 ft. over SW. slope.	
7.70	Wash, 30 lks. wide, 3 ft. deep, drains S. 40° W.; asc. 20 ft. over SW. slope.
20.60	Wash, 40 lks. wide, 3 ft. deep, drains S. 40° W.; asc. 20 ft. over SW. slope.
39.17	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
<p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd. T6S R26E.</p>	
<p style="text-align: center;">  </p>	
39.47	Point for the original witness $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original witness cor.
39.97	<p>The true point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist., falls in wash, 30 lks. wide, 2 ft. deep, drains S. 60° W. where the monument cannot be perpetuated.</p> <p>Asc. 10 ft. over SW. slope.</p>
46.50	Wash, 50 lks. wide, 2 ft. deep, drains S. 30° W.; asc. 10 ft. over SW. slope.
52.75	Wash, 1.00 ch. wide, 3 ft. deep, drains S. 50° W.; asc. 20 ft. over SW. slope.
77.00	Wash, 10 lks. wide, 1 ft. deep, drains S. 45° W.
79.94	<p>The cor. of secs. 5, 6, 7 and 8, which is monumented by a malpais stone, 30x7x7 ins., firmly set, mkd. and witnessed as described in the official record.</p> <p>At the cor. point</p>

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground with brass cap mkd.

T6S R26E

S 6 | S 5
S 7 | S 8

1960

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling bench on SW. slope, with SW. drainage.

Soil, shallow, gravelly sandy clay.

Timber, none.

Undergrowth, scattered mesquite, greasewood and cacti.

From the cor. of secs. 4, 5, 8 and 9.

N. 89° 44' W., bet. secs. 5 and 8.

Over rolling land, on general SW. slope.

Desc. 10 ft. over SW. slope.

5.40 Wash, 20 lks. wide, 1 ft. deep, drains SW.; desc. 10 ft. over SW. slope.

10.10 Wash, 20 lks. wide, 1 ft. deep, drains S. 20° W.; desc. 10 ft. over SW. slope.

18.30 Wash, 10 lks. wide, 1 ft. deep, drains S.; desc. 10 ft. over SW. slope.

20.80 Wash, 15 lks. wide, 1 ft. deep, drains S.

38.60 Wash, 20 lks. wide, 1 ft. deep, drains SW.

40.09 The ¼ sec. cor. of secs. 5 and 8, which is monumented by a malpais, 18x8x6 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R26E

S 5
¼ S 8

1960

Deposit the original cor. stone alongside iron post.

Rebuild mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 89° 52' W., beginning new measurement.

Over rolling land on SW. slope.

2.40 Wash, 80 lks. wide, 2 ft. deep, drains SW.

4.60 Wash, 20 lks. wide, 3 ft. deep, drains SW.

11.10 Wash, 1.00 ch. wide, 2 ft. deep, drains SW.

BOOK 4615

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains	
13.30	Wash, 60 lks. wide, 4 ft. deep, drains S. 20° W.
19.70	Track road, bears N. and S.
30.20	Wash, 90 lks. wide, 3½ ft. deep, drains S. 20° W.
38.80	Wash, 30 lks. wide, 1 ft. deep, drains SW.
40.07	The cor. of secs. 5, 6, 7 and 8.
<p>Land, rolling on SW. slope and with general SW. drainage. Soil, shallow, gravelly sandy clay. Timber, none. Undergrowth, scattered mesquite, greasewood and cacti.</p>	
<p>S. 89° 00' W., bet. secs. 6 and 7.</p>	
<p>Over rolling land, through scattered mesquite and greasewood.</p>	
<p>Desc. 10 ft. over SW. slope.</p>	
9.50	Wash, 20 lks. wide, 2 ft. deep, drains SW.; desc. 10 ft. over SW. slope.
24.00	Wash, 50 lks. wide, 4 ft. deep, drains SW.; desc. 20 ft. over SW. slope.
36.10	Fence, bears N. 50° E. and S. 50° W.
40.12	The ¼ sec. cor. of secs. 6 and 7, which is monumented by a malpais stone, 20x10x5 ins. firmly set, mkd. and witnessed as described in the official record.
<p>At the cor. point</p>	
<p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to brass cap mkd.</p>	
<p>T6S R26E</p>	
<p>½ S 6</p>	
<p>½ S 7</p>	
<p>1960</p>	
<p>Deposit the original cor. stone alongside iron post.</p>	
<p>S. 88° 50' W., beginning new measurement.</p>	
<p>Over rolling land on SW. slope.</p>	
1.00	Wash, 40 lks. wide, 2 ft. deep, drains S. 30° W.
5.10	Wash, 30 lks. wide, 2 ft. deep, drains S. 30° W.; desc. 40 ft. over SW. slope.
28.70	Wash, 30 lks. wide, 4 ft. deep, drains S. 30° W.
33.41	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp.
<p>Land, rolling on SW. slope and drainage.</p>	
<p>Soil, shallow, gravelly sandy clay.</p>	
<p>Timber, none.</p>	
<p>Undergrowth, mesquite, greasewood and cacti.</p>	

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 05' W., bet. secs. 5 and 6:

Over rolling land, through scattered mesquite and greasewood.

Asc. 20 ft. over SW. slope.

23.80 Fence, bears N. 50° E. and S. 50° W.

40.26 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, which is mkd. by a malpais stone, 15x14x8 ins., firmly set, mkd. and witnessed as described in the official record.

At the cor. point.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to brass cap mkd.

T6S R26E

$\frac{1}{4}$
S 6 | S 5
1960

Deposit the original cor. stone alongside iron post.

N. 0° 05' W., beginning new measurement.

Over rolling land.

Asc. 10 ft. over SW. slope.

5.30 Wash, 40 lks. wide, 3 ft. deep, drains S. 20° W.; asc. 20 ft. over SW. slope.

16.00 Wash, 1.00 ch. wide, 3 ft. deep, drains SW.; asc. 120 ft. over steep SE. slope.

38.22 Intersect the First Standard Parallel South, at the closing cor. of secs. 5 and 6, which is monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

From this point the standard $\frac{1}{4}$ sec. cor. of sec. 31 bears N. 89° 52' W., 2.80 chs. dist., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

Land, rolling.

Soil, gravelly, sandy clay.

Timber, none.

Undergrowth, mesquite, greasewood and cacti.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 5 is at midpoint and on the N. bdy. of the Tp. (First Standard Parallel South).

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base to brass cap mkd.

T5S R26E

$\frac{1}{4}$ S 5
T6S
1960

From this cor. the standard sec. cor. of secs. 31 and 32, which is monumented by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears W., 2.88 chs. dist.

BOOK 4615

Dependent Resurvey, Subdivisional Lines, T. 6 S., R. 26 E.

Chains

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 6 on the N. bdy. of the Tp. (First Standard Parallel South) is at proportionate dist. as based upon the original plat.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base to brass cap mkd.

T5S R26E

$\frac{1}{4}$ S 6

T6S

1960

From this cor. the standard cor. of T. 5 S., Rs. 25 and 26 E., which is monumented by an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears N. 89° 51' W., 3.02 chs. dist.

GENERAL DESCRIPTION

T. 6 S., R. 26 E., Gila and Salt River Meridian, Arizona is located in Graham County, approximately three miles north of the city of Safford, Arizona. The township is situated on a well developed bahada, which has a general south-west slope and drainage. The elevation of the township ranges from about 2900 to 5200 ft. above sea level, the highest point being at the northeast corner on the west flank of Weber Peak. The lowest elevation is located at the southwest corner of the township on the flood plain of the Gila River. The soil of the township is shallow, poorly developed, gravelly sandy clay, with the exception of a small area in the south-west quarter of section 31, which has a deep, well developed, sandy loam, river alluvium. This soil produces a vegetative cover composed of desert trees, shrubs, weeds, cacti and grasses, with the mesquite, greasewood and ocotillo cacti predominating.

No springs, wells or other permanent sources of water within the boundaries of the township were noted during this survey. The drainage is composed of numerous intermittent streams draining south-west to the Gila River. Water for use in connection with stock grazing in the township is obtained by the constructions of earthen dams in the washes, which catch and hold the run-off. There are several such dams scattered throughout the lower portion of the township. However, there was no water in any of the ponds during this survey.

The proximity of the city of Safford to the township has created considerable activity on the land, both in minerals and land use. The interest in the minerals has been both past and present, as evidenced by the patented mining claims in section 2 and the core drilling taking place at present. Land uses consist of patented farm land and small tracts in section 31, Safford City dump located in portions of sections 29, 30, 31 and 32, and a cemetery located in section 32. There are numerous roads adjacent to and within the boundaries of the township. The paved road from Safford to the airport roughly parallels the south boundary. The main north-south road, graded and gravelled, enters the township at the south boundary near the quarter section corner of section 32, and bears northeast leaving the township at the north boundary, 15 chains west of the northeast corner of section 2. The remainder of the roads are for the most part bulldozed and/or jeep trails.

Since there is considerable housing development on land like that of T. 7 S., R. 26 E. south of Safford, and a small development less than a quarter of a mile south of the south boundary, it is to be expected that there will be considerable interest in the land in the near future, depending on the growth and development of Safford.

4-680
(Feb., 1950)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Eldon W. Sibley	Crew Chief
LaVern Griffin	Principal Assistant
Wallace R. Ott	Chainman
Douglas G. Haycock	Flagman
Gary T. Oviatt	Cornerman
Dan V. Coleman	Axeman
Glen B. Hatch	Crew Chief
William R. Savage	Principal Assistant
Neil R. Forsyth	Chainman
R. Gordon Shurtz	Flagman
Jerry Lee Thomas	Cornerman
Parley Pratt	Axeman

CERTIFICATE OF CADASTRAL ENGINEER

We, Dell Cazier, Glen B. Hatch & Eldon W. Sibley, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 10th day of August, 1959, we have ~~surveyed~~ independently resurveyed the east, south and west boundaries and the subdivisioal lines of T. 6 S., R. 26 E.

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
February 9, 1961

Dell Cazier, Cadastral Surveyor
Glen B. Hatch, Survey Aid
Eldon W. Sibley, Survey Aid

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., JAN 24 1962, 19

The foregoing field notes of the survey of dependent resurvey of the east, south and west boundaries and the subdivisioal lines of T. 6 S., R. 26 E. of the Gila and Salt River Meridian, Arizona

executed by Dell Cazier, Cadastral Surveyor, Glen B. Hatch, Survey Aid and Eldon W. Sibley, Survey Aid having been critically examined and found correct, are hereby approved.

Chief, Division of Engineering
Cadastral Engineering Staff Officer.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 6 S., R. 26 E., G&SR Mer., Arizona, is a true copy of the original field notes.

Cadastral Engineering Staff Officer.