

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
ORIGINAL

# FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY OF  
TOWNSHIP 6 SOUTH, RANGE 31 EAST,

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION

AND

ORIGINAL SURVEY COMPLETING THE SUBDIVISION

OF

TOWNSHIP 6 SOUTH, RANGE 30 EAST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

### EXECUTED BY

Phil D. Smith, Cadastral Surveyor in 1957

Vern E. Lane, Cadastral Surveyor (Chief of Party) in 1960

Boyd S. Owens, Cartographic Survey Aid, in 1960

Under special instructions dated November 16, 1954, which provided  
and supplemental special instructions dated January 13, 1956 and approved  
for the surveys included under Group No. 299, approved January 13, 1956  
November 16, 1954

and assignment instructions dated November 1, 1957  
January 13, 1960

Survey commenced January 18 1960  
February 8, 1957

Survey completed February 3, 1960

1A

BOOK 4618

# INDEX DIAGRAM

Township 6 South, Range 30 East

6 12	5 11	4 10	3 9	2	1
7 35 35	8 27 34	9 24 27	10 8 23	11 8	12
13 34 33	14 27 33	15 22 26	16 7 22	17 6	18 5
19 32 32	20 26 31	21 21	22 20 19	23 15 19	24 4 15
25 31 30	26 30	27	28 18 18	29 14 17	30 2 14
31 29	32	33	34 16	35 13	36 1

GPO 866119

———— Phil D. Smith  
 ———— Boyd S. Owens

Township 6 South, Range 30 East

Chains

The south boundary of the township was surveyed by C. E. Hunter in 1931. The east boundary was surveyed by D. Drummond in 1891. Drummond also surveyed a portion of the subdivision in 1891. The north boundary, (First Standard Parallel South) was surveyed by T. F. White in 1882. The west boundary was surveyed by H. G. Parker in 1955 and resurveyed by E. W. Sibley and E. S. Owens concurrently under this same group and the record appears in the field notes of T. 6 S., R. 29 E. Sections 28 and 33 were surveyed by White and Bilbray in 1951.

The following field notes are those of the resurvey of a portion of the east boundary and a portion of the subdivision and the original survey completing the subdivision of the township. The survey was requested by the State Supervisor for Arizona to facilitate range management.

For the record of the instruments and methods used for this survey, see page 1 of T. 6 S., R. 29 E.

The geographic position for the southeast corner of the township is latitude 32° 51' 39.1" N. and longitude 109° 13' 06.1" W., as determined by traverse from U. S. G. S. triangulation station "Guthrie" situated in section 30, T. 6 S., R. 30 E.

The magnetic declination was read at a number of stations throughout the survey and the average of these readings was found to be 12° 30' E.

Dependent Resurvey of Portion of West Bdy., of T. 6 S., R. 31 E., Establishing New Cors. for T. 6 S., R. 30 E., at Regular Intervals North from the Cor. of Tps. 6 and 7 S., Rs. 30 and 31 E.

Reestablishment of the survey executed by D. Drummond in 1891.

Beginning at the cor. of Tps. 6 and 7 S., Rs. 30 and 31 E., which is an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

N. 0° 05' W., on the W. bdy. of sec. 31, T. 6 S., R. 31 E.

Over broken land; asc. 75 ft. over SE. slope.

10.10 Ridge, bears N. 30° E. and S. 30° W.; desc. 370 ft. over rocky NW. slope.

34.80 Wash, 60 lks. wide, 4 ft. deep, drains N. 30° E.; asc. 75 ft. over rocky S. slope.

38.00 Top of ascent on knoll; desc. 30 ft. over N. slope.

39.51 The orig. 1/4 sec. cor. of secs. 31 and 36, Tps. 6 S., Rs. 30 and 31 E., monumented with a lava stone, 14x8x6 ins., firmly set, plainly mkd. in mound of stone. This point now functions as sec. cor. of sec. 31, T. 6 S., R. 31 E. only.

At the point for the cor.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S  
R31E  
1/4  
S31

1957

Deposit the original monument alongside the iron post.

N. 0° 12' W., beginning new measurement.

Dependent Resurvey, Portion of West Boundary, T. 6 S., R. 31 E.

Chains	
	Desc. 20 ft. over N. slope.
.49	Point for the $\frac{1}{2}$ sec. cor. of sec. 36, T. 6 S., R. 30 E.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S
	R30E
	S36
	1957
1.10	Four-strand barbed wire fence, bears E. and W.
6.00	Wash, 50 lks. wide, 2 ft. deep, course S. 80° E.; asc. 70 ft. over S. slope.
9.10	Spur, slopes S. 30° E.; desc. 60 ft. over NE. slope.
12.60	Wash, 40 lks. wide, 2 ft. deep, course SE.; asc. 160 ft. over S. slope.
28.70	Ridge, bears E. and W.; desc. 100 ft. over N. slope.
29.70	Four-strand barbed wire fence, bears NW. and SE.
39.20	Bottom of draw, drains N. 10° E.
39.50	The original cor. of secs. 25, 30, 31 and 36, T. 6 S., R. 30 and 31 E., mkd. by a malpais stone, 15x6x4 ins., firmly set and plainly mkd. in a mound of stone, as described in the official record. This point now functions as the cor. of secs. 30 and 31 only.
	At the point for the cor.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) cut in surface rock and supported in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S
	R30E R31E
	S36   S30
	S36   S31
	1957
	Deposit the original monument alongside the iron post.
	Land, broken.
	Soil, gravelly light clay and malpais rocks.
	Timber, thinly scattered scrub ; juniper.
	Undergrowth, scattered locust brush, catclaw and cacti.
	N. 0° 03' W., on the W. bdy. of sec. 30, T. 6 S., R. 31 E.
	Over rolling land; asc. 90 ft. over SW. slope.
.99	Point for the cor. of secs. 25 and 36, T. 6 S., R. 30 E.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S
	R30E R31E
	S25   S30
	S36   S30
	1957

BOOK 4013

## Dependent Resurvey of Portion of West Boundary, T. 6 S., R. 31 E.

Chains

10.60 Spur, slopes S. 25° E.; desc. 80 ft. over NE slope.

16.90 Drain, course N. 25° E.; asc. 150 ft. over S. slope.

36.50 Top of ascent, thence over rolling land.

40.22 The original  $\frac{1}{2}$  sec. cor. of secs 25 and 30, T. 6 S., R. 30 and 31, finally set by a malpais stone, 15x6x4 ins., firmly set, plainly mkd. and witnessed by a mound of stone. This point now functions as the  $\frac{1}{2}$  sec. cor. of sec. 30 only.

At the point for the cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S  
R31E  
|  
½  
S30  
1957

Deposit the original monument alongside the iron post.

N, 0° 04' E., beginning new measurement.

.77 Point for the  $\frac{1}{2}$  sec. cor. of sec. 25, T. 6 S., R. 30 E.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S  
R30E  
|  
½  
S25  
1957

Cont. over rolling land.

Base of slope; asc. 200 ft. over NE slope.

30.40 Wash, 30 lks. wide, 3 ft. deep, drains N. 30° E.; asc. 70 ft. over SE slope.

39.86 The original cor. of secs 19, 24, 25 and 30, T. 6 S., R. 30 and 31, finally set by a malpais stone, 12x6x4 ins., firmly set and plainly mkd. and witnessed by a mound of stone. This point now functions as the cor. of secs. 19 and 30 only.

At the point for the cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S  
R30E R31E  
S25 | S19  
      | S30  
1957

Deposit the original stone alongside the iron post.

Land, rolling.

Soil, light sandy clay and rocky.

Timber, thinly scattered scrub juniper.

Undergrowth, greasewood, cacti, locus brush.

## Dependent Resurvey, Portion of West Boundary, T. 6 S., R. 31 E.

Chains	
	N. 0° 03' W., on the W. bdy. of sec. 19. Over rolling land.
.91	Point for the cor. of secs. 24 and 25, T. 6 S., R. 30 E. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;">T6S R30E R31E S24   S19 S25   1957</div>
	Cont. over rolling land.
21.00	Wash, 50 lks. wide, 3 ft. deep, drains S. 20° E.; asc. 160 ft. over rocky SW. slope.
29.00	Slope changes to S.
35.10	Ridge, bears E. and W.; desc. 10 ft.
39.93	<del>The original ¼ sec. cor. of secs. 19 and 24, T. 6 S., R. 30 and 31 E., mkd. by a lava stone, 15x6x6 ins. firmly set, plainly mkd. and witnessed with a mound of stone. This point now functions as the ¼ sec. cor. of sec. 19 only.</del> At the point for the cor. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;">T6S R31E ¼ S19 1957</div> Deposit the original monument alongside the iron post.
	N. 0° 04' W., beginning new measurement.
.98	Point for the ¼ sec. cor. of sec. 24, T. 6 S., R. 30 E. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;">T6S R30E ¼ S24 1957</div>
	Desc. 140 ft. over rocky N. slope.
9.00	Wash, 60 lks. wide, 3 ft. deep, drains E.; thence along an E. slope.
30.10	Trail road, bears N. 70° W. and S. 70° E.; thence over rolling land.

## Dependent Resurvey of Portion of West Boundary of T. 6 S., R. 31 E.

Chains  
39.78

The cor. of secs. 13, 18, 19 and 24, mkd. by the original monument, a lava stone, 20x10x8 ins., firmly set and plainly mkd. and witnessed by a mound of stone.

At the point for the cor.

Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) cut in rock surface and supported in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S  
R30E R31E  
S13 | S18  
S24 | S19  
1957

Deposit the original monument alongside the iron post.

Land, rolling.

Soil, shallow light clay and rocky.

Timber, thinly scattered scrub juniper.

Undergrowth, cacti, greasewood and locus brush.

## Dependent Resurvey of Portion of the Subdivision, T. 6 S., R. 30 E.

Reestablishment of survey executed by D. Drummond in 1891.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., an iron post, 2½ ins. diam., previously described.

West, on the S. bdy. of sec. 13.

Over rolling land; desc. 10 ft.

2.00 Wash, 30 lks. wide, 3 ft. deep, course N. 30° E.; asc. 80 ft. over an E. slope.

9.10 Spur, slopes N. 8 chs. to end; desc. 80 ft. over W. slope.

15.00 Wash, 30 lks. wide, 2 ft. deep, drains N. 20° E.; asc. 230 ft. over rolling land sloping E.

40.25 Trail road, bears N. and S.

40.49 The original 4. set cor. of secs. 13 and 24, mkd. by a lava stone, 14x5x4 ins., firmly set and plainly mkd. and witnessed by a mound of stone. This point now functions as the 4. sec. cor. of sec. 13 only.

At the point for the cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E  
½ S13  
1957

Deposit the original cor. alongside the iron post.

N. 86° 44' W., beginning new measurement.

Asc. 40 ft. over E. slope.

## Dependent Resurvey of Portion of Subdivision of T. 6 S., R. 30 E.

Chains	
3.00	Slope changes to a NE. slope.
7.00	Ridge, bears NW. and SE.; desc. 130 ft. over rocky SW. slope.
20.60	Base of descent; asc. 150 ft. over SE. slope.
33.50	Spur, slopes SW.; desc. 80 ft. over NW. slope.
36.00	Slope changes to W.
40.32	<p>The original cor. of secs. 13 and 14, mkd. by a lava stone 15x10x6 ins., firmly set, plainly mkd. and witnessed by a mound of stone. This point now functions as the cor. of secs. 13 and 14 only.</p> <p>At the point for the cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E S14   S13 S23 1957</p> <p>Deposit the original monument alongside the iron post.</p> <p>Land, rolling. Soil, shallow light clay and rocky. Timber, none. Undergrowth, greasewood, catclaw and cacti.</p>
	<p>S. 88° 50' W., on the S. bdy. of sec. 14.</p> <p>Over rolling land; desc. 40 ft.</p>
3.70	Wash, 60 lks. wide, 3 ft. deep, drains S. 70° E.; asc. 180 ft. over SE. slope.
16.60	Ridge, bears N. 25° E. and S. 30° W.; desc. 50 ft. along SW. slope of a spur extending NW. from ridge.
40.62	<p>The original cor. of secs. 14 and 23, mkd. by a lava stone 15x8x4 ins., firmly set, plainly mkd. and witnessed by a mound of stone. This point now functions as the cor. of sec. 14 only.</p> <p>At the point for the cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R28E ½ S14 1957</p> <p>Deposit the original corner monument alongside the iron post.</p>
	<p>S. 88° 46' W., beginning new measurement.</p> <p>Desc. 20 ft.</p>
3.00	Base of descent; asc. 110 ft. along S. slope.



Dependent Resurvey of Portion of Subdivision of T. 6 S., R. 30 E.

Chains

20.05 Trail road, bears N. 70° E. and S. 70° W.; slope changes to SE.

21.00 Four-strand barbed wire fence, bears N. 70° E. and S. 70° W.

23.60 Ridge, bears N. 60° E. and S. 60° W.; desc. 20 ft.

40.18 The original sec. 14 cor. of secs. 14, 15, 22 and 23, laid by a 12x6x4 in. stone, firmly set, plainly mkd. and witnessed. This point now functions as the SW cor. of sec. 14.

At the point for the cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E  
| S14  
1957

Deposit the original stone alongside the iron post.

Land, rolling.

Soil, shallow light clay and rocky.

Timber, thinly scattered scrub juniper.

Undergrowth, greasewood, cacti and catclaw.

N. 1° 16' W., on the W. bdy. of sec. 14.

Over rolling land; desc. 70 ft. over N. slope.

8.00 Wash, 1 ch. wide, 4 ft. deep, drains E.; asc. 130 ft. over SE. slope.

20.00 Top of ascent, thence over rolling land.

33.70 Old railroad grade, bears N. 30° E. and S. 30° W.

39.97 The original sec. 14 cor. of secs. 14 and 15, mkd. by a 12x6x4 in. stone, firmly set, plainly mkd. and witnessed, by a mound of stone. This point now functions as the SW cor. of sec. 14 only.

At the point for the cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S R30E  
| ½  
| S14  
1957

Deposit the original monument alongside the iron post.

N. 0° 42' E., beginning new measurement.

Desc. 30 ft.

1.60 State Highway No. 666, an asphalt surfaced road, bears N. 60° E. and S. 60° W.; desc. 220 ft. over NW. slope.

27.70 Wash, 70 lks. wide, 3 ft. deep, drains N. along line from S. 15° W.

29.00 Leave wash, drains N. 15° E.; thence along an E. slope.

## Dependent Resurvey of Portion of Subdivision of T. 6 S., R. 30 E.

Chains	
32.00	Wash, drains E.; cont. along an E. slope.
40.105	<p>Point for the cor. of secs. 11 and 14, determined latitudinally at proportionate dist. and longitudinally at the record westing from the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14. There is no remaining evidence of the cor. originally set to function as the cor. of secs. 10, 11, 14 and 15.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E   S11   S14 1957</p> <p>Land, rolling. Soil, shallow light clay and rocky. Timber, none. Undergrowth, scattered catclaw, cacti and greasewood.</p>
	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14 is mkd. by the original monument, a malpais stone, 15x6x4 ins., firmly set, plainly mkd. and witnessed with a mound of stone.</p> <p>At the point for the cor.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E   S11   S14 1960 1957</p> <p>Deposit the original cornerstone alongside the iron post. N. <math>89^{\circ} 48'</math> W., bet. secs. 11 and 14.</p> <p>Over rolling land.</p>
13.30	Right-of-way fence, bears with highway.
15.30	State Highway No. 666, an asphalt surfaced highway, bears N. $35^{\circ}$ W. and S. $35^{\circ}$ E.
17.60	Right-of-way fence, bears with highway.
38.00	Wash, 50 lks. wide, 3 ft. deep, drains N. $10^{\circ}$ E.; asc. 50 ft.
40.03	<p>The cor. of secs. 11 and 14.</p> <p>Land, rolling. Soil, shallow light clay and rocky. Timber, none. Undergrowth, greasewood, catclaw and cacti.</p>
	<p>N. <math>0^{\circ} 15'</math> W., on the W. bdy. of sec. 11.</p> <p>Over rolling land; asc. 60 ft. over SE. slope.</p>

## Dependent Resurvey of Portion of Subdivision of T. 6 S., R. 30 E.

Chains	
9.50	Spur, slopes N. 65° E.; desc. 90 ft.
14.30	Wash, 30 lks. wide, 2 ft. deep, drains E. 5 chs., thence N. 60° E.; asc. 80 ft.
19.30	Spur, slopes E.; desc. 120 ft. over NE. slope.
40.10	<p>The original cor. of secs. 10 and 11, mkd. by a malpais stone, 12x6x4 ins., firmly set, plainly mkd. and witnessed, by 2 mounds of stone. This point now functions as the cor. of sec. 11 only.</p> <p>At the point for the cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E   ¼   S11 1960 1957</p> <p>Deposit the original cor. alongside the iron post.</p> <hr/> <p>N. 0° 15' E., beginning new measurement.</p> <p>Desc. 90 ft.</p>
17.90	Wash, 60 lks. wide, 3 ft. deep, drains NE.; asc. 90 ft.
32.60	Spur, slopes N. 20° E.; desc. 60 ft.
39.97	<p>The cor. of secs. 2, 3, 10 and 11, mkd. by the original malpais stone, 15x8x6 ins., firmly set, plainly mkd. and witnessed by a mound of stone.</p> <p>At the point for the cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E S3   S2 S10   S11 1957</p> <p>Deposit the original cornerstone alongside the iron post.</p> <p>Land, rolling. Soil, shallow light clay and rocky. Timber, thinly scattered scrub juniper. Undergrowth, greasewood, catclaw and cacti.</p>
	S. 89° 17' W., on the S. bdy. of sec. 3.
	Over rolling land; desc. 80 ft.
8.00	Wash, 30 lks. wide, 5 ft. deep, drains N.; asc. 100 ft. over rocky E. slope.
20.70	Spur, slopes N.; desc. 100 ft. over W. slope.
30.30	Wash, 80 lks. wide, 3 ft. deep, drains N.; asc. 80 ft. over E. slope.

## Dependent Resurvey of Portion of Subdivision of T. 6 S., R. 30 E.

Chains	
33.30	Spur, slopes N., 4 chs. to end; desc. 70 ft.
38.30	Wash, 1.20 chs. wide, 4 ft. deep, course N. 25° E.; asc. 30 ft.
39.99	<p>The original <del>cor.</del> sec. cor. of secs. 3 and 10, mkd. by a malpais stone, 9x5x3 ins., firmly set and plainly mkd. This point now functions as the <del>cor.</del> sec. cor. of sec. 3 only.</p> <p>At the point for the cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E  <math>\frac{1}{2}</math> S3  1957</p> <p>Deposit the original cornerstone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 56' W., beginning new measurement.</p> <p>Asc. 70 ft. over E. slope.</p>
3.60	Spur, slopes N.; desc. 40 ft. over NW. slope.
7.90	Slope changes to N.; asc. 160 ft. along broken N. slope on S. side of wash draining NE.
15.00	Same wash, 40 lks. wide, 4 ft. deep, drains easterly from SW.; asc. 80 ft.
24.00	Spur, projects N. 70° E.; thence along N. slope.
39.88	<p>The original <del>cor.</del> sec. cor. of secs. 3, 4, 19 and 10, mkd. by a malpais stone, 14x6x6 ins., firmly set, plainly mkd. This point now functions as the <del>cor.</del> of secs. 3 and 4 only.</p> <p>At the point for the cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E  S4   S3  S9  1957</p> <p>Deposit the original cornerstone alongside the iron post.</p> <p>Land, rolling and broken.  Soil, shallow light clay and rocky.  Timber, none.  Undergrowth, scattered catclaw, cacti, moderate greasewood.</p>
	N. 89° 53' W. on the S. bdy. of sec. 4.
	Over mountainous land; asc. 290 ft. over rocky E. slope.
17.50	Four-strand barbed wire fence, bears N. and S.
19.00	Slope changes to NE.
22.00	Spur, slopes N.; desc. 50 ft. over NW. slope.

## Dependent Resurvey of Portion of Subdivision of T. 6 S., R. 30 E.

Chains

26.00	Wash, course N.; asc. 80 ft. over NE. slope.
40.00	<p>The original cor. of secs. 4 and 9, mkd. by a <del>malpais</del> <del>stone</del>, <del>14x6x6 ins.</del>, firmly set and plainly mkd. and witnessed by a mound of <del>refly</del> <del>stone</del> <del>platts</del>. This point now functions as the cor. of sec. 4 only.</p> <p>At the point for the cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E S4 1957</p> <p>Deposit the original cornerstone alongside the iron post.</p> <p>Cor. is located in a saddle of a rocky spur sloping N.</p>
1.30	Begin descent of 380 ft. over rocky W. slope.
25.90	Wash, 60 lks. wide, 3 ft. deep, drains N.; asc. 230 ft. over rocky E. slope.
39.73	<p>The original cor. of secs. 4 and 5, by and 9, mkd. by a <del>malpais</del> <del>stone</del>, <del>14x6x6 ins.</del>, firmly set and plainly mkd. and witnessed by a mound of <del>refly</del> <del>stone</del> <del>platts</del>. This point now functions as the cor. of secs. 4 and 5 only.</p> <p>At the point for the cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E S5 S4 S 8 1957</p> <p>Deposit the original cornerstone alongside the iron post.</p> <p>Land, mountainous. Soil, rocky. Timber, thinly scattered scrub juniper. Undergrowth, moderate greasewood, cacti and catclaw.</p>
	N. 88° 24' W., on the S. bdy. of sec. 5.
	Over mountainous land; asc. 80 ft. over NE. slope.
12.00	Spur, slopes N.; desc. 120 ft. over W. slope.
20.00	Wash, drains N. 70° W.; thence along N. slope.
27.90	Wash, drains N. 20° E.; asc. 120 ft. over E. slope.
35.00	Top of ascent on hilltop; desc. 80 ft. over W. slope.
39.87	<p>The original cor. of secs. 5 and 8, mkd. by a <del>malpais</del> <del>stone</del>, <del>14x8x6 ins.</del>, firmly set and plainly mkd. and witnessed by a mound of <del>refly</del> <del>stone</del> <del>platts</del>. This point now functions as the cor. of sec. 5 only.</p> <p>At the point for the cor.</p>

## Dependent Resurvey of Portion of Subdivision of T. 6 S., R. 30 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

¼ S5

1957

Deposit the original monument alongside the iron post.

N. 89° 42' W., beginning new measurement.

4.00 Wash, course N. 30° W.; thence along a N. slope.

14.20 Wash, 50 lks. wide, 3 ft. deep, course NE.; asc. 450 ft. over NE. slope.

39.77 The original cor. of secs. 5, 6, 7 and 8, mkd. by a malpais stone, 15x6x4 ins., firmly set, 7 plainly mkd. and witnessed by a mound of stone. This point now functions as the cor. of secs. 5 and 6 only.

At the point for the cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 5 ft. base to top, with brass cap mkd.

T6S R30E

S6 | S5

8-7

1957

Deposit the original cornerstone alongside the iron post.

Land, mountainous.

Soil, shallow light clay and rocky.

Timber, thinly scattered scrub juniper.

Undergrowth, cacti, catclaw and locus brush.

N. 89° 51' W., on the S. bdy. of sec. 6.

Over mountainous land; asc. 30 ft.

3.00 Spur, slopes N.; desc. 240 ft. over NW. slope.

32.90 Wash, 40 lks. wide, 3 ft. deep, course N.; asc. 100 ft.

39.70 The original ¼ sec. cor. of secs. 6 and 7, mkd. by a 16x10x4 ins. lava stone, as described in the official record. This point now functions as the ¼ sec. cor. of sec. 6 only.

At the point for the cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S R30E

¼ S6

1957

Deposit the original cornerstone alongside the iron post.

S. 89° 29' W., beginning new measurement.

Asc. 40 ft. over an E. slope.

PLATE 4373

Dependant Resurvey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	
4.70	Spur, slopes N. 30° E.; desc. 80 ft. along N. slope.
18.00	Wash, drains N. 2 chs., thence N. 70° E.; asc. 200 ft. over E. slope.
28.80	Spur, slopes N. 20° E.; desc. 20 ft.
35.56	The cor. of secs. 1, 6, 7 and 12, mkd. by an iron post, 2½ ins. diam., conforming to the record.
	Land, mountainous. Soil, shallow light clay and rocky. Timber, thinly scattered scrub juniper. Undergrowth, cacti, greasewood and catclaw.
Original Survey of Portion of Subdivision, T. 6 S., R. 30 E.	
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., mkd. by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.
	N. 0° 01' W., bet. secs. 35 and 36.
	Over mountainous land; desc. 290 ft. over N. slope.
25.00	Slope changes to NW.
31.20	Wash, 40 lks. wide, 2 ft. deep, drains N. 60° E.; asc. 120 ft. over rocky SE. slope.
36.70	Small spur, slopes N. 55° E.; desc. 60 ft.
40.00	Point for the ¼ sec. cor. of secs. 35 and 36.
	Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S R30E ¼ S35 S36 1957
	Desc. 55 ft.
43.45	Wash, 50 lks. wide, 2 ft. deep, drains E.; asc. 190 ft. over rocky S. slope.
50.55	Top of ascent, bears E. and W.; desc. 40 ft. over nearly level top of bench.
69.30	Leave bench, bears E. and W.; desc. 140 ft. over N. slope.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.
	Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) cut in surface rock and supported in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S R30E S26 S25 S35 S36 1957
	Land, mountainous. Soil, shallow light clay and rocky. Timber, thinly scattered scrub juniper. Undergrowth, catclaw and cacti.

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	
	From the cor. of secs. 25 and 36, on the E. bdy. of the Tp. N. 89° 56' W., bet. secs. 25 and 36. Over mountainous land; asc. 320 ft. over rolling to broken E. slope.
13.70	Four-strand barbed wire fence, bears N. 80° W. and S. 60° E.
32.30	Wash, 40 lks. wide, 2 ft. deep, drains S. 70° E.
34.00	Slope changes to NE.
38.50	Slope changes to N.
40.09	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.  T6S R30E $\frac{1}{4}$ $\frac{S25}{S36}$ 1957
	Thence along a rolling to broken N. slope.
62.15	Wash, 40 lks. wide, 2 ft. deep, drains N. 20° E.
80.19	The cor. of secs. 25, 26, 35 and 36. Land, mountainous. Soil, rocky. Timber, very scattered scrub juniper. Undergrowth, scattered locus brush, yellow brush, catclaw, cacti, heavy native grasses.
	N. 0° 01' W., bet. secs. 25 and 26. Over mountainous land.
1.50	Wash, 1 ch. wide, 2 ft. deep, drains E.; thence over rolling to broken land; asc. 150 ft. over general S. slope.
16.00	Wash, 30 lks. wide, 1 ft. deep, drains S. 20° E.; asc. 350 ft. over S. slope.
32.35	Ridge, bears E. and W.; desc. 50 ft. over N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.  T6S R30E $\frac{1}{4}$ S26   S25 1957
	Cont. to desc. 340 ft. over N. slope to sec. cor.
65.00	Draw, drains E.
71.90	Wash, 50 lks. wide, 4 ft. deep, drains N. 30° E.
72.60	Same wash, drains N. 35° W., 3 chs., thence N.
78.90	Same wash, drains NE. 1 ch., thence N.; thence along a W. slope.



## BOOK 4618

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains 80.00	<p>Point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E S23 S24 S26 S25 1957</p> <p>Land, mountainous. Soil, shallow light clay and rocky. Timber, none. Undergrowth, scattered locus brush, catclaw, cacti, heavy native grasses.</p>
36.20	<p>From the cor. of secs. 24 and 25, on the E. bdy. of the Tp. N. 89° 58' W., bet. secs. 24 and 25.</p> <p>Over mountainous land; asc. 430 ft. over E. slope of ridge.</p> <p>Ridge, bears N. and S.; desc. 20 ft. over rocky W. slope.</p>
40.15	<p>Point for the ¼ sec. cor. of secs. 24 and 25.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E ¼ S24 ¼ S25 1957</p> <p>Desc. 310 ft. over W. slope.</p>
50.00	<p>Draw, drains N. 15° W.; asc. 280 ft. over E. slope.</p>
66.80	<p>Spur, slopes N. 5° W.; desc. 220 ft. over W. slope.</p>
80.30	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, mountainous. Soil, rocky. Timber, very scattered scrub juniper. Undergrowth, scattered locus brush, catclaw, cacti, native grass.</p>
10.40	<p>N. 0° 01' W., bet. secs. 23 and 24.</p> <p>Over mountainous land; asc. 40 ft. along W. slope.</p> <p>Top of ascent on spur sloping N. 70° W.; desc. 120 ft. over general N. slope.</p>
20.05	<p>Wash, 30 lks. wide, drains N. 85° E.; asc. 140 ft. over rocky SW. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 23 and 24.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains

T6S R30E

$$\begin{array}{r} \frac{1}{2} \\ \hline S23 | S24 \end{array}$$

1957

Asc. 30 ft. over SW. slope.

52.50 Ridge, bears N. 30° W. and S. 30° E.; desc. 310 ft. over NE. slope.

68.80 Wash, 60 lks. wide, 2 ft. deep, drains E.; asc. 70 ft. over SW. slope.

72.00 Slope changes to W.

81.04 Intersect the S. bdy. of sec. 13 at the point for the closing cor. of secs. 23 and 24.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

S13

$$\begin{array}{r} \hline S23 | S24 \end{array}$$

C C

1957

From this closing cor. the cor. of secs. 13 and 14 bears N. 86° 44' W., 40 lks. dist., an iron post, 2½ ins. diam., hereinbefore described.

Land, mountainous.

Soil, rocky.

Timber, thinly scattered scrub juniper.

Undergrowth, scattered locus brush, catclaw, greasewood, cacti and grass.

The point for the ½ sec. cor. of sec. 24, on the N. bdy. of the sec. is at midpoint bet. the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp. and the closing cor. of secs. 23 and 24.

At the point for the cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

$$\begin{array}{r} \frac{1}{2} \\ \hline S24 \end{array}$$

1957

From this cor. the ½ sec. cor. of sec. 13 bears West 32 lks. dist., an iron post, 2½ ins. diam., hereinbefore described.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., mkd. by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record.

N. 0° 01' W., bet. secs. 34 and 35.

Over mountainous land.

BOOK 4018

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	
.40	Wash, 60 lks. wide, 2 ft. deep, drains N. 35° E.; asc. 120 ft. over SE. slope.
11.60	Spur, slopes E.; desc. 150 ft. over rocky general N. slope.
22.30	Wash, 30 lks. wide, 2 ft. deep, drains N. 70° E.; asc. 110 ft. over S. slope.
31.90	Spur, slopes E.; desc. 80 ft. over N. slope.
39.55	Trail road, bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.  Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T6S R30E $\frac{1}{4}$ S34 S35 1957
	Desc. 40 ft.
41.90	Drain, course NE.; desc. 120 ft. over rolling land.
63.00	Trail road, bears SW. and NE.
65.00	Wash, 3 ft. deep, 60 lks. wide, course NE.; asc. 70 ft.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.  Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T6S R30E S27 S26 S34 S35 1957
	Land, rolling and broken. Soil, shallow light clay and rocky. Timber, none. Undergrowth, catclaw, cacti and grass.
	From the cor. of secs. 25, 26, 35 and 36.  West, bet. secs. 26 and 35.  Over rocky rolling land; asc. 90 ft. along N. slope.
2.50	Wash, 2 ft. deep, 1 ch. wide, course N. 80° E.; asc. 60 ft.
19.50	Top of ascent; desc. 80 ft.
29.50	Drain, course NE.; asc. 140 ft.
40.12	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.  Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T6S R30E $\frac{1}{4}$ S26 S35 1957

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	
	Cor. is located on ridge bearing NE. and SW. Thence by triangulation, with calls of topography estimated; desc. over NW. slope.
47.00	Trail road, bears N. and S. 70° W.
62.00	Wash, 20 lks. wide, 3 ft. deep, course NE.
70.00	Wash, course NE.; asc. 80 ft. over E. slope.
80.24	The cor. of secs. 26, 27, 34 and 35.  Land, rolling. Soil, rocky. Timber, none. Undergrowth, catclaw, scattered cacti and grass.
	N. 89° 57' W., bet. secs. 27 and 34.  Over broken land; asc. 80 ft. over NE. slope.
10.00	Top of ascent on hillside, sloping NE.; desc. 60 ft. along N. slope.
21.60	Wash, 1 ch. wide, 4 ft. deep, course N. 80° E.; asc. 200 ft. over SE. slope.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.  Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd.  T6S R30E $\frac{1}{4}$ $\frac{S27}{S34}$ 1957
	Asc. 440 ft. over SE. slope.
80.02	The cor. of secs. 27, 28, 33 and 34, mkd. by an iron post, 2 ins. diam., conforming to the record.  Land, mountainous. Soil, shallow clay and rocky. Timber, thinly scattered scrub juniper. Undergrowth, catclaw and cacti.
	From the cor. of secs. 26, 27, 34 and 35.  N. 0° 01' W., bet. secs. 26 and 27,  Over rolling land; desc. 60 ft. over NE. slope.
3.80	Wash, 1 ch. wide, 4 ft. deep, course E.; asc. 90 ft. over SE. slope.
12.40	Spur, slopes E.; desc. 100 ft. over N. slope.
20.60	Trail road, bears N. 70° W. and S. 70° E.
22.80	Wash, 60 lks. wide, 4 ft. deep, course NE.; asc. 300 ft. over SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.

BOOK 4618

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T6S R30E

$$\frac{1}{2}$$

S27		S26
1957		

- 41.00 Top of ascent on hillside, sloping E.; desc. 200 ft. over NE. slope.
- 57.30 Wash, drains NW.; asc. 120 ft. along SW. slope.
- 72.00 Thence along a W. slope.
- 80.00 Point for the cor. of secs. 22; 23, 26 and 27.

Set an iron post, 30 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T6S R30E

S22		S23
S27		S26
1957		

Land, rolling.  
Soil, shallow light clay and rocky.  
Timber, none.  
Undergrowth, cacti and catclaw.

From the cor. of secs. 23, 24, 25 and 26.

N. 89° 57' W., bet. secs. 23 and 26.

Over broken land.

- 40.16 Point for the ¼ sec. cor. of secs. 23 and 26.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T6S R30E

$$\frac{1}{4}$$

S23		S26
1957		

Cont. over broken land.

- 80.31 The cor. of secs. 22, 23, 26 and 27.

Land, broken.  
Soil, shallow light clay and rocky.  
Timber, none.  
Undergrowth, cacti and catclaw.

N. 89° 51' W., bet. secs. 22 and 27.

Over rolling land; desc. 220 ft. over W. slope.

- 21.00 Wash, drains N. 20° E.
- 26.00 Wash, drains N. 80° E. from N. 60° W.; asc. 100 ft. over NE. slope.

BOOK 4618

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains 39.88	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 27.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E <math>\frac{1}{4}</math> <math>\frac{S22}{S27}</math> 1957</p> <p>Asc. 480 ft. over NE. slope.</p>
69.60	<p>Spur, slopes N.; desc. 240 ft. over W. slope.</p>
79.76	<p>The cor. of secs. 21, 22, 27 and 28, an iron post, 2 ins. diam., conforming to the record.</p> <p>Land, rolling. Soil, shallow light clay and rocky. Timber, none. Undergrowth, catclaw and cacti.</p>
36.10	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. <math>0^{\circ} 01'</math> W., bet. secs. 22 and 23.</p> <p>Over rolling land; desc. 320 ft. over top of spur sloping N.</p> <p>Wash, 4 ft. deep, 60 lks. wide, course E.</p>
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 4 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E <math>\frac{1}{4}</math> S22   S23 1957</p>
79.26	<p>Intersect the S. bdy. of sec. 14 at the point for the closing cor. of secs. 22 and 23.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground, in a mound of stone, <math>3\frac{1}{2}</math> ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E S14 S22   S23 C C 1957</p> <p>From this cor. the SW. cor. of sec. 14 bears S. <math>88^{\circ} 46'</math> W., 1.12 chs. dist., an iron post, <math>2\frac{1}{2}</math> ins. diam., hereinbefore described.</p> <p>Land, rolling. Soil, shallow light clay and rocky. Timber, none. Undergrowth, cacti and catclaw.</p>
	<p>The point for the <math>\frac{1}{4}</math> sec. cor. of sec. 23 is at midpoint on the N. bdy. of sec. 23, and on the S. bdy. of sec. 14.</p>

BOOK 4618

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

¼ S23

1957

From this cor. the ¼ sec. cor. of sec. 14 bears S, 88° 50' W., 98 lks. dist., an iron post, 2½ ins. diam., hereinbefore described.

From the cor. of secs. 21, 22, 27 and 28.

N. 0° 02' W., bet. secs. 21 and 22.

Over rocky mountainous land; desc. 230 ft. over NW. slope.

15.00 Wash, 1.00 ch. wide, 3 ft. deep, drains N. 20° W. from SW.; asc. 90 ft. over SW. slope.

23.00 Point, bears W.; desc. 100 ft. over NW. slope.

31.08 Fence, 4-strand barbed wire, bears N. 70° E. and S. 70° W.

31.50 Trail road, bears S. 70° W. and SE.; desc. 10 ft. over NW. slope.

36.10 Same wash, drains NE.; asc. 20 ft. over SE. slope.

40.00 Point for the ¼ sec. cor. of secs. 21 and 22.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.

T6S R30E

¼ S21 | S22

1957

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

40.80 Fence, 4-strand barbed wire, bears SW. and NE.; asc. 30 ft. over SE. slope.

42.80 State Highway 666, bears NE. and SW.; asc. 20 ft. over SE. slope.

44.80 Fence, 4-strand barbed wire, bears SW. and NE.; asc. 610 ft. over steep and rocky SE. slope.

72.40 Ridge, bears NE. and SW.; desc. 100 ft. over rocky NW. slope.

80.00 Point for the cor. of secs. 15, 16, 21 and 22.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

S16 | S15

S21 | S22

1957

Land, mountainous.

Soil, gravelly, light clay and rocky.

Timber, very scattered juniper.

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

## Chains

East, bet. secs. 15 and 22.

Over rocky mountainous land, through scattered timber; asc. 60 ft. over NW. slope.

6.20 Ridge, bears SW. and slopes sharply NE.; desc. 340 ft. over steep SE. slope.

32.02 Fence, 4-strand barbed wire, bears NE. and SW.

33.97 State Highway 666, bears N. 46° E. and S. 46° W.; desc. 30 ft. over SE. slope.

39.97 Point for the  $\frac{1}{4}$  sec. cor. of sec. 22, at midpoint on the N. bdy. of sec. 22Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 $\frac{1}{2}$  ft. base to top, with brass cap mkd.

T6S R30E

 $\frac{1}{4}$  S22

1957

40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 15.Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 8 ins. in the ground to bedrock, in a mound of stone to top, 4 ft. base, with brass cap mkd.

T6S R30E

 $\frac{1}{4}$  S15

1957

40.30 Trail road, bears N. and S. 2.00 chs., thence N. 70° E.; desc. 40 ft. over rolling SE. slope.

45.80 Same road, bears N. 70° E. and S. 70° W.; desc. 90 ft. over rolling SE. slope.

75.00 Wash, 1.50 chs. wide, 10 ft. deep, drains irregularly NE.; asc. 40 ft. over NW. slope.

78.80 Intersect the W. bdy. of sec. 14.

Point for the closing cor. of secs. 15 and 22.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S R30E

C S15 S14

C S22

1957

From this cor. the SW. cor. of sec. 14 bears S. 1° 16' E., 1.04 chs. dist., an iron post, 2 $\frac{1}{2}$  ins. diam., previously described.

Land, mountainous.

Soil, gravelly, light clay and rocky.

Timber, scattered juniper.

From the cor. of secs. 15, 16, 21 and 22.

N. 0° 02' W., bet. secs. 15 and 16.



## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	Over rocky mountainous land; desc. 540 ft. over steep NW. slope.
25.40	Wash, 1.00 ch. wide, 3 ft. deep, drains NE.; asc. 80 ft. over SE. slope.
30.60	Small stock reservoir, bears E. 1.50 chs. dist.; asc. 100 ft. over steep SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T6S R30E $\frac{1}{4}$ S16   S15 1957
	Asc. 150 ft. over SE. slope.
58.00	Spur, bears N. $40^{\circ}$ E.; desc. 250 ft. over steep N. slope.
69.60	Wash, 1.00 ch. wide, 3 ft. deep, drains NE. from W.; asc. 340 ft. over steep SE. slope.
80.00	Point for the cor. of secs. 9, 10, 15 and 16. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S R30E S. 9   S10 S16   S15 1960 1957
	Land, mountainous. Soil, gravelly, light clay and rocky. Timber, none.
	East, bet. secs. 10 and 15.
	Over rocky mountainous land; desc. 280 ft. over steep SE. slope.
12.00	Wash, 1.00 ch. wide, 3 ft. deep, drains NE.; asc. 80 ft. over NW. slope.
20.60	Spur, bears NE.; desc. 200 ft. over SE. slope.
35.40	Trail road, bears NE. and SW.; desc. 40 ft. over SE. slope.
38.80	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 10 and 15. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T6S R30E $\frac{1}{4}$ S10 W S15 C 1957
39.90	Wash, 1.00 ch. wide, 3 ft. deep, drains NE.
40.00	True point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15 falls in wash where cor. cannot be perpetuated.

BOOK 4618

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains

Asc. 90 ft. over NW. slope.

48.70 Spur, bears NE.; trail road, bears NE. and SW.; desc. 100 ft. over rolling NE. slope.

71.80 Begin descent over steep E. slope; desc. 140 ft.

78.48 Intersect the W. bdy. of sec. 11.

Point for the closing cor. of secs. 10 and 15.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

	T6S	R30E
C	S10	S11
C	S15	
	1960	

From this cor. the sec. cor. of secs. 11 and 14 bears S. 0° 15' E., .845 chs. dist., an iron post, 2½ ins. diam., previously described.

Land, mountainous.

Soil, gravelly, light clay and rocky.

Timber, none.

Point for the E. ¼ sec. cor. of sec. 15 is on the W. bdy. of sec. 14 an at midpoint on the E. bdy. of sec. 15.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.

	T6S	R30E
		¼
	S15	
	1960	

From this cor. the ¼ sec. cor. of secs. 14 bears S. 0° 42' W., 1.02 chs. dist., an iron post, 2½ ins. diam., previously described.

Point for the E. ¼ sec. cor. of sec. 10 is on the W. bdy. of sec. 11 and 40 chs. N. from the closing cor. of secs. 10 and 15.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.

	T6S	R30E
		¼
	S10	
	1960	

From this cor. the ¼ sec. cor. of sec. 10 bears S. 0° 15' W., 74 lks. dist., an iron post, 2½ ins. diam., previously described.

From the cor. of secs. 9, 10, 15 and 16.

N. 0° 02' W., bet. secs. 9 and 10.

Over rocky mountainous land; asc. 70 ft. over SE. slope.

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	
3.80	Spur, bears N. 60° E.; desc. 320 ft. over steep N. slope.
19.50	Head of wash, 20 lks. wide, 4 ft. deep, drains irregularly N.; desc. 240 ft. over steep N. slope along wash.
37.70	Stock water reservoir, thence along right bank of wash.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.  Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.  T6S R30E $\frac{1}{4}$ S 9   S10 1960 1957  Desc. 20 ft. over N. slope.
43.90	Junction of washes, drains NE. from W. and S.; asc. 80 ft. over SE. slope.
56.00	Spur, bears E.; desc. 100 ft. over NE. slope.
64.30	Wash, 20 lks. wide, 6 ft. deep, drains E.; asc. 80 ft. over SE. slope.
70.50	Spur, bears E.; desc. 120 ft. over N. slope.
79.56	Intersect the S. bdy. of sec. 3.  Point for the closing cor. of secs. 9 and 10.  Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.  T6S R30E S3 S 9   S10 C C 1960 1957  From this cor. the cor. of secs. 3 and 4 bears N. 88° 56' W., 1.14 chs. dist., an iron post, 2½ ins. diam., previously described.  Land, mountainous. Soil, gravelly, light clay and rocky. Timber, none.
	True point for the N. $\frac{1}{4}$ sec. cor. of sec. 10 is on the S. bdy. of sec. 3 and at an easting of 40.00 chs. from the closing cor. of secs. 9 and 10, falls in wash where cor. cannot be perpetuated.  Point selected for the witness cor. of sec. 10, bears S. 89° 17' W., 1.10 chs. dist.  Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock; in a mound of stone, 4 ft. base to top, with brass cap mkd.  T6S R30E W $\frac{1}{4}$ S10 C 1960

BOOK 4618

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains

From the true point the  $\frac{1}{4}$  sec. cor. of sec. 3 bears S.  $89^{\circ} 17' W.$ , 1.26 chs. dist., an iron post,  $2\frac{1}{2}$  ins. diam., previously described.

From the cor. of secs. 20, 21, 28 and 29, mkd. by an iron post, 2 ins. diam., conforming to the record.

N.  $0^{\circ} 02' W.$ , bet. secs. 20 and 21.

Over mountainous land; desc. 90 ft. over NE. slope.

4.50 Wash, 40 lks. wide, 2 ft. deep, course SE.; asc. 480 ft. over SW. slope.

27.10 Fence, bears E. and W. on top of ridge bearing NW. and SE.; asc. 40 ft. along an E. slope.

35.70 A finger of the same ridge, extends 30 chs. N.  $60^{\circ} E.$ ; desc. 40 ft.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 20 and 21.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 4 ins. in the ground, to solid rock, supported in a mound of stone,  $3\frac{1}{2}$  ft. base to top, with brass cap mkd.

T6S R30E

$\frac{1}{4}$   
S20 | S21  
1957

Desc. 500 ft. over steep N. slope.

61.00 Wash, course N.  $70^{\circ} E.$ ; asc. 250 ft. over S. slope.

80.00 Point for the cor. of secs. 16, 17, 20 and 21.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

S17 | S16  
S20 | S21  
1957

Land, mountainous.  
Soil, shallow light clay and rocky.  
Timber, thinly scattered scrub juniper.  
Undergrowth, catclaw and cacti.

From the cor. of secs., 15, 16, 21 and 22.

S.  $89^{\circ} 57' W.$ , bet. secs. 16 and 21.

Over mountainous land, through widely scattered timber; desc. 380 ft. over steep NW. slope.

18.20 Ravine, drains NE.; asc. 120 ft. over NE. slope.

27.20 Spur, bears NE.; desc. 140 ft. over NW. slope.

37.78 Point selected for the witness  $\frac{1}{4}$  sec. cor. of secs. 16 and 21.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 15 ins. in the ground to bedrock, in a mound of stone,  $3\frac{1}{2}$  ft. base to top, with brass cap mkd.

BOOK 412

Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	
	T6S R30E W $\frac{1}{2}$ S16 C S21 1960 1957.
39.80	Wash, 1.00 ch. wide, 3 ft. deep, drains N. 60° E.
39.93	True point for the $\frac{1}{2}$ sec. cor. of secs. 16 and 21 falls in wash where cor. cannot be perpetuated.  Asc. 500 ft. over steep and rocky SE. slope.
78.90	Ridge, bears N. 60° E. and S. 60° W.
79.85	The cor. of secs. 16, 17, 20 and 21.  Land, mountainous. Soil, gravelly, light clay and rocky. Timber, widely scattered juniper.
	N. 0° 02' W., bet. secs. 16 and 17.  Over mountainous land, through widely scattered timber; desc. 390 ft. over steep and rocky NW. slope.
15.60	Ravine, drains N. 60° E.; asc. 560 ft. over steep and rocky SE. slope.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 16 and 17.  Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S R30E $\frac{1}{2}$ S17 S16 1960 1957
	Asc. 40 ft. over SE. slope.
47.30	Ridge, bears E. and W.
49.40	Fence, 4-strand barbed wire, bears SW. and irregularly NE.; desc. 440 ft. over steep NW. slope.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.  Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S R30E S8 S9 S17 S16 1960 1957
	Land, mountainous. Soil, gravelly, light clay and rocky. Timber, widely scattered juniper.
	From the cor. of secs., 9, 10, 15 and 16. S. 89° 59' W., bet. secs. 9 and 16.

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	Over rocky mountainous land; asc. 80 ft. over steep SE. slope.
7.20	Spur, bears NE.; thence along steep N. slope.
39.91	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S R30E $\frac{1}{4}$ $\frac{S 9}{S16}$ 1960 1957
	Cont. along N. slope.
43.00	Ravine, drains N. $60^\circ$ E.; asc. 520 ft. over steep E. slope.
65.80	Fence, 4-strand barbed wire, bears SW. and N. $20^\circ$ E., along ridge top.
66.40	Ridge, bears SW. and N. $20^\circ$ E.; desc. 360 ft. over steep W. slope.
79.82	The cor. of secs. 8, 9, 16 and 17. Land, mountainous. Soil, gravelly, light clay and rocky. Timber, none.
	N. $0^\circ 02'$ W., bet. secs. 8 and 9. Over rocky mountainous land; desc. 120 ft. along steep W. slope.
29.40	Slope changes to steep NW. slope; desc. 320 ft.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T6S R30E $\frac{1}{4}$ $\frac{S8}{S9}$ 1960 1957
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of cor. Desc. 200 ft. over steep N. slope.
53.00	Slope changes to NW.; desc. 160 ft.
61.50	Wash, 60 lks. wide, 2 ft. deep, drains NE.; asc. 100 ft. over SE. slope.
79.74	Intersect the S. bdy. of sec. 4. Point for the closing cor. of secs. 8 and 9. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T6S R30E $\frac{1}{4}$ $\frac{S4}{S4}$

BOOK 4018

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains

T6S R30E

S 4

S8 | S9

C C

1960

1957

From this cor. the cor. of secs. 4 and 5 bears N. 89° 56' W., 1.26 chs. dist., an iron post, 2½ ins. diam., previously described.

Land, mountainous.

Soil, gravelly, light clay and rocky.

Timber, none.

Point for the N. ¼ sec. cor. of sec. 9 is on the S. bdy. of sec. 4 and at midpoint on the N. bdy. of sec. 9.

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

¼ S9

1957

From this cor. the ¼ sec. cor. of sec. 4 bears N. 89° 53' W., 1.33 chs. dist., an iron post, 2½ ins. diam., previously described.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., an iron post, 2 ins. diam., conforming to the record.

N. 0° 03' W., bet. secs. 31 and 32.

Over mountainous land; asc. 20 ft.

7.70 Wash, 40 lks. wide, 3 ft. deep, course S. 25° E.; asc. 510 ft. over S. slope.

40.00 Point for the ¼ sec. cor. of secs. 31 and 32.

Set an iron post, 2½ ins. diam., 30 ins. long, on solid rock, supported in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

S31 | S32

1957

Asc. 270 ft. over S. slope.

64.80 Ridge, bears N. 30° W. and S. 30° E.; desc. 250 ft. over NE. slope.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

S30 | S29

S31 | S32

1957

BOOK 4618

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains

Land, mountainous.  
Soil, shallow light clay and rocky.  
Timber, scattered scrub juniper.

From the cor. of secs. 28, 29, 32 and 33, an iron post, 2 ins. diam., conforming to the record.

N. 89° 57' W., bet. secs. 29 and 32.

Over mountainous land; asc. 240 ft. over SE. slope.

40.03 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

$\frac{1}{4}$  S29

$\frac{1}{4}$  S32

1957

Asc. 240 ft. over SE. slope.

64.80 Wash, 40 lks. wide, 2 ft. deep, course S. 60° E.; asc. 320 ft. over NE. slope.

80.05 The cor. of secs. 29, 30, 31 and 32.

Land, mountainous.

Soil, gravelly light clay and rocky.

Timber, none.

N. 89° 58' W., bet. secs. 30 and 31.

Over mountainous land; asc. 440 ft. over NE. slope.

13.10 Top of ascent on ridge, bears N. 20° W. and S. 20° E.; desc. 360 ft. over W. slope.

27.00 Wash, drains S. 20° W.; asc. 40 ft.

31.00 Spur, slopes S.; desc. 200 ft. over SW. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 30 and 31.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T6S R30E

$\frac{1}{4}$  S30

$\frac{1}{4}$  S31

1957

40.10 Wash, drains S.; asc. 640 ft. over E. slope.

65.20 Spur, slopes S.; desc. 240 ft. over W. slope.

76.21 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., an iron post, 2½ ins. diam., conforming to the record.

Land, mountainous.

Soil, gravelly light clay and rocky.

Timber, scattered scrub juniper.



BOOK 487

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 03' W., bet. secs. 29 and 30.

Over mountainous land; desc. 40 ft. over NE. slope.

4.00 Wash, drains S. 60° E.; asc. 660 ft. over S. slope.

31.30 Spur, slopes steeply to the E.; desc. 240 ft. over N. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 30.

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to solid rock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.

T6S R30E

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S30} | \text{S29} \\ 1957 \end{array}$$

Desc. 680 ft. over NE. slope.

70.10 Wash, drains S. 70° E.; asc. 80 ft. along SE. slope.

80.00 Point for the cor. of secs. 19, 20, 29 and 30.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S R30E

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S19} | \text{S20} \\ \text{S30} | \text{S29} \\ 1957 \end{array}$$
Land, mountainous.  
Soil, gravelly light clay and rocky.  
Timber, scattered scrub juniper.

From the cor. of secs. 20, 21, 28 and 29, an iron post, 2 ins. diam., conforming to the record.

N. 89° 47' W., bet. secs. 20 and 29.

Over mountainous land; asc. 560 ft. over NE. slope.

40.05 Point for the  $\frac{1}{4}$  sec. cor. of secs. 20 and 29.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T6S R30E

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S20} \\ \text{S29} \\ 1957 \end{array}$$

Asc. 200 ft. over NE. slope.

53.50 Spur, slopes S. 60° E.; desc. 280 ft. over SW. slope.

75.80 Wash, drains SE.; asc. 100 ft.

80.09 The cor. of secs. 19, 20, 29 and 30.

Land, mountainous.  
Soil, gravelly light clay and rocky.  
Timber, scattered scrub juniper.

Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	<p>N. 89° 55' W., bet. secs. 19 and 30.</p> <p>Over mountainous land; asc. 760 ft. over SE. slope.</p> <p>39.50 Top of ascent, bears N. 20° E. and S. 20° W.; asc. 40 ft. along a N. slope.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 19 and 30.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E ¼ S19 S30 1958</p> <p>Asc. 120 ft. along N. slope.</p> <p>76.16 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., an iron post, 2½ ins. diam., conforming to the record.</p> <p>Land, mountainous. Soil, gravelly light clay and rocky. Timber, scattered scrub juniper.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 03' W., bet. secs. 19 and 20.</p> <p>Over mountainous land; along and E. slope.</p> <p>7.50 Wash, drains SE.; asc. 560 ft. over S. slope.</p> <p>24.70 Fence, 4-strand barbed wire, bears N. 60° E. and S. 60° W.</p> <p>25.50 Top of ascent, bears NE. and S. 60° W.; desc. 400 ft. over NW. slope.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to solid rock, supported in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E ¼ S19   S20 1957</p> <p>Desc. 540 ft. over NW. slope.</p> <p>64.00 Wash, drains NE.; asc. 140 ft. along E. slope.</p> <p>80.00 Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, supported in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R30E S18   S17 S19   S20 1957</p> <p>Land, mountainous. Soil, gravelly light clay and rocky. Timber, scattered scrub juniper.</p>

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	From the cor. of secs. 16, 17, 20 and 21. N. 89° 51' W., bet. secs. 17 and 20.  Over rocky mountainous land; desc. 240 ft. over steep NW. slope.
20.10	Wash, 70 lks. wide, 3 ft. deep, drains NE.; asc. 320 ft. over steep SE. slope.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.  Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.  T6S R30E $\frac{1}{4}$ <u>S17</u> S20 1960 1957
	Thence along steep S. slope.
76.70	Top of ascent on S. slope; desc. 10 ft. over SW. slope.
80.08	The cor. of secs. 17, 18, 19 and 20.  Land, mountainous. Soil, gravelly, light clay and rocky. Timber, none.
	S. 89° 50' W., bet. secs. 18 and 19.  Over rocky mountainous land; desc. 20 ft. over SW. slope.
3.00	Ravine, drains SE.; asc. 680 ft. over steep NE. slope.
29.00	Slope changes to E.; asc. 60 ft.
33.70	Spur, bears S. 20° W.; desc. 60 ft. over W. slope.
38.60	Fence, 4-strand barbed wire, bears S. 20° W. and N. 20° E.; desc. 40 ft. over W. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.  Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 $\frac{1}{2}$ ft. base to top, with brass cap mkd.  T6S R30E $\frac{1}{4}$ <u>S18</u> S19 1960 1958
	Desc. 120 ft. over W. slope.
47.50	Slope changes to N.; thence along steep N. slope.
64.10	Slope changes to W.; desc. 260 ft.
75.96	The cor. of secs. 13, 18, 19 and 24, an iron post, 2 $\frac{1}{2}$ ins. diam., conforming to the 1955 survey.  Land, mountainous. Soil, gravelly, light clay and rocky. Timber, none.

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains	From the cor. of secs. 17, 18, 19 and 20. N. 0° 03' W., bet. secs. 17 and 18.
	Over rocky mountainous land, through widely scattered timber; asc. 480 ft. over steep S. slope.
15.90	Ridge, bears E. and W.; fence, 4-strand barbed wire, bears same; desc. 520 ft. over steep NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.  T6S R30E $\frac{1}{4}$ S18   S17 1960 1957
	Desc. 150 ft. along E. slope.
67.60	Head of ravine, drains E.; asc. 110 ft. over SE. slope.
80.00	Ridge, bears S. 15° W. and N. 15° E.; point for the cor. of secs. 7, 8, 17 and 18. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.  T6S R30E S77   S 8 S18   S17 1960 1957
	Land, mountainous. Soil, gravelly, light clay and rocky. Timber, widely scattered juniper.
	From the cor. of secs. 8, 9, 16 and 17. N. 89° 52' W., bet. secs. 8 and 17.
	Over rocky mountainous land, through widely scattered timber; desc. 440 ft. over steep W. slope.
17.30	Wash, 1.50 chs. wide, 5 ft. deep, drains N. 15° E.; asc. 360 ft. over steep E. slope.
31.00	Spur, bears NE.; desc. 140 ft. over NW. slope.
40.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.  T6S R30E $\frac{1}{4}$ S. 8 S17 1960 1957
	Desc. 200 ft. over steep NW. slope.
46.90	Wash, 50 lks. wide, 4 ft. deep, drains NE.; asc. 760 ft. over steep E. slope.

BOOK 4918

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains 80.14	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, mountainous. Soil, gravelly, light clay and rocky. Timber, widely scattered juniper.</p>
14.80	<p>N. 89° 44' W., bet. secs. 7 and 18.</p> <p>Over rocky mountainous land, through widely scattered timber; desc. 400 ft. over steep W. slope.</p> <p>Ravine, drains N. 8.00 chs. thence NW.; asc. 280 ft. over steep E. slope.</p>
23.30	Slope changes to NE.; asc. 100 ft.
40.00	<p>Spur, bears NW.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 18.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R30E <math>\frac{1}{4}</math> S 7 S18 1960 1957</p>
62.90	<p>Desc. 440 ft. over steep SW. slope.</p> <p>Ravine, drains NW.</p>
66.20	Ravine, drains N. 3.00 chs. to above wash, thence NW.; asc. 100 ft. over NE. slope.
73.00	Fence, 4-strand barbed wire, bears NW. and SE.; asc. 20 ft. over NE. slope.
75.97	<p>The cor. of secs. 7, 12, 13 and 18, an iron post, <math>2\frac{1}{2}</math> ins. diam., conforming to the 1955 survey.</p> <p>Land, mountainous. Soil, gravelly, light clay and rocky. Timber, widely scattered juniper.</p>
22.50	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0° 03' W., bet. secs. 7 and 8.</p> <p>Over mountainous land, through widely scattered timber; along W. slope of ridge.</p> <p>Ridge, bears NW. and SE., 5.00 chs., thence S. 15° W.; desc. 480 ft. over steep NE. slope.</p>
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 8.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R30E</p>

## BOOK 4618

## Survey of a Portion of the Subdivision of T. 6 S., R. 30 E.

Chains

T6S R30E

$$\frac{1}{2}$$

$$S 7 | S 8$$

1960

1957

Desc. 240 ft. along E. slope.

80.87

Intersect the S. bdy. of sec. 5.

Point for the closing cor. of secs. 7 and 8.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

$$S 5$$

$$S 7 | S 8$$

C C

1960

1957

From this cor. the cor. of secs. 5 and 6 bears N.  $89^{\circ} 42'$  W., 0.745 chs. dist., an iron post,  $2\frac{1}{2}$  ins. diam., previously described.

Land, mountainous.

Soil, gravelly, light clay and rocky.

Timber, widely scattered juniper.

Point for the N.  $\frac{1}{4}$  sec. cor. of sec. 8 is on the S. bdy. of sec. 5 and at midpoint on the N. bdy. of sec. 8.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6S R30E

$$\frac{1}{4} S 8$$

1957

From this cor. the  $\frac{1}{4}$  sec. cor. of sec. 5 bears N.  $88^{\circ} 24'$  W., 1.05 chs. dist., an iron post,  $2\frac{1}{2}$  ins. diam., previously described.

Point for the N.  $\frac{1}{4}$  sec. cor. of sec. 7 is on the S. bdy. of sec. 6, and at a westing of 40.00 chs. from the closing cor. of secs. 7 and 8.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S R30E

$$\frac{1}{4} S 7$$

1960

From this cor. the  $\frac{1}{4}$  sec. cor. of sec. 6 bears N.  $89^{\circ} 51'$  W., 0.445 chs. dist., an iron post,  $2\frac{1}{2}$  ins. diam., previously described.

BOOK 4018

Survey

Township 6 South, Range 30 East

Chains

## GENERAL DESCRIPTION

The area encompassed by this survey is principally mountainous, with the general elevation ranging from approximately 4100 ft. to 5500 ft. above sea level. The soil is very shallow in depth and is a gravelly light clay and extremely rocky.

There is a scattered to moderate growth of sage, catclaw, greasewood, soap weed and cacti throughout the area with scattered growth of scrub juniper along the slopes and ridges.

Access is provided by trail roads and by Arizona State Highway No. 666 which traverses through the township.

No sources of water or permanent habitations were noted during the survey.

Principal use of the area is for cattle grazing.

4-680  
(Feb., 1950)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Alburn D. Griffin	Principal Assistant
Lacel E. Bland	Front Chainman
Deon J. Allen	Notekeeper
Ray D. Neilson	Flagman
Darwin P. Russell	Cornerman
Abdu Karrar	Flagman



**CERTIFICATE OF CADASTRAL ENGINEER**

I, Phil D. Smith, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of November, 1954, I have ~~surveyed~~ resurveyed a portion of the west boundary of T. 6 S., R. 31 E., and a portion of the subdivision of T. 6 S., R. 30 E., and made an original survey of a portion of the subdivision of T. 6 S., R. 30 E.

of the Gila & Salt Riv. Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

August 6, 1958

Salt Lake City, Utah

*Phil D. Smith*

Phil D. Smith

Cadastral Surveyor

**CERTIFICATE OF APPROVAL**

BUREAU OF LAND MANAGEMENT,

Washington, D. C., \_\_\_\_\_, 19\_\_\_\_

The foregoing field notes of the ~~survey of~~ resurvey of a portion of the west boundary of T. 6 S., R. 31 E. and a portion of the subdivision of T. 6 S., R. 30 E., and an original survey of a portion of the subdivision of T. 6 S., R. 30 E., Gila and Salt River Meridian, Arizona

executed by Phil D. Smith, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

\_\_\_\_\_  
*Cadastral Engineering Staff Officer.*

**CERTIFICATE OF TRANSCRIPT**

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 6 S., R. 30 E., G.&S.R.M., Ariz. is a true copy of the original field notes.

\_\_\_\_\_  
*Cadastral Engineering Staff Officer.*

41

4-680  
(Feb., 1950)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS


NAMES	CAPACITY
Boyd S. Owens	Front Chainman
Glen Hatch	Transitman
La Vern Griffin	Notekeeper
Don Coleman	Flagman & Cornerman
Gary Oviatt	Flagman & Cornerman

CERTIFICATE OF CADASTRAL ENGINEER

I, Vern E. Lane, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of November, 1954 and supplemental special instructions dated January 13, 1956 I have ~~surveyed~~ supervised the resurvey of a portion of the subdivision and original survey completing the subdivision of T. 6 S., R. 30 E.

of the Gila And Salt River ~~Salt Lake~~ Meridian, in the State of Utah ~~Utah~~ Arizona, which are represented in the foregoing field notes as having been executed under my supervision ~~by me and under my direction~~; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah  
April 11, 1960


  
Vern E. Lane  
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., FEB 1 1962, 19

The foregoing field notes of the ~~survey of~~ resurvey of a portion of the subdivision and original survey completing the subdivision of T. 6 S., R. 30 E., ~~Salt Lake Meridian, Utah~~ Gila And Salt River Meridian, Arizona.

executed by Boyd S. Owens, Cadastral Surveyor, under the supervision of Vern E. Lane, Cadastral Surveyor (Chief of Party) having been critically examined and found correct, are hereby approved.

  
E. J. Pennington  
Chief, DIVISION OF ENGINEERING

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 6 S., R. 30 E., SLM, Utah, is a true copy of the original field notes.

Cadastral Engineering Staff Officer