

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

THE COMPLETION

of

THE SUBDIVISION

of

TOWNSHIP 12 NORTH, RANGE 12 WEST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Horace G. Parker Cadastral Surveyor

Under special instructions dated July 29, 19 59, which provided  
for the surveys included under Group No. 337, approved August 7, 1959  
and assignment instructions dated October 23, 19 59

Survey commenced November 4, 19 59

Survey completed December 13, 19 60

BOOK 4638

# INDEX DIAGRAM

Township 12 North, Range 12 West

44	43	31	23		
•	42 5	31 4	22 3	2	1
42	41	30	22		
7	40 8	29 9	21 10	14 11	8 12
39	39	29	29	14	7
18	38 17	28 16	19 15	13 14	7 18
38	37	27	18	12	5
19	36 20	27 21	18 22	11 23	5 24
35	35	26	17	11	4
30	34 29	25 28	16 27	10 26	3 25
33	33	24	16	10	2
31	32 32	23 33	15 34	9 35	1 36

## Township 12 North, Range 12 West

## Chains

The Third Standard Parallel North, which is the north boundary of Township 12 North, Range 12 West, was surveyed by Alfred N. Oliver in 1911. The south boundary was surveyed by Hugo Price in 1917. The east and west boundaries and the subdivisional lines of section 1 and section 2 were surveyed by Phil D. Smith and Donald C. Harding in 1956. The survey was initiated upon the official request of the State Supervisor of Arizona to provide identification of the boundaries of the public domain to facilitate administration under appropriate public land laws.

The following field notes are those of the survey of the subdivision of T. 12 N., R. 12 W., Gila and Salt River Meridian, Arizona.

The survey was executed with a W. and L. E. Gurley transit, serial No. 49657, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition, having been placed in proper adjustment prior to the beginning of the field work and maintained in precise adjustment throughout the survey.

The direction of all lines herein reported are determined by deflecting from meridians established by observations on the sun throughout the progress of the survey.

Measurements were made with a steel tape, 8 chains in length, graduated in tenths, for the first link, then at link intervals for 99 links, and thereafter at intervals of 10 links. The tape was tested by comparison with a standard tape and found correct. The measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustments; the horizontal equivalents only are entered in this field note record.

The geographic position of the southeast corner of the township as determined from the data furnished with the special instructions is determined to be latitude  $34^{\circ} 19' 52''$  N., and longitude  $113^{\circ} 27' 22''$  W. The average of a considerable number of readings over all parts of the township gives a value of  $15^{\circ}$  E. for the mean magnetic declination.

## Completion of the Subdivision of T. 12 N., R. 12 W.

Beginning the subdivisional survey at the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the township, which is monumented with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record.

N.  $0^{\circ} 01'$  W., bet. secs. 35 and 36.

Over gently rolling land, through scattering timber and heavy undergrowth; desc. 40 ft. over NNW. slope.

4.00 Wash, 30 lks. wide, 3 ft. deep, drains S.  $70^{\circ}$  W., asc. 20 ft. over S. slope.

8.00 Top of low flat spur, slopes W.; desc. 10 ft. over N. slope.

13.30 Wash, 25 lks. wide, 10 ft. deep, drains W.; asc. 30 ft. over S. slope.

24.20 Top of spur, slopes W.; desc. 70 ft. over steep N. slope.

25.80 Road, bears E. and W.

## BOOK 4638

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
29.80	Left bank of wash, bears E. and W.; enter large sandy wash, drains W.
35.00	Leave wash, right bank, 6 ft. high, bears E. and W.; asc. 50 ft. over SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12NR12W $\frac{1}{4}$ S35 S36 1959
	Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
	Continue over heavily rolling land, through scattering timber and undergrowth; asc. 120 ft. over S. slope.
49.20	Top of spur, slopes W.; desc. 60 ft. over broken NW. slope.
61.90	Small draw, 8 lks. wide, 10 ins. deep, drains SW.; asc. 230 ft. over steep, rocky S. slope.
75.30	Top of spur, slopes W.; desc. 20 ft. over gradual N. slope.
80.00	Point for the cor. of secs. 25, 26, 35, and 36.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, to solid rock and in a mound of stone to top, with brass cap mkd.
	T12NR12W S26 S25 S35 S36 1959
	Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
	Land, southern half, gently rolling; northern half, heavily rolling. Soil, sandy and gravelly, stony. Timber, paloverde, catclaw; undergrowth, cactus, yucca, ocotillo, sagebrush, and cholla.
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., which is marked with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record.
	N. $89^{\circ} 59'$ W., bet. secs. 25 and 36.
	Over heavily rolling land, through scattering timber and undergrowth; desc. 20 ft. over NW. slope.
3.50	Draw, 10 lks. wide, drains SW.; asc. 30 ft. over SE. slope.
9.80	Spur, slopes SW.; desc. 60 ft. over broken W. slope.
26.60	Wash, 60 lks. wide, 3 ft. deep, drains S.; asc. 100 ft. over E. slope.
35.00	Rocky ridge spur, slopes S.; desc. 60 ft. over W. slope.
39.89	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T12NR12W  
W ¼ ← S25  
C S36  
1959

Raise a mound of stone, 4 ft. base, 2½ ft. high, N. of cor.

This corner set at the base of red sandstone cliff, bears N. & S.

39.99 True point for the ¼ sec. cor. of secs. 25 and 36, not monumented. This point falls on solid rock in the bottom of a small wash, 4 lks. wide, 2 ft. deep, drains S. 30° W., and it was deemed unsafe for the corner.

Continue over heavily rolling mountainous land.

40.20 Left bank of sandy wash, course S.

43.60 Right bank of sandy wash, course S. 20° E.; asc. 90 ft. over abrupt E. slope.

50.90 Low spur, slopes S.; desc. 20 ft. over W. slope.

52.80 Wash, 15 lks. wide, 20 ft. deep, drains S. 20° W.; asc. 170 ft. over broken E. slope.

79.98 The cor. of secs. 25, 26, 35, and 36.

Land, heavily rolling mountainous.  
Soil, sandy and gravelly, stony.  
Timber, paloverde and catclaw; undergrowth, cactus, yucca, ocotillo, cholla, and sagebrush.

N. 0° 01' W., bet. secs. 25 and 26.

Over heavily rolling mountainous land, through scattering timber and undergrowth; asc. 20 ft. over S. slope.

2.88 Top of spur, slopes SW.; desc. 260 ft. over N. slope.

17.20 Large wash, 50 lks. wide, 2 ft. deep, drains W.; asc. 60 ft. over SW. slope.

23.00 Broken and rocky spur slopes SW.; thence over broken W. slope.

40.00 Point for the ¼ sec. cor. of secs. 25 and 26.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W  
¼  
S26 | S25  
1959

Continue over mountainous land; asc. 440 ft. over broken SW. slope.

58.60 Top of rocky spur, slopes W.; desc. 58 ft. over N. slope.

69.30 Draw, near head, 8 lks. wide, 3 ft. deep, drains SE.; asc. 112 ft. over broken S. slope.

BOOK 4638

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

77.10 Top of spur, slopes SW.; desc. 60 ft. over NW. slope.

80.00 Point for the cor. of secs. 23, 24, 25, and 26.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W  
 $\frac{S23}{S26} | \frac{S24}{S25}$   
 1959

Land, heavily rolling mountainous.

Soil, sandy and gravelly, stony.

Timber, paloverde; undergrowth, greasewood, cholla, cactus, ocotillo.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., which is marked with an iron post, 2½ ins. diam., firmly set in the ground, marked and witnessed as described in the official record.

S. 89° 57' W., bet. secs. 24 and 25.

Over rolling mountainous land, through scattering timber and undergrowth.

8.00 Wash, 50 lks. wide, 2 ft. deep, drains SW.; asc. 15 ft. over SE. slope.

13.40 Ridge spur, slopes S. 20° W.; desc. 20 ft. over SW. slope.

21.00 Left bank of a sandy wash, course S.

24.70 Right bank of a sandy wash, course S.; asc. 20 ft. over SE. slope.

26.10 Low ridge spur, slopes S.; desc. 20 ft. over SW. slope.

32.30 Wash, 100 lks. wide, 4 ft. deep, drains SE.; asc. 60 ft. over E. slope.

40.01 Point for the ¼ sec. cor. of secs. 24 and 25.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W  
 $\frac{1}{4} \frac{S24}{S25}$   
 1959

Continue over heavily rolling mountainous land; asc. 130 ft. over NE. slope.

47.50 Ridge spur, slopes SE.; desc. 20 ft. over SW. slope.

49.90 Draw, drains SE.; thence along broken S. slope.

59.90 Draw, 10 lks. wide, drains SE.; asc. 290 ft. over E. slope.

72.40 Ridge, bears SE. and NW.; desc. 130 ft. along NW. slope.

80.02 The cor. of secs. 23, 24, 25, and 26.

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, paloverde; undergrowth, cactus, yucca, greasewood, ocotillo, and cholla.
	N. 0° 01' W., bet. secs. 23 and 24.
	Over heavily rolling mountainous land, through scattering timber and undergrowth; desc. 20 ft. over NW. slope.
2.60	Head of draw, 5 lks. wide, drains W.; asc. 240 ft. over S. slope.
10.70	Rocky ridge spur, slopes S. 60° E.; desc. 460 ft. over broken, rocky NE. slope.
38.60	Wash, 10 lks. wide, 4 ft. deep, drains E.; asc. 10 ft. over S. slope
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 23 and 24.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12NR12W $\frac{1}{2}$ S23   S24 1959
	Continue over heavily rolling mountainous land; asc. 5 ft. over S. slope.
41.80	Spur, slopes N. 60° E.; desc. 40 ft. over NE. slope.
51.20	Wash, 25 lks. wide, 3 ft. deep, drains SE.; asc. 30 ft. over S. slope.
64.00	Round spur, slopes SW.; desc. 10 ft. over NW. slope.
72.00	Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.; asc. 40 ft. over SE. slope.
80.00	Point for the cor. of secs. 13, 14, 23, and 24.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12NR12W S14   S13 S23   S24 1959
	Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
	Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, and greasewood.
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp. which is marked with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in the ground, marked and witnessed as described in the official record.

## BOOK 4638

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
	S. 89° 54' W., bet. secs. 13 and 24.
	Over heavily rolling land, through scattering timber and undergrowth; asc. 20 ft. over E. slope.
1.40	Spur, slopes SW.; desc. 30 ft. over W. slope.
5.70	Draw, 8 lks. wide, 10 ins. deep, drains S 20° W.; asc. 30 ft. over E. slope.
10.50	Rocky spur, slopes S.; desc. 20 ft. over SW. slope.
14.60	Draw, 20 lks. wide, 1 ft. deep, drains S. 20° E.; asc. 50 ft. over E. slope.
20.60	Broken ridge spur, sloping S.; desc. 20 ft. over W. slope.
23.60	Draw, 5 lks. wide, drains S.; asc. 10 ft. over SE. slope.
29.60	Ridge spur, slopes S.; desc. 70 ft. over W. slope.
36.60	Wash, 30 lks. wide, 2 ft. deep, drains South.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.  Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12NR12W $\frac{1}{4}$ $\frac{S13}{S24}$ 1959
	Continue over gently rolling land, through scattering timber; desc. 30 ft. over W. slope.
45.90	Wash, 80 lks. wide, 3 ft. deep, drains S.; asc. 30 ft. over E. slope.
47.90	Low spur, slopes S.; desc. 30 ft. over W. slope.
48.70	Draw, 60 lks. wide, drains S. 20° E.; asc. 40 ft. over E. slope.
53.70	Low ridge spur, slopes S.; thence desc. 35 ft. over SW. slope.
56.30	Small draw, 5 lks. wide, drains S.; asc. 10 ft. over E. slope.
60.80	Top of spur, slopes S.; desc. 20 ft. over W. slope.
63.80	Small draw, 10 lks. wide, drains S.; asc. 40 ft. over E. slope.
73.30	Top of spur, slopes S.; desc. 50 ft. over W. slope.
76.10	Draw, 8 lks. wide, drains S.; asc. 20 ft. over E. slope.
80.06	The cor. of secs. 13, 14, 23, and 24.  Land, eastern half, heavily rolling; western half, gently rolling. Soil, sandy and gravelly, stony. Timber, paloverde and catclaw; undergrowth, cactus, cholla, ocotillo, and creosote bush.



Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
	N. 0° 01' W., bet. secs. 13 and 14.
	Over gently rolling land, through scattering timber and undergrowth. Asc. 80 ft. over E. slope.
10.60	Ridge spur, slopes SW.; desc. 50 ft. over NW. slope.
15.10	Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. 70 ft. over broken SW. slope.
36.10	Ridge spur, slopes SW.; desc. 40 ft. over NW. slope.
37.70	Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. 10 ft. over SE. slope.
40.00	Point for the 1/2 sec. cor. of secs. 13 and 14.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12NR12W 1/2 S14   S13 1959
	Asc. 40 ft. over SE. slope.
43.55	Broken ridge spur, slopes SW.; desc. 30 ft. over NW. slope.
47.95	Wash, 15 lks. wide, 2 ft. deep, drains W.; asc. 80 ft. over rolling to broken SW. slope.
69.00	Top of ascent, S. rim of small canyon bears E. and W.; desc. 135 ft. over N. slope.
75.90	Wash, 200 lks. wide, 4 ft. deep, drains NW.; asc. 60 ft. over SW. slope.
80.00	Point for the cor. of secs. 11, 12, 13, and 14.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12NR12W S11   S12 S14   S13 1959
	Land, gently rolling. Soil, sandy and gravelly, stony. Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, and creosote bush.
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., which is marked with an iron post, 2 1/2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record.
	S. 89° 56' W., bet. secs. 12 and 13.
	Over heavily rolling land, through scattering timber and undergrowth; asc. 10 ft. over gradual E. slope.
1.20	Ridge spur, slopes SW.; desc. 120 ft. over NW. slope.

## BOOK 4630

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
14.10	Wash, 15 lks. wide, 2 ft. deep, drains SW.; asc. 20 ft. over SE. slope.
31.60	Ridge spur, slopes S. 20° W.; desc. 50 ft. over broken to rolling SW. slope.
40.03	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 12 and 13.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p>
	<p>T12NR12W  <math>\frac{1}{4}</math> <u>S12</u>  S13  1959</p>
	Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
	Desc. 180 ft. over NW. slope through scattering timber.
57.40	Wash, 300 lks. wide, 3 ft. deep, drains SW.; asc. <sup>30 ft.</sup> over broken S. to SE slope.
80.06	<p>The cor. of secs. 11, 12, 13, and 14.</p> <p>Land, heavily rolling.  Soil, sandy and gravelly, stony.  Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, and creosote bush.</p>
	N. 0° 04' W., bet. secs. 11 and 12.
	Over heavily rolling land, through scattering timber and undergrowth; asc. 40 ft. over SW. slope.
14.90	Broken ridge spur, slopes W.; thence over rolling to broken W. slope
20.90	Ridge spur slopes W.; desc. 140 ft. over NW. slope.
24.90	Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. 30 ft. over S. slope.
32.50	Ridge spur, slopes W.; desc. 20 ft. over N. slope.
36.00	Draw, 35 lks. wide, 2 ft. deep, drains W.; asc. 15 ft. over S. slope
40.06	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p>
	<p>T12NR12W  <math>\frac{1}{4}</math>  S11   S12  1959</p>
	Asc. 260 ft. over rolling to broken S. slope; through scattering timber.
80.12	The cor. of secs. 1, 2, 11, and 12, which is marked with an iron post, $2\frac{1}{2}$ ins. in diam., firmly set in the ground, marked and witnessed as described in the official record.

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	Land, heavily rolling. Soil, sandy and gravelly, stony. Timber, palo verde; undergrowth, cactus, yucca, ocotillo, cholla, and creosote bush.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., which is marked with an iron post, .2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record.  N. 0° 01' W., bet. secs. 34 and 35.  Over gently rolling land; through scattering timber and undergrowth.
.01	Fence, 4 strand barbed wire, bears E. and W.
.53	Road, bears E. and W.
11.00	Wash, 30 lks. wide, 3 ft. deep, drains SW.; asc. 30 ft. over S. slope.
37.20	South rim of a small canyon, bears E. and W.; desc. 64 ft. over N. slope.
37.50	Enter wash, course W.
40.00	True point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35 falls in sandy wash, 2 ft. deep, draining W. at forks of washes, and is deemed unsafe for the corner. Not monumented.
40.50	Enter bottom land, bears W. and NE.
41.00	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 34 and 35.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T12N R12W  <math>\frac{1}{4}</math>            S34   S35            ↓            W C            1959         </div>
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.  Continue over heavily rolling land, through scattering timber and undergrowth; asc. 170 ft. over S. slope.
65.00	Flat ridge, bears NE. and SW.; desc. 30 ft. over NW. slope.
68.80	Draw, 10 lks. wide, drains SW.; asc. 50 ft. over SE. slope.
76.20	Broken ridge spur, slopes SW.; desc. 30 ft. over NW. slope.
79.08	Point selected for the witness cor. of secs. 26, 27, 34, and 35.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.  <div style="text-align: center;">           T12N R12W            S27   S26            S34   S35            W C            1959         </div>
80.00	True point for the cor. of secs. 26, 27, 34 and 35 falls in a sandy wash, 30 lks. wide, 4 ft. deep, draining SW., and it is deemed unsafe for the corner, not monumented.

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

Land, southern half, gently rolling; northern half, heavily rolling.  
Soil, sandy and gravelly, stony.  
Timber, palo verde and catclaw; undergrowth, cactus, yucca, ocotillo,  
creosote bush, and saguaro.

From the cor. of secs. 25, 26, 35, and 36.

N. 89° 58' W., bet. secs. 26 and 35.

Over heavily rolling mountainous land, through scattering timber  
and medium heavy undergrowth; desc. 350 ft. over rolling and broken  
S. to SW. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 35.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the  
ground, to solid rock, and in a mound of stone to top, with brass  
cap mkd.

T12N R12W  
 $\frac{1}{4}$   $\frac{S26}{S35}$   
1959

Descend 130 ft. over SW. slope.

62.60 Wash, 100 lks. wide, 3 ft. deep, drains SW.; asc. 60 ft. over  
broken E. slope.

76.00 Broken ridge spur, slopes SW.; desc. 20 ft. over NW. slope.

80.00 True point for the cor. of secs. 26, 27, 34 and 35.

Land, heavily rolling mountainous.  
Soil, sandy and gravelly, stony.  
Timber, palo verde and catclaw; undergrowth, cactus, yucca, ocotillo,  
creosote bush and saguaro.

N. 0° 01' W., bet. secs. 26 and 27.

Over heavily rolling mountainous land; through scattering timber,  
and medium heavy undergrowth; asc. 210 ft. over broken SE. slope.

19.70 Broken spur, slopes SW.; desc. 90 ft. over broken NW. slope.

36.20 Draw, 10 lks. wide, drains SW.; asc. 15 ft. over S. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 27.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the  
ground, with brass cap mkd.

T12N R12W  
 $\frac{1}{4}$   
S27 | S26  
1959

Raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Continue ascent; asc. 400 ft. over rocky and broken SW. slope.

66.20 Draw, 8 lks wide, drains SW.; asc. 330 ft. over S. slope.

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

80.00 Point for the cor. of secs. 22, 23, 26, and 27.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W  
 S22 | S23  
 S27 | S26  
 1959

Land, heavily rolling mountainous.  
 Soil, sandy and gravelly, stony.  
 Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, creosote bush, and saguaro.

From the cor. of secs. 23, 24, 25, and 26.

S. 89° 56' W., bet. secs. 23 and 26.

Over rough, broken, mountainous land, through scattering timber and undergrowth; by triangulation on the line between secs. 23 and 26 to a point on a high rocky spur; desc. 460 ft. over rolling, and broken NW. to W. slope.

39.99 True point for the ¼ sec. cor. of secs. 23 and 26, inaccessible, not monumented.

40.54 Point selected for the witness ¼ sec. cor. of secs. 23 and 26.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W  
 ¼ ——— S23 ——— W  
           S26 ——— C  
 1959

42.61 Point for the triangulation station on the line bet. secs. 23 and 26, on a high, rocky spur, projecting SE. Continue by triangulation on the line bet. secs. 23 and 26, over rough, broken, mountainous land.

44.00 Draw, 50 lks. wide, 3 ft. deep, drains S.; asc. 700 ft. over broken NE. slope.

66.21 Point for the triangulation station on the line bet. secs. 23 and 26. Top of high, rocky, ridge bears NW. & SE.; desc. 360 ft. over small cliffs and rocky SW. slope.

79.98 The cor. of secs. 22, 23, 26, and 27.

Land, rough, broken, mountainous.  
 Soil, sandy and gravelly, stony.  
 Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, creosote bush, and saguaro.

N. 0° 01' W., bet. secs. 22 and 23.

Over rough, broken, mountainous land, through scattering timber, and undergrowth; asc. 150 ft. over S. slope.

## BOOK 4638

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
4.10	Top of spur, slopes SW.; desc. 30 ft. over NW. slope.
8.10	Head of draw, 6 lks. wide, drains W.; asc. 120 ft. over SW. slope.
18.20	Top of high, rocky ridge, bears NW. and SE.; desc. 260 ft. over steep, rocky, and broken NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.  <div style="text-align: center;">           T12NR12W  <math>\frac{1}{4}</math>            S22   S23            1959         </div>
	Desc. 345 ft. over steep NE. to N. slope.
54.90	Main wash, 150 lks. wide, 5 ft. deep, drains SE., 8 chains, thence S. $20^{\circ}$ E.; asc. 355 ft. over small cliffs, and rocky SW. slope.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.  <div style="text-align: center;">           T12NR12W            S15   S14            S22   S23            1959         </div>
	Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.  Land, heavily rolling, mountainous. Soil, sandy and gravelly, stony. Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, creosote bush, and saguaro.
	From the cor. of secs. 13, 14, 23, and 24.  S. $89^{\circ} 57'$ W. bet. secs. 14 and 23.  Over gently rolling land, through scattering timber and undergrowth; asc. 32 ft. over E. slope.
2.65	Spur, slopes SW.; desc. 15 ft. over W. slope.
4.65	Draw, 8 lks. wide, drains S.; thence desc. over rolling SW. slope.
26.00	Wash, 20 lks. wide, 4 ft. deep, drains NW.; asc. 125 ft. over NE. slope.
39.96	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T12NR12W  <math>\frac{1}{4}</math> — S14            S23            1959         </div>
	Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
	Continue over heavily rolling land, through scattering timber; asc. 191 ft. over steep, rocky NE. slope.
56.90	Top of high, flat topped ridge, bears N. 20° W. and S. 20° E., continue along N. slope.
65.70	Begin descent; desc. 170 ft. over NW. slope.
79.92	The cor. of secs. 14, 15, 22, and 23.
	Land, eastern half, gently rolling; western half, heavily rolling. Soil, sandy and gravelly, stony. Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, and creosote bush.
	N. 0° 01' W., bet. secs. 14 and 15.
	Over heavily rolling mountainous land, through scattering timber and undergrowth; asc. 20 ft. over SW. slope.
2.00	Top of ascent; slopes W., begin descent; desc. 290 ft. over steep, rocky NW. slope.
16.70	Main wash, 100 lks. wide, 5 ft. deep, drains SW.; asc. 190 ft. over steep, rocky S. slope.
27.50	Rocky and broken ridge, bears NE. and SW.; desc. 75 ft. over abrupt NW. slope.
30.40	Draw, 8 lks. wide, 3 ft. deep, drains W.; asc. 120 ft. over S. slope.
37.80	Top of ascent; on W. slope of ridge; desc. 60 ft. over abrupt NW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12NR12W $\frac{1}{4}$ S15   S14 1959
	Desc. 284 ft. over abrupt NW. slope.
51.50	Main wash, 200 lks. wide, 4 ft. deep, drains SW.; asc. 15 ft. over SW. slope.
53.30	End of low, flat spur, slopes S. 70° W.; desc. 30 ft. over NW. slope.
56.30	Wash, 100 lks. wide, 4 ft. deep, drains S. 20° W., approximately 8 chs. dist. to junction with main wash; asc. 270 ft. over SE. slope.
73.50	Ridge bears NE & SW.; desc. 75 ft. over NW. slope.
80.00	Point for the cor. of secs. 10, 11, 14, and 15.
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12NR12W S10   S11 S15   S14 1959

## BOOK 4638

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

Land, heavily rolling, mountainous.  
Soil, sandy and gravelly, stony.  
Timber, paloverde; undergrowth, cactus, yucca, cholla, ocotillo,  
creosote bush, and saguaro.

From the cor. of secs. 11, 12, 13, and 14.

S. 89° 54' W., bet. secs. 11 and 14.

Over heavily rolling mountainous land, through scattering timber  
and undergrowth; desc. 30 ft. over SW. slope.

- 6.00 Main wash, 200 lks. wide, 4 ft. deep, drains NW.; asc. 110 ft. over  
E. slope.
- 13.80 Top of rim, bears SE. and NW., continue ascent; asc. 20 ft. over  
SE. slope.
- 19.90 Top of same rim, bears N. 70° E. and S. 70° W.; desc. 230 ft. over  
W. to NW. slope.
- 39.95 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 14.
- Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the  
ground, to solid rock, and in a mound of stone to top, with brass  
cap mkd.
- T12NR12W  
 $\frac{1}{4}$   $\frac{S11}{S14}$   
1959
- Desc. 15 ft. over NW. slope.
- 40.40 Left bank of main wash, course SW.; continue in wash.
- 44.20 Right bank of main wash, course S. 70° W., continue along N. side  
of main wash; asc. 60 ft. over SE. slope.
- 52.20 Small ridge spur, slopes SW.; desc. 70 ft. over broken NW. slope.
- 59.60 Wash, 20 lks. wide, 4 ft. deep, drains SW. 25 lks., thence NW.
- 62.70 Same wash, 20 lks. wide, 10 ft. deep, drains SW.; asc. 145 ft. over  
SE. slope.
- 72.80 Ridge spur, slopes SW.; desc. 54 ft. over NW. slope.
- 79.90 The cor. of secs. 10, 11, 14, and 15.

Land, heavily rolling, mountainous.  
Soil, sandy and gravelly, stony.  
Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla,  
creosote bush and saguaro.

N. 0° 18' W. bet. secs. 10 and 11.

Over heavily rolling mountainous land, through scattering timber  
and medium heavy undergrowth; thence over rolling and broken W.  
slope.



## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

- 14.70 Rocky spur, slopes W.; desc. 141 ft. over NW. slope.
- 22.30 Wash, 60 lks. wide, 4 ft. deep, drains W.; asc. 340 ft. over steep rocky S. slope.
- 40.17 Point for the  $\frac{1}{2}$  sec. cor. of secs. 10 and 11.  
Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.  
  
T12NR12W  
 $\frac{1}{2}$   
S10|S11  
1960  
  
Asc. 100 ft. over rolling to broken S. slope.
- 75.70 Ridge spur, slopes W.; desc. 90 ft. over NW. slope.
- 80.34 The cor. of secs. 2, 3, 10, and 11, which is marked by an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, marked and witnessed, as described in the official record.  
  
Land, heavily rolling mountainous.  
Soil, sandy and gravelly, stony.  
Timber, paloverde, ironwood, and catclaw; undergrowth, cactus, yucca, sagebrush, ocotillo, and saguaro.
- 
- From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., which is marked with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record.  
  
N.  $0^{\circ} 02'$  W., bet. secs. 33 and 34.  
  
Over rolling land; through scattering timber, and undergrowth; asc. 30 ft. over rolling S. slope.
- 15.70 South rim of wide canyon, bears E. & W.; desc. 55 ft. over N. slope.
- 18.00 Left bank of a sandy wash, course west.
- 23.70 Right bank of wash, course west; asc. 90 ft. over rolling to broken SE. slope.
- 40.00 Point for the  $\frac{1}{2}$  sec. cor. of secs. 33 and 34.  
Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.  
  
T12NR12W  
 $\frac{1}{2}$   
S33|S34  
1959
- 40.50 Small draw, 5 lks. wide, drains W.; thence along rolling to broken W. slope.
- 64.10 Wash, 80 lks. wide, 4 ft. deep, drains SW.; asc. 80 ft. over S. slope
- 71.10 Spur, slopes east; desc. 25 ft. over NE. slope.
- 77.10 Head of draw, 5 lks. wide, drains SE.; asc. 30 ft. over SE. slope.

## BOOK 4638

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T12NR12W S28 S27 S33 S34 1959</p> <p>Land, rolling. Soil, sandy and gravelly, stony. Timber, paloverde; undergrowth, cactus, yucca, cholla, ocotillo, greasewood, and saguaro.</p>
39.36	<p style="text-align: center;">true point for the From the/cor. of secs: 26, 27, 34, and 35.</p> <p>N. 89° 57' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land, through scattered timber, and undergrowth; desc. 90 ft. over rolling and broken SW. slope.</p> <p>Point selected for the witness ¼ sec. cor. of secs. 27 and 34.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T12NR12W ¼ ← S27 W S34 C 1959</p>
40.02	<p>True point for the ¼ sec. cor. of secs. 27 and 34, falls in a small sandy wash, 25 lks. wide, 3 ft. deep, drains S. 20° W. and is deemed unsafe for the corner; not monumented.</p> <p>Thence over gently rolling S. slope.</p>
52.30	<p>Wash, 100 lks. wide, 3 ft. deep, drains S.; desc. 20 ft. over rolling and broken SW. slope.</p>
80.04	<p>The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, gently rolling. Soil, sandy and gravelly, stony. Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, greasewood and saguaro.</p>
2.10	<p>N. 0° 02' W., bet. secs. 27 and 28.</p> <p>Over moderately heavily rolling land, through medium heavy undergrowth; asc. 14 ft. over SE. slope.</p> <p>Bench, bears E. and W.; desc. 100 ft. over NW. slope.</p>
10.60	<p>Wash, 30 lks. wide, 4 ft. deep, drains W.; asc. 170 ft. over SE. slope.</p>
18.90	<p>Ridge spur, on E. slope; desc. 80 ft. over NE. slope.</p>

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

32.50 Wash, 15 lks. wide, 2 ft. deep, drains SW.; asc. 10 ft. over SE. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 27 and 28.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W  
 $\frac{1}{4}$   
 S28 | S27  
 1959

Continue over heavily rolling land; asc. 16 ft. over SE. slope.

47.60 Top of ascent, slopes N.  $70^\circ$  E.; desc. 40 ft. over NW. slope.

50.60 Wash, 15 lks. wide, 4 ft. deep, drains S.  $30^\circ$  E.; asc. 270 ft. over SW. slope.

72.00 Spring, in wash, bears West; approximately 4 chs. dist.

77.60 Top of ascent; very rocky with large boulders, slopes W.; desc. 30 ft. over N. slope.

79.10 Head of draw, drains W.; asc. 30 ft. over S. slope.

80.00 Point for the cor. of secs. 21, 22, 27, and 28.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W  
 S21 | S22  
 S28 | S27  
 1959

Land, heavily rolling.

Soil, sandy and gravelly, stony.

Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, greasewood, and saguaro.

From the cor. of secs. 22, 23, 26, and 27.

N.  $89^\circ 57'$  W., bet. secs. 22 and 27.

Over heavily rolling mountainous land, through scattering timber, and undergrowth; asc. 90 ft. over SE. slope.

5.30 Ridge spur, slopes SW.; desc. 565 ft. over rocky and broken NW. slope.

39.90 Draw, drains SW.

40.04 Point for the  $\frac{1}{4}$  sec. cor. of secs. 22 and 27.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W  
 $\frac{1}{4}$  S22  
 S27  
 1959

Over heavily rolling mountainous land, through scattering timber and undergrowth; asc. 45 ft. over rocky and broken SE. slope.

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
45.40	Broken spur, slopes S.; desc. 60 ft. over SW. slope.
49.30	Draw, 10 lks. wide, drains NW.; asc. 80 ft. over NE. slope.
60.90	Top of rocky spur, slopes NW.; desc. 300 ft. over broken NW. to W. slope.
80.08	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, greasewood, and saguaro.</p>
	<p>N. 0° 02' W., bet. secs. 21 and 22.</p> <p>Over heavily rolling mountainous land, through scattering timber, and undergrowth.</p>
7.20	Rocky ridge spur, slopes West; thence over broken NW. slope.
10.40	Wash, 30 lks. wide, 10 ft. deep, drains West; asc. 70 ft. over S. slope.
22.30	Wash, 20 lks. wide, 4 ft. deep, drains S. 20° W.; asc. 60 ft. over SW. slope.
38.20	Wash, 20 lks. wide, 3 ft. deep, drains S. 20° W.; asc. 30 ft. over SW. slope.
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;">T12NR12W <math>\frac{1}{4}</math> S21   S22 1959</p>
	Asc. 620 ft. over rolling and broken SW. slope.
80.00	<p>Point for the cor. of secs. 15, 16, 21, and 22.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;">T12NR12W S16   S15 S21   S22 1959</p>
	<p>Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, greasewood, and saguaro.</p>
	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 89° 50' W., bet. secs. 15 and 22.</p>

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

Over heavily rolling mountainous land, through scattering timber and undergrowth; desc. 330 ft. over steep, rocky W. slope.

10.20 Wash, 50 lks. wide, 3 ft. deep, drains S.; asc. 185 ft. over steep E. slope.

16.50 Ridge spur, slopes S.; desc. 130 ft. over SW. slope.

26.30 Draw, drains SE.; asc. 40 ft. over NE. slope.

36.25 Top of spur, slopes NE., continue along N. slope.

40.02 Point for the  $\frac{1}{2}$  sec. cor. of secs. 15 and 22.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W  
 $\frac{1}{2}$   $\frac{S15}{S22}$   
1960

Desc. 60 ft. over steep W. slope.

42.85 Wash, 10 lks. wide, 3 ft. deep, drains N.; asc. 80 ft. over E. slope.

44.90 Top of spur, slopes N.; desc. 50 ft. over W. slope.

48.86 Wash, 20 lks. wide, 2 ft. deep, drains N.; asc. 30 ft. over E. slope.

54.50 Top of spur, slopes N., continue along N. slope.

59.00 Begin descent; desc. 40 ft. over W. slope.

63.35 Wash, 10 lks. wide, 2 ft. deep, drains N.  $20^\circ$  E.; asc. 75 ft. over E. slope.

74.40 Top of spur, slopes NW.; thence along rocky to broken S. slope.

80.04 The cor. of secs. 15, 16, 21, and 22.

Land, heavily rolling mountainous.

Soil, sandy and gravelly, stony.

Timber, paloverde and catclaw; undergrowth, cactus, ocotillo, cholla, greasewood, and saguaro.

N.  $0^\circ 02'$  W., bet. secs. 15 and 16.

Over heavily rolling mountainous land, through scattering timber and medium heavy undergrowth; asc. 20 ft. over S. slope.

.90 Top of ridge, bears E. and W.; desc. 470 ft. over broken and rocky N. to NE. slope.

28.30 Wash, 2 chs. wide, 4 ft. deep, drains W.; asc. 350 ft. over S. slope.

39.90 Shoulder of spur, on W. side of flat topped mesa, slopes W.

40.00 Point for the  $\frac{1}{2}$  sec. cor. of secs. 15 and 16.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

BOOK 4638  
Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
	<p style="text-align: center;">T12NR12W <math>\frac{1}{4}</math> S16 S15 1960</p> <p>From this cor., a spring in the bottom of a wash, 2 chs. wide, in a canyon, bears N. 70° W., approximately 20 chs. dist.</p> <p>Over heavily rolling mountainous land; desc. 350 ft. over NW. slope.</p>
59.60	Wash, 2 chs. wide, 4 ft. deep, drains SW.; asc. 410 ft. over steep rocky SE. slope.
80.00	Point for the cor. of secs. 9, 10, 15, and 16.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T12NR12W S 9 S10 <u>S16 S15</u> 1960</p> <p>Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, paloverde and catclaw; undergrowth, cactus, ocotillo, cholla, saguaro and greasewood.</p>
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89° 54' W., bet. secs. 10 and 15.</p> <p>Over heavily rolling mountainous land, through scattering timber and undergrowth; desc. 210 ft. over NW. to W. slope.</p>
25.60	Wash, 40 lks. wide, 4 ft. deep, drains SW.; asc. 60 ft. over SE. slope.
27.80	Top of spur, slopes S.; desc. over SW. slope.
33.60	Same wash, 60 lks. wide, 4 ft. deep, drains NW.; asc. 70 ft. over E. slope.
35.10	Spur, slopes N.; desc. 60 ft. over W. slope.
38.90	Same wash, 60 lks. wide, 4 ft. deep, drains SW.; asc. 50 ft. over E. slope.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T12NR12W <math>\frac{1}{4}</math> S10 <u>S15</u> 1960</p> <p>Asc. 155 ft. over E. slope.</p>
47.60	Spur, slopes S.; desc. 70 ft. over W. slope.
55.80	Wash, 30 lks. wide, 3 ft. deep, drains S.; asc. 210 ft. over E. slope.

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

- 66.40 Ridge spur, slopes S.; desc. 130 ft. over W. slope.
- 73.20 Wash, 20 lks. wide, 3 ft. deep, drains S. 20° W.; asc. 200 ft. over E. slope.
- 80.04 The cor. of secs. 9, 10, 15, and 16.
- Land, heavily rolling mountainous.  
Soil, sandy and gravelly, stony.  
Timber, paloverde and catclaw; undergrowth, cactus, ocotillo, cholla, saguaro, and greasewood.

N. 0° 02' W., bet. secs. 9 and 10.

Over heavily rolling mountainous land, through scattering timber and undergrowth; asc. 50 ft. over rocky SE. slope.

- 5.20 Ridge spur, slopes SW.; desc. 170 ft. over rolling to broken NW. to W. slope.
- 26.20 Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. 159 ft. over broken SE. slope.
- 40.00 Point for the  $\frac{1}{2}$  sec. cor. of secs. 9 and 10.
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W

$\frac{1}{2}$

S 9 | S10

1960

Asc. 90 ft. over SE. slope.

- 44.30 Ridge, bears N. 20° E. and S. 20° W., along rolling W. slope
- 54.00 Ridge spur, slopes SW.; desc. 195 ft. over N. slope.
- 61.50 Wash, 20 lks. wide, 3 ft. deep, drains W.; asc. 65 ft. over S. slope.
- 65.80 Ridge spur, slopes W.; desc. 120 ft. over NW. slope.
- 74.20 Wash, 30 lks. wide, 4 ft. deep, drains S. 70° W.; asc. 68 ft. over rocky S. slope.
- 80.00 Point for the cor. of secs. 3, 4, 9, and 10.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W.

S 4 | S 3

S 9 | S10

1960

Land, heavily rolling mountainous.  
Soil, sandy and gravelly, stony.  
Timber, paloverde and catclaw; undergrowth, cactus, ocotillo, cholla, greasewood, and saguaro.

BOOK 4638

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains

From the cor. of secs. 2, 3, 10, and 11.

S. 89° 54' W., bet. secs. 3 and 10.

Over heavily rolling mountainous land, through scattering timber and undergrowth; desc. 30 ft. over W. slope.

7.10 Wash, 30 lks. wide, 3 ft. deep, drains S.; asc. 330 ft. over E. slope.

16.20 Ridge, top of, slopes SE.; desc. 108 ft. over NW. to W. slope.

29.40 Wash, 10 lks. wide, 2 ft. deep, drains S.; asc. 116 ft. over E. slope.

39.81 Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 10.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{r} T12NR12W \\ S \ 3 \\ \hline \frac{1}{4} \ S10 \\ 1960 \end{array}$$

Continue over heavily rolling mountainous land; asc. 20 ft. over E. slope.

43.40 Ridge spur, slopes S.; desc. 260 ft. over NW. slope.

60.50 Wash, 15 lks. wide, 3 ft. deep, drains SW.; asc. 40 ft. over SE. slope.

79.62 The cor. of secs. 3, 4, 9, and 10.

Land, heavily rolling mountainous.

Soil, sandy and gravelly, stony.

Timber, paloverde and catclaw; undergrowth, cactus, cholla, ocotillo, saguaro and greasewood.

N. 0° 02' W., bet. secs. 3 and 4.

Over heavily rolling mountainous land, through scattering timber, and medium heavy undergrowth; asc. 45 ft. over SW. slope.

7.60 Ridge spur, slopes W. to SW.; desc. 206 ft. over steep rocky N. slope.

15.70 Wash, 10 lks. wide, 3 ft. deep, drains W.; asc. 60 ft. over rocky and broken slope.

38.10 Saddle in spur, slopes W.; desc. 35 ft. over rocky N. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 4.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{r} T12NR12W \\ \frac{1}{4} \\ S \ 4 \ S \ 3 \\ 1960 \end{array}$$

Desc. 40 ft. over rocky N. slope.



## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

43.00 Fence, 4 strands barbed wire on steel posts, bears E. and W.

48.80 Wash, 1 ch. wide, 3 ft. deep, drains W.; asc. 30 ft. over rolling S. to SW. slope.

61.20 Intersect the Third Standard Parallel North.

Point for the closing corner of secs. 3 and 4.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T13N R12W  
S34  
S 4 | S 3  
C C  
T12N R12W  
1960

From this corner, the standard  $\frac{1}{4}$  sec. cor. of sec. 34, T. 13 N., R. 12 W., which is an iron post, 1 in. diam., firmly set in the ground and in a mound of stone, with brass cap marked and witnessed as described in the official record, bears East, 3.04 chs. dist.

From this same corner, the witness corner for the standard corner of secs. 33 and 34, T. 13 N. R. 12 W., which is an iron post,  $2\frac{1}{2}$  ins. diam., firmly set in the ground, with brass cap marked and witnessed as described in the official record, bears West, 33.51 chs. dist.

Land, heavily rolling mountainous.

Soil, sandy and gravelly, stony.

Timber, palo verde and catclaw; undergrowth, cactus, yucca, ocotillo, cholla, saguaro and greasewood.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 3 is at midpoint and on the N. bdy. of the Tp.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 4 ins. in the ground, to solid stone, and in a mound of stone to top, with brass cap mkd.

T13N R12W  
 $\frac{1}{4}$  S 3  
T12N R12W  
1960

From this corner, the standard cor. of secs. 34 and 35, T. 13 N., R. 12 W., which is an iron post, 2 ins. diam., firmly set in the ground, and in a mound of stone, with brass cap marked and witnessed as described in the official record, bears East, 3.15 chs. dist.

From this same corner, the standard  $\frac{1}{4}$  sec. cor. of sec. 34, T. 13 N., R. 12 W., which is an iron post, 1 in. diam., firmly set in the ground, with brass cap marked and witnessed as described in the official record, bears West, 36.85 chs. dist.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., which is marked with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record.

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	<p>N. 0° 02' W., bet. secs. 32 and 33.</p> <p>Over nearly level bottom land; in flood water channel of Big Sandy River; through heavy timber and undergrowth.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 32 and 33.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R12W <math>\frac{1}{4}</math> S32   S33 1959</p> <p>from which</p> <p>A cottonwood, 12 ins. diam., bears S. 26° 57' W., 70 lks. dist., marked T12N., R12W., <math>\frac{1}{4}</math> S32 BT.</p> <p>No other suitable bearing tree available.</p> <p>Raise a mound of stone, <math>3\frac{1}{2}</math> ft. base, 2 ft. high, W. of cor.</p> <p>Continue over nearly level bottom land; through scattering timber, and heavy undergrowth.</p> <p>80.00 Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T12N R12W S29   S28 S32   S33 1959</p> <p>from which</p> <p>A cottonwood, 12 ins. diam., bears N. 52° 02' E., 56 lks. dist., marked T12N., R12W., S28 BT.</p> <p>A cottonwood, 12 ins. diam., bears S. 85° 26' E., 185 lks. dist., marked T12N., R12W., S29 BT.</p> <p>No other suitable bearing trees available.</p> <p>Raise a mound of stone, 4 ft. base, <math>2\frac{1}{2}</math> ft. high, W. of cor.</p> <p>Land, nearly level bottom land, subject to overflow. Soil, alluvium. Timber, cottonwood, paloverde, and mesquite; undergrowth, sagebrush and willows.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89° 54' W., bet. secs. 28 and 33.</p> <p>Over heavily rolling land; through scattering timber and undergrowth; asc. 20 ft. over E. slope.</p> <p>1.20 Spur, slopes S. 20° W., top of high rocky peak, bears S. 20° W., 10 chs. dist.; desc. 85 ft. over SW. slope.</p>
--------	---

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
5.60	Head of wash, 10 lks. wide, 2 ft. deep, drains NW.; asc. 10 ft. over NE. slope.
23.10	Top of spur, slopes N., 1 ch., thence slopes S. 70° W.; desc. 100 ft. over rolling NW. slope.
40.03	Point for the ¼ sec. cor. of secs. 28 and 33.
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12NR12W S28 S33 1959
	Desc. 16 ft. over NW. slope.
41.70	Left bank of wash, drains SW.; thence in wash, <span style="background-color: black; color: black;">[REDACTED]</span>
57.70	Right bank of wash, drains SW.; asc. 90 ft. over a perpendicular cliff, which bears N. 20° E. and S. 20° W.
61.40	Spur, slopes S. 20° W.; desc. 130 ft. over W. slope.
73.00	Enter river bottom, left bank, course SE.; thence over nearly level river bottom land, through heavy undergrowth and scattering timber.
80.06	The cor. of secs. 28, 29, 32, and 33.
	Land, heavily rolling. Soil, sandy and gravelly, stony. Timber, paloverde and cottonwood; undergrowth, cactus, yucca, cholla, ocotillo, mesquite and saguaro.
	N. 0° 02' W., bet. secs. 28 and 29.
	Over river bottom land; through scattering timber and heavy undergrowth.
6.40	Leave river bottom land; left bank, course SE.; asc. 320 ft. over broken SW. slope.
18.30	Ridge spur, slopes W.; desc. 120 ft. over N. slope.
22.60	Draw, 10 lks. wide, drains W.; asc. 50 ft. over S. slope.
29.60	Ridge spur, slopes W.; desc. 40 ft. over NW. slope.
33.50	Draw, 15 lks. wide, drains W.; asc. 30 ft. over S. slope.
37.50	Ridge spur, slopes W.; desc. 70 ft. over N. slope.
38.70	Wash, 20 lks. wide, 3 ft. deep, drains W., 3 chs., thence SW.; asc. 20 ft. over S. slope.
40.00	Point for the ¼ sec. cor. of secs. 28 and 29.
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

BOOK 4638

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains

T12NR12W

$$\frac{1}{2}$$

S29	S28
-----	-----

 1959

Asc. 35 ft. over SE. slope.

44.10 Top of low, flat spur, slopes SW., thence over rolling and broken W. slope.

66.50 Ridge spur, slopes W.; desc. 90 ft. over NE. slope.

73.50 Wash, 20 lks. wide, 3 ft. deep, drains SW.; asc. over gradual S. slope.

80.00 Point for the cor. of secs. 20, 21, 28, and 29.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W

S20	S21
S29	S28

 1959

Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of cor.

Land, heavily rolling.

Soil, sandy and gravelly, stony.

Timber, paloverde and cottonwood; undergrowth, cactus, yucca, cholla, ocotillo, greasewood, and saguaro.

From the cor. of secs. 21, 22, 27, and 28.

N. 89° 56' W., bet. secs. 21 and 28.

Over heavily rolling land, through scattering timber and undergrowth; desc. 160 ft. over steep, rocky, and broken W. to SW. slope.

17.70 Wash, 20 lks. wide, drains SW.

40.00 Point for the ¼ sec. cor. of secs. 21 and 28.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W

$$\frac{1}{4}$$

S21	S28
-----	-----

 1959

Desc. 70 ft. over rolling and broken SW. slope.

73.60 Ridge spur, slopes S. 20° W.; desc. 30 ft. over W. slope.

77.40 Draw, 10 lks. wide, 1 ft. deep, drains S.; asc. 20 ft. over E. slope.

80.00 The cor. of secs. 20, 21, 28, and 29.

Land, gently rolling.

Soil, sandy and gravelly, stony.

Timber, paloverde; undergrowth, cactus, yucca, ocotillo, cholla, greasewood, and saguaro.

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

N. 0° 02' W.; bet. secs. 20 and 21.

Over heavily rolling land, through scattering timber and medium heavy undergrowth; asc. 67 ft. over S. slope.

- 7.30 Top of small spur, slopes E.; desc. 30 ft. over N. slope.
- 11.20 Draw, 15 lks. wide, drains SW.; asc. 70 ft. over S. slope.
- 21.50 South rim of canyon, bears E. and W.; desc. 110 ft. over N. slope.
- 27.50 Left bank of large sandy wash, drains W.
- 38.30 Right bank of sandy wash, drains S. 75° W.; asc. 30 ft. over steep E. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 20 and 21.

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W

$\frac{1}{4}$

S20 | S21

1959

Asc. 27 ft. over S. slope.

- 42.00 Ridge spur, slopes S. 70° W.; asc. 210 ft. over a series of small spurs, sloping West.
- 69.10 Wash, 20 lks. wide, 2 ft. deep, drains NW.; asc. 200 ft. over S. slope.
- 80.00 Point for the cor. of secs. 16, 17, 20, and 21.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W

S17 | S16

S20 | S21

1959

Land, heavily rolling.

Soil, sandy and gravelly, stony.

Timber, paloverde; undergrowth, cactus, cholla, ocotillo, yucca, greasewood, catclaw, and saguaro.

From the cor. of secs. 15, 16, 21, and 22.

N. 89° 57' W.; bet. secs. 16 and 21:

Over rough, broken, mountainous land; through scattering timber and undergrowth; desc. 160 ft. over steep, rocky W. slope.

- 10.30 Bottom of descent; asc. 30 ft. over E. slope.
- 11.20 Top of spur, slopes S.; asc. 110 ft. over SE. slope.
- 20.25 Rocky spur, slopes S. 20° W.; desc. 410 ft. over broken, steep, W. slope.

## BOOK 4638

Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

40.01 Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 21.Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 4 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W

$$\frac{1}{4} \frac{S16}{S21}$$

1959

Continue over rough, broken, mountainous land; through scattering timber and undergrowth; desc. 330 ft. over SW. slope.

61.10 Wash, 50 lks. wide, in canyon, 20 ft. deep, drains SE.; asc. 270 ft. over steep, rocky SE. slope.

67.90 Spur, slopes SE.; desc. 10 ft.

80.02 The cor. of secs. 16, 17, 20, and 21.

Land, heavily rolling and broken mountainous.

Soil, sandy and gravelly, stony.

Timber, paloverde; undergrowth, cactus, yucca, cholla, ocotillo, and greasewood.

N.  $0^{\circ} 02'$  W., bet. secs. 16 and 17.

Over heavily rolling mountainous land, through scattering timber and medium heavy undergrowth; asc. 90 ft. over SE. slope.

6.30 Ridge spur, slopes S.  $70^{\circ}$  W.; asc. 170 ft. over broken SW. slope.

39.95 Top of spur, slopes SW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 17.Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W

$$\frac{1}{4} \frac{S17|S16}{1960}$$

Asc. 290 ft. over SW. slope.

52.20 Top of spur, slopes W.; desc. 80 ft. over NE. slope.

60.50 Bottom of descent; asc. 220 ft. over S. slope.

70.60 Ridge, bears E. and W.; desc. 290 ft. over broken N. slope.

80.00 Point for the cor. of secs. 8, 9, 16, and 17.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12NR12W

$$\frac{S8|S9}{S17|S16}$$

1960

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, palo verde and catclaw; undergrowth, cactus, cholla, ocotillo, saguaro and greasewood.
	From the cor. of secs. 9, 10, 15, and 16.
	S. 89° 59' W., bet. secs. 9 and 16.
	Over rolling mountainous land, through scattering timber and medium heavy undergrowth; asc. 16 ft. over E. slope.
1.20	Flat spur, slopes SW., desc. 370 ft. over NW. slope.
22.80	Wash, 20 lks. wide, 3 ft. deep; drains SW., asc. 182 ft. over SE. slope.
38.30	Top of ridge, bears NE. and SW.
39.91	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12N R12W S 9 $\frac{1}{4}$ <u>          </u> S 16 1960
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.
	Desc. 60 ft. over W. slope.
55.20	Wash, 10 lks. wide, 2 ft. deep, drains N., asc. 240 ft. over E. slope.
77.70	Spur; slopes N., continue along N. slope.
79.82	The cor. of secs. 8, 9, 16, and 17.
	Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, palo verde and catclaw; undergrowth, cactus, cholla, ocotillo, saguaro, and greasewood.
	N. 0° 02' W., bet. secs. 8 and 9.
	Over heavily rolling mountainous land, through scattering timber and undergrowth; desc. 180 ft. over N. slope.
7.30	Wash, 10 lks. wide, 3 ft. deep, drains E., asc. 29 ft. over SE. slope.
9.40	End of spur, slopes N70°E., desc. 140 ft. over NE. slope.
20.30	Wash, 1chs. wide, 3 ft. deep, drains N70°W.
28.30	Begin ascent; asc. 40 ft. over S. slope.
30.90	Spur, slopes W., desc. 50 ft. over N. slope.
38.80	Bottom of descent, continue over nearly level land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

Chains	
	<p style="text-align: center;">T12N R12W  <math>\frac{1}{4}</math>  S 8   S 9  1960</p> <p>Continue over gently rolling land; asc. 70 ft. over rolling S. slope.</p>
67.80	Center of large sandy wash, approximately 7 chs. wide, 3 ft. deep, drains S.70°W.
73.70	Base of hill, bears N.26°E. and S.20°W.; asc. 140 ft. over abrupt SW. slope.
80.00	Point for the cor. of secs. 4, 5, 8, and 9.
	<p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R12W  S 5   S 4  S 8   S 9  1960</p> <p>Land, heavily rolling mountainous.  Soil, sandy and gravelly, stony.  Timber, palo verde and catclaw; undergrowth, cactus, cholla, ocotillo, saguaro and greasewood.</p>
	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>S. 89° 55' W., bet. secs. 4 and 9.</p> <p>Over heavily rolling mountainous land, through scattering timber and medium heavy undergrowth; desc. 63 ft. over W. slope.</p>
3.10	Wash, 10 lks. wide, 2 ft. deep, drains S.20°W., asc. 10 ft. over SE. slope.
12.10	Ridge spur, slopes SW., desc. 150 ft. over NW. slope.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.
	<p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R12W  <math>\frac{1}{4}</math> S 4  S 9  1960</p> <p>Continue over rolling mountainous land; desc. 210 ft. over NW. slope.</p>
67.70	Center of large sandy wash, approximately 8 chs. wide, 4 ft. deep, drains S.70°W., asc. 180 ft. over SE. slope.
77.00	Spur, slopes S. 20° W., desc 90 ft. over W. slope.
79.96	The cor. of secs. 4, 5, 8, and 9.
	<p>Land, heavily rolling mountainous.  Soil sandy and gravelly, stony.  Timber, palo verde and catclaw; undergrowth, cactus, ocotillo, cholla, saguaro and greasewood.</p>



## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

N. 0° 02' W., bet. secs. 4 and 5.

Over heavily rolling mountainous land, through scattering timber and undergrowth; asc. 60 ft. over SW. slope.

2.50 Top of rimrock, edge bears E. and W., continue ascent; asc. 150 ft. over slightly rolling land, along E. rim of canyon.

37.80 Top of rimrock, edge bears NE. and SW., begin descent; desc. 30 ft. over NW. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 5.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12N R12W  
 $\frac{1}{4}$   
 S 5 | S 4  
 1960

Continue descent; desc. 160 ft. over steep, rocky NW. slope.

50.10 Wash, 40 lks. wide, 4 ft. deep, drains SW., asc. 60 ft. over steep S. slope.

61.54 Intersect the Third Standard Parallel North

Point for the closing cor. of secs. 4 and 5.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 4 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T13N R12W  
 S 33  
 S 5 | S 4  
 C C  
 T12N R12W  
 1960

From this corner, the standard  $\frac{1}{4}$  sec. cor. of sec. 33, T. 13 N., R. 12 W., which is an iron post, 1 in. in diam., firmly set in the ground and mound of stone, with brass cap marked and witnessed as described in the official record, bears East, 2.97 chs. dist.

From this same corner, the standard cor. of secs. 32 and 33, T. 13 N., R. 12 W., which is an iron post, 2 ins. in diam., firmly set in the ground, with brass cap marked and witnessed as described in the official record, bears West, 37.03 chs. dist.

Land, heavily rolling mountainous.

Soil, sandy and gravelly, stony.

Timber, palo verde and catclaw; undergrowth, cactus, ocotillo, cholla, saguaro and greasewood.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 4, is at midpoint and on the N. bdy. of the Tp.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains

T13N R12W

 $\frac{1}{4}$  S 4

T12N R12W

1960

Raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, S. of cor.

From this corner, the standard cor. of secs. 33 and 34, T. 13 N., R. 12 W., which is an iron post, 2 ins. in diam., firmly set in the ground, with brass cap marked and witnessed as described in the official record, bears East, 3.01 chs. dist.

From this same corner, the standard  $\frac{1}{4}$  sec. cor. of sec. 33, T. 13 N., R. 12 W., which is an iron post, 1 in. in diam., firmly set in the ground, with brass cap marked and witnessed as described in the official record, bears West, 36.99 chs. dist.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy of the Tp., which is marked with an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record.

N.  $0^{\circ}$  03' W., bet. secs. 31 and 32.

Over heavily rolling mountainous land; through scattering timber and medium heavy undergrowth; desc. 300 ft. over rolling NE. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 32.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12N R12W

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 31 \text{ | S } 32 \end{array}$$

1959

Desc. 20 ft. over N. slope.

43.70 Draw, 10 lks. wide, drains NE., asc. 30 ft. over SE. slope.

46.90 Low, flat topped spur, slopes NE., desc. 60 ft. over N. slope.

51.90 Wash, 20 lks. wide, 3 ft deep, drains E., asc. 70 ft. over broken S. slope.

57.40 Spur, slopes S.  $70^{\circ}$  E., desc. 40 ft. over N. slope.

65.10 Wash, 15 lks. wide, 3 ft. deep, drains E., asc. 30 ft. over SE. slope.

72.80 Rocky spur, slopes E., desc. 100 ft. over N. slope.

80.00 Point for the cor. of secs. 29, 30, 31, and 32.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12N R12W

S 30 | S 29

S 31 | S 32

1959

Land, heavily rolling.

Soil, sandy and gravelly, stony.

Timber; palo verde, undergrowth, cactus, yucca, cholla, ocotillo, catclaw, greasewood, and saguaro.

## Completion of the Subdivision of T, 12 N., R. 12 W.

Chains	
40.05	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89° 56' W., bet. secs. 29 and 32.</p> <p>Over nearly level bottom land, in the Big Sandy River; through scattering timber and dense undergrowth.</p> <p>True point for the <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 32, falls in Big Sandy river and is deemed unsafe for the corner, not monumented.</p> <p>At a point, due South, 5.00 chs. dist., on S. bank of river, point selected for the witness <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 32.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R12W</p> <p>W↑C</p> <p>S 29</p> <hr style="width: 50px; margin: 0 auto;"/> <p><math>\frac{1}{4}</math></p> <p>S 32</p> <p>1959</p> </div> <p>Raise a mound of stone, 4 ft. base, <math>2\frac{1}{2}</math> ft. high, N. of cor.</p> <p>Continue in main channel of Big Sandy river.</p>
78.00	<p>Leave river bottom land course SE.; edge bears NW. and SE., asc. 20 ft. over NE. slope.</p>
79.40	<p>Top of ascent; desc. 12 ft over NW slope to the cor.</p>
80.10	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, nearly level, river bottom. Soil, sandy and gravelly silt loam. Timber, cottonwood and mesquite; undergrowth, rabbitbrush, willows, sagebrush, greasewood, cactus and ocotillo.</p>
	<p>N. 89° 56' W., bet. secs. 30 and 31.</p> <p>Over heavily rolling land; through scattering timber and undergrowth; asc. 100 ft. over SE. slope.</p> <p>.70 Wash, 20 lks. wide, 6 ins. deep, drains NE.</p> <p>7.30 Spur, slopes NE., desc. 30 ft. over NW. slope.</p> <p>13.90 Draw, 8 lks. wide, drains NE., asc. 50 ft. over E. slope.</p> <p>15.90 Ridge spur, slopes NE., desc. 15 ft. over NW. slope.</p> <p>19.70 Wash, 15 lks. wide, 1 ft. deep, drains NE., asc. 160 ft. over SE. slope.</p> <p>32.10 Spur, slopes SE., desc. 15 ft. over W. slope.</p> <p>33.10 Head of draw, 5 lks. wide, drains S., asc. 40 ft. over SE. slope.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 30 and 31.</p>
	<p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R12W</p> <p>S 30</p> <hr style="width: 50px; margin: 0 auto;"/> <p><math>\frac{1}{4}</math></p> <p>S 31</p> <p>1959</p> </div>

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
40.50	Spur, slopes SE., desc. 110 ft. over SW. slope.
53.10	Draw, 8 lks. wide, drains SE., asc. 15 ft. over SE. slope.
64.30	Low, flat spur, slopes NE., desc. 40 ft. over W. slope.
65.30	Right bank of wash, 3 ft. high, drains NE.
71.30	Left bank of wash, drains NE., asc. 40 ft. over SE. slope.
79.32	Intersect W. bdy. of the Tp., at the cor. of secs. 25, 30, 31, and 36, which is marked with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in the ground, and in a mound of stone to top, marked and witnessed as described in the official record.
	Land, heavily rolling. Soil, sandy and gravelly, stony. Timber, palo verde; undergrowth, cactus, yucca, ocotillo, cholla, greasewood and saguaro.
	From the cor. of secs. 29, 30, 31, and 32. N. $0^{\circ} 03' W.$ , bet. secs. 29 and 30. Over nearly level river bottom land, through heavy undergrowth.
12.30	Right bank of Big Sandy river, course S. $60^{\circ} E.$ ; leave undergrowth.
30.33	Left bank of Big Sandy river, course S. $60^{\circ} E.$ , enter medium heavy timber and undergrowth.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12N R12W $\frac{1}{4}$ S 30   S 29 1959
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Continue over gently rolling land, through scattering timber and medium heavy undergrowth; asc. 20 ft. over SW. slope.
42.00	Low spur, slopes W.; desc. 10 ft. over gradual N. slope.
57.60	Wash, 10 lks. wide, 1 ft. deep, drains NW., asc. 60 ft. over S. slope.
63.50	Spur, slopes W.; desc. 15 ft. over gradual N. slope.
74.10	Wash, 10 lks. wide, 2 ft. deep, drains W.; asc. 15 ft. over gradual S. slope.
80.00	Point for the cor of secs. 19, 20, 29, and 30. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12N R12W S 19   S 20 S 30   S 29 1959

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

This corner is on spur sloping West.  
Land, south half, nearly level river bottom; north half, gently rolling.  
Soil, sandy silt loam, sandy and gravelly, stony.  
Timber, palo verde and mesquite; undergrowth, cactus, ocotillo, yucca, greasewood, willows, and saguaro.

From the cor. of secs. 20, 21, 28 and 29.

N. 89° 58' W., bet. secs. 20 and 29.

Over medium heavily rolling land, through scattering timber and undergrowth; asc. 20 ft. over E. slope.

- 3.50 Ridge spur, slopes SW.; desc. 80 ft. over W. slope.  
6.50 Draw, 15 lks. wide, 2 ft. deep, drains SW.; asc. 50 ft. over E. slope.  
12.00 Ridge spur, slopes SW.; desc. 90 ft. over W. slope.  
17.50 Draw, 12 lks. wide, 1 ft. deep, drains SW.; asc. 20 ft. over E. slope.  
21.70 Ridge spur, slopes SW., desc. 100 ft. over W. slope.  
35.15 Draw, 15 lks. wide, 2 ft. deep, drains SW.; asc. 30 ft. over E. slope.  
40.10 Point for the  $\frac{1}{4}$  sec. cor. of secs. 20 and 29.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12N R12W  
S 20  
 $\frac{1}{4}$  ———  
S 29  
1959

Continue over gently rolling land; asc. 25 ft. over SE. slope.

- 44.80 Ridge spur, slopes SW.; desc. 110 ft. over W. slope.  
58.20 Draw, 10 lks wide, 1 ft. deep, drains SW.; asc. 20 ft. over E. slope.  
72.00 Ridge spur, slopes SW.; desc. 30 ft. over W. slope.  
76.50 Draw, 15 lks. wide, 2 ft. deep, drains SW.; asc. 20 ft. over E. slope.  
80.20 The cor. of secs. 19, 20, 29, and 30.

Land, heavily rolling to gently rolling.  
Soil, sandy and gravelly clay, stony.  
Timber, palo verde; undergrowth, cactus, yucca, ocotillo, cholla, greasewood, and saguaro.

N. 89° 53' W., bet. secs. 19 and 30.

Over gently rolling land, through scattering timber and heavy undergrowth; desc. 90 ft. over W. slope.

- 9.10 Leave heavy timber; bears N. and S., left bank of Big Sandy river, 20 ft. high, course S.15°E.; desc. over perpendicular bank; continue over river bottom land.  
38.10 Right bank of the Big Sandy River, 3 ft. high, course South; enter heavy timber.  
40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 30.

BOOK 4028

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. in diam., 24 ins. in the ground, with brass cap mkd.

T12N R12W  
S 19

$\frac{1}{4}$   
S 30  
1959

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of corner.

72.70 Wash, 30 lks. wide, 1 ft. deep, drains SE.; asc. 30 ft. over SE. slope.

79.31 Intersect W. bdy. of the Tp., at the cor. of secs. 19, 24, 25, and 30, which is marked with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, marked and witnessed as described in the official record.

Land, heavily rolling to gently rolling.

Soil, sandy and gravelly clay, stony.

Timber, palo verde; undergrowth, cactus, yucca, ocotillo, cholla, greasewood, and saguaro.

From the cor. of secs. 19, 20, 29 and 30.

N.  $0^{\circ} 03'$  W., bet. secs. 19 and 20.

Over gently rolling land, through scattering timber and heavy undergrowth, desc. 50 ft. over N. slope.

15.60 Wash, 4 chs. wide, 8 ft. deep, drains W.; asc. 100 ft. over S. slope.

26.70 Top of ascent; slopes W.; continue over nearly level land.

34.00 Begin descent; desc. 90 ft. over N. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 20.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, to solid rock and in a mound of stone to top, with brass cap mkd.

T12N R12W

$\frac{1}{4}$   
S 19 | S 20  
1960

Continue over gently rolling land, through scattering timber; asc. 60 ft. over gradual S. slope.

42.20 Top of ascent; slopes W., continue over nearly level land.

47.90 Begin descent; desc. 30 ft. over N. slope.

51.00 Wash, 20 lks. wide, 10 ft. deep, drains N.  $70^{\circ}$ W.; asc. 60 ft. over gradual S. slope.

57.40 Top of ascent; slopes W.

66.45 Begin descent; desc. 130 ft. over an abrupt N. slope.

70.10 Bottom of descent; begin ascent, asc. 80 ft. over SW. slope.

74.40 Top of ascent; slopes NW.; desc. 30 ft. over N. slope, enter heavy timber.

78.98 Point selected for the witness cor. of secs. 17, 18, 19 and 20.

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T12N R12W  
 S 18 | S 17  
 ————  
 S 19 | S 20  
 W | C  
 1960

from which

An ironwood, 10 ins. diam., bears N.  $85^{\circ} 00'$  E., 121 lks. dist., mkd. T12N R12W S17 WC BT.

An ironwood, 14 ins. diam., bears S.  $67^{\circ} 30'$  E., 138 lks. dist., mkd. T12N R12W S20 WC BT.

An ironwood, 10 ins. diam., bears S.  $46^{\circ} 20'$  W., 35 lks. dist., mkd. T12N R12W S19 WC BT.

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

80.00 True point for the cor. of secs. 17, 18, 19, and 20, falls in a sandy wash, 40 lks. wide, 6 ft. deep, draining S.  $80^{\circ}$  W. not monumented.

Land, gently rolling.

Soil, sandy and gravelly, stony.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, ocotillo, greasewood, cholla, and saguaro.

From the cor. of secs. 16, 17, 20, and 21.

N.  $89^{\circ} 53'$  W., bet. secs. 17 and 20.

Over rolling mountainous land, through scattering timber and medium heavy undergrowth; asc. 15 ft. over SE. slope.

1.00 Spur, slopes S.  $20^{\circ}$  E.; desc. 120 ft. over W. to SW. slope.

5.50 Wash, 10 lks wide, 3 ft. deep, drains S.; asc. 30 ft. over E. slope.

8.10 Ridge spur, slopes SW., desc. 300 ft. over rolling and broken SW. to W. slope.

32.10 Wash, 30 lks. wide, 4 ft. deep; drains SW.

40.18 Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 20.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam.; 20 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12N R12W  
 S 17  
 ————  
 $\frac{1}{4}$   
 S 20  
 1960

Raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, N. of cor.

Continue descent; desc. 180 ft. over rolling and broken SW. to W. Slope.

48.60 Wash, 40 lks. wide, 4 ft. deep, drains N.  $70^{\circ}$  W., continue gradual descent, along S. side of wash, through medium heavy timber.

80.36 The cor. of secs. 17, 18, 19, and 20.

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

Land, rolling mountainous.  
Soil, sandy and gravelly, stony.  
Timber, palo verde, ironwood, mesquite; undergrowth, cactus, ocotillo,  
cholla, saguaro and greasewood.

N. 89° 51' W., bet. secs. 18 and 19.

Over nearly level land, through heavy timber and dense undergrowth;  
desc. 15 ft. over gradual W. slope.

2.50 Bottom of descent; Left bank of the Big Sandy River, course S.15°E.;  
over nearly level river bottom land, through dense undergrowth.

28.30 Right bank of Big Sandy river, 3 ft. high, course S.15°E., leave  
river bottom land, asc. 110 ft. over E. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 18 and 19.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground,  
and in a collar of stone to top, with brass cap mkd.

T12N R12W

S 18

$\frac{1}{4}$

S 19

1960

Raise a mound of stone,  $3\frac{1}{2}$  ft. base,  $2\frac{1}{2}$  ft. high, N. of cor.

Continue over heavily rolling land; through scattering timber and  
medium heavy undergrowth; asc. 50 ft. over E. slope.

43.60 Top of spur, slopes S 20°E., desc. 30 ft. over W. slope.

51.70 Wash, 20 lks. wide, 4 ft. deep, drains S.60°E., asc. 170 ft. over  
NE. slope.

79.25 Intersect W. bdy. of the Tp., at the cor. of secs. 13, 18, 19, and  
24, which is marked with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set in  
the ground, marked and witnessed as described in the official record.

Land, eastern half; nearly level; western half, heavily rolling.  
Soil, sandy silt loam and sandy and gravelly, stony.  
Timber, palo verde and mesquite; undergrowth, cactus, yucca, ocotillo,  
cholla, greasewood, willows, and saguaro.

From the cor. of secs. 17, 18, 19, and 20.

N. 0° 03' W., bet. secs. 17 and 18.

Over gently rolling land; through scattering timber and undergrowth.

.20 Bank of wash, 4 ft. high, drains WSW., asc. 15 ft. over S. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 18.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground,  
to solid rock, and in a mound of stone to top, with brass cap mkd.

T12N R12W

$\frac{1}{4}$

S 18 | S 17

1960

48.00 Leave gently rolling land; continue over heavily rolling mountainous  
land, through scattering timber and undergrowth; asc. 100 ft. over  
steep rocky S. slope.



## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
52.40	Top of small rocky spur, slopes E., desc. 10 ft. over N. slope.
60.30	Draw, drains SW.; begin ascent; asc. 110 ft. over S. slope.
67.40	Top of same spur, slopes S.20°W., desc. 50 ft. over NW. slope.
74.30	Wash, 30 lks. wide, 8 ft. deep, drains S. 70°W., asc. 40 ft. over abrupt S. slope.
75.50	Top of ascent; slopes S.70°E., desc. 60 ft. over NE. slope.
77.00	Enter large sandy wash, approximately 40 lks.wide, draining S.20°W., continue in wash.
80.00	Point for the cor. of secs. 7, 8, 17, and 18, falls in sandy wash, and it is deemed unsafe for the corner. For witness cor. see the line between secs. 7 and 8.
	Land, S $\frac{1}{2}$ gently rolling; N $\frac{1}{2}$ heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, cottonwood, mesquite, palo verde and catclaw; undergrowth, cactus, ocotillo, cholla, saguaro and greasewood.
	From the cor. of secs. 8, 9, 16, and 17. N. 89° 51' W. bet. secs. 8 and 17. Over heavily rolling mountainous land, through scattering timber and undergrowth; desc. 40 ft. over NW. slope.
2.10	Draw, drains N.20°W., asc. 90 ft. over NE. slope.
21.70	Ridge, bears N.20°W. and S.20°E., desc. 510 ft. over broken W. slope.
40.14	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	T12N R12W S 8 $\frac{1}{4}$ ————— S 17 1960
	Continue descent over broken W. slope., desc. 200 ft. over W. slope.
52.60	Wash, 40 lks. wide, 4 ft. deep, drains SW., asc. 70 ft. over E. slope.
58.70	Ridge spur, slopes SW.; desc. 240 ft. over steep, rocky W. slope.
80.28	The true point for the cor. of secs. 7, 8, 17, and 18, in sandy wash. Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, palo verde and catclaw; undergrowth, cactus, ocotillo, cholla, saguaro and greasewood.
	N. 89°45' W., bet. secs. 7 and 18. Over heavily rolling mountainous land, through scattering timber and medium heavy undergrowth; asc. 297 ft. over steep E. slope.
4.20	Wash .50 lks.wide, 6 ft. deep, drains SSE.
13.30	Rocky spur, slopes SSE. Top of round topped peak, bears NNE., .5 chs dist. , desc. 353 ft. over steep SW. slope.

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
34.50	Wash, 20 lks. wide, 2 ft. deep, drains SE., asc. 50 ft. over NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	$\begin{array}{r} T12N R12W \\ S 7 \\ \hline \frac{1}{4} S 18 \\ 1960 \end{array}$
	Over rolling to broken NE. slope.
47.60	Top of ascent; end of spur, slopes N.; desc. 110 ft. over rocky, rolling and broken W. slope.
62.80	Wash, 10 lks. wide, 4 ft. deep, drains S.20°W., asc. 170 ft. over steep SE. slope.
66.80	Spur, slopes S.20°W., desc. 150 ft. over W. slope.
70.00	Wash, 20 lks. wide, 3 ft. deep, drains SW., asc. 10 ft. over SE. slope.
74.50	Spur, slopes S., desc. 20 ft. over SW. slope.
77.60	Wash, 15 lks. wide, 3 ft. deep, drains S., asc. 20 ft. over E. slope.
79.18	Intersect W. bdy. of the Tp., at the cor. of secs. 7, 12, 13, and 18, which is marked by an iron post, $2\frac{1}{2}$ ins. diam., firmly set in the ground, marked and witnessed as described in the official record.
	Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, palo verde and catclaw; undergrowth, cactus, ocotillo; cholla, saguaro and greasewood.
	From the true point for the cor. of secs. 7, 8, 17, and 18.
	N. 0° 03' W., bet. secs. 7 and 8.
	Over heavily rolling mountainous land; through scattering timber and undergrowth, continue in wash, asc. 12 ft. over S. slope.
.90	Left bank of wash, course SSE.
1.18	Point selected for the witness cor. of secs. 7, 8, 17, and 18; near top of ascent; sloping W.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.
	$\begin{array}{r} T12N R12W \\ S 7 \quad   \quad S 8 \\ \hline S 18 \quad   \quad S 17 \\ \downarrow \\ W C \\ 1960 \end{array}$
	Desc. 15 ft. over rocky N. slope.
2.00	Left bank of wash, bears S.70°W. and N.70°E., approximately 60 lks. thence N.20°W., continue in wash.
8.00	Left bank of same wash, bears S.20°E. and N.20°W.; asc. 540 ft. over abrupt S. slope.
27.80	Continue ascent of 140 ft. over SW. slope.

## Completion of the Subdivision of T.12 N., R.12 W.

Chains	
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 8.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R12W</p> <p><math>\frac{1}{4}</math></p> <p>S 7   S 8</p> <p>1960</p> </div> <p>Asc. 20 ft. over SW. slope.</p>
42.90	Ridge spur, slopes S.80°W.; desc. 400 ft. over N. slope.
78.50	<p>Point selected for the witness cor. of secs. 5, 6, 7, and 8.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. in diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R12W</p> <p>W C</p> <p>S 6   S 5</p> <p>S 7   S 8</p> <p>1960</p> </div>
79.00	Bottom of descent; edge bears S.70°E. and N.70°W., enter flat wash area.
80.00	<p>True point for the cor. of secs. 5, 6, 7, and 8, falls in a large sandy wash area approximately 5 chs. wide.</p> <p>Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, palo verde and catclaw; undergrowth, cactus, ocotillo, cholla, saguaro and greasewood.</p>
	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 89° 52' W., bet. secs. 5 and 8.</p> <p>Over heavily rolling mountainous land, through scattering timber and undergrowth; desc. 180 ft. over W. slope.</p>
6.90	Wash, 40 lks. wide, 3 ft. deep, drains S., asc. 310 ft. over E. slope.
22.30	Top of ascent; slopes S.20°E., desc. 60 ft. over W. slope.
34.20	Wash, 20 lks. wide, 5 ft. deep, drains S.20°E., asc. 100 ft. over E. slope.
40.20	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R12W</p> <p>S 5</p> <hr style="width: 50px; margin: 0 auto;"/> <p><math>\frac{1}{4}</math></p> <p>S 8</p> <p>1960</p> </div> <p>Raise a mound of stone, 3 ft. base, <math>2\frac{1}{2}</math> ft. high, N. of cor.</p>
40.58	Point selected for E. end of triangulation; begin descent over abrupt broken W. slope; desc. 630 ft.

## Completion of the Subdivision of T. 12 N., R. 12 W.

Chains	
76.00	Bottom of descent; edge bears NW. and SE., continue over nearly level flood land.
80.40	<p>The true point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Land, heavily rolling mountainous. Soil, sandy and gravelly, stony. Timber, palo verde and catclaw; undergrowth, cactus, ocotillo, cholla, saguaro and greasewood.</p>
	N. 89° 41' W., bet. secs. 6 and 7.
	Over nearly level flood land.
1.40	Bank of wash, 6 ft. high, bears NW. and SE. asc. 40 ft. over gradual N. slope, through scattering timber and undergrowth.
25.90	Base of spur, bears N.20°W. and S.20°E., asc. 140 ft. over steep, rocky, NE. slope.
33.50	Rocky spur, slopes N., desc. 100 ft. over steep NW. slope.
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 7.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.</p>
	<p style="text-align: center;">T12N R12W S 6 <math>\frac{1}{4}</math> ——— S 7 1960</p>
	Asc. 170 ft. over rolling N. slope.
58.10	Fence, 4 strand barbed wire on steel posts, bears N. and S.
60.50	Wash, 20 lks. wide, 4 ft. deep, drains N., continue ascent; asc. 90 ft. over NE. slope.
68.50	Spur, slopes NE., desc. 40 ft. over W. slope.
70.60	Wash, 20 lks. wide, 3 ft. deep, drains N.20°E., asc. 150 ft. over E. to NE. slope.
79.00	<p>Intersect W. bdy. of Tp. at the cor. of secs. 1, 6, 7, and 12, which is marked with an iron post, <math>2\frac{1}{2}</math> ins. in diam., firmly set in the ground, marked and witnessed as described in the official record.</p> <p>Land, rolling mountainous. Soil, sandy and gravelly, stony. Timber, palo verde and catclaw; undergrowth, cactus, ocotillo, cholla, saguaro, and greasewood.</p>
	From the true point for the cor. of secs. 5, 6, 7, and 8.
	N. 0° 03' W., bet. secs. 5 and 6.
	Over wash area.
3.00	Leave wash area, continue by triangulation, begin ascent; asc. 630 ft. over steep, rocky SW. slope.
34.70	Top of rimrock, edge bears SE. and W., asc. 30 ft. over gentle S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of 5 and 6.

## Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T12N R12W

$\frac{1}{4}$   
S 6 | S 5  
1960

Asc. 40 ft. over gradual S. slope.

61.06 Intersect the third standard parallel North.

Point for the closing cor. of secs. 5 and 6.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T13N R12W

S 32  
-----  
S 6 | S 5  
C | C  
T12N R12W  
1960

From this corner, the standard  $\frac{1}{4}$  sec. cor. of sec. 32, T. 13 N., R. 12 W., which is an iron post, 1 in. diam., firmly set in the ground, with brass cap marked and witnessed as described in the official record, bears East, 3.34 chs. dist.

From this same corner, the standard cor. of secs. 31 and 32, T. 13 N., R. 12 W., which is an iron post, 2 ins. diam., firmly set in the ground, with brass cap marked and witnessed as described in the official record, bears West, 36.66 chs. dist.

Land, heavily rolling mountainous.

Soil, sandy and gravelly, stony.

Timber, palo verde and catclaw; undergrowth, cactus, ocotillo, cholla, saguaro and greasewood.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 5, is at midpoint and on the N. bdy. of the Tp.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T13N R12W

$\frac{1}{4}$  S 5  
T12N R12W  
1960

From this corner, the standard cor. of secs. 32 and 33, T. 13 N., R. 12 W., which is an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record, bears East, 3.15 chs. dist.

From this same corner, the standard  $\frac{1}{4}$  sec. cor. of sec. 32, T. 13 N., R. 12 W., which is an iron post, 1 in. diam., firmly set in the ground, marked and witnessed as described in the official record, bears West, 36.85 chs. dist.

## BOOK 4638

Completion of the Subdivision of T. 12 N., R. 12 W.

## Chains

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 6 is 40.00 chs. West of the closing corner of secs. 5 and 6 on the N. bdy. of the Tp. This point falls in a sandy wash, 30 lks. wide, draining S.  $20^{\circ}$  W.; not monumented.

At the point selected for the witness N.  $\frac{1}{4}$  sec. cor. of sec. 6; East, 0.62 lks. dist. from true point for corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T13N R12W

←  
W C  $\frac{1}{4}$  S 6

T12N R12W

1960

From the true point for the N.  $\frac{1}{4}$  cor of sec. 6, the standard cor. of secs. 31 and 32, T. 13 N., R. 12 W., which is an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record, bears East, 3.34 chs. dist.

From the true point for the N.  $\frac{1}{4}$  cor. of sec. 6, the witness standard  $\frac{1}{4}$  sec. cor. of sec. 31, T. 13 N., R. 12 W., which is an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record, bears West, 40.66 chs. dist.

---

 General Description
 

---

Township 12 North, Range 12 West is gently rolling mountainous land in the southern part to heavily rolling mountainous land in the central and northern portion, with some cliffs, and is cut up with numerous deep, dry, canyons. Big Sandy River cuts across the southwest portion of the township, and is a wide, mostly dry, very sandy wash, except during a few months of the year, when run-off occurs. The soil of the bottom land along the river is a very fine sandy silt loam and the other soil in the township is sandy and gravelly, stony. There is a considerable growth of cottonwood trees and willows along the river with a scattering to heavy growth of palo verde, catclaw, and mesquite, all non-commercial, over the remainder of the township. There are several springs in the NE.  $\frac{1}{4}$  of sec. 16 and in the NE.  $\frac{1}{4}$  of sec. 28. There are no settlers living within the township and no cultivated land. The only apparent revenue derived at the present time is from grazing as there is a fair growth of native grasses throughout the township. There is no mining activity in the township at the present time.

4-680  
(Feb., 1950)

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**FIELD ASSISTANTS**

NAMES	CAPACITY
Darrell D. Holbrook	Survey Aide
Dee Von Thompson	Survey Aide
Lynn S. Griffin	Notekeeper
Jeddie J. Judd	Drag Chainman
John R. Koger	Cornerman and truck driver
Cleo T. Wooton	Flagman

CERTIFICATE OF CADASTRAL ENGINEER

I, Horace G. Parker, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of July, 1959, I have surveyed the remaining Subdivision Lines of Township 12 North, Range 12 West,

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

January 9, 1961

Horace G. Parker
Horace G. Parker
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., AUG 7 1962, 19

The foregoing field notes of the survey of the completion of the Subdivisions of Township 12 North, Range 12 West, Gila and Salt River Meridian, Arizona.

executed by Horace G. Parker, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

Chief, Division of Cadastral Engineering
Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.