

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

DEPENDENT RESURVEY

of

A PORTION OF THE SUBDIVISIONAL LINES

of

TOWNSHIP 8 SOUTH, RANGE 26 EAST

Of the Gila and Salt River *Meridian,*

In the State of Arizona

EXECUTED BY

Dell Cazier Cadastral Surveyor

Under special instructions dated March 22, 19 61, *which provided*
for the surveys included under Group No. 360, *approved* March 22, 1961
and assignment instructions dated March 27, 19 61

Survey commenced April 3, 19 61

Survey completed April 7, 19 61

1A

BOOK 4640

INDEX DIAGRAM

Township 8 South, Range 26 East

6	5	4	3	2	1
7	8	9	10	11	12
18 9	17	16	15	14	13
19 7	8 20 6	21	22	23	24
30 5	5 29 4	3 28	27	26	25
31	3 32	2 33	34	35	36

Dependent Resurvey of a Portion of the
Subdivisional Lines of T. 8 S., R. 26 E.

Chains

The south, west, east and north boundaries and the subdivisional lines were surveyed in 1875 by T. F. White, the south boundary was resurveyed in 1904 by P. Contzen. The south, west, east and north boundaries were resurveyed in 1957 by D. E. Harding.

The following field notes are those of the dependent resurvey of the boundaries of sections 19, 29, 30, 31 and 32.

The survey was initiated on the official request of the State Supervisor for Arizona to perpetuate the original corner locations and to provide identification of the boundaries of the public lands to facilitate administration under appropriate public land laws.

The identified evidence of the original corners consisted of the remains of the corner monument and/or the remains of bearing objects. Only about one quarter of the original corner positions could be identified. The remainder of the positions were lost. Before restoring the corners, the lines were retraced and a diligent search made for any evidence of the original corners, bearing objects, and any other calls of the original field note record. When duly identified the corner positions were remonumented and new accessories established. After completing the necessary retracements to connect with the identified corner locations, and exhausting every reasonable possibility of finding direct evidence for the control of each particular corner, the rules of proportionate measurement were applied in order to ascertain the position of lost corners. The true lines thus adjusted to the identified original evidence were then run.

This survey was executed with a W. & L. E. Gurley transit, serial No. 481346, constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition prior to beginning the survey and was maintained in proper adjustment throughout the progress of the survey.

The azimuth of the lines of the survey was determined by observations on Polaris at elongation, on line and carried forward by sustained angulation and checked for accuracy by altitude observations on the sun taken throughout the progress of the survey.

Measurements were made with a narrow steel tape, eight chains in length, graduated in tenths for the first 10 links, in links for the next 90 links and thereafter at intervals of 10 links. The tape was tested by comparison with a standard one-chain steel tape and found to be correct. All measurements were made on the slope and the vertical angle of each interval ascertained by a clinometer in good adjustment. Horizontal equivalents alone are entered in the field notes. All lines of this survey were run by direct method. The retracement data was checked and verified prior to conclusion of the field work and in order to simplify the record the true line notes are supplied herewith, which refer to the completed survey.

The geographic position of the southeast corner of section 32 is latitude $32^{\circ} 41' 11.382''$ N. and longitude $109^{\circ} 41' 54.560''$ W., as determined by direct tie to U.S.C. & G.S. triangulation station "Swift" which is located in the southwest quarter of section 17, T. 8 S., R. 26 E.

The magnetic declination was read at a number of stations throughout the township and the average of these readings was found to be 13° East.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 S., R. 26 E., G. & S. R. Mer., Arizona

Reestablishment of the Survey Executed by
T. F. White, dated Sept. 23, 1874.

BOOK 4640

Dependent Resurvey of a Portion of the
Subdivisional Lines of T. 8 S., R. 26 E.

Chains

Beginning at the cor. of secs. 32 and 33, which is monumented by an iron post $2\frac{1}{2}$ ins. in diam., firmly set, mkd. and witnessed as described in the official record of the dependent resurvey of the boundaries of T. 8 S., R. 26 E. as executed by Donald E. Harding in 1957.

N. $0^{\circ} 04'$ E., bet. secs. 32 and 33.

Over nearly level land void of timber.

.32 Irrigation canal, 2 ft. wide, 1 ft. deep, flows to W.

.40 Fence, 5 strand barbed wire, bears E. and W.

.52 Reference monument for cor. of secs. 32 and 33, an iron post, $2\frac{1}{2}$ ins. diam., firmly set and marked as described in 1957 resurvey field notes.

20.00 Fence, 5 strand barbed wire, bears E. and W.

26.40 Road, bladed, bears E. and W.

26.65 Irrigation canal, concrete lined, 2 ft. wide, 1 ft. deep, flows to W.

39.87 The point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, in line with property line fences to the N., E. and W. This is the position for the cor. as accepted by local ranchers; it is accepted as the best evidence of the position of the original cor.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T8S R26E

$\frac{1}{4}$

S32|S33

1961

N. $0^{\circ} 03'$ E., beginning new measurement.

Along fence line.

18.20 Fence terminates at junction of fences bearing NE. and SW.

20.00 Fence, bears E. and W.

21.50 Road, bladed, bears NE. and SW.

39.77 The cor. of secs. 28, 29, 32 and 33 as determined by the remains of charcoal deposits. It is accepted as the best evidence of the position of the original corner.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in diam., 24 ins. in the ground with brass cap mkd.

T8S R26E

S29|S28

S32|S33

1961

Land, nearly level.

Soil, sandy clay.

Undergrowth, scattering catclaw and creosote brush.

Timber, none.

Dependent Resurvey of a Portion of the
Subdivisional Lines of T. 8 S., R. 26 E.

Chains	
	N. 0° 03' E., bet. secs. 28 and 29. Over nearly level desert land.
16.90	Fence, bears E. and W.
26.60	Wash, 1.50 chs. wide, 7 ft. deep, drains to NE.
39.77	Point for the $\frac{1}{4}$ sec. cor of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to bedrock and in a mound of stone, $3\frac{1}{2}$ ft. base to top with brass cap mkd. <div style="text-align: center;"> T 8S R26E $\frac{1}{4}$ S29 S28 1961 </div> from which A fence post in a fence line bearing N. S., and W., bears S. 34° W., 63 links dist.
39.99	Road, graded, bears irregularly E. and W.; begin gentle descent to the section corner.
50.80	Draw, drains to E.
58.50	Fence, bears E. and W.
79.54	The cor. of secs. 20, 21, 28 and 29 as determined from the remains of the original bearing trees: A mesquite, 6 ins. diam., bears N. 10° W., 186 lks. dist. A mesquite stump, bears N. 39° W., 198 links dist. At the cor. point Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top with brass cap mkd. <div style="text-align: center;"> T 8S R26E S20 S21 S29 S28 1961 </div> Land, nearly level desert. Soil, sandy, gravelly. Undergrowth, catclaw and creosotebrush. Timber, none.
	From the cor. of secs. 31 and 32, which is mkd. by an iron post $2\frac{1}{2}$ ins diam., firmly set, marked and witnessed as described in the official dependent resurvey record of the boundaries of T. 8 S., R. 26 E. N. 0° 06' W., bet. secs. 31 and 32. Over level cultivated land.
.32	Irrigation canal, 2 ft wide, 1 ft. deep, concrete lined, flows to E.
.38	Enter cultivated fields, bears E. and W.

BOOK 4640

Dependent Resurvey of a Portion of the
Subdivisional Lines of T. 8 S., R. 26 E.

Chains	
39.20	Fence, 3 strand barbed wire, bears E. and W.
39.50	Irrigation canal, 2 ft. wide, 1 ft. deep, concrete lined, flows to E.
39.87	Point for the $\frac{1}{4}$ cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd. <div style="text-align: center;"> T 8S R26E $\frac{1}{4}$ S31 S32 1961 </div>
59.90	Fence, bears E. and W.
73.90	Road, bears NW. and SE. for 5.00 chs. to ranch house.
76.10	Fence, bears E. and W.
79.74	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top with brass cap mkd. <div style="text-align: center;"> T 8S R26E S30 S29 <hr style="width: 50%; margin: 0 auto;"/> S31 S32 1961 </div> <p style="text-align: center;">Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>Land, level cultivated. Soil, sandy clay. Undergrowth, patches of creosote brush. Timber, none.</p>
	From the cor. of secs. 28, 29, 32 and 33. N. 89° 56' W., bet. secs. 29 and 32.
.40	Fence, bears N. and S.
11.20	Irrigation canal, 2 ft. wide, 1 ft. deep, concrete lined, drains to N.
11.80	Wash, 15 lks. wide, 8 ft. deep, drains to N.
22.67	Irrigation canal, 2 ft. wide, 1 ft. deep, concrete lined, drains to N.
36.00	Leave cultivated area, bears NW. and SE.; begin ascent E. slope.
38.00	Spur, projects NE.; desc. W. slope.
39.48	Point selected for the witness $\frac{1}{4}$ cor of secs. 29 and 32. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd; <div style="text-align: center;"> T 8S R26E S29 WC $\frac{1}{4}$ ← S32 1961 </div>

Dependent Resurvey of a Portion of the
Subdivisional Lines of T 8 S., R. 26 E.

Chains	
39.78	True point for the $\frac{1}{4}$ cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor. The point falls on steep W. slope of spur where cor. cannot be perpetuated.
39.80	Fence, 4 strand barbed wire, R-O-W for Highway No. 666.
40.55	Centerline of U.S. Highway No. 666, bears N. and S.
41.30	R-O-W fence for U.S. Highway No. 666, parallels highway.
49.69	End descent.
61.17	Power line, bears generally N. and S.; thence asc. 30 ft.
70.60	Top of ascent; ridge bears NE. and SW., desc. gradually.
79.10	Road, graded, bears NE. and SW.
79.57	The cor. of secs. 29, 30, 31 and 32. Land, gently rolling. Soil, sandy, gravelly. Undergrowth, patches of creosote brush. Timber, none.
	S. 89° 48' W., bet. secs. 30 and 31.
	Over gently rolling land.
2.36	Road, bladed, bears NW. and SE.
2.94	Fence, 4 strand barbed wire, bears N. and S.
11.00	Low spur, slopes NE., gradual descent.
22.00	Draw, drains to NE.
32.50	Fence, 4 strand barbed wire, bears NW. and SE.
39.64	Point for the $\frac{1}{4}$ cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to bedrock and in a mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd
	T 8S R26E S30 $\frac{1}{4}$ S 31 1961
56.30	Telephone line, 3 wires, bears N. and S.
78.49	The cor. of secs. 25, 30, 31 and 36 on the W. Bdy. of the Township, marked by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, properly marked and witnessed as described in the official resurvey record. Land, gently rolling desert. Soil, gravelly with some large boulders. Undergrowth, scattering creosote brush, and catclaw. Timber, none.
	From the cor. of secs. 29, 30, 31 and 32. N. 0° 15' W., bet. secs. 29 and 30.

BOOK 4640

Dependent Resurvey of a Portion of the
Subdivisional Lines of T. 8 S., R. 26 E.

Chains	
	Over nearly level desert land void of timber.
19.50	Wash, 30 links wide, 4 ft. deep, drains to E.
28.15	Power line, bears NW. and SE.
34.35	Wash, 30 links wide, 4 ft. deep, drains to E.
39.87	Point for the $\frac{1}{4}$ cor of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground with brass cap mkd. <div style="text-align: center;"> T 8S R26E $\frac{1}{4}$ S30 S29 1961 </div>
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W. of corner.
41.00	Fence, barbed wire, bears E. and W.
54.20	Trail road, bears E. and W.
66.10	Trail road, bears N. 20° W. and S. 20° E.
67.10	Wash, 20 links wide, 5 ft. deep, drains to NE.
79.74	The cor. of secs. 19, 20, 29 and 30 as determined from the remains of the original post and charred stake. At the corner point. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 5 ft. base, to top with brass cap mkd. <div style="text-align: center;"> T 8S R26E S19 S20 S30 S29 1961 </div>
	Land, nearly level. Soil, sandy, gravelly. Undergrowth, catclaw and creosote brush. Timber, none.
	From the cor. of secs. 20, 21, 28 and 29. N. 89° 59' W., bet. secs. 20 and 29. Over gently rolling desert land, through chaparral and cacti.
9.82	Draw, drains irregularly to N.; asc. gentle E. slope.
40.00	Point for the $\frac{1}{4}$ cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground in a collar of stone to top, with brass cap mkd. <div style="text-align: center;"> T 8S R26E S20 $\frac{1}{4}$ S29 1961 </div>

Dependent Resurvey of a Portion of the
Subdivisional Lines of T. 8 S., R. 26 E.

Chains

Deposit glass at base of iron post.

from which

An Arizona State Highway monument mkd. Elev. 3271.06 + P.O.C.
Sta. 1079+50, 1960 bears S. 45° 26' W., 3.07 chs. dist.

42.60 Fence, R-O-W for U.S. Highway No. 666, bears N. and S.

43.40 Centerline of U.S. Highway No. 666, bears N. and S.

44.20 Fence, R-O-W parallels highway.

49.00 Draw, drains to NE.

80.00 The cor. of secs. 19, 20, 29, and 30.

Land, gently rolling.
Soil, sandy, gravelly.
Undergrowth, creosote brush and cacti.
Timber, none.

S. 89° 54' W., bet. secs. 19 and 30.

Over nearly level land.

3.50 Road, bladed, bears N. and S.; begin gentle ascent.

8.00 Low ridge, bears NE. and SW.; desc. 30 ft.

12.19 Draw, drains to NE., gentle ascent.

18.40 Low spur, projects NE.

19.77 Point for E. 1/16 cor. of secs. 19 and 30, at proportionate dist.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground
to bedrock and in a mound of stone, 3 ft. base to top with brass
cap mkd.

T 8S R26E
S19
E 1/16 ———
S30
1961

24.90 Power line, bears N. and S.

35.80 Wash, 20 links wide, 3 ft. deep, drains to NE.

39.54 Point for the ¼ cor. of secs. 19 and 30, at proportionate dist.;
there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground
to bedrock and in a mound of stone, 3 ft. base to top with brass
cap mkd.

T 8S R26E
S19
¼ ———
S30
1961

from which

The flag pole on the United States Federal Prison bears N. 33°
34' W., 9.29 chs. dist.

BOOK 4640

Dependent Resurvey of a Portion of the
Subdivisional Lines of T. 8 S., R. 26 E.

Chains	
58.00	Oiled road, 16 links wide, bears NE. and SW.
58.70	Telegraph line, bears NE. and SW.
59.31	Point for the W. 1/16 cor. of secs. 19 and 30, at proportionate dist. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.
	T 8S R26E S19 W 1/16 ——— S30 1961
78.09	The cor. of secs. 19, 24, 25 and 30 on the W. Bdy. of the Township, marked by an iron post, 2½ ins. in diam., firmly set, properly marked and witnessed as described in the official resurvey records.
	Land, nearly level. Soil, sandy, rocky. Undergrowth, cacti and creosote brush. Timber, none.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0° 13' W., bet. secs. 19 and 20.
	Over gently rolling desert land, through sparse undergrowth.
5.70	Spur, projects E.; desc. 60 ft. N. slope.
9.30	Draw, drains to E.; asc. to ridge.
17.50	Ridge, bears E. and W.; desc. 52 ft. on N. slope.
23.34	Wash, 20 links wide, 3 ft. deep, drains to E.
39.83	Point for the ¼ cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone 3½ ft. base to top with brass cap mkd.
	T8S R26E ¼ S19 S20 1961
59.50	Fence, 3 strand barbed wire, bears E. and W.
69.10	Center of oiled road under construction at time of survey; will be Arizona State Highway after completion, bears E. and W.
69.70	Fence, 3 strand barbed wire, parallels highway.
79.66	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.
	T8S R26E S18 S17 S19 S20 1961

Dependent Resurvey of a Portion of the
Subdivisional Lines of T. 8 S., R. 26 E.

Chains

Deposit glass at base of post

from which

The cor. of secs. 15, 16, 21 and 22 bears S. 89° 57' E., 158.92 chains dist. as determined by the remains of the original bearing trees;

A mesquite stump, bears S. 74° 30' E., 97 lks. dist.
(record bearing S. 73° E.)

A mesquite stump, bears N. 61° E., 152 lks. dist.

A mesquite stump, bears S. 76° 03' W., 20 lks. dist.
(record bearing S. 72° 30' W.)

A mesquite stump, bears N. 73° 41' W., 67 lks. dist.
(record bearing N. 78° W.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T8S R26E	
S16	S15
S21	S22
1961	

Deposit glass at base of post.

From the cor. of secs. 17, 18, 19 and 20, U.S.C. and G.S. triangulation station "Swift" bears N. 83° 42' E., 9.89 chains distant.

The cor. of secs. 5, 6, 31 and 32 on the N. Bdy. of the Township bears North, 239.03 chains distant and is marked by an iron post, 2½ ins. in diam., firmly set, properly marked and witnessed as described in the official resurvey records.

Land, nearly level.

Soil, rocky.

Undergrowth, scattering cacti and chaparral.

Timber, none.

N. 89° 44' W., bet. secs. 18 and 19.

.40 Fence, 5 strand barb wire, bears N. and S.

26.10 Enter sandy mesa.

39.72 The ¼ sec. cor. of secs. 18 and 19 as determined from the original mound of stone and remains of the bearing trees:

A mesquite, 7 ins. in diam., 14 lks. distant.

A mesquite, 8 ins. in diam., 27 lks. distant.
(Both stumps record dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone 4 ft. base to top with brass cap mkd.

T8S R26E	
¼	S18
	S19
1961	

Dependent Resurvey of a Portion of the
Subdivisional Lines of T. 8 S., R. 26 E.

Chains	<p>S. 89° 57' W., beginning new measurement.</p>
24.04	<p>Power line, bears N. 26° W. and S. 26° E.</p>
38.18	<p>The cor. of secs. 13, 18, 19 and 24 on the W. Bdy. of the Township marked by an iron post, 2$\frac{1}{2}$ ins. in diam., firmly set, properly marked and witnessed as described in the official resurvey records.</p> <p>Land, nearly level mesa. Soil, sandy. Undergrowth, scattering cacti and creosote brush. Timber, none.</p>
	<p>General Description</p>
	<p>The land of T. 8 S., R. 26 E. is a dissected bajada, which extends northeast from Mount Graham. The area surveyed is located approximately 12 miles south of the city of Safford, Arizona. The elevation of the area ranges from about 3,800 feet above sea level in the southwest quarter of section 31 to about 3,000 above sea level in the northeast quarter of section 29.</p> <p>The drainage of the area consists of numerous tributary dry washes, and two main intermittent streams; Stockton Wash and Jacobson Canyon, which drain east and north about six miles to the Gila River.</p> <p>There are two distinct soil types in the area surveyed. In the stream valleys created by the intermittent streams there is a deep well-developed river alluvium. Most of the land where this soil is found, which amounts to about 45%, has passed into private ownership. Where adequate water is available this soil produces excellent crops of cotton, lucern and other forage plants.</p> <p>In that portion, approximately 55%, of the area surveyed which is still under Federal jurisdiction the soil is boulder strewn, rocky, sandy clay and produces a vegetation cover of black brush, cacti, with catclaw and mesquite in thickets along the drainage.</p> <p>There are two hard surface roads in the area. U. S. No. 666 extends north and south through the area surveyed. The other hard surface road begins at a junction with U. S. No. 666 near the northeast corner of section 19 and bears southwest. This road is now under construction and when finished will become a state highway. Besides these two surfaced roads there are numerous improved light duty and unimproved roads so that any portion of the area is easily accessible.</p> <p>The only sources of water noted during this survey were the wells, ponds and lake on private land.</p> <p>The area surveyed is so highly developed that it was impractical to number and locate the improvements and permanent residents. At present there is considerable activity in and around the area. The private land is being sold for home sites as the growth of Safford seems to be southward. It seems reasonable to expect that the value of the land will increase.</p>

BOOK 4846

4-680
(Feb., 1950)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Wallace Ott	Notekeeper
Gary Rutledge	Chainman
Gordon Shurtz	Chainman
Wyne Fisher	Flagman
Parley Pratt	Cornerman

BOOK 4640

CERTIFICATE OF CADASTRAL ENGINEER

I, Dell Cazier, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day of March, 1961, I have ~~surveyed~~ dependently resurveyed a portion of the subdivisional lines of Township 8 South, Range 26 East,

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

December 1, 1961

Dell Cazier
Dell Cazier
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., JUL 25 1962, 19

The foregoing field notes of the ~~survey of~~ dependent resurvey of a portion to the subdivisional line of T. 8 S., R. 26 E., Gila and Salt River Meridian, Arizona,

executed by Dell Cazier, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

E. R. Huntington
Cadastral Engineering Staff Officer
Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

Cadastral Engineering Staff Officer