

ORIGINAL

BOOK 407

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

of the

DEPENDENT RESURVEY

of

A PORTION OF THE EAST BOUNDARY

of

TOWNSHIP 15 NORTH, RANGE 12 WEST

and

The Survey

of the

SUBDIVISIONAL LINES

of

TOWNSHIP 15 NORTH, RANGE 11 WEST

*Of the* Gila and Salt River Base and *Meridian,*

*In the State of* ARIZONA

## EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

*Under special instructions dated* November 4, 1960, *which provided*  
*for the surveys included under Group No.* 356, *approved* November 15, 1960  
*and assignment instructions dated* December 29, 1961

*Survey commenced* January 9, 1962

*Survey completed* March 7, 1962

BOOK 4651

# INDEX DIAGRAM

Township 15 North, Range 11 West

|    |           |           |           |           |           |           |           |           |           |           |           |           |
|----|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
|    | 52        |           | 52        |           | 36        |           | 27        |           | 18        |           | 10        |           |
| 50 | <b>6</b>  | 51        | <b>5</b>  | 35        | <b>4</b>  | 26        | <b>3</b>  | 17        | <b>2</b>  | 9         | <b>1</b>  |           |
|    | 49        |           | 48        |           | 34        |           | 25        |           | 17        |           | 8         |           |
| 50 | <b>7</b>  | 48        | <b>8</b>  | 33        | <b>9</b>  | 24        | <b>10</b> | 16        | <b>11</b> | 8         | <b>12</b> |           |
|    | 46        |           | 46        |           | 33        |           | 24        |           | 15        |           | 7         |           |
| 47 | <b>18</b> | 45        | <b>17</b> | 32        | <b>16</b> | 23        | <b>15</b> | 14        | <b>14</b> | 6         | <b>13</b> |           |
|    | 43        |           | 42        |           | 31        |           | 22        |           | 14        |           | 6         |           |
| 44 | <b>19</b> | 41        | <b>20</b> | 31        | <b>21</b> | 21        | <b>22</b> | 13        | <b>23</b> | 5         | <b>24</b> |           |
|    | 40        |           | 39        |           | 30        |           | 20        |           | 12        |           | 4         |           |
| 41 | <b>30</b> | 39        | <b>29</b> | 29        | <b>28</b> | 20        | <b>27</b> | 12        | <b>26</b> | 3         | <b>25</b> |           |
|    | 38        |           | 37        |           | 28        |           | 19        |           | 11        |           | 3         |           |
| 1  | 38        | <b>31</b> | 36        | <b>32</b> | 27        | <b>33</b> | 18        | <b>34</b> | 10        | <b>35</b> | 2         | <b>36</b> |

TOWNSHIP 15 NORTH, RANGE 11 WEST,  
GILA AND SALT RIVER MERIDIAN, ARIZONA

1.3

## Chains

The west half of the north boundary was surveyed in 1916 by Ross and Warner. The east half of the north boundary was surveyed in 1930 by Hiester and Hunter. The east boundary was surveyed in 1926 by Sawyer and Hunter. The south boundary was surveyed in 1958 by Crain. The west boundary was surveyed by Ross and Warner in 1916.

The following notes are those of the survey of the subdivisional lines of Township 15 North, Range 11 West, and the dependent resurvey of the east bdy. of sec. 36, Township 15 North, Range 12 West, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions, dated November 4, 1960.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, all corners were monumented with standard iron posts, 30 inches long, 2½ inches in diameter, flanged at the bases and with brass caps riveted to the tops. Original corner monuments were deposited alongside the new monuments, unless described otherwise.

The geographic position of the southeast corner of the township is: Latitude, 34°35'25" North, and Longitude, 113°21'16" West. The magnetic declination was found to be 15°15' East.

Dependent Resurvey of the East Boundary of Sec. 36,  
Township 15 North, Range 12 West, G. & S. R. Meridian, Arizona

Reestablishment of the Survey  
Executed in 1916 by Warner and Ross

From the cor. of Ts. 14 and 15 N., R. 12 W., monumented by an iron post, 3 inches in diam., set, mkd. and witnessed as described in the official record.

North, along the east bdy. of sec. 36.

Over broken mountainous land, through scattered undergrowth.

- 2.61 The witness closing cor. of Ts. 14 and 15 N., R. 11 W., monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record of the survey of 1958.
- 2.82 True point for the closing cor. of Ts. 14 and 15 N., R. 11 W.  
Descend over broken NE. slope.
- 33.50 Wash, drains NW.
- 35.00 Spur, slopes NW.
- 40.23 Point for the ¼ sec. cor. of sec. 36, T. 15 N., R. 12 W. at proportionate dist., there is no remaining evidence of the original cor. The cor. point falls in the bottom of Kaiser Canyon at an unsafe location and was not remonumented.
- 40.50 Small stream of good water, course SW.
- 41.93 Point selected for the witness ¼ sec. cor. of sec. 36, T. 15 N., R. 12 W.

## Chains

Set the iron post, on solid rock, mound with stones to top, cap mkd.

T15 N  
R12W R11W  
1/4  
S 36  
W C  
1962

- 42.80 Asc. over steep slope and ledges facing SE.
- 60.64 Top of ledges, ascend over S. slope.
- 79.60 Begin descent over steep rocky N. slope.
- 80.46 The cor. of secs. 25 and 36, T. 15 N., R. 12 W., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.
- Land, mountainous.  
Soil, rocky.  
Timber, none; undergrowth, palo verde, cactus, greasewood and salt cedar.

SURVEY OF THE SUBDIVISIONAL LINES  
TOWNSHIP 15 NORTH, RANGE 11 WEST, ARIZONA

From the corner of secs. 1, 2, 35 and 36 on the S. bdy. of the township, an iron post, 2½ ins. diam., set, marked and witnessed as described in the official record.

N. 0°01' W., bet. secs. 35 and 36.

Ascend over gentle S. slope, through heavy desert undergrowth and scattered cedar and palo verde.

- 22.00 Wash, 30 lks. wide, 1 ft. deep, drains SE.; asc. steep S. slope.

- 40.00 Point for the ¼ sec. cor. of secs. 35 and 36.

Set the iron post, 6 ins. in the ground and in a mound of stone, 3½ ft. base to top, with cap mkd.

T15N R11W  
1/4  
S 35 | S 36  
1962

- 43.40 Spur, slopes S. 25° W.; asc. over rocky SW. slope.
- 50.80 Spur, projects SW.
- 57.30 Draw, near head, drains S. 20° W.
- 73.80 Ridge, bears S. 85° E., and N. 40° W.; desc. NE. slope.
- 80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set the iron post, 6 ins. in the ground, mound with stones to top, cap mkd.

## Chains

T15N R11W  
 S 26 | S 25  
 S 35 | S 36  
 1962

Land, broken and mountainous.  
 Soil, rocky clay loam.  
 Timber, scattered Juniper and palo verde; undergrowth, greasewood,  
 cactus, catclaw and grass.

From the cor. of secs. 25, 30, 31 and 36, on the east bdy. of the township, an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.

N. 89°57' W., bet. secs. 25 and 36.

Desc. rocky W. slope, through scattered timber and undergrowth.

- .60 Small ravine, drains S.
- 3.20 Spur, slopes S.
- 10.10 Wash, 15 lks. wide, 1 ft. deep, drains SE.
- 17.80 Spur, slopes S. 20° E.
- 31.10 Wash, 50 lks. wide, 3 ft. deep, drains SE.
- 36.70 Spur, slopes N.; desc. NW. slope.
- 39.99 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 36.
- Set the iron post, 4 ins. in the ground, mound with stone to top, cap mkd.

T15N R11W  
 $\frac{1}{4}$   $\frac{S 25}{S 36}$   
 1962

- 40.10 Same wash as one at 31.10, drains irregularly E.
- 43.40 Same wash, thence along S. side.
- 59.10 Same wash, thence along N. side.
- 70.40 Same wash, drains S. 50° E., circling to NE.; asc. NE. slope.
- 79.98 The cor. of secs. 25, 26, 35 and 36.

Land, rough and mountainous.  
 Soil, rocky.  
 Timber, scattered juniper and palo verde; undergrowth, catclaw,  
 greasewood, and grass.

N. 0°01' W., bet. secs. 25 and 26.

Over broken mountainous land, through scattered undergrowth,  
 desc. NE. slope.

- 1.20 Small ravine, drains SE.
- 4.00 Small spur, slopes SE.
- 10.30 Small wash, drains SE.

| Chains |   |
|--------|---|
| 13.00  | Spur, slopes SE.  |
| 19.80  | Small wash, drains SE.  |
| 35.50  | Ridge, bears E. and W.; desc. steep N. slope.   |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.   |
|        | Set the iron post, 8 ins. in the ground, mound with stone to top, cap mkd.  |
|        | T15N R11W<br>$\frac{1}{4}$<br>S 26   S 25<br>1962   |
|        | Desc. over steep N. slope.  |
| 52.00  | Wash, 30 lks. wide, 3 ft. deep, drains irregularly E.   |
| 61.60  | Spur, slopes SE.  |
| 67.00  | Ravine, drains E.   |
| 76.90  | Wash, 180 lks. wide, 1 ft. deep, drains irregularly SE., jeep road in bottom of wash; asc. SW. slope.   |
| 80.00  | Point for the cor. of secs. 23, 24, 25 and 26.  |
|        | Set the iron post, 6 ins. in the ground, mound with stone to top, cap mkd.  |
|        | T15N R11W<br>S 23   S 24<br>S 26   S 25<br>1962   |
|        | Land, mountainous.<br>Soil, rocky clay loam.<br>Timber, scattered palo verde; undergrowth, cactus, catclaw and grass.   |
|        | From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the township, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record. |
|        | N. 89°52' W., bet. secs. 24 and 25.   |
|        | Over rocky mountainous land; desc. W. slope through scattered undergrowth.  |
| .80    | Small wash, drains S.   |
| 2.60   | Wash, 20 lks. wide, 1 ft. deep, drains SE.  |
| 15.10  | Spur, slopes S.; desc. steep rocky W. slope.  |
| 23.70  | Wash, 10 lks. wide, 1 ft. deep, drains S. approx. 2 chains, thence SE.  |
| 29.50  | Wash, 40 lks. wide, 1 ft. deep, drains irregularly SE.; asc. steep broken NE. slope.  |
| 40.03  | Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.   |

## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

5.

## Chains

Set the iron post, 8 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

$\frac{1}{2}$   $\frac{S\ 24}{S\ 25}$

1962

- 41.40 Head of small draw, drains NE.
- 50.90 Ridge, bears NW. and SE.
- 54.80 Small wash, drains S.
- 58.60 High rocky spur, slopes S.; desc. steep W. slope.
- 64.90 Wash, 10 lks. wide, 1 ft. deep, drains SW.
- 80.06 The cor. of secs. 23, 24, 25 and 26.
- Land, broken and mountainous.  
Soil, rocky clay loam.  
Timber, none; undergrowth, scattered cactus, catclaw, palo verde and grass.

N. 0°01' W., bet. secs. 23 and 24.

Over mountainous land, through scattered undergrowth; asc. along rolling W. slope.

- 10.30 Small wash, drains S. 75° W., approx. 1.00 chain to main wash which drains S. circling to SE.
- 18.80 Small wash, drains S. 75° W.
- 35.20 Wash, 10 lks. wide, 1 ft. deep, drains SW.; asc. rocky S. slope.
- 40.00 Point for the  $\frac{1}{2}$  sec. cor. of secs. 23 and 24.
- Set the iron post, 6 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

$\frac{1}{2}$   $\frac{S\ 23}{S\ 24}$

1962

- 47.00 Small draw, drains W. from NE.
- 53.70 Rocky spur, slopes S. 70° W.; desc. over steep rolling N. slope.
- 60.20 Finger spur, slopes W.
- 72.50 Small wash, drains W.
- 80.00 Point for the cor. of secs. 13, 14, 23 and 24.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

$\frac{S\ 14}{S\ 23}$  |  $\frac{S\ 13}{S\ 24}$

1962

## Chains

Land, mountainous.  
Soil, rocky, 3rd rate.  
Timber, none; undergrowth; cactus, catclaw, palo verde and grass.

From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township, an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.

West, bet. secs. 13 and 24.

Over mountainous land, through scattered undergrowth; desc. steep W. slope.

- 14.30 Small wash, drains S. 25° W.  
16.30 Small wash, drains S. 15° W.  
28.80 Small wash, running water, course SE.  
36.80 Rocky ravine, drains S. 20° E.; asc. gentle rocky SE. slope.  
40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 24.  
Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

$\frac{1}{4}$   $\frac{S\ 13}{S\ 24}$

1962

- 40.70 Wash, 10 lks. wide, 2 ft. deep, drains SE.  
51.90 Rocky spur, slopes irregularly S.  
55.30 Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W., circling to SE.  
65.00 Spur, slopes S. 70° W.; desc. steep NW. slope.  
80.01 The cor. of secs. 13, 14, 23 and 24.

Land, rolling mountainous.  
Soil, rocky, 3rd rate.  
Timber, none; undergrowth, cactus, catclaw, grass and palo verde.

N. 0°01' W., bet. secs. 13 and 14.

Over rolling mountainous land, through scattered undergrowth.

- 5.20 Draw, drains W.  
13.00 Small spur, slopes W.  
26.80 Wash, 20 lks. wide, 1 ft. deep, drains SW.; asc. rocky SE. slope.  
40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 14.  
Set the iron post 3 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

$\frac{1}{4}$   $\frac{S\ 14}{S\ 13}$

1962



| Chains |  |        |      |      |      |
|--------|--|--------|------|------|------|
| 42.00  | <p>Asc. SE. slope</p> <p>Saddle on rocky spur sloping SW., asc. steep rocky SW. slope.</p> <p>High rocky spur, slopes W.; cont. asc. over rocky SW. slope.</p> <p>Top of high rocky hill sloping W.; desc. steep N. slope.</p> <p>Point for the cor. of secs. 11, 12, 13 and 14.</p>           |        |      |      |      |
| 57.20  | <p>Set the iron post, 14 ins. in the ground, mound with stones to top, cap mkd.</p>  |        |      |      |      |
| 77.90  | <p>T15N R11W</p> <table border="1" style="margin: auto;"> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> </table> <p>1962</p>   | S 11   | S 12 | S 14 | S 13 |
| S 11   | S 12   |        |      |      |      |
| S 14   | S 13   |        |      |      |      |
| 80.00  | <p>Land, high broken mountains.<br/>Soil, rocky, 3rd rate.<br/>Timber, none; undergrowth, scattered cactus, palo verde, catclaw and grass.</p>   |        |      |      |      |
| 28.20  | <p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the township, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.</p>  |        |      |      |      |
| 38.20  | <p>West, bet. secs. 12 and 13.</p> <p>Over mountainous land, by triangulation, topography estimated; desc. over steep ledgy W. slope through heavy undergrowth.</p>  |        |      |      |      |
| 40.11  | <p>Wash, 30 lks. wide, 2 ft. deep, drains S. circling SW. from NE.; asc. E. slope.</p> <p>Low rocky spur, slopes S. 20° E.; desc. gentle SW. slope.</p> <p>Point for the ¼ sec. cor. of secs. 12 and 13.</p> <p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p> |        |      |      |      |
| 40.30  | <p>T15N R11W</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S 12</td> <td></td> </tr> <tr> <td>S 13</td> <td></td> </tr> </table> <p>1962</p>   | ¼ S 12 |      | S 13 |      |
| ¼ S 12 |  |        |      |      |      |
| S 13   |  |        |      |      |      |
| 49.90  | <p>Thence by chaining measurement.</p>   |        |      |      |      |
| 57.90  | <p>Small ravine, near head, drains SE.; asc. steep E. slope.</p>   |        |      |      |      |
| 70.80  | <p>Rocky spur, slopes SE.; desc. along S. slope.</p>   |        |      |      |      |
| 79.30  | <p>Rocky ridge, slopes S. from NE.; desc. steep W. slope.</p>  |        |      |      |      |
| 80.22  | <p>Draw, near head, drains NW.; asc. steep NE. slope.</p>  |        |      |      |      |
| 79.30  | <p>Slope changes to N.</p>   |        |      |      |      |
| 80.22  | <p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, high rolling and broken mountains.<br/>Soil, rocky clay loam.<br/>Timber, none; undergrowth, scattered brush, catclaw, cactus and grass.</p>  |        |      |      |      |

## Chains

N. 0°01' W., bet. secs. 11 and 12.

Over high rolling mountainous land, desc. over steep N. slope. through scattered undergrowth.

7.30 Small rocky spur, slopes W. from S.

14.90 Wash, 20 lks. wide, 1 ft. deep, drains irregularly W. from NE.; asc. rocky S. slope.

26.70 Top of asc., bears E. and W.; desc. gentle NW. slope through heavy brush.

37.10 Small ravine, drains W.; asc. SW. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 12.

Set the iron post, 6 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

$\frac{1}{4}$   
S 11 | S 12  
1962

41.90 Top of asc.; desc. N. slope.

48.80 Wash, 10 lks. wide, 1 ft. deep, drains N. 70° W.

50.60 Small spur, slopes W.; cont. asc. over general S. slope.

58.20 Wash, 20 lks. wide, 6 ins. deep, drains irregularly SW. from irregularly N.

73.20 Same wash; asc. S. slope.

76.30 Barbed wire fence, bears E. and W.

80.00 Point for the cor. of secs. 1, 2, 11 and 12.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

S 2 | S 1  
S 11 | S 12  
1962

Land, rolling mountains.

Soil, rocky clay loam.

Timber, none; undergrowth, cactus, grass, brush, scattered palo verde and catclaw.

From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the township, an iron post, 2 ins. diam., set, mkd., and witnessed as described in the official record.

N. 89°51' W., bet. secs. 1 and 12.

Over gentle rolling mountainous land, through scattered to heavy brush; desc. W. slope.

6.70 Wash, 10 lks. wide, 1 ft. deep, drains S. circling to SE.; stock pond bears N. 2.00 chains dist.; asc. gentle E. slope.

| Chains |   |
|--------|---|
| 11.40  | Dirt road, bears S. and NW.   |
| 20.00  | Small spur, slopes SE.; desc. gentle W. slope.  |
| 27.70  | Wash, 15 lks. wide, 6 ins. deep, drains S. circling to SE.; cont. over gentle rolling land.   |
| 37.40  | Small wash, drains SE.  |
| 40.08  | Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.<br>Set the iron post 20 ins. in the ground and in a collar of stone, cap mkd.                                  |
|        | T15N R11W<br>$\frac{1}{4} \frac{S \ 1}{S \ 12}$<br>1962   |
|        | Asc. over gentle E. slope, through heavy brush.   |
| 53.20  | Ridge, bears N. 20° W., and S.; desc. over gentle rolling land.   |
| 59.70  | Head of small wash, drains SW.  |
| 76.30  | Head of draw, drains N. approx. 4.00 chains, thence W.  |
| 80.16  | The cor. of secs. 1, 2, 11 and 12.<br>Land, gently rolling.<br>Soil, rocky sandy clay loam.<br>Timber, none; undergrowth, grass, cactus and catclaw.                    |
|        | N. 0°01' W., bet. secs. 1 and 2.<br>Over gently rolling mountainous land.   |
| .20    | Small ridge, bears NW. and SE.; desc. gentle N. slope.  |
| 4.30   | Wash, 50 lks. wide, 1 ft. deep, drains NW. from E.; asc. S. slope through scattered brush.  |
| 23.70  | Slope changes to SW.; asc.  |
| 33.90  | Top of asc.; cont. over gently rolling land.  |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.<br>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.                                  |
|        | T15N R11W<br>$\frac{1}{4} \frac{S \ 2}{S \ 1}$<br>1962  |
| 62.50  | Small rocky spur, slopes SE.; cont. over gently rolling, rocky land through heavy brush.  |
| 78.28  | Intersect the N. bdy. of the township.<br>Point for the closing corner of secs. 1 and 2.<br>Set the iron post, 18 ins. in the ground and in a collar of stone, cap mkd. |

Chains

T16N R11W  
S 35  
 S 2 | S.1  
 T15N R11W  
 C C  
 1962

Build a mound of stone, 3 ft. base, 2 ft. high, S. of corner.

The cor. of secs. 1, 2, 35 and 36 bears East, 5.19 chs. dist., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 35 and 36, T. 16 N., R. 11 W., only; marks altered to

T16N R11W  
S 35 | S 36  
 S 1  
 T15N  
 62  
 1930

Land, gently rolling with rocky outcrops.  
 Soil, clay loam and rocky.  
 Timber, none; undergrowth, cactus, catclaw and brush.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the township.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T16N R11W  
 $\frac{1}{4}$  S 1  
 T15N  
 1962

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 36 bears East 5.06 chs. dist., monumented by an iron post, 1 inch in diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  sec. cor. of sec. 36, T. 16 N., R. 11 W. only; marks altered to

$\frac{1}{4}$  S 36  
 62  
 1930

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township, an iron post, 2 $\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the official record.

N. 0°01' W., bet. secs. 34 and 35.

Over rolling, rocky mountainous land through cacti, palo verde and creosote brush; asc. along W. slope.

7.40 Bladed dirt road, bears SW. and S. 10° E.; asc. S. slope.

18.50 Spur, slopes S. 30° E., from West; desc. NE. slope.

31.30 Wash, 30 lks. wide, 2 ft. deep, drains E. approx. 9.00 chs., thence S.; asc. S. slope.

Subdivisional Lines, T. 15 N., R. 11 W., Arizona

| Chains |  |
|--------|--|
| 35.60  | Spur, slopes SW.; desc. along gentle W. slope.   |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.  |
|        | Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.   |
|        | <p style="text-align: center;">T15N R11W<br/> <math>\frac{1}{4}</math><br/> S 34   S 35<br/> 1962</p>  |
|        | Thence over rolling S. slope.  |
| 51.10  | Wash, 10 lks. wide, 1 ft. deep, drains S. 15° W.   |
| 65.50  | Spur, slopes SW.; desc. NW. slope.   |
| 75.10  | Small wash, drains SW.; asc. S. slope.   |
| 80.00  | Point for the cor. of secs. 26, 27, 34 and 35.   |
|        | Set the iron post, 10 ins. in the ground, mound with stones to top, cap mkd.   |
|        | <p style="text-align: center;">T15N R11W<br/> S 27   S26<br/> S 34   S 35<br/> 1962</p>  |
|        | <p>Land, rolling mountains.<br/> Soil, rocky, 3rd rate.<br/> Timber, none; undergrowth, scattered palo verde, creosote brush,<br/> cactus and grass.</p> |
|        | From the cor. of secs. 25, 26, 35 and 36.  |
|        | N. 89°57' W., bet. secs. 26 and 35.  |
|        | Over rocky mountainous land, through scattered palo verde and cactus; asc. NE. slope.  |
| 9.20   | Rocky spur, slopes SE., from N.; desc. rocky W. slope.   |
| 15.60  | Small wash drains S.   |
| 22.80  | Wash, 20 lks. wide, 1 ft. deep, drains SE. circling to S.; asc. E. slope.  |
| 29.10  | Small rocky spur, projects N.; asc. rolling E. slope.  |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.  |
|        | Set the iron post, 8 ins. in the ground, mound with stones to top, cap mkd.  |
|        | <p style="text-align: center;">T15N R11W<br/> <math>\frac{1}{4}</math> S 26<br/> S 35<br/> 1962</p>  |
| 48.40  | Spur, slopes SE.; desc. SW. slope.   |
| 71.10  | Spur, slopes S. 20° E.   |
| 75.70  | Small spur, slopes SW.; cont. to desc. along general S. slope.   |
| 79.99  | The cor. of secs. 26, 27, 34 and 35.   |

## Chains

Land, rolling mountains.  
Soil, rocky, 3rd rate.  
Timber, none; undergrowth, scattered palo verde, catclaw, grass  
and cactus.

N. 0°01' W., bet. secs. 26 and 27.

Over rolling mountainous land through scattered undergrowth;  
asc. steep S. slope.

2.00 Spur, slopes S. 30° W.; desc. NW. slope.

6.00 Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.

11.30 Spur, slopes West about 4.00 chs. dist., thence South.

25.00 Small wash, drains irregularly SW.; asc. SE. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 27.

Set the iron post, 10 ins. in the ground, mound with stones to top,  
cap mkd.

T15N R11W  
 $\frac{1}{4}$   
S 27 | S 26  
1962

Asc. steep rocky SE. slope.

54.30 Divide, bears NW., East and S. 15° W.; desc. over rolling land  
facing North, through scattered palo verde.

66.60 Draw, drains NE., circling to East.

71.10 Wash, 15 lks. wide, 1 ft. deep, drains E.; asc. S. slope.

75.50 Slope changes to E.

80.00 Point for the cor. of secs. 22, 23, 26 and 27.

Set the iron post 6 ins. in the ground, mound with stones to top,  
cap mkd.

T15N R11W  
S 22 | S 23  
S 27 | S 26  
1962

Land, broken and mountainous.  
Soil, rocky clay loam.  
Timber, scattered palo verde; undergrowth, scattered cactus,  
catclaw, grass and greasewood.

From the cor. of secs. 23, 24, 25 and 26.

N. 89°56' W., bet. secs. 23 and 26.

Over rolling, rocky mountainous land, through scattered palo verde,  
and undergrowth; desc. gentle W. slope.

2.80 Main wash, jeep road in bottom, 2.00 chs. wide, 1 ft. deep, drains  
irregularly SE.; asc. steep rolling E. slope.

18.90 Small draw, drains NE.

## Chains

- 33.30 Top of steep ascent, continue along gentle SE. slope.
- 38.60 Rocky spur, slopes S.; desc. W. slope.
- 39.99 Point for the  $\frac{1}{4}$  sec. cor. of secs. 23 and 26.
- Set the iron post, 6 ins. in the ground, mound with stones to top, cap mkd.
- T15N R11W  
 $\frac{1}{4}$   $\frac{S\ 23}{S\ 26}$   
1962
- 55.90 Wash, 10 lks. wide, 1 ft. deep, drains S.; asc. E. slope.
- 64.80 Top of ascent, bears NE. and SE.; desc. W. slope.
- 70.70 Wash, 15 lks. wide, 1 ft. deep, drains SW. about 4.00 chains, thence SE.
- 74.80 Draw, drains SE.; asc. rolling E. slope.
- 79.97 The cor. of secs. 22, 23, 26 and 27.
- Land, mountainous.  
Soil, rocky clay loam.  
Timber, scattered palo verde; undergrowth, cactus, grass, catclaw, and greasewood.
- 
- N. 0°01' W., bet. secs. 22 and 23.
- Over rocky mountainous land; asc. gentle SE. slope.
- 18.30 Saddle on ridge bearing NE. and SW.; desc. NW. slope.
- 28.50 Wash, 10 lks. wide, 1 ft. deep, drains NE.; asc. gentle SE. slope.
- 37.00 Low ridge, bears NE. and SW.; desc. gentle NW. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 22 and 23.
- Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
- T15N R11W  
 $\frac{1}{4}$   
S 22 | S 23  
1962
- 45.10 Wash, 20 lks. wide, 1 ft. deep, drains irregularly East; asc. steep S. slope.
- 52.30 Spur, slopes West; desc. NW. slope.
- 58.40 Wash, 10 lks. wide, 1 ft. deep, drains SW. from N.
- 61.20 Leave wash; asc. S. slope.
- 75.40 Road, bears S. 15° W. and irregularly N.
- 76.00 Begin desc. along NE. slope.
- 78.15 Same road, bears NW. circling to NE. and SE. circling to SW.

| Chains |   |        |      |      |      |
|--------|---|--------|------|------|------|
| 80.00  | <p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set the iron post, 14 ins. in the ground, mound with stones to top, cap mkd.</p> <div style="text-align: center;"> <p>T15N R11W</p> <table border="1" style="margin: auto;"> <tr> <td>S 15</td> <td>S 14</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> </table> <p>1962</p> </div> <p>Land, rolling.<br/>Soil, rocky clay loam.<br/>Timber, none; undergrowth, palo verde, cactus, catclaw, grass, and greasewood.</p> | S 15   | S 14 | S 22 | S 23 |
| S 15   | S 14  |        |      |      |      |
| S 22   | S 23  |        |      |      |      |
|        | <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°56' W., bet. secs. 14 and 23.</p> <p>By triangulation, topography as estimated; desc. steep NW. slope through undergrowth.</p>  |        |      |      |      |
| 8.00   | <p>Main wash, jeep road in bottom, 40 lks. wide, 2 ft. deep, drains S. 15° W., circling to S.; asc. steep rolling E. slope.</p>   |        |      |      |      |
| 39.99  | <p>Point for the ¼ sec. cor. of secs. 14 and 23.</p> <p>Set the iron post 10 ins. in the ground, mound with stone to top, cap mkd.</p> <div style="text-align: center;"> <p>T15N R11W</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S 14</td> <td></td> </tr> <tr> <td>S 23</td> <td></td> </tr> </table> <p>1962</p> </div> <p>End of triangulation.</p> <p>Ascend gentle E. slope.</p>  | ¼ S 14 |      | S 23 |      |
| ¼ S 14 |   |        |      |      |      |
| S 23   |   |        |      |      |      |
| 41.50  | <p>Ridge, bears N. and S.; desc. W. slope.</p>  |        |      |      |      |
| 48.50  | <p>Wash, 15 lks. wide, 2 ft. deep, drains S. circling to SE.; asc. E. slope.</p>  |        |      |      |      |
| 59.80  | <p>Rocky spur, slopes S. and SE.; desc. SW. slope.</p>  |        |      |      |      |
| 72.50  | <p>Wash, 40 lks. wide, 1 ft. deep, drains SE.; asc. NE. slope.</p>  |        |      |      |      |
| 79.97  | <p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, mountainous.<br/>Soil, rocky clay loam.<br/>Timber, none; undergrowth, palo verde, grass, catclaw, greasewood and cactus.</p>  |        |      |      |      |
|        | <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Desc. NE. slope through undergrowth.</p>   |        |      |      |      |
| .40    | <p>Small ravine near head, drains E.; asc. S. slope.</p>  |        |      |      |      |
| 3.20   | <p>Bladed road, bears NE. and SW.</p>   |        |      |      |      |
| 5.20   | <p>Small spur, slopes E.</p>  |        |      |      |      |



| Chains |   |
|--------|---|
| 21.30  | Same road, bears irregularly N. and S.; desc. N. slope.   |
| 23.20  | Wash, 50 lks. wide, 1 ft. deep, drains S. 30° E.; asc. gentle SW. slope.  |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.   |
|        | Set the iron post, 10 ins. in the ground, mound with stones to top, cap mkd.  |
|        | T15N R11W<br>$\frac{1}{4}$<br>S 15   S 14<br>1962.  |
|        | A windmill bears S. 19°41' W., 11.20 chains dist.   |
| 51.90  | Small wash, drains SW., circling to S.  |
| 69.90  | Slope changes to steep S.; ascend.  |
| 78.80  | Ridge, bears NW. and SE.; desc. over N. slope through heavy brush.  |
| 80.00  | Point for the cor. of secs. 10, 11, 14 and 15.  |
|        | Set the iron post, 10 ins. in the ground, mound with stones to top, cap mkd.  |
|        | T15N R11W<br>S 10   S 11<br>S 15   S 14<br>1962   |
|        | Land, mountainous.<br>Soil, rocky clay loam.<br>Timber, none; undergrowth, brush, catclaw, cactus, grass and greasewood.      |
|        | From the cor. of secs. 11, 12, 13 and 14.   |
|        | N. 89°56' W., bet. secs. 11 and 14.   |
|        | By triangulation, topography as estimated; desc. along N. slope through heavy brush.  |
| 5.00   | Slope changes to steep W.   |
| 31.90  | Wash, 50 lks. wide, 1 ft. deep, drains S. 15° W. about 2.00 chains to junction.   |
| 33.90  | End of spur sloping from N.   |
| 35.80  | Main wash, jeep road in bottom, 50 lks. wide, 1 ft. deep, drains irregularly SE.; end of triangulation; asc. gentle E. slope. |
| 39.95  | Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.   |
|        | Set the iron post, 22 ins. in the ground, cap mkd.  |
|        | T15N R11W<br>$\frac{1}{4}$ S 11<br>S 14<br>1962   |
|        | Raise a mound of stone North of the corner.   |

| Chains |  |
|--------|--|
| 42.20  | Small wash, drains NE.; asc. over steep rolling land facing NE.  |
| 50.20  | Small spur, slopes NE.   |
| 59.00  | Draw, drains NE.   |
| 72.60  | Top of ascent, bears NW. and SE.; desc. gentle W. slope.   |
| 74.00  | Small wash, drains S. from NW.; asc. NE. slope.  |
| 79.90  | The cor. of secs. 10, 11, 14 and 15.<br><br>Land, mountainous.<br>Soil, rocky clay loam.<br>Timber, none; undergrowth, scattered scrub oak, cactus, grass, catclaw and greasewood.   |
|        | N. 0°01' W., bet. secs. 10 and 11.<br><br>Descend over rolling NE. slope through brush.  |
| 7.00   | Low finger spur, slopes SE.  |
| 16.50  | Wash, 10 lks. wide, 1 ft. deep, drains SE.; asc. rocky SW. slope.  |
| 24.30  | Spur, slopes SE.; desc. NE. slope.   |
| 35.30  | Small wash, drains E.; asc. S. slope.  |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.<br><br>Set an iron post, 10 ins. in the ground, mound with stones to top, cap mkd.<br><br>T15N R11W<br>$\frac{1}{4}$<br>S 10   S 11<br>1962<br><br>The cor. is located on small spur sloping SE.<br><br>Descend along general East slope through heavy brush.                    |
| 62.50  | Wash, jeep road in bottom, 30 lks. wide, 1 ft. deep, drains SE.; asc. over gentle rolling land, S. drainage and exposure.  |
| 73.70  | Wash, 30 lks. wide, 1 ft. deep, drains S. 30° E.; asc. gentle SW. slope.   |
| 80.00  | Point for the sec. cor. of secs. 2, 3, 10 and 11.<br><br>Set the iron post, 8 ins. in the ground, mound with stones to top, cap mkd.<br><br>T15N R11W<br>S 3   S 2<br>S 10   S 11<br>1962<br><br>Land, mountainous.<br>Soil, rocky sandy clay loam.<br>Timber, none; undergrowth, brush, grass, cactus, catclaw, greasewood and scrub oak. |

| Chains |   |
|--------|---|
|        | From the cor. of secs. 1, 2, 11 and 12.<br>N. 89°57' W., bet. secs. 2 and 11.<br>Over rolling land through undergrowth.   |
| 7.90   | Barbed wire fence, bears N. 70° W., and S. 70° E.   |
| 11.80  | Ridge, bears N. and S. circling to SW., desc. W. slope.   |
| 23.70  | Wash, 30 lks. wide, 2 ft. deep, drains SW. circling to SE.; asc. E. slope.  |
| 29.80  | Rocky spur slopes S.; desc. W. slope.   |
| 38.50  | Wash, 10 lks. wide, 1 ft. deep, drains SE. circling to S.; asc. E. slope.   |
| 39.94  | Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.<br>Set the iron post, 14 ins. in the ground, mound with stones to top, cap mkd.<br><br>T15N R11W<br>$\frac{1}{4} \frac{S \ 2}{S \ 11}$<br>1962 |
| 57.60  | Spur, slopes S. from N. 70° W.  |
| 64.30  | Spur, slopes S.; desc. SW. slope.   |
| 79.88  | The cor. of secs. 2, 3, 10 and 11.<br><br>Land, mountainous.<br>Soil, rocky clay loam.<br>Timber, none; undergrowth, brush, grass, cactus and catclaw.  |
|        | N. 0°01' W., bet. secs. 2 and 3.<br>Ascend over steep rocky SW. slope through undergrowth.  |
| 7.10   | Top of steep ascent, continue over gentle S. slope.   |
| 29.00  | Low ridge, bears irregularly East and West; desc. gentle NW. slope.   |
| 39.00  | Barbed wire fence, bears E. and W.  |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.<br>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.<br><br>T15N R11W<br>$\frac{1}{4}$<br>S 3   S 2<br>1962           |
| 46.60  | Wash, 10 lks. wide, 1 ft. deep, drains NW.; asc. S. slope.  |
| 56.80  | Spur, slopes NW.; desc. N. slope.   |
| 64.10  | Wash, 20 lks. wide, 1 ft. deep, drains W.   |
| 72.80  | Spur, slopes W.   |

BOOK 4881

## Chains

77.90 Wash, 15 lks. wide, 1 ft. deep, drains W.; asc. gentle S. slope.

78.40 Intersect the N. bdy. of the township.

Point for the closing cor. of secs. 2 and 3.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T16N  
S 34  
 S 3 | S 2  
 T15N R11W  
 C C  
 1962

The cor. of secs. 2, 3, 34 and 35, bears East 5.19 chs. dist., monumented by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 34 and 35, T. 16 N., R. 11 W., only, marks altered to

T16N R11W  
S 34 | S 35  
 S 2  
 T15N  
 1962  
 1930

Land, rolling and mountainous.

Soil, sandy clay loam and rocky.

Timber, none; undergrowth, cactus, catclaw and grass.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 2 is at mid point between closing corners and on the N. bdy. of the township.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T16N R11W  
 $\frac{1}{4}$  S 2  
 T15N  
 1962

The  $\frac{1}{4}$  sec. cor. of secs. 2 and 35 bears East 5.19 chs. dist., monumented by an iron post, 1 inch in diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  cor. of sec. 35, T. 16 N., R. 11 W., only, marks altered to

$\frac{1}{4}$  S 35  
 1962  
 1930

Beginning at the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township, monumented by an iron post  $2\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the official record.

N.  $0^{\circ}02'$  W., bet. secs. 33 and 34.

Ascend over rocky SW. slope.

6.90 Slope changes to rocky NW.; descend.

14.60 Rocky ravine, drains SW.; asc. steep rocky S. slope.

## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

19.

| Chains |  |
|--------|--|
| 25.40  | Rocky ridge, bears E. and W.; desc. steep rocky N. slope.  |
| 33.20  | Wash, 20 lks. wide, 1 ft. deep, drains W. circling to SE.; asc. over ledgy S. slope.   |
| 39.00  | Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 33 and 34.<br>Set an iron post, 6 ins. in the ground, mound with stones to top, cap mkd. |
|        | T15N R11W<br>$\frac{1}{4}$<br>W C<br>S 33 $\uparrow$ S 34<br>1962  |
| 40.00  | True point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34 falls on SE. face of ledge where cor. cannot be perpetuated.                               |
| 69.10  | Fence, barbed wire, bears N. 16° W., and S. 16° E.   |
| 76.50  | Small rocky wash, drains S. 15° E.   |
| 80.00  | Point for the cor. of secs. 27, 28, 33 and 34.<br>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.                             |
|        | T15N R11W<br>S 28   S 27<br>S 33   S 34<br>1962  |
|        | Land, mountainous.<br>Soil, rocky clay loam.<br>Timber, none; undergrowth, scattered palo verde, yucca, cactus, grass and greasewood.                    |
|        | From the cor. of secs. 26, 27, 34 and 35.  |
|        | N. 89°58' W., bet. secs. 27 and 34.  |
|        | By triangulation, topography as estimated.   |
|        | Ascend over E. slope through undergrowth.  |
| 8.00   | Ridge, bears S. from NE.; desc. over steep W. slope.   |
| 18.00  | Main wash, 50 lks. wide, 1 ft. deep, drains irregularly S. 15° E.; asc. over steep E. slope.   |
| 35.40  | Bladed dirt road, along ridge top bearing N. 10° W., and irregularly S.; desc. over W. slope. End of triangulation.                                      |
| 40.03  | Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.<br>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.                  |
|        | T15N R11 W<br>$\frac{1}{4}$ S 27<br>S 34<br>1962   |
| 44.90  | Small ravine, drains SW.   |

## Chains

- 52.30 Small ravine, drains SW. circling to S.
- 54.60 Wash, 15 lks. wide, 1 ft. deep, drains SE. circling to S.; asc. rocky NE. slope.
- 70.80 Rocky spur, slopes NW.; desc. rocky W. slope.
- 80.06 The cor. of secs. 27, 28, 33 and 34.
- Land, mountainous.  
Soil, rocky clay loam.  
Timber, none; undergrowth, brush, ocotillo, cactus, palo verde, yucca, and grass.
- 
- N. 0°02' W., bet. secs. 27 and 28.  
Ascend over rocky SW. slope.
- 3.00 Top of small rocky outcrop; thence over gentle rolling land, S. drainage and exposure.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 27 and 28.
- Set the iron post, 10 ins. in the ground, mound with stones to top, cap mkd.
- T15N R11W  
 $\frac{1}{4}$   
S 28 | S 27  
1962
- 43.70 Bladed dirt road, bears irregularly E. and W.; asc. gentle S. slope.
- 45.80 Low spur, slopes W.
- 50.20 Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.
- 70.20 Fence, barbed wire, bears N. 70° E., and S. 70° W.
- 70.60 Spur, slopes SW.; desc. N. slope.
- 75.50 Small wash, drains SW.; asc. S. slope.
- 78.60 Spur, slopes W.; desc. N. slope.
- 80.00 Point for the cor. of secs. 21, 22, 27 and 28.
- Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
- T15N R11W  
S 21 | S 22  
S 28 | S 27  
1962
- Land, rolling mountainous.  
Soil, rocky clay loam.  
Timber, widely scattered juniper and palo verde; undergrowth, scattered cactus, catclaw, grass and greasewood.
- 
- From the cor. of secs. 22, 23, 26 and 27.
- N. 89°59' W., bet. secs. 22 and 27.
- Asc. E. slope through undergrowth.

## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

21.

| Chains |  |
|--------|--|
| 2.60   | Spur, slopes S.; desc. W. slope.   |
| 6.90   | Wash, 20 lks. wide, 1 ft. deep, drains S. circling to E.; asc. E. slope.   |
| 15.70  | Ridge, bears N. and S.; thence over rolling land.  |
| 17.90  | Bladed dirt road, bears N. and S. circling to W.   |
| 19.00  | Same road, bears irregularly E. and W.   |
| 26.30  | Wash, 10 lks. wide, 1 ft. deep, drains irregularly S.  |
| 30.21  | Same road, bears irregularly E. and W.   |
| 31.60  | Low spur, slopes S.  |
| 35.60  | Same road, bears irregularly E. and W.   |
| 37.60  | Small draw, near head, drains S. 20° E.  |
| 38.00  | Same road, bears irregularly S. and E.; asc. steep E. slope.   |
| 40.05  | Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.  |
|        | Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.  |
|        | T15N R11W<br>$\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$<br>1962   |
| 46.80  | Narrow ledgy spur, slopes sharply S.; desc. ledgy SW. slope.   |
| 57.20  | Draw, drains S. circling to SE.  |
| 65.00  | High rocky spur, slopes sharply S.; desc. over steep ledgy W. slope.   |
| 68.90  | Fence, barbed wire, bears NE. and SW., desc. over NW. slope.   |
| 80.10  | The cor. of secs. 21, 22, 27 and 28.   |
|        | Land, broken mountains.<br>Soil, rocky.<br>Timber, none; undergrowth, scattered cactus, grass, brush, ocotillo and greasewood. |
|        | N. 0°02' W., bet. secs. 21 and 22.   |
|        | Descend over NW. slope through undergrowth and scattered juniper.  |
| 20.80  | Small wash, drains SW.   |
| 24.80  | Spur, slopes W.  |
| 29.90  | Wash, 15 lks. wide, 1 ft. deep, drains NW.   |
| 35.20  | Main wash, 1.00 chain wide, 1 ft. deep, drains SW.; asc. steep S. slope. Jeep road in bottom of wash.                          |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.  |
|        | Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.   |

| Chains |  |
|--------|--|
|        | T15N R11W<br>$\frac{1}{2}$<br>S 21   S 22<br>1962  |
| 42.90  | Rocky spur, slopes W., desc. over NW. slope.   |
| 46.40  | Wash, 60 lks. wide, 1 ft. deep, drains S. 30° W.; asc. SE. slope.  |
| 71.00  | Rocky spur, slopes East; desc. over NE. slope.   |
| 79.90  | Point selected for the witness cor. of secs. 15, 16, 21 and 22.<br><br>Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.   |
|        | T15N R11W<br>S 16   S 15<br>S 21   S 22<br>W C<br>1962   |
| 80.00  | Raise a mound of stone West of the corner.<br><br>True point for the cor. of secs. 15, 16, 21 and 22 falls in small wash draining SE.<br><br>Land, mountainous.<br>Soil, rocky sandy clay loam.<br>Timber, scattered juniper on extreme S. portion; undergrowth, cactus, yucca, grass, brush and greasewood. |
|        | From the cor. of secs. 14, 15, 22 and 23.<br><br>N. 89°58' W., bet. secs. 15 and 22.<br><br>Asc. along NE. slope through brush.  |
| 1.40   | Bladed dirt road, bears irregularly N. and S.; asc. E. slope.  |
| 7.00   | Ridge, bears N. and S. circling to SW.   |
| 7.30   | Fence, barbed wire, bears N. 10° W. and S. 10° E.  |
| 19.00  | Spur, slopes NW.   |
| 24.10  | Wash, 20 lks. wide, 2 ft. deep, drains S. circling to W.   |
| 30.60  | Spur, slopes S.  |
| 36.60  | Draw, drains S.  |
| 38.10  | High rocky spur, slopes NE.; desc. rocky W. slope.   |
| 40.03  | Point for the $\frac{1}{2}$ sec. cor. of secs. 15 and 22.<br><br>Set the iron post, 10 ins. in the ground, mound with stones to top, cap mkd.  |
|        | T15N R11W<br>$\frac{1}{2}$ S 15<br>S 22<br>1962  |
| 49.60  | Wash, 20 lks. wide, 1 ft. deep, drains SW.   |



Chains

53.10 Wash, 30 lks. wide, 1 ft. deep, drains S. circling to SE.

59.50 Ridge, bears N. and S.

66.10 Small wash, drains SW.

69.70 Spur, slopes SW.

74.00 Wash, jeep road in bottom, 30 lks. wide, 1 ft. deep, drains irregularly SW.

78.90 Small ravine, drains S. 15° E.

80.07 The true point for the cor. of secs. 15, 16, 21 and 22.

Land, rolling mountains.

Soil, rocky clay loam.

Timber, none; undergrowth, cactus, brush, greasewood, grass and catclaw.

N. 0°02' W., bet. secs. 15 and 16.

Ascend over rocky SW. slope.

7.30 Spur, slopes SE.

15.90 Wash, 30 lks. wide, 1 ft. deep, drains SE.

32.90 Draw, drains SW. about 1.00 chains, thence S.

38.00 Rocky spur, slopes S. 65° E.; desc. over gentle NE. slope.

40.00 Point for the ¼ sec. cor. of secs. 15 and 16.

Set the iron post, 10 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

¼

S 16 | S 15

1962

A windmill bears S. 14°<sup>38'</sup>/E., 29.98 chains dist.

41.50 Small draw, near head, drains SE.

50.20 Spur, slopes S. 60° E.

67.00 Wash, 10 lks. wide, 2 ft. deep, drains SE.

78.30 Small spur, slopes SW.; desc. N. slope.

80.00 Point for the cor. of secs. 9, 10, 15 and 16.

Set the iron post, 15 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

S 9 | S 10

S 16 | S 15

1962

Land, mountainous.

Soil, rocky clay loam.

Timber, none; undergrowth, greasewood, catclaw, ocotillo, and grass.

24

BOOK 451

Subdivisional Lines, T. 15 N., R. 11 W., Arizona

| Chains |  |
|--------|--|
|        | From the cor. of secs. 10, 11, 14 and 15.  |
|        | N. 89°59' W., bet. secs. 10 and 15.  |
|        | Asc. over E. slope through undergrowth.  |
| 1.40   | Ridge, bears SE. and NW.; desc. steep SW. slope.   |
| 17.05  | Bladed dirt road, bears N. 30° W., and S. 30° E., asc. gentle SE. slope.   |
| 18.10  | Top of ascent, bears N. and S.; desc. W. slope.  |
| 18.70  | Fence, barbed wire, bears N. and S.  |
| 22.10  | Small wash, drains S. 70° W. from N. 30° E.  |
| 33.20  | Wash, 40 lks. wide, 2 ft. deep, drains S. circling to SW.  |
| 35.40  | Top of low knoll.  |
| 39.00  | Small wash, drains S. 15° W.; asc. along rolling S. slope.   |
| 40.00  | Point for the ¼ sec. cor. of secs. 10 and 15.  |
|        | Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.  |
|        | T15N R11W<br>¼ $\frac{S\ 10}{S\ 15}$<br>1962   |
| 42.50  | Spur, slopes SW.   |
| 47.70  | Small wash, drains SW.   |
| 48.70  | End of small spur sloping from N.  |
| 49.90  | Main wash, 50 lks. wide, 1 ft. deep, drains S. circling to SW.   |
| 64.00  | Spur, slopes S.  |
| 74.80  | Wash, 20 lks. wide, 2 ft. deep, drains S. 20° E. circling to S.; asc. along N. slope.  |
| 79.99  | The cor. of secs. 9, 10, 15 and 16.  |
|        | Land, rolling mountains.<br>Soil, clay loam and rocky.<br>Undergrowth, mesquite, catclaw, brush, cactus, grass and greasewood. |
|        | N. 0°02' W., bet. secs. 9 and 10.  |
|        | Descend over N. slope through undergrowth.   |
| 4.40   | Small wash, drains SE.   |
| 12.00  | Head of wash, drains S. 20° E.   |
| 31.80  | Spur, slopes S. 10° E., from East.   |
| 34.50  | Small draw, drains W. circling to S.; asc. SW. slope.  |

## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

25.

## Chains

- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 9 and 10.  
Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
- T15N R11W  
 $\frac{1}{4}$   
S 9 | S 10  
1962
- 41.10 Top of small spur, slopes SW.
- 43.90 Small wash, drains S. 75° W. for 3.00 chains, thence S.
- 59.60 High spur, slopes W.; desc. NW. slope.
- 72.30 Head of wash, drains S. 20° W.; asc. steep S. slope.
- 80.00 Point for the cor. of secs. 3, 4, 9 and 10.  
Set an iron post 16 ins. in the ground, mound with stones to top, cap mkd.
- T15N R11W  
S 4 | S 3  
S 9 | S 10  
1962
- Land, mountainous.  
Soil, rocky clay loam.  
Undergrowth, cactus, grass, catclaw, greasewood and palo verde.  
Timber, none.
- 
- From the cor. of secs. 2, 3, 10 and 11.  
N. 89°58' W., bet. secs. 3 and 10.  
Desc. W. slope through undergrowth.
- 1.90 Small wash, drains S. to SE.; desc. SW. slope.
- 11.50 Wash, 20 lks. wide, 1 ft. deep, drains S. 20° E.
- 16.50 Bladed dirt road, bears S. 12° E. and N. 12° W.; asc. NE. slope.
- 32.10 Ridge, bears N. 25° W., and S. 25° E.
- 32.30 Fence, barbed wire, follows along ridge.
- 36.30 Small wash, drains irregularly SE.; asc. gentle E. slope through heavy brush.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 10.  
Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.
- T15N R11W  
 $\frac{1}{4}$   $\frac{S 3}{S 10}$   
1962
- 53.00 Saddle of low ridge, bears SE. and NW.

26

BOOK 4851

## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

26.

## Chains

- 62.30 Head of wash, drains SE. circling to S.; asc. steep E. slope.
- 66.70 Top of ascent, bears N. and S.
- 71.00 Fence, barbed wire, bears N. 65° E. and S. 65° W.
- 77.00 Ridge, bears SE. and NW.
- 78.47 Fence, barbed wire, bears NW. and SE.
- 80.01 The cor. of secs. 3, 4, 9 and 10.
- Land, high rolling mountains.  
Soil, clay loam and rocky.  
Timber, none; undergrowth, heavy brush, cactus, grass and greasewood.
- 
- N. 0°02' W., bet. secs. 3 and 4.
- Ascend over S. slope.
- 1.20 Fence, barbed wire, bears N. 53° W. and S. 53° E.
- 1.60 Ridge, bears N. 60° W., and S. 60° E.; desc. along rolling land E. drainage and exposure.
- 26.20 Small rocky spur, slopes NE.; continue along the E. side of high mesa.
- 29.80 Wash, drains E.
- 40.00 Point for the  $\frac{1}{2}$  sec. cor. of secs. 3 and 4.
- Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
- T15N R11W  
 $\frac{1}{2}$   
S 4 | S 3  
1962
- Descend NE. slope.
- 43.30 Small wash, drains NE.
- 51.40 Small wash, drains NE., stock watering trough in bottom of wash, 80 lks. West.
- 59.30 Low spur, slopes NE.
- 60.10 Fence, barbed wire, bears N. 50° W. and S. 60° E.
- 72.90 Wash, 15 lks. wide, 2 ft. deep, drains NE.
- 77.85 Fence, barbed wire, bears E. and W.
- 78.31 Intersect the N. bdy. of the township.
- Point for the closing cor. of secs. 3 and 4.
- Set the iron post 18 ins. in the ground and in a collar of stone, cap mkd.

## Chains

T16N.  
S 33  
 S 4 | S 3  
 T15N R11W  
 C G  
 1962

Raise a mound of stone South of the corner.

The cor. of secs. 3, 4, 33 and 34 bears East 5.17 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 33 and 34, T. 16 N., R. 11 W., only, marks altered to

T16N R11W  
S 33 | S 34  
 S 3  
 T15N  
 1962  
 1916

Land, mountainous.

Soil, rocky clay loam.

Timber, none; undergrowth, cactus, brush, greasewood, catclaw and grass.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 3 is at mid point between closing corners and on the N. bdy. of the township.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

T16N  
 $\frac{1}{4}$  S 3  
 T15N R11W  
 1962

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 34 bears East 5.18 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  cor. of sec. 34, T. 16 N., R. 11 W., only, marks altered to

T16N R11W  
 $\frac{1}{4}$  S 34  
 T15N  
 1962  
 1930

From the true point for the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township, witness cor. for which bears West, 2.30 chs. dist., monumented by an iron post, 2 $\frac{1}{2}$  ins. diam., set, mkd., and witnessed as described in the official record.

N. 0°02' W., bet. secs. 32 and 33.

Ascend over ledgy mountainous land draining South.

3.60 Wash, 40 lks. wide, 3 ft. deep, drains S. 20° E. circling to S.

8.40 Rocky spur, projects W.

12.90 Same wash as one at 3.60, drains S. 10° W. circling to SE.

28

405

## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

28.

## Chains

- 32.40 Finger spur, projects E.; desc. rocky N. slope.
- 36.10 Slope changes to rocky SE.; ascend.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 32 and 33.  
Set the iron post, over broken limestone, and in a mound of stone to top, cap mkd.
- T15N R11W  
 $\frac{1}{4}$   
S 32 | S 33  
1962
- Ascend over steep rocky S. slope.
- 46.40 Finger spur, slopes S. 70° E.; ascend along broken E. slope.
- 50.30 Slope changes to rocky N.; descend.
- 56.10 Power line, bears N. 70° W., and S. 70° E.
- 56.70 Jeep road, parallels power line; asc. S. slope.
- 65.50 Slope changes to ledgy W.; descend.
- 79.80 Point selected for the witness cor. of secs. 28, 29, 32 and 33.  
Set the iron post, 4 ins. in the ground, mound with stones to top, cap mkd.
- T15N T11W  
S 29 | S 28  
S 32 | S 33  
W C  
1962
- 80.00 The true point for the cor. of secs. 28, 29, 32 and 33 falls on ledgy shelf where cor. cannot be perpetuated.  
Land, mountainous.  
Soil, rocky.  
Timber, none; undergrowth, paloverde, cactus, catclaw, and greasewood.
- 
- From the cor. of secs. 27, 28, 33 and 34.  
N. 89°56' W., bet. secs. 28 and 33.  
Over steep mountainous land through undergrowth.  
By triangulation, topography as estimated, desc. SW. slope.
- 5.00 Wash, 30 lks. wide, 1 ft. deep, drains S.; asc. steep E. slope.
- 22.80 End of triangulation on high rocky ridge, bears N. and S. circling to SW.; desc. SW. slope.
- 32.80 Rocky spur, slopes S. 30° W.; desc. steep W. slope.
- 40.10 Point for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 33.  
Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.

| Chains |   |
|--------|---|
|        | T15N R11W<br>$\frac{1}{2}$ $\frac{S\ 28}{S\ 33}$<br>1962  |
| 41.60  | Wash, 20 lks. wide, steep sloping banks, drains S. 20° W.; asc. steep E. slope.                                   |
| 51.00  | Spur, slopes S.; desc. SW. slope.   |
| 57.70  | Rocky spur, slopes S.; desc. ledgy W. slope.  |
| 65.40  | Draw, drains S. 70° W.; desc. along S. slope.   |
| 72.70  | Slope changes to W.; descend.   |
| 80.20  | True point for the cor. of secs. 28, 29, 32 and 33.   |
|        | Land, mountainous.<br>Soil, rocky.<br>Timber, none; undergrowth, palo verde, cactus, brush, greasewood and grass. |
|        | N. 0°02' W., bet. secs. 28 and 29.  |
|        | Over mountainous land through undergrowth.  |
| .50    | Rocky wash, 20 lks. wide, 2 ft. deep, drains SW.  |
| 13.90  | End of high rocky spur, sloping from E.   |
| 21.60  | Wash, 40 lks. wide, 2 ft. deep, drains N. 50° W., circling S.; asc. S. slope.                                     |
| 32.00  | Top of ascent, bears E. and W.  |
| 37.40  | Small wash, drains E. to SE.  |
| 40.00  | Point for the $\frac{1}{2}$ sec. cor. of secs. 28 and 29.   |
|        | Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.  |
|        | T15N R11W<br>$\frac{1}{2}$<br>S 29   S 28<br>1962   |
|        | Ascend S. slope.  |
| 41.00  | Rocky spur, slopes W.   |
| 47.90  | Small wash, drains W.   |
| 54.10  | Small spur, slopes W. from NE.  |
| 64.80  | Small wash, drains S. 75° W.  |
| 65.50  | Bladed dirt road, bears irregularly E. and W.   |
| 71.80  | Main wash, road in bottom, 2.00 chs. wide, 1 ft. deep, drains W. circling to SW.                                  |
| 74.50  | Dirt road, bears N. 80° E. and S. 80° W.  |

30

8000 4051

Subdivisional Lines, T. 15 N., R. 11 W., Arizona

|           |  |           |  |        |      |      |      |
|-----------|--|-----------|--|--------|------|------|------|
| Chains    |  |           |  |        |      |      |      |
| 77.90     | Small wash, drains SW.   |           |  |        |      |      |      |
| 80.00     | Point for the cor. of secs. 20, 21, 28 and 29.<br><br>Set the iron post 24 ins. in the ground, cap mkd.<br><br><div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T15N R11W</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 20</td> <td style="padding-left: 5px;">S 21</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 29</td> <td style="padding-left: 5px;">S 28</td> </tr> </table> <p>1962</p> </div><br>Raise a mound of stone West of the corner.<br><br>Cor. is located in the bottom of shallow, small wash, draining south.<br><br>Land, mountainous.<br>Soil, rocky, sandy clay loam.<br>Timber, none; undergrowth, palo verde, cactus, catclaw, greasewood and grass.   | T15N R11W |  | S 20   | S 21 | S 29 | S 28 |
| T15N R11W |  |           |  |        |      |      |      |
| S 20      | S 21   |           |  |        |      |      |      |
| S 29      | S 28   |           |  |        |      |      |      |
|           | From the cor. of secs. 21, 22, 27 and 28.<br><br>N. 89°55' W., bet. secs. 21 and 28.<br><br>Ascend along gentle N. slope.<br><br>2.10 Spur, slopes W.; descend.<br><br>22.80 Slope changes to SW.<br><br>34.30 Main wash, jeep road in bottom, 1.30 chs. wide, 1 ft. deep, drains S. 15° W., circling to W.; asc. along gentle S. slope.<br><br>40.10 Point for the ¼ sec. cor. of secs. 21 and 28.<br><br>Set the iron post, 10 ins. in the ground, mound with stones to top, cap mkd.<br><br><div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T15N R11W</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">¼ S 21</td> <td style="padding-left: 5px;">S 28</td> </tr> </table> <p>1962</p> </div><br>A windmill bears N. 56°18' E., 11.97 chs. dist.<br><br>A windmill bears N. 61° 55' W., 20.68 chs. dist.<br><br>Enter scattered juniper trees.<br><br>42.40 Slope changes to gentle SW.; descend.<br><br>50.35 Small pole corral with loading chute, bears N., 55 lks. dist.<br><br>65.50 Wash, 20 lks. wide, 1 ft. deep, drains SW.<br><br>66.40 Dirt road, bears N. 30° E. and S. 30° W.<br><br>77.70 Wash, 15 lks. wide, 1 ft. deep, drains SW.<br><br>79.50 Small finger spur, near end, slopes S.<br><br>80.20 The cor. of secs. 20, 21, 28 and 29.<br><br>Land, rolling.<br>Soil, rocky and sandy.<br>Timber, widely scattered juniper; undergrowth, cactus, catclaw, | T15N R11W |  | ¼ S 21 | S 28 |      |      |
| T15N R11W |  |           |  |        |      |      |      |
| ¼ S 21    | S 28   |           |  |        |      |      |      |



## Chains

palo verde, grass and greasewood.

N. 0°02' W., bet. secs. 20 and 21.

Ascend over gentle S. slope, through scattered juniper and palo verde.

12.55 Small wash, drains S. 15° E.

17.20 Begin descent over gentle rolling N. slope.

29.30 Small wash, drains SW. circling S.; asc. over rolling SW. slope.

37.20 Small wash, drains S. 20° W.

40.00 Point for the  $\frac{1}{2}$  sec. cor. of secs. 20 and 21.

Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

$\frac{1}{2}$   
S 20 | S 21  
1962

42.10 Small spur, slopes S. 80° W.

44.20 Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.

58.10 High spur, slopes S., from N. 70° E.

63.30 Small wash, drains NW., circles to SW.

71.50 Spur, slopes W.

76.70 Small wash, drains SW.

78.60 Low spur, slopes S. 50° W.

79.90 Point selected for the witness cor. of secs. 16, 17, 20 and 21.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

S 17 | S 16  
S 20 | S 21  
W C  
1962

80.00 The true point for the cor. of secs. 16, 17, 20 and 21 falls in edge of wash in an unsafe place.

Land, mountainous.

Soil, rocky sandy clay loam.

Timber, scattered juniper; undergrowth, catclaw, palo verde, cactus.

From the true point for the cor. of secs. 15, 16, 21 and 22.

N. 89°54' W., bet. secs. 16 and 21.

Ascend over E. slope through undergrowth.

| Chains |   |
|--------|---|
| 7.20   | Spur, slopes SE.; desc. SW. slope.  |
| 15.00  | Wash, 10 lks. wide, 1 ft. deep, drains S. 20° E.; asc. E. slope.  |
| 18.80  | Low spur, slopes S. 10° E.  |
| 22.30  | Wash, 30 lks. wide, 1 ft. deep, drains S. 20° E.; asc. steep E. slope.  |
| 37.60  | Rocky spur, slopes S. 30° E.; desc. steep W. slope.   |
| 40.10  | Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.   |
|        | Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.  |
|        | T15N R11W<br>$\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$<br>1962  |
| 46.30  | Small wash, drains S.   |
| 50.10  | Low ridge, bears N. 20° E., and S. 20° W.   |
| 55.10  | Wash, 10 lks. wide, 1 ft. deep, drains irregularly SW.  |
| 69.70  | Rocky spur, slopes S.   |
| 76.60  | Small spur, slopes SW.  |
| 80.19  | The true point for the cor. of secs. 16, 17, 20 and 21.   |
|        | Land, mountainous.<br>Soil, rocky and gravelly.<br>Timber, none; undergrowth, cactus, catclaw and greasewood.     |
|        | N. 0°02' W., bet. secs. 16 and 17.  |
|        | Over rolling mountainous land, through widely scattered juniper.  |
| 3.40   | Small spur, slopes W.   |
| 10.90  | Saddle on spur, sloping W.  |
| 22.90  | Wash, 15 lks. wide, 1 ft. deep, drains W.; asc. SW. slope.  |
| 37.50  | Top of ascent, bears E. and W.; desc. N. slope through juniper.   |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.   |
|        | Set the iron post, 8 ins. in the ground, mound with stones to top, cap mkd.                                       |
|        | T15N R11W<br>$\frac{1}{4}$<br>S 17   S 16<br>1962   |
|        | A windmill bears N. 16°26' W., 8.03 chs. dist.  |
| 45.40  | Wash, 90 lks. wide, 1 ft. deep, drains S. 75° W., road in bottom of wash bears S. 75° W., and NE. circling to NW. |
| 47.90  | Same road, bears S. 82° W., 2.29 chs. dist., ending at windmill. Leave timber; asc. over rolling land facing S.   |

| Chains |   |
|--------|---|
| 64.70  | Small spur, slopes SW.  |
| 80.00  | Point for the cor. of secs. 8, 9, 16 and 17.<br>Set the iron post, 16 ins. in the ground, mound with stones to top, cap mkd.  |
|        | T15N R11W<br>S 8   S 9<br>S 17   S 16<br>1962   |
|        | Land, mountainous.<br>Soil, rocky clay loam.<br>Timber, scattered juniper on S. 45.00 chains; undergrowth, cactus, palo verde, catclaw, greasewood and grass.                                       |
|        | From the cor. of secs. 9, 10, 15 and 16.<br>N. 89°54' W., bet. secs. 9 and 16.<br>Over rolling mountainous land, through undergrowth.<br>By triangulation, topography as estimated; desc. W. slope. |
| 24.00  | Wash, 30 lks. wide, 1 ft. deep, drains S. 60° W.; asc. E. slope.  |
| 30.00  | Narrow spur, slopes S.  |
| 35.50  | Wash, 20 lks. wide, 1 ft. deep, drains S. 20° W.; asc. E. slope.  |
| 40.07  | Point for the $\frac{1}{2}$ sec. cor. of secs. 9 and 16.<br>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.   |
|        | T15N R11W<br>$\frac{1}{2}$ S 9<br>S 16<br>1962  |
|        | End of triangulation.   |
| 42.20  | Spur, slopes S.   |
| 51.10  | Wash, 15 lks. wide, 2 ft. deep, drains irregularly SW.  |
| 65.20  | Spur, slopes S.   |
| 67.90  | Wash, 10 lks. wide, 1 ft. deep, drains S. 15° W.  |
| 77.80  | Spur, slopes S.; desc. SW. slope.   |
| 80.14  | The cor. of secs. 8, 9, 16 and 17.<br>Land, mountainous.<br>Soil, rocky clay loam.<br>Timber, none; undergrowth, cactus, catclaw, brush and greasewood.   |
|        | N. 0°02' W., bet. secs. 8 and 9.<br>Over steep south slope of mesa by triangulation.  |

| Chains |   |
|--------|---|
| 37.70  | End of triangulation on narrow rocky spur, projecting N. 71° W.; desc. over steep rocky N. slope.   |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.<br>Set an iron post 6 ins. in the ground, mound with stones to top, cap mkd.                  |
|        | T15N R11W<br>$\frac{1}{4}$<br>S 8   S 9<br>1962   |
|        | By triangulation, topography as estimated; desc. over steep N. slope.   |
| 50.00  | Draw, drains N. 80° E. circling to N.; asc. along rocky SE. slope.  |
| 57.30  | End of triangulation on spur projecting E.; desc. over steep broken N. slope.   |
| 80.00  | Point for the cor. of secs. 4, 5, 8 and 9.<br>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.                              |
|        | T15N R11W<br>S 5   S 4<br>S 8   S 9<br>1962   |
|        | Land, mountainous.<br>Soil, rocky clay loam.<br>Timber, none; undergrowth, cactus, scrub oak, brush, catclaw and grass.                               |
|        | From the cor. of secs. 3, 4, 9 and 10.  |
|        | N. 89°52' W., bet. secs. 4 and 9.   |
|        | Ascend along S. slope of high broken mesa.  |
| 28.00  | Head of draw, drains S. 10° E.; asc. abruptly over E. slope.  |
| 32.70  | High spur, projects S. from mesa top; desc. over steep W. slope.  |
| 40.10  | Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.<br>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.                 |
|        | T15N R11W<br>$\frac{1}{4}$ $\frac{S 4}{S 9}$<br>1962  |
|        | Triangulation station "Loaf" bears N. 52°49' E., 9.95 chs. dist., monumented by a regulation bronze disc. cemented in bedrock flush with the surface. |
| 42.70  | Head of ravine, drains N. 50° W.; asc. along ledgy NE. slope.   |
| 53.70  | Top of ascent, bears NW. and SE.; desc. steep W. slope.   |

## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

35.

## Chains

|       |   |
|-------|---|
| 77.00 | Wash, 20 lks. wide, 2 ft. deep, drains N. 10° W.  |
| 80.20 | The cor. of secs. 4, 5, 8 and 9.<br>Land, mountainous.<br>Soil, rocky clay loam.<br>Timber, none; undergrowth, cactus, thick brush, oak and grass.  |
|       | N. 0°02' W., bet. secs. 4 and 5.<br>Descend over gentle N. slope, through undergrowth.  |
| 6.30  | Wash, 20 lks. wide, 3 ft. deep, drains N. 70° W.  |
| 27.00 | Wash, 30 lks. wide, 4 ft. deep, drains N. 60° W.  |
| 33.10 | Small spur, slopes W.   |
| 37.10 | Wash, 20 lks. wide, 3 ft. deep, drains W.   |
| 40.00 | Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.<br>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.<br><br>T15N R11W<br>$\frac{1}{4}$<br>S 5   S 4<br>1962  |
| 42.10 | Small spur, slopes S. 80° W.  |
| 47.90 | Wash, 20 lks. wide, 2 ft. deep, drains W.   |
| 59.80 | Spur, slopes W.   |
| 66.00 | Wash, 15 lks. wide, 1 ft. deep, drains W.   |
| 71.80 | Spur, slopes NW., desc. along NE. slope.  |
| 78.03 | Intersect the N. bdy. of the township.<br>Point for the closing corner of secs. 4 and 5.<br>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.<br><br>T16N R11W<br>S 32<br>S 5   S 4<br>T15N R11W<br>C C<br>1962<br><br>The cor. of secs. 4, 5, 32 and 33 bears East 5.39 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 32 and 33, T. 16 N., R. 11 W., only, marks altered to<br><br>T16N R11W<br>S 32   S 33<br>S 4<br>T15N<br>1962<br>1916 |

Chains

Land, mountainous.  
Soil, rocky clay loam.  
Timber, none; undergrowth, cactus, brush, greasewood, catclaw and grass.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 4 is at mid-point between the closing corners and on the N. bdy. of the township.

Set the iron post 14 ins. in the ground, mound with stone to top, cap mkd.

T16N  
-----  
 $\frac{1}{4}$  S 4  
T15N R11W  
1962

The  $\frac{1}{4}$  sec. cor. of secs. 4 and 33 bears East, 5.28 chs. dist., monumented by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  sec. cor. of sec. 33, T. 16 N., R. 11 W., only, marks altered to

S 33  
 $\frac{1}{4}$   
-----  
1962  
1916

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the township, monumented by an iron post 2 $\frac{1}{2}$  ins. diam., set, mkd. and witnessed as described in the official record.

N. 0°03' W., bet. secs. 31 and 32.

Over steep rocky SW. slope; ascend.

10.90 S. rim of mesa, bears SE. and N. 80° W.; thence over gentle rolling mesa top.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 32.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W  
 $\frac{1}{4}$   
S 31 | S 32  
1962

45.40 Enter scattered junipers; desc. gentle N. slope.

49.40 N. rim of mesa, bears E. and W.

65.80 Wash, 20 lks. wide, 1 ft. deep, drains irregularly W.

73.30 Spur, slopes S. 80° W.

77.60 Main wash, 1.50 chains wide, 1 ft. deep, drains irregularly SW.

78.90 Dirt road, along W. edge of wash; asc. SE. slope.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

## Chains

Set the iron post 8 ins. in the ground, mound with stone to top, cap mkd.

T15N R11W  
 S 30 | S 29  
 S 31 | S 32  
 1962

Land, rolling.

Soil, clay loam, sandy in washes, and rocky.

Timber, scattered juniper on N. 35.00 chains; undergrowth, cactus, brush, greasewood and catclaw.

From the true point for the cor. of secs. 28, 29, 32 and 33.

West bet. secs. 29 and 32.

Descend over ledgy W. slope, through scattered junipers.

.80 Wash, 30 lks. wide, 2 ft. deep, drains S. 20° W.

6.10 Rocky spur, slopes S.

16.90 Head of draw, drains SW. circling to S.

36.80 Wash, 15 lks. wide 1 ft. deep, drains SW.

39.20 Small wash, drains S. about 1.00 chain, thence SW.; asc. E. slope.

39.85 Point for the  $\frac{1}{2}$  sec. cor. of secs. 29 and 32.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W  
 $\frac{1}{2}$  S 29  
 S 32  
 1962

43.00 Small spur, slopes S.

48.00 Power line, bears N. 52° W., and S. 52° E.

49.00 Jeep road, bears N. and S.

55.10 Wash, 40 lks. wide, 2 ft. deep, drains N. 75° W., circling to S.

60.60 Same wash, drains S. circling to W.

71.10 Dim road, bears N. 60° E. and S. 60° W.

71.30 Spur, slopes N. 60° E.; desc. NW. slope.

78.30 Main wash, 1.50 chains wide, 1 ft. deep, drains irregularly SW.

79.00 Road, follows along edge of wash; asc. SE. slope.

79.70 The cor. of secs. 29, 30, 31 and 32..

Land, mountainous.

Soil, rocky and sandy.

Timber, scattered juniper; undergrowth, catclaw, cactus, creosote, and grass.

## Chains

West, bet. secs. 30 and 31.

Asc. over general E. slope, through scattered junipers.

6.20 Small wash, drains S.

10.70 Low rise, bears N. and S.

14.10 Draw, about 4.00 chains from head, drains S. 20° W.

18.70 Low spur, slopes SW.

28.00 Wash, 20 lks. wide, 1 ft. deep, drains S., leave timber; asc. over steep E. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 30 and 31.

Set the iron post 10 ins. in the ground, mound with stone to top, cap mkd.

$$\begin{array}{r} \text{T15N R11W} \\ \frac{1}{4} \frac{\text{S } 30}{\text{S } 31} \\ 1962 \end{array}$$

43.50 Top of steep ascent, bears N. and SW.; continue gentle ascent over E. slope.

60.30 High rocky hill, bears N. and SW.; desc. over NW. slope.

73.47 Intersect the E. bdy. of T. 15 N., R. 12 W.

Point for the closing cor. of secs. 30 and 31.

Set an iron post 18 ins. in the ground, cap mkd.

$$\begin{array}{r} \text{T15N} \\ \text{R12W R11W} \\ \text{S } 25 \left| \begin{array}{l} \text{S } 30 \text{ C} \\ \text{S } 31 \text{ C} \end{array} \right. \\ 1962 \end{array}$$

Raise a mound of stone, E. of the corner.

The cor. of secs. 25, 30, 31 and 36 bears South 2.40 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 25 and 36, T. 15 N., R. 12 W., only, marks altered to

$$\begin{array}{r} \text{T15N} \\ \text{R12W R11W} \\ \text{S } 25 \left| \begin{array}{l} \text{S } 30 \\ \text{S } 31 \end{array} \right. \text{S } 31 \\ 1962 \\ 1916 \end{array}$$

Land, mountainous.

Soil, rocky.

Timber, scattered juniper on E. 28.00 chains; undergrowth, cactus, catclaw, ocotillo, palo verde, and grass.

Point for the W.  $\frac{1}{4}$  sec. cor. of sec. 31 is on the W. bdy. at mid-point bet. the C.Cs.



## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

39.

## Chains

Set the iron post 10 ins. in the ground, mound with stone to top, cap mkd.

T 15 N R11W

1/2  
S 31  
1962

The head of Kaiser Springs bears N. 62°01' E., 21.59 chs. dist.  
Small flow of water in canyon from spring.

The 1/2 sec. cor. of sec. 36 bears South, 2.61 chs. dist.

From the cor. of secs. 29, 30, 31 and 32.

N. 0°03' W., bet. secs. 29 and 30.

Asc. over gentle SE. slope, through scattered junipers.

10.30 Road, bears E. and W.; desc. over gentle NW. slope.

24.45 Power line, bears N. 75° W., and S. 75° E.

38.10 Wash, 30 lks. wide, 1 ft. deep, drains irregularly SW.; asc. S. slope.

40.00 Point for the 1/2 sec. cor. of secs. 29 and 30.

Set the iron post, on broken bedrock, mound with stones to top, cap mkd.

T15N R11W

1/2  
S 30 | S 29  
1962

42.20 Small ravine, drains SW.

49.00 Low spur, slopes SW.

57.20 Draw, near head, drains NW. circling to SW.

71.50 Small rocky ridge, bears NE. and SW.

80.00 Point for the cor. of secs. 19, 20, 29 and 30.

Set the iron post 20 ins. in the ground, cap mkd.

T15N R11W

S 19 | S 20  
S 30 | S 29  
1962

Raise a mound of stone West of the corner.

Land, rolling mountains.

Soil, rocky and sandy clay loam.

Timber, scattered juniper; undergrowth, cactus, palo verde, yucca, catclaw, ocotillo and grass.

From the cor. of secs. 20, 21, 28 and 29.

S. 89°57' W., bet. secs. 20 and 29.

Over gently rolling land, through scattered junipers.

## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

| Chains |  |
|--------|--|
| 13.00  | Bladed dirt road, bears N. 15° W. and S. 15° E.  |
| 16.60  | Wash, 40 lks. wide, 1 ft. deep, drains S. 15° E.   |
| 23.10  | Ridge, bears N. and S.   |
| 30.90  | Wash, 20 lks. wide, 1 ft. deep, drains SW.   |
| 38.80  | Spur, slopes SE.; desc. SW. slope.   |
| 39.87  | Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.<br>Set an iron post, 6 ins. in the ground, mound with stones to top, cap mkd.  |
|        | T15N R11W<br>$\frac{1}{4}$ $\frac{S 20}{S 29}$<br>1962   |
| 46.10  | Draw, about 1.00 chain from head, drains S.  |
| 49.60  | Spur, slopes S. 60° W.   |
| 60.10  | Wash, 15 lks. wide, 2 ft. deep, drains S. 10° W.   |
| 72.90  | Low ridge, bears NE. and SW.   |
| 79.73  | The cor. of secs. 19, 20, 29 and 30.<br>Land, rolling mountainous.<br>Soil, sandy clay loam and rocky.<br>Timber, scattered juniper; undergrowth, cactus, yucca, ocotillo, palo verde, greasewood and grass. |
|        | West, bet. secs. 19 and 30.<br>Over gently rolling land, through scattered juniper.  |
| 9.40   | Low rise, slopes SW.   |
| 15.00  | Wash, 10 lks. wide, 1 ft. deep, drains S. 15° W.   |
| 21.00  | Bladed dirt road, bears SW. and NE.  |
| 25.70  | Draw, drains SW.   |
| 33.10  | Spur, slopes SW.; desc. NW. slope.   |
| 40.00  | Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.<br>Set an iron post 24 ins. in the ground, cap mkd.  |
|        | T15N R11W<br>$\frac{1}{4}$ $\frac{S 19}{S 30}$<br>1962   |
|        | Raise a mound of stone N. of the corner.   |
| 41.30  | Finger spur, slopes NW.; desc. W. slope.   |
| 46.70  | Small draw, drains N. 60° W. from E.   |
| 50.10  | Same draw, drains S. 60° W.  |
| 59.80  | Wash, 30 lks. wide, 4 ft. deep, drains SW.   |

## Chains

70.80 Bladed road, bears N. 20° W. and S. 10° E.

73.49 Intersect the West bdy. of the township.

Point for the closing cor. of secs. 19 and 30.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T15N  
R12W R11W  
S 24 | S 19 C  
          | S 30 C  
1962

The cor. of secs. 19, 24, 25 and 30 bears South, 2.42 chains dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 24 and 25, T. 15 N., R. 12 W., only, marks altered to

T15N  
R12W R11W  
S 24 | S 30  
S 25 |  
1962  
1916

Land, mountainous.

Soil, rocky clay loam.

Timber, scattered juniper; undergrowth, cactus, palo verde, greasewood, ocotillo, and grass.

Point for the W.  $\frac{1}{4}$  sec. cor. of sec. 30 is on the West bdy. at mid-point bet. closing corners.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T15N  
R12W R11W  
          |  $\frac{1}{4}$   
          | S 30  
1962

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 30 bears South 2.41 chains dist., monumented by an iron post 1 inch in diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  sec. cor. of sec. 25, T. 15 N., R. 12 W., only, marks altered to

T15N  
R12W R11W  
          |  $\frac{1}{4}$   
S 25 |  
1962  
1916

From the cor. of secs. 19, 20, 29 and 30.

N. 0°03' W., bet. secs. 19 and 20.

Ascend over S. slope, through scattered junipers.

Subdivisional Lines, T. 15 N., R. 11 W., Arizona

Chains

- 5.50 Slope changes to SE.; ascend.
- 16.90 Low ridge, bears NE. and SW.; descend.
- 20.50 Bladed road, bears irregularly E. and W.; desc. N. slope.
- 34.30 Wash, 15 lks. wide, 2 ft. deep, drains W.
- 37.80 End of spur, slopes SW.; desc. NW. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 20.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W  
 $\frac{1}{4}$   
 S 19 | S 20  
 1962

- 41.60 Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
- 45.90 Ridge, bears SW. and NE.
- 51.10 Enter wash, 2.00 chains wide, 1 ft. deep, drains irregularly SW. from N.
- 64.70 Road in bottom of wash.
- 64.90 Leave wash, from NE.; asc. SE. slope.
- 80.00 Point for the cor. of secs. 17, 18, 19 and 20.

Set the iron post 8 ins. in the ground, mound with stone to top, cap mkd.

T15N R11W  
 S 18 | S 17  
 S 19 | S 20  
 1962

Land, rolling and broken.  
 Soil, rocky and sandy.  
 Timber, scattered junipers; undergrowth, cactus, yucca, greasewood, catclaw, palo verde and grass.

From the true point for the cor. of secs. 16, 17, 20 and 21.

West, bet. secs. 17 and 20.

Desc. along small wash draining irregularly W.

- 15.60 Wash, 10 lks. wide, 3 ft. deep, drains S. 60° W., from NE.; asc. SE. slope.
- 23.90 Spur, slopes SW.
- 32.50 Wash, 30 lks. wide, 2 ft. deep, drains SW.
- 39.88 Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 20.

Set the iron post, on solid rock, mound with stones to top, cap mkd.

T15N R11W  
 $\frac{1}{4}$  S 17  
 S 20  
 1962

## Chains

- The cor. is located on low spur sloping SW.
- 45.20 Small wash, drains S. 70° W. from NE.
- 45.80 Small wash, drains SW.
- 54.90 Rocky outcrop on spur sloping SW.; desc. steep W. slope.
- 63.10 Bladed dirt road, bears irregularly N. and S.; small wash drains SW.
- 68.10 Low rise, bears N. and S.
- 73.60 Wash, 2.00 chains wide, 2 ft. deep, drains S. 10° W. from NE., road in bottom of wash.
- 79.75 The cor. of secs. 17, 18, 19 and 20.
- Land, rolling.  
Soil, sandy clay loam and rocky.  
Timber, scattered juniper; undergrowth, cactus, catclaw, palo verde, brush and grass.
- 
- West, bet. secs. 18 and 19.
- Over mountainous land, through scattered juniper, asc. E. slope.
- 2.60 End of high spur, slopes S.
- 14.00 Wash, 10 lks. wide, 1 ft. deep, drains S. 30° W.
- 24.20 High rocky spur, slopes SW.
- 34.30 Wash, 50 lks. wide, 2 ft. deep, drains S. about 1.00 chain, thence SW.
- 39.00 Low rise, bears N. and S., desc. gentle W. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 18 and 19.
- Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.
- T15N R11W  
 $\frac{1}{4}$   $\frac{S 18}{S 19}$   
1962
- 40.90 Small ravine, drains S.
- 52.70 Rocky spur, slopes SW.

Chains

62.00 Bladed dirt road, bears N. and S.  
 65.60 Wash, 60 lks. wide, 1 ft. deep, drains SW.  
 66.90 Wash, 20 lks. wide, 1 ft. deep, drains S.  
 69.20 Begin ascent over steep E. slope.  
 73.46 Intersect the W. bdy. of the township.  
 Point for the closing corner of secs. 18 and 19.  
 Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T15N  
 R12W R11W  
 S 13 | S 18 C  
       | S 19 C  
 1962

The cor. of secs. 13, 18, 19 and 24 bears South, 2.47 chs. dist., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 13 and 24, T. 15 N., R. 12 W., only, marks altered to

T15N  
 R12W R11W  
 S 13 | S 19  
 S 24 |  
 1962

From the closing corner of sec. 18 and 19,  
 A windmill bears S. 51°56' E., 6.33 chs. dist.

Land, mountainous.  
 Soil, rocky clay loam.  
 Timber, scattered juniper; undergrowth, cactus, brush, catclaw, palo verde, grass and ocotillo.

The point for the W. ¼ sec. cor. of sec. 19 is on the W. bdy. and at mid-point bet. closing corners. The true point falls in wash and road bearing E. and W., in an unsafe location.

From the true point

Point selected for the witness ¼ sec. cor. of sec. 19 bears S., 1.44 chs. dist.

Set the iron post 24 ins. in the ground, cap mkd.

## Chains

T15N  
R12W R11W  
↑  
W C | S 19  
1962

Raise a mound of stone E. of the corner.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 24 bears S. 2.44 chs. dist. from the true point for the  $\frac{1}{4}$  sec. cor. of sec. 19, monumented by an iron post 1 inch in diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  sec. cor. of sec. 24, T. 15 N., R. 12 W., only, marks altered to

T15N  
R12W R11W  
 $\frac{1}{4}$  |  
S 24 |  
1962  
1916

From the cor. of secs. 17, 18, 19 and 20.

N.  $0^{\circ}03'$  W., bet. secs. 17 and 18.

Ascend along E. to SE. slope, through scattered juniper.

11.50 Top of small knoll.

30.20 Wash, 20 lks. wide, 3 ft. deep, drains SW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 18.

Set an iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W  
 $\frac{1}{4}$   
S 18 | S 17  
1962

Asc. over broken S. slope.

47.70 Wash, 20 lks. wide, 2 ft. deep, drains W. for 1.00 chain, thence S.

65.80 Spur, slopes S.  $10^{\circ}$  E.

80.00 Point for the cor. of secs. 7, 8, 17 and 18.

Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W  
S 7 | S 8  
S 18 | S 17  
1962

"Lion Spring" bears N.  $56^{\circ}35'$  E., 34.05 chs. dist., a small seep developed with two man made tunnels, 20 lks. apart, and a  $\frac{3}{4}$  inch iron pipe leading southerly to cement water trough.

Land, rolling and broken.

Soil, rocky clay loam.

Timber, widely scattered junipers; undergrowth, yucca, palo verde and cactus.

## Chains

From the cor. of secs. 8, 9, 16 and 17.

N. 89°59' W., bet. secs. 8 and 17.

Over rolling mountainous land, through scattered junipers, general S. drainage and exposure.

4.90 Draw, drains S.

8.00 Spur, slopes S.

17.30 Draw, drains SW.

24.40 Spur, slopes S.

32.10 Draw, drains S.

37.40 Rocky spur, slopes S.; desc. W. slope.

39.80 Small wash, drains S.

39.92 Point for the  $\frac{1}{4}$  sec. cor. of secs. 8 and 17.

Set the iron post 12 ins. in the ground, mound with stone to top, cap mkd.

T15N R11W

$\frac{1}{4}$   $\frac{S}{S}$   $\frac{8}{17}$

1962

45.40 Dirt road, bears SW. and N., ending at "Lion Spring."

52.10 Spur, slopes S.; desc. W. slope.

56.80  $\frac{5}{4}$  inch water pipe, bears southerly from "Lion Spring."

59.40 Draw, drains S. circling SW.

66.30 Draw, drains SW.

71.40 Draw, drains SW.

75.80 Finger spur, slopes S.

79.83 The cor. of secs. 7, 8, 17 and 18.

Land, mountainous.

Soil, rocky clay loam.

Timber, scattered juniper; undergrowth, cactus, palo verde, greasewood and grass.

West, bet. secs. 7 and 18.

Over rolling mountainous land; asc. E. slope.

3.00 Spur, slopes S.

4.90 Wash, 5 lks. wide, 2 ft. deep, drains S. 20° W.

11.00 Small spur, slopes S.

16.00 Wash, 5 lks. wide, 2 ft. deep, drains S. 15° E.

23.80 Spur, slopes S. 15° E.

26.80 Draw, near head, drains S. 20° E.



## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

47.

Chains  
29.60

Spur, slopes S.

32.60

Fence, bears NE. and SW.

40.00

Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 18.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

$$\begin{array}{r} \text{T15N R11W} \\ \frac{1}{4} \frac{\text{S } 7}{\text{S } 18} \\ 1962 \end{array}$$

58.50

Wash, 20 lks. wide, 3 ft. deep, drains SW.

66.40

Spur, slopes S.; desc. along rolling S. slope.

73.42

Intersect the W. bdy. of the Township.

Point for the closing cor. of secs. 7 and 18.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

$$\begin{array}{r} \text{T15N} \\ \text{R12W R11W} \\ \text{S } 12 \left| \frac{\text{S } 7 \text{ C}}{\text{S } 18 \text{ C}} \right. \\ 1962 \end{array}$$

The cor. of secs. 7, 12, 13 and 18 bears South, 2.34 chains dist., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 12 and 13, T. 15 N., R. 12 W., only, marks altered to

$$\begin{array}{r} \text{T15N} \\ \text{R12W R11W} \\ \frac{\text{S } 12}{\text{S } 13} \left| \text{S } 18 \right. \\ 1962 \\ 1916 \end{array}$$

Land, mountainous.

Soil, rocky clay loam.

Timber, scattered juniper; undergrowth, cactus, catclaw, palo verde, yucca, grass and greasewood.

The point for the W.  $\frac{1}{4}$  sec. cor. of sec. 18 is on the W. bdy. and at mid-point bet. closing corners.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

$$\begin{array}{r} \text{T15N} \\ \text{R12W R11W} \\ \left| \frac{1}{4} \right. \\ \left| \text{S } 18 \right. \\ 1962 \end{array}$$

The  $\frac{1}{4}$  sec. cor. of secs. 13 and 18 bears South, 2.40 chains dist., monumented by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  sec. cor. of sec. 13, T. 15 N., R. 12 W. only, marks altered to

Chains

T15N  
 R12W R11W  
 1/4  
 S 13  
 1962  
 1916

From the cor. of secs. 7, 8, 17 and 18.

N. 0°03' W., bet. secs. 7 and 8.

Over high broken mountainous land; asc. steep S. slope.

30.40 Top of ascent; desc. over steep rocky N. slope.

39.90 Point selected for the witness 1/4 sec. cor. of secs. 7 and 8.

Set the iron post on solid rock and in a mound of stones to top, cap mkd.

T15N R11W  
 1/4  
 S 7 ↑ S 8  
 W C  
 1962

40.00 True point for the 1/4 sec. cor. of secs. 7 and 8 falls on face of large boulder where cor. cannot be perpetuated.

Continue over steep rocky and ledgy mountainous land by triangulation, topography as estimated.

52.00 Rocky wash, 20 lks. wide, 2 ft. deep, drains W.

59.00 Spur, slopes S. 80° W., continue ascent.

75.30 High rocky spur, slopes W.; desc. steep N. slope (end of triangulation).

79.50 Desc. abruptly over ledge facing N.

80.00 Point for the cor. of secs. 5, 6, 7 and 8.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W  
 S 6 | S 5  
 S 7 | S 8  
 1962

Land, rough and broken.

Soil, rocky.

Timber, none; undergrowth, cactus, greasewood, catclaw, oak, brush and grass.

From the cor. of secs. 4, 5, 8 and 9.

S. 89°53' W., bet. secs. 5 and 8.

Over steep broken mountainous land; by triangulation; asc. over general E. slope.

## Chains

39.89 Point for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 8 falls on precipitous E. slope and was not monumented.

49.70 Point selected for the witness  $\frac{1}{4}$  sec. cor. of secs. 5 and 8.

Set the iron post on broken bedrock, mound with stones to top, cap mkd.

T15N R11W

$\frac{1}{4}$   $\frac{S 5}{S 8}$  WC

1962

End of triangulation.

Ascend about 10 ft. over ledge facing E.

50.00 Rim of mesa, bears N. and S. circling to E.; asc. E. slope.

63.00 Rim of mesa, bears S. and NW.; desc. abruptly over steep rocky W. slope.

74.10 Head of draw, drains W.; desc. over ledges facing W.

79.78 The cor. of secs. 5, 6, 7 and 8.

Land, steep and broken.

Soil, rocky clay loam.

Timber, none; undergrowth, cactus, brush, oak, grass.

West, bet. secs. 6 and 7.

By triangulation, over broken mountainous land, through undergrowth, topography as estimated.

4.50 Small spur, slopes NW.

15.00 Low saddle on ridge, bearing S.  $80^\circ$  E. and N.  $80^\circ$  W.; asc. SE. slope.

35.50 Mesa rim, bears SW. and NE.; thence over gentle rolling mesa top.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 7.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W

$\frac{1}{4}$   $\frac{S 6}{S 7}$

1962

End of triangulation.

59.00 Rim of mesa, bears N.  $20^\circ$  W. and S.; desc. over steep broken W. slope.

73.49 Intersect the W. bdy. of the township.

Point for the closing cor. of secs. 6 and 7.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

Subdivisional Lines, T. 15 N., R. 11 W., Arizona

Chains

T15N  
R12W R11W  
S 1 | S 6 C  
      | S 7 C  
1962

The cor. of secs. 1, 6, 7 and 12 bears South, 2.07 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 1 and 12, T. 15 N., R. 12 W., only, marks altered to

T15N  
R12W R11W  
S 1 | S 7  
S 12 |  
1962  
1916

Land, mountainous.  
Soil, rocky clay loam.  
Timber, none; undergrowth, brush, oak, catclaw, grass and cactus.

The point for the W.  $\frac{1}{4}$  sec. cor. of sec. 7 is on the W. bdy. at mid-point bet. closing corners.

Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.

T15N  
R12W R11W  
      |  $\frac{1}{4}$   
      | S 7  
1962

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12 bears South, 2.20 chs. dist., monumented by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  cor. of sec. 12, T. 15 N., R. 12 W., only, marks altered to

T15N  
R12W R11W  
      |  $\frac{1}{4}$   
S 12 |  
1962  
1916

Point for the W.  $\frac{1}{4}$  sec. cor. of sec. 6 is on the W. bdy. and at 40.00 chains North of the closing corner of secs. 6 and 7.

Set the iron post on solid rock, mound with stones to top, cap mkd.

T15N  
R12W R11W  
      |  $\frac{1}{4}$   
      | S. 6  
1962

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 6 bears South 2.07 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  sec. cor. of sec. 1, T. 15 N., R. 12 W. only, marks altered to

Subdivisional Lines, T. 15 N., R. 11 W., Arizona

Chains

T15N  
R12W R11W  
1/4 |  
S 1 |  
1962  
1916

From the cor. of secs. 5, 6, 7 and 8.

N. 0°03' W., bet. secs. 5 and 6.

Over broken mountainous land; desc. gentle N. slope.

1.60 Bottom of draw, drains N. 70° W.; asc. rocky S. slope.

6.20 Rocky spur, slopes S. 75° W.

10.50 Begin descent over ledgy N. slope.

34.20 Wash, 30 lks. wide, 2 ft. deep, drains N. 30° W.

39.50 Spur, slopes W.

40.00 Point for the 1/4 sec. cor. of secs. 5 and 6.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T15N R11W  
1/4  
S 6 | S 5  
1962

Desc. over NW. slope through heavy brush.

57.50 Wash, 30 lks. wide, 3 ft. deep, drains NE.

62.10 Low spur, slopes NE.; desc. over gentle N. slope.

78.15 Intersect the N. bdy. of the township.

Point for the closing corner of secs. 5 and 6.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

T16N R11W  
S 31  
S 6 | S 5  
T15N R11W  
C C  
1962

The cor. of secs. 5, 6, 31 and 32 bears East, 5.19 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the cor. of secs. 31 and 32, T. 16 N., R. 11 W., only, marks altered to

T16N R11W  
S 31 | S 32  
S 5  
T15N R11W  
1962  
1916

## Subdivisional Lines, T. 15 N., R. 11 W., Arizona

## Chains

Land, mountainous.  
Soil, rocky clay loam.  
Timber, none; undergrowth, brush, catclaw, oak, cactus, greasewood and grass.

Point for the N.  $\frac{1}{4}$  sec. cor. of sec. 5 is on the N. bdy. of the township at mid-point bet. closing corners.

Set the iron post 14 inches in the ground, mound with stones to top, cap mkd.

T16N

$\frac{1}{4}$  S 5

T15N R11W

1962

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 32 bears East, 5.29 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  sec. cor. of sec. 32, T. 16 N., R. 11 W., only, marks altered to

S 32

$\frac{1}{4}$

1962

1916

Point for the N.  $\frac{1}{4}$  sec. cor. of sec. 6 is 40.00 chains West of the closing corner of secs. 5 and 6, and on the N. bdy. of the township.

Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.

T16N

$\frac{1}{4}$  S 6

T15N R11W

1962

The  $\frac{1}{4}$  sec. cor. of secs. 6 and 31 bears East, 5.19 chs. dist., monumented by an iron post, 1 inch diam., set, mkd. and witnessed as described in the official record. This cor. now functions as the  $\frac{1}{4}$  sec. cor. of sec. 31, T. 16 N., R. 11 W., only, marks altered to

S 31

$\frac{1}{4}$

1962

1916

## GENERAL DESCRIPTION

Township 15 North, Range 11 West is located in the Burro Cliffs and is for the most part steep mountainous land cut by numerous washes and gullies, the highest elevations being the prominent black mesa extending through sections 4 and 5, while the lower elevations are the washes located in the southern portion of the township which drain the east and central area southerly into Burro Creek. The extreme north and northwest part of the township is drained northwesterly by tributaries of Sycamore Creek. The west area is drained westerly, emptying into the Big Sandy. Kaiser Spring Canyon drains the area in the southwest.

Township 15 North, Range 11 West, G. & S. R. Meridian, Arizona

Chains

The grazing of livestock is at the present time the predominating interest as there is a moderate growth of grass and browse throughout the township, with several springs and windmills affording a continued water supply.

A good bladed road leading from Highway 93 to Bagdad extends east and west through the southern part of the township with several roads branching off to give access to most of the area.





55

BOOK 4651

### CERTIFICATE OF CADASTRAL ENGINEER

I, Boyd S Owens, HEREBY CERTIFY upon honor that, in  
 pursuance of special instructions bearing date of the 4 th day of November, 1960,  
 I have surveyed the subdivisional lines of Township 15 North, Range 11 West and  
dependently resurveyed the East bdy. of sec. 36, T. 15 N., R. 12 West  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 of the G&SR Meridian, in the State of Arizona, which are  
 represented in the foregoing field notes as having been executed by me and under my direction; and that  
 said survey has been made in strict conformity with said instructions, the Manual of Instructions for the  
 Survey of the Public Lands of the United States, and in the specific manner described in the foregoing  
 field notes.

Phoenix, Ariz.  
July 27, 1962

Boyd S Owens  
 Cadastral Surveyor

### CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
 Washington, D. C., MAR 13 1963, 19\_\_\_\_

The foregoing field notes of the survey of the subdivisional lines of Township 15 North,  
Range 11 West and the dependent resurvey of the east boundary of Section 36,  
Township 15 North, Range 12 West, of the Gila and Salt River Base and Meridian

executed by Boyd S. Owens, Cadastral Surveyor,  
 having been critically examined and found correct, are hereby approved.

E. J. Hennington  
 Cadastral Engineering Staff Officer,  
 Chief, Division of Engineering

### CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in  
T. 15 N., R. 11 W., is a true copy of the original field notes.~~

~~\_\_\_\_\_  
 Cadastral Engineering Staff Officer.~~