

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Subdivisions

of

Township 3 South, Range 12 West

Of the Gila and Salt River *Meridian,*

In the State of Arizona

EXECUTED BY

Horace G. Parker, Cadastral Surveyor

Under special instructions dated July 30 *, 1959, which provided*
for the surveys included under Group No. 339, approved August 7, 1959
and assignment instructions dated February 17 *, 19 60.*

Survey commenced March 25 *, 19 60.*

Survey completed February 28 *, 19 61.*

1A

BOOK 4654

INDEX DIAGRAM

Township 3 South, Range 12 West
 White and Hiester - 1941

Parker - 1960	35	35	26	19	13	7
	•	34	•	25	•	6
	34	33	25	18	12	5
	7	32	•	24	•	5
	32	31	24	17	11	4
	18	31	17	23	16	4
30	30	22	17	16	10	3
19	29	20	22	21	15	9
29	28	21	15	15	9	3
30	28	20	14	27	8	2
27	27	20	14	14	8	2
31	26	22	13	24	7	1
		20	20	28	7	28

Crain - 1957

Heise - 1914

GPO 866119

Township 3 South, Range 12 West, Arizona

1. B

Chains

The south boundary was surveyed in 1914 by J. F. Hesse. The north boundary was surveyed in 1941 by Hiester and White. The east boundary was surveyed in 1957-58 by D. A. Crain. The west boundary was surveyed concurrently under this group.

The following notes are those of the survey of the subdivisional lines of Township 3 South, Range 12 West, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated July 30, 1959.

True bearings and horizontal distances for the surveyed lines are given in these notes. All corners were monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: 33°07'00" N. latitude and 113°26'37" W. longitude. The magnetic declination was found to be 15° East.

Subdivision of T. 3 S., R. 12 W.

Beginning at the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

N. 0°01' W., bet. secs. 35 and 36.

Over nearly level land, through scattered timber and undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 35 and 36.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
¼
S 35 | S 36
1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.

64.50 Wash, 50 lks. wide, 4 ft. deep, drains SE.

80.00 Point for the cor. of secs. 25, 26, 35, and 36.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
S 26 | S 25
S 35 | S 36
1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.

Land, nearly level.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca and greasewood.

Chains

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., marked by an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the official record.

West, bet. secs. 25 and 36.

Over slightly rolling land, through scattered timber and undergrowth.

10.50 Wash, 20 lks. wide, 3 ft. deep, drains S.

27.00 Wash, 25 lks. wide, 3 ft. deep, drains S.

40.00 Point for the ¼ sec. cor. of secs. 25 and 36.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
S 25
¼ ———
S 36
1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of corner.

80.00 The cor. of secs. 25, 26, 35, and 36.

Land, slightly rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°01' W., bet. secs. 25 and 26.

Over slightly rolling land, through scattered timber and undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 25 and 26.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
¼
S 26 | S 25
1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

51.50 Wash, 10 lks. wide, 3 ft. deep, drains SE.

52.80 Fence, barbed wire, bears E. and W.

80.00 Point for the cor. of secs. 23, 24, 25 and 26.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
S 23 | S 24
S 26 | S 25
1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.

Subdivision of T. 3 S., R. 12 W., Arizona

3.

Chains

Land, slightly rolling.
Soil, gravel, sandy clay and loam.
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., marked by an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the official record.

S. 89°58' W., bet. secs. 24 and 25.

40.00 Over slightly rolling land, through scattered timber and undergrowth.
Point for the ¼ sec. cor. of secs. 24 and 25.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \text{S 24} \\ \hline \frac{1}{4} \text{ S 25} \\ 1960 \end{array}$$

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of corner.

49.70 Wash, 15 lks. wide, 2 ft. deep, drains S.

80.00 The cor. of secs. 23, 24, 25 and 26.

Land, slightly rolling.
Soil, gravel, sandy clay and loam.
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°01' W., bet. secs. 23 and 24.

40.00 Over slightly rolling land, through scattered timber and undergrowth.
Point for the ¼ sec. cor. of secs. 23 and 24.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S, R12W} \\ \frac{1}{4} \\ \text{S 23 | S 24} \\ 1960 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

63.00 Wash, 10 lks. wide, 3 ft. deep, drains S. 30° W.

80.00 Point for the cor. of secs. 13, 14, 23 and 24.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \text{S 14 | S 13} \\ \hline \text{S 23 | S 24} \\ 1960 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Land, slightly rolling.
Soil, gravel, sandy clay and loam.
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., marked by an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the official record.

N. 89°55' W., bet. secs. 13 and 24.

40.02 Over nearly level land, through scattered timber and undergrowth.
Point for the ¼ sec. cor. of secs. 13 and 24.

Set the iron post 24 ins. in the ground, with brass cap mkd.

Chains	
	<p style="text-align: center;">T3S R12W $\frac{1}{2}$ $\frac{S\ 13}{S\ 24}$ 1960</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.</p>
48.30	Wash, 20 lks. wide, 2 ft. deep, drains S. 10° W.
75.10	Wash, 10 lks. wide, 3 ft. deep, drains S. 10° W.
80.04	The cor. of secs. 13, 14, 23, and 24.
	<p>Land, slightly rolling. Soil, gravel, sandy clay and loam. Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.</p>
	<p>N. 0°01' W., bet. secs. 13 and 14. Over slightly rolling land, through scattered timber and undergrowth.</p>
30.80	Wash, 10 lks. wide, 1 ft. deep, drains S. 20° E.
40.00	Point for the ¼ sec. cor. of secs. 13 and 14.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T3S R12W $\frac{1}{4}$ $\frac{S\ 14\ S\ 13}{1960}$</p>
80.00	<p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of corner. Point for the cor. of secs. 11, 12, 13 and 14.</p>
	Set the iron post 20 ins. in the ground, to solid rock, and in a collar of stone to top, with brass cap mkd.
	<p style="text-align: center;">T3S R12W $\frac{S\ 11\ S\ 12}{S\ 14\ S\ 13}$ 1960</p>
	<p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of corner. Land, slightly rolling. Soil, gravel, sandy clay and loam. Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.</p>
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., marked by an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the official record.</p>
	N. 89°55' W., bet. secs. 12 and 13.
	Over gently rolling land, through scattered timber and undergrowth.
3.10	Wash, 10 lks. wide, 1 ft. deep, drains S.
40.02	Point for the ¼ sec. cor. of secs. 12 and 13.
	Set the iron post 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T3S R12W $\frac{1}{4}$ $\frac{S\ 12}{S\ 13}$ 1960</p>
	Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of corner.

Subdivision of T. 3 S., R. 12 W., Arizona

5.

Chains

- 41.80 Wash, 10 lks. wide, $2\frac{1}{2}$ ft. deep, drains S. 10° W.
 51.10 Wash, 20 lks. wide, $2\frac{1}{2}$ ft. deep, drains S. 10° E.
 76.00 Wash, 20 lks. wide, 2 ft. deep, drains S. 20° E.
 80.04 The cor. of secs. 11, 12, 13, and 14.

Land, gently rolling.
 Soil, gravel, sandy clay and loam.
 Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. $0^\circ 01'$ W., bet. secs 11 and 12.

Over gently rolling land, through scattered timber and undergrowth.

- 14.80 Wash, 20 lks. wide, 2 ft. deep, drains S. 20° E.
 40.00 Point for the $\frac{1}{2}$ sec. cor. of secs. 11 and 12.

Set the iron post 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T3S R12W
 $\frac{1}{2}$
 S 11 | S 12
 1960

Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

- 80.00 Point for the cor. of secs. 1, 2, 11, and 12.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 S 2 | S 1
 S 11 | S 12
 1960

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

Land, slightly rolling.
 Soil, gravel, sandy clay and loam.
 Timber, palo verde and ironwood; undergrowth, cactus, yucca and greasewood.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., marked by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, marked and witnessed as described in the official record.

N. $89^\circ 55'$ W., bet. secs. 1 and 12.

Over gently rolling land, through scattered timber and undergrowth.

- 33.20 Wash, 100 lks. wide, $1\frac{1}{2}$ ft. deep, drains S. 15° W.
 40.01 Point for the $\frac{1}{2}$ sec. cor. of secs. 1 and 12.

Set the iron post 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

Chains

T3S R12W
 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{1}{12}$
 1960

Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of corner.

56.20 Wash, 30 lks. wide, $2\frac{1}{2}$ ft. deep, drains S. 20° W.

80.02 The cor. of secs. 1, 2, 11, and 12.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. $0^\circ 01'$ W., bet. secs. 1 and 2.

Over gently rolling land, through scattered timber and undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Set the iron post 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T3S R12W
 $\frac{1}{4}$
 S 2 | S 1
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

80.08 Intersect S. bdy. of sec. 35, T. 2 S., R. 12 W.

Point for the closing cor. of secs. 1 and 2.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R12W
 $\frac{S}{S}$ 35
 S 2 | S 1
 C | C
 T3S R12W
 1960

Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, S. of corner.

From this point, the $\frac{1}{4}$ sec. cor. of sec. 35, T. 2 S., R. 12 W. marked by an iron post, 1 inch diam., firmly set, marked and witnessed as described in the official record, bears West, 14.03 chs. dist.

From this same point, the cor. of secs. 35 and 36, T. 2 S., R. 12 W., marked by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record, bears East, 25.97 chs. dist.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

Subdivision of T. 3 S., R. 12 W., Arizona

7.

Chains

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the township.

At the cor. point

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R12W

$\frac{1}{4}$ S 1

T3S R12W

1960

Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, S. of corner.

From this point, the cor. of secs. 35 and 36, T. 2 S., R. 12 W., bears West, 14.03 chs. dist.

From this same point, the $\frac{1}{4}$ sec. cor. of sec. 36, T. 2 S., R. 12 W., marked by an iron post, 1 in. diam., firmly set marked and witnessed as described in the official record, bears East, 25.97 chs. dist.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

N. $0^{\circ}01'$ W., bet. secs. 34 and 35.

Over slightly rolling land, through scattered timber and undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W

$\frac{1}{4}$

S 34 | S 35

1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Continue over gently rolling land.

46.30 Wash, 100 lks. wide, 3 ft. deep, drains SE.

49.50 Wash, 20 lks. wide, 1 ft. deep, drains SE.

80.00 Point for the cor. of secs. 26, 27, 34, and 35.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W

S 27 | S 26

S 34 | S 35

1960

Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

Land, slightly and gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

Chains

From the cor. of secs. 25, 26, 35 and 36.

S. 89°58' W., bet. secs. 26 and 35.

Over gently rolling land, through scattered timber and undergrowth.

14.00 Wash, 30 lks.wide, 2 ft. deep, drains SE.

40.03 Point for the 1/2 sec. cor. of secs. 26 and 35.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 1/2 S 26
 S 35
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

49.75 Wash, 10 lks. wide, 5 ft. deep, drains S. 10° E.

64.75 Fence, barbed wire, bears N. and S.

74.60 Road, partially graded, bears N. and S.

80.06 The cor. of secs. 26, 27, 34 and 35.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°01' W., bet. secs. 26 and 27.

Over gently rolling land, through scattered timber and undergrowth.

40.00 Point for the 1/2 sec. cor. of secs. 26 and 27.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 1/2
 S 27 | S 26
 1960

Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W. of corner.

80.00 Point for the cor. of secs. 22, 23, 26 and 27.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 S 22 | S 23
 S 27 | S 26
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

Subdivision of T. 3 S., R. 12 W., Arizona

Chains

From the cor. of secs. 23, 24, 25, and 26.

S. 89°57' W., bet. secs. 23 and 26.

Over gently rolling land, through scattered timber and undergrowth.

11.80 Wash, 20 lks. wide, 1½ ft. deep, drains S.

37.70 Wash, 10 lks. wide, 1 ft. deep, drains S. 10° E.

40.04 Point for the ¼ sec. cor. of secs. 23 and 26.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 ¼ S 23
 S 26
 1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of corner.

63.20 Road, partially graded, bears N. and S.

75.10 Wash, 20 lks. wide, 2 ft. deep, drains S.

80.08 The cor. of secs. 22, 23, 26 and 27.

Land, gently rolling.
 Soil, gravel, sandy clay and loam.
 Timber, palo verde and ironwood; undergrowth, cactus, yucca, and
 greasewood.

N. 0°01' W., bet. secs. 22 and 23.

Over slightly rolling land, through scattered timber and undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 22 and 23.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 ¼ S 22 | S 23
 1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.

80.00 Point for the cor. of secs. 14, 15, 22, and 23.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
S 15 | S 14
S 22 | S 23
 1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.

Land, gently and slightly rolling.
 Soil, gravel, sandy clay and loam.
 Timber, palo verde and ironwood; undergrowth, cactus, yucca, and
 greasewood.

Chains

From the cor. of secs. 13, 14, 23, and 24.

S. 89°58' W., bet. secs. 14 and 23.

Over gently rolling land, through scattered timber and undergrowth.

11.80 Wash, 10 lks. wide, 3 ft. deep, drains S. 10° E.

39.99 Point for the ¼ sec. cor. of secs. 14 and 23.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 $\frac{1}{4}$ S 14
 S 23
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

42.60 Road, partially graded, bears N. 15° E. and S. 15° W.

50.20 Wash, 20 lks. wide, 1½ ft. deep, drains S.

74.10 Wash, 10 lks. wide, 1 ft. deep, drains S.

79.98 The cor. of secs. 14, 15, 22, and 23.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°01' W., bet. secs. 14 and 15.

Over gently rolling land, through scattered timber and undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 14 and 15.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 $\frac{1}{4}$
 S 15 | S 14
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

59.80 Wash, 30 lks. wide, 3 ft. deep, drains SW.

80.00 Point for the cor. of secs. 10, 11, 14, and 15.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
S 10 | S 11
 S 15 | S 14
 1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

Chains

From the cor. of secs. 11, 12, 13, and 14.

S. 89°55' W., bet. secs. 11 and 14.

Over gently rolling land, through scattered timber and undergrowth.

30.20 Road, partially graded, bears N. 10° E. and S. 10° W.

39.99 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T3S R12W} \\ \frac{1}{4} \frac{\text{S 11}}{\text{S 14}} \\ 1960 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

74.70 Wash, 40 lks. wide, 3 ft. deep, drains S.

77.80 Wash, 10 lks. wide, 2½ ft. deep, drains S.

79.98 The cor. of secs. 10, 11, 14, and 15.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°01' W., bet. secs. 10 and 11.

Over gently rolling land, through scattered timber and undergrowth.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T3S R12W} \\ \frac{1}{4} \\ \text{S 10} | \text{S 11} \\ 1960 \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

80.00 Point for the cor. of secs. 2, 3, 10, and 11.

Set the iron post 16 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} \text{T3S R12W} \\ \text{S 3} | \text{S 2} \\ \text{S 10} | \text{S 11} \\ 1960 \end{array}$$

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

Chains	
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°57' W., bet. secs. 2 and 11.</p> <p>Over gently rolling land, through scattered timber and undergrowth.</p>
8.80	Wash, 10 lks. wide, 3 ft. deep, drains S.
30.60	Wash, 5 lks. wide, 3 ft. deep, drains S.
32.80	Road, partially graded, bears NE. and SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.
	<p>Set the iron post 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3S R12W</p> <p>$\frac{1}{4}$ <u>S 2</u></p> <p>S 11</p> <p>1960</p> </div> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.</p>
50.50	Wash, 10 lks. wide, 4 ft. deep, drains S.
80.00	The cor. of secs. 2, 3, 10 and 11.
	<p>Land, gently rolling.</p> <p>Soil, gravel, sandy clay and loam.</p> <p>Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.</p>
	<p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over gently rolling land, through scattered timber and undergrowth.</p>
13.90	Wash, 10 lks. wide, 1 ft. deep, drains SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	<p>Set the iron post 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3S R12W</p> <p>$\frac{1}{4}$</p> <p>S 3 S 2</p> <p>1960</p> </div> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.</p>
68.00	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° E.
80.09	Intersect S. bdy of sec. 34, T. 2 S., R. 12 W.
	<p>Point for the closing cor. of secs. 2 and 3.</p> <p>Set the iron post 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T2S R12W</p> <p>S 34</p> <hr/> <p>S 3 S 2</p> <p>C C</p> <p>T3S R12W</p> <p>1960</p> </div> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, S. of corner.</p> <p>From this point, the $\frac{1}{4}$ sec. cor. of sec. 34, T. 2 S., R. 12 W.,</p>

Chains

marked by an iron post, 1 in. diam., firmly set, marked and witnessed as described in the official record, bears West; 14.05 chs. dist.

From this same point, the cor. of secs. 34 and 35, T. 2 S., R. 12 W., marked by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record, bears East; 25.95 chs. dist.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 2 is at midpoint and on the N. bdy. of the township.

At the corner point

Set the iron post 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

T2S R12W

$\frac{1}{4}$ S 2

T3S R12W

1960

Raise a mound of stone, 3 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, S. of corner.

From this point, the cor. of secs. 34 and 35, T. 2 S., R. 12 W., bears West, 14.04 chs. dist.

From this same point, the $\frac{1}{4}$ sec. cor. of sec. 35, T 2 S., R. 12 W., bears East; 25.96 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

N. 0°02' W., bet. secs. 33 and 34.

Over gently rolling land, through scattered timber and undergrowth.

8.75 Wash, 20 lks. wide, 2 ft. deep, drains SE.

29.20 Wash, 15 lks. wide, 2 ft. deep, drains SE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W

$\frac{1}{4}$

S 33 | S 34

1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

79.95 Wash, 5 lks. wide, 1 $\frac{1}{2}$ ft. deep, drains E.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W

S 28 | S 27

S 33 | S 34

1960

Raise a mound of stone, 3 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.

Chains

Land, gently rolling.
Soil, gravel, sandy clay and loam.
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 26, 27, 34 and 35.

S. 89°55' W., bet. secs. 27 and 34.

Over gently rolling land, through scattered timber and undergrowth.

23.10 Wash, 140 lks. wide, 2½ ft. deep, drains S.

30.20 Wash, 50 lks. wide, 2½ ft. deep, drains SE.

33.30 Wash, 10 lks. wide, 2 ft. deep, drains SE.

40.01 Point for the ¼ sec. cor. of secs. 27 and 34.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \frac{1}{4} \text{ S } 27 \\ \hline \text{S } 34 \\ 1960 \end{array}$$

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of corner.

40.50 Wash, 40 lks. wide, 1 ft. deep, drains S.

56.10 Wash, 50 lks. wide, 3 ft. deep, drains S. 15° E.

79.20 Wash, 10 lks. wide, 2 ft. deep, drains S.

80.02 The cor. of secs. 27, 28, 33 and 34.

Land, gently rolling.
Soil, gravel, sandy clay and loam.
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°02' W., bet. secs. 27 and 28.

Over gently rolling land, through scattered timber and undergrowth.

2.30 Wash, 10 lks. wide, 1 ft. deep, drains SE.

14.90 Wash, 20 lks. wide, 2 ft. deep, drains S. 10° E.

40.00 Point for the ¼ sec. cor. of secs. 27 and 28.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \frac{1}{4} \\ \text{S } 28 \text{ | } \text{S } 27 \\ 1960 \end{array}$$

Raise a mound of stone, 3½ ft. base, 2½ ft. high,
W. of corner.

Chains

79.00 Wash, 20 lks. wide, 2 ft. deep, drains SE.

80.00 Point for the cor. of secs. 21, 22, 27 and 28.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 S 21 | S 22
 S 28 | S 27
 1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.

Land, gently rolling.
 Soil, gravel, sandy clay and loam.
 Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 22, 23, 26, and 27.

S. 89°58' W., bet. secs. 22 and 27.

Over gently rolling land, through scattered timber and undergrowth.

27.90 Wash, 12 lks. wide, 2 ft. deep, drains S. 10° E.

33.80 Wash, 120 lks. wide, 4 ft. deep, drains S. 10° E.

39.98 Point for the ¼ sec. cor. of secs. 22 and 27.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 S 22
 ¼ ———
 S 27
 1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of corner.

52.50 Wash, 35 lks. wide, 3 ft. deep, drains S. 15° E.

69.90 Wash, 20 lks. wide, 2 ft. deep, drains S. 15° E.

78.30 Wash, 15 lks. wide, 1 ft. deep, drains S.

79.96 The cor. of secs. 21, 22, 27 and 28.

Land, gently rolling.
 Soil, gravel, sandy clay and loam.
 Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°02' W., bet. secs. 21 and 22.

Over gently rolling land, through scattered timber and undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 21 and 22.

Set the iron post 24 ins. in the ground, with brass cap mkd.

BOOK 4001

16

Chains

T3S R12W
 $\frac{1}{2}$
 S 21 | S 22
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

74.60 Wash, 40 lks. wide, 2 ft. deep, drains SE.

79.60 Point selected for the witness cor. of secs. 15, 16, 21, and 22.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 S 16 | S 15
 S 21 | S 22
 W C
 1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.

80.00 Point for the cor. of secs. 15, 16, 21, and 22, not monumented, falls in center of a sandy wash, 20 lks. wide, 3 ft. deep, draining SE.

Land, gently rolling.
 Soil, gravel, sandy clay and loam.
 Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 14, 15, 22 and 23.

S. 89°58' W., bet. secs. 15 and 22.

Over gently rolling land, through scattered timber and undergrowth.

24.20 Wash, 30 lks. wide, 3 ft. deep, drains S.

37.70 Wash, 60 lks. wide, 3 ft. deep, drains S.

40.01 Point for the ¼ sec. cor. of secs. 15 and 22.

Set the iron post 15 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T3S R12W
 $\frac{1}{4}$ S 15
 S 22
 1960

53.50 Wash, 180 lks. wide, 4 ft. deep, drains S. 10° E.

59.60 Wash, 50 lks. wide, 2 ft. deep, drains S. 10° E.

72.40 Wash, 100 lks. wide, 2 ft. deep, drains S. 20° E.

80.02 The true point for the cor. of secs. 15, 16, 21, and 22.

Land, gently rolling.
 Soil, gravel, sandy clay and loam.
 Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

Subdivision of T. 3 S., R. 12 W., Arizona

17.

Chains

N. 0°02' W., bet. secs. 15 and 16.

Over gently rolling land, through scattered timber and undergrowth.

10.40 Wash, 20 lks. wide, 2 ft. deep, drains SE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.

Set the iron post 15 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T3S R12W

 $\frac{1}{4}$ S 16 | S 15
1960

68.70 Wash, 25 lks. wide, 2 ft. deep, drains SE.

80.00 Point for the cor. of secs. 9, 10, 15, and 16.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W

S 9 | S 10
S 16 | S 15
1960Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 10, 11, 14, and 15.

West, bet. secs. 10 and 15.

Over gently rolling land, through scattered timber and undergrowth.

2.90 Wash, 10 lks. wide, 2 ft. deep, drains S.

35.30 Wash, 10 lks. wide, 2 ft. deep, drains S.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W

 $\frac{1}{4}$ S 10
S 15
1960Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of corner.

57.50 Wash, 100 lks. wide, 3 ft. deep, drains S.

80.02 The cor. of secs. 9, 10, 15, and 16.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

Chains

N. 0°02' W., bet. secs. 9 and 10.

Over gently rolling land, through scattered timber and undergrowth.

18.70 Wash, 25 lks. wide, 2½ ft. deep, drains E.

26.50 Wash, 55 lks. wide, 3 ft. deep, drains E.

40.00 Point for the ¼ sec. cor. of secs. 9 and 10.

Set the iron post 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T3S R12W

¼

S 9 | S 10

1960

52.00 Wash, 100 lks. wide, 3 ft. deep, drains S. 20° W.

72.90 Same wash, 100 lks. wide, 2 ft. deep, drains SE.

79.78 Point selected for the witness cor. of secs. 3, 4, 9, and 10.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W

S 4 | S 3

S 9 | S 10

W C

1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.

80.00 True point for the cor. of secs. 3, 4, 9, and 10, not monumented, falls in bottom of sandy wash, 100 lks. wide, and is deemed unsafe for the corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 2, 3, 10 and 11.

S. 89°57' W., bet. secs. 3 and 10.

Over gently rolling land, through scattered timber and undergrowth.

6.80 Wash, 10 lks. wide, 2 ft. deep, drains S.

10.10 Wash, 10 lks. wide, 2 ft. deep, drains S.

40.01 Point for the ¼ sec. cor. of secs. 3 and 10.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W

S 3

¼ S 10

1960

Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of corner.

Subdivision of T. 3 S., R. 12 W., Arizona

19.

Chains

54.80 Wash, 10 lks. wide, 2 ft. deep, drains S. 10° W.

80.02 The true point for the cor. of secs. 3, 4, 9, and 10.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°02' W., bet. secs. 3 and 4.

Over gently rolling land, through scattered timber and undergrowth.

40.00 Point for the $\frac{1}{2}$ sec. cor. of secs. 3 and 4.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W

 $\frac{1}{2}$

S 4 | S 3

1960

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.

80.14 Intersect S. bdy of sec. 33, T. 2 S., R. 12 W.

Point for the closing cor. of secs. 3 and 4.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R12W

S 33

S 4 | S 3

C | C

T 3 S

1960

Raise a mound of stone, 3 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, S. of corner.From this point, the witness $\frac{1}{2}$ sec. cor. of sec. 33, T. 2 S., R. 12 W., marked by an iron post, 1 in. diam., firmly set, marked and witnessed as described in the official record, bears West, 15.03 chs. dist.

From this same point, the cor. of secs. 33 and 34, T. 2 S., R. 12 W., marked by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record, bears East, 25.97 chs. dist.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

The point for the N. $\frac{1}{2}$ sec. cor. of sec. 3 is at midpoint and on the N. bdy. of the township.

At the cor. point

Set an iron post 24 ins. in the ground, with brass cap mkd.

Chains	
	<p>T2S R12W $\frac{1}{4}$ S 3 T3S R12W 1960</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of corner.</p> <p>From this point, the cor. of secs. 33 and 34, T. 2 S., R. 12 W. bears West, 14.04 chs. dist.</p> <p>From the same point, the $\frac{1}{4}$ sec. cor. of sec. 34, T. 2 S., R. 12 W., bears East 25.96 chs. dist.</p>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., firmly set in the ground, marked and witnessed as described in the official record.</p> <p>N. 0°02' W., bet. secs. 32 and 33.</p> <p>Over gently rolling land, through scattered timber and undergrowth.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.</p> <p>Set the iron post 24 ins. in the ground, with brass cap mkd.</p>
	<p>T3S R12W $\frac{1}{4}$ S 32 S 33 1960</p>
79.80	<p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains S. 80° E.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set the iron post 24 ins. in the ground, with brass cap mkd.</p>
	<p>T3S R12W $\frac{1}{4}$ S 29 S 28 S 32 S 33 1960</p>
	<p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of corner.</p> <p>Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°58' W., bet. secs. 28 and 33.</p> <p>Over slightly rolling land, through scattered timber and undergrowth.</p>
15.00	<p>Wash, 20 lks. wide, 2 ft. deep, drains S. 20° E.</p>
32.90	<p>Wash, 20 lks. wide, 3 ft. deep, drains S.</p>

Chains

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 $\frac{1}{4}$ S 28
 S 33
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

80.00

The cor. of secs. 28, 29, 32, and 33.

Land, slightly rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°02' W., bet. secs. 28 and 29.

Over gently rolling land, through scattered timber and undergrowth.

12.90

Wash, 10 lks wide, 2 ft. deep, drains E.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 $\frac{1}{4}$
 S 29 | S 28
 1960

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

80.00

Point for the cor. of secs. 20, 21, 28, and 29.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
S 20 | S 21
S 29 | S 28
 1960

Land, slightly rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 21, 22, 27 and 28.

N. 89°57' W., bet. secs. 21 and 28.

Over gently rolling land, through scattered timber and undergrowth.

4.50

Wash, 10 lks. wide, course S.

30.00

Wash, 15 lks. wide, course SE.

40.03

Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.

Set the iron post 24 ins. in the ground, with brass cap mkd.

Chains

T3S R12W
 $\frac{1}{2}$ $\frac{S\ 21}{S\ 28}$
 1961

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.

48.00 Wash, 15 lks. wide, course S. 20° E.

63.00 Wash, 5 lks. wide, course S. 20° E.

80.06 The cor. of secs. 20, 21, 28 and 29.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. $0^\circ 02'$ W., bet. secs. 20 and 21.

Over gently rolling land, through scattered timber and undergrowth.

32.80 Wash, 10 lks. wide, course SE.

39.20 Wash, 20 lks. wide, course SE.

40.00 Point for the $\frac{1}{2}$ sec. cor. of secs. 20 and 21, not monumented, falls in wash.

41.10 Point selected for the witness $\frac{1}{2}$ sec. cor. of secs. 20 and 21.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 $\frac{1}{2}$
 $S\ 20 \downarrow S\ 21$
 W C
 1961

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

80.00 Point for the cor. of secs. 16, 17, 20, and 21.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 $\frac{S\ 17 \mid S\ 16}{S\ 20 \mid S\ 21}$
 1961

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the true point for the cor. of secs. 15, 16, 21 and 22.

S. $89^\circ 58'$ W., bet. secs. 16 and 21.

Chains

Over gently rolling land, through scattered timber and undergrowth.

33.20 Wash, 30 lks. wide, course S. 20° E.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \frac{1}{4} \frac{\text{S 16}}{\text{S 21}} \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.

63.50 Wash, 5 lks. wide, course SE.

80.02 The cor. of secs. 16, 17, 20 and 21.

Land, slightly rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°02' W., bet. secs. 16 and 17.

Over gently rolling land, through scattered timber and undergrowth.

32.10 Wash, 20 lks. wide, course S. 80° E.

36.50 Wash, 30 lks. wide, course S. 80° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \frac{1}{4} \\ \text{S 17} \mid \text{S 16} \\ 1961 \end{array}$$

44.40 Wash, 20 lks. wide, course E.

80.00 Point for the cor. of secs. 8, 9, 16 and 17.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \text{S 8} \mid \text{S 9} \\ \text{S 17} \mid \text{S 16} \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

24

Subdivision of T. 3 S., R. 12 W., Arizona

24.

Chains

From the cor. of secs. 9, 10, 15, and 16.

N. 89°59' W., bet. secs. 9 and 16.

Over gently rolling land, through scattered timber and undergrowth.

19.00 Wash, 15 lks. wide, course SE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \frac{1}{4} \text{ S } 9 \\ \hline \text{S } 16 \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.

68.00 Wash, 20 lks. wide, course S. 20° E.

80.00 The cor. of secs. 8, 9, 16 and 17.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°02' W., bet. secs. 8 and 9.

Over gently rolling land, through scattered timber and undergrowth.

39.80 Wash, 20 lks. wide, course S. 60° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \frac{1}{4} \\ \text{S } 8 | \text{S } 9 \\ \hline 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

63.50 Wash, 30 lks. wide, course S. 60° E.

80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \text{S } 5 | \text{S } 4 \\ \hline \text{S } 8 | \text{S } 9 \\ 1961 \end{array}$$

Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

Chains

From the true point for the cor. of secs. 3, 4, 9 and 10.

S. 89°57' W., bet. secs. 4 and 9.

Over gently rolling land, through scattered timber and undergrowth.

10.70 Wash, 100 lks. wide, course S. 20° E.

17.20 Wash, 30 lks. wide, course S. 20° E.

34.40 Wash, 5 lks. wide, course S. 30° E.

40.00 Point for the $\frac{1}{2}$ sec. cor. of secs. 4 and 9.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 $\frac{1}{2}$ S 4
S 9
1961

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of corner.

56.90 Wash, 20 lks. wide, drains S. 20° W.

80.00 The cor. of secs. 4, 5, 8 and 9.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 0°02' W., bet. secs. 4 and 5.

Over gently rolling land, through scattered timber and undergrowth.

14.60 Wash, 30 lks. wide, drains S. 80° E.

22.70 Wash, 10 lks. wide, drains S. 80° E.

37.20 Wash, 20 lks. wide, drains E.

40.00 Point for the $\frac{1}{2}$ sec. cor. of secs. 4 and 5.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 $\frac{1}{2}$
S 5 | S 4
1961

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.

53.80 Wash, 20 lks. wide, drains E.

73.90 Wash, 5 lks. wide, drains E.

80.20 Intersect S. bdy. of sec. 32, T. 2 S., R. 12 W.

Point for the closing cor. of secs. 4 and 5.

Set the iron post 24 ins. in the ground, with brass cap mkd.

Chains

T2S R12W
 S 32
 S 5 | S 4
 C | C
 T3S R12W
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of corner.
 From this point the ¼ sec. cor. of sec. 32, T. 2 S., R. 12 W., bears West, 13.89 chs. dist., marked by an iron post, 1 in. diam., firmly set, marked and witnessed as described in the official record.

From the same point the cor. of secs. 32 and 33, T. 2 S., R. 12 W., bears East, 26.11 chs. dist., marked by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

The point for the N. ¼ sec. cor. of sec. 4 is at midpoint and on the N. bdy. of the township.

At the cor. point

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R12W
 ¼ S 4
 T3S R12W
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of corner.

From this point the cor. of secs. 32 and 33, T. 2 S., R. 12 W., bears West, 13.96 chs. dist.

From the same point the witness ¼ sec. cor. of sec. 33, T. 2 S., R. 12 W., bears West, 25.04 chs. dist.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record.

N. 0°03' W., bet. secs. 31 and 32.

Over gently rolling land, through scattered timber and undergrowth.

26.00 Wash, 10 lks. wide, drains E.

35.60 Wash, 10 lks. wide, drains E.

40.00 Point for the ¼ sec. cor. of secs. 31 and 32.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 ¼
 S 31 | S 32
 1961

Chains

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

44.80 Wash, 10 lks. wide, course SE.

80.00 Point for the cor. of secs. 29, 30, 31, and 32.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \hline \text{S } 30 \mid \text{S } 29 \\ \text{S } 31 \mid \text{S } 32 \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 28, 29, 32 and 33.

S. 89°57' W., bet. secs. 29 and 32.

Over gently rolling land, through scattered timber and undergrowth.

5.00 Wash, 10 lks. wide, drains S. 80° E.

40.01 Point for the ¼ sec. cor. of secs. 29 and 32.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \hline \frac{1}{4} \text{ S } 29 \\ \text{S } 32 \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.

46.80 Trail road, bears N. 20° W. and S. 20° E.

62.70 Wash, 20 lks. wide, drains S. 10° E.

80.02 The cor. of secs. 29, 30, 31, and 32.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. 89°57' W., bet. secs. 30 and 31.

Over gently rolling land, through scattered timber and undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 30 and 31.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \hline \frac{1}{4} \text{ S } 30 \\ \text{S } 31 \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Chains

79.07 The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, marked and witnessed as described in the field notes of the E. bdy. of T. 3 S., R. 13 W., surveyed under this group.

Land, gently rolling.
Soil, gravel, sandy clay and loam.
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 29, 30, 31, and 32.

N. 0°03' W., bet. secs. 29 and 30.

Over gently rolling land, through scattered timber and undergrowth.

32.00 Wash, 20 lks. wide, drains SE.

40.00 Point for the ¼ sec. cor. of secs. 29 and 30.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
¼
S 30 | S 29
1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

53.60 Wash, 20 lks. wide, drains SE.

76.20 Low spur, slopes SW.

79.80 Trail road, bears NW. and SE.

80.00 Point for the cor. of secs. 19, 20, 29, and 30.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
S 19 | S 20
S 30 | S 29
1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Land, gently rolling.
Soil, gravel, sandy clay and loam.
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 20, 21, 28, and 29.

N. 89°59' W., bet. secs. 20 and 29.

Over gently rolling land, through scattered timber and undergrowth.

40.03 Point for the ¼ sec. cor. of secs. 20 and 29.

Set the iron post 24 ins. in the ground, with brass cap mkd.

Chains

T3S R12W
 $\frac{1}{4}$ S 20
 S 29
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.

- 41.00 Wash, 10 lks. wide, drains SE.
 72.50 Wash, 10 lks. wide, drains SE.
 80.06 The cor. of secs. 19, 20, 29 and 30.

Land, gently rolling.
 Soil, gravel, sandy clay and loam.
 Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

S. 89°58' W., bet. secs. 19 and 30.

Over gently rolling land, through scattered timber and undergrowth.

- 0.20 Road, bears NW. and SE.
 10.40 Rocky spur, slopes SE.
 18.00 Wash, 20 lks. wide, drains SE.
 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.

Set the iron post 24 ins. in the ground, with brass cap mkd.

T3S R12W
 $\frac{1}{4}$ S 19
 S 30
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of corner.

- 75.20 Wash, 50 lks. wide, drains S.
 78.92 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.; marked by an iron post, 2½ ins. diam., set, marked and witnessed as described in the field notes of the E. bdy. of T. 3S., R. 13 W., surveyed under this group.

Land, gently rolling.
 Soil, gravel, sandy clay and loam.
 Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 19, 20, 29 and 30.

N. 0°03' W., bet. secs. 19 and 20.

Over gently rolling land, through scattered timber and undergrowth.

- 9.60 Wash, 15 lks. wide, drains SE.

Chains

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T3S\frac{1}{4}R12W \\ S\ 19|S\ 20 \\ 1961 \end{array}$$
Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

80.00

Point for the cor. of secs. 17, 18, 19 and 20.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T3S\ R12W \\ S\ 18|S\ 17 \\ S\ 19|S\ 20 \\ 1961 \end{array}$$
Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of corner.

Land, slightly rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 16, 17, 20 and 21.

S. $89^{\circ}58'$ W., bet. secs. 17 and 20.

Over gently rolling land, through scattered timber and undergrowth.

40.03

Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T3S\ R12W \\ \frac{1}{4} \frac{S\ 17}{S\ 20} \\ 1961 \end{array}$$
Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.

46.10

Wash, 30 lks. wide, drains S. 30° E.

67.80

Wash, 20 lks. wide, drains S. 20° W.

80.06

The cor. of secs. 17, 18, 19 and 20.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

N. $89^{\circ}57'$ W., bet. secs. 18 and 19.

Over gently rolling land, through scattered timber and undergrowth.

Chains

20.90 Wash, 10 lks. wide, course S. 20° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \frac{1}{4} \text{ S } 18 \\ \hline \text{S } 19 \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of corner.

78.88 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.; marked by an iron post, 2 $\frac{1}{2}$ ins. diam., set, marked and witnessed as described in the field notes of the E. bdy. of T. 3 S., R. 13 W., surveyed under this group.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 17, 18, 19 and 20.

N. 0°03' W., bet. secs. 17 and 18.

Over gently rolling land, through scattered timber and undergrowth.

38.00 Wash, 20 lks. wide, course SE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S}\frac{1}{4}\text{R12W} \\ \text{S } 18 \text{ | } \text{S } 17 \\ \hline 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.

64.00 Wash, 20 lks. wide, course SE.

80.00 Point for the cor. of secs. 7, 8, 17, and 18.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T3S R12W} \\ \text{S } 7 \text{ | } \text{S } 8 \\ \hline \text{S } 18 \text{ | } \text{S } 17 \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 8, 9, 16 and 17.

S. 89°59' W., bet. secs. 8 and 17.

Chains

- Over gently rolling land, through scattered timber and undergrowth.
- 40.05 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.
- Set the iron post 24 ins. in the ground, with brass cap mkd.
- $$\begin{array}{r} \text{T3S R12W} \\ \frac{1}{4} \frac{\text{S } 8}{\text{S } 17} \\ 1961 \end{array}$$
- Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.
- 41.30 Wash, 40 lks. wide, course S.
- 80.10 The cor. of secs. 7, 8, 17 and 18.
- Land, gently rolling.
Soil, gravel, sandy clay and loam.
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.
-
- S. $89^{\circ}59'$ W., bet. secs. 7 and 18.
- Over gently rolling land, through scattered timber and undergrowth.
- 13.30 Wash, 20 lks. wide, course SE.
- 39.40 Wash, 10 lks. wide, course SE.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.
- Set the iron post 24 ins. in the ground, with brass cap mkd.
- $$\begin{array}{r} \text{T3S R12W} \\ \frac{1}{4} \frac{\text{S } 7}{\text{S } 18} \\ 1961 \end{array}$$
- Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of corner.
- 53.60 Wash, 10 lks. wide, drains SE.
- 60.40 Wash, 10 lks. wide, drains SE.
- 78.89 The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp.; marked by an iron post, $2\frac{1}{2}$ ins. diam., set, marked and witnessed as described in the field notes of the E. bdy. of T. 3 S., R. 13 W., surveyed under this group.
- Land, gently rolling.
Soil, gravel, sandy clay and loam.
Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.
-
- From the cor. of secs. 7, 8, 17 and 18.
- N. $0^{\circ}03'$ W., bet. secs. 7 and 8.
- Over gently rolling land, through scattered timber and undergrowth.
- 3.60 Wash, 30 lks. wide, drains S. 60° E.
- 6.80 Wash, 20 lks. wide, drains S. 80° E.

Chains

19.20 Wash, 20 lks. wide, drains S. 70° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T3S\frac{1}{4}R12W \\ S\ 7\ | S\ 8 \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.

80.00 Point for the cor. of secs. 5, 6, 7 and 8.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T3S\ R12W \\ S\ 6\ | S\ 5 \\ \hline S\ 7\ | S\ 8 \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

From the cor. of secs. 4, 5, 8 and 9.

S. 89°59'W., bet. secs. 5 and 8.

Over gently rolling land, through scattered timber and undergrowth.

5.80 Wash, 10 lks. wide, drains S. 30° E.

27.30 Wash, 60 lks. wide, drains S. 60° E.

40.04 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.

Set the iron post 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T3S\ R12W \\ \frac{1}{4} \frac{S\ 5}{S\ 8} \\ 1961 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of corner.

52.50 Wash, 50 lks. wide, drains NE.

57.30 Same wash, drains S. 70° E.

73.20 Wash, 50 lks. wide, drains S. 20° E.

80.08 The cor. of secs. 5, 6, 7 and 8.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

Chains	S. 89°58' W., bet. secs. 6 and 7. Over gently rolling land, through scattered timber and undergrowth.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 6 and 7. Set the iron post 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T3S R12W $\frac{1}{2}$ $\frac{S\ 6}{S\ 7}$ 1961 </div> Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of corner.
60.00	Wash, 10 lks. wide, course SE.
78.86	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.; marked by an iron post, 2 $\frac{1}{2}$ ins. diam., set, marked and witnessed as described in the field notes of the E. bdy. of T. 3 S., R. 13 W., surveyed under this group. Land, gently rolling. Soil, gravel, sandy clay and loam. Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.
	From the cor. of secs. 5, 6, 7 and 8. N. 0°03' W., bet. secs. 5 and 6. Over gently rolling land, through scattered timber and undergrowth.
5.30	Wash, 10 lks. wide, course E.
9.00	Wash, 30 lks. wide, course E.
19.60	Wash, 10 lks. wide, course E.
35.10	Wash, 10 lks. wide, course E.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 5 and 6. Set the iron post 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T3S R12W $\frac{1}{2}$ S 6 S 5 1961 </div> Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of corner.
48.50	Wash, 100 lks. wide, drains E.
52.30	Wash, 10 lks. wide, drains E.
61.70	Wash, 20 lks. wide, drains E.
64.00	Wash, 30 lks. wide, drains E.
80.22	Intersect S. bdy. of secs. 31, T. 2 S., R. 12 W. Point for the closing cor. of secs. 5 and 6. Set the iron post 24 ins. in the ground, with brass cap mkd.

Chains

T2S R12W
 S 31
 S 6 | S 5
 C | C
 T3S R12W
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of corner.

From this point the ¼ sec. cor. of sec. 31, T. 2 S., R. 12 W., bears West 13.77 chs. dist., marked by an iron post, 1 in. diam., firmly set, marked and witnessed as described in the official record.

From the same point the cor. of secs. 31 and 32, T. 2 S., R. 12 W., bears East 26.23 chs. dist., marked by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

Land, gently rolling.

Soil, gravel, sandy clay and loam.

Timber, palo verde and ironwood; undergrowth, cactus, yucca, and greasewood.

The point for the N. ¼ sec. cor. of sec. 5 is at midpoint and on the N. bdy. of the township.

At the cor. point

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R12W
 ½ S 5
 T3S R12W
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of corner.

From this point the cor. of secs. 31 and 32, T. 2 S., R. 12 W., bears West, 13.83 chs. dist.

From the same point the ¼ sec. cor. of sec. 32, T. 2 S., R. 12 W., bears East, 26.17 chs. dist.

The point for the N. ¼ sec. cor. of sec. 6 is 40.00 chs. West of the closing corner of secs. 5 and 6, and on the S. bdy. of sec. 31, T. 2 S., R. 12 W.

At the cor. point

Set the iron post 24 ins. in the ground, with brass cap mkd.

T2S R12W
 ½ S 6
 T3S R12W
 1961

Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of corner.

From this point the cor. of Ts. 2 S., Rs. 12 and 13 W., bears West, 13.77 chs. dist., marked by an iron post, 3 ins. diam., set, marked and witnessed as described in the official record.

Chains

From the same point the $\frac{1}{4}$ sec. cor. of sec. 31, T. 2 S., R. 12 W., bears East, 26.23 chs. distant.

General Description

The land in this township is gently rolling, traversed by numerous dry washes. The soil is gravel and a sandy clay and loam covered with loose stones.

The drainage is southerly and southeasterly. No springs or perennial streams were noted during the course of the survey. There is a scattered growth of typical desert timber and undergrowth over most of the area.

A partially graded road traverses the easterly part of the township bearing generally north and south. There are some trail roads in the southwest part of the area.

No evidence of mineral deposits was noted.

CERTIFICATE OF CADASTRAL ENGINEER

I, Horace G. Parker, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of July, 1959,

I have surveyed the Subdivisional Lines of T. 3 S., R. 12 W.

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

February 28, 1961

Horace G. Parker
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., MAR 13 1963, 19

The foregoing field notes of the survey of the Subdivisional lines of T. 3 S., R. 12 W., Gila and Salt River Meridian, Arizona

executed by Horace G. Parker, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

Chief, Division of Cadastral Engineering
Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Chief, Division of Cadastral Engineering