

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Of the

DEPENDENT RESURVEY

of the

East Boundary

and a

COMPLETION SURVEY

of the

Subdivisional Lines

of

Township 11 North, Range 14 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Virgil E. Spratt, Cadastral Surveyor

Under special instructions dated September 12, 19 61, which provided for the surveys included under Group Number 365, approved September 15, 1961, and assignment instructions dated December 29, 19 61.

Survey commenced February 26, 19 62

Survey completed April 27, 19 62

1A

PLATE 1970

INDEX DIAGRAM

Township 11 North, Range 14 West,

6	5	4	3 15 17	2 7 16	1 1 7
7	8	9	10 17 19	11 8 18	12 2 9
18	17	16	22 ($\frac{1}{4}$) 15 19 21	14 9 20	13 3 10
19	20	21	25 ($\frac{1}{4}$) 22 22 24	23 11 23	24 4 12
30 34 35	29 31 34	28 28 32	30 ($\frac{1}{4}$) 27 25 31	26 13 26	25 5 13
31 36 37($\frac{1}{4}$)	32 32 37($\frac{1}{4}$)	33 28 33($\frac{1}{4}$)	30 ($\frac{1}{4}$) 34 26 29($\frac{1}{4}$)	35 14 27($\frac{1}{4}$)	36 6 15($\frac{1}{4}$)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

15

CHAINS

Township 11 North, Range 14 West
Gila and Salt River Meridian, Arizona

The south boundary was surveyed in 1913 by S. E. Blout. The north boundary and the north four miles of the west boundary were surveyed in 1916 by Harris and Gonin. The east boundary was surveyed in 1917 by H. Price. Sections 4 through 9 and 16 through 21 were surveyed by Harris and Gonin in 1916. The survey of the south two miles of the west boundary is contained in the field notes of the current survey of T. 11 N., R. 15 W.

The following notes are those of a dependent resurvey of the east boundary, and the completion survey of the subdivisional lines of T. 11 N., R. 14 W., G&SRM, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated September 12, 1961.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described to the contrary, all corners were monumented with standard iron posts 30 inches long, 2½ inches in diameter, flanged at the bases and with brass caps riveted to the tops.

The geographic position of the southeast corner of the township is: Latitude 34°14'49" North and Longitude 113°40'11" West.

The magnetic declination was found to be 15° E.

Dependent Resurvey of the East Boundary
Township 11 North, Range 14 West

Retracing the survey of 1917 by H. Price, establishing corners for T. 11 N., R. 14 W. at 40- and 80-chain intervals in southing, placing the fractional distance next to the south boundary of the township.

Topography remains essentially the same as reported in the official record. The only items of topography given in the resurvey are those of a recent nature.

Beginning at the cor. of secs. 1, 6, 31 and 36, Ts. 11 and 12 N., Rs. 13 and 14 W., monumented by an iron post, as described in the official record.

S. 0°15' W., along the east boundary of T. 11 N., R. 14 W., bet. secs. 1 and 6.

16.30 Road, graded, bears S. 40° E., by N. 40° W.

18.00 Road, graded, bears S. 45° W. by N. 45° E.

40.00 Point for the ¼ sec. cor. of sec. 1.

Set the post 12 ins. in the ground, mound with stone to top, cap mkd.

CHAINS

T11N
R14W
¼
S 1
1962

41.36 The ¼ sec. cor. of secs. 1 and 6, monumented by an iron post as described in the official record. This corner now functions as the ¼ sec. cor. of sec. 6 only, therefore I remark cap to read

T11N
R13W
¼
S 6
1916
1962

S. 0°15' W., beginning new measurement.

38.64 Point for the cor. of secs. 1 and 12.

Set the post 6 ins. in the ground, mound with stone to top, cap mkd.

T11N
R14W
S 1
S12
1962

40.05 The cor. of secs. 1, 6, 7 and 12, monumented by an iron post as described in the official record. This cor. now functions as the cor. of secs. 6 and 7 only, therefore I remark the cap to read

T11N
R13W
S 6
S 7
1962
1917

Land, mountainous and broken.
Soil, igneous and sandy clay.
Timber, none; undergrowth, cactus and greasewood.

S. 0°13' W., bet. secs. 7 and 12.

29.60 Road, graded, bears E. and W.

38.59 Point for the ¼ sec. cor. of sec. 12.

Set the post 6 ins. in the ground, mound with stone to top, cap mkd.

T11N
R14W
¼
S 12
1962

40.08 The ¼ sec. cor. of secs. 7 and 12, monumented by an iron post as described in the official record. This corner now functions as the ¼ sec. cor. of sec. 7 only, therefore I remark cap to read

4670
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Resurvey, E. Bdy., T. 11 N., R. 14 W., Arizona
	<div style="text-align: center;"> <p>T11N R13W 1/4 S 7 1962 1917</p> </div> <hr/> <p>S. 0°16' W., beginning new measurement.</p>
23.00	Road, graded, bears S. 20° E. and N. 20° W.
31.20	Road, graded, bears SE. by NW.
38.51	Point for the cor. of secs. 12 and 13. Set the post 15 ins. in the ground, mound with stone to top, cap mkd.
	<div style="text-align: center;"> <p>T11N R14W S 12 S 13 1962</p> </div>
39.98	The cor. of secs. 7, 12, 13, and 18, monumented by an iron post as described in the official record. This cor. now functions as the cor. of secs. 7 and 18 only, therefore I remark cap to read
	<div style="text-align: center;"> <p>T11N R13W S 7 S18 1962 1917</p> </div> <p>Land, mountainous and broken. Soil, igneous rock and sandy clay. Timber, none; undergrowth, cactus and greasewood.</p> <hr/> <p>S. 0°23' W., bet. secs. 13 and 18.</p>
4.70	Road, graded, bears E. and W.
8.30	Road, graded, bears SE. and NW.
11.30	Road, graded, bears E. and W.
38.53	Point for the 1/4 sec. cor. of sec. 13. Set the post 12 ins. in the ground, mound with stone to top, cap mkd.
	<div style="text-align: center;"> <p>T11N R14W 1/4 S13 1962</p> </div>
40.14	The 1/4 sec. cor. of secs. 13 and 18, monumented by an iron post as described in the official record. This corner now functions as the 1/4 sec. cor. of sec. 18 only, therefore I remark cap to read

CHAINS		
	<p style="text-align: center;">T11N R13W S 18 1962 1917</p> <hr/> <p>S. 0°10' W., beginning new measurement.</p>	
20.50	Intersect line 2-3 M.S. No. 2579, Iron Clad lode, from which Cor. No. 2 bears N. 19°42' W., 6.87 chs. dist., and Cor. No. 3 bears S. 19°42' E., 15.86 chs. dist.	
37.87	Intersect line 3-4 M.S. No. 2579, Iron Clad lode, from which Cor. No. 3 bears N. 65°48' E., 5.92 chs. dist., and Cor. No. 4 bears S. 65°48' W., 2.44 chs. distant.	
38.39	Point for the cor. of secs. 13 and 24. Set the iron post 6 ins. in the ground, mound with stone to top, cap mkd.	<p style="text-align: center;">T11N R14W S13 S24 1962</p>
	<p>from which</p> <p style="padding-left: 40px;">U.S.L.M. No. 2579 bears N. 49°06' W., 35.51 chs. dist., monumented by a stone in place, marked and witnessed as described in the official record.</p>	
39.98	The cor. of secs. 13, 18, 19 and 24, monumented by an iron post as described in the official record. This cor. now functions as the cor. of secs. 18 and 19 only, therefore I remark cap to read	<p style="text-align: center;">T11N R13W S 18 S 19 1962 1917</p>
	<p>Land, mountainous and broken. Soil, sandstone and gravelly loam. Timber, none; undergrowth, cactus, greasewood and palo verde.</p> <hr/> <p>S. 0°07' W. bet. secs. 19 and 24.</p>	
15.40	Road, graded, bears E. and W.	
38.41	Point for the 1/4 sec. cor. of sec. 24. Set the post 20 ins. in the ground, mound with stone to top, cap mkd.	<p style="text-align: center;">T11N R14W S 24 1962</p>
40.26	The 1/4 sec. cor. of secs. 19 and 24, monumented by an iron post as described in the official record. This cor. now functions as the 1/4 sec. cor. of sec. 19 only, therefore I remark cap to read	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Resurvey, E. Bdy., T. 11 N., R. 14 W., Arizona
	<p style="text-align: center;">T11N R13W 1/4 S 19 1962 1917</p>
	<p>S. 0°14' W., beginning new measurement.</p>
36.40	<p>Road, graded, bears E. and W.</p>
38.15	<p>Point for the cor. of secs. 24 and 25.</p>
	<p>Set the post 8 ins. in the ground, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T11N R14W S 24 S 25 1962</p>
39.91	<p>The cor. of secs. 19, 24, 25 and 30, monumented by an iron post as described in the official record. This corner now functions as the cor. of secs. 19 and 30 only, therefore I remark cap to read</p>
	<p style="text-align: center;">T11N R13W S 19 S 30 1962 1917</p>
	<p>Land, mountainous and broken. Soil, clay loam and decomposing shale. Timber, none; undergrowth, cactus, palo verde and greasewood.</p>
	<p>S. 0°11' W., bet. secs. 25 and 30.</p>
38.24	<p>Point for the 1/4 sec. cor. of sec. 25.</p>
	<p>Set the post 6 ins. in the ground, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T11N R14W 1/4 S 25 1962</p>
40.11	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented by an iron post as described in the official record. This corner now functions as the 1/4 sec. cor. of sec. 30 only, therefore I remark cap to read</p>
	<p style="text-align: center;">T11N R13W 1/4 S 30 1962 1917</p>

6

CHAINS

	<p>S. 0°14' W., beginning new measurement.</p>
<p>38.13</p>	<p>Point for the cor. of secs. 25 and 36.</p> <p>Set the post 6 ins. in the ground, mound with stone to top, cap mkd.</p> <div style="text-align: center;"> <p>T11N R14W <u>S 25</u> S 36 1962</p> </div>
<p>40.09</p>	<p>The corner of secs. 25, 30, 31 and 36, monumented by an iron post as described in the official record. This cor. now functions as the cor. of secs. 30 and 31 only, therefore I remark cap to read</p> <div style="text-align: center;"> <p>T11N R13W <u>S 30</u> S 31 1962 1917</p> </div> <p>Land, mountainous and broken. Soil, gravelly loam and alluvial silt. Timber, none; undergrowth, cactus, ironwood and greasewood.</p>
<p>38.04</p>	<p>S. 0°13' W., bet. secs. 31 and 36.</p> <p>Point for the ¼ sec. cor. of sec. 36.</p> <p>Set the post 18 ins. in the ground, mound with stone to top, cap mkd.</p> <div style="text-align: center;"> <p>T11N R14W ¼ <u>S 36</u> 1962</p> </div>
<p>40.04</p>	<p>The ¼ sec. cor. of secs. 31 and 36, monumented by an iron post as described in the official record. This corner now functions as the ¼ sec. cor. of sec. 31 only, therefore I remark cap to read</p> <div style="text-align: center;"> <p>T11N R13W ¼ <u>S 31</u> 1962 1917</p> </div>
<p>39.99</p>	<p>S. 0°12' W., beginning new measurement.</p> <p>The cor. of secs. 1, 6, 31 and 36, T. 10 and 11 N., Rs. 13 and 14 W., monumented by an iron post as described in the official record.</p> <p>Land, mountainous and broken. Soil, gravelly loam and alluvial silt. Timber, none; undergrowth, cactus, ironwood and greasewood.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion Survey, Subdivisions, Township 11 North, Range 14 West, Arizona</p> <hr/> <p>Beginning at the cor. of secs. 1, 2, 35 and 36, on the north boundary of the township, monumented by an iron post as described in the official record.</p> <p>S. 0°01' E., bet. secs. 1 and 2.</p> <p>Asc. gradual N. slope, through scattered palo verde and greasewood.</p>
1.20	Spur, projects SE.
6.20	Wash, 2½ ft. deep, 20 lks. wide, drains E.
10.80	Road to Kingman and Yucca, graded, bears S. 80° E. and N. 80° W.
14.90	Wash, 3 ft. deep, 30 lks. wide, drains NE.
26.70	Spur, projects E.
38.50	Wash, 2½ ft. deep, 20 lks. wide, drains NE.
40.00	Point for the ¼ sec. cor. of secs. 1 and 2.
	<p>Set the post 15 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;"> T11N R14W ¼ S2 S1 1962 </p>
41.60	Wash, 2½ ft. deep, 10 lks. wide, drains E.
44.60	Wash, 2½ ft. deep, 20 lks. wide, drains E.
46.10	Wash, 2 ft. deep, 10 lks. wide, drains NW.
59.30	Spur, projects NW.; begin desc. over gentle S. slope.
79.50	Wash, 2 ft. deep, 56 lks. wide, drains E.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	<p>Set the post 24 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;"> T11N R14W S 2 S 1 S11 S12 1962 </p> <p>Soil, sandy clay. Land, rolling and broken. Timber, none; undergrowth, palo verde, cactus and greasewood.</p> <hr/> <p>S. 89°56' E., bet. secs. 1 and 12.</p> <p>Desc. gentle E. slope. through scattered desert vegetation.</p>

CHAINS		
10.90	Wash, 2½ ft. deep, 15 lks. wide, drains NE.	
15.10	Wash, 2½ ft. deep, 40 lks. wide, drains E. from SW. Thence along bottom of wash.	
23.50	Leave wash, 2½ ft. deep, 50 lks. wide, drains SE.; asc. gradual W. slope.	
36.00	Ridge, bears S. 20° E. and N. 20° W.; desc. E. slope.	
40.00	Point for the ¼ sec. cor. of secs. 1 and 12. Set the post 12 ins. in the ground, mound with stone to top, cap mkd.	
T11N R14W ¼ $\frac{S 1}{S 12}$ 1962		
41.40	Road to Kingman and Yucca, graded, bears S. 35° E., and N. 35° W.	
47.40	Spur, projects NE.	
59.76	Spur, projects NE.	
79.70	The cor. of secs. 1 and 12, on E. bdy. of the township. Land, rolling and broken. Soil, sandy and rocky. Timber, none; undergrowth, desert growth.	
<hr/> From the cor. of secs. 1, 2, 11 and 12. S. 0°01' E., bet. secs. 11 and 12. Asc. gradual N. slope through scattered palo verde, cactus and greasewood.		
9.80	Wash, 2½ ft. deep, 80 lks. wide, drains NE. and dirt road bearing E. and W.	
17.80	Wash, 3 ft. deep, 10 lks. wide, drains NE.	
24.80	Wash, 2½ ft. deep, 40 lks. wide, drains NE.	
30.40	Spur, projects W.	
39.00	Wash, 3½ ft. deep, 10 lks. wide, drains NE.	
40.00	Point for the ¼ sec. cor. of secs. 11 and 12. Set the post 14 ins. in the ground, mound with stone to top, cap mkd.	
T11N R14W ¼ S11 S12 1962		
46.70	Spur, projects E.	
49.70	Wash, 2½ ft. deep, 10 lks. wide, drains E.	
56.40	Spur, projects irregularly E.	
63.40	Wash, 2 ft. deep, 10 lks. wide, drains E.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Completion Survey, Subdivisions, Township 11 North, Range 14 West, Arizona
66.30	Wash, 2½ ft. deep, 25 lks. wide, drains NE.
74.00	Ridge, bears S. 30° E. and N. 30° W.; asc. NW. slope.
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set the post 6 ins. in the ground, mound with stone to top, cap mkd. <div style="text-align: center;"> T11N R14W S11 S12 S14 S13 1962 </div> Land, rolling and broken. Soil, sandy loam. Timber, none; undergrowth, scattered palo verde, greasewood and cactus.
	S. 89°55' E., bet. secs. 12 and 13. Asc. gradual W. slope, through scattered desert vegetation.
2.60	Spur, projects SE.; desc. gradual E. slope.
18.10	Wash, 1½ ft. deep, 10 lks. wide, drains NE.
23.30	Draw, drains S.; asc. gradual W. slope of rocky ridge.
40.00	Point for the ¼ sec. cor. of secs. 12 and 13. Set the post 8 ins. in the ground, mound with stone to top, cap mkd. <div style="text-align: center;"> T11N R14W ¼ S 12 S 13 1962 </div>
46.20	Ridge, bears irregularly N. and S.; desc. steep rocky E. slope.
65.00	Wash, 2½ ft. deep, 15 lks. wide, drains NE.
79.36	The cor. of secs. 12 and 13, on the E. bdy. of the township. Land, rolling and broken. Soil, sandy loam. Timber, none; undergrowth, palo verde, greasewood and cactus.
	From the cor. of secs. 11, 12, 13 and 14. S. 0°01' E., bet. secs. 13 and 14. Asc. N. slope, through scattered desert vegetation.
5.20	Spur, projects SE.
16.90	Road, graded, bears irregularly E. and W.

CHAINS	
27.30	Wash, 1½ ft. deep, 10 lks. wide, drains SE.
33.80	Knoll, shale.
40.00	Point for the ¼ sec. cor. of secs. 13 and 14.
	Set the post 6 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W ¼ S14 S13 1962
45.50	Wash, 2 ft. deep, 20 lks. wide, drains SE.
58.20	Spur, projects NW.
62.50	Wash, 2 ft. deep, 30 lks. wide, drains NE.; asc. gradual N. slope.
73.80	Spur, projects NE.; desc. S. slope.
77.50	Wash, 2 ft. deep, 30 lks. wide, drains NE.; asc. N. slope.
80.00	Point for the cor. of secs. 13, 14, 23 and 24, falls on the sheer face of rock, impossible to perpetuate.
	Land, rolling and broken with rocky bluffs. Soil, sandy, clay loam. Timber, none; undergrowth, cactus, catclaw, grease-wood and palo verde.
	S. 89°57' E., bet. secs. 13 and 24.
	Asc. NW. slope.
6.10	Spur, projects N.; desc. E. slope.
15.40	Wash, 2 ft. deep, 20 lks. wide, drains NE.
31.90	Wash, 2½ ft. deep, 60 lks. wide, drains SE.
35.30	Spur, projects S.
38.80	Wash, 2½ ft. deep, 180 lks. wide, drains NE.
40.00	Point for the ¼ sec. cor. of secs. 13 and 24.
	Set the post 8 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W ¼ $\frac{S\ 13}{S\ 24}$ 1962
41.30	Wash, 2 ft. deep, 60 lks. wide, drains NE.
48.00	Spur, projects SE.
53.20	Wash, 2 ft. deep, 60 lks. wide, drains NE.
64.90	Wash, 2½ ft. deep, 40 lks. wide, drains SE.
68.20	Spur, projects SE.
73.20	Spur, projects SE.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Completion Survey, Subdivisions Township 11 North, Range 14 West, Arizona				
76.53	Intersect line 4-1, M.S. 2579, Iron Clad lode, from which Cor. No. 4 bears S. 19°42' E., 0.51 chs. dist., and Cor. No. 1 bears N. 19°42' W., 22.22 chs. dist.				
77.77	Intersect line 3-4 M.S. 2579, Iron Clad lode, from which Cor. No. 4 bears S. 65°48' W., 1.17 chs. dist., and Cor. No. 3 bears N. 65°48' E., 7.19 chs. dist.				
78.93	The cor. of secs. 13 and 24, on the E. bdy. of the township. Land, rolling and broken. Soil, sandy and rocky clay loam. Timber, none; undergrowth, cactus, palo verde and greasewood.				
	From the true point for the cor. of secs. 13, 14, 23 and 24. S. 0°01' E., bet. secs. 23 and 24. Asc. steep N. slope, through scattered palo verde, cactus and greasewood.				
1.50	Point for the witness cor. of secs. 13, 14, 23 and 24. Set the post 15 ins. in the ground, mound with stone to top, cap mkd.				
	<div style="text-align: center;"> T11N R14W WC <table border="1" style="margin: auto;"> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> </table> 1962 </div>	S14	S13	S23	S24
S14	S13				
S23	S24				
12.70	Ridge, rocky, bears E. and W.; desc. S. slope.				
28.30	Spur, projects SW.				
35.60	Wash, 2½ ft. deep, 10 lks. wide, drains SW.				
38.40	Spur, projects SW.				
40.00	Point for the ¼ sec. cor. of secs. 23 and 24. Set the post 8 ins. in the ground, mound with stone to top, cap mkd.				
	<div style="text-align: center;"> T11N R14W ¼ <table border="1" style="margin: auto;"> <tr> <td>S23</td> <td>S24</td> </tr> </table> 1962 </div>	S23	S24		
S23	S24				
42.50	Wash, 2 ft. deep, 10 lks. wide, drains SW.				
47.20	Spur, projects W.				
57.20	Wash, 2 ft. deep, 15 lks. wide, drains SE.				
60.40	Spur, projects SE.; desc. over S. slope.				
71.30	Road, graded, bears S. 65° E. and N. 65° W.				

CHAINS		
73.40	Wash, 2½ ft. deep, 20 lks. wide, drains SW.	
79.70	Spur, projects W.	
80.00	Point for the cor., secs. 23, 24, 25 and 26.	
	Set the post 6 ins. in the ground, mound with stone to top, cap mkd.	
	T11N R14W <u>S23</u> <u>S24</u> <u>S26</u> <u>S25</u> 1962	
	Land, rolling and broken. Soil, sandy loam. Timber, none; undergrowth, cactus and palo verde.	
<hr/>		
	S. 89°59' E., bet. secs. 24 and 25.	
	Desc. gentle E. slope.	
12.80	Wash, 2½ ft. deep, 10 lks. wide, drains SE.	
17.80	Spur, projects NW.	
18.80	Road, graded, bears S. 20° E. and N. 20° W.	
21.10	Wash, 2½ ft. deep, 100 lks. wide, drains S.	
22.50	Road, bears S. 70° E. and N. 70° W.	
25.70	Wash, 2½ ft. deep, 20 lks. wide, drains S.	
28.50	Road, bears S. 40° W. and N. 40° E.	
29.70	Road, bears S. 10° W. and N. 10° E.	
32.60	Road, graded, bears E. and W.	
38.80	Road, bears W. and N. 65° E.	
40.00	Point for the ¼ sec. cor. of secs. 24 and 25.	
	Set the post 6 ins. in the ground, mound with stone to top, cap mkd.	
	T11N R14W ¼ <u>S 24</u> <u>S 25</u> 1962	
43.10	Wash, 2½ ft. deep, 10 lks. wide, drains NE.	
44.40	Wash, 2½ ft. deep, 10 lks. wide, drains SE.	
52.60	Spur, projects NE.	
58.30	Wash, 2 ft. deep, 10 lks. wide, drains SE.	
60.30	Wash, 2 ft. deep, 10 lks. wide, drains SE.	
78.60	The cor. of secs. 24 and 25, on the E. bdy. of the township.	
	Land, rolling and broken. Soil, sandy and rocky loam. Timber, none; undergrowth, cactus and palo verde.	
<hr/>		

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Completion Survey, Subdivisions Township 11 North, Range 14 West, Arizona</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26. S. 0°01' E., bet. secs. 25 and 26. Desc. gentle S . slope, through scattered palo verde, cactus and greasewood.</p> <p>8.00 Spur, projects E.</p> <p>31.80 Wash, 2 ft. deep, 10 lks. wide, drains SW.</p> <p>34.80 Wash, 2 ft. deep, 10 lks. wide, drains SE.</p> <p>35.90 Wash, 2 ft. deep, 10 lks. wide, drains SW.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 25 and 26. Set the post 20 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T11N R14W ¼ S26 S25 1962</p> <p>42.80 Wash, 2 ft. deep, 25 lks. wide, drains SW.</p> <p>44.90 Spur, projects W.; desc. S. slope.</p> <p>45.30 Road, graded, bears E. and W.</p> <p>48.70 Wash, 2 ft. deep, 20 lks. wide, drains SW.</p> <p>57.90 Ridge, bears SE. and NW.</p> <p>77.00 Spur, projects SE.</p> <p>80.00 Point for the cor. of secs. 25, 26, 35 and 36. Set the post 8 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T11N R14W S26 S25 S35 S36 1962</p> <p>Land, rolling and broken. Soil, rocky and sandy clay loam. Timber, none; undergrowth, desert vegetation.</p> <hr/> <p>S. 89°55' E. bet. secs. 25 and 36.</p> <p>0.20 Wash, 1 ft. deep, 30 lks. wide, drains SW.</p> <p>19.20 Wash, 2 ft. deep, 100 lks. wide, drains SW.</p> <p>24.50 Wash, 2 ft. deep, 60 lks. wide, drains NW. into wash 3 chs. N.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 25 and 36.</p>

CHAINS		
	<p>Set the post 8 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T11N R14W $\frac{1}{4} \frac{S\ 25}{S\ 36}$ 1962</p>	
49.40	Ravine, drains N.	
65.70	Spur, bears N. and S.	
68.93	Ravine, drains N.	
73.63	Spur, projects SW.	
78.16	The corner of secs. 25 and 36, on the E. bdy. of the township.	
<hr/>		
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 0°01' E. bet. secs. 35 and 36.</p> <p>Desc. gradual S. slope.</p>	
.60	Wash, 2½ ft. deep, 50 lks. wide, drains SW.	
11.10	Wash, 2½ ft. deep, drains W.	
40.00	Point for the ¼ sec. cor. of secs. 35 and 36.	
	<p>Set the post 6 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T11N R14W $\frac{1}{4}$ S35 S36 1962</p>	
46.30	Spur, projects E.	
56.70	Ridge, bears SW. by E.	
63.00	Wash, 2 ft. deep, 10 lks. wide, drains SW.; asc. N. slope.	
71.70	Spur projects SW.; desc. S. slope.	
75.40	Wash, 2½ ft. deep, 20 lks. wide, drains NW.; asc. N. slope.	
82.16	Point for the closing cor. of secs. 35 and 36 on the S. bdy. of the township.	
	<p>Set the post 8 ins. in the ground, mound with stone to top, cap mkd.</p> <p style="text-align: center;">T11N R14W S35 S36 $\frac{C\ C}{1962}$</p>	
	<p>From this cor., the cor. of secs. 1, 2, 35 and 36, Ts. 10 and 11 N., R. 14 W., monumented by an iron post as described in the official record, bears N. 89°57' W., 2.08 chs. dist. This cor. now functions as the cor. of secs. 2 and 3 only, therefore I remark the brass cap to read</p> <p style="text-align: center;">$\frac{S2 S1}{T10N\ R14W}$ 1913 1962</p>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Completion Survey, Subdivisions, Township 11 North, Range 14 West, Arizona
	Land, rolling and broken. Soil, rocky and sandy clay loam. Timber, none; undergrowth, desert vegetation.
	The point for the $\frac{1}{4}$ sec. cor. of sec. 36 is at 40.00 chains in easting from the CC. of secs. 35 and 36, and on the S. bdy. of the township.
	Set the post 8 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W $\frac{1}{4}$ S 36 <hr style="width: 20%; margin: auto;"/> 1962
	From this cor. the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented by an iron post as described in the official record, bears N. 89°57' W., 2.08 chs. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 1 only, therefore I remark cap to read
	<hr style="width: 20%; margin: auto;"/> $\frac{1}{4}$ S 1 T10N R14W 1913 1962
	From the cor. of secs. 2, 3, 34 and 35 on the N. boundary of the township, monumented by an iron post as described in the official record.
	S. 0°01' E., bet. secs. 2 and 3.
	Desc. S. slope.
4.50	Spur, projects SE.
13.90	Spur, projects NW.
25.80	Wash, 2 ft. deep, 15 lks. wide, drains SE.
27.80	Spur, projects SE.
34.00	Wash, 2 ft. deep, 20 lks. wide, drains SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	Set the post 15 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W $\frac{1}{4}$ S 3 S 2 1962
42.60	Wash, 2 ft. deep, 10 lks. wide, drains SE.
46.40	Ridge, bears E. and W.; desc. gradual S. slope.
61.70	Wash, 2 ft. deep, 50 lks. wide, drains SE.; asc. steep and rocky N. slope.

CHAINS

77.60 Spur, projects E.; desc. S. slope.

79.50 Draw, drains SE.; asc. NE. slope.

80.00 Point for the cor. of secs. 2, 3, 10 and 11.

Set the post 12 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
S 3 | S 2
S10 | S11
1962

Land, rolling and broken.
Soil, sandy loam.
Timber, none; undergrowth, scattered palo verde, cactus and greasewood.

S. 89°56' E., bet. secs. 2 and 11.

Desc. E. slope.

.50 Draw, drains SE.

11.20 Wash, 2½ ft. deep, 60 lks. wide, drains NE.

34.90 Wash, 2½ ft. deep, 60 lks. wide, drains SE.

35.00 Road, graded, bears S. 20° E. and N. 20° W.; asc. W. slope.

40.13 Point for the ¼ sec. cor. of secs. 2 and 11.

Set the post 10 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
¼ S 2
S 11
1962

40.20 Ridge, bears N. 30° W. and S. 30° E.; desc. E. slope.

54.40 Spur, projects NE.

58.70 Wash, 2 ft. deep, 15 lks. wide, drains E.

73.00 Wash, 2½ ft. deep, 100 lks. wide, drains NE.

80.26 The cor. of secs. 1, 2, 11 and 12.

Land, rolling and broken.
Soil, rocky and sandy clay loam.
Timber, none; undergrowth, desert vegetation.

From the cor. of secs. 2, 3, 10 and 11.

S. 89°50' W., bet. secs. 3 and 10.

Asc. nearly vertical E. slope.

7.80 Spur, projects, NE.

13.70 Crest of ridge, bears N. 10° W. and S. 10° E.; desc. W. slope.

19.70 Draw, drains S.; asc. E. slope.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Completion Survey, Subdivisions Township 11 North, Range 14 West, Arizona
25.50	Crest of spur sloping S.; desc. SW. slope.
32.00	Slope changes; asc. steep rocky E. slope.
37.60	Ridge, bears N. 20° E. and S. 20° W.
40.23	Point for the ¼ sec. cor. of secs. 3 and 10. Set the post 12 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W ¼ $\frac{S \ 3}{S \ 10}$ 1962
	from which U.S.L.M. No. 2584 bears S. 61°17'38" W., 10.04 chs. dist., monumented by a stone in place, 36 x 20 x 12 inches above ground, marked and witnessed as described in the official record.
44.10	Intersect line 3-4 of the M.S. No. 2584, New Hampshire lode, from which Cor. No. 4 bears S. 6°46' W., 8.66 chs. dist., and Cor. No. 3 bears N. 6°46' E., 14.07 chs. dist.
62.43	Intersect line 3-4 of the M.S. 2584, Vermont lode; from which Cor. No. 4 bears S. 6°46' W., 6.44 chs. dist., and Cor. No. 3 bears N. 6°46' E., 16.29 chs. distant.
67.30	Road, bladed, bears N. 30° W. and S. 30° E.
75.80	Spur, projects SW.
79.10	Wash, 2 ft. deep, 35 lks. wide, drains S.
80.46	The cor. of secs. 3, 4, 9 and 10, monumented by an iron post as described in the official record. Land, rough and broken. Soil, sandy clay loam. Timber, none; undergrowth, cactus, palo verde and greasewood.
	From the cor. of secs. 2, 3, 10 and 11. S. 0°01' E., bet. secs. 10 and 11. Asc. steep rocky N. slope.
5.00	Spur, projects NE.; desc. steep E. slope.
11.10	Ravine, drains NE.; asc. steep N. slope.
21.00	Ridge, bears N. 40° W. and S. 40° E.; desc. steep S. slope.
38.40	Road, bladed, bears N. 68° W. and S. 60° E.

CHAINS		
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11. Set the post 15 ins. in the ground, mound with stone to top, cap mkd.	
T11N R14W $\frac{1}{4}$ S10 S11 1962		
41.30	Wash, 2 $\frac{1}{2}$ ft. deep, 15 lks. wide, drains SE.	
54.40	Wash, 2 ft. deep, 10 lks. wide, drains NE.	
65.10	Road, bears irregularly E. and W.	
71.30	Ridge, bears S. 80° W. and N. 80° E.; desc. gradual S. slope.	
77.90	Wash, 2 $\frac{1}{2}$ ft. deep, 10 lks. wide, drains SE.	
79.70	Spur, projects SE.	
80.00	Point for the cor. of secs. 10, 11, 14 and 15. Set the post 4 ins. in the ground, mound with stone to top, cap mkd.	
T11N R14W S10 S11 S15 S14 1962		
Land, rolling and broken. Soil, sandy loam. Timber, none; undergrowth, scattered palo verde, cactus and greasewood.		
East, bet. secs. 11 and 14.		
Asc. SW. slope of spur projecting SE.		
1.16	Spur, projects SE.	
14.50	Wash, 2 $\frac{1}{2}$ ft. deep, 15 lks. wide, drains SE.	
18.50	Wash, 2 ft. deep, 10 lks. wide, drains SE.	
21.00	Road, graded, bears N. 40° W. and S. 40° E.	
40.17	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14. Set the post 6 ins. in the ground, mound with stone to top, cap mkd.	
T11N R14W $\frac{1}{4}$ $\frac{S 11}{S 14}$ 1962		
40.40	Road, bears N. 30° W. and S. 30° E.	
43.40	Wash, 2 ft. deep, 15 lks. wide, drains SE.	
50.00	Wash, 2 ft. deep, 15 lks. wide, drains E.; thence along wash.	
54.00	Leave wash, drains NE.	
58.20	Wash, 2 ft. deep, 10 lks. wide, drains SE.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	<p>Completion Survey, Subdivisions, Township 11 North, Range 14 West, Arizona</p>
59.50	Wash, 2 ft. deep, 10 lks. wide, drains NE.
63.00	Spur, projects NE.
73.20	Spur, projects NW.
77.00	Wash, 2½ ft. deep, 10 lks. wide, drains NW.; asc. W. slope.
80.34	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling and broken. Soil, sandy clay loam. Timber, none; undergrowth, scattered palo verde, cactus and greasewood.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p>
	<p>S. 89°50' W. between secs. 10 and 15.</p>
	<p>Asc. E. slope.</p>
22.31	Spur, projects NW.
40.11	Point for the ¼ sec. cor. of secs. 10 and 15.
	<p>Set the post 6 ins. in the ground, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T11N R14W ¼ $\frac{S\ 10}{S\ 15}$ 1962</p>
	<p>Desc. W. slope.</p>
43.90	Spur, projects NW.
52.80	Wash, 2 ft. deep, 15 lks. wide, drains N.; asc. steep E. slope.
60.00	Ridge, bears N. and S.; desc. W. slope.
76.70	Wash, 2½ ft. deep, 20 lks. wide, drains W.
80.22	<p>The cor. of secs. 9, 10, 15 and 16, monumented by an iron post as described in the official record.</p>
	<p>Land, rolling and broken. Soil, sandy and rocky clay loam. Timber, none; undergrowth, scattered palo verde and cactus.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p>
	<p>S. 0°01' E., bet. secs. 14 and 15, along E. slope.</p>
.80	Wash, 2 ft. deep, 10 lks. wide, drains E.
17.00	Wash, 2 ft. deep, 10 lks. wide, drains E.

CHAINS	
34.20	Wash, 2 ft. deep, 10 lks. wide, drains E.; asc. along E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15. Set the post 3 ins. in the ground, mound with stone to top, cap mkd. T11N R14W $\frac{1}{4}$ S15 S14 1962 Desc. along E. slope.
46.70	Road, graded, bears E. and W.
54.80	Wash, 1 ft. deep, 10 lks. wide, drains E.
57.80	Wash, 1 ft. deep, 10 lks. wide, drains E.
65.20	Wash, 2 ft. deep, 20 lks. wide, drains E.
71.60	Ridge, bears SW. and NE.
80.00	Point for the cor. of secs. 14, 15, 22 and 23. Set the post 8 ins. in the ground, mound with stone to top, cap mkd. T11N R14W S15 S14 S22 S23 1962 Land, broken. Soil, rocky clay loam. Timber, none; undergrowth, cactus, palo verde and greasewood.
S. 89°56' E., bet. secs. 14 and 23.	
4.60	Wash, 2 ft. deep, 10 lks. wide, drains SE.
5.40	Spur, projects S.
9.50	Spur, projects SE.
22.80	Wash, 2½ ft. deep, 30 lks. wide, drains SE.
29.60	Road, graded, bears N. 30° W. and S. 30° E.
36.40	Spur, projects SW.
39.60	Wash, 2½ ft. deep, 10 lks. wide, drains SW.
40.17	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23. Set the post 7 ins. in the ground, mound with stone to top, cap mkd. T11N R14W $\frac{1}{4}$ S 14 S 23 1962
43.10	Spur, projects SW.
55.80	Spur, projects SE.
60.90	Spur, projects SE.
64.20	Road, graded, bears S. 30° W. and N. 30° E.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Completion Survey, Subdivisions Township 11 North, Range 14 West, Arizona
65.90	Spur, projects NE.
69.40	Ravine, drains NE.
71.40	Spur, projects NE.
80.34	The corner of secs. 13, 14, 23 and 24. Land, rolling and broken. Soil, sandy clay loam. Timber, none; undergrowth, desert vegetation.
	From the cor. of secs. 14, 15, 22 and 23.
	West, bet. secs. 15 and 22.
3.40	Spur, projects N.
12.00	Wash, 1½ ft. deep, 10 lks. wide, drains SE.
17.50	Ridge, bears S. and N. 20° E.; desc. W. slope.
28.50	Wash, 2½ ft. deep, 30 lks. wide, drains SE.; asc. E. slope.
40.21	Point for the ¼ sec. cor. of secs. 15 and 22. Set the post 6 ins. in the ground, mound with stone to top, cap mkd.
	$\begin{array}{r} \text{T11N R14W} \\ \frac{1}{4} \frac{\text{S } 15}{\text{S } 22} \\ 1962 \end{array}$
	Asc. E. slope.
48.00	Spur, projects N.; desc. N. slope.
59.00	Spur, projects NE.
62.10	Wash, 2½ ft. deep, 30° lks. wide, drains NE.; asc. E. slope.
77.20	Spur, projects N.; desc. W. slope.
80.42	Point for the closing cor. of secs. 15 and 22 on the line bet. secs. 15 and 16. Set the post 10 ins. in the ground, mound with stone to top, cap mkd.
	$\begin{array}{r} \text{T11N R14W} \\ \text{C S } 15 \\ \text{C S } 22 \\ 1962 \end{array}$
	From this cor. the cor. of secs. 15, 16, 21 and 22, monumented by an iron post as described in the official record, bears S. 0°02' E., 52 lks. dist. This corner now functions as the cor. of 16 and 21 only, therefore I remark cap to read

CHAINS

T11N R14W

S 16
S 21
1913
1962

Land, rolling and broken.
Soil, sandy clay loam.
Timber, none; undergrowth, desert vegetation.

The point for the $\frac{1}{4}$ sec. cor. of sec. 15 is at mid-point on the W. bdy. of the section.

Set the post 6 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W

$\frac{1}{4}$
S 15
1962

From this cor. the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented by an iron post as described in the official record, bears S. $0^{\circ}02'$ E., 26 lks. dist. This cor. now functions as the cor. of sec. 16 only, therefore I remark cap to read

T11N R14W

$\frac{1}{4}$
S 16
1913
1962

From the cor. of secs. 14, 15, 22 and 23.

S. $0^{\circ}01'$ E., bet. secs. 22 and 23.

Asc. N. slope.

- 2.90 Spur, projects SE.; desc. S. slope.
- 14.10 Spur, projects SW.
- 18.30 Wash, $2\frac{1}{2}$ ft. deep, 20 lks. wide, drains SE.; asc. N. slope.
- 18.70 Road, graded, bears E. and W.
- 24.10 Ridge, bears S. 60° E. and N. 60° W.
- 29.80 Wash, $1\frac{1}{2}$ ft. deep, 10 lks. wide, drains SE.
- 32.80 Spur, projects SE.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.

Set the post 10 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W

$\frac{1}{4}$
S22
S23
1962

- 42.00 Wash, 2 ft. deep, 40 lks. wide, drains S.
- 44.40 Spur, projects S.
- 46.60 Wash, 2 ft. deep, 40 lks. wide, drains NE.; asc. N. slope.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Completion Survey, Subdivisions Township 11 North, Range 14 West, Arizona
49.00	Spur, projects E.
49.90	Wash, 2 ft. deep, 10 lks. wide, drains E.; asc. N. slope.
58.30	Spur, projects NW.
69.30	Ridge, bears N. 40° E. and S. 40° W.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set the post 15 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W S22 S23 S27 S26 1962
	Land, rolling and broken. Soil, sandy clay loam. Timber, none; undergrowth, cactus, palo verde and greasewood.
	East, bet. secs. 23 and 26.
	Asc. W. slope.
1.60	Ridge, bears N. 10° E. and S. 10° E
13.80	Spur, projects SE.
21.40	Ridge, bears N. 35° W. and S. 35° E.
29.00	Wash, 2½ ft. deep, 15 lks. wide, drains SE.
31.50	Spur, projects SE.
36.40	Wash, 2½ ft. deep, 15 lks. wide, drains S.
38.90	Wash, 2 ft. deep, 10 lks. wide, drains SE.
40.21	Point for the ¼ sec. cor. of secs. 22 and 26.
	Set the post 6 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W ¼ S 23 S 26 1962
43.40	Spur, projects NW.
51.30	Ridge, bears N. and S.
57.50	Spur, projects N.
69.40	Wash, 2 ft. deep, 100 lks. wide, drains SE.
75.60	Wash, 2 ft. deep, 30 lks. wide, drains SW.
80.42	The cor. of secs. 23, 24, 25 and 26.

CHAINS

Land, rolling and broken.
Soil, sandy clay loam.
Timber, none; undergrowth, desert vegetation.

From the corner of secs. 22, 23, 26 and 27.

West, between sections 22 and 27.

Desc. W. slope.

2.00 Ravine, drains SW.; asc. E. slope.

5.30 Spur, projects S.

12.30 Wash, 2½ ft. deep, 10 lks. wide, drains SE.

26.50 Spur, projects S.; desc. W. slope.

37.60 Ravine, drains NE.; asc. E. slope.

39.10 Spur, projects N.

40.25 Point for the ¼ sec. cor. of secs. 22 and 27.

Set the post 15 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
¼ $\frac{S\ 22}{S\ 27}$
1962

40.80 Wash, 2 ft. deep, 10 lks. wide, drains NE.

50.90 Spur, projects NW.; desc. W. slope.

60.20 Ravine, drains SW.; asc. E. slope.

62.30 Spur, projects S.; desc. SW. slope.

73.20 Wash, 2½ ft. deep, 15 lks. wide, drains SE.; asc. E. slope.

80.50 Point for the closing cor. of secs. 22 and 27, on the line bet. secs. 21 and 22.

Set the post 6 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
 $\frac{C\ S\ 22}{C\ S\ 27}$
1962

From this cor. the cor. of secs. 21, 22, 27 and 28, monumented by an iron post as described in the official record, bears S. 0°02' E., 0.68 chs. dist. This cor. now functions as the cor. of secs. 21 and 28 only, therefore I remark the brass cap to read

T11N R14W
 $\frac{S\ 21}{S\ 28}$
1913
1962

Land, rolling and broken.
Soil, sandy clay loam.
Timber, none; undergrowth, desert vegetation.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Completion Survey, Subdivisions
Township 11 North, Range 14 West, Arizona

The point for the $\frac{1}{4}$ sec. cor. of sec. 22 is at mid-point on the W. bdy. of the section.

Set the post 12 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
|
 $\frac{1}{4}$
S22
1962

From this cor. the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented by an iron post as described in the official record, bears S. $0^{\circ}02'$ E., 60 lks. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 21 only, therefore I remark cap to read

T11N R14W
 $\frac{1}{4}$ |
S21
1913
1962

From the cor. of secs. 22, 23, 26 and 27.

S. $0^{\circ}01'$ E., bet. secs. 26 and 27.

Desc. S. slope.

- 3.60 Spur, projects SW.
- 30.00 Spur, projects SE.
- 39.10 Spur, projects SE.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.

Set the post 12 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
 $\frac{1}{4}$
S27 | S26
1962

Desc. S. slope.

- 42.70 Spur, projects, SE.
- 43.60 Road, bladed, bears N. 70° W. and S. 70° E.; asc. N. slope.
- 68.30 Crest of knoll; desc. S. slope.
- 76.90 Point selected for the witness cor. of secs. 26, 27, 34 and 35.

Set the post 4 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
S27 | S26
S34 | S35
W | C
1962

CHAINS					
80.00	<p>True point for the cor. of secs. 26, 27, 34 and 35; falls in the bottom of a nearly vertical ravine, not feasible to monument.</p> <p>Land, steep and mountainous. Soil, sandy and rocky loam. Timber, none; undergrowth, cactus and greasewood.</p> <hr/> <p>S. 89°52' E., bet. secs. 26 and 35.</p>				
2.00	<p>Edge of deep ravine in which true point for cor. is located, drains irregularly W. and SW.; asc. nearly vertical W. slope.</p>				
6.00	<p>Spur, projects N. 30° W.</p>				
11.70	<p>Wash, 2 ft. deep, 20 lks. wide, drains NW.</p>				
24.50	<p>Road, follows crest of ridge bearing N. and S.</p>				
36.50	<p>Ravine, drains SE.</p>				
40.15	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.</p> <p>Set the post 6 ins. in the ground, mound with stone to top, cap mkd.</p> <div style="text-align: center;"> <p>T11N R14W</p> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">$\frac{1}{4}$</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 26</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 35</td> </tr> </table> <p>1962</p> </div>	$\frac{1}{4}$	S 26		S 35
$\frac{1}{4}$	S 26				
	S 35				
43.40	<p>Ridge, bears N. and S.</p>				
45.00	<p>Wash, 3 ft. deep, 200 lks. wide, drains S.</p>				
73.00	<p>Spur, projects S.</p>				
80.30	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, steep and broken. Soil, sandy and rocky clay loam. Timber, none; undergrowth, cactus, palo verde and greasewood.</p> <hr/> <p>From the true point for the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 0°01' E., bet. secs. 34 and 35.</p>				
1.00	<p>S. edge of canyon floor.</p>				
7.45	<p>Spur, projects SW.</p>				
15.00	<p>Spur, projects SW.</p>				
28.00	<p>Spur, rocky, projects SE.</p>				
31.00	<p>Canyon, drains SW.; asc. N. slope.</p>				
40.00	<p>True point for the $\frac{1}{4}$ sec. cor. of sec. 34 and 35, impossible to perpetuate at this location.</p>				
47.00	<p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 34 and 35.</p> <p>Set the post 6 ins. in the ground, mound with stone to top, cap mkd.</p>				

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Completion Survey, Subdivisions
Township 11 North, Range 14 West, Arizona

T11N R14W

$\frac{1}{4}$

WC

S34 | S35

1962

Cor. is located on ridge, bearing SE. and NW.

52.00

Spur, projects E.

56.60

Knoll, rocky.

61.00

Spur, rocky, projects SE.

65.00

Spur, rocky, projects SW.

73.00

Wash, 2 ft. deep, 10 lks. wide, drains SE.

74.00

Spur, rocky, projects SE.

82.06

Point for the closing cor. of secs. 34 and 35 on the S. bdy. of the township.

Set the post 12 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W

S34 | S35
C | C

T10N

1962

From this cor., the cor. of secs. 2, 3, 34 and 35, monumented by an iron post as described in the official record, bears N. 89°57' W., 1.96 chs. dist. This cor. now functions as the cor. of secs. 2 and 3 only, therefore I remark cap to read

S 3 | S 2

T10N R14W

1913

1962

Land, rolling and broken.
Soil, sandy clay loam.
Timber, none; undergrowth, desert vegetation.

The point for the $\frac{1}{4}$ cor. of sec. 35 is at mid-point bet. the closing cors. and on the S. bdy. of the township.

Set the post 10 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W

$\frac{1}{4}$ S 35

T10N

1962

From this cor. the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, monumented by an iron post as described in the official record, bears N. 89°57' W., 2.02 chs. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 2 only, therefore I remark the cap to read

CHAINS	
	<hr/> $\frac{1}{4}$ S 2 T10N R14W 1913 1962 <hr/>
	From the cor. of secs. 21 and 28.
	S. 0°02' E., bet. secs. 27 and 28.
5.32	Ridge, bears NW. by SE.
6.92	Spur, projects SW.
20.02	Ravine, drains SW.; asc. steep N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of sec. 28, impossible to perpetuate.
45.00	Point selected for the witness $\frac{1}{4}$ sec. cor. of sec. 28.
	Set the post 8 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W WC $\frac{1}{4}$ S28 1962
45.02	Spur, projects E.
56.82	Ravine, drains SE.; asc. N. slope.
67.32	Spur, projects SE.
71.82	Spur, projects SW.
80.00	Point for the cor. of secs. 28 and 33.
	Set the post 8 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W $\frac{1}{4}$ S 28 $\frac{1}{4}$ S 33 1962
	Land, broken and mountainous. Soil, rocky and sandy loam. Timber, none; undergrowth, scattered cactus, palo verde and greasewood.
	S. 0°02' E., bet. secs. 33 and 34.
	Desc. steep, rocky, S. slope.
10.00	Toe of slope, continue over slight S. slope.
13.80	Road, abandoned, bears S. 30° W. and N. 30° E.
18.70	Wash, 2 ft. deep, 25 lks. wide, drains S.; thence in wash.
20.50	Leave wash, course SE.
26.40	Spur, projects SW.
28.80	Wash, 2 ft. deep, 25 lks. wide, drains SE.
32.40	Wash, same, drains SW.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Completion Survey, Subdivisions
Township 11 North, Range 14 West, Arizona

- 35.80 Spur, projects SW.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 33, impossible to perpetuate.
- 43.21 Point selected for the witness $\frac{1}{4}$ sec. cor. of sec. 33.
Set the post 8 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
WC
 $\frac{1}{4}$ S33|
1962

- 54.70 Wash, 2 ft. deep, 10 lks. wide, drains SW.
- 60.90 Wash, 2 ft. deep, 15 lks. wide, drains SW.
- 67.90 Wash, $2\frac{1}{2}$ ft. deep, 20 lks. wide, drains SW.

- 81.21 Point for the closing cor. of secs. 33 and 34 on the S. bdy. of the township.
Set the post 10 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
S33|S34
C C

T10N
1962

From this cor. the cor. of secs. 3, 4, 33 and 34, monumented by an iron post as described in the official record, bears N. $89^{\circ}57'$ W., 1.70 chs. dist. This cor. now functions as the cor. of secs. 3 and 4 only, therefore I remark cap to read

T11N
S 4|S 3
1913
1962

Land, mountainous and broken.
Soil, sandy clay loam.
Timber, none; undergrowth, cactus, catclaw, palo verde and greasewood.

The point for the S. $\frac{1}{4}$ sec. cor. of sec. 34 is at mid-point bet. the closing cors. and on the S. bdy. of the township.

Set the post 10 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
 $\frac{1}{4}$ S 34

T10N
1962

From this cor., the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, monumented by an iron post as described in the official record, bears N. $89^{\circ}57'$ W., 1.83 chs. dist. This cor.

CHAINS

now functions as the $\frac{1}{4}$ sec. cor. of sec. 3 only,
therefore I remark cap to read

$\frac{1}{4}$ S 3
 T10N R14W
 1913
 1962

From the cor. of secs. 26, 27, 34 and 35.

West, bet. secs. 27 and 34, by triangulation, topography
is estimated.

Desc. steep SE. slope.

34.70 Canyon floor, drains S.; asc. steep slope.

36.00 Road, bears irregularly N. and S.

40.22 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.

Set the post 10 ins. in the ground, mound with stone
to top, cap mkd.

T11N R14W
 $\frac{1}{4}$ $\frac{S\ 27}{S\ 34}$
 1962

41.90 Ridge, bears irregularly N. and S.

46.10 Ravine, drains SW.

50.20 Spur, projects SW.

75.40 Canyon, drains SW.

80.44 Point for the closing cor. of secs. 27 and 34 on the
line bet. secs. 27 and 28; the cor. of secs. 28 and 33
bears S. $0^{\circ} 02'$ E., 0.68 chs. dist.

Set the post 8 ins. in the ground, mound with stone
to top, cap mkd.

T11N R14W
 $\frac{C\ S\ 27}{C\ S\ 34}$
 1962

Land, steep broken, mountainous.
Soil, extremely rocky and sandy loam.
Timber, none; undergrowth, cactus, palo verde and
greasewood.

The W. $\frac{1}{4}$ sec. cor. of sec. 27 is at mid-point on the
line bet. secs. 27 and 28, impossible to perpetuate.

The witness $\frac{1}{4}$ sec. cor. of sec. 28 is selected as the
witness $\frac{1}{4}$ sec. cor. for sec. 27; therefore I remark
the cap to read

T11N R14W
 WC
 $\frac{1}{4}S28 | \frac{1}{4}S27$
 1962

From the true point for the W. $\frac{1}{4}$ sec. cor. of sec. 27
the true point for the E. $\frac{1}{4}$ sec. cor. of sec. 28 bears
S. $0^{\circ}02'$ E., 0.68 chs. dist.

The W. $\frac{1}{4}$ sec. cor. of sec. 34 is 40.00 chs. in southing
from the CC of secs. 27 and 34 and on the line bet.
secs. 33 and 34, impossible to perpetuate.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Completion Survey, Subdivisions
Township 11 North, Range 14 West, Arizona

The witness $\frac{1}{4}$ sec. cor. of sec. 33 is selected as the witness $\frac{1}{4}$ sec. cor. for sec. 34, therefore I remark the cap to read

T11N R14W
WC
 $\frac{1}{4}$ | $\frac{1}{4}$
S 33 | S 34
1962

From the true point for the W. $\frac{1}{4}$ sec. cor. of sec. 34, the true point for the E. $\frac{1}{4}$ sec. cor. of sec. 33 bears S. $0^{\circ}02'$ E., 0.68 lks. dist.

From the cor. of secs. 20, 21, 28 and 29, monumented by an iron post as described in the official record.

S. $0^{\circ}02'$ E., bet. secs. 28 and 29.

Desc. S. slope.

- 5.40 Spur, projects W.
- 30.00 Ridge, bears E. and W.
- 35.10 Ravine, drains SE.
- 39.60 Ravine, drains SE.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.
- Set the post 18 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
 $\frac{1}{4}$
S 29 | S 28
1962

- 41.30 Spur, projects E.
- 43.10 Wash, $2\frac{1}{2}$ ft. deep, 10 lks. wide, drains NE.; asc. N. slope.
- 52.20 Top of knoll.
- 65.60 Spur, projects SE.
- 74.20 Wash, 2 ft. deep, 10 lks. wide, drains SW.
- 80.00 Point for the cor. of secs. 28, 29, 32, and 33.

Set the post 18 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
S29 | S28
S32 | S33
1962

Land, steep and broken.
Soil, rocky clay loam.
Timber, none; undergrowth, cactus, palo verde and greasewood.

CHAINS	
	S. 89°55' E., bet. secs. 28 and 33.
	Asc. W. slope.
9.50	Wash, 1 ft. deep, 100 lks. wide, drains SW.
10.40	Road, bears SW. and NE. 2 chs. to end; asc. W. slope.
32.40	Ridge, bears NE. and SW.; desc. E. slope.
39.96	Point for the ¼ sec. cor. of secs. 28 and 33.
	Set the post 12 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W ¼ $\frac{S\ 28}{S\ 33}$ 1962
47.00	Wash, 3 ft. deep, 800 lks. wide, drains S.
52.80	Spur, projects S.
64.20	Ravine, drains S.
68.90	Toe of steep spur, projecting S.
73.90	Ravine, drains SW.
77.90	Spur, projects SW.
79.92	The cor. of secs. 28 and 33.
	Land, steep and broken. Soil, rocky clay. Timber, none; undergrowth, cactus, palo verde and greasewood.
	From the cor. of secs. 28, 29, 32 and 33.
	S. 0°02' E., bet. secs. 32 and 33.
	Asc. N. slope.
11.00	Spur, projects SE.
18.80	Road, graded, bears N. 65° E. by S. 65° W.; desc. S. slope.
27.20	Wash, 2 ft. deep, 10 lks. wide, drains SW.
32.10	Ridge, rocky, bears S. 30° W. and N. 30° E.
40.00	True point for the ¼ sec. cor. of secs. 32 and 33, impossible to perpetuate.
41.10	Wash, 2½ ft. deep, 20 lks. wide, drains SW.
41.51	Point selected for the witness ¼ sec. cor. of secs. 32 and 33.
	Set the post 4 ins. in the ground, mound with stone to top, cap mkd.
	T11N R14W ¼ WC S32 S33 1962

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS

Completion Survey, Subdivisions
Township 11 North, Range 14 West, Arizona

- 45.20 Spur, projects SW.
- 53.10 Spur, projects SE.
- 56.10 Saddle and ridge bears S. 70° E. and N. 70° W.
- 61.30 Wash, 2½ ft. deep, 60 lks. wide, drains SW.
- 71.70 Wash, 2 ft. deep, 10 lks. wide, drains SW.
- 74.20 Spur, projects SW.
- 81.11 Point for the closing corner of secs. 32 and 33 on the S. boundary of the township.

Set the post 3 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
S32 | S33
C | C

1962

From this cor. the cor. of secs. 4, 5, 32 and 33, monumented by an iron post as described in the official record, bears N. 89°57' W., 2.21 chs. dist. This cor. now functions as the cor. of secs. 4 and 5 only, therefore I remark cap to read

T11N
S 5 | S 4
T10N R14W
1913
1962

Land, broken and mountainous.
Soil, sandy clay loam.
Timber, none; undergrowth, desert vegetation.

The point for the S. ¼ sec. cor. of sec. 33 is at mid-point bet. closing cors., and on the S. bdy. of the township.

Set the post 8 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
¼ S 33

T10N
1962

From this cor. the witness ¼ sec. cor. of secs. 4 and 33, monumented by an iron post as described in the official record, bears N. 89°57' W., 1.20 chs. dist. This cor. now functions as the witness cor. of sec. 4 only, therefore I remark the cap to read

WC ¼ -----
S 4
T10N R14W
1913
1962

CHAINS

From the cor. of secs. 19, 20, 29 and 30, monumented by an iron post as described in the official record.

S. 0°03' E., bet. secs. 29 and 30.

Desc. S. slope.

2.50 Wash, 2 ft. deep, 30 lks. wide, drains SE.; asc. along broken NE. slope.

18.80 Spur, projects E.; desc. S. slope.

24.50 Wash, 2 ft. deep, 100 lks. wide, drains SE.; asc. N. slope.

33.40 Spur, projects S. 10° E.; desc. S. slope.

39.20 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 29 and 30.

Set the post 10 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
 $\frac{1}{4}$
 WC
 S30|S29
 1962

40.00 True point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, impossible to perpetuate.

40.20 Wash, 2 ft. deep, 100 lks. wide, drains SW.; asc. N. slope.

53.70 Spur, projects W.; desc. SW. slope.

71.10 Wash, 2 ft. deep, 100 lks. wide, drains SE.; asc. broken N. slope.

76.20 Spur, projects E.

77.70 Ravine, drains E.; asc. N. slope.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

Set the post 12 ins. in the ground, mound with stone to top, cap mkd.

T11N R14W
S30|S29
S31|S32
 1962

Land, steep and broken.
 Soil, clay.
 Timber, none; undergrowth, cactus, palo verde and greasewood.

East, bet. secs. 29 and 32.

Desc. E. slope.

6.41 Wash, 2 ft. deep, 200 lks. wide, drains S.

25.26 Ridge, bears NE. and S.

30.80 Ravine, drains S.

31.30 Spur, projects S.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Completion Survey, Subdivisions Township 11 North, Range 14 West, Arizona
32.60	Gorge, 100 ft. deep, drains S.
40.24	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32. Set the post 10 ins. in the ground, mound with stone to top, cap mkd. <div style="text-align: center;"> T11N R14W $\frac{1}{4}$ $\frac{S\ 29}{S\ 32}$ 1962 </div>
41.30	Ravine, drains SW.
47.80	Ridge, bears NE. and SW.
51.90	Ravine, drains S.
62.60	Ravine, drains S.; asc. steep SW. slope.
67.60	Peak of ridge, bears NE. and SW.; desc. E. slope.
75.00	Wash, 1 ft. deep, 30 lks. wide, drains SW.
80.48	The cor. of secs. 28, 29, 32 and 33. Land, steep and broken. Soil, clay. Timber, none; undergrowth, cactus, palo verde and greasewood.
	<hr/> From the cor. of secs. 29, 30, 31 and 32. S. 89°47' W., bet. secs. 30 and 31. Desc. W. slope.
10.90	Wash, 2 ft. deep, 50 lks. wide, drains S.
19.40	Crest, lava outcropping.
29.20	Crest, lava outcropping, bears irregularly N. and S.
35.90	Wash, 2 ft. deep, 100 lks. wide, drains S.; continue across broken S. slope and lava ledges.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31. Set the post 8 ins. in the ground, mound with stone to top, cap mkd. <div style="text-align: center;"> T11N R14W $\frac{1}{4}$ $\frac{S\ 30}{S\ 31}$ 1962 </div>
50.00	Ravine, drains SW.
55.74	Ridge, bears NE. and SW.
64.10	Wash, 1 ft. deep, 30 lks. wide, drains SW.

CHAINS	
79.96	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the township, as described in the field notes of the concurrent survey of the E. bdy. of T. 11 N., R. 15 W., under this group.</p>
	<hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p>
	<p>S. 0°03' E., bet. secs. 31 and 32.</p>
	<p>Asc. N. slope.</p>
3.90	<p>Spur, projects SE.; desc. S. slope.</p>
13.90	<p>Ravine, drains E.; asc. NE. slope.</p>
27.30	<p>Ravine, drains SW.; asc. rocky N. slope.</p>
32.90	<p>High and rocky peak.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.</p>
	<p>Set the post 6 ins. in the ground, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T11N R14W $\frac{1}{4}$ S31 S32 1962</p>
	<p>Desc. S. slope.</p>
48.60	<p>Wash, 2 ft. deep, 25 lks. wide, drains SE.; asc. N. slope.</p>
55.60	<p>Spur, projects SE.; desc. S. slope.</p>
59.50	<p>Road, graded, bears SE. and NW.</p>
64.60	<p>Road, same, bears NE. and SW.</p>
68.40	<p>Ravine, drains SW.; asc. rocky N. slope.</p>
71.60	<p>Spur, projects E.; desc. S. slope.</p>
76.50	<p>Wash, 2 ft. deep, 50 lks. wide, drains SW.</p>
77.69	<p>Intersect line 4-1 M.S. No. 3983 Pittsburg No. 2 lode; from which Cor. No. 4 bears N. 47°42' E., 20.78 chs. dist., and Cor. No. 1 bears S. 47°42' W., 1.95 chs. distant.</p>
80.83	<p>Point for the closing cor. of secs. 31 and 32 on the S. bdy. of the township.</p>
	<p>Set the post 6 ins. in the ground, mound with stone to top, cap mkd.</p>
	<p style="text-align: center;">T11N R14W S31 S32 <u> C C </u> T10N 1962</p>
	<p>From this cor. the cor. of secs. 5, 6, 31 and 32, monumented by an iron post as described in the official record, bears N. 89°57' W., 1.90 chs. dist. This cor. now functions as the cor. of secs. 5 and 6 only, therefore I remark cap to read</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

37.

CHAINS

Completion Survey, Subdivisions
Township 11 North, Range 14 West, Arizona
$$\begin{array}{r} \text{T11N} \\ \hline \text{S } 6 \mid \text{S } 5 \\ \text{T10N R14W} \\ 1913 \\ 1962 \end{array}$$

Land, broken and mountainous.
Soil, sandy clay loam.
Timber, none; undergrowth, desert vegetation.

The point for the S. $\frac{1}{4}$ sec. cor. of sec. 32 is at mid-point bet. the closing corners and on the S. bdy. of the township.

Set the post 12 ins. in the ground, mound with stone to top, cap mkd.

$$\begin{array}{r} \text{T11N R14W} \\ \hline \frac{1}{4} \text{ S } 32 \\ \text{T10N} \\ 1962 \end{array}$$

From this cor. the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, monumented by an iron post as described in the official record, bears N. $89^{\circ}57'$ W., 2.05 chs. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 5 only, therefore I remark cap to read

$$\begin{array}{r} \text{T11N} \\ \hline \frac{1}{4} \text{ S } 5 \\ \text{T10N R14W} \\ 1913 \\ 1961 \end{array}$$

The point for the S. $\frac{1}{4}$ sec. cor. of sec. 31 is at 40.00 chs. in westing from the CC of secs. 31 and 32 and on the S. bdy. of the township.

Set the post 10 ins. in the ground, mound with stone to top, cap mkd.

$$\begin{array}{r} \text{T11N R14W} \\ \hline \frac{1}{4} \text{ S } 31 \\ \text{T10N} \\ 1962 \end{array}$$

From this cor. the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented by an iron post as described in the official record, bears N. $89^{\circ}57'$ W., 1.90 chs. dist. This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 6 only, therefore I remark the cap to read

$$\begin{array}{r} \text{T11N} \\ \hline \frac{1}{4} \text{ S } 6 \\ \text{T10N R14W} \\ 1913 \\ 1962 \end{array}$$

CHAINS

General Description

The land within Township 11 North, Range 14 West is principally rolling mountains and broken mesa, with steep lava and sandstone formations. It has a general southwesterly exposure and drainage emptying into the Bill Williams River which flows westerly just below the south boundary of the township.

There is a great deal of mining activity in the township, much of which is current.

Due to the mining activity there are several graded roads connecting with the Kingman and Yucca road. There are also numerous dead end roads into the south and southeast portion.

The soil is principally a light shallow sandy clay, with numerous sandstone and lava outcroppings, covered with a scattered undergrowth of cacti, palo verde, and greasewood. There is no timber.

The only water noted is an intermittent underground seepage in a wash which drains S. through the west half of section 26, then diagonally from the northeast corner to the southwest corner of section 35. In this area the rock formations have formed a series of "tanks" which are filled with sand. The water remains from one foot to three feet below the surface of the sand with the exception of the places where it must pass over a series of rock drops. The water flowing from one such rock drop is estimated to be ten gallons per hour. A miner located in section 26 has piped water from this wash to his cabin.

40

0

CERTIFICATE OF SURVEY

I, Virgil E. Spratt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2th day of September, 19 61, I have dependently resurveyed the east boundary and made a completion survey of the subdivisional lines of Township 11 North, Range 14 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 16, 1962
(Date)

Virgil E. Spratt
(Cadastral Surveyor)
Virgil E. Spratt

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL
Bureau of Land Management

The foregoing field notes of the dependent resurvey of the east boundary and completion survey of the subdivisional lines of Township 11 North, Range 14 West, Gila and Salt River Meridian, Arizona,

executed by Virgil E. Spratt, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

Washington, D. C.
SEP 24 1963
(Date)

RE Brown
Acting (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in Arizona, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)