

BOOK 1870

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

SURVEY

North Boundary

Subdivisional Lines

Township 41 North, Range 10 West

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Paul G. Bauer, Surveying Technician

Under special instructions dated June 22, 19 62, which provided for the surveys included under Group Number 377, approved July 2, 1962, and assignment instructions dated August 31, 19 62.

Survey commenced September 4, 19 62

Survey completed October 9, 19 62

1A

4376

INDEX DIAGRAM

Township 41 North, Range 10 West,

5	4	3	2	2	1
6 39	5 30	4 24	3 18	2 11	1
38	38	29	23	17	11
7 37	8 29	9 23	10 17	11 10	12
37	36	28	22	16	10
18 35	17 27	16 22	15 15	14 9	13
35	34	27	21	15	9
19 34	20 26	21 21	22 14	23 8	24
33	32	26	20	14	8
30 32	29 26	28 19	27 13	26 7	25
31	31	25	19	12	6
31 30	32 24	33 18	34 12	35 5	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

1. B

CHAINS	
	<p>Township 41 North, Range 10 West, Gila and Salt River Meridian, Arizona</p> <hr/> <p>The east boundary was surveyed in 1925 by Hiester and Bandy. The south boundary which is the Tenth Standard Parallel North, was surveyed in 1939 by Muscott and Warner. The west boundary was surveyed in 1956 by P. K. Russell.</p> <p>The following notes are those of the survey of the north boundary and the subdivisional lines of Township 41 North, Range 10 West, Gila and Salt River Meridian, Arizona.</p> <p>This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated June 22, 1962.</p> <p>Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.</p> <p>The geographical position of the southeast corner of the township is: Latitude, 36°54'13.61" North and Longitude, 113°18'58.8" West.</p> <p>The magnetic declination was found to be 16° East.</p> <hr/> <p style="text-align: center;">Survey of the North Boundary Township 41 North, Range 10 West</p> <hr/> <p>From the cor. of Ts. 41 and 42 N., Rs. 9 and 10 W., monumented by an iron post as described in the official record.</p> <p>S. 89°56' W., bet. secs. 1 and 36.</p> <p>Over gently rolling W. slope through moderate creosote brush.</p> <p>8.30 Low spur, slopes SW.; thence over gently rolling land.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 1 and 36.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T42N R10W ¼ $\frac{S \ 36}{S \ 1}$ T41N 1962</p> <p>47.50 Graded road leading to Hurricane, Utah, bears N. 69°30' E. and S. 69°30' W.</p> <p>53.50 Wash, 20 lks. wide, 1 ft. deep, drains S. 60° W.</p> <p>67.80 Wash, 5 lks. wide, 1 ft. deep, drains S. 20° W.</p>

2

CHAINS

- 79.80 Point selected for the witness cor. of secs. 1, 2, 35 and 36.
- Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.
- | | |
|-----------|-----|
| T42N R10W | |
| S35 | S36 |
| S2 | S1 |
| WC | |
| T41N | |
| 1962 | |
- 80.00 True point for the cor. of secs. 1, 2, 35 and 36 falls in wash 30 lks. wide, 2 ft. deep, draining S. 20° W.
- Land, gently rolling.
Soil, gravelly.
No timber; undergrowth, creosote brush and black brush.
-
- S. 89°56' W., bet. secs. 2 and 35.
- Over gently rolling land draining S.
- 15.20 Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.
- 16.00 Old road, bears N. and S.
- 23.00 Dim blade road, bears N. 20° E. and S. 20° W.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35.
- Set the iron post 20 ins. in the ground and in a collar of stone, cap mkd.
- | | |
|------------------------------------|--|
| T42N R10W | |
| $\frac{1}{4}$ $\frac{S\ 35}{S\ 2}$ | |
| T41N | |
| 1962 | |
- Raise a mound of stone N. of the cor.
- 57.30 Dim road, bears SE. and NW.
- 79.80 Point selected for the witness cor. of secs. 2, 3, 34 and 35.
- Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
- | | |
|-----------|-----|
| T42N R10W | |
| S34 | S35 |
| S3 | S2 |
| WC | |
| T41N | |
| 1962 | |
- 80.00 True point for the cor. of secs. 2, 3, 34 and 35 falls in edge of Ft. Pearce Wash.
- Land, gently rolling.
Soil, gravelly.
No timber; undergrowth, creosote brush and black brush.
-
- S. 89°56' W., bet. secs. 3 and 34.
- Over rolling land.
- .70 Ft. Pearce Wash, 100 lks. wide, 3 ft. deep, drains NW.; asc. NE. slope.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>N. Bdy., T. 41 N., R. 10 W., Arizona</p> <hr/>
14.00	<p>Ravine, drains N. 10° E.; asc. over steep rocky NE. slope.</p>
32.80	<p>West edge of escarpment, bears N. and S. 25° E.; desc. over steep SW. slope.</p>
39.50	<p>Wash, 50 lks. wide, 1 ft. deep, drains NW.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 3 and 34.</p> <p>Set the iron post 24 ins. in the ground and in a collar of stone, cap mkd.</p>
	<p>T42N R10W $\frac{1}{4} \frac{S \ 34}{S \ 3}$ T41N 1962</p>
	<p>Raise a mound of stone N. of the cor.</p>
	<p>Asc. over rolling E. slope.</p>
51.00	<p>Slope changes to rolling N.</p>
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34.</p> <p>Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p>T42N R10W $\frac{S33 \ S34}{S \ 4 \ S \ 3}$ T41N 1962</p>
	<p>Land, rolling and slightly broken. Soil, rocky. No timber; undergrowth, creosote and blackbrush.</p> <hr/>
	<p>S. 89°56' W., bet. secs. 4 and 33.</p>
	<p>Over rolling N. slope cut by small gullies and ravines draining N.</p>
25.20	<p>Desc. over steep W. slope.</p>
31.20	<p>Main Run Wash, 150 lks. wide, 3 ft. deep, drains N.; asc. over E. slope.</p>
39.30	<p>Small spur, slopes N. 1.00 ch. to end.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 4 and 33.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p>T42N R10W $\frac{1}{4} \frac{S \ 33}{S \ 4}$ T41N 1962</p>

CHAINS	
41.50	Small ravine, drains N. 30° E.; asc. over rocky E. slope.
49.10	Rocky point, projects N.
52.30	Ravine, 10 lks. wide, 1 ft. deep, drains N. 15° W.
64.40	Ravine, 15 lks. wide, 1 ft. deep, drains N. 10° E.
70.20	Spur, slopes N.
75.70	Desc. over steep W. slope.
80.00	Point for the cor. of secs. 4, 5, 32 and 33.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T42N R10W S32 S33 S 5 S 4 T41N 1962
	Land, broken rocky hills. Soil, rocky. No timber; undergrowth, scattered brush.
S. 89°56' W., bet. secs. 5 and 32.	
	Over rolling mountainous land; desc. W. slope.
.50	Wash, 10 lks. wide, 1 ft. deep, drains N. for 1.80 chs. thence NE.; asc. over E. slope.
7.70	Asc. over rocky N. slope.
12.40	Desc. over steep W. slope.
19.80	Wash, 10 lks. wide, 3 ft. deep, drains N.; asc. over steep E. slope.
29.00	Rocky spur, slopes N.
30.70	Desc. over steep W. slope.
38.80	Wash, 10 lks. wide, 1 ft. deep, drains N.
40.00	Point for the ¼ sec. cor. of secs. 5 and 32.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T42N R10W ¼ S 32 S 5 T41N 1962
	Asc. over steep rocky E. slope.
49.80	Slope changes to broken, rocky N.
66.40	Deep ravine, drains N. for 1.00 ch. thence NE.
80.00	Point for the cor. of secs. 5, 6, 31 and 32.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>N. Bdy., T. 41 N., R. 10 W., Arizona</p>
	<p style="text-align: center;">T42N R10W S31 S32 S 6 S 5 T41N 1962</p> <p>Land, rolling and broken. Soil, rocky. No timber; undergrowth, scattered brush.</p>
	<p>S. 89°56' W., bet. secs. 6 and 31.</p>
	<p>Over broken, rocky N. slope cut by numerous small washes and gullies.</p>
38.80	<p>West edge of escarpment bears N. and S.; desc. abruptly over W. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 6 and 31.</p>
	<p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T42N R10W ¼ S 31 S 6 T41N 1962</p>
	<p>Desc. over steep rocky W. slope.</p>
59.60	<p>Base of steep desc.; thence, over gently rolling land.</p>
79.30	<p>Wash, 50 lks. wide, 1 ft. deep, drains N. 80° W. from SE.</p>
79.71	<p>The cor. of Ts. 41 and 42 N., Rs. 10 and 11 W., monumented by an iron post as described in the official record.</p>
	<p>Land, broken on E. 50.00 chs., gently rolling on remainder. Soil, rocky, clay loam. No timber; undergrowth, scattered brush.</p>
	<p style="text-align: center;">Survey of the Subdivisional Lines Township 41 North, Range 10 West</p>
	<p>From the standard corner of secs. 35 and 36 on the S. bdy. of the township, monumented by an iron post as described in the official record.</p>
	<p>N. 0°01' W., bet. secs. 35 and 36.</p>
	<p>Over gently rolling hills, E. drainage.</p>
14.90	<p>Wash, 20 lks. wide, 3 ft. deep, drains E.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 35 and 36.</p>
	<p>Set the iron post 10 ins. in the ground, mound with</p>

CHAINS		
	stones to top, cap mkd.	
		T41N R10W $\frac{1}{2}$ S35 S36 1962
65.40	Confluence of two washes draining E. from W. and S. 10° W.	
72.90	Desc. over steep NE. slope.	
80.00	Point for the cor. of secs. 25, 26, 35 and 36.	
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R10W S26 S25 S35 S36 1962
	Raise a mound of stone W. of the cor.	
	Land, rolling hills. Soil, gravelly and rocky. No timber; undergrowth, sage and black brush.	
	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the township, monumented by an iron post as described in the official record.	
	West, bet. secs. 25 and 36.	
	Over rolling canyon bottom.	
2.40	Wash, 10 lks. wide, 1 ft. deep, drains N. 2.00 chs. to junction.	
7.10	Wash, 15 lks. wide, 1 ft. deep, drains N. 60° E.	
8.90	Wash, 20 lks. wide, 1 ft. deep, drains S. 60° E.	
13.00	Wash, 15 lks. wide, 1 ft. deep, drains N. 60° E. curving to SE.; asc. over steep E. slope.	
20.40	Asc. over gentle E. slope.	
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.	
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R10W $\frac{1}{4}$ $\frac{S\ 25}{S\ 36}$ 1962
54.70	Edge of canyon, bears irregularly NE. and SW.; desc. over steep NW. slope.	
60.10	Base of steep slope; continue along canyon bottom.	
69.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 70° E. curving to N.	
79.90	Same wash, drains S. 60° E. curving to N. 70° E.	
80.06	The cor. of secs. 25, 26, 35 and 36.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 41 N , R. 10 W., Arizona
	<p>Land, rolling hills. Soil, rocky and gravelly. No timber; undergrowth, moderate brush.</p>
	<p>N. 0°01' W., bet. secs. 25 and 26.</p> <p>Over rolling hills, E. drainage.</p>
.35	Wash, 10 lks. wide, 1 ft. deep, drains S. 60° E. from irregularly SW.; asc. over steep S. slope.
6.30	N. rim of canyon, bears N. 80° W. and S. 80° E.; thence over spur sloping E.
8.80	S. rim of small canyon, bears S. 60° W. and N. 60° E.; desc. over steep N. slope.
11.80	Wash, 5 lks. wide, 1 ft. deep, drains NE.
15.80	Wash, 20 lks. wide, 1 ft. deep, drains E.; asc. steep S. slope.
20.20	Canyon rim, bears S. 60° W. and NE.; thence, over spur sloping E.
29.20	Desc. over steep NW. slope.
35.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 70° E.; asc. over steep S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.
	<p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W $\frac{1}{4}$ S26 S25 1962</p>
41.80	N. rim of canyon, bears N. 60° E. and S. 60° W.; desc. over gentle NW. slope.
55.00	Slope changes to E.
70.70	Wash, 20 lks. wide, 3 ft. deep, drains E. for 2.00 chs. thence N.
78.10	Confluence of two washes draining NE. from S. 20° E. and SW.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	<p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W S23 S24 S26 S25 1962</p> <p>Raise a mound of stone W. of the cor.</p>

CHAINS

Land, rolling hills cut by canyons draining E.
Soil, rocky and gravelly.
No timber; undergrowth, moderate sage and black brush.

From the true point for the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the township, the witness cor. which bears South 32 lks. dist. is monumented by an iron post as described in the official record.

S. 89°57' W., bet. secs. 24 and 25.

Over steep broken slopes of Cottonwood Canyon; by traverse and triangulation; asc. over broken ledgy SE. slope.

20.80 Rocky spur on N. side of Cottonwood Canyon, projects S. 20° W.; desc. over steep, ledgy W. slope.

36.70 Cottonwood Wash, 40 lks. wide, 1 ft. deep, drains N. 20° W. from S. 10° E.; asc. steep E. slope.

40.03 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W

$\frac{1}{4}$ $\frac{S\ 24}{S\ 25}$

1962

Continue by triangulation.

77.40 S. rim of Cottonwood Canyon, bears N. 5° W. and S. curving to E.

80.06 The cor. of secs. 23, 24, 25 and 26.

Land, broken slopes of Cottonwood Canyon.
Soil, rocky.
Timber, none; undergrowth, sparse brush.

N. 0°01 W., bet. secs. 23 and 24.

Along S. side of Cottonwood Canyon.

11.60 Spur, projects sharply N. 60° E., by triangulation desc. over steep ledgy N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W

$\frac{1}{4}$ S23|S24

1962

End of triangulation; desc. NE. slope.

45.30 Cottonwood Wash, drains NW.; thence along rolling W. slope near the base of the Hurricane Cliffs.

80.00 Point for the cor. of secs. 13, 14, 23 and 24.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 41 N., R. 10 W., Arizona
	T41N R10W S14 S13 S23 S24 1962
	Land, broken canyon walls and steep slopes. Soil, rocky. No timber, scant undergrowth.
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township, monumented by an iron post as described in the official record.
	S. 89°56' W., bet. secs. 13 and 24.
	Over gently rolling land through moderate brush.
35.10	Wash, 5 lks. wide, 1 ft. deep, drains N.
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W $\frac{1}{4}$ S 13 S 24 1962
44.60	Rim of Hurricane Cliffs, bears N. 15° E. and S. 15° W.; by triangulation desc. over broken cliffs and steep slope facing W.
80.08	The cor. of secs. 13, 14, 23 and 24.
	Land, rolling on E. 44.00 chs., broken on remainder. Soil, gravelly and rocky. No timber; undergrowth, moderate brush on top of cliffs.
	N. 0°01' W., bet. secs. 13 and 14.
	Over gently rolling NW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W $\frac{1}{4}$ S14 S13 1962
80.00	Point for the cor. of secs. 11, 12, 13, and 14.
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W S11 S12 S14 S13 1962

CHAINS		
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling NW. slope. Soil, rocky and gravelly. No timber; undergrowth, moderate creosote brush, blackbrush and cactus.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>S. 89°56' W., bet. secs. 12 and 13.</p> <p>Over gently rolling land.</p>	
11.90	Wash, 10 lks. wide, 1 ft. deep, drains N.	
18.40	Rim of Hurricane Cliffs, bears N. and S.; by triangulation, desc. over nearly vertical ledges and steep slope facing West.	
40.02	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W 1/4 S 12 S 13 1962</p>	
	<p>The cor. is located at the base of the Hurricane Cliffs.</p> <p>End of triangulation; desc. over W. slope.</p>	
80.04	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling and broken. Soil, rocky and gravelly. No timber; undergrowth, blackbrush and creosote.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over gently rolling W. slope through moderate brush.</p>	
34.80	Wash, 50 lks. wide, 1 ft. deep, drains W. 1.00 ch. to main wash draining N.	
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12 falls on E. bank of wash, drains N. 30° W. from S., unsafe position.	
40.30	<p>Point selected for the witness 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set the iron post 20 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W 1/4 S11 S12 WC 1962</p>	
72.10	Fort Pearce Wash, 150 lks. wide, 2 ft. deep, drains N. 70° W.	
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p style="text-align: center;">Subdivision, T. 41 N., R. 10 W., Arizona</p> <hr/> <p style="text-align: center;">T41N R10W S 2 S 1 S11 S12 1962</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located on the edge of old track road bearing NW. and SE.</p> <p>Land, gently rolling. Soil, gravelly. No timber; undergrowth, moderate brush.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>S. 89°58' W., bet. secs. 1 and 12.</p> <p>Over rolling land on the N. side of Rock Canyon wash.</p>
40.04	Point for the ¼ sec. cor. of secs. 1 and 12 falls on side of small wash draining S., in unsafe place.
40.14	Point selected for the witness ¼ sec. cor. of secs. 1 and 12.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	<p>T41N R10W ¼ S 1 W S 12 C 1962</p>
80.08	The cor. of secs. 1, 2, 11 and 12.
	Land, gently rolling. Soil, gravelly. No timber; undergrowth, moderate black brush and creosote. <hr/>
	N. 0°06' E., bet. secs. 1 and 2.
	Over low rolling hills cut by small washes.
31.00	Wash, 15 lks. wide, 1 ft. deep, drains W. from N. 60° E.
40.00	Point for the ¼ sec. cor. of secs. 1 and 2.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	<p>T41N R10W ¼ S 2 S 1 1962</p>
52.30	Wash, 20 lks. wide, 1 ft. deep, drains W.

CHAINS		
57.10	Graded road leading to Hurricane, Utah, bears NE. and SW.	
74.20	Wash, 20 lks. wide, 1 ft. deep, drains W. curving to SW.	
79.80	Wash, 30 lks. wide, 2 ft. deep, drains S. 20° W.	
80.00	The true point for the cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the township.	
	Land, gently rolling hills. Soil, gravelly. No timber; undergrowth, blackbrush and creosote.	
	From the true point for the standard corner of secs. 34 and 35, on the S. bdy. of the township, the witness cor. bears East 1.00 chain dist., monumented by an iron post as described in the official record.	
	N. 0°01' W., bet. secs. 34 and 35.	
	Along the top of the Hurricane Cliffs.	
40.00	Point for the ¼ sec. cor. of secs. 34 and 35.	
	Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.	
	T41N R10W ¼ S34 S35 1962	
49.10	Rim of Hurricane Cliffs, bears N. 10° E. and S. 15° W. circling to S. By triangulation; desc. over nearly vertical ledges facing N. 70° W.	
80.00	Point for the cor. of secs. 26, 27, 34 and 35 falls on inaccessible slope.	
	Land, rolling and broken. Soil, rocky and exposed sandstone. No timber; undergrowth, moderate brush on top of Hurricane Cliffs.	
	From the cor. of secs. 25, 26, 35 and 36.	
	N. 89°58' W., bet. secs. 26 and 35.	
	Over rolling land, by triangulation and traverse.	
6.00	Wash, 10 lks. wide, 1 ft. deep, drains NE. circling to E.; asc. over SE. slope.	
16.10	Top of ascent; thence over gently rolling land.	
40.02	Point for the ¼ sec. cor. of secs. 26 and 35.	
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.	
	T41N R10W ¼ S 26 S 35 1962	
	Raise a mound of stone N. of the cor.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS													
	Subdivision, T. 41 N., R. 10 W., Arizona												
70.44	<p>Point selected for the witness cor. of secs. 26, 27, 34 and 35.</p> <p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td colspan="2">T41N R10W</td></tr> <tr><td>W</td><td>S27</td><td>S26</td></tr> <tr><td>C</td><td>S34</td><td>S35</td></tr> <tr><td></td><td colspan="2">1962</td></tr> </table> </div> <p>The cor. is located on rim of Hurricane Cliffs facing W.; unable to occupy the true point.</p> <p>Desc. over nearly vertical ledges and steep slope facing W.</p>		T41N R10W		W	S27	S26	C	S34	S35		1962	
	T41N R10W												
W	S27	S26											
C	S34	S35											
	1962												
80.04	<p>True point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling and broken. Soil, rocky and gravelly. No timber; undergrowth, moderate brush on top of Hurricane Cliffs.</p> <hr/> <p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>By triangulation, desc. over steep face of Hurricane Cliffs.</p>												
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.</p> <p>Set the iron post 2 ins. in the ground, mound with stones to top, cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td colspan="2">T41N R10W</td></tr> <tr><td></td><td>$\frac{1}{4}$</td><td></td></tr> <tr><td></td><td>S27</td><td>S26</td></tr> <tr><td></td><td colspan="2">1962</td></tr> </table> </div> <p>End of triangulation; desc. along W. slope.</p>		T41N R10W			$\frac{1}{4}$			S27	S26		1962	
	T41N R10W												
	$\frac{1}{4}$												
	S27	S26											
	1962												
43.40	<p>Wash, 20 lks. wide, 4 ft. deep, drains W.; thence along base of Hurricane Cliffs.</p>												
73.80	<p>Wash, 15 lks. wide, 2 ft. deep, drains NW.</p>												
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td colspan="2">T41N R10W</td></tr> <tr><td></td><td>S22</td><td>S23</td></tr> <tr><td></td><td>S27</td><td>S26</td></tr> <tr><td></td><td colspan="2">1962</td></tr> </table> </div> <p>Land, broken and rolling. Soil, rocky. Timber, none; undergrowth, light brush and cactus.</p> <hr/>		T41N R10W			S22	S23		S27	S26		1962	
	T41N R10W												
	S22	S23											
	S27	S26											
	1962												

CHAINS		
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°59' W., bet. secs. 23 and 26.</p> <p>Asc. over gently rolling E. slope.</p>	
21.20	Rolling spur top, slopes NE.; desc. NW. slope.	
33.40	Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.; asc. gentle E. slope.	
36.91	<p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 23 and 26.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p>	
	<p>T41N R10W</p> <p>$\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$ WC</p> <p>1962</p>	
37.00	Rim of Hurricane Cliffs; bears NE. and SW.; by triangulation, desc. over steep ledges and slope facing NW.	
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26 falls on inaccessible face of Hurricane Cliffs.	
80.02	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, E. 37.00 chs. gently rolling, broken on remainder. Soil, rocky and gravelly. No timber; undergrowth, moderate brush on top of Hurricane Cliffs.</p>	
	<hr/> <p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over gentle NW. slope through moderate undergrowth.</p>	
7.60	Wash, 10 lks. wide, 2 ft. deep, drains N. 60° W.	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.</p> <p>Set the iron post 28 ins. in the ground, cap mkd.</p>	
	<p>T41N R10W</p> <p>$\frac{1}{4}$</p> <p>S22 S23</p> <p>1962</p>	
	<p>Raise a mound of stone W. of the cor.</p> <p>from the cor.</p>	
	<p>A wire corral bears N. 35°24' W., 12.96 chs. dist. (eastern most cor.)</p>	
41.55	Fence, barbed wire, bears N. 39°50' W. and S. 39°50' E.	
64.80	Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.	
66.00	Graded road to Hurricane, Utah, bears N. 42° E. and S. 42° W.	
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set the iron post 28 ins. in the ground, cap mkd.</p>	
	<p>T41N R10W</p> <p>$\frac{S15\ S14}{S22\ S23}$</p> <p>1962</p>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 41 N., R. 10 W., Arizona
	<hr/> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, gravelly. No timber; undergrowth, moderate creosote, sage and cactus.</p> <hr/>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°59' W., bet. secs. 14 and 23.</p> <p>Desc. over NW. slope.</p>
7.20	Desc. over alluvial fan created by Cottonwood Wash.
23.20	Cottonwood wash, 80 lks. wide, 2 ft. deep, drains NW.
32.00	Leave fan area, desc. over gently rolling W. slope.
40.02	Point for the ¼ sec. cor. of secs. 14 and 23.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	<p>T41N R10W</p> <p>¼ $\frac{S\ 14}{S\ 23}$</p> <p>1962</p>
68.00	Wash, 15 lks. wide, 1 ft. deep, drains N. 60° W.
69.40	Old road, bears N. 20° E. and S. 20° W.
70.40	Bladed road leading to Hurricane, Utah, bears N. 15° E. and S. 15° W.
74.40	Wash, 10 lks. wide, 1 ft. deep, drains N.
80.04	The cor. of secs. 14, 15, 22 and 23.
	<p>Land, gently rolling. Soil, gravelly. No timber; undergrowth, moderate brush.</p> <hr/>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land.</p>
35.20	Wash, 20 lks. wide, 1 ft. deep, drains N. 60° W.
40.00	Point for the ¼ sec. cor. of secs. 14 and 15.
	Set the iron post 28 ins. in the ground, cap mkd.
	<p>T41N R10W</p> <p>¼ $\frac{S15}{S14}$</p> <p>1962</p>
	<p>Raise a mound of stone W. of the cor.</p>
40.30	Wash, 10 lks. wide, 1 ft. deep, drains N. 80° W.

CHAINS		
57.50	Wash, 20 lks. wide, 1 ft. deep, drains N. 30° E.	
74.70	Dim blade road, bears N. 16° E. and S. 20° W.	
80.00	Point for the cor. of secs. 10, 11, 14 and 15.	
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.	
	T41N R10W <u>S10 S11</u> <u>S15 S14</u> 1962	
	Land, gently rolling hills. Soil, gravelly. No timber; undergrowth, moderate black brush and creosote.	
<hr/>		
	From the cor. of secs. 11, 12, 13 and 14.	
	S. 89°59' W., bet. secs. 11 and 14.	
	Over gently rolling land.	
1.70	Wash, 15 lks. wide, 1 ft. deep, drains NW.	
5.80	Wash, 20 lks. wide, 1 ft. deep, drains N. 20° W.	
10.10	Wash, 15 lks. wide, 1 ft. deep, drains N.	
15.40	Deep gully, drains N. 15° W.	
18.10	Small gully, drains N. 20° E.	
29.10	Graded road leading to Hurricane, Utah, bears N. 23° E. and S. 23° W.	
39.50	Wash, 15 lks. wide, 1 ft. deep, drains NW.	
40.01	Point for the ¼ sec. cor. of secs. 11 and 14.	
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.	
	T41N R10W ¼ <u>S 11</u> <u>S 14</u> 1962	
41.10	Small wash, drains NW.	
44.50	Dim road, bears N. and S.	
50.00	Small wash, drains NW.	
62.10	Cottonwood Wash, 60 lks. wide, 1 ft. deep, drains N. 10° W.	
78.30	Dim blade road, bears N. and S. 15° W.	
80.02	The cor. of secs. 10, 11, 14 and 15.	
-	Land, gently rolling. Soil, gravelly. No timber; undergrowth, moderate black brush and creosote.	
<hr/>		

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 41 N., R. 10 W., Arizona
	N. 0°01' W., bet. secs. 10 and 11.
	Over low rolling hills.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T41N R10W $\frac{1}{4}$ S10 S11 1962</p>
42.70	Wash, 30 lks. wide, 1 ft. deep, drains NE. from S. 80° W.
64.50	Wash, 10 lks. wide, 1 ft. deep, drains NW.
77.30	Wash, 10 lks. wide, 1 ft. deep, drains N. 75° W.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T41N R10W S 3 S 2 S10 S11 1962</p>
	Land, gently rolling hills.
	Soil, gravelly.
	No timber; undergrowth, sparse blackbrush and brigham tea.
	From the cor. of secs. 1, 2, 11 and 12.
	S. 89°59' W., bet. secs. 2 and 11.
	Over low rolling land cut by numerous gullies and washes.
10.50	Dim track road, bears N. 70° W. and S. 70° E.
13.30	Fort Pearce Wash, 200 lks. wide, 1 ft. deep, drains NW. from S. 70° E.
34.60	Old road leading to Hurricane, Utah, bears N. 6° W. and S. 6° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T41N R10W $\frac{1}{4}$ $\frac{S 2}{S 11}$ 1962</p>
41.25	Graded road leading to Hurricane, Utah, bears N. 18° W. and S. 15° E.

CHAINS	
46.30	Cottonwood Wash, 110 lks. wide, 2 ft. deep, drains N.
65.40	Wash, 10 lks. wide, 1 ft. deep, drains SW.
80.00	The cor. of secs. 2, 3, 10 and 11.
	Land, low rolling hills. Soil, gravelly. No timber; undergrowth, sparse black brush and creosote brush.
	<hr/> N. 0°06' E., bet. secs. 2 and 3.
	Asc. over SW. slope.
15.60	Asc. along steep W. slope of high hill.
19.90	Desc. over NW. slope.
35.20	Enter gently rolling land.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W $\frac{1}{4}$ S 3 S 2 1962
51.50	Asc. steep S. slope.
54.50	Ridge, bears NW. and E.; desc. over steep NE. slope.
79.40	Fort Pearce Wash, 100 lks. wide, 3 ft. deep, drains N. 30° W. from irregularly SE.
79.94	The true point for the cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the township.
	Land, rolling and broken. Soil, gravel and exposed sandstone. No timber; undergrowth, creosote and black brush.
	<hr/> From the standard cor. of secs. 33 and 34 on the S. bdy. of the township, monumented by an iron post as described in the official record.
	N. 0°02' W., bet. secs. 33 and 34.
	Desc. over general NE. slope covered with volcanic rock.
15.50	Ravine, drains S. 80° E.; asc. over rolling E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W $\frac{1}{4}$ S33 S34 1962
	from which A well, 6 ft. diam., 26 ft. deep, 14 ft. of water, bears S. 69°55' E., 39.06 chs. dist.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 41 N., R. 10 W., Arizona
	Raise a mound of stone W. of the cor.
55.30	Desc. over gently rolling E. slope.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	Set the iron post 22 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W S28 S27 S33 S34 1962
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, volcanic rock and gravel. No timber; undergrowth, black brush and cactus.
	From the true point for the cor. of secs. 26, 27, 34 and 35.
	S. 89°59' W., bet. secs. 27 and 34.
	By triangulation, topography as taken from U.S.G.S. topographic sheet; desc. over broken ledges and steep slope facing W. (Hurricane Cliffs).
35.00	Bottom of Rock Canyon, drains N.; asc. steep rocky E. slope.
39.97	Point for the ¼ sec. cor. of secs. 27 and 34.
	Set the iron post among large lava rocks and in a mound of stone to top, cap mkd.
	T41N R10W ¼ S 27 S 34 1962
	End of triangulation.
42.50	Spur, slopes N.; thence, over low rolling land.
55.60	Graded road leading to Hurricane, Utah, bears N. 10° E. and S. 10° W.; asc. over E. slope.
79.94	The cor. of secs. 27, 28, 33 and 34.
	Land, steep and broken on E. ½ mile, rolling on remainder. Soil, rocky and gravel. No timber; undergrowth, black brush and cactus.
	N. 0°02' W., bet. secs. 27 and 28.
	Desc. over rolling E. slope.

CHAINS

- 9.00 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E. circling to E.; thence over rolling land, E. drainage and exposure.
- 40.00 Point for the ¼ sec. cor. of secs. 27 and 28.
Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W
¼
S28|S27
1962
- 48.00 Wash, 30 lks. wide, 6 ins. deep, drains N. 70° E.
- 72.10 Rim of small escarpment, bears N. 30° E. and S. 30° W.; desc. over NW. slope.
- 79.00 Enter gently rolling land.
- 80.00 Point for the cor. of secs. 21, 22, 27 and 28.
Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W
S21|S22
S28|S27
1962

Land, rolling hills.
Soil, gravelly.
No timber; undergrowth, black brush and cactus.

- From the cor. of secs. 22, 23, 26 and 27.
N. 89°57' W., bet. secs. 22 and 27.
Desc. over NW. slope.
- 6.50 Wash, 30 lks. wide, 1 ft. deep, drains NW.
- 37.70 Graded road leading to Hurricane, Utah, bears N. 5° W. and S. 5° E.
- 39.99 Point for the ¼ sec. cor. of secs. 22 and 27.
Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W
¼ S 22
S 27
1962
- 53.60 Wash, 100 lks. wide, 5 ft. deep, drains N. 15° W.; asc. E. slope.
- 72.70 Escarpment rim, bears N. 30° E. and S. 30° W.; desc. NW. slope.
- 79.00 Enter nearly level land.
- 79.98 The cor. of secs. 21, 22, 27 and 28.

Land, rolling.
Soil, gravelly.
No timber; undergrowth, black brush and cactus.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 41 N., R. 10 W., Arizona
	N. 0°02' W., bet. secs. 21 and 22.
	Over gently rolling land.
15.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 35° E.
35.80	Wash, 30 lks. wide, 1 ft. deep, drains N. 20° E.
40.00	Point for the ¼ sec. cor. of secs. 21 and 22.
	Set the iron post 24 ins. in the ground and in a collar of stone, cap mkd.
	T41N R10W ¼ S21 S22 1962
	Raise a mound of stone W. of the cor.
55.70	Dim blade road, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W S16 S15 S21 S22 1962
	Land, gently rolling. Soil, rocky sandy clay loam. No timber; undergrowth, black brush and brigham tea.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89°58' W., bet. secs. 15 and 22.
	Over gently rolling land.
18.10	Main Run Wash, 100 lks. wide, 2 ft. deep, drains N. 10° W. from S. 10° W.
37.70	Barbed wire fence, bears N. 80° W. and S. 80° E.
39.96	Point for the ¼ sec. cor. of secs. 15 and 22.
	Set the iron post 24 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W ¼ S 15 S 22 1962
	from which
	An improved water seep and pond 25 ft. in diam., 6 ins. of water, bears S. 8° 10' E., 8.20 chs. distant.

CHAINS		
	Raise a mound of stone N. of the cor.	
40.70	Old blade road, bears NE. and SW.	
43.50	Wash, 30 lks. wide, 1 ft. deep, drains N.	
47.90	Wash, 40 lks. wide, 1 ft. deep, drains N.	
49.20	Wash, 40 lks. wide, 1 ft. deep, drains N. 75° E. for 1.00 chain, thence N.	
54.90	Wash, 30 lks. wide, 1 ft. deep, drains irregularly N.	
79.92	The cor. of secs. 15, 16, 21 and 22.	
	Land, gently rolling. Soil, gravelly. No timber; undergrowth, moderate brush and creosote.	
	<hr/>	
	N. 0°02' W., bet. secs. 15 and 16.	
	Over gently rolling land.	
2.60	Wash, 50 lks. wide, 1 ft. deep, drains N. 30° E.	
6.50	Barbed wire fence, bears N. 81°30' W., and S. 81°30' E.	
24.30	Wash, 20 lks. wide, 1 ft. deep, drains N. 25° E.	
36.30	Wash, 60 lks. wide, 1 ft. deep, drains N. 10° W. from SE.	
40.00	Point for the ¼ sec. cor. of secs. 15 and 16.	
	Set the iron post 20 ins. in the ground, and in a collar of stone, cap mkd.	
		T41N R10W ¼ S16 S15 1962
43.50	Wash, 60 lks. wide, 1 ft. deep, drains N. 30° E.	
65.40	Wash, 25 lks. wide, 1 ft. deep, drains NE.	
80.00	Point for the cor. of secs. 9, 10, 15 and 16.	
	Set the iron post 9 ins. in the ground, mound with stones to top, cap mkd.	
		T41N R10W S 9 S10 S16 S15 1962
	Land, gently rolling. Soil, rocky clay loam. No timber; undergrowth, sparse black brush and brigham tea.	
	<hr/>	
	From the cor. of secs. 10, 11, 14 and 15.	
	N. 89°57' W., bet. secs. 10 and 15.	
	Over gently rolling hills.	
39.94	Point for the ¼ sec. cor. of secs. 10 and 15.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	<p>Subdivision, T. 41 N., R. 10 W., Arizona</p> <hr/> <p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W $\frac{1}{4} \begin{array}{l} S 10 \\ S 15 \end{array}$ 1962</p>
50.10	Main Run Wash, 50 lks. wide, 2 ft. deep, drains N. from SE.
52.70	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° E.
68.70	Wash, 40 lks. wide, 2 ft. deep, drains N. 15° E.
79.88	The cor. of secs. 9, 10, 15 and 16.
	<p>Land, gently rolling hills. Soil, rocky clay loam. No timber; undergrowth, scattered brush and brigham tea.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling hills.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.</p> <p>Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W $\frac{1}{4} \begin{array}{l} S 9 \\ S 10 \end{array}$ 1962</p>
51.40	Main Run Wash, 200 lks. wide, 2 ft. deep, drains N. 75° W. for approximately 4.00 chs., thence N.
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T41N R10W $\begin{array}{l} S 4 S 3 \\ S 9 S 10 \end{array}$ 1962</p> <p>No accessories available.</p> <p>Land, gently rolling hills. Soil, gravelly. No timber; undergrowth, scattered brush and brigham tea.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°56' W., bet. secs. 3 and 10.</p> <p>Over rolling land through scattered undergrowth.</p>
5.50	Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W.
9.10	Wash, 8 lks. wide, 1 ft. deep, drains NW.

CHAINS	
29.00	Wash, 20 lks. wide, 1 ft. deep, drains N. 30° E.
38.70	Wash, 10 lks. wide, 4 ins. deep, drains N. 15° E.
39.93	Point for the ¼ sec. cor. of secs. 3 and 10.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T41N R10W $\frac{1}{4}$ $\frac{S \ 3}{S \ 10}$ 1962</p>
59.10	Wash, 30 lks. wide, 4 ins. deep, drains N. 30° W.
63.60	Wash, 100 lks. wide, 4 ins. deep, drains N. 15° E.
79.86	The cor. of secs. 3, 4, 9 and 10.
	<p>Land, rolling and slightly broken. Soil, gravelly. Timber, none; undergrowth, scattered brush and brigham tea.</p>
	<p>N. 0°03' W., bet. secs. 3 and 4. Over gently rolling land through sparse undergrowth.</p>
40.00	Point for the ¼ sec. cor. of secs. 3 and 4.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T41N R10W $\frac{1}{4}$ S 4 S 3 1962</p>
49.20	Asc. over SE. slope.
55.10	S. rim of bluff, bears NE. and SW.; desc. over general N. slope.
79.80	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the township.
	<p>Land, S. ½ mile gently rolling, slightly broken on remainder. Soil, gravelly and rocky. No timber; undergrowth, sparse brush and brigham tea.</p>
	<p>From the standard cor. of secs. 32 and 33 on the S. bdy. of the township, monumented by an iron post as described in the official record.</p>
	N. 0°03' W., bet. secs. 32 and 33.
	By triangulation, asc. over SW. slope.
10.00	Asc. steep SW. slope.
40.00	Point for the ¼ sec. cor. of secs. 32 and 33.
	Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T41N R10W $\frac{1}{4}$ S32 S33 1962</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS					
	Subdivision, T. 41 N., R. 10 W., Arizona				
	<p>from which</p> <p style="padding-left: 40px;">Triangulation Station BUTTE bears N. 10°48' E., 15.35 chs. dist.</p> <p>The cor. is located on a spur sloping sharply West for about 2.00 chs. then SW.</p>				
66.50	Mesa rim, bears N. 15° W. and S. 15° E.; thence over mesa top.				
77.30	Point selected for the witness cor. of secs. 28, 29, 32 and 33.				
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.				
	T41N R10W WC <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S29</td> <td style="padding: 0 5px;">S28</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S32</td> <td style="padding: 0 5px;">S33</td> </tr> </table> 1962	S29	S28	S32	S33
S29	S28				
S32	S33				
77.40	NW. rim of mesa, bears NE. and SW.; desc. steep. NW. slope.				
80.00	Point for the cor. of secs. 28, 29, 32 and 33 falls on precipitous slope in unsafe position.				
	Land, steep and broken. Soil, rocky. No timber; undergrowth, sparse black brush.				
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°57' W., bet. secs. 28 and 33.</p> <p>Over gently rolling N. slope.</p>				
8.90	Wash, 15 lks. wide, 6 ins. deep, drains N. 35° E.; asc. over E. slope.				
39.96	Point for the ¼ sec. cor. of secs. 28 and 33.				
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.				
	T41N R10W <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> </tr> <tr> <td></td> <td style="border-right: 1px solid black; padding: 0 5px;">S 33</td> </tr> </table> 1962	¼	S 28		S 33
¼	S 28				
	S 33				
42.00	Asc. along rocky, rolling N. slope.				
77.00	Narrow rocky spur, slopes sharply N.; desc. along NW. slope.				
79.92	The true point for the cor. of secs. 28, 29, 32 and 33.				
	Land, moderate steep slopes covered with volcanic rock. Soil, rocky. No timber; undergrowth, moderate black brush.				

CHAINS

N. 0°03' W., bet. secs. 28 and 29.

By triangulation; desc. over steep rocky N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W

$\frac{1}{4}$
S29 | S28
1962

End of triangulation.

54.30 Wash, 6 lks. wide, 1 ft. deep, drains NE. from S. 20° W.; continue descent.

80.00 Point for the cor. of secs. 20, 21, 28 and 29.

Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W

S20 | S21
S29 | S28
1962

Raise a mound of stone W. of the cor.

Land, moderate N. slope.

Soil, rocky.

No timber; undergrowth, moderate black brush.

From the cor. of secs. 21, 22, 27 and 28.

S. 89°55' W., bet. secs. 21 and 28.

Over gently rolling land.

21.00 Wash, 10 lks. wide, 6 ins. deep, drains N. 10° E.

32.20 Wash, 15 lks. wide, 1 ft. deep, drains N. 15° E.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.

Set the iron post 24 ins. in the ground and in a collar of stone, cap mkd.

T41N R10W

$\frac{1}{4}$ S 21
S 28
1962

Raise a mound of stone N. of the cor.

40.30 Wash, 10 lks. wide, 6 ins. deep, drains N. 15° E.

80.04 The cor. of secs. 20, 21, 28 and 29.

Land, gently rolling.

Soil, rocky clay loam.

No timber; undergrowth, scattered to moderate black brush.

N. 0°03' W., bet. secs. 20 and 21.

Over gently rolling land cut by washes and gullies.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 41 N. R. 10 W., Arizona
5.50	Wash, 25 lks. wide, 1 ft. deep, drains N. 20° E.
25.80	Wash, 10 lks. wide, 6 ins. deep, drains NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21. Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W $\frac{1}{4}$ S20 S21 1962
55.90	Begin triangulation over steep ledgy SE. slope.
80.00	Point for the cor. of secs. 16, 17, 20 and 21 falls on inaccessible slope on E. side of rocky point projecting south. Land, S. 60 chs. gently rolling, remainder steep SE. slope. Soil, rocky clay loam. No timber; undergrowth, scattered black brush.
	From the cor. of secs. 15, 16, 21 and 22. S. 89°50' W., bet. secs. 16 and 21. Over low, slightly broken hills.
3.20	Wash, 50 lks. wide, 1 ft. deep, drains NE.
36.00	Wash, 20 lks. wide, 6 ins. deep, drains N. circling to NE.
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21. Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W $\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$ 1962
	By triangulation; asc. over moderate E. slope.
74.00	Asc. over steep E. slope.
80.10	The true point for the cor. of secs. 16, 17, 20 and 21. Land, East $\frac{1}{2}$ mile low broken hills, West $\frac{1}{2}$ mile moderate to steep E. slope. Soil, rocky clay loam. No timber; undergrowth, moderate to scattered black brush.
	N. 0°03' W., bet. secs. 16 and 17. Over mountainous land; by triangulation, asc. along steep, ledgy E. slope.

CHAINS

9.20 SE. rim of mesa, bears NE. and SW.; thence, over mesa top.

9.30 Point selected for the witness cor. of secs. 16, 17, 20 and 21.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W
WC
S17|S16
S20|S21
1962

25.10 Desc. over steep, broken NE. slope.

40.00 Point for the 1/4 sec. cor. of secs. 16 and 17.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W
1/4
S17|S16
1962

51.70 Wash, 5 lks. wide, 1 ft. deep, drains NW. from S. 10° W.

55.00 Same wash, drains N. from SW.

57.20 Same wash, drains N. 30° E. circling to N. 10° E.

70.80 Rim of small bluff, bears NW. and SE.; desc. over NE. slope.

80.00 Point for the cor. of secs. 8, 9, 16 and 17.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W
S 8|S 9
S17|S16
1962

Land, mountainous.
Soil, rocky.
No timber; undergrowth, moderate to scattered black brush.

From the cor. of secs. 9, 10, 15 and 16.

S. 89°54' W., bet. secs. 9 and 16.

Over gently rolling hills.

28.60 Wash, 15 lks. wide, 1 ft. deep, drains NE.

40.06 Point for the 1/4 sec. cor. of secs. 9 and 16.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W
1/4 S 9
S 16
1962

45.90 Wash, 10 lks. wide, 6 ins. deep, drains NE.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 41 N. R. 10 W., Arizona
62.20	Wash, 20 lks. wide, 1 ft. deep, drains N. 15° E.
76.50	Wash, 20 lks. wide, 1 ft. deep, drains N. 5° E. for about 2.00 chs. thence NE.
80.12	The cor. of secs. 8, 9, 16 and 17. Land, gently rolling hills. Soil, rocky clay loam. No timber; undergrowth, sparse blackbrush and brigham tea.
	N. 0°03' W. bet. secs. 8 and 9. Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9. Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd. T41N R10W 1/4 S 8 S 9 1962
54.30	Wash, 10 lks. wide, 6 ins. deep, drains N. 20° E.
66.90	Wash, 40 lks. wide, 1 ft. deep, drains NE.
80.00	Point for the cor. of secs. 4, 5, 8 and 9. Set the iron post 12 ins. in the ground, mound with gravel to top, cap mkd. T41N R10W S 5 S 4 S 8 S 9 1962 Land, gently rolling hills. Soil, gravelly. No timber; undergrowth, sparse black brush and brigham tea.
	From the cor. of secs. 3, 4, 9 and 10. S. 89°55' W., bet. secs. 4 and 9. Over gently rolling land.
22.80	Main Run Wash, 50 lks. wide, 2 ft. deep, drains N. 5° W. circling to NW.
32.70	Wash, 10 lks. wide, 6 ins. deep, drains N. 10° E.
37.50	Wash, 10 lks. wide, 6 ins. deep, drains N. 10° E.
40.06	Point for the 1/4 sec. cor. of secs. 4 and 9. Set the iron post 20 ins. in the ground, mound with stones to top, cap mkd.

CHAINS

T41N R10W

 $\frac{1}{4} \frac{S 4}{S 9}$

1962

57.60 Wash, 40 lks. wide, 1 ft. deep, drains N. 50° E.

80.12 The cor. of secs. 4, 5, 8 and 9.

Land, gently rolling hills.

Soil, gravelly.

No timber; undergrowth, sparse black brush and brigham tea.

N. 0°04' E., bet. secs. 4 and 5.

Over gently rolling land.

15.00 Asc. over steep SE. slope.

34.30 Rim of bluff, bears N. 20° E. and S. 20° W.; desc. gentle N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.

Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W

 $\frac{1}{4} S 5 | S 4$

1962

50.40 Wash, 10 lks. wide, 6 ins. deep, drains N. 20° E.

55.00 Rim of bluff, bears N. 15° E. and SW.; desc. over NW. slope.

79.89 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the township.

Land, mountainous.

Soil, rocky.

No timber; undergrowth, moderate black brush.

From the standard cor. of secs. 31 and 32 on the S. bdy. of the township, monumented by an iron post as described in the official record.

N. 0°03' W., bet. secs. 31 and 32.

Asc. over gentle S. slope.

32.00 Desc. over gentle N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W

 $\frac{1}{4} S 31 | S 32$

1962

Asc. over S. slope.

50.40 Spur, slopes W.; desc. over N. slope.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 41 N. R. 10 W., Arizona
72.40	N. Rim of mesa, bears NW. and SE.; desc. over steep NE. slope.
80.00	Point for the cor. of secs. 29, 30, 31 and 32. Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd. <div style="text-align: center;"> T41N R10W <u>S30 S29</u> <u>S31 S32</u> 1962 </div> The cor. is located on a red colored spur sloping N. 30° E. Land, gently rolling on S. 72.00 chs., steep slope on remainder. Soil, rocky clay loam. No timber; undergrowth, black brush, cactus and brigham tea.
40.00	From the true point for the cor. of secs. 28, 29, 32 and 33. West, bet. secs. 29 and 32. Over broken mountainous land by triangulation; general N. drainage and exposure. Point for the ¼ sec. cor. of secs. 29 and 32. Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd. <div style="text-align: center;"> T41N R10W ¼ <u>S 29</u> <u>S 32</u> 1962 </div> End of triangulation; asc. over E. slope.
44.80	N. end of knoll; thence, by triangulation over steep land sloping North.
80.00	The cor. of secs. 29, 30, 31 and 32. Land, mountainous. Soil, rocky. No timber; undergrowth, black brush.
	S. 89°58' W., bet. secs. 30 and 31. Asc. over steep NE. slope.
10.70	Mesa rim, bears NW. and S. 70° E.; thence, over top of East Mesa.
40.00	Point for the ¼ sec. cor. of secs. 30 and 31. Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

CHAINS		
	<p>T41N R10W $\frac{1}{4}$ $\frac{S\ 30}{S\ 31}$ 1962</p>	
62.40	Mesa rim, bears N. and SE.; desc. over steep W. slope.	
79.88	<p>The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>Land, mountainous. Soil, rocky. No timber; undergrowth, black brush, cactus and brigham tea.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. Desc. over steep N. slope.</p>	
14.40	Wash, 20 lks. wide, 1 ft. deep, drains N. from SW.	
17.30	Same wash, drains N. 15° E.	
26.50	Wash, 20 lks. wide, 6 ins. deep, drains NE. from W.; asc. over SE. slope.	
36.50	Desc. along E. slope.	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.</p> <p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p>	
	<p>T41N R10W $\frac{1}{4}$ $\frac{S30 S29}{S30 S29}$ 1962</p>	
59.00	<p>Desc. over NE. slope.</p> <p>Enter gently rolling land.</p>	
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.</p>	
	<p>T41N R10W $\frac{S19 S20}{S30 S29}$ 1962</p>	
	<p>Land, mountainous. Soil, rocky. No timber; undergrowth, moderate black brush.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29. S. 89°59' W., bet. secs. 20 and 29. Over gently rolling land.</p>	
8.00	Wash, 100 lks. wide, 3 ft. deep, drains N. 60° E.	
31.60	Wash, 10 lks. wide, 6 ins. deep, drains N. 10° E.	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 41 N., R. 10 W., Arizona
39.99	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.</p> <p>Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W $\frac{1}{4}$ $\frac{S\ 20}{S\ 29}$ 1962</p>
42.20	Wash, 10 lks. wide, 6 ins. deep, drains N. circling to NE.
60.40	Rim of small bluff, bears N. 15° W. and S. 15° W.; desc. over W. slope.
71.00	Enter series of small washes draining N. 15° E.
73.50	Leave washes, continue over nearly level land.
79.98	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, gently rolling. Soil, rocky clay loam. No timber; undergrowth, black brush, brigham tea and cactus.</p> <hr/> <p>S. 89°57' W., bet. secs. 19 and 30.</p> <p>Over gently rolling land.</p>
8.10	Wash, 10 lks. wide, 6 ins. deep, drains N.
19.80	Wash, 20 lks. wide, 1 ft. deep, drains N.
24.30	Wash, 10 lks. wide, 6 ins. deep, drains N. 30° E.
36.50	Small wash, drains N.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.</p> <p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W $\frac{1}{4}$ $\frac{S\ 19}{S\ 30}$ 1962</p> <p>Raise a mound of stone N. of the cor.</p>
43.20	Wash, 20 lks. wide, 2 ft. deep, drains N. 15° W.; asc. over NE. slope.
50.80	Wash, 20 lks. wide, 1 ft. deep, drains N.
79.83	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the township, monumented by an iron post as described in the official record.

CHAINS

Land, gently rolling on E. $\frac{1}{2}$ mile, moderate slope on remainder.
Soil, rocky clay loam.
No timber; undergrowth, black brush, cactus and brigham tea.

From the cor. of secs. 19, 20, 29 and 30.

N. $0^{\circ}03'$ W., bet. secs. 19 and 20.

Desc. over gently N. slope.

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.

Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W

$\frac{1}{4}$
S19 | S20
1962

Asc. over gentle S. slope.

55.30

Top of ascent; desc. over N. slope.

68.60

Wash, 20 lks. wide, 1 ft. deep, drains S. 60° W.; thence over low broken hills.

77.50

Point selected for the witness cor. of secs. 17, 18, 19 and 20.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W

WC
S18 | S17
S19 | S20
1962

80.00

Point for the cor. of secs. 17, 18, 19 and 20 falls on steep slope where cor. could not be perpetuated.

Land, low broken hills.
Soil, rocky clay loam.
No timber; undergrowth, black brush and brigham tea.

From the true point for the cor. of secs. 16, 17, 20 and 21.

N. $89^{\circ}58'$ W., bet. secs. 17 and 20.

Asc. over steep ledgy E. slope.

3.00

Narrow ledgy point, projects S.; by triangulation, descend over steep ledgy W. slope.

39.97

Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T41N R10W

$\frac{1}{4}$ S 17
S 20
1962

End of triangulation; thence, over low rolling hills.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	Subdivision, T. 41 N , R. 10 W., Arizona
42.20	Wash, 25 lks. wide, 6 ins. deep, drains SW.
43.60	Wash, 15 lks. wide, 6 ins. deep, drains S. 30° W.
73.80	Wash, 30 lks. wide, 1 ft. deep, drains N. 65° W.
79.94	True point for the cor. of secs. 17, 18, 19 and 20.
	<p>Land, steep and broken on E. 30 chs.; rolling on remainder. Soil, rocky clay loam. No timber; undergrowth, black brush and brigham tea.</p>
	S. 89°55' W., bet. secs. 18 and 19.
	Over low broken hills.
1.20	Wash, 10 lks. wide, 4 ins. deep, drains N.
16.50	Rim of low hill, bears NE. and SW.; desc. over NW. slope.
24.60	Wash, 30 lks. wide, 1 ft. deep, drains N. circling to NE.
27.80	Wash, 20 lks. wide, 6 ins. deep, drains NE.; asc. along S. slope.
40.00	Point for the ¼ sec. cor. of secs. 18 and 19.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T41N R10W ¼ $\frac{S\ 18}{S\ 19}$ 1962</p>
	Asc. over SE. slope.
51.90	Top of broken hill, slopes to NW. N., NE. and S.; desc. over SW. slope.
71.00	Enter gently rolling land.
79.68	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the township, monumented by an iron post as described in the official record.
	<p>Land, rolling and broken. Soil, rocky clay loam. No timber; undergrowth, sparse black brush and brigham tea.</p>
	From the true point for the cor. of secs. 17, 18, 19 and 20.
	N. 0°03' W., bet. secs. 17 and 18.
	Over rolling slightly broken land.

CHAINS	
3.60	Wash, 70 lks. wide, 3 ft. deep, drains irregularly NW. from S. 65° E,
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W $\frac{1}{4}$ S18 S17 1962
44.40	Wash, 25 lks. wide, 6 ins. deep, drains W.
52.60	Wash, 10 lks. wide, 6 ins. deep, drains S. 70° W.
57.30	Rim of low hill, bears E. and W.; desc. over steep N. slope.
65.00	Asc. over gentle SW. slope.
73.80	Desc. over NW. slope.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W S 7 S 8 S18 S17 1962
	Land, rolling and broken. Soil, rocky clay loam. No timber; undergrowth, moderate black brush.
	<hr/> From the cor. of secs. 8, 9, 16 and 17.
	West, bet. secs. 8 and 17.
	Over low rolling land along the N. base of small mesa.
12.50	Wash, 10 lks. wide, 6 ins. deep, drains NE. for about 3.00 chs., thence N.
21.10	Wash, 10 lks. wide, 6 ins. deep, drains irregularly N. 30° E.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W $\frac{1}{4}$ $\frac{S 8}{S17}$ 1962
	Raise a mound of stone N. of the cor.
43.20	Fence, barbed wire, bears N. 30° W. and S. 30° E.
48.40	Wash, 10 lks. wide, 6 ins. deep, drains NW.
53.40	Small spur, slopes NW.
55.50	Wash, 10 lks. wide, 6 ins. deep, drains NW.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 41 N., R. 10 W., Arizona
66.60	Wash, 20 lks. wide, 1 ft. deep, drains N. 60° W.
79.98	The cor. of secs. 7, 8, 17 and 18. Land, rolling and slightly broken. Soil, rocky clay loam. No timber; undergrowth, moderate black brush.
	S. 89°53' W., bet. secs. 7 and 18. Over gently rolling land.
26.80	Wash, 10 lks. wide, 6 ins. deep, drains N.
38.10	Wash, 90 lks. wide, 2 ft. deep, drains N. 20° W.
40.00	Point for the ¼ sec. cor. of secs. 7 and 18. Set the iron post 20 ins. in the ground, mound with stones to top, cap mkd.
	T41N R10W ¼ $\frac{S \ 7}{S \ 18}$ 1962
	Raise a mound of stone N. of the cor.
41.30	Low spur, slopes N. 30° E. about 2.00 chs. to end.
45.90	Wash, 30 lks. wide, 6 ins. deep, drains NE.
61.40	Wash, 20 lks. wide, 1 ft. deep, drains NE.
75.40	Enter wash 20 lks. wide, 1 ft. deep, drains irregularly NE. from S. 75° W.
76.70	Leave wash, asc. along S. slope.
79.60	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the township, monumented by an iron post as described in the official record. Land, gently rolling. Soil, rocky clay loam. No timber; undergrowth, moderate black brush.
	From the cor. of secs. 7, 8, 17 and 18. N. 0°03' W., bet. secs. 7 and 8. Over rolling land.
4.40	Wash, 20 lks. wide, 1 ft. deep, drains N. 60° W.
13.00	Wash, 10 lks. wide, 6 ins. deep, drains N. 60° W.
20.50	Wash, 20 lks. wide, 1 ft. deep, drains SW.; asc. over small spurs and gullies putting W.

CHAINS	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8 falls in unsafe place.
40.10	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	<p>T41N R10W $\frac{1}{4}$ S 7 S 8 WC 1962</p>
	By triangulation, ascend over steep broken slope facing W.
80.00	Point for the cor. of secs. 5, 6, 7 and 8 falls at inaccessible place on steep broken W. slope.
	Land, S. $\frac{1}{2}$ mile, rolling; N. $\frac{1}{2}$ mile steep and broken. Soil, rocky clay loam. No timber; undergrowth, scattered to moderate black brush.
	<hr/> From the cor. of secs. 4, 5, 8 and 9.
	N. $89^{\circ}58'$ W., bet. secs. 5 and 8.
	Over rolling land.
11.50	Asc. over SE. slope.
24.00	Asc. over steep E. slope.
34.60	Mesa rim, bears N. 15° E. and S.; thence over mesa top.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.
	Set the iron post 2 ins. in the ground, mound with stones to top, cap mkd.
	<p>T41N R10W $\frac{1}{4}$ $\frac{S 5}{S 8}$ 1962</p>
50.90	Wash, 10 lks. wide, 1 ft. deep, drains N. from S. 15° W.
77.40	Rim of mesa, bears N. 20° W., and S. 20° E.; desc. over ledges and steep broken slope facing W.
80.02	True point for the cor. of secs. 5, 6, 7 and 8.
	Land, rolling and broken. Soil, rocky. No timber; undergrowth, moderate black brush and brigham tea.
	<hr/> S. $89^{\circ}52'$ W., bet. secs. 6 and 7.
	By triangulation, desc. over steep, broken W. slope.
16.00	Base of steep slope; desc. over gentle W. slope.
38.20	End of triangulation.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTE PAPER

CHAINS	
	Subdivision, T. 41 N. R. 10 W., Arizona
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <p>Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W $\frac{1}{4} \frac{S 6}{S 7}$ 1962</p>
46.70	Wash, 10 lks. wide, 6 ins. deep, drains irregularly NW.
50.80	Wash, 100 lks. wide, 2 ft. deep, drains N. from SE.
53.10	Wash, 10 lks. wide, 1 ft. deep, drains NE.; thence, over nearly level land.
79.50	<p>The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the township, monumented by an iron post as described in the official record.</p> <p>Land, steep and broken on E. 16.00 chs.; gently rolling on remainder. Soil, gravelly and rocky. No timber; undergrowth, black brush and brigham tea.</p> <hr/> <p>From the true point for the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°06' E., bet. secs. 5 and 6.</p> <p>Asc. over steep, broken W. slope.</p>
4.60	Mesa rim, bears N. 20° W. and S. 20° E.
4.70	<p>Point selected for the witness cor. of secs. 5, 6, 7 and 8.</p> <p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W $\frac{S 6 S 5}{S 7 S 8}$ WC 1962</p> <p>Desc. over rolling N. slope.</p>
31.80	Wash, 10 lks. wide, 6 ins. deep, drains N. 25° E.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.</p> <p>Set the iron post 4 ins. in the ground to bedrock, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R10W $\frac{1}{4} \frac{S 6 S 5}{S 7 S 8}$ 1962</p>

CHAINS

79.81

The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the township.

Land, steep and broken on S. 4.60 chs., rolling N. slope on remainder.

Soil, rocky.

No timber; undergrowth, moderate black brush and brigham tea.

General Description

The southeast corner of Township 41 North, Range 10 West is located on top of the Hurricane Cliffs; East Mesa cuts through the southwest corner with steep slopes and buttes along the southern part of the township. Isolated mesas are found in sections 2, 3, and 17, with a large mesa extending through the northwest corner of the township. The remaining area varies from nearly level land to low rolling hills cut by numerous washes and gullies. The elevation varies from 5415 feet above sea level in section 35 to 2950 feet in section 6.

Cottonwood Wash and Main Run Wash and their tributaries drain the east and central parts of the township northerly, emptying into Fort Pearce Wash, which cuts through the northeast corner of the township draining westerly. The remaining area is drained northerly by numerous washes and gullies forming into a large un-named wash which leaves the township in the northwest corner of section 6.

Black brush, brigham tea and cactus comprise most of the vegetation within the township, with a fair growth of native grass found along some of the north slopes. Small seeps in Fort Pearce Wash, a seep in section 22 and an improved well in section 34 were the only sources of water noted during this survey. Limited grazing of livestock is at present the primary interest with some mineral claims having been staked but not active at the present time.

CERTIFICATE OF SURVEY

We Boyd S. Owens
X Paul G. Bauer

, HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 22 day of June, 1962,

We have surveyed the north boundary and the subdivisional lines of Township 41 North, Range 10 West

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ^{us} ~~me~~ and under ^{our} ~~my~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 10, 1963
(Date)

Boyd S. Owens
(Cadastral Surveyor)
Boyd S. Owens

July 10, 1963
(Date)

Paul G. Bauer
(Cadastral Surveyor)
Surveying Technician
Paul G. Bauer

CERTIFICATE OF APPROVAL
Bureau of Land Management

The foregoing field notes of the survey of the north boundary and the subdivisional lines of Township 41 North, Range 10 West, of the Gila and Salt River Meridian, Arizona

executed by Boyd S. Owens and Paul G. Bauer, Cadastral Surveyor and Surveying Technician, having been critically examined and found correct, are hereby approved.
Washington, D.C.

DEC 20 1963
(Date)

E. L. Livingston
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)